

IPPM Working Group
Internet-Draft
Intended status: Best Current Practice
Expires: January 5, 2015

A. Akhter
B. Claise
Cisco Systems, Inc.
July 4, 2014

Passive Performance Metrics Sub-Registry
draft-ietf-ippm-registry-passive-01.txt

Abstract

This document specifies the Passive Performance Metrics sub-registry of the Performance Metric Registry. This sub-registry contains Passive Performance Metrics, especially those defined in RFCs prepared in the IP Performance Metrics (IPPM) Working Group of the IETF, and possibly applicable to other IETF metrics.

This document specifies a way to organize registry entries into columns that are well-defined, permitting consistent development of entries over time (a column may be marked NA if it is not applicable for that metric). The design is intended to foster development of registry entries based on existing reference RFCs, whilst each column serves as a check-list item to avoid omissions during the registration process. Every entry in the registry, before IANA action, requires Expert review as defined by concurrent IETF work in progress "Registry for Performance Metrics" ([draft-ietf-ippm-metric-registry](#)).

The document contains example entries for the Passive Performance Metrics sub-registry: a registry entry for a passive metric based on octetTotalCount as defined in [RFC5102](#) and a protocol specific passive metric based on RTP packets lost as defined in [RFC3550](#). The examples are for Informational purposes and do not create any entry in the IANA registry.

Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute

working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on January 5, 2015.

Copyright Notice

Copyright (c) 2014 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Open Issues	4
2.	Introduction	5
3.	Terminology	6
4.	Background and Motivation	6
5.	Scope	7
6.	Passive Registry Categories and Columns	7
6.1.	Common Registry Indexes and Information	8
6.1.1.	Identifier	8
6.1.2.	Name	8
6.1.3.	URI	8
6.1.4.	Status	8
6.1.5.	Requester	8
6.1.6.	Revision	8
6.1.7.	Revision Date	8
6.1.8.	Description	8
6.1.9.	Reference Specification(s)	8
6.2.	Metric Definition	9
6.2.1.	Reference Definition	9
6.2.2.	Fixed Parameters	9
6.3.	Method of Measurement	9
6.3.1.	Reference Implementation	9

6.3.2.	Traffic Filter Criteria	10
6.3.3.	Measurement Timing	10
6.3.4.	Output Type(s) and Data Format	10
6.3.5.	Metric Units	11
6.3.6.	Run-time Parameters and Data Format	11
6.4.	Comments and Remarks	11
7.	Example Generalized Passive Octet Count Entry	11
7.1.	Registry Indexes	12
7.1.1.	Element Identifier	12
7.1.2.	Metric Name	12
7.1.3.	URI	12
7.1.4.	Status	12
7.1.5.	Requester	12
7.1.6.	Revision	12
7.1.7.	Revision Date	12
7.1.8.	Metric Description	13
7.1.9.	Reference Specification(s)	13
7.2.	Metric Definition	13
7.2.1.	Reference Definition	13
7.2.2.	Fixed Parameters	13
7.3.	Method of Measurement	13
7.3.1.	Reference Implementation	13
7.3.2.	Traffic Filter Criteria	13
7.3.3.	Measurement Timing	13
7.3.4.	Output Type(s) and Data Format	14
7.3.5.	Metric Units	14
7.3.6.	Run-time Parameters and Data Format	14
7.4.	Comments and Remarks	14
8.	Example 5min Passive Egress Octet Count Entry on WAN Interface	14
8.1.	Registry Indexes	15
8.1.1.	Element Identifier	15
8.1.2.	Metric Name	15
8.1.3.	URI	15
8.1.4.	Status	15
8.1.5.	Requester	15
8.1.6.	Revision	15
8.1.7.	Revision Date	15
8.1.8.	Metric Description	16
8.1.9.	Reference Specification(s)	16
8.2.	Metric Definition	16
8.2.1.	Reference Definition	16
8.2.2.	Fixed Parameters	16
8.3.	Method of Measurement	16
8.3.1.	Reference Implementation	16
8.3.2.	Traffic Filter Criteria	16
8.3.3.	Measurement Timing	17
8.3.4.	Output Type(s) and Data Format	17

8.3.5.	Metric Units	17
8.3.6.	Run-time Parameters and Data Format	17
8.4.	Comments and Remarks	17
9.	Example Passive RTP Lost Packet Count	17
10.	Example BLANK Registry Entry	17
10.1.	Registry Indexes	18
10.1.1.	Element Identifier	18
10.1.2.	Metric Name	18
10.1.3.	URI	18
10.1.4.	Status	18
10.1.5.	Requester	18
10.1.6.	Revision	18
10.1.7.	Revision Date	18
10.1.8.	Metric Description	18
10.1.9.	Reference Specification(s)	18
10.2.	Metric Definition	18
10.2.1.	Reference Definition	19
10.2.2.	Fixed Parameters	19
10.3.	Method of Measurement	19
10.3.1.	Reference Implementation	19
10.3.2.	Traffic Filter Criteria	19
10.3.3.	Measurement Timing	19
10.3.4.	Output Type(s) and Data Format	19
10.3.5.	Metric Units	19
10.3.6.	Run-time Parameters and Data Format	20
10.4.	Comments and Remarks	20
11.	Security Considerations	20
12.	IANA Considerations	20
13.	Acknowledgements	21
14.	References	21
14.1.	Normative References	21
14.2.	Informative References	21
	Authors' Addresses	23

1. Open Issues

1. This draft must be aligned with [draft-ietf-ippm-registry-active](#): structure, content, examples, etc.
2. Do we need definitions for Active Metric and Passive Metric? To be decided with the authors of [ietf-ippm-metric-registry](#) and [ietf-ippm-registry-active](#)

Active (Performance) Metric: specific to Performance Metrics metered by an Active Measurement Method.

Passive (Performance) Metric: specific to Performance Metrics metered by an Passive Measurement Method.

3. See the EDITOR's NOTE within this draft.
4. Should the "Measurement Timing" be part of the registry?
5. What is difference between "Reference Specification(s)" and "Reference Definition"
6. [draft-ietf-ippm-metric-registry](#) contain requester and reviewer guidelines for performance metrics. Do we have guidelines specific to the extra passive performance metric fields in this document?

2. Introduction

The IETF has been specifying and continues to specify Performance Metrics. While IP Performance Metrics (IPPM) is the working group (WG) primarily focusing on Performance Metrics definition at the IETF, other working groups, have also specified Performance Metrics:

The "Metric Blocks for use with RTP's Extended Report Framework" [[XRBLOCK](#)] WG recently specified many Performance Metrics related to "RTP Control Protocol Extended Reports (RTP XR)" [[RFC3611](#)], which establishes a framework to allow new information to be conveyed in RTP, supplementing the original report blocks defined in "RTP: A Transport Protocol for Real-Time Applications", [[RFC3550](#)].

The Benchmarking Methodology" [[BMWG](#)] WG proposed some Performance Metrics as part of the benchmarking methodology.

The IP Flow Information eXport WG (IPFIX) [[IPFIX](#)] has existing and proposed Information Elements related to performance metrics.

The Performance Metrics for Other Layers (PMOL) [[PMOL](#)], a concluded working group, defined some Performance Metrics related to Session Initiation Protocol (SIP) voice quality [[RFC6035](#)], as well as guidelines for defining performance metrics [[RFC6390](#)]

It is expected that more and more Performance Metrics will be defined in the future, not only IP based metrics, but also protocol-specific ones and application-specific ones.

"Registry for Performance Metrics" [[I-D.ietf-ippm-metric-registry](#)] specifies a common registry for Performance Metrics. This document specifies the creation of a sub-registry specific to Performance Metrics metered by an Passive Measurement Method (passive metrics). Note that a sister document, "Active Performance Metric Sub-Registry"

[[I-D.ietf-ippm-registry-active](#)], specifies a sub-registry for the active metric (Performance Metrics metered by an Active Measurement).

The Passive Performance Measurements Sub-Registry contains passive performance metrics that meet the criteria set by the IETF and review of the Performance Metric Experts. It is expected that the majority of the metrics will have been defined elsewhere within the IETF working groups such as IPPM, BMWG, IPFIX, etc.

This sub-registry is part of the Performance Metric Registry [[I-D.ietf-ippm-metric-registry](#)] which specifies that all sub-registries must contain at least the following common fields: the identifier, the name, the URI, the status, the requester, the revision, the revision date, the description, and the reference specification(s). In addition to these common fields the passive metrics sub-registry has additional fields that provide the necessary background for interoperability and adoption.

3. Terminology

"Registry for Performance Metrics" [[I-D.ietf-ippm-metric-registry](#)] specifies the following terms: Performance Metric, Registered Performance Metric, Performance Metrics Registry (also known as Registry), Proprietary Registry, Performance Metrics Experts, Performance Metrics Directorate, Parameter, Active Measurement Method, Passive Measurement Method, and Hybrid Measurement Method.

Capitalized terms used in this document that are defined in the Terminology section of [[I-D.ietf-ippm-metric-registry](#)] are to be interpreted as defined there.

4. Background and Motivation

EDITOR's NOTE: from [draft-manyfolks-ippm-metric-registry-00](#).
Proposal: we can simply refers to [draft-ietf-ippm-registry-active-00 section 5](#), instead of duplicating text.

IPPM Passive Performance Metric registration is meant to allow wider adoption of common metrics in an inter-operable way. There are challenges with metric interoperability and adoption (to name a few) due to flexible input parameters, confusion between many similar metrics, and varying output formats.

One clear motivation for having such a registry is to allow a controller to request a measurement agent to perform a measurement using a specific metric (see [[I-D.ietf-lmap-framework](#)]). Such a request can be performed using any control protocol that refers to the value assigned to the specific metric in the registry.

Similarly, the measurement agent can report the results of the measurement and by referring to the metric value it can unequivocally identify the metric that the results correspond to.

There are several side benefits of having a registry with well-chosen entries. First, the registry could serve as an inventory of useful and used metrics that are normally supported by different implementations of measurement agents. Second, the results of the metrics would be comparable even if they are performed by different implementations and in different networks, as the metric and method is unambiguously defined.

5. Scope

[I-D.ietf-ippm-metric-registry] defines the overall structure for a Performance Metric Registry and provides guidance for defining a sub registry.

This document defines the Passive Performance Metrics Sub-registry; passive metrics are those where the measurements are based the observation of on network traffic, generated either from the end users or from network elements. Specifically, this traffic has not been generated for the purpose of measurement.

A row in the registry corresponds to one Registered Performance Metric, with entries in the various columns specifying the metric. [Section 6](#) defines the additional columns for a Registered Passive Performance Metric.

As discussed in [[I-D.ietf-ippm-metric-registry](#)], each entry (row) must be tightly defined; the definition must leave open only a few parameters that do not change the fundamental nature of the measurement (such as source and destination addresses), and so promotes comparable results across independent implementations. Also, each registered entry must be based on existing reference RFCs (or other standards) for performance metrics, and must be operationally useful and have significant industry interest. This is ensured by expert review for every entry before IANA action.

6. Passive Registry Categories and Columns

This section defines the categories and columns of the registry. Below, categories are described at the 6.x heading level, and columns are at the 6.x.y heading level. There are three categories, divided into common information (from [[I-D.ietf-ippm-metric-registry](#)]), metric definition and an open Comments section.

6.1. Common Registry Indexes and Information

This category has multiple indexes to each registry entry. It is defined in [[I-D.ietf-ippm-metric-registry](#)]:

6.1.1. Identifier

Defined in [[I-D.ietf-ippm-metric-registry](#)]. Definition text to be copied once source is stable.

6.1.2. Name

Defined in [[I-D.ietf-ippm-metric-registry](#)], same comment as above.

6.1.3. URI

Defined in [[I-D.ietf-ippm-metric-registry](#)], same comment as above.

6.1.4. Status

Defined in [[I-D.ietf-ippm-metric-registry](#)], same comment as above.

6.1.5. Requester

Defined in [[I-D.ietf-ippm-metric-registry](#)], same comment as above.

6.1.6. Revision

Defined in [[I-D.ietf-ippm-metric-registry](#)], same comment as above.

6.1.7. Revision Date

Defined in [[I-D.ietf-ippm-metric-registry](#)], same comment as above.

6.1.8. Description

Defined in [[I-D.ietf-ippm-metric-registry](#)], same comment as the above.

6.1.9. Reference Specification(s)

Defined in [[I-D.ietf-ippm-metric-registry](#)], same comment as the above.

6.2. Metric Definition

This category includes columns to prompt all necessary details related to the passive performance metric definition, including the RFC reference and values of input factors, called fixed parameters, which are left open in the origin definition but have a particular value defined by the performance metric.

6.2.1. Reference Definition

This entry provides references to relevant sections of the RFC(s) defining the metric, as well as any supplemental information needed to ensure an unambiguous definition for implementations.

6.2.2. Fixed Parameters

Fixed Parameters are input factors whose value must be specified in the Registry. The measurement system uses these values.

Where referenced metrics supply a list of Parameters as part of their descriptive template, a sub-set of the Parameters will be designated as Fixed Parameters. For example, for RTP packet loss calculation relies on the validation of a packet as RTP which is a multi-packet validation controlled by MIN_SEQUENTIAL as defined by [[RFC3550](#)]. Varying MIN_SEQUENTIAL values can alter the loss report and this value could be set as a fixed parameter.

A Parameter which is Fixed for one Registry entry may be designated as a Run-time Parameter for another Registry entry.

6.3. Method of Measurement

This category includes columns for references to relevant sections of the RFC(s) and any supplemental information needed to ensure an unambiguous method for implementations.

6.3.1. Reference Implementation

This entry provides references to relevant sections of the RFC(s) describing the method of measurement, as well as any supplemental information needed to ensure unambiguous interpretation for implementations referring to the RFC text.

Specifically, this section should include pointers to pseudocode or actual code that could be used for an unambiguous implementation.

6.3.2. Traffic Filter Criteria

The filter specifies the traffic constraints that the passive measurement method used is valid (or invalid) for. This includes valid packet sampling ranges, width of valid traffic matches (eg. all traffic on interface, UDP packets packets in a flow (eg. same RTP session)).

It is possible that the measurement method may not have a specific limitation. However, this specific registry entry with it's combination of fixed parameters implies restrictions. These restrictions would be listed in this field.

6.3.3. Measurement Timing

Measurement timing defines the behavior of the measurement method with respect to timing.

Is the measurement continuous?

If the measurement is sampled, what is the format of sampling? (eg random packet, random time, etc.)

How long is the measurement interval?

6.3.4. Output Type(s) and Data Format

For entries which involve a stream and many singleton measurements, a statistic may be specified in this column to summarize the results to a single value. If the complete set of measured singletons is output, this will be specified here.

Some metrics embed one specific statistic in the reference metric definition, while others allow several output types or statistics.

Each entry in the output type column contains the following information:

- o Value: The name of the output type
- o Data Format: provided to simplify the communication with collection systems and implementation of measurement devices.
- o Reference: the specification where the output type is defined

The output type defines the type of result that the metric produces. It can be the raw result(s) or it can be some form of statistic. The specification of the output type must define the format of the

output. In some systems, format specifications will simplify both measurement implementation and collection/storage tasks. Note that if two different statistics are required from a single measurement (for example, both "Xth percentile mean" and "Raw"), then a new output type must be defined ("Xth percentile mean AND Raw").

6.3.5. Metric Units

The measured results must be expressed using some standard dimension or units of measure. This column provides the units.

When a sample of singletons (see [[RFC2330](#)] for definitions of these terms) is collected, this entry will specify the units for each measured value.

6.3.6. Run-time Parameters and Data Format

Run-Time Parameters are input factors that must be determined, configured into the measurement system, and reported with the results for the context to be complete. However, the values of these parameters is not specified in the Registry, rather these parameters are listed as an aid to the measurement system implementor or user (they must be left as variables, and supplied on execution).

Where metrics supply a list of Parameters as part of their descriptive template, a sub-set of the Parameters will be designated as Run-Time Parameters.

The Data Format of each Run-time Parameter SHALL be specified in this column, to simplify the control and implementation of measurement devices.

Examples of Run-time Parameters include IP addresses, measurement point designations, start times and end times for measurement, and other information essential to the method of measurement.

6.4. Comments and Remarks

Besides providing additional details which do not appear in other categories, this open Category (single column) allows for unforeseen issues to be addressed by simply updating this Informational entry.

7. Example Generalized Passive Octet Count Entry

tbd

This section is Informational.

This section gives an example registry entry for a generalized the passive metric octetDeltaCount described in [[RFC5102](#)].

[7.1.](#) Registry Indexes

This category includes multiple indexes to the registry entries, the element ID and metric name.

[7.1.1.](#) Element Identifier

An integer having enough digits to uniquely identify each entry in the Registry.

TBD by IANA.

[7.1.2.](#) Metric Name

A metric naming convention is TBD.

One possibility based on the proposal in [[I-D.ietf-ippm-metric-registry](#)]:

Pas_IP-Octet-Delta-General

[7.1.3.](#) URI

urn:ietf:params:performance:metric-something

[7.1.4.](#) Status

Current

[7.1.5.](#) Requester

TBD

[7.1.6.](#) Revision

0

[7.1.7.](#) Revision Date

TBD

7.1.8. Metric Description

A delta count of the number of octets observed.

7.1.9. Reference Specification(s)

octetDeltaCount described in [section 5.10.1 of \[RFC5102\]](#)

7.2. Metric Definition

This category includes columns to prompt the entry of all necessary details related to the metric definition, including the RFC reference and values of input factors, called fixed parameters.

7.2.1. Reference Definition

octetDeltaCount described in [section 5.10.1 of \[RFC5102\]](#)

7.2.2. Fixed Parameters

As this is the generalised version of the IP delta count metric, there are no fixed parameters.

7.3. Method of Measurement

7.3.1. Reference Implementation

For <metric>.

<section reference>

7.3.2. Traffic Filter Criteria

This measurement only covers IP packets and the IP payload (including the IP header) of these packets. Non-IP packets (BPDUs, ISIS) will not be accounted. Layer 2 overhead (Ethernet headers, MPLS, QinQ, etc.) will also not be represented in the measurement.

7.3.3. Measurement Timing

This is a continuous measurement of the IP octets seen in the traffic selection scope (run-time parameter).

The measurement interval is a run time parameter.

There is no sampling.

7.3.4. Output Type(s) and Data Format

It is possible that multiple observation intervals are reported in a single report. In such a case concatenation of the interval reports (deltaOctetCount, start-time, end-time) is allowed.

The delta octet count metric reports a observation start time and end time.

- o Value: observation-start-time and observation-end-time
- o Data Format: 64-bit NTP Time-stamp Format
- o Reference: [section 6 of \[RFC5905\]](#)

7.3.5. Metric Units

The measured results are expressed in octets with a data format of unsigned64 as described in [\[RFC5102\]](#)

7.3.6. Run-time Parameters and Data Format

Run-time Parameters are input factors that must be determined, configured into the measurement system, and reported with the results for the context to be complete.

- o samplingTimeInterval, length of time a single report covers. unsigned32 microseconds [\[RFC5477\]](#)
- o observationInterface, ifindex of interface to monitor. -1 represents all interfaces. -2 represents WAN facing and -3 represents LAN facing. unsigned32.
- o observation direction, unsigned8 where 0 represents incoming traffic on interface, 1 outgoing and 2 represents both incoming and outgoing.

7.4. Comments and Remarks

Additional (Informational) details for this entry

8. Example 5min Passive Egress Octet Count Entry on WAN Interface

tbd

This section is Informational.

This section gives an example registry entry for accounting of outgoing WAN IP traffic the passive metric in terms of octetDeltaCount, as described in [[RFC5102](#)].

[8.1.](#) Registry Indexes

This category includes multiple indexes to the registry entries, the element ID and metric name.

[8.1.1.](#) Element Identifier

An integer having enough digits to uniquely identify each entry in the Registry.

TBD by IANA.

[8.1.2.](#) Metric Name

A metric naming convention is TBD.

One possibility based on the proposal in [[I-D.ietf-ippm-metric-registry](#)]:

Pas_IP-Octet-Delta-WAN-egress

[8.1.3.](#) URI

urn:ietf:params:performance:metric-something

[8.1.4.](#) Status

Current

[8.1.5.](#) Requester

TBD

[8.1.6.](#) Revision

0

[8.1.7.](#) Revision Date

TBD

8.1.8. Metric Description

A delta count of the number of octets observed outgoing on WAN interface.

8.1.9. Reference Specification(s)

octetDeltaCount described in [section 5.10.1 of \[RFC5102\]](#)

8.2. Metric Definition

This category includes columns to prompt the entry of all necessary details related to the metric definition, including the RFC reference and values of input factors, called fixed parameters.

8.2.1. Reference Definition

octetDeltaCount described in [section 5.10.1 of \[RFC5102\]](#)

8.2.2. Fixed Parameters

As this is a specific version of Pas_IP-Octet-Delta-General that performs metering of all outgoing WAN traffic.

- o samplingTimeInterval= 300000000, length of time a single report covers. unsigned32 microseconds [\[RFC5477\]](#)
- o observationInterface= -2, ifindex of interface to monitor. -1 represents all interfaces. -2 represents WAN facing and -3 represents LAN facing. unsigned32.
- o observation direction= 1, unsigned8 where 0 represents incoming traffic on interface, 1 outgoing and 2 represents both incoming and outgoing.

8.3. Method of Measurement

8.3.1. Reference Implementation

For <metric>.

<section reference>

8.3.2. Traffic Filter Criteria

This measurement only covers IP packets observed in the WAN outgoing direction. The bytes counted are the IP payload (including the IP header) of these packets. Non-IP packets (BPDUs, ISIS) will not be

accounted. Layer 2 overhead (Ethernet headers, MPLS, QinQ, etc.) will also not be represented in the measurement.

8.3.3. Measurement Timing

This is a continuous measurement of the IP octets seen in the traffic selection scope (run-time parameter), each of a 5 minute duration.

There is no sampling.

8.3.4. Output Type(s) and Data Format

It is possible that multiple observation intervals are reported in a single report. In such a case concatenation of the interval reports (deltaOctetCount, start-time, end-time) is allowed.

The delta octet count metric reports a observation start time and end time.

- o Value: observation-start-time and observation-end-time
- o Data Format: 64-bit NTP Time-stamp Format
- o Reference: [section 6 of \[RFC5905\]](#)

8.3.5. Metric Units

The measured results are expressed in octets with a data format of unsigned64 as described in [\[RFC5102\]](#)

8.3.6. Run-time Parameters and Data Format

There are no run-time parameters for this registry entry.

8.4. Comments and Remarks

Additional (Informational) details for this entry

9. Example Passive RTP Lost Packet Count

tbd

10. Example BLANK Registry Entry

This section is Informational. (?)

This section gives an example registry entry for the <type of metric and specification reference> .

10.1. Registry Indexes

This category includes multiple indexes to the registry entries, the element ID and metric name.

10.1.1. Element Identifier

An integer having enough digits to uniquely identify each entry in the Registry.

10.1.2. Metric Name

A metric naming convention is TBD.

10.1.3. URI

urn:ietf:params:performance:metric-something

10.1.4. Status

Current

10.1.5. Requester

TBD

10.1.6. Revision

0

10.1.7. Revision Date

TBD

10.1.8. Metric Description

A metric Description is TBD.

10.1.9. Reference Specification(s)

Section YY, RFCXXXX

10.2. Metric Definition

10.2.1. Reference Definition

< possible section reference>

10.2.2. Fixed Parameters

Fixed Parameters are input factors that must be determined and embedded in the measurement system for use when needed. The values of these parameters is specified in the Registry.

<list fixed parameters>

10.3. Method of Measurement

10.3.1. Reference Implementation

For <metric>.

<section reference>

10.3.2. Traffic Filter Criteria

<list filter criteria limitations and allowances >

10.3.3. Measurement Timing

< list timing requirements and limitations >

10.3.4. Output Type(s) and Data Format

The output types define the type of result that the metric produces.

- o Value:

- o Data Format: (There may be some precedent to follow here, but otherwise use 64-bit NTP Time-stamp Format, see [section 6 of \[RFC5905\]](#)).

- o Reference: <section reference>

10.3.5. Metric Units

The measured results are expressed in <units>.

<section reference>.

10.3.6. Run-time Parameters and Data Format

Run-time Parameters are input factors that must be determined, configured into the measurement system, and reported with the results for the context to be complete.

<list of run-time parameters>

<reference(s)>.

10.4. Comments and Remarks

Additional (Informational) details for this entry

11. Security Considerations

This registry has no known implications on Internet Security.

12. IANA Considerations

IANA is requested to create The Passive Performance Metric Sub-registry within the Performance Metric Registry defined in [[I-D.ietf-ippm-metric-registry](#)]. The Sub-registry will contain the following categories and (bullet) columns, (as defined in [section 6](#) above):

Common Registry Indexes and Info

- o Identifier
- o Name
- o URI
- o Status
- o Requester
- o Revision
- o Revision Date
- o Description
- o Reference Specification(s)

Metric Definition

- o Reference Definition

- o Fixed Parameters

Method of Measurement

- o Reference Implementation

- o Traffic Filter Criteria

- o Measurement Timing

- o Output Type(s) and Data format

- o Metric Units

- o Run-time Parameters

Comments and Remarks

13. Acknowledgements

The authors thank the prior work of Al Morton, Marcelo Bagnulo and Phil Eardley in "[draft-ietf-ippm-registry-active](#)" which was used both as a template for this document and source of text.

14. References

14.1. Normative References

[I-D.ietf-ippm-metric-registry]
Bagnulo, M., Claise, B., Eardley, P., and A. Morton,
"Registry for Performance Metrics", [draft-ietf-ippm-metric-registry-00](#) (work in progress), July 2014.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.

14.2. Informative References

[BMWG] IETF, , "Benchmarking Methodology (BMWG) Working Group, <http://datatracker.ietf.org/wg/bmwg/charter/>", .

[I-D.ietf-ippm-registry-active]
Morton, A., Bagnulo, M., and P. Eardley, "Active Performance Metric Sub-Registry", [draft-ietf-ippm-registry-active-00](#) (work in progress), April 2014.

[I-D.ietf-lmap-framework]

Eardley, P., Morton, A., Bagnulo, M., Burbridge, T., Aitken, P., and A. Akhter, "A framework for large-scale measurement platforms (LMAP)", [draft-ietf-lmap-framework-07](#) (work in progress), June 2014.

[IPFIX] IETF, , "IP Flow Information eXport (IPFIX) Working Group, <http://datatracker.ietf.org/wg/ipfix/charter/>", .

[PMOL] IETF, , "IP Performance Metrics for Other Layers (PMOL) Working Group, <http://datatracker.ietf.org/wg/pmol/charter/>", .

[RFC2330] Paxson, V., Almes, G., Mahdavi, J., and M. Mathis, "Framework for IP Performance Metrics", [RFC 2330](#), May 1998.

[RFC3550] Schulzrinne, H., Casner, S., Frederick, R., and V. Jacobson, "RTP: A Transport Protocol for Real-Time Applications", STD 64, [RFC 3550](#), July 2003.

[RFC3611] Friedman, T., Caceres, R., and A. Clark, "RTP Control Protocol Extended Reports (RTCP XR)", [RFC 3611](#), November 2003.

[RFC5102] Quittek, J., Bryant, S., Claise, B., Aitken, P., and J. Meyer, "Information Model for IP Flow Information Export", [RFC 5102](#), January 2008.

[RFC5477] Dietz, T., Claise, B., Aitken, P., Dressler, F., and G. Carle, "Information Model for Packet Sampling Exports", [RFC 5477](#), March 2009.

[RFC5905] Mills, D., Martin, J., Burbank, J., and W. Kasch, "Network Time Protocol Version 4: Protocol and Algorithms Specification", [RFC 5905](#), June 2010.

[RFC6035] Pendleton, A., Clark, A., Johnston, A., and H. Sinnreich, "Session Initiation Protocol Event Package for Voice Quality Reporting", [RFC 6035](#), November 2010.

[RFC6390] Clark, A. and B. Claise, "Guidelines for Considering New Performance Metric Development", [BCP 170](#), [RFC 6390](#), October 2011.

[XRBLOCK] IETF, , "Metric Blocks for use with RTCP's Extended Report Framework (XRBLOCK), <http://datatracker.ietf.org/wg/xrblock/charter/>", .

Authors' Addresses

Aamer Akhter
Cisco Systems, Inc.
7025 Kit Creek Road
RTP, NC 27709
USA

Email: aakhter@cisco.com

Benoit Claise
Cisco Systems, Inc.
De Kleetlaan 6a b1
1831 Diegem
Belgium

Phone: +32 2 704 5622

Email: bclaise@cisco.com

