

IP Performance Metrics Working Group  
Internet Draft  
Document: <[draft-ietf-ippm-reordering-00.txt](#)>  
Category: Standards Track

A.Morton  
L.Ciavattone  
G.Ramachandran  
AT&T Labs  
S.Shalunov  
Internet2  
J.Perser  
Spirent

## Reordering Metric for IPPM

### Status of this Memo

This document is an Internet-Draft and is in full conformance with all provisions of [Section 10 of RFC2026](#) [1].

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts. Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or made obsolete by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/lid-abstracts.txt>

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

### 1. Abstract

This memo defines a simple metric to determine if a network has maintained packet order. It provides motivations for the new metric, suggests a metric definition, and discusses the issues associated with measurement. The memo includes sample metrics to quantify the extent of reordering in several useful dimensions. Some examples of evaluation using the various sample metrics are included.

### 2. Conventions used in this document

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [2]. Although [RFC 2119](#) was written with protocols in mind, the key words are used in this document for similar reasons. They are used to ensure the results of measurements from two different

implementations are comparable, and to note instances when an implementation could perturb the network.

### 3. Introduction

Ordered delivery is a property of successful packet transfer attempts, where the packet sequence ascends for each arriving packet and there are no backward steps.

An explicit sequence number, such as the sending time of each packet or an incrementing message number carried in each packet establishes the Source Sequence.

The presence of reordering at the Destination is based on arrival order.

This metric classifies arriving packets with sequence numbers smaller than their predecessors as out-of-order, or reordered. For example, if arriving packets are numbered 1,2,4,5,3, then packet 3 is reordered. This is equivalent to Paxson's reordering definition in [3], where "late" packets were declared reordered. The alternative is to emphasize "premature" packets instead (4 and 5 in the example). The metric's construction is very similar to the sequence space validation for received segments in [RFC793](#) [4]. Earlier work to define ordered delivery includes [5], and more ???.

#### 3.1 Motivation

A reordering metric is relevant for most applications, especially when assessing network support for Real-Time media streams. The extent of reordering may be sufficient to cause a received packet to be discarded by functions above the IP layer.

Packet order is not expected to change during transfer, but several specific path characteristics can cause their order to change.

Examples are:

- \* When two paths, one with slightly longer transfer time, support a single packet stream or flow, then packets traversing the longer path may arrive out-of-order. Multiple paths may be used to achieve load balancing, or may arise from route instability.
- \* To increase capacity, a network device designed with multiple processors serving a single port may reorder as a byproduct.
- \* A layer 2 retransmission protocol that compensates for an error-prone link may cause packet reordering.
- \* If for any reason, the packets in a buffer are not serviced in the

order of their arrival, their order will change.

- \* If packets in a flow are assigned to multiple buffers (following evaluation of traffic characteristics, for example), and the buffers have different occupations and/or service rates, then order will likely change.

The ability to restore order at the destination will likely have finite limits. Practical hosts have receiver buffers with finite

size in terms of packets, bytes, or time (such as de-jitter buffers). Once the initial determination of reordering is made, it is useful to quantify the extent of reordering, or lateness, in all meaningful dimensions.

### [3.2](#) Goals and Objectives

The definitions below intend to satisfy the goals of:

1. Determining whether or not packet order is maintained.
2. Quantifying the extent (achieving this second goal requires assumptions of upper layer functions and capabilities to restore order, and therefore several solutions).

Reordering Metrics MUST:

- + be relevant to one or more known applications
- + be computable "on the fly"
- + work with Poisson and Periodic test streams
- + work even if the stream has duplicate or lost packets

Reordering Metrics SHOULD:

- + have concatenating results for segments measured separately
- + have simplicity for easy consumption and understanding
- + have relevance to TCP performance
- + have relevance to Real-time application performance

## [4.](#) An Ordered Arrival Singleton Metric

The IPPM framework [RFC 2330](#) [3] gives the definitions of singletons, samples, and statistics.

The evaluation of packet order requires several supporting concepts. The first is an incrementing sequence number applied to packets at the source (decrementing sequences can be accommodated, and sequence roll-over is treated later). The source order may be established by a simple message number, a byte stream number, or it may be the actual time when each packet departs from the Src.

The second supporting concept is a stored value which is the "next expected" packet number. Under normal conditions, the value of Next Expected (NextExp) is the sequence number of the previous packet (plus 1 for message numbering). In byte stream numbering, NextExp is a value 1 byte greater than the last in-order packet sequence number + payload. If Src time is used as the sequence number, NextExp is the Src time from the last in-order packet + 1 clock tick.

Each packet within a packet stream can be evaluated for its order singleton metric.

#### [4.1](#) Metric Name:

Type-P-Non-Reversing-Order

#### [4.2](#) Metric Parameters:

- + Src, the IP address of a host
- + Dst, the IP address of a host
- + SrcTime, the time of packet emission from the Src
- + SrcNum, the packet sequence number applied at the Src, in units of messages or bytes.
- + NextExp, the Next Expected Sequence number at the Dst, in units of messages, time, or bytes.
- + PayloadSize, the number of bytes contained in the information field and referred to when the SrcNum sequence is based on byte transfer.

#### [4.3](#) Definition:

In-order packets have sequence numbers (or Src times) greater than or equal to the value of Next Expected. Each new in-order packet will increase the Next Expected (typically by 1 for message numbering, or the payload size plus 1 for byte numbering). The Next Expected value cannot decrease, thereby specifying non-reversing order as the basis to identify reordered packets.

A reordered packet outcome occurs when a single IP packet at the Dst Measurement Point results in the following:

The packet has a Src sequence number lower than the Next Expected

(NextExp), and therefore the packet is reordered. The Next Expected value does not change on the arrival of this packet.

This definition can also be specified in pseudo-code.

On successful arrival of a packet with sequence number n:

```
    if n >= NextExp, /* n is in-order */
        then
            NextExp = n + PayloadSize + 1;
    else /* when n < NextExp */
        designate packet n as reordered;
```

When using message-based sequence numbering or Src time, PayloadSize=0.

#### [4.4](#) Discussion

Any arriving packet bearing a sequence number from the sequence that establishes the Next Expected value can be evaluated to determine if

it is in-order, or reordered, based on a previous packet's arrival. In the case where Next Expected is Undefined (because the arriving packet is the first successful transfer), the packet is designated in-order.

#### [5.](#) Sample Metrics

It is highly desirable to assert the degree to which a packet is out-of-order with respect to a sample of packets. This section defines several metrics that quantify the extent of reordering in various units of measure. Each metric highlights a relevant application.

##### [5.1](#) N-Reordering

[Note: This is a modified definition of N-Reordering.]

Metric Name: Type-P-packet-N-reordering-Poisson/Periodic-Stream

Parameter Notation: Let N be a positive integer (a parameter). Let K be a positive integer (sample size, the number of packets sent). Let L be a non-negative integer representing the number of packets that were received out of the K packets sent. Assign each sent packet a sequence number, 1 to K. Let  $\langle S_1, \dots, S_L \rangle$  be the original sequence numbers of the received packets, in the order of arrival (duplicates are possible).

Definition 1: Received packet number I ( $N < I \leq L$ ) is called N-reordered IFF for all J such that  $I-N \leq J < I$  we have  $S_J > S_I$ .

Let  $M$  be the number of  $N$ -reordered packets in the sample.

Definition 2: The degree of  $N$ -reordering of the sample is  $M/(K-N)$ .

Definition 3: The degree of reordering of the sample is its degree of 1-reordering.

Definition 4: A sample is said to have no reordering if its degree of reordering is 0.

Discussion:

The degree of  $N$ -reordering may be expressed as a percentage, in which case the number from definition 2 is multiplied by 100.

$N$ -reordering is particularly useful for determining the portion of reordered packets which can or cannot be restored to order in a typical TCP receiver buffer based on their arrival order alone (and without the aid of retransmission).

[need more on this].

## [5.2](#) Reordering Offset

Any packet whose sequence number causes the Next Expected value to increment by more than the usual increment indicates a discontinuity in the sequence. From this point on, any packets with sequence number less than the Next Expected value can be assigned Offset values indicating their position (in packets or bytes) and lateness in terms of time of arrival with respect to a sequence discontinuity. The various Offset metrics are calculated only on reordered packets, as defined in [section 4](#).

### [5.2.1](#) Metric Name: Type-P-packet-Position-Offset-Poisson/Periodic-Stream

Metric Parameters: In addition to the parameters defined for Type-P-Non-Reversing-Order, we specify:

- + DstOrder, numerical order in which each packet in the stream arrives at Dst

Definition: Reordered packets are associated with a specific sequence discontinuity by determining which earlier packet's sequence number skipped over them. We calculate all expressions of Offset with respect to that packet. Position Offset is calculated

from a Dst Order number assigned to each packet on arrival:

Position Offset =  
DstOrder(reordered packet)-DstOrder(packet at discontinuity)

Using the notation of [Section 5.1](#), an equivalent definition is:

The Position Offset of Reordered Packet I is  $M = I - J$ , for  $\min\{J | 1 \leq J < I\}$  that satisfies  $S_J > S_I$ .

### [5.2.2](#) Metric Name: Type-P-packet-Late-Time-Poisson/Periodic-Stream

Metric Parameters: In addition to the parameters defined for Type-P-Non-Reversing-Order, we specify:

+ DstTime, the time that each packet in the stream arrives at Dst

Definition: Lateness in time is calculated using Dst times.

Late Time =  
DstTime(reordered packet)-DstTime(packet at discontinuity)

Using similar notation to that of [Section 5.1](#), an equivalent definition is:

The Late Time of Reordered Packet I is  $T = \text{DstTime}_I - \text{DstTime}_J$ , for  $\min\{J | 1 \leq J < I\}$  that satisfies  $S_J > S_I$ , or  $\text{SrcTime}_J > \text{SrcTime}_I$ .

### [5.2.3](#) Metric Name: Type-P-packet-Byte-Offset-Poisson/Periodic-Stream

Morton, et al. Standards Track exp. Dec 2002  
Reordering Metric for IPPM

Page 6  
June 2002

Metric Parameters: We use the same parameters defined above.

Definition: Byte stream offset can be determined from the payload sizes of intervening packets.

Byte Offset =  
PayloadNum(reordered packet, DstOrder=m)  
- Sum[PayloadSize(packet, DstOrder=m-1),  
PayloadSize(packet, DstOrder=m-2), ...  
PayloadSize(packet at discontinuity)]

### [5.2.4](#) Discussion

The Offset metrics can predict whether reordered packets will be useful in a general, limited receiver buffer system. The limit may be the number of bytes or packets the buffer can store, or the time of storage prior to a cyclic play-out instant (as with de-jitter buffers).

Note that the One-way IPDV [6] gives the delay variation for a packet w.r.t. the preceding packet in the source sequence. Lateness and IPDV give an indication of whether a buffer at Dst has sufficient storage to accommodate the network's behavior and restore order. When an earlier packet in the Src sequence is lost, IPDV will necessarily be undefined for adjacent packets, and Late Time may provide the only way to evaluate the usefulness of a packet.

In the case of de-jitter buffers, there are circumstances where the receiver employs loss concealment at the intended play-out time of a late packet. However, if this packet arrives out of order, the Late Time determines whether the packet is still useful. IPDV no longer applies, because the receiver establishes a new play-out schedule with more buffer delay to accommodate similar events in the future - this requires very minimal processing.

When packets in the stream have variable sizes, it may be most useful to characterize Offset in terms of the payload size(s) of stored packets (using byte stream numbering).

For a sample of packets in a stream, results may be reported as a ratio of reordered packets to total packets sent by the source during the test. If separate reordering events can be distinguished, then an event count may also be reported (along with the event description, such as the number of reordered packets and their offsets). The distribution of various Offset metrics may also be reported and summarized as average, range, etc.

## 6. Measurement Issues

The results of sequence tests will be dependent on the time interval between measurement packets (both at the Src, and during transport

where spacing may change). Clearly, packets launched infrequently (e.g., 1 per 10 seconds) are unlikely to be reordered.

The Non-reversing order criterion remains valid and useful when a stream of packets experiences packet loss, or both loss and reordering. In other words, losses alone do not cause subsequent packets to be declared reordered.

Assuming that the necessary sequence information (sequence number and/or source time stamp) is included in the packet payload (possibly in application headers such as RTP), packet sequence may be evaluated in a passive measurement arrangement. Also, it is possible to evaluate sequence at a single point along a path, since the usual need for synchronized Src and Dst Clocks may be relaxed to

some extent.

When the Src sequence is based on byte stream, or payload numbering, care must be taken to avoid declaring retransmitted packets out-of-sequence. The additional reference of Src Time is one way to avoid this ambiguity.

Since this metric definition may use sequence numbers with finite range, it is possible that the sequence numbers could reach end-of-range and roll over to zero during a measurement. By definition, the Next Expected value cannot decrease, and all packets received after a roll-over would be declared out-of-sequence. Sequence number roll-over can be avoided by using combinations of counter size and test duration where roll-over is impossible (and sequence is reset to zero at the start). Also, message-based numbering results in slower sequence consumption. There may still be cases where methodological mitigation of this problem is desirable (e.g., long-term testing). The elements of mitigation are:

1. There must be a test to detect if a roll-over has occurred. It would be nearly impossible for the sequence numbers of successive packets to jump by more than half the total range, so these large discontinuities are designated as roll-over.
2. All sequence numbers used in computations are represented in a sufficiently large precision. The numbers have a correction applied (equivalent to adding a significant digit) whenever roll-over is detected.
3. Out-of-order packets coincident with sequence numbers reaching end-of-range must also be detected for proper application of correction factor.

## 7. Examples of Order Evaluation

This section provides some examples to illustrate how the non-reversing order criterion works, and the value of viewing reordering in both the dimensions of time and position.

Table 1 gives a simple case of reordering, where one packet (the packet with SrcNum=4) arrives out-of-order. Packets are arranged according to their arrival, and message numbering is used.

Table 1 Example with Packet 4 Reordered,  
Sending order(SrcNum@Src): 1,2,3,4,5,6,7,8,9,10

SrcNum	Src	Dst	Dst	Posit.	Late	
@Dst	NextExp	Time	Time	Order	Offset	Time

1	1	0	68	68		1		
2	2	20	88	68	0	2		
3	3	40	108	68	0	3		
5	4	80	148	68	-82	4		
6	6	100	168	68	0	5		
7	7	120	188	68	0	6		
8	8	140	208	68	0	7		
4	9	60	210	150	82	8	4	62
9	9	160	228	68	0	9		
10	10	180	248	68	0	10		

Each column gives the following information:

SrcNum Packet sequence number at the Source.  
NextExp The value of NextExp when the packet arrived(before update).  
SrcTime Packet time stamp at the Source, ms.  
DstTime Packet time stamp at the Destination, ms.  
Delay 1-way delay of the packet, ms.  
IPDV IP Packet Delay Variation, ms  
IPDV = Delay(SrcNum)-Delay(SrcNum-1)  
DstOrder Order in which the packet arrived at the Destination.  
Posit.Offset The Position Offset of an out-of-order packet.  
LateTime The lateness of an out-of-order packet, ms.

We can see that when packet 4 arrives, NextExp=9, and it is declared reordered. Further, we can compute the Offset of packet 4 in terms of position (8-4=4 using DstOrder) and Late Time (210-148=62ms using DstTime) compared to packet 5's arrival. If Dst has a de-jitter buffer that holds more than 4 packets, or at least 62 ms storage, packet 4 may be useful. Note that 1-way delay and IPDV also indicate unusual behavior for packet 4.

If all packets contained 100 byte payloads, then Byte Offset is equal to 500 bytes.

In the notation of N-reordering,  $\langle S_1, \dots, S_I, \dots, S_L \rangle$  the received packets are represented as:

1\_1, 2\_2, 3\_3, 5\_4, 6\_5, 7\_6, 8\_7, 4\_8, 9\_9, 10\_10

when  $N=1$ ,  $7 \leq J < 8$ , and  $8_7 > 4_8$ , so packet  $I=8$  is 1-reordered.

when  $N=2$ ,  $6 \leq J < 8$ , and  $7_6 > 4_8$ , so packet  $I=8$  is 2-reordered.  
when  $N=3$ ,  $5 \leq J < 8$ , and  $6_5 > 4_8$ , so packet  $I=8$  is 3-reordered.  
when  $N=4$ ,  $4 \leq J < 8$ , and  $5_4 > 4_8$ , so packet  $I=8$  is 4-reordered.

We note that the Position Offset is equal to the Max(N) with N-reordering.

Table 2 Example with Packets 5 and 6 Reordered,  
Sending order(SrcNum@Src): 1,2,3,4,5,6,7,8,9,10

SrcNum	Src	Dst	Dst	Posit.	Late
@Dst	NextExp	Time	Time	Offset	Time
1	1	0	68		
2	2	20	88		
3	3	40	108		
4	4	60	128		
7	5	120	188		
5	8	80	189	1	1
6	8	100	190	2	2
8	8	140	208		
9	9	160	228		
10	10	180	248		

[ Remaining examples need to have N-reordering added ]

Table 2 shows a case where packets 5 and 6 arrive just behind packet 7, so both 5 and 6 are declared out-of-order. Their positional offsets (6-5=1 and 7-5=2, using DstOrder again) and Late times (189-188=1, 190-188=2) are small.

Table 3 Example with Packets 4, 5, and 6 reordered  
Sending order(SrcNum@Src): 1,2,3,4,5,6,7,8,9,10,11

SrcNum	Src	Dst	Dst	Posit.	Late
@Dst	NextExp	Time	Time	Offset	Time
1	1	0	68		
2	2	20	88		
3	3	40	108		
7	4	120	188		
8	8	140	208		
9	9	160	228		
10	10	180	248		
4	11	60	250	4	62
5	11	80	252	5	64
6	11	100	256	6	68
11	11	200	268		

The case in Table 3 is where three packets in sequence have long transit times. Delay, Late time, and Offset capture this very well, and indicate variation in reordering extent, while IPDV indicates that the spacing between packets 4,5,and 6 has changed.

## 8. Security Considerations [mostly borrowed from npmps]

### 8.1 Denial of Service Attacks

This metric requires a stream of packets sent from one host (Src) to another host (Dst) through intervening networks. This method could be abused for denial of service attacks directed at Dst and/or the intervening network(s).

Administrators of Src, Dst, and the intervening network(s) should establish bilateral or multi-lateral agreements regarding the timing, size, and frequency of collection of sample metrics. Use of this method in excess of the terms agreed between the participants may be cause for immediate rejection or discard of packets or other escalation procedures defined between the affected parties.

### 8.2 User data confidentiality

Active use of this method generates packets for a sample, rather than taking samples based on user data, and does not threaten user data confidentiality. Passive measurement must restrict attention to the headers of interest. Since user payloads may be temporarily stored for length analysis, suitable precautions MUST be taken to keep this information safe and confidential.

### 8.3 Interference with the metric

It may be possible to identify that a certain packet or stream of packets is part of a sample. With that knowledge at Dst and/or the intervening networks, it is possible to change the processing of the packets (e.g. increasing or decreasing delay) that may distort the measured performance. It may also be possible to generate additional packets that appear to be part of the sample metric. These additional packets are likely to perturb the results of the sample measurement.

To discourage the kind of interference mentioned above, packet interference checks, such as cryptographic hash, may be used.

## 9. IANA Considerations

Since this metric does not define a protocol or well-known values, there are no IANA considerations in this memo.

## 10. References

- 1 Bradner, S., "The Internet Standards Process -- Revision 3", [BCP 9](#), [RFC 2026](#), October 1996.
- 2 Bradner, S., "Key words for use in RFCs to Indicate Requirement

Levels", [RFC 2119](#), March 1997.

Morton, et al. Standards Track exp. Dec 2002  
Reordering Metric for IPPM

Page 11  
June 2002

- 3 V.Paxson, "Measurements and Analysis of End-to-End Internet Dynamics," Ph.D. dissertation, U.C. Berkeley, 1997, <ftp://ftp.ee.lbl.gov/papers/vp-thesis/dis.ps.gz>.
- 4 Postel, J., "Transmission Control Protocol", STD 7, [RFC 793](#), September 1981.  
Obtain via: <http://www.rfc-editor.org/rfc/rfc793.txt>
- 5 L.Ciavattone and A.Morton, "Out-of-Sequence Packet Parameter Definition (for Y.1540)", Contribution number T1A1.3/2000-047, October 30, 2000. <ftp://ftp.t1.org/pub/t1a1/2000-A13/0a130470.doc>
- 6 Demichelis, C., and Chimento, P., "IP Packet Delay Variation Metric for IPPM", work in progress.

## 11. Acknowledgments

The authors would like to acknowledge the helpful discussions with Matt Mathis, and . We gratefully acknowledge the foundation laid by the authors of the IP performance Framework [3].

## 11. Author's Addresses

Al Morton  
AT&T Labs  
Room D3 - 3C06  
200 Laurel Ave. South  
Middletown, NJ 07748 USA  
Phone +1 732 420 1571 Fax +1 732 368 1192  
<acmorton@att.com>

Len Ciavattone  
AT&T Labs  
Room C4 - 2B29  
200 Laurel Ave. South  
Middletown, NJ 07748 USA  
Phone +1 732 420 1239  
<lencia@att.com>

Gomathi Ramachandran  
AT&T Labs  
Room C4 - 3D22

200 Laurel Ave. South  
Middletown, NJ 07748 USA  
Phone +1 732 420 2353  
<gomathi@att.com>

Stanislav Shalunov  
University Corporation for Advanced Internet Development

Morton, et al. Standards Track exp. Dec 2002  
Reordering Metric for IPPM

Page 12  
June 2002

200 Business Park Drive, Suite 307  
Armonk, NY 10504  
Phone: + 1 914 765 1182  
EMail: <shalunov@internet2.edu>

Jerry Perser  
Spirent Communications  
26750 Agoura Road  
Calabasas, CA 91302 USA  
Phone: + 1 818 676 2300  
EMail: <jerry.perser@spirentcom.com>

#### Full Copyright Statement

"Copyright (C) The Internet Society (date). All Rights Reserved.  
This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to the Internet Society or other Internet organizations, except as needed for the purpose of developing Internet standards in which case the procedures for copyrights defined in the Internet Standards process must be followed, or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by the Internet Society or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

