

Network Working Group  
Internet-Draft  
Intended status: Informational  
Expires: March 10, 2013

L. Ciavattone  
AT&T Labs  
R. Geib  
Deutsche Telekom  
A. Morton  
AT&T Labs  
M. Wieser  
Technical University Darmstadt  
September 6, 2012

**Test Plan and Results Supporting Advancement of [RFC 2679](#) on the  
Standards Track  
draft-ietf-ippm-testplan-rfc2679-03**

**Abstract**

This memo provides the supporting test plan and results to advance [RFC 2679](#) on One-way Delay Metrics along the standards track, following the process in [RFC 6576](#). Observing that the metric definitions themselves should be the primary focus rather than the implementations of metrics, this memo describes the test procedures to evaluate specific metric requirement clauses to determine if the requirement has been interpreted and implemented as intended. Two completely independent implementations have been tested against the key specifications of [RFC 2679](#). This memo also provides direct input for development of RFC 2679bis.

**Requirements Language**

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

**Status of this Memo**

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on March 10, 2013.

#### Copyright Notice

Copyright (c) 2012 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

This document may contain material from IETF Documents or IETF Contributions published or made publicly available before November 10, 2008. The person(s) controlling the copyright in some of this material may not have granted the IETF Trust the right to allow modifications of such material outside the IETF Standards Process. Without obtaining an adequate license from the person(s) controlling the copyright in such materials, this document may not be modified outside the IETF Standards Process, and derivative works of it may not be created outside the IETF Standards Process, except to format it for publication as an RFC or to translate it into languages other than English.



## Table of Contents

<a href="#">1.</a>	Introduction . . . . .	<a href="#">4</a>
<a href="#">2.</a>	A Definition-centric metric advancement process . . . . .	<a href="#">5</a>
<a href="#">3.</a>	Test configuration . . . . .	<a href="#">5</a>
<a href="#">4.</a>	Error Calibration, <a href="#">RFC 2679</a> . . . . .	<a href="#">9</a>
<a href="#">4.1.</a>	NetProbe Error and Type-P . . . . .	<a href="#">10</a>
<a href="#">4.2.</a>	Perfas+ Error and Type-P . . . . .	<a href="#">12</a>
<a href="#">5.</a>	Pre-determined Limits on Equivalence . . . . .	<a href="#">13</a>
<a href="#">6.</a>	Tests to evaluate <a href="#">RFC 2679</a> Specifications . . . . .	<a href="#">13</a>
6.1.	One-way Delay, ADK Sample Comparison - Same & Cross Implementation . . . . .	<a href="#">14</a>
<a href="#">6.1.1.</a>	NetProbe Same-implementation results . . . . .	<a href="#">15</a>
<a href="#">6.1.2.</a>	Perfas+ Same-implementation results . . . . .	<a href="#">16</a>
<a href="#">6.1.3.</a>	One-way Delay, Cross-Implementation ADK Comparison . . . . .	<a href="#">17</a>
<a href="#">6.1.4.</a>	Conclusions on the ADK Results for One-way Delay . . . . .	<a href="#">17</a>
<a href="#">6.1.5.</a>	Additional Investigations . . . . .	<a href="#">18</a>
<a href="#">6.2.</a>	One-way Delay, Loss threshold, <a href="#">RFC 2679</a> . . . . .	<a href="#">21</a>
<a href="#">6.2.1.</a>	NetProbe results for Loss Threshold . . . . .	<a href="#">22</a>
<a href="#">6.2.2.</a>	Perfas+ Results for Loss Threshold . . . . .	<a href="#">22</a>
<a href="#">6.2.3.</a>	Conclusions for Loss Threshold . . . . .	<a href="#">22</a>
<a href="#">6.3.</a>	One-way Delay, First-bit to Last bit, <a href="#">RFC 2679</a> . . . . .	<a href="#">22</a>
<a href="#">6.3.1.</a>	NetProbe and Perfas+ Results for Serialization . . . . .	<a href="#">23</a>
<a href="#">6.3.2.</a>	Conclusions for Serialization . . . . .	<a href="#">24</a>
<a href="#">6.4.</a>	One-way Delay, Difference Sample Metric (Lab) . . . . .	<a href="#">25</a>
<a href="#">6.4.1.</a>	NetProbe results for Differential Delay . . . . .	<a href="#">25</a>
<a href="#">6.4.2.</a>	Perfas+ results for Differential Delay . . . . .	<a href="#">26</a>
<a href="#">6.4.3.</a>	Conclusions for Differential Delay . . . . .	<a href="#">26</a>
<a href="#">6.5.</a>	Implementation of Statistics for One-way Delay . . . . .	<a href="#">26</a>
<a href="#">7.</a>	Conclusions and <a href="#">RFC 2679</a> Errata . . . . .	<a href="#">27</a>
<a href="#">8.</a>	Security Considerations . . . . .	<a href="#">27</a>
<a href="#">9.</a>	IANA Considerations . . . . .	<a href="#">28</a>
<a href="#">10.</a>	Acknowledgements . . . . .	<a href="#">28</a>
<a href="#">11.</a>	References . . . . .	<a href="#">28</a>
<a href="#">11.1.</a>	Normative References . . . . .	<a href="#">28</a>
<a href="#">11.2.</a>	Informative References . . . . .	<a href="#">29</a>
	Authors' Addresses . . . . .	<a href="#">30</a>



## **1. Introduction**

The IETF IP Performance Metrics (IPPM) working group has considered how to advance their metrics along the standards track since 2001, with the initial publication of Bradner/Paxson/Mankin's memo [[I-D.bradner-metricstest](#)]. The original proposal was to compare the performance of metric implementations. This was similar to the usual procedures for advancing protocols, which did not directly apply. It was found to be difficult to achieve consensus on exactly how to compare implementations, since there were many legitimate sources of variation that would emerge in the results despite the best attempts to keep the network paths equal, and because considerable variation was allowed in the parameters (and therefore implementation) of each metric. Flexibility in metric definitions, essential for customization and broad appeal, made the comparison task quite difficult.

A renewed work effort investigated ways in which the measurement variability could be reduced and thereby simplify the problem of comparison for equivalence.

The consensus process documented in [[RFC6576](#)] is that metric definitions should be the primary focus of evaluation rather than the implementations of metrics. Equivalent test results are deemed to be evidence that the metric specifications are clear and unambiguous. This is now the metric specification equivalent of protocol interoperability. The [[RFC6576](#)] advancement process either produces confidence that the metric definitions and supporting material are clearly worded and unambiguous, OR, identifies ways in which the metric definitions should be revised to achieve clarity.

The metric RFC advancement process requires documentation of the testing and results. [[RFC6576](#)] retains the testing requirement of the original standards track advancement process described in [[RFC2026](#)] and [[RFC5657](#)], because widespread deployment is insufficient to determine whether RFCs that define performance metrics result in consistent implementations.

The process also permits identification of options that were not implemented, so that they can be removed from the advancing specification (this is a similar aspect to protocol advancement along the standards track). All errata must also be considered.

This memo's purpose is to implement the advancement process of [[RFC6576](#)] for [[RFC2679](#)]. It supplies the documentation that accompanies the protocol action request submitted to the Area Director, including description of the test set-up, results for each implementation, evaluation of each metric specification, and



conclusions.

In particular, this memo documents the consensus on the extent of tolerable errors when assessing equivalence in the results. The IPPM working group agreed that the test plan and procedures should include the threshold for determining equivalence, and that this aspect should be decided in advance of cross-implementation comparisons. This memo includes procedures for same-implementation comparisons that may influence the equivalence threshold.

Although the conclusion reached through testing is that [\[RFC2679\]](#) should be advanced on the Standards Track with modifications, the revised text of RFC 2679bis is not yet ready for review. Therefore, this memo documents the information to support [\[RFC2679\]](#) advancement, and the approval of RFC2679bis is left for future action.

## **2. A Definition-centric metric advancement process**

The process described in [Section 3.5 of \[RFC6576\]](#) takes as a first principle that the metric definitions, embodied in the text of the RFCs, are the objects that require evaluation and possible revision in order to advance to the next step on the standards track. This memo follows that process.

## **3. Test configuration**



One metric implementation used was NetProbe version 5.8.5, (an earlier version is used in the AT&T's IP network performance measurement system and deployed world-wide [\[WIPM\]](#)). NetProbe uses UDP packets of variable size, and can produce test streams with Periodic [\[RFC3432\]](#) or Poisson [\[RFC2330\]](#) sample distributions.

The other metric implementation used was Perfas+ version 3.1, developed by Deutsche Telekom [\[Perfas\]](#). Perfas+ uses UDP unicast packets of variable size (but supports also TCP and multicast). Test streams with Periodic, Poisson or uniform sample distributions may be used.

Figure 2 shows a view of the test path as each Implementation's test flows pass through the Internet and the L2TPv3 tunnel IDs (1 and 2), based on Figures 2 and 3 of [\[RFC6576\]](#).







Illustrations of a test setup with a bi-directional tunnel. The upper diagram emphasizes the VLAN connectivity and geographical location. The lower diagram shows example flows traveling between two measurement implementations (for simplicity, only two flows are shown).

Figure 1

The testing employs the Layer 2 Tunnel Protocol, version 3 (L2TPv3) [[RFC3931](#)] tunnel between test sites on the Internet. The tunnel IP and L2TPv3 headers are intended to conceal the test equipment addresses and ports from hash functions that would tend to spread different test streams across parallel network resources, with likely variation in performance as a result.

At each end of the tunnel, one pair of VLANs encapsulated in the



tunnel are looped-back so that test traffic is returned to each test site. Thus, test streams traverse the L2TP tunnel twice, but appear to be one-way tests from the test equipment point of view.

The network emulator is a host running Fedora 14 Linux [[Fedora14](#)] with IP forwarding enabled and the "netem" Network emulator [[netem](#)] loaded and operating as part of the Fedora Kernel 2.6.35.11. Connectivity across the netem/Fedora host was accomplished by bridging Ethernet VLAN interfaces together with "brctl" commands (e.g., eth1.100 <-> eth2.100). The netem emulator was activated on one interface (eth1) and only operates on test streams traveling in one direction. In some tests, independent netem instances operated separately on each VLAN.

The links between the netem emulator host and router and switch were found to be 100baseTx-HD (100Mbps half duplex) when the testing was complete. Use of Half Duplex was not intended, but probably added a small amount of delay variation that could have been avoided in full duplex mode.

Each individual test was run with common packet rates (1 pps, 10pps) Poisson/Periodic distributions, and IP packet sizes of 64, 340, and 500 Bytes. These sizes cover a reasonable range while avoiding fragmentation and the complexities it causes, and thus complying with the notion of "standard formed packets" described in [Section 15 of RFC2330](#).

For these tests, a stream of at least 300 packets were sent from Source to Destination in each implementation. Periodic streams (as per [[RFC3432](#)]) with 1 second spacing were used, except as noted.

With the L2TPv3 tunnel in use, the metric name for the testing configured here (with respect to the IP header exposed to Internet processing) is:

Type-IP-protocol-115-One-way-Delay-<StreamType>-Stream

With ([Section 4.2. RFC2679](#)) Metric Parameters:

- + Src, the IP address of a host (12.3.167.16 or 193.159.144.8)
- + Dst, the IP address of a host (193.159.144.8 or 12.3.167.16)
- + T0, a time
- + Tf, a time
- + lambda, a rate in reciprocal seconds



+ Thresh, a maximum waiting time in seconds (see [Section 3.8.2 of \[RFC2679\]](#)) And ([Section 4.3. \[RFC2679\]](#))

Metric Units: A sequence of pairs; the elements of each pair are:

+ T, a time, and

+ dT, either a real number or an undefined number of seconds.

The values of T in the sequence are monotonic increasing. Note that T would be a valid parameter to Type-P-One-way-Delay, and that dT would be a valid value of Type-P-One-way-Delay.

Also, [Section 3.8.4 of \[RFC2679\]](#) recommends that the path SHOULD be reported. In this test set-up, most of the path details will be concealed from the implementations by the L2TPv3 tunnels, thus a more informative path trace route can be conducted by the routers at each location.

When NetProbe is used in production, a traceroute is conducted in parallel with, and at the outset of measurements.

Perfas+ does not support traceroute.



```
IPLGW#traceroute 193.159.144.8
```

```
Type escape sequence to abort.
```

```
Tracing the route to 193.159.144.8
```

```
 1 12.126.218.245 [AS 7018] 0 msec 0 msec 4 msec
 2 cr84.n54ny.ip.att.net (12.123.2.158) [AS 7018] 4 msec 4 msec
   cr83.n54ny.ip.att.net (12.123.2.26) [AS 7018] 4 msec
 3 cr1.n54ny.ip.att.net (12.122.105.49) [AS 7018] 4 msec
   cr2.n54ny.ip.att.net (12.122.115.93) [AS 7018] 0 msec
   cr1.n54ny.ip.att.net (12.122.105.49) [AS 7018] 0 msec
 4 n54ny02jt.ip.att.net (12.122.80.225) [AS 7018] 4 msec 0 msec
   n54ny02jt.ip.att.net (12.122.80.237) [AS 7018] 4 msec
 5 192.205.34.182 [AS 7018] 0 msec
   192.205.34.150 [AS 7018] 0 msec
   192.205.34.182 [AS 7018] 4 msec
 6 da-rg12-i.DA.DE.NET.DTAG.DE (62.154.1.30) [AS 3320] 88 msec 88 msec
88 msec
 7 217.89.29.62 [AS 3320] 88 msec 88 msec 88 msec
 8 217.89.29.55 [AS 3320] 88 msec 88 msec 88 msec
 9 * * *
```

It was only possible to conduct the traceroute for the measured path on one of the tunnel-head routers (the normal trace facilities of the measurement systems are confounded by the L2TPv3 tunnel encapsulation).

#### 4. Error Calibration, [RFC 2679](#)

An implementation is required to report on its error calibration in [Section 3.8 of \[RFC2679\]](#) (also required in [Section 4.8](#) for sample metrics). Sections [3.6](#), [3.7](#), and [3.8](#) of [\[RFC2679\]](#) give the detailed formulation of the errors and uncertainties for calibration. In summary, [Section 3.7.1 of \[RFC2679\]](#) describes the total time-varying uncertainty as:

$$\text{Esynch}(t) + R_{\text{source}} + R_{\text{dest}}$$

where:

$\text{Esynch}(t)$  denotes an upper bound on the magnitude of clock synchronization uncertainty.

$R_{\text{source}}$  and  $R_{\text{dest}}$  denote the resolution of the source clock and the destination clock, respectively.

Further, [Section 3.7.2 of \[RFC2679\]](#) describes the total wire-time





uncertainty as

$H_{source} + H_{dest}$

referring to the upper bounds on host-time to wire-time for source and destination, respectively.

[Section 3.7.3 of \[RFC2679\]](#) describes a test with small packets over an isolated minimal network where the results can be used to estimate systematic and random components of the sum of the above errors or uncertainties. In a test with hundreds of singletons, the median is the systematic error and when the median is subtracted from all singletons, the remaining variability is the random error.

The test context, or Type-P of the test packets, must also be reported, as required in [Section 3.8 of \[RFC2679\]](#) and all metrics defined there. Type-P is defined in [Section 13 of \[RFC2330\]](#) (as are many terms used below).

#### **[4.1.](#) NetProbe Error and Type-P**

Type-P for this test was IP-UDP with Best Effort DSCP. These headers were encapsulated according to the L2TPv3 specifications [\[RFC3931\]](#), and thus may not influence the treatment received as the packets traversed the Internet.

In general, NetProbe error is dependent on the specific version and installation details.

NetProbe operates using host time above the UDP layer, which is different from the wire-time preferred in [\[RFC2330\]](#), but can be identified as a source of error according to [Section 3.7.2 of \[RFC2679\]](#).

Accuracy of NetProbe measurements is usually limited by NTP synchronization performance (which is typically taken as  $\sim \pm 1\text{ms}$  error or greater), although the installation used in this testing often exhibits errors much less than typical for NTP. The primary stratum 1 NTP server is closely located on a sparsely utilized network management LAN, thus it avoids many concerns raised in [Section 10 of \[RFC2330\]](#) (in fact, smooth adjustment, long-term drift analysis and compensation, and infrequent adjustment all lead to stability during measurement intervals, the main concern).

The resolution of the reported results is  $1\mu\text{s}$  ( $\mu\text{s}$  = microsecond) in the version of NetProbe tested here, which contributes to at least  $\pm 1\mu\text{s}$  error.



NetProbe implements a time-keeping sanity check on sending and receiving time-stamping processes. When the significant process interruption takes place, individual test packets are flagged as possibly containing unusual time errors, and are excluded from the sample used for all "time" metrics.

We performed a NetProbe calibration of the type described in [Section 3.7.3 of \[RFC2679\]](#), using 64 Byte packets over a cross-connect cable. The results estimate systematic and random components of the sum of the Hsource + Hdest errors or uncertainties. In a test with 300 singletons conducted over 30 seconds (periodic sample with 100ms spacing), the median is the systematic error and the remaining variability is the random error. One set of results is tabulated below:

(Results from the "R" software environment for statistical computing and graphics - <http://www.r-project.org/> )

```
> summary(XD4CAL)
```

CAL1		CAL2		CAL3	
Min.	: 89.0	Min.	: 68.00	Min.	: 54.00
1st Qu.:	99.0	1st Qu.:	77.00	1st Qu.:	63.00
Median :	110.0	Median :	79.00	Median :	65.00
Mean	:116.8	Mean	: 83.74	Mean	: 69.65
3rd Qu.:	127.0	3rd Qu.:	88.00	3rd Qu.:	74.00
Max.	:205.0	Max.	:177.00	Max.	:163.00

```
>
```

NetProbe Calibration with Cross-Connect Cable, one-way delay values in microseconds (us)

The median or systematic error can be as high as 110 us, and the range of the random error is also on the order of 116 us for all streams.

Also, anticipating the Anderson-Darling K-sample (ADK) [\[ADK\]](#) comparisons to follow, we corrected the CAL2 values for the difference between means between CAL2 and CAL3 (as specified in [\[RFC6576\]](#)), and found strong support for the (Null Hypothesis that) the samples are from the same distribution (resolution of 1 us and alpha equal 0.05 and 0.01)



```
> XD4CVCAL2 <- XD4CAL$CAL2 - (mean(XD4CAL$CAL2)-mean(XD4CAL$CAL3))
> boxplot(XD4CVCAL2,XD4CAL$CAL3)
> XD4CV2_ADK <- adk.test(XD4CVCAL2, XD4CAL$CAL3)
> XD4CV2_ADK
```

Anderson-Darling k-sample test.

```
Number of samples: 2
Sample sizes: 300 300
Total number of values: 600
Number of unique values: 97
```

```
Mean of Anderson Darling Criterion: 1
Standard deviation of Anderson Darling Criterion: 0.75896
```

$T = (\text{Anderson Darling Criterion} - \text{mean})/\text{sigma}$

Null Hypothesis: All samples come from a common population.

```

                t.obs P-value extrapolation
not adj. for ties 0.71734 0.17042          0
adj. for ties    -0.39553 0.44589          1
>
using [Rtool] and [Radk].
```

#### **[4.2.](#) Perfas+ Error and Type-P**

Perfas+ is configured to use GPS synchronisation and uses NTP synchronization as a fall-back or default. GPS synchronisation worked throughout this test with the exception of the calibration stated here (one implementation was NTP synchronised only). The time stamp accuracy typically is 0.1 ms.

The resolution of the results reported by Perfas+ is 1us (us = microsecond) in the version tested here, which contributes to at least +/-1us error.

```
Port    5001 5002 5003
Min.    -227 -226 294
Median  -169 -167 323
Mean    -159 -157 335
Max.      6  -52 376
s       102 102 93
```

Perfas+ Calibration with Cross-Connect Cable, one-way delay values in microseconds (us)

The median or systematic error can be as high as 323 us, and the range of the random error is also less than 232 us for all streams.



## **5. Pre-determined Limits on Equivalence**

This section provides the numerical limits on comparisons between implementations, in order to declare that the results are equivalent and therefore, the tested specification is clear. These limits have their basis in [Section 3.1 of \[RFC6576\]](#) and the Appendix of [\[RFC2330\]](#), with additional limits representing IPPM consensus prior to publication of results.

A key point is that the allowable errors, corrections, and confidence levels only need to be sufficient to detect mis-interpretation of the tested specification resulting in diverging implementations.

Also, the allowable error must be sufficient to compensate for measured path differences. It was simply not possible to measure fully identical paths in the VLAN-loopback test configuration used, and this practical compromise must be taken into account.

For Anderson-Darling K-sample (ADK) comparisons, the required confidence factor for the cross-implementation comparisons SHALL be the smallest of:

- o 0.95 confidence factor at 1ms resolution, or
- o the smallest confidence factor (in combination with resolution) of the two same-implementation comparisons for the same test conditions.

A constant time accuracy error of as much as +/-0.5ms MAY be removed from one implementation's distributions (all singletons) before the ADK comparison is conducted.

A constant propagation delay error (due to use of different sub-nets between the switch and measurement devices at each location) of as much as +2ms MAY be removed from one implementation's distributions (all singletons) before the ADK comparison is conducted.

For comparisons involving the mean of a sample or other central statistics, the limits on both the time accuracy error and the propagation delay error constants given above also apply.

## **6. Tests to evaluate [RFC 2679](#) Specifications**

This section describes some results from real-world (cross-Internet) tests with measurement devices implementing IPPM metrics and a network emulator to create relevant conditions, to determine whether the metric definitions were interpreted consistently by implementors.





The procedures are slightly modified from the original procedures contained in [Appendix A.1 of \[RFC6576\]](#). The modifications include the use of the mean statistic for comparisons.

Note that there are only five instances of the requirement term "MUST" in [\[RFC2679\]](#) outside of the boilerplate and [\[RFC2119\]](#) reference.

### **6.1. One-way Delay, ADK Sample Comparison - Same & Cross Implementation**

This test determines if implementations produce results that appear to come from a common delay distribution, as an overall evaluation of [Section 4 of \[RFC2679\]](#), "A Definition for Samples of One-way Delay". Same-implementation comparison results help to set the threshold of equivalence that will be applied to cross-implementation comparisons.

This test is intended to evaluate measurements in sections [3](#) and [4](#) of [\[RFC2679\]](#).

By testing the extent to which the distributions of one-way delay singletons from two implementations of [\[RFC2679\]](#) appear to be from the same distribution, we economize on comparisons, because comparing a set of individual summary statistics (as defined in [Section 5 of \[RFC2679\]](#)) would require another set of individual evaluations of equivalence. Instead, we can simply check which statistics were implemented, and report on those facts.

1. Configure an L2TPv3 path between test sites, and each pair of measurement devices to operate tests in their designated pair of VLANs.
2. Measure a sample of one-way delay singletons with 2 or more implementations, using identical options and network emulator settings (if used).
3. Measure a sample of one-way delay singletons with \*four\* instances of the \*same\* implementations, using identical options, noting that connectivity differences SHOULD be the same as for the cross implementation testing.
4. Apply the ADK comparison procedures (see [Appendix C of \[RFC6576\]](#)) and determine the resolution and confidence factor for distribution equivalence of each same-implementation comparison and each cross-implementation comparison.
5. Take the coarsest resolution and confidence factor for distribution equivalence from the same-implementation pairs, or the limit defined in [Section 5](#) above, as a limit on the



equivalence threshold for these experimental conditions.

6. Apply constant correction factors to all singletons of the sample distributions, as described and limited in [Section 5](#) above.
7. Compare the cross-implementation ADK performance with the equivalence threshold determined in step 5 to determine if equivalence can be declared.

The common parameters used for tests in this section are:

- o IP header + payload = 64 octets
- o Periodic sampling at 1 packet per second
- o Test duration = 300 seconds (March 29, 2011)

The netem emulator was set for 100ms average delay, with uniform delay variation of +/-50ms. In this experiment, the netem emulator was configured to operate independently on each VLAN and thus the emulator itself is a potential source of error when comparing streams that traverse the test path in different directions.

In the result analysis of this section:

- o All comparisons used 1 microsecond resolution.
- o No Correction Factors were applied.
- o The 0.95 confidence factor (1.960 for paired stream comparison) was used.

#### **[6.1.1.1.](#) NetProbe Same-implementation results**

A single same-implementation comparison fails the ADK criterion (s1 <-> sB). We note that these streams traversed the test path in opposite directions, making the live network factors a possibility to explain the difference.

All other pair comparisons pass the ADK criterion.



ti.obs (P)	s1	s2	sA
s2	0.25 (0.28)		
sA	0.60 (0.19)	-0.80 (0.57)	
sB	2.64 (0.03)	0.07 (0.31)	-0.52 (0.48)

NetProbe ADK Results for same-implementation

#### [6.1.2.](#) Perfas+ Same-implementation results

All pair comparisons pass the ADK criterion.

ti.obs (P)	p1	p2	p3
p2	0.06 (0.32)		
p3	1.09 (0.12)	0.37 (0.24)	
p4	-0.81 (0.57)	-0.13 (0.37)	1.36 (0.09)

Perfas+ ADK Results for same-implementation



**6.1.3. One-way Delay, Cross-Implementation ADK Comparison**

The cross-implementation results are compared using a combined ADK analysis [[Radk](#)], where all NetProbe results are compared with all Perfas+ results after testing that the combined same-implementation results pass the ADK criterion.

When 4 (same) samples are compared, the ADK criterion for 0.95 confidence is 1.915, and when all 8 (cross) samples are compared it is 1.85.

Combination of Anderson-Darling K-Sample Tests.

Sample sizes within each data set:

Data set 1 : 299 297 298 300 (NetProbe)

Data set 2 : 300 300 298 300 (Perfas+)

Total sample size per data set: 1194 1198

Number of unique values per data set: 1188 1192

...

Null Hypothesis:

All samples within a data set come from a common distribution.

The common distribution may change between data sets.

NetProbe	ti.obs	P-value	extrapolation
not adj. for ties	0.64999	0.21355	0
adj. for ties	0.64833	0.21392	0
Perfas+			
not adj. for ties	0.55968	0.23442	0
adj. for ties	0.55840	0.23473	0

Combined Anderson-Darling Criterion:

	tc.obs	P-value	extrapolation
not adj. for ties	0.85537	0.17967	0
adj. for ties	0.85329	0.18010	0

The combined same-implementation samples and the combined cross-implementation comparison all pass the ADK criteria at  $P \geq 0.18$  and support the Null Hypothesis (both data sets come from a common distribution).

We also see that the paired ADK comparisons are rather critical. Although the NetProbe s1-sB comparison failed, the combined data set from 4 streams passed the ADK criterion easily.

**6.1.4. Conclusions on the ADK Results for One-way Delay**

Similar testing was repeated many times in the months of March and April 2011. There were many experiments where a single test stream





from NetProbe or Perfas+ proved to be different from the others in paired comparisons (even same implementation comparisons). When the outlier stream was removed from the comparison, the remaining streams passed combined ADK criterion. Also, the application of correction factors resulted in higher comparison success.

We conclude that the two implementations are capable of producing equivalent one-way delay distributions based on their interpretation of [[RFC2679](#)].

#### **[6.1.5](#). Additional Investigations**

On the final day of testing, we performed a series of measurements to evaluate the amount of emulated delay variation necessary to achieve successful ADK comparisons. The need for Correction factors (as permitted by [Section 5](#)) and the size of the measurement sample (obtained as sub-sets of the complete measurement sample) were also evaluated.

The common parameters used for tests in this section are:

- o IP header + payload = 64 octets
- o Periodic sampling at 1 packet per second
- o Test duration = 300 seconds at each delay variation setting, for a total of 1200 seconds (May 2, 2011 at 1720 UTC)

The netem emulator was set for 100ms average delay, with (emulated) uniform delay variation of:

- o +/-7.5 ms
- o +/-5.0 ms
- o +/-2.5 ms
- o 0 ms

In this experiment, the netem emulator was configured to operate independently on each VLAN and thus the emulator itself is a potential source of error when comparing streams that traverse the test path in different directions.

In the result analysis of this section:



- o All comparisons used 1 microsecond resolution.
- o Correction Factors *were* applied as noted (under column heading "mean adj"). The difference between each sample mean and the lowest mean of the NetProbe or Perfas+ stream samples was subtracted from all values in the sample. ("raw" indicates no correction factors were used.) All correction factors applied met the limits described in [Section 5](#).
- o The 0.95 confidence factor (1.960 for paired stream comparison) was used.

When 8 (cross) samples are compared, the ADK criterion for 0.95 confidence is 1.85. The Combined ADK test statistic ("TC observed") must be less than 1.85 to accept the Null Hypothesis (all samples in the data set are from a common distribution).



Emulated Delay		Sub-Sample size			
Variation	0ms				
adk.combined (all)		300 values		75 values	
Adj. for ties		raw	mean adj	raw	mean adj
TC observed		226.6563	67.51559	54.01359	21.56513
P-value		0	0	0	0
Mean std dev (all),us		719		635	
Mean diff of means,us		649	0	606	0
Variation +/- 2.5ms					
adk.combined (all)		300 values		75 values	
Adj. for ties		raw	mean adj	raw	mean adj
TC observed		14.50436	-1.60196	3.15935	-1.72104
P-value		0	0.873	0.00799	0.89038
Mean std dev (all),us		1655		1702	
Mean diff of means,us		471	0	513	0
Variation +/- 5ms					
adk.combined (all)		300 values		75 values	
Adj. for ties		raw	mean adj	raw	mean adj
TC observed		8.29921	-1.28927	0.37878	-1.81881
P-value		0	0.81601	0.29984	0.90305
Mean std dev (all),us		3023		2991	
Mean diff of means,us		582	0	513	0
Variation +/- 7.5ms					
adk.combined (all)		300 values		75 values	
Adj. for ties		raw	mean adj	raw	mean adj
TC observed		2.53759	-0.72985	0.29241	-1.15840
P-value		0.01950	0.66942	0.32585	0.78686
Mean std dev (all),us		4449		4506	
Mean diff of means,us		426	0	856	0

From the table above, we conclude the following:

1. None of the raw or mean adjusted results pass the ADK criterion with 0 ms emulated delay variation. Use of the 75 value sub-sample yielded the same conclusion. (We note the same results when comparing same implementation samples for both NetProbe and Perf+.)
2. When the smallest emulated delay variation was inserted (+/-2.5ms), the mean adjusted samples pass the ADK criterion and the high P-value supports the result. The raw results do not pass.



3. At higher values of emulated delay variation ( $\pm 5.0\text{ms}$  and  $\pm 7.5\text{ms}$ ), again the mean adjusted values pass ADK. We also see that the 75-value sub-sample passed the ADK in both raw and mean adjusted cases. This indicates that sample size may have played a role in our results, as noted in the Appendix of [[RFC2680](#)] for Goodness-of-Fit testing.

We note that 150 value sub-samples were also evaluated, with ADK conclusions that followed the results for 300 values. Also, same-implementation analysis was conducted with results similar to the above, except that more of the "raw" or uncorrected samples passed the ADK criterion.

## **6.2. One-way Delay, Loss threshold, [RFC 2679](#)**

This test determines if implementations use the same configured maximum waiting time delay from one measurement to another under different delay conditions, and correctly declare packets arriving in excess of the waiting time threshold as lost.

See [Section 3.5 of \[RFC2679\]](#), 3rd bullet point and also [Section 3.8.2 of \[RFC2679\]](#).

1. configure an L2TPv3 path between test sites, and each pair of measurement devices to operate tests in their designated pair of VLANs.
2. configure the network emulator to add 1.0 sec one-way constant delay in one direction of transmission.
3. measure (average) one-way delay with 2 or more implementations, using identical waiting time thresholds (Thresh) for loss set at 3 seconds.
4. configure the network emulator to add 3 sec one-way constant delay in one direction of transmission equivalent to 2 seconds of additional one-way delay (or change the path delay while test is in progress, when there are sufficient packets at the first delay setting)
5. repeat/continue measurements
6. observe that the increase measured in step 5 caused all packets with 2 sec additional delay to be declared lost, and that all packets that arrive successfully in step 3 are assigned a valid one-way delay.

The common parameters used for tests in this section are:





- o IP header + payload = 64 octets
- o Poisson sampling at  $\lambda = 1$  packet per second
- o Test duration = 900 seconds total (March 21, 2011)

The netem emulator was set to add constant delays as specified in the procedure above.

#### **[6.2.1.](#) NetProbe results for Loss Threshold**

In NetProbe, the Loss Threshold is implemented uniformly over all packets as a post-processing routine. With the Loss Threshold set at 3 seconds, all packets with one-way delay >3 seconds are marked "Lost" and included in the Lost Packet list with their transmission time (as required in [Section 3.3 of \[RFC2680\]](#)). This resulted in 342 packets designated as lost in one of the test streams (with average delay = 3.091 sec).

#### **[6.2.2.](#) Perfas+ Results for Loss Threshold**

Perfas+ uses a fixed Loss Threshold which was not adjustable during this study. The Loss Threshold is approximately one minute, and emulation of a delay of this size was not attempted. However, it is possible to implement any delay threshold desired with a post-processing routine and subsequent analysis. Using this method, 195 packets would be declared lost (with average delay = 3.091 sec).

#### **[6.2.3.](#) Conclusions for Loss Threshold**

Both implementations assume that any constant delay value desired can be used as the Loss Threshold, since all delays are stored as a pair <Time, Delay> as required in [\[RFC2679\]](#). This is a simple way to enforce the constant loss threshold envisioned in [\[RFC2679\]](#) (see specific section references above). We take the position that the assumption of post-processing is compliant, and that the text of the RFC should be revised slightly to include this point.

#### **[6.3.](#) One-way Delay, First-bit to Last bit, [RFC 2679](#)**

This test determines if implementations register the same relative change in delay from one packet size to another, indicating that the first-to-last time-stamping convention has been followed. This test tends to cancel the sources of error which may be present in an implementation.

See [Section 3.7.2 of \[RFC2679\]](#), and [Section 10.2 of \[RFC2330\]](#).



1. configure an L2TPv3 path between test sites, and each pair of measurement devices to operate tests in their designated pair of VLANs, and ideally including a low-speed link (it was not possible to change the link configuration during testing, so the lowest speed link present was the basis for serialization time comparisons).
2. measure (average) one-way delay with 2 or more implementations, using identical options and equal size small packets (64 octet IP header and payload)
3. maintain the same path with additional emulated 100 ms one-way delay
4. measure (average) one-way delay with 2 or more implementations, using identical options and equal size large packets (500 octet IP header and payload)
5. observe that the increase measured between steps 2 and 4 is equivalent to the increase in ms expected due to the larger serialization time for each implementation. Most of the measurement errors in each system should cancel, if they are stationary.

The common parameters used for tests in this section are:

- o IP header + payload = 64 octets
- o Periodic sampling at 1 packet per second
- o Test duration = 300 seconds total (April 12)

The netem emulator was set to add constant 100ms delay.

#### **[6.3.1.](#) NetProbe and Perfas+ Results for Serialization**

When the IP header + payload size was increased from 64 octets to 500 octets, there was a delay increase observed.



Mean Delays in us

NetProbe

Payload	s1	s2	sA	sB
500	190893	191179	190892	190971
64	189642	189785	189747	189467
Diff	1251	1394	1145	1505

Perfas

Payload	p1	p2	p3	p4
500	190908	190911	191126	190709
64	189706	189752	189763	190220
Diff	1202	1159	1363	489

Serialization tests, all values in microseconds

The typical delay increase when the larger packets were used was 1.1 to 1.5 ms (with one outlier). The typical measurements indicate that a link with approximately 3 Mbit/s capacity is present on the path.

Through investigation of the facilities involved, it was determined that the lowest speed link was approximately 45 Mbit/s, and therefore the estimated difference should be about 0.077 ms. The observed differences are much higher.

The unexpected large delay difference was also the outcome when testing serialization times in a lab environment, using the NIST Net Emulator and NetProbe [[I-D.morton-ippm-advance-metrics](#)].

### **[6.3.2.](#) Conclusions for Serialization**

Since it was not possible to confirm the estimated serialization time increases in field tests, we resort to examination of the implementations to determine compliance.

NetProbe performs all time stamping above the IP-layer, accepting that some compromises must be made to achieve extreme portability and measurement scale. Therefore, the first-to-last bit convention is supported because the serialization time is included in the one-way delay measurement, enabling comparison with other implementations.

Perfas+ is optimized for its purpose and performs all time stamping close to the interface hardware. The first-to-last bit convention is supported because the serialization time is included in the one-way delay measurement, enabling comparison with other implementations.



#### **[6.4.](#) One-way Delay, Difference Sample Metric (Lab)**

This test determines if implementations register the same relative increase in delay from one measurement to another under different delay conditions. This test tends to cancel the sources of error which may be present in an implementation.

This test is intended to evaluate measurements in sections [3](#) and [4](#) of [[RFC2679](#)].

1. configure an L2TPv3 path between test sites, and each pair of measurement devices to operate tests in their designated pair of VLANs.
2. measure (average) one-way delay with 2 or more implementations, using identical options
3. configure the path with X+Y ms one-way delay
4. repeat measurements
5. observe that the (average) increase measured in steps 2 and 4 is ~Y ms for each implementation. Most of the measurement errors in each system should cancel, if they are stationary.

In this test, X=1000ms and Y=1000ms.

The common parameters used for tests in this section are:

- o IP header + payload = 64 octets
- o Poisson sampling at  $\lambda = 1$  packet per second
- o Test duration = 900 seconds total (March 21, 2011)

The netem emulator was set to add constant delays as specified in the procedure above.

##### **[6.4.1.](#) NetProbe results for Differential Delay**

Average pre-increase delay, microseconds	1089868.0
Average post 1s additional, microseconds	2089686.0
Difference (should be $\approx Y = 1s$ )	999818.0

Average delays before/after 1 second increase

The NetProbe implementation observed a 1 second increase with a 182 microsecond error (assuming that the netem emulated delay difference





is exact).

We note that this differential delay test has been run under lab conditions and published in prior work [[I-D.morton-ippm-advance-metrics](#)]. The error was 6 microseconds.

#### **[6.4.2.](#) Perfas+ results for Differential Delay**

Average pre-increase delay, microseconds	1089794.0
Average post 1s additional, microseconds	2089801.0
Difference (should be $\approx Y = 1s$ )	1000007.0

Average delays before/after 1 second increase

The Perfas+ implementation observed a 1 second increase with a 7 microsecond error.

#### **[6.4.3.](#) Conclusions for Differential Delay**

Again, the live network conditions appear to have influenced the results, but both implementations measured the same delay increase within their calibration accuracy.

#### **[6.5.](#) Implementation of Statistics for One-way Delay**

The ADK tests the extent to which the sample distributions of one-way delay singletons from two implementations of [[RFC2679](#)] appear to be from the same overall distribution. By testing this way, we economize on the number of comparisons, because comparing a set of individual summary statistics (as defined in [Section 5 of \[RFC2679\]](#)) would require another set of individual evaluations of equivalence. Instead, we can simply check which statistics were implemented, and report on those facts, noting that [Section 5 of \[RFC2679\]](#) does not specify the calculations exactly, and gives only some illustrative examples.



	NetProbe	Perfas+
5.1. Type-P-One-way-Delay-Percentile	yes	no
5.2. Type-P-One-way-Delay-Median	yes	no
5.3. Type-P-One-way-Delay-Minimum	yes	yes
5.4. Type-P-One-way-Delay-Inverse-Percentile	no	no

#### Implementation of [Section 5](#) Statistics

Only the Type-P-One-way-Delay-Inverse-Percentile has been ignored in both implementations, so it is a candidate for removal or deprecation in RFC2679bis (this small discrepancy does not affect candidacy for advancement).

## **7. Conclusions and [RFC 2679](#) Errata**

The conclusions throughout [Section 6](#) support the advancement of [\[RFC2679\]](#) to the next step of the standards track, because its requirements are deemed to be clear and unambiguous based on evaluation of the test results for two implementations. The results indicate that these implementations produced statistically equivalent results under network conditions that were configured to be as close to identical as possible.

Sections [6.2.3](#) and [6.5](#) indicate areas where minor revisions are warranted in RFC2679bis. The IETF has reached consensus on guidance for reporting metrics in [\[RFC6703\]](#), and this memo should be referenced in RFC2679bis to incorporate recent experience where appropriate.

We note that there is currently one erratum with status "Held for document update" for [\[RFC2679\]](#), and it appears this minor revision and additional text should be incorporated in RFC2679bis.

## **8. Security Considerations**

The security considerations that apply to any active measurement of live networks are relevant here as well. See [\[RFC4656\]](#) and [\[RFC5357\]](#).



## **9. IANA Considerations**

This memo makes no requests of IANA, and hopes that IANA will welcome our new computer overlords as willingly as the authors.

## **10. Acknowledgements**

The authors thank Lars Eggert for his continued encouragement to advance the IPPM metrics during his tenure as AD Advisor.

Nicole Kowalski supplied the needed CPE router for the NetProbe side of the test set-up, and graciously managed her testing in spite of issues caused by dual-use of the router. Thanks Nicole!

The "NetProbe Team" also acknowledges many useful discussions with Ganga Maguluri.

## **11. References**

### **11.1. Normative References**

- [RFC2026] Bradner, S., "The Internet Standards Process -- Revision 3", [BCP 9](#), [RFC 2026](#), October 1996.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC2330] Paxson, V., Almes, G., Mahdavi, J., and M. Mathis, "Framework for IP Performance Metrics", [RFC 2330](#), May 1998.
- [RFC2679] Almes, G., Kalidindi, S., and M. Zekauskas, "A One-way Delay Metric for IPPM", [RFC 2679](#), September 1999.
- [RFC2680] Almes, G., Kalidindi, S., and M. Zekauskas, "A One-way Packet Loss Metric for IPPM", [RFC 2680](#), September 1999.
- [RFC3432] Raisanen, V., Grotefeld, G., and A. Morton, "Network performance measurement with periodic streams", [RFC 3432](#), November 2002.
- [RFC4656] Shalunov, S., Teitelbaum, B., Karp, A., Boote, J., and M. Zekauskas, "A One-way Active Measurement Protocol (OWAMP)", [RFC 4656](#), September 2006.
- [RFC5357] Hedayat, K., Krzanowski, R., Morton, A., Yum, K., and J.



Babiarz, "A Two-Way Active Measurement Protocol (TWAMP)", [RFC 5357](#), October 2008.

- [RFC5657] Dusseault, L. and R. Sparks, "Guidance on Interoperation and Implementation Reports for Advancement to Draft Standard", [BCP 9](#), [RFC 5657](#), September 2009.
- [RFC6576] Geib, R., Morton, A., Fardid, R., and A. Steinmitz, "IP Performance Metrics (IPPM) Standard Advancement Testing", [BCP 176](#), [RFC 6576](#), March 2012.
- [RFC6703] Morton, A., Ramachandran, G., and G. Maguluri, "Reporting IP Network Performance Metrics: Different Points of View", [RFC 6703](#), August 2012.

### **11.2. Informative References**

- [ADK] Scholz, F. and M. Stephens, "K-sample Anderson-Darling Tests of fit, for continuous and discrete cases", University of Washington, Technical Report No. 81, May 1986.
- [Fedora14] "Fedora Project Home Page", <http://fedoraproject.org/>, 2012.
- [I-D.bradner-metricstest] Bradner, S. and V. Paxson, "Advancement of metrics specifications on the IETF Standards Track", [draft-bradner-metricstest-03](#) (work in progress), August 2007.
- [I-D.morton-ippm-advance-metrics] Morton, A., "Lab Test Results for Advancing Metrics on the Standards Track", [draft-morton-ippm-advance-metrics-02](#) (work in progress), October 2010.
- [Perfas] Heidemann, C., "Qualitaet in IP-Netzen Messverfahren", published by ITG Fachgruppe, 2nd meeting 5.2.3 (NGN) [http://www.itg523.de/oeffentlich/01nov/Heidemann\\_QOS\\_Messverfahren.pdf](http://www.itg523.de/oeffentlich/01nov/Heidemann_QOS_Messverfahren.pdf) , November 2001.
- [RFC3931] Lau, J., Townsley, M., and I. Goyret, "Layer Two Tunneling Protocol - Version 3 (L2TPv3)", [RFC 3931](#), March 2005.
- [Radk] Scholz, F., "adk: Anderson-Darling K-Sample Test and Combinations of Such Tests. R package version 1.0.", , 2008.





- [Rtool] R Development Core Team, "R: A language and environment for statistical computing. R Foundation for Statistical Computing, Vienna, Austria. ISBN 3-900051-07-0, URL <http://www.R-project.org/>", , 2011.
- [WIPM] "AT&T Global IP Network", <http://ipnetwork.bgtmo.ip.att.net/pws/index.html>, 2012.
- [netem] ""netem" Documentation", <http://www.linuxfoundation.org/collaborate/workgroups/networking/netem>, 2009.

## Authors' Addresses

Len Ciavattone  
AT&T Labs  
200 Laurel Avenue South  
Middletown, NJ 07748  
USA

Phone: +1 732 420 1239  
Fax:  
Email: [lencia@att.com](mailto:lencia@att.com)  
URI:

Ruediger Geib  
Deutsche Telekom  
Heinrich Hertz Str. 3-7  
Darmstadt, 64295  
Germany

Phone: +49 6151 58 12747  
Email: [Ruediger.Geib@telekom.de](mailto:Ruediger.Geib@telekom.de)

Al Morton  
AT&T Labs  
200 Laurel Avenue South  
Middletown, NJ 07748  
USA

Phone: +1 732 420 1571  
Fax: +1 732 368 1192  
Email: [acmorton@att.com](mailto:acmorton@att.com)  
URI: <http://home.comcast.net/~acmacm/>



Matthias Wieser  
Technical University Darmstadt  
Darmstadt,  
Germany

Phone:

Email: [matthias\\_michael.wieser@stud.tu-darmstadt.de](mailto:matthias_michael.wieser@stud.tu-darmstadt.de)