

IPS
Internet Draft
Document: [draft-ietf-ips-iscsi-boot-00.txt](#)
Category: Standards Track

Prasenjit Sarkar
IBM
Duncan Missimer
HP
Constantin Sapuntzakis
Cisco
17 November 2000

A Standard for BootStrapping Clients using the iSCSI Protocol

Status of this Memo

This document is an Internet-Draft and is in full conformance with all provisions of [Section 10 of RFC2026](#) [[11](#)].

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts. Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or made obsolete by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress." The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/1id-abstracts.txt> The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

Abstract

The Small Computer Systems Interface (SCSI) is a popular family of protocols for communicating with I/O devices, especially storage devices. iSCSI is a proposed transport protocol for SCSI that operates on top of TCP[12]. This memo describes a standard mechanism to enable clients to bootstrap themselves using the iSCSI protocol. The goal of this standard is to enable clients to obtain the information to open an iSCSI session with the iSCSI bootstrapping server, assuming this information is not available.

1. Requirements

1. There must be no restriction of network topology between the iSCSI boot client and the boot server. Consequently, it is possible for an iSCSI boot client to boot from an iSCSI boot server behind gateways/firewalls/etc as long as it is possible to establish an iSCSI session between the client and the server.
2. The following represents the minimum information required for an

iSCSI boot client to contact an iSCSI boot server: (a) the client's IP address (IPv6 or IPv4) and (b) the server's iSCSI Service Delivery Port Name.

The above assumes that the default LUN for the boot process is 0 and the default port for the iSCSI boot server is the well-known iSCSI port. However, both can be overridden at the time of configuration.

Additional information may be required at each stage of the boot process.

3. It is possible for the iSCSI boot client to have none of the above information when the boot client software is started.

4. The client should be able to complete boot without user intervention (for boots that occur during an unattended power-up). However, there should be a mechanism for the user to input values so as to bypass stages of the boot protocol.

5. Additional protocol software (for example, DHCP) may be necessary if the minimum information required for an iSCSI session is not provided.

2. Related Work

The Reverse Address Resolution Protocol (RARP) [7] (through the extensions defined in the Dynamic RARP (DRARP)) [4] explicitly addresses the problem of network address discovery, and includes an automatic IP address assignment mechanism. The Trivial File Transfer Protocol (TFTP) [9] provides for transport of a boot image from a boot server. BOOTP [5,8,10] is a transport mechanism for a collection of configuration information. BOOTP is also extensible, and official extensions have been defined for several configuration parameters. DHCPv4 [3,6] and DHCPv6 [13] are standards for hosts to be dynamically configured in an IP network. The Resource Location Protocol RLP provides for location of higher level services [1].

3. DHCP stage

In order to use an iSCSI boot server, the following pieces of information are required.

- The IP address of the iSCSI boot client (IPv4 or IPv6)

- The IP transport endpoint for the iSCSI service delivery port for the iSCSI boot server. If the transport is TCP, for example, this has to resolve to an IP address and a TCP port number.

- The eight-byte LUN structure identifying the device within the iSCSI boot server (see [section 4.12.2](#) of SAM-2 17 Sept 2000)

At boot time, all or none of this information may be stored in the firmware of the iSCSI boot client. This section describes techniques for obtaining the required information.

An iSCSI boot client which does not know its IP address at power-on may acquire its IP address via DHCP. An iSCSI boot client which is capable of using both DHCPv6 and DHCPv4 should first attempt to use DHCPv6 to obtain its IP address, falling back on DHCPv4 in the event of failure.

Unless otherwise specified here, DHCP fields such as the client ID and gateway information are used identically with applications other than iSCSI.

A DHCPv4 or BOOTP server may instruct an iSCSI client how to reach its boot device. The servers use the "file" field of the BOOTP/DHCPV4 header to instruct the iSCSI client of which boot server to connect to and how to do so. The format of the "file" field is:

```
"iscsi:" <servername> ":" <port> ":" <LUN> ":" <targetname>
```

The "file" field begins with literal UTF-8 string "iscsi:" to instruct the client to use iSCSI/TCP (as opposed to NFS or some other mechanism) to boot.

The fields "port", "LUN" and "targetname" are optional and should be left blank if there are no values corresponding to the fields.

The "servername" is the name of iSCSI server and contains either a domain name, a literal IPv4 address, or a bracketed literal IPv6 address. If the servername field contains a domain name, the domain name must comply with the restrictions in [section 3 of RFC1034](#) and [section 2.1 of RFC1123](#). If the servername field contains a literal

IPv4 address, the IPv4 address is in standard dotted decimal notation. If the servername field contains an IPv6 address, the address is represented in bracketed literal IPv6 address format as specified in RFCs 2373 and 2732.

If the "servername" is a domain name, then the reply from the host configuration server MAY contain the Domain Name Server Option described in [section 3.8 of RFC 2132](#).

The "port" is the decimal representation of the port on which the iSCSI server is listening. If not specified, the port defaults to the well-known iSCSI port.

The "LUN" field is 16 UTF-8 bytes representing the 8-byte LU number in hex. Digits above 9 may be either lower or upper case, and all 16 nibbles must be present. The LUN field is blank, then LUN 0 is assumed.

Note that SCSI targets are allowed to present different LU numberings for different SCSI initiators, so that to our knowledge nothing precludes a SCSI target from exporting several different devices to several different SCSI initiators as their respective LU 0s.

The "targetname" field is a UTF-8 ([\[RFC2279\]](#)) string containing the name of the iSCSI target, the details of which are specified by the iSCSI standard[12]. If the targetname is provided, the iSCSI boot client may use the targetname as mandated by the iSCSI standard.

In the case of a DHCPv6 server, a proposed extension for iSCSI boot information would provide the information returned in the "file" field by a DHCPv4 server. The interpretation of the information will be identical in both DHCPv4 and DHCPv6. The proposed extension would be obtained as per the rules stated in [RFC 2939](#).

If the iSCSI working group registers an extension for iSCSI boot information which may be used by both DHCPv4 and DHCPv6, then that extension field shall be used by the DHCPv4 server rather than the "file" field.

The above assumes that the default connection method uses TCP as stated in the iSCSI standard. Should SCTP ([RFC 2960](#)) be also approved as a transport mechanism for iSCSI, then the draft will be amended to

provide for alternate transport protocols.

Detailed message formats will be available in a future version of this draft.

[4.](#) Discovery Server stage:

This stage is required if the DHCP server (v4 or v6) is unaware of the identity of the iSCSI boot server. In such a situation, the DHCP server must return the identity of an iSCSI discovery server within a proposed extension for iSCSI Discovery Server. This extension would be obtained following the rules stated in [RFC 2939](#) and would apply to both DHCPv4 and DHCPv6.

The iscsi boot client then MAY send a message to the discovery server according to the specifications stated in the iSCSI Naming and Discovery document[14]. The discovery server provides the boot client a list of SCSI targets the client is allowed to access, along with the access permissions for each of the target.

The iscsi boot client goes through the list of SCSI targets and must select the first SCSI target with the bootable attribute as the iSCSI bootstrapping server. If such an attribute does not exist in any of the SCSI targets, the boot client must select the first SCSI target in the list of SCSI targets as the iSCSI boot server.

If the list of SCSI targets is empty, subsequent actions are left to the discretion of the implementor.

The packets and software requirements are stated in the iSCSI Naming and Discovery document[14].

[5.](#) Boot Stage

Once the iSCSI boot client has obtained the minimum information to open an iSCSI session with the iSCSI boot server, the actual booting process can start.

The actual sequence of iSCSI commands needed to complete the boot process is left to the implementor. This was done because of varying requirements from different vendors and equipment, making it difficult to specify a common subset of the iSCSI standard that would

be acceptable to everybody.

The iSCSI session established for boot may be taken over the booted software in the bootstrapping client - this is left to the discretion of the implementor.

6. Security

Securing the host configuration protocol is beyond the scope of this document. Authentication of DHCP messages is described in [draft-ietf-dhc-authentication-14.txt](#).

The iSCSI standard support various methods of authenticated login and encrypted and authenticated connections for security. How to configure the security parameters of an iSCSI boot client is beyond the (current) scope of this document.

The security discussions in the iSCSI standard[12] are applicable to this document.

Acknowledgments

We wish to thank John Hufferd (IBM) for taking the initiative to form the iSCSI boot team, and Julian Satran (IBM) for providing insightful comments. We also wish to thank the unnamed others for their help with this document.

References

- [1] Acetta, M., "Resource Location Protocol", [RFC 887](#), CMU, December 1983.
- [2] Alexander, S., and R. Droms, "DHCP Options and BOOTP Vendor Extensions", [RFC 2132](#), Lachman Technology, Inc., Bucknell University, October 1993.
- [3] R. Droms, "Dynamic Host Configuration Protocol", [RFC 2131](#), Bucknell University, March 1997.
- [4] Brownell, D, "Dynamic Reverse Address Resolution Protocol (DRARP)", Work in Progress.

- [5] Croft, B., and J. Gilmore, "Bootstrap Protocol (BOOTP)", [RFC 951](#), Stanford and SUN Microsystems, September 1985.
- [6] Droms, D., "Interoperation between DHCP and BOOTP" [RFC 2132](#), Bucknell University, October 1993.
- [7] Finlayson, R., Mann, T., Mogul, J., and M. Theimer, "A Reverse Address Resolution Protocol", [RFC 903](#), Stanford, June 1984.
- [8] Reynolds, J., "BOOTP Vendor Information Extensions", [RFC 1497](#), USC/Information Sciences Institute, August 1993.
- [9] Sollins, K., "The TFTP Protocol (Revision 2)", [RFC 783](#), NIC, June 1981.
- [10] Wimer, W., "Clarifications and Extensions for the Bootstrap Protocol", [RFC 1532](#), Carnegie Mellon University, October 1993.
- [11] Bradner, S., "The Internet Standards Process -- Revision 3", [RFC 2026](#), October 1996.
- [12] Satran, J., "iSCSI", Internet-Draft, November 2000.
- [13] Bound, J., Canney, M., and Perkins, C., "Dynamic Host Configuration Protocol for IPv6", Internet-Draft, May 2000.
- [14] Voruganti, K. et al., "iSCSI Naming and Discovery", Internet-Draft, November 2000.

Author's Addresses

Sarkar

Expires: May 2001

[Page 6]

Standards-Track

iSCSI BootStrapping Draft

17 November 2000

Prasenjit Sarkar
IBM Almaden Research Center
650 Harry Road
San Jose, CA 95120, USA
Phone: +1 408 927 1417
Email: psarkar@almaden.ibm.com

Duncan Missimer

Hewlett-Packard Company
19420 Homestead Road, M/S 4310
Cupertino, CA 95014, USA
Phone: +1 408 447 5390
Email: duncan_missimer@hp.com

Constantine Sapuntzakis
Cisco Systems, Inc.
170 W. Tasman Drive
San Jose, CA 95134, USA
Phone: +1 650 520 0205
Email: csapuntz@cisco.com

Full Copyright Statement

"Copyright (C) The Internet Society (date). All Rights Reserved. This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to the Internet Society or other Internet organizations, except as needed for the purpose of developing Internet standards in which case the procedures for copyrights defined in the Internet Standards process must be followed, or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by the Internet Society or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE."