

Network Working Group
Corp
Internet Draft
Network
[draft-ietf-ipsec-esp-v3-00.txt](#)
1997

Stephen Kent, BBN
Randall Atkinson, @Home
2 October

IP Encapsulating Security Payload (ESP)

Status of This Memo

This document is an Internet Draft. Internet Drafts are working documents of the Internet Engineering Task Force (IETF), its Areas, and its working groups. Note that other groups may also distribute working documents as Internet Drafts.

Internet Drafts are draft documents valid for a maximum of 6 months. Internet Drafts may be updated, replaced, or obsoleted by other documents at any time. It is not appropriate to use Internet Drafts as reference material or to cite them other than as "work in progress".

This particular Internet Draft is a product of the IETF's IPsec working group. It is intended that a future version of this draft be submitted to the IPng Area Directors and the IESG for possible publication as a standards-track protocol.

Table of Contents

[1.](#)
Introduction.....[3](#)

[2.](#) Encapsulating Security Payload Packet
Format.....[4](#)

[2.1](#) Security Parameters

Index.....[4](#)

[2.2](#) Sequence
Number[5](#)

[2.3](#) Payload
Data.....[5](#)

[2.4](#) Padding (for
Encryption).....[6](#)

[2.5](#) Pad
Length.....[7](#)

[2.6](#) Next
Header.....[7](#)

[2.7](#) Authentication
Data.....[7](#)

[3.](#) Encapsulating Security Protocol
Processing.....[7](#)

[3.1](#) ESP Header
Location.....[7](#)

[3.2](#) Algorithms.....

[10](#) [3.2.1](#) Encryption Algorithms.....

[10](#) [3.2.2](#) Authentication Algorithms.....

[10](#) [3.3](#) Outbound Packet Processing.....

[11](#) [3.3.1](#) Security Association Lookup.....

[11](#) [3.3.2](#) Packet Encryption.....

[11](#) [3.3.3](#) Sequence Number Generation.....

[12](#) [3.3.4](#) Integrity Check Value Calculation.....

[12](#) [3.3.5](#) Fragmentation.....

[13](#) [3.4](#) Inbound Packet Processing.....

[13](#) [3.4.1](#) Reassembly.....

[13](#) [3.4.2](#) Security Association Lookup.....

[13](#) [3.4.3](#) Sequence Number Verification.....

[14](#) [3.4.4](#) Integrity Check Value Verification.....

[15](#) [3.4.5](#) Packet Decryption.....

[15](#) [4.](#) Auditing.....

[17](#) [5.](#) Conformance Requirements.....

[17](#) [6.](#) Security Considerations.....

[17](#) [7.](#) Differences from [RFC 1827](#).....

[18](#) Acknowledgements.....

[18](#) References.....

[18](#) Disclaimer.....

[20](#) Author Information.....

[20](#)

1. Introduction

The Encapsulating Security Payload (ESP) header is designed to provide a mix of security services in IPv4 and IPv6. ESP may be applied alone, in combination with the IP Authentication Header (AH) [[KA97b](#)], or in a nested fashion, e.g., through the use of tunnel mode

(see 'Security Architecture for the Internet Protocol' [[KA97a](#)], hereafter referred to as the Security Architecture document). Security services can be provided between a pair of communicating hosts, between a pair of communicating security gateways, or between a security gateway and a host. For more details on how to use ESP and AH in various network environments, see the Security Architecture document [[KA97a](#)].

The ESP header is inserted after the IP header and before the upper layer protocol header (transport mode) or before an encapsulated IP header (tunnel mode). These modes are described in more detail below.

ESP is used to provide confidentiality, data origin authentication, connectionless integrity, an anti-replay service (a form of partial sequence integrity), and limited traffic flow confidentiality. The set of services provided depends on options selected at the time of Security Association establishment and on the placement of the implementation. Confidentiality may be selected independent of all other services. However, use of confidentiality without integrity/authentication (either in ESP or separately in AH) may subject traffic to certain forms of active attacks that could undermine the confidentiality service (see [[Bel96](#)]). Data origin authentication and connectionless integrity are joint services (hereafter referred to jointly as 'authentication') and are offered as

an option in conjunction with confidentiality. The anti-replay service may be selected only if data origin authentication is selected, and its election is solely at the discretion of the receiver. Traffic flow confidentiality requires selection of tunnel mode, and is most effective if implemented at a security gateway, where traffic aggregation may be able to mask true source-destination patterns.

It is assumed that the reader is familiar with the terms and concepts described in the Security Architecture document. In particular, the reader should be familiar with the definitions of security services offered by ESP and AH, the concept of Security Associations, the ways

in which ESP can be used in conjunction with the Authentication Header (AH), and the different key management options available for

ESP and AH. (With regard to the last topic, the current key management options required for both AH and ESP are manual keying and

Kent, Atkinson
3]


[Page

automated keying via Oakley/ISAKMP.)

2. Encapsulating Security Payload Packet Format

The protocol header (IPv4, IPv6, or Extension) immediately preceding the

ESP header will contain the value 50 in its Protocol (IPv4) or Next Header (IPv6, Extension) field [STD-2].



* If included in the Payload field, cryptographic synchronization data, e.g., an IV, usually is not encrypted per se, although it often is referred to as being part of the ciphertext.

The following subsections define the fields in the header format. "Optional" means that the field is omitted if the option is not

selected, i.e., it is present in neither the packet as transmitted nor as formatted for computation of an ICV. Whether or not an option

is selected is defined as part of Security Association (SA) establishment. Thus the format of ESP packets for a given SA is fixed, for the duration of the SA. In contrast, "mandatory" fields are always present in the ESP packet format, for all SAs.

2.1 Security Parameters Index

The SPI is an arbitrary 32-bit value that, in combination with the destination IP address and security protocol, uniquely identifies the

Security Association for this datagram. The set of SPI values in the range 1 through 255 are reserved by the Internet Assigned Numbers Authority (IANA) for future use; a reserved SPI value will not normally be assigned by IANA unless the use of the assigned SPI value is specified in an RFC. It is ordinarily selected by the destination system upon establishment of an SA (see the Security Architecture document for more details). The SPI field is mandatory.

The SPI value of zero (0) is reserved for local, implementation-specific use and MUST NOT be sent on the wire. For example, a key management implementation MAY use the zero SPI value to mean "No Security Association Exists" during the period when the IPsec implementation has requested that its key management entity establish a new SA, but the SA has not yet been established.

2.2 Sequence Number

This unsigned 32-bit field contains a monotonically increasing counter value (sequence number). It is mandatory and is always present even if the receiver does not elect to enable the anti-replay service for a specific SA. Processing of the Sequence Number field is at the discretion of the receiver, i.e., the sender MUST always transmit this field, but the receiver need not act upon it (see the discussion of Sequence Number Verification in the "Inbound Packet Processing" section below).

The sender's counter and the receiver's counter are initialized to 0 when an SA is established. (The first packet sent using a given SA will have a Sequence Number of 1; see [Section 3.3.3](#) for more details on how the Sequence Number is generated.) If anti-replay has been enabled, the transmitted Sequence Number must never be allowed to cycle. Thus, the sender's counter and the receiver's counter MUST be reset (by establishing a new SA and thus a new key) prior to the transmission of the 2³²nd packet on an SA.

2.3 Payload Data

Payload Data is a variable-length field containing data described by the Next Header field. The Payload Data field is mandatory and is an integral number of bytes in length. If the algorithm used to encrypt the payload requires cryptographic synchronization data, e.g., an Initialization Vector (IV), then this data MAY be carried explicitly in the Payload field. Any encryption algorithm that requires such explicit, per-packet synchronization data MUST indicate the length,

any structure for such data, and the location of this data as part of an RFC specifying how the algorithm is used with ESP. If such synchronization data is implicit, the algorithm for deriving the data

Kent, Atkinson
5]

[Page

MUST be part of the RFC.

2.4 Padding (for Encryption)

Several factors require or motivate use of the Padding field.

If an encryption algorithm is employed that requires the plaintext to be a multiple of some number of bytes, e.g., the block size of a block cipher, the Padding field is used to fill the plaintext (consisting of the Payload Data, Pad Length and Next Header fields, as well as the Padding) to the size required by the algorithm.

Padding also may be required, irrespective of encryption algorithm requirements, to ensure that the resulting ciphertext terminates on a 4-byte boundary. Specifically, the Pad Length and Next Header fields must be right aligned within a 4-byte word, as illustrated in the ESP packet format figure above.

Padding beyond that required for the algorithm or alignment reasons cited above, may be used to conceal the actual length of the payload, in support of (partial) traffic flow confidentiality. However, inclusion of such additional padding has adverse bandwidth implications and thus its use should be undertaken with care.

The transmitter MAY add 0-255 bytes of padding. Inclusion of the Padding field in an ESP packet is optional, but all implementations MUST support generation and consumption of padding.

If Padding bytes are needed but the encryption algorithm does not specify the padding contents, then the following default processing MUST be used. The Padding bytes are initialized with a series of (unsigned, 1-byte) integer values. The first padding byte appended to the plaintext is numbered 1, with subsequent padding bytes making up a monotonically increasing sequence: 1, 2, 3, ... When this padding scheme is employed, the receiver SHOULD inspect the Padding

field. (This scheme was selected because of its relative simplicity, ease of implementation in hardware, and because it offers limited protection against certain forms of "cut and paste" attacks in the absence of other integrity measures, if the receiver checks the padding values upon decryption.)

Any encryption algorithm that requires Padding other than the default described above, MUST define the Padding contents (e.g., zeros or

random data) and any required receiver processing of these Padding bytes in an RFC specifying how the algorithm is used with ESP. In such circumstances, the content of the Padding field will be determined by the encryption algorithm and mode selected and defined in the corresponding algorithm RFC. The relevant algorithm RFC MAY specify that a receiver MUST inspect the Padding field or that a receiver MUST inform senders of how the receiver will handle the Padding field.

2.5 Pad Length

The Pad Length field indicates the number of pad bytes immediately preceding it. The range of valid values is 0-255, where a value of zero indicates that no Padding bytes are present. The Pad Length field is mandatory.

2.6 Next Header

The Next Header is an 8-bit field that identifies the type of data contained in the Payload Data field, e.g., an extension header in IPv6 or an upper layer protocol identifier. The value of this field is chosen from the set of IP Protocol Numbers defined in the most recent "Assigned Numbers" [[STD-2](#)] RFC from the Internet Assigned Numbers Authority (IANA). The Next Header field is mandatory.

2.7 Authentication Data

The Authentication Data is a variable-length field containing an Integrity Check Value (ICV) computed over the ESP packet minus the Authentication Data. The length of the field depends upon the authentication function selected. However, where the algorithm yields more than 96 bits, the output of the computation is truncated to the leftmost 96 bits. The Authentication Data field is optional, and is included only if the authentication service has been selected for the SA in question.

3. Encapsulating Security Protocol Processing

3.1 ESP Header Location

Like AH, ESP may be employed in two ways: transport mode or tunnel mode. The former mode is applicable only to host implementations and provides protection for upper layer protocols, but not the IP header.


(In this mode, note that for "bump-in-the-stack" or "bump-in-the-wire" implementations, as defined in the Security Architecture document, inbound and outbound IP fragments may require an IPsec implementation to perform extra IP reassembly/fragmentation in order

Security Payload (ESP)

to both conform to this specification and provide transparent IPsec support. Special care is required to perform such operations within these implementations when multiple interfaces are in use.)


In transport mode, ESP is inserted after the IP header and before an upper layer protocol, e.g., TCP, UDP, ICMP, etc. or before any other

IPsec headers that have already been inserted. In the context of IPv4, this translates to placing ESP after the IP header (and any options that it contains), but before the upper layer protocol. (Note that the term "transport" mode should not be misconstrued as restricting its use to TCP and UDP. For example, an ICMP message MAY be sent using either "transport" mode or "tunnel" mode.) The following diagram illustrates ESP transport mode positioning for a typical IPv4 packet, on a "before and after" basis. (The "ESP trailer" encompasses any Padding, plus the Pad Length, and Next Header fields.)




In the IPv6 context, ESP is viewed as an end-to-end payload, and thus should appear after hop-by-hop, routing, and fragmentation extension headers. The destination options extension header(s) could appear either before or after the ESP header depending on the semantics desired. However, since ESP protects only fields after the ESP header, it generally may be desirable to place the destination options header(s) after the ESP header. The following diagram illustrates ESP transport mode positioning for a typical IPv6 packet.

BEFORE APPLYING ESP



AFTER APPLYING ESP



* = if present, could be before ESP, after ESP, or both

If more than one IPsec header/extension is required:



- o the order of application of the security headers MUST be defined by security policy
- o The following 3 cases MUST be supported:
 1. [IP][AH][upper]
 2. [IP][ESP][upper]
 3. [IP][AH][ESP][upper]
- o arbitrary nesting is allowed -- Senders MAY generate arbitrary nestings of IPsec headers and Receivers SHOULD accept arbitrary nestings of IPsec headers.

Tunnel mode ESP may be employed in either hosts or security gateways.

When ESP is implemented in a security gateway (to protect subscriber transit traffic), tunnel mode must be used. In tunnel mode, the "inner" IP header carries the ultimate source and destination addresses, while an "outer" IP header may contain distinct IP addresses, e.g., addresses of security gateways. In tunnel mode,

ESP

protects the entire inner IP packet, including the entire inner IP header. The position of ESP in tunnel mode, relative to the outer IP header, is the same as for ESP in transport mode. The following diagram illustrates ESP tunnel mode positioning for typical IPv4 and IPv6 packets.



* = construction of outer IP hdr/extensions and
modification of inner IP hdr/extensions is discussed below.

3.2 Algorithms

The mandatory-to-implement algorithms are described in [Section 5](#), "Conformance Requirements". Other algorithms MAY be supported.

3.2.1 Encryption Algorithms

The encryption algorithm employed is specified by the SA. ESP is designed for use with symmetric encryption algorithms. Because IP packets may arrive out of order, each packet must carry any data required to allow the receiver to establish cryptographic synchronization for decryption. This data may be carried explicitly in the payload field, e.g., as an IV (as described above), or the data may be derived from the packet header. Since ESP makes provision for padding of the plaintext, encryption algorithms employed with ESP may exhibit either block or stream mode characteristics.

3.2.2 Authentication Algorithms

The authentication algorithm employed for the ICV computation is specified by the SA. For point-to-point communication, suitable authentication algorithms include keyed Message Authentication Codes (MACs) based on symmetric encryption algorithms (e.g., DES) or on one-way hash functions (e.g., MD5 or SHA-1). For multicast communication, one-way hash algorithms combined with asymmetric signature algorithms are appropriate, though performance and space considerations currently preclude use of such algorithms. Note:

Where

an algorithm yields more than 96 bits, the output of the computation

Kent, Atkinson
10]

[Page

is truncated to the leftmost 96 bits.

3.3 Outbound Packet Processing

In transport mode, the transmitter encapsulates the upper layer protocol information in the ESP header/trailer, and retains the specified IP header (and any IP extension headers in the IPv6 context). In tunnel mode, the outer and inner IP header/extensions can be inter-related in a variety of ways. The construction of the outer IP header/extensions during the encapsulation process is described in the Security Architecture document. If there is more than one IPsec header/extension required by security policy, the order of the application of the security headers MUST be defined by security policy.

3.3.1 Security Association Lookup

ESP is applied to an outbound packet only after an IPsec implementation determines that the packet is associated with an SA that calls for ESP processing. The process of determining what, if any, IPsec processing is applied to outbound traffic is described in the Security Architecture document.

3.3.2 Packet Encryption

The transmitter:

1. encapsulates (into the ESP Payload field):
 - for transport mode -- just the original upper layer protocol information.
 - for tunnel mode -- the entire original IP datagram.
2. adds any necessary padding.
3. encrypts the result (Payload Data, Padding, Pad Length, and Next Header) using the key, encryption algorithm, algorithm mode indicated by the SA and cryptographic synchronization data (if any).
 - If explicit cryptographic synchronization data, e.g., an IV, is indicated, it is input to the decryption algorithm per the algorithm specification and placed in the Payload field.
 - If implicit cryptographic synchronization data, e.g., an IV, is indicated, it is constructed and input to the decryption algorithm as per the algorithm

specification.

The exact steps for constructing the outer IP header depend on the mode (transport or tunnel) and are described in the Security Architecture document.

Kent, Atkinson
11]

[Page

If authentication is selected, encryption is performed first, before the authentication, and the encryption does not encompass the Authentication Data field. This order of processing facilitates rapid detection and rejection of replayed or bogus packets by the receiver, prior to decrypting the packet, hence potentially reducing the impact of denial of service attacks. It also allows for the possibility of parallel processing of packets at the receiver, i.e., decryption can take place in parallel with authentication. Note that

since the Authentication Data is not protected by encryption, a keyed authentication algorithm must be employed to compute the ICV.

3.3.3 Sequence Number Generation

The sender's counter is initialized to 0 when an SA is established. The transmitter increments the Sequence Number for this SA and inserts the new value into the Sequence Number field. Thus the first packet sent using a given SA will have a Sequence Number of 1.

If anti-replay has been enabled, the transmitter checks to ensure that the counter has not cycled before inserting the new value in the Sequence Number field. In other words, the transmitter MUST NOT send

a packet on an SA if doing so would cause the Sequence Number to cycle. An attempt to transmit a packet that would result in Sequence

Number overflow is an auditable event. (Note that this approach to Sequence Number management does not require use of modular arithmetic.)

If anti-replay has not been enabled, the sender does not need to monitor or reset the counter, e.g., in the case of manual key management. NOTE: If the receiver does NOT notify the sender that anti-replay is enabled, then the sender may overflow the counter and may send packets that the receiver will reject.

3.3.4 Integrity Check Value Calculation

If authentication is selected for the SA, the transmitter computes the ICV over the ESP packet minus the Authentication Data. Thus the SPI, Sequence Number, Payload Data, Padding (if present), Pad Length, and Next Header are all encompassed by the ICV computation. Note that the last 4 fields will be in ciphertext form, since encryption is performed prior to authentication.

For some authentication algorithms, the byte string over which the ICV computation is performed must be a multiple of a blocksize

specified by the algorithm. If the length of this byte string does not match the blocksize requirements for the algorithm, implicit padding MUST be appended to the end of the ESP packet, prior to ICV

computation. The padding octets MUST have a value of zero. The blocksize (and hence the length of the padding) is specified by the algorithm specification. This padding is not transmitted with the packet.

3.3.5 Fragmentation

If necessary, fragmentation is performed after ESP processing within an IPsec implementation. Thus, transport mode ESP is applied only to whole IP datagrams (not to IP fragments). An IP packet to which ESP has been applied may itself be fragmented by routers en route, and such fragments must be reassembled prior to ESP processing at a receiver. In tunnel mode, ESP is applied to an IP packet, the payload of which may be a fragmented IP packet. For example, a security gateway or a "bump-in-the-stack" or "bump-in-the-wire" IPsec implementation (as defined in the Security Architecture document) may apply tunnel mode ESP to such fragments.

3.4 Inbound Packet Processing

3.4.1 Reassembly

If required, reassembly is performed prior to ESP processing. If a packet offered to ESP for processing appears to be an IP fragment, i.e., the OFFSET field is non-zero or the MORE FRAGMENTS flag is set, the receiver MUST discard the packet; this is an auditable event. The audit log entry for this event SHOULD include the SPI value, date/time, Source Address, Destination Address, and (in IPv6) the Flow ID.

3.4.2 Security Association Lookup

Upon receipt of a (reassembled) packet containing an ESP Header, the receiver determines the appropriate (unidirectional) SA, based on the destination IP address, security protocol (ESP), and the SPI. (This process is described in more detail in the Security Architecture document.) The SA indicates whether the Sequence Number field will be checked, whether the Authentication Data field should be present, and it will specify the algorithms and keys to be employed for decryption and ICV computations (if applicable).

If no valid Security Association exists for this session (for example, the receiver has no key), the receiver MUST discard the packet; this is an auditable event. The audit log entry for this

event SHOULD include the SPI value, date/time, Source Address, Destination Address, and (in IPv6) the cleartext Flow ID.

Kent, Atkinson
13]

[Page

3.4.3 Sequence Number Verification

All ESP implementations MUST support the anti-replay service, though its use may be enabled or disabled on a per-SA basis. This service MUST NOT be enabled unless the authentication service also is enabled

for the SA, since otherwise the Sequence Number field has not been integrity protected. (Note that there are no provisions for managing

transmitted Sequence Number values among multiple senders directing traffic to a single, multicast SA. Thus the anti-replay service SHOULD NOT be used in a multi-sender multicast environment that employs a single, multicast SA.)

If the receiver does not enable anti-replay for an SA, no checks are performed on the inbound Sequence Number. If an SA establishment protocol such as Oakley/ISAKMP is employed, then the receiver SHOULD notify the transmitter, during SA establishment, if the receiver will

provide anti-replay protection.

If the receiver has enabled the anti-replay service for this SA, the receive packet counter for the SA MUST be initialized to zero when the SA is established. For each received packet, the receiver MUST verify that the packet contains a Sequence Number that does not duplicate the Sequence Number of any other packets received during the life of this SA. This SHOULD be the first ESP check applied to

a packet after it has been matched to an SA, to speed rejection of duplicate packets.

Duplicates are rejected through the use of a sliding receive window. (How the window is implemented is a local matter, but the following text describes the functionality that the implementation must exhibit.) A MINIMUM window size of 32 MUST be supported; but a window size of 64 is preferred and SHOULD be employed as the default.

Another window size (larger than the MINIMUM) MAY be chosen by the receiver. (The receiver does NOT notify the sender of the window size.)

The "right" edge of the window represents the highest, validated Sequence Number value received on this SA. Packets that contain Sequence Numbers lower than the "left" edge of the window are rejected. Packets falling within the window are checked against a list of received packets within the window. An efficient means for performing this check, based on the use of a bit mask, is described in the Security Architecture document.

If the received packet falls within the window and is new, or if the packet is to the right of the window, then the receiver proceeds to

ICV verification. If the ICV validation fails, the receiver MUST

Kent, Atkinson
14]

[Page

discard the received IP datagram as invalid; this is an auditable event. The audit log entry for this event SHOULD include the SPI value, date/time, Source Address, Destination Address, the Sequence Number, and (in IPv6) the Flow ID. The receive window is updated only if the ICV verification succeeds.

DISCUSSION:

Note that if the packet is either inside the window and new, or is outside the window on the "right" side, the receiver MUST authenticate the packet before updating the Sequence Number window data.

3.4.4 Integrity Check Value Verification

If authentication has been selected, the receiver computes the ICV over the ESP packet minus the Authentication Data using the specified authentication algorithm and verifies that it is the same as the ICV included in the Authentication Data field of the packet. Details of the computation are provided below.

If the computed and received ICV's match, then the datagram is valid, and it is accepted. If the test fails, then the receiver MUST discard the received IP datagram as invalid; this is an auditable event. The log data SHOULD include the SPI value, date/time received, Source Address, Destination Address, and (in IPv6) the cleartext Flow ID.

DISCUSSION:

Begin by removing and saving the ICV value (Authentication Data field). Next check the overall length of the ESP packet minus the Authentication Data. If implicit padding is required, based on the blocksize of the authentication algorithm, append zero-filled bytes to the end of the ESP packet directly after the Next Header field. Perform the ICV computation and compare the result with the saved value. Note that if the output of the authentication algorithm is greater than 96 bits, the output should be truncated to the leftmost 96 bits. (If a digital signature and one-way hash are used for the ICV computation, the matching process is more complex and will be described in the algorithm specification.)

3.4.5 Packet Decryption

The receiver:

1. decrypts the ESP Payload Data, Padding, Pad Length, and
Next

Kent, Atkinson
15]

[Page

Header using the key, encryption algorithm, algorithm mode, and cryptographic synchronization data (if any), indicated by the SA.

e.g.,

- If explicit cryptographic synchronization data, an IV, is indicated, it is taken from the Payload field and input to the decryption algorithm as per algorithm specification.
- If implicit cryptographic synchronization data, an IV, is indicated, a local version of the IV is constructed and input to the decryption algorithm as per the algorithm specification.

2. removes/ignores any padding
3. reconstructs the original IP datagram from:
 - for transport mode -- original IP header plus the original upper layer protocol information in the Payload field
 - for tunnel mode -- tunnel IP header + the entire datagram in the ESP Payload field.

The exact steps for reconstructing the original datagram depend on the mode (transport or tunnel) and are described in the Security Architecture document. At a minimum, in an IPv6 context, the receiver SHOULD ensure that the decrypted data is 8-byte aligned, to facilitate processing by the protocol identified in the Next Header field.

If authentication has been selected, ICV verification SHOULD be performed before decryption. This order of processing facilitates rapid detection and rejection of replayed or bogus packets by the receiver, prior to decrypting the packet, hence potentially reducing the impact of denial of service attacks. Note: The receiver MAY start decryption in parallel with authentication, but care must be taken to avoid possible race conditions with regard to packet access and reconstruction of the decrypted packet.

Note that there are two ways in which the decryption can "fail".

- o The selected SA may not be correct.
- o The encrypted ESP packet could be corrupted.

The latter case would be detected if authentication is selected for the SA, as would tampering with the SPI. However, an SA mismatch might still occur due to tampering with the IP Destination Address. In either case, the erroneous result of the decryption operation (an

invalid IP datagram or transport-layer frame) will not necessarily be detected by IPsec, and is the responsibility of later protocol processing.

Kent, Atkinson
16]

[Page

4. Auditing

Not all systems that implement ESP will implement auditing. However, if ESP is incorporated into a system that supports auditing, then the ESP implementation MUST also support auditing and MUST allow a system administrator to enable or disable auditing for ESP. For the most part, the granularity of auditing is a local matter. However, several auditable events are identified in this specification and for each of these events a minimum set of information that SHOULD be included in an audit log is defined. Additional information also MAY be included in the audit log for each of these events, and additional events, not explicitly called out in this specification, also MAY result in audit log entries. There is no requirement for the receiver to transmit any message to the purported transmitter in response to the detection of an auditable event, because of the potential to induce denial of service via such action.

5. Conformance Requirements

Implementations that claim conformance or compliance with this specification MUST implement the ESP syntax and processing described here and MUST comply with all requirements of the Security Architecture document. If the key used to compute an ICV is manually distributed, correct provision of the anti-replay service would require correct maintenance of the counter state at the transmitter, until the key is replaced, and there likely would be no automated recovery provision if counter overflow were imminent. Thus a compliant implementation SHOULD NOT provide this service in conjunction with SAs that are manually keyed. A compliant ESP implementation MUST support the following mandatory-to-implement algorithms:

- DES in CBC mode [[MD97](#)]
- HMAC with MD5 [[MG97a](#)]
- HMAC with SHA-1 [[MG97b](#)]

6. Security Considerations

Security is central to the design of this protocol, and thus security considerations permeate the specification. Additional security-relevant aspects of using the IPsec protocol are discussed in the Security Architecture document.

7. Differences from [RFC 1827](#)

This document differs from [RFC 1827](#) [[ATK95](#)] in several significant ways. The major difference is that, this document attempts to specify a complete framework and context for ESP, whereas [RFC 1827](#) provided a "shell" that was completed through the definition of transforms. The combinatorial growth of transforms motivated the reformulation of the ESP specification as a more complete document, with options for security services that may be offered in the context

of ESP. Thus, fields previously defined in transform documents are now part of this base ESP specification. For example, the fields necessary to support authentication (and anti-replay) are now defined

here, even though the provision of this service is an option. The fields used to support padding for encryption, and for next protocol identification, are now defined here as well. Packet processing consistent with the definition of these fields also is included in the document.

Acknowledgements

Many of the concepts embodied in this specification were derived from or influenced by the US Government's SP3 security protocol, ISO/IEC's NLSP, or from the proposed swIPe security protocol. [[SDNS89](#), [IS092](#), [IB93](#)].

For over 2 years, this document has evolved through multiple versions and iterations. During this time, many people have contributed significant ideas and energy to the process and the documents themselves. The authors would like to thank Karen Seo for providing extensive help in the review, editing, background research, and coordination for this version of the specification. The authors would also like to thank the members of the IPSEC and IPng working groups, with special mention of the efforts of (in alphabetic order):
Steve Bellovin, Steve Deering, Phil Karn, Perry Metzger, David Mihelcic, Hilarie Orman, Norman Shulman, William Simpson and Nina Yuan.

References

[[ATK95](#)] R. Atkinson, "IP Encapsulating Security Payload (ESP)", [RFC 1827](#), August 1997.

[Bel89] Steven M. Bellovin, "Security Problems in the TCP/IP Protocol Suite", ACM Computer Communications Review, Vol. 19, No. 2, March 1989.

Kent, Atkinson
18]

[Page

- [Bel96] Steven M. Bellovin, "Problem Areas for the IP Security Protocols", Proceedings of the Sixth Usenix Unix Security Symposium, July, 1996.
- [CERT95] Computer Emergency Response Team (CERT), "IP Spoofing Attacks and Hijacked Terminal Connections", CA-95:01, January 1995. Available via anonymous ftp from info.cert.org.
- [DH95] Steve Deering & Robert Hinden, Internet Protocol Version 6 (IPv6) Specification, [RFC 1883](#), December 1995.
- [IB93] John Ioannidis & Matt Blaze, "Architecture and Implementation of Network-layer Security Under Unix", Proceedings of the USENIX Security Symposium, Santa Clara, CA, October 1993.
- [IS092] ISO/IEC JTC1/SC6, Network Layer Security Protocol, ISO-IEC DIS 11577, International Standards Organisation, Geneva, Switzerland, 29 November 1992.
- [KA97a] Steve Kent, Randall Atkinson, "Security Architecture for the Internet Protocol", Internet Draft, ?? 1997.
- [KA97b] Steve Kent, Randall Atkinson, "IP Authentication Header", Internet Draft, ?? 1997.
- [Ken91] Steve Kent, "US DoD Security Options for the Internet Protocol (IPSO)", [RFC-1108](#), November 1991.
- [MD97] C. Madson & N. Doraswamy, "The ESP DES-CBC Cipher Algorithm With Explicit IV", Internet Draft, 07/02/1997."
- [MG97a] C. Madson & R. Glenn, "The Use of HMAC-MD5-96 within ESP and AH", Internet Draft, 7/2/97.
- [MG97b] C. Madson & R. Glenn, "The Use of HMAC-SHA-1-96 within ESP and AH", Internet Draft, 7/2/97.
- [NIST77] US National Bureau of Standards, "Data Encryption Standard", Federal Information Processing Standard (FIPS) Publication 46, January 1977.
- [NIST80] US National Bureau of Standards, "DES Modes of Operation" Federal Information Processing Standard (FIPS) Publication 81, December 1980.

- [NIST81] US National Bureau of Standards, "Guidelines for Implementing and Using the Data Encryption Standard", Federal Information Processing Standard (FIPS) Publication 74, April 1981.
- [NIST88] US National Bureau of Standards, "Data Encryption Standard", Federal Information Processing Standard (FIPS) Publication 46-1, January 1988.
- [STD-2] J. Reynolds and J. Postel, "Assigned Numbers", STD-2, 20 October 1994.
- [Sch94] Bruce Schneier, Applied Cryptography, John Wiley & Sons, New York, NY, 1994. ISBN 0-471-59756-2
- [SDNS89] SDNS Secure Data Network System, Security Protocol 3, SP3, Document SDN.301, Revision 1.5, 15 May 1989, as published in NIST Publication NIST-IR-90-4250, February 1990.

Disclaimer

The views and specification here are those of the authors and are not necessarily those of their employers. The authors and their employers specifically disclaim responsibility for any problems arising from correct or incorrect implementation or use of this specification.

Author Information

Stephen Kent
BBN Corporation
70 Fawcett Street
Cambridge, MA 02140
USA
E-mail: kent@bbn.com
Telephone: +1 (617) 873-3988

Randall Atkinson
@Home Network
425 Broadway,
Redwood City, CA 94063
USA
E-mail: rja@inet.org

