

Internet Draft
Document: [draft-ietf-iptel-trip-mib-08.txt](#)
Expires: February 2004

D. Zinman
D. Walker
J. Jiang

Management Information Base
for Telephony Routing over IP (TRIP)
<[draft-ietf-iptel-trip-mib-08.txt](#)>

Status of this Memo

This document is an Internet-Draft and is in full conformance with all provisions of [Section 10 of RFC 2026](#) [RFC2026].

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups MAY also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and MAY be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/1id-abstracts.txt>

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

Copyright Notice

Copyright (C) The Internet Society (2003). All Rights Reserved.

Abstract

This memo defines a portion of the MIB (Management Information Base) module for use with network management protocols in the Internet community. In particular, it describes a set of managed objects that are used to manage for TRIP (Telephony Routing over IP) devices.

Table of Contents

Status of this Memo.....	1
Copyright Notice.....	1
Abstract.....	1
1. The Internet-Standard Management Framework.....	3
2. Introduction.....	3
3. Conventions used in this document.....	3
4. Overview.....	3
5. Structure of TRIP MIB.....	3
5.1 Textual Conventions.....	4
6. Definitions.....	4
6.1 TRIP Textual Conventions.....	4
6.2 TRIP MIB.....	7
7. Security Considerations.....	41
8. Full Copyright Statement.....	43
9. Normative References.....	43
10. Informative References.....	44
11. Intellectual Property Notice.....	44
12. Acknowledgments.....	45
13. Author's Addresses.....	45

1. The Internet-Standard Management Framework

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to [section 7 of RFC 3410](#) [[RFC3410](#)].

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. MIB module objects are generally accessed through the Simple Network Management Protocol (SNMP). Objects in this MIB module are defined using the mechanisms defined in the Structure of Management Information (SMI). This memo specifies a MIB module that is compliant to the SMIV2, which is described in STD 58, [RFC 2578](#) [[RFC2578](#)], STD 58, [RFC 2579](#) [[RFC2579](#)] and STD 58, [RFC 2580](#) [[RFC2580](#)].

2. Introduction

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it describes a set of managed objects that are used to schedule management operations periodically or at specified dates and times. Since TRIP [[RFC3219](#)] is modeled after the Border Gateway Protocol (BGP-4) [[RFC1771](#)], the managed objects for TRIP are also modeled after [RFC1657](#) - Definitions of Managed Objects for the Fourth Version of the Border Gateway Protocol (BGP-4) using SMIV2 [[RFC1657](#)].

3. Conventions used in this document

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [BCP-0014](#) [[BCP0014](#)].

4. Overview

This MIB module provides managed objects for TRIP devices defined in Telephony Routing over IP [[RFC3219](#)]. TRIP is an inter-domain application-layer control protocol that exchanges information between TRIP location servers (LS) to provide efficient IP telephony routing.

5. Structure of TRIP MIB

This MIB module utilizes the framework described in [RFC 2788](#) [[RFC2788](#)] for management of multiple instances of TRIP from a single entity. The Network Services Monitoring MIB module `applTable` will be populated with entries corresponding to each TRIP Location Server in the system. Each TRIP Location Server will then have an `applIndex` associated with it. The value assigned to `applIndex` will represent the distinct instance of TRIP.

Zinman/Walker/Jiang

3

Internet Draft

August 2003

The TRIP MIB module contains the following groups of objects:

- o The `tripConfigGroup` contains the common configuration objects applicable to all TRIP applications referenced by the `applIndex`.
- o The `tripPeerTableConfigGroup` contains the configuration objects applicable to all TRIP peers of the Location Server referenced by the `applIndex`.
- o The `tripRouteGroup` contains the configuration objects related to the routes of all TRIBs of this Location Server.
- o The `tripItadTopologyGroup` contains information about the topology of the TRIP ITADs concerning this Location Server.
- o The `tripPeerTableStatsGroup` contains the statistical objects applicable to all TRIP peers of the Location Server referenced by the `applIndex`.
- o The `tripNotificationGroup` contains notifications that the TRIP application can generate.
- o The `tripNotifObjectGroup` contains the objects needed by one or more of the notifications.

5.1 Textual Conventions

The data types `TripItad` and `TripId` are used as textual conventions in this document. A TRIP ITAD (IP Telephony Administrative Domain) is described in [[RFC3219](#)]. A TRIP ID is used as a distinct identifier for a TRIP Location Server. A `TripAppProtocol` is used to identify an application protocol. A `TripAddressFamily` is used to define an address family. `TripCommunityId` is used as a distinct identifier for a TRIP community. `TripProtocolVersion` depicts the version number of the TRIP protocol. `TripSendReceiveMode` describes the operational mode of the TRIP application.

6. Definitions

6.1 TRIP Textual Conventions

TRIP-TC DEFINITIONS ::= BEGIN

IMPORTS

MODULE-IDENTITY,
Unsigned32,
Integer32,
mib-2
FROM SNMPv2-SMI

TEXTUAL-CONVENTION
FROM SNMPv2-TC;

tripTC MODULE-IDENTITY
LAST-UPDATED "200308110000Z" -- Aug 11, 2003
ORGANIZATION "IETF IPTel Working Group.
Mailing list: iptel@lists.bell-labs.com"
CONTACT-INFO

Zinman/Walker/Jiang

4

Internet Draft

August 2003

"Co-editor David Zinman
postal: 265 Ridley Blvd.
Toronto ON, M5M 4N8
Canada
email: dzinman@rogers.com
phone: +1 416 433 4298

Co-editor Dave Walker
SS8 Networks, Inc.
postal: 495 March Road, Suite #500
Ottawa, ON, K2K 3G1
Canada
email: drwalker@ss8.com
phone: +1 613 592 2100

Co-editor Jianping Jiang
SS8 Networks, Inc.
postal: 495 March Road, Suite #500
Ottawa, ON, K2K 3G1
Canada
email: jianping@ss8.com
phone: +1 613 592 2100
"

DESCRIPTION

"Initial version of TRIP (Telephony Routing Over IP)
MIB Textual Conventions module used by other
TRIP-related MIB Modules.

Copyright (C) The Internet Society (2003). This version of
this MIB module is part of RFC xxxx, see the RFC itself
for full legal notices."

REVISION "200308110000Z" -- Aug 11, 2003

```

DESCRIPTION
    "The initial version, Published as RFC xxxx."
    ::= { mib-2 xxxx } -- to be assigned by IANA

--
-- Textual Conventions
--
TripItad ::= TEXTUAL-CONVENTION
    STATUS current
    DESCRIPTION
        "The values for identifying the IP Telephony
        Administrative Domain (ITAD)."
```

```

    SYNTAX Unsigned32 (0..4294967295)
```

```

TripId ::= TEXTUAL-CONVENTION
    STATUS current
    DESCRIPTION
        "The TRIP Identifier uniquely identifies a LS within its
        ITAD. It is a 4 octet unsigned integer that may, but not
        necessarily, represent the IPv4 address of a Location
```

Zinman/Walker/Jiang 5

Internet Draft August 2003

```

        Server. Where bytes 1-4 of the Unsigned32 represent
        1-4 bytes of the IPv4 address in network-byte order. For
        an IPv6 network, TripId will not represent the IPv6
        address."
    SYNTAX Unsigned32 (0..4294967295)
```

```

TripAddressFamily ::= TEXTUAL-CONVENTION
    STATUS current
    DESCRIPTION
        "A type of address for a TRIP route. Address families
        defined within this MIB module are:
```

Code	Address Family
1	Decimal Routing Numbers
2	PentaDecimal Routing Numbers
3	E.164 Numbers"

```

    SYNTAX INTEGER { decimal(1), pentadecimal(2), e164(3) }
```

```

TripAppProtocol ::= TEXTUAL-CONVENTION
    STATUS current
    DESCRIPTION
        "The application protocol used for communication with TRIP
        Location Servers. Protocols defined in this MIB Module
        are:
```

Code	Protocol
------	----------

1	SIP
2	H.323-H.225.0-Q.931
3	H.323-H.225.0-RAS
4	H.323-H.225.0-Annex-G"

SYNTAX INTEGER { sip(1), q931(2), ras(3), annexG(4) }

TripCommunityId ::= TEXTUAL-CONVENTION

STATUS current

DESCRIPTION

"The range of legal values for a TRIP Community Identifier."

SYNTAX Unsigned32 (0..4294967295)

TripProtocolVersion ::= TEXTUAL-CONVENTION

STATUS current

DESCRIPTION

"The version number of the TRIP protocol."

SYNTAX Integer32 (1..255)

TripSendReceiveMode ::= TEXTUAL-CONVENTION

STATUS current

DESCRIPTION

"The operational mode of the TRIP application. Possible values are:

Zinman/Walker/Jiang

6

Internet Draft

August 2003

- 1 - Send Receive mode
- 2 - Send only mode
- 3 - Receive Only mode"

SYNTAX INTEGER { sendReceive(1), sendOnly(2), receiveOnly(3) }

END

[6.2](#) TRIP MIB

TRIP-MIB DEFINITIONS ::= BEGIN

IMPORTS

MODULE-IDENTITY,

OBJECT-TYPE,

NOTIFICATION-TYPE,

Unsigned32,

Integer32,

Counter32,

mib-2

FROM SNMPv2-SMI

DateAndTime,

TimeInterval,
TruthValue,
TimeStamp,
StorageType,
RowStatus
FROM SNMPv2-TC

OBJECT-GROUP,
MODULE-COMPLIANCE,
NOTIFICATION-GROUP
FROM SNMPv2-CONF

InetAddressType,
InetAddress,
InetPortNumber
FROM INET-ADDRESS-MIB

applIndex,
applRFC2788Group
FROM NETWORK-SERVICES-MIB

TripItad,
TripId,
TripAppProtocol,
TripAddressFamily,
TripCommunityId,
TripProtocolVersion,
TripSendReceiveMode
FROM TRIP-TC;

Zinman/Walker/Jiang

7

Internet Draft

August 2003

tripMIB MODULE-IDENTITY

LAST-UPDATED "200308110000Z" -- Aug 11, 2003
ORGANIZATION "IETF IPTel Working Group.
Mailing list: iptel@lists.bell-labs.com"

CONTACT-INFO

"Co-editor David Zinman
postal: 265 Ridley Blvd.
Toronto ON, M5M 4N8
Canada
email: dzinman@rogers.com
phone: +1 416 433 4298

Co-editor Dave Walker
SS8 Networks, Inc.
postal: 495 March Road, Suite #500
Ottawa, ON, K2K 3G1

Canada
email: drwalker@ss8.com
phone: +1 613 592 2100

Co-editor Jianping Jiang
SS8 Networks, Inc.
postal: 495 March Road, Suite #500
Ottawa, ON, K2K 3G1
Canada
email: jianping@ss8.com
phone: +1 613 592 2100
"

DESCRIPTION

"The MIB module describing Telephony Routing over IP (TRIP). TRIP is a policy driven inter-administrative domain protocol for advertising the reachability of telephony destinations between location servers (LS), and for advertising attributes of the routes to those destinations.

Copyright (C) The Internet Society (2003). This version of this MIB module is part of RFC xxxx, see the RFC itself for full legal notices."

REVISION "200308110000Z" -- Aug 11, 2003

DESCRIPTION

"The initial version, Published as RFC xxxx."

::= { mib-2 xxxx } -- to be assigned by IANA

tripMIBNotifications OBJECT IDENTIFIER ::= { tripMIB 0 }
tripMIBObjects OBJECT IDENTIFIER ::= { tripMIB 1 }
tripMIBConformance OBJECT IDENTIFIER ::= { tripMIB 2 }
tripMIBNotifObjects OBJECT IDENTIFIER ::= { tripMIB 3 }

tripMIBCompliance OBJECT IDENTIFIER ::= { tripMIBConformance 1 }

Zinman/Walker/Jiang

8

Internet Draft

August 2003

tripMIBGroups OBJECT IDENTIFIER ::= { tripMIBConformance 2 }

--

-- tripCfgTable

--

tripCfgTable OBJECT-TYPE

SYNTAX SEQUENCE OF TripCfgEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"This table contains the common configuration objects applicable to all TRIP applications referenced by the applIndex. Each row represents those objects for a particular TRIP LS present in this system. The instances of TRIP LS's are uniquely identified by the applIndex. The objects in this table SHOULD be nonVolatile and survive a reboot."

::= { tripMIBObjects 1 }

tripCfgEntry OBJECT-TYPE

SYNTAX TripCfgEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"A row of common configuration."

INDEX { applIndex }

::= { tripCfgTable 1 }

TripCfgEntry ::=

SEQUENCE {

tripCfgProtocolVersion	TripProtocolVersion,
tripCfgItad	TripItad,
tripCfgIdentifier	TripId,
tripCfgOperStatus	INTEGER,
tripCfgAdminStatus	INTEGER,
tripCfgAddrIAddrType	InetAddressType,
tripCfgAddr	InetAddress,
tripCfgPort	InetPortNumber,
tripCfgMinItadOriginationInterval	Integer32,
tripCfgMinRouteAdvertisementInterval	Integer32,
tripCfgMaxPurgeTime	Integer32,
tripCfgDisableTime	Integer32,
tripCfgSendReceiveMode	TripSendReceiveMode,
tripCfgStorage	StorageType

}

tripCfgProtocolVersion OBJECT-TYPE

SYNTAX TripProtocolVersion

MAX-ACCESS read-only

STATUS current

DESCRIPTION

Zinman/Walker/Jiang

9

Internet Draft

August 2003

"This object will reflect the version of TRIP supported by this system. It follows the same format as TRIP version information contained in the TRIP messages generated by this TRIP entity."

REFERENCE

```

        "RFC 3291, section 4.2."
    ::= { tripCfgEntry 1 }

tripCfgItad OBJECT-TYPE
    SYNTAX      TripItad
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "The Internet Telephony Administrative domain (ITAD)
        of this LS."
    ::= { tripCfgEntry 2 }

tripCfgIdentifier OBJECT-TYPE
    SYNTAX      TripId
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The object that identifies this TRIP Client."
    ::= { tripCfgEntry 3 }

tripCfgAdminStatus OBJECT-TYPE
    SYNTAX      INTEGER {
                    up(1),
                    down(2)
                }
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "The desired TRIP state.

        up(1) : Set the application to normal operation.

        down(2): Set the application to a state where it will
        not process TRIP messages."
    ::= { tripCfgEntry 4 }

tripCfgOperStatus OBJECT-TYPE
    SYNTAX      INTEGER {
                    up(1),
                    down(2),
                    faulty(3)
                }
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The current operational state of the TRIP protocol."

```

up(1): The application is operating normally, and is processing (receiving and possibly issuing) TRIP requests and responses.

down(2): The application is currently not processing TRIP messages. This occurs if the TRIP application is in an initialization state or if tripCfgAdminStatus is set to down(2).

faulty(3): The application is not operating normally due to a fault in the system.

If tripCfgAdminStatus is down(2) then tripOperStatus SHOULD be down(2). If tripAdminStatus is changed to up(1) then tripOperStatus SHOULD change to up(1) if there is no fault that prevents the TRIP protocol from moving to the up(1) state."

::= { tripCfgEntry 5 }

tripCfgAddrIAddrType OBJECT-TYPE

SYNTAX InetAddressType

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The type of Inet Address of the tripAddr."

REFERENCE

["RFC 3291, section 3."](#)

::= { tripCfgEntry 6 }

tripCfgAddr OBJECT-TYPE

SYNTAX InetAddress

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The network address of the local LS that the peer connects to. The type of address depends on the object tripCfgAddrIAddrType."

REFERENCE

["RFC 3291, section 3."](#)

::= { tripCfgEntry 7 }

tripCfgPort OBJECT-TYPE

SYNTAX InetPortNumber

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"The local tcp/udp port on the local LS that the peer connects to."

::= { tripCfgEntry 8 }

tripCfgMinItadOriginationInterval OBJECT-TYPE

SYNTAX Integer32 (1..2147483647)

Zinman/Walker/Jiang

11

Internet Draft

August 2003

UNITS "Seconds"
MAX-ACCESS read-write
STATUS current
DESCRIPTION
"The minimum amount of time that MUST elapse between
advertisement of the update message that reports changes
within the LS's own ITAD."
DEFVAL { 30 }
::= { tripCfgEntry 9 }

tripCfgMinRouteAdvertisementInterval OBJECT-TYPE

SYNTAX Integer32 (1..2147483647)
UNITS "Seconds"
MAX-ACCESS read-write
STATUS current
DESCRIPTION
"Specifies minimal interval between successive
advertisements to a particular destination from an LS."
DEFVAL { 30 }
::= { tripCfgEntry 10 }

tripCfgMaxPurgeTime OBJECT-TYPE

SYNTAX Integer32 (1..2147483647)
UNITS "Seconds"
MAX-ACCESS read-write
STATUS current
DESCRIPTION
"Indicates the interval that the LS MUST maintain routes
marked as withdrawn in its database."
DEFVAL { 10 }
::= { tripCfgEntry 11 }

tripCfgDisableTime OBJECT-TYPE

SYNTAX Integer32 (1..2147483647)
UNITS "Seconds"
MAX-ACCESS read-write
STATUS current
DESCRIPTION
"Indicates the interval that the TRIP module of the
LS MUST be disabled while routes originated by this
LS with high sequence numbers can be removed."
DEFVAL { 180 }
::= { tripCfgEntry 12 }

tripCfgSendReceiveMode OBJECT-TYPE

SYNTAX TripSendReceiveMode
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "The operational mode of the TRIP entity running on this
 system."
::= { tripCfgEntry 13 }

Zinman/Walker/Jiang

12

Internet Draft

August 2003

tripCfgStorage OBJECT-TYPE
 SYNTAX StorageType
 MAX-ACCESS read-write
 STATUS current
 DESCRIPTION
 "The storage type for this conceptual row."
 DEFVAL { nonVolatile }
 ::= { tripCfgEntry 14 }

--

-- TripRouteTypeTable

--

tripRouteTypeTable OBJECT-TYPE
 SYNTAX SEQUENCE OF TripRouteTypeEntry
 MAX-ACCESS not-accessible
 STATUS current
 DESCRIPTION
 "The TRIP peer Route Type table contains one entry per
 supported protocol - address family pair. The objects in
 this table are volatile and are refreshed after a reboot."
 ::= { tripMIBObjects 2 }

tripRouteTypeEntry OBJECT-TYPE
 SYNTAX TripRouteTypeEntry
 MAX-ACCESS not-accessible
 STATUS current
 DESCRIPTION
 "An entry containing information about the route type
 that a particular TRIP entity supports. Each entry
 represents information about either the local or a remote
 LS peer. The object tripRouteTypePeer is used to
 distinguish this. In the case of a local LS, the
 address/port information will reflect the values
 configured in tripCfgTable. In the case of a remote
 peer, the address/port information will reflect the
 values of an entry in the tripPeerTable."

Implementation need to be aware that if the size of tripRouteTypeAddr exceeds 111 sub-IDs, then OIDs of column instances in this table will have more than 128 sub-IDs and cannot be access using SNMPv1, SNMPv2c, or snmpv3."

```
INDEX { applIndex,
        tripRouteTypeAddrInetType,
        tripRouteTypeAddr,
        tripRouteTypePort,
        tripRouteTypeProtocolId,
        tripRouteTypeAddrFamilyId }
 ::= { tripRouteTypeTable 1 }
```

```
TripRouteTypeEntry ::= SEQUENCE {
```

Zinman/Walker/Jiang

13

Internet Draft

August 2003

```
        tripRouteTypeAddrInetType      InetAddressType,
        tripRouteTypeAddr                InetAddress,
        tripRouteTypePort                InetPortNumber,
        tripRouteTypeProtocolId          TripAppProtocol,
        tripRouteTypeAddrFamilyId        TripAddressFamily,
        tripRouteTypePeer                INTEGER
    }
```

```
tripRouteTypeAddrInetType OBJECT-TYPE
```

```
    SYNTAX      InetAddressType
```

```
    MAX-ACCESS  not-accessible
```

```
    STATUS      current
```

```
    DESCRIPTION
```

```
        "The type of Inet Address of the tripRouteTypeAddr."
```

```
    REFERENCE
```

```
        "RFC 3291, section 3."
```

```
 ::= { tripRouteTypeEntry 1 }
```

```
tripRouteTypeAddr OBJECT-TYPE
```

```
    SYNTAX      InetAddress
```

```
    MAX-ACCESS  not-accessible
```

```
    STATUS      current
```

```
    DESCRIPTION
```

```
        "The network address of this entry's TRIP peer LS."
```

```
    REFERENCE
```

```
        "RFC 3291, section 3."
```

```
 ::= { tripRouteTypeEntry 2 }
```

```
tripRouteTypePort OBJECT-TYPE
```

```
    SYNTAX      InetPortNumber
```

```
    MAX-ACCESS  not-accessible
```

```
    STATUS      current
```

```
    DESCRIPTION
```

"The port for the TCP connection between this and
an associated TRIP peer."
::= { tripRouteTypeEntry 3 }

tripRouteTypeProtocolId OBJECT-TYPE

SYNTAX TripAppProtocol

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The object identifier of a protocol that the associated
peer is using."

::= { tripRouteTypeEntry 4 }

tripRouteTypeAddrFamilyId OBJECT-TYPE

SYNTAX TripAddressFamily

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The object identifier of an address family that the

Zinman/Walker/Jiang

14

Internet Draft

August 2003

associated peer belongs to."
::= { tripRouteTypeEntry 5 }

tripRouteTypePeer OBJECT-TYPE

SYNTAX INTEGER { local(1), remote(2) }

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"This object identifies whether this entry is
associated with a 'local' or 'remote' LS peer."

::= { tripRouteTypeEntry 6 }

--

-- tripSupportedCommunityTable

--

tripSupportedCommunityTable OBJECT-TYPE

SYNTAX SEQUENCE OF TripSupportedCommunityEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The list of TRIP communities that this LS supports. A
TRIP community is a group of destinations that share
common properties.

The TRIP Supported Communities entry is used to group
destinations so that the routing decision can be based

on the identity of the group."

REFERENCE

["RFC 3219, section 5.9"](#)

::= { tripMIBObjects 3 }

tripSupportedCommunityEntry OBJECT-TYPE

SYNTAX TripSupportedCommunityEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"Entry containing information about a community. A TRIP community is a group of destinations that share some common property. This attribute is used so that routing decisions can be based on the identity of the group."

INDEX { applIndex, tripSupportedCommunityId }

::= { tripSupportedCommunityTable 1 }

TripSupportedCommunityEntry ::= SEQUENCE {

tripSupportedCommunityId TripCommunityId,

tripSupportedCommunityItad TripItad,

tripSupportedCommunityStorage StorageType,

tripSupportedCommunityRowStatus RowStatus

}

tripSupportedCommunityId OBJECT-TYPE

Zinman/Walker/Jiang

15

Internet Draft

August 2003

SYNTAX TripCommunityId

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The identifier of the supported Community."

::= { tripSupportedCommunityEntry 1 }

tripSupportedCommunityItad OBJECT-TYPE

SYNTAX TripItad

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The ITAD of the community."

::= { tripSupportedCommunityEntry 2 }

tripSupportedCommunityStorage OBJECT-TYPE

SYNTAX StorageType

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The storage type for this conceptual row. Conceptual

```

        rows having the value 'permanent' need not allow write-
        access to any columnar objects in the row. It is not a
        requirement that this storage be non volatile."
    DEFVAL { nonVolatile }
    ::= { tripSupportedCommunityEntry 3 }

```

tripSupportedCommunityRowStatus OBJECT-TYPE

```

    SYNTAX      RowStatus
    MAX-ACCESS   read-create
    STATUS       current
    DESCRIPTION
        "The row status of the entry. This object is REQUIRED
        to create or delete rows by a manager. A value for
        tripSupportedCommunityItad MUST be set for row creation
        to be successful. If the instance already exists for a
        particular applIndex, the row create operation will
        fail.

        The value of this object has no effect on whether
        other objects in this conceptual row can be modified."
    ::= { tripSupportedCommunityEntry 4 }

```

```

--
-- TripPeerTable
--
    tripPeerTable    OBJECT-TYPE
        SYNTAX      SEQUENCE OF TripPeerEntry
        MAX-ACCESS   not-accessible
        STATUS       current
        DESCRIPTION
            "The TRIP peer table. This table contains one entry per

```

Zinman/Walker/Jiang

16

Internet Draft

August 2003

```

        TRIP peer, and information about the connection with
        the peer."
    ::= { tripMIBObjects 4 }

```

tripPeerEntry OBJECT-TYPE

```

    SYNTAX      TripPeerEntry
    MAX-ACCESS   not-accessible
    STATUS       current
    DESCRIPTION
        "Entry containing information about the connection with
        a TRIP peer.

        Implementation need to be aware that if the size of
        tripPeerRemoteAddr exceeds 113 sub-IDs, then OIDs of
        column instances in this table will have more than 128

```

```

        sub-IDs and cannot be access using SNMPv1, SNMPv2c, or
        snmpv3."
INDEX { applIndex,
        tripPeerRemoteAddrInetType,
        tripPeerRemoteAddr,
        tripPeerRemotePort }
 ::= {tripPeerTable 1}

TripPeerEntry ::= SEQUENCE {
    tripPeerRemoteAddrInetType      InetAddressType,
    tripPeerRemoteAddr              InetAddress,
    tripPeerRemotePort              InetPortNumber,
    tripPeerIdentifier              TripId,
    tripPeerState                   INTEGER,
    tripPeerAdminStatus             INTEGER,
    tripPeerNegotiatedVersion        TripProtocolVersion,
    tripPeerSendReceiveMode         TripSendReceiveMode,
    tripPeerRemoteItad              TripItad,
    tripPeerConnectRetryInterval    Integer32,
    tripPeerMaxRetryInterval        Integer32,
    tripPeerHoldTime                Integer32,
    tripPeerKeepAlive               Integer32,
    tripPeerHoldTimeConfigured      Integer32,
    tripPeerKeepAliveConfigured     Integer32,
    tripPeerMaxPurgeTime            Integer32,
    tripPeerDisableTime             Integer32,
    tripPeerLearned                 TruthValue,
    tripPeerStorage                 StorageType,
    tripPeerRowStatus               RowStatus
}

tripPeerRemoteAddrInetType OBJECT-TYPE
    SYNTAX      InetAddressType
    MAX-ACCESS   not-accessible
    STATUS      current
    DESCRIPTION
        "The type of Inet Address of the tripPeerRemoteAddr."

```

Zinman/Walker/Jiang

17

Internet Draft

August 2003

```

REFERENCE
    "RFC 3291, section 3."
 ::= { tripPeerEntry 1 }

tripPeerRemoteAddr OBJECT-TYPE
    SYNTAX      InetAddress
    MAX-ACCESS   not-accessible
    STATUS      current
    DESCRIPTION

```

"The IP address of this entry's TRIP peer LS."
REFERENCE
"RFC 3291, section 3."
::= { tripPeerEntry 2 }

tripPeerRemotePort OBJECT-TYPE
SYNTAX InetPortNumber
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"The remote port for the TCP connection between the
TRIP peers."
::= { tripPeerEntry 3 }

tripPeerIdentifier OBJECT-TYPE
SYNTAX TripId
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"TRIP identifier of the peer."
::= { tripPeerEntry 4 }

tripPeerState OBJECT-TYPE
SYNTAX INTEGER {
idle(1),
connect(2),
active(3),
openSent(4),
openConfirm(5),
established(6)
}
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"TRIP Peer Finite State Machine state."

idle(1) : The initial state. Local LS refuses all
incoming connections. No application
resources are allocated to processing
information about the remote peer.

connect(2) : Local LS waiting for a transport
protocol connection to be completed to

the peer, and is listening for inbound
transport connections from the peer.

active(3) : Local LS is listening for an inbound connection from the peer, but is not in the process of initiating a connection to the remote peer.

openSent(4) : Local LS has sent an OPEN message to its peer and is waiting for an OPEN message from the remote peer.

openConfirm(5): Local LS has sent an OPEN message to the remote peer, received an OPEN message from the remote peer, and sent a KEEPALIVE message in response to the OPEN. The local LS is now waiting for a KEEPALIVE message or a NOTIFICATION message in response to its OPEN message.

established(6): LS can exchange UPDATE, NOTIFICATION, and KEEPALIVE messages with its peer."

::= { tripPeerEntry 5 }

tripPeerAdminStatus OBJECT-TYPE

SYNTAX INTEGER {
up(1),
down(2)
}

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"This object is used to affect the TRIP connection state.

up(1) : Allow a connection with the peer LS.

down(2) : disconnect the connection from the peer LS and do not allow any further connections to this peer.

If this value is set to down(2) then tripPeerState will have the value of idle(1)."

DEFVAL { up }

::= { tripPeerEntry 6 }

tripPeerNegotiatedVersion OBJECT-TYPE

SYNTAX TripProtocolVersion

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The negotiated version of TRIP running between this

```
    local entity and this peer."  
    ::= { tripPeerEntry 7 }
```

```
tripPeerSendReceiveMode OBJECT-TYPE  
    SYNTAX      TripSendReceiveMode  
    MAX-ACCESS  read-only  
    STATUS      current  
    DESCRIPTION  
        "The operational mode of this peer."  
    ::= { tripPeerEntry 8 }
```

```
tripPeerRemoteItad OBJECT-TYPE  
    SYNTAX      TripItad  
    MAX-ACCESS  read-only  
    STATUS      current  
    DESCRIPTION  
        "The Internet Telephony Administrative domain of  
        this peer."  
    ::= { tripPeerEntry 9 }
```

```
tripPeerConnectRetryInterval OBJECT-TYPE  
    SYNTAX      Integer32 (0..2147483647)  
    UNITS       "Seconds"  
    MAX-ACCESS  read-create  
    STATUS      current  
    DESCRIPTION  
        "Specifies the initial amount of time that will elapse  
        between connection retry. This value SHOULD double  
        after each attempt up to the value of  
        tripPeerMaxRetryInterval. This value MUST always be less  
        than or equal to the value of tripPeerMaxRetryInterval.  
        Attempts to set this value higher than the max retry  
        will not be allowed."  
    DEFVAL      { 120 }  
    ::= { tripPeerEntry 10 }
```

```
tripPeerMaxRetryInterval OBJECT-TYPE  
    SYNTAX      Integer32 (0..2147483647)  
    UNITS       "Seconds"  
    MAX-ACCESS  read-create  
    STATUS      current  
    DESCRIPTION  
        "Specifies the maximum amount of time that will elapse  
        between connection retries. Once the value of  
        tripPeerConnectRetryInterval has reached this value, no  
        more retries will be attempted. Attempts to set this  
        value lower than the retry interval SHOULD not be  
        allowed."  
    DEFVAL      { 360 }
```

::= { tripPeerEntry 11 }

tripPeerHoldTime OBJECT-TYPE

Zinman/Walker/Jiang

20

Internet Draft

August 2003

SYNTAX Integer32 (1..2147483647)

UNITS "Seconds"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The time interval in seconds for the hold timer that is established with the peer. The value of this object is the smaller of the values in tripPeerHoldTimeConfigured and the hold time received in the open message."

::= { tripPeerEntry 12 }

tripPeerKeepAlive OBJECT-TYPE

SYNTAX Integer32 (1..2147483647)

UNITS "Seconds"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Specifies the amount of time that MUST elapse between keep alive messages. This value is negotiated with the remote when a connection is established."

::= { tripPeerEntry 13 }

tripPeerHoldTimeConfigured OBJECT-TYPE

SYNTAX Integer32 (0 | 3..65535)

UNITS "Seconds"

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"Specifies the maximum time that MAY elapse between the receipt of successive keepalive or update message. A value of 0 means that keepalive or update messages will not be sent."

DEFVAL { 240 }

::= { tripPeerEntry 14 }

tripPeerKeepAliveConfigured OBJECT-TYPE

SYNTAX Integer32 (1..2147483647)

UNITS "Seconds"

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"Specifies the amount of time that MUST elapse between

```
        keep alive messages."
DEFVAL { 30 }
::= { tripPeerEntry 15 }
```

```
tripPeerMaxPurgeTime OBJECT-TYPE
    SYNTAX      Integer32 (1..65535)
    UNITS        "Seconds"
    MAX-ACCESS   read-create
    STATUS       current
```

Zinman/Walker/Jiang

21

Internet Draft

August 2003

```
DESCRIPTION
    "Indicates the interval that the LS MUST maintain routes
    marked as withdrawn in its database."
DEFVAL { 10 }
::= { tripPeerEntry 16 }
```

```
tripPeerDisableTime OBJECT-TYPE
    SYNTAX      Integer32 (1..65535)
    UNITS        "Seconds"
    MAX-ACCESS   read-create
    STATUS       current
    DESCRIPTION
        "Indicate the interval that the TRIP module of the remote
        peer LS MUST be disabled while routes originated by the
        local LS with high sequence numbers can be removed."
    DEFVAL { 180 }
    ::= { tripPeerEntry 17 }
```

```
tripPeerLearned OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
        "Indicates whether this entry was learned or
        configured."
    DEFVAL { false }
    ::= { tripPeerEntry 18 }
```

```
tripPeerStorage OBJECT-TYPE
    SYNTAX      StorageType
    MAX-ACCESS   read-create
    STATUS       current
    DESCRIPTION
        "The storage type for this conceptual row.  Conceptual
        rows having the value 'permanent' need not allow write-
        access to any columnar objects in the row. It is not a
        requirement that this storage be non volatile."
```



```
DEFVAL { nonVolatile }
::= { tripPeerEntry 19 }
```

tripPeerRowStatus OBJECT-TYPE

```
SYNTAX      RowStatus
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
```

"The row status of the entry. This object is REQUIRED to create or delete rows remotely by a manager. If the instance already exists for a particular applIndex, the row create operation will fail.

The value of this object has no effect on whether other objects in this conceptual row can be modified.

Zinman/Walker/Jiang

22

Internet Draft

August 2003

Entries in this table can be learned by the TRIP application, or provisioned through this table."
::= { tripPeerEntry 20 }

--

-- TripPeerStatisticsTable

--

tripPeerStatisticsTable OBJECT-TYPE

```
SYNTAX      SEQUENCE OF TripPeerStatisticsEntry
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
```

"The TRIP peer stats table. This table contains one entry per remote TRIP peer, and statistics related to the connection with the remote peer. The objects in this table are volatile."

::= { tripMIBObjects 5 }

tripPeerStatisticsEntry OBJECT-TYPE

```
SYNTAX      TripPeerStatisticsEntry
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
```

"Entry containing information about the connection with a TRIP peer."

AUGMENTS { tripPeerEntry }

::= { tripPeerStatisticsTable 1 }

TripPeerStatisticsEntry ::= SEQUENCE {

tripPeerInUpdates Counter32,

```

tripPeerOutUpdates          Counter32,
tripPeerInTotalMessages     Counter32,
tripPeerOutTotalMessages    Counter32,
tripPeerFsmEstablishedTransitions Counter32,
tripPeerFsmEstablishedTime   DateAndTime,
tripPeerInUpdateElapsedTime  TimeInterval,
tripPeerStateChangeTime     TimeStamp
}

```

tripPeerInUpdates OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of TRIP update messages received from this remote peer since the last restart of this location server."

::= { tripPeerStatisticsEntry 1 }

tripPeerOutUpdates OBJECT-TYPE

SYNTAX Counter32

Zinman/Walker/Jiang

23

Internet Draft

August 2003

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of TRIP update messages sent to this remote peer since the last restart of this LS."

::= { tripPeerStatisticsEntry 2 }

tripPeerInTotalMessages OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The total number of TRIP messages received from the remote peer on this connection since the last restart of this LS."

::= { tripPeerStatisticsEntry 3 }

tripPeerOutTotalMessages OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The total number of outgoing TRIP messages sent to the remote peer since the last restart of this LS."

::= { tripPeerStatisticsEntry 4 }

tripPeerFsmEstablishedTransitions OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of times the remote peer has transitioned
into the established state since the last restart of this
LS."

::= { tripPeerStatisticsEntry 5 }

tripPeerFsmEstablishedTime OBJECT-TYPE

SYNTAX DateAndTime

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Indicates the time and date that this remote peer entered
the 'established' state."

::= { tripPeerStatisticsEntry 6 }

tripPeerInUpdateElapsedTime OBJECT-TYPE

SYNTAX TimeInterval

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Elapsed time in hundredths of seconds since the last
TRIP update message was received from this remote peer."

Zinman/Walker/Jiang

24

Internet Draft

August 2003

::= { tripPeerStatisticsEntry 7 }

tripPeerStateChangeTime OBJECT-TYPE

SYNTAX TimeStamp

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The value of sysUpTime when the last state change of
tripPeerState took place."

::= { tripPeerStatisticsEntry 8 }

-- TRIP Received Route Table. This table contains
-- all routes from all sources. Each entry consists
-- of a route and its associated path attributes.

tripRouteTable OBJECT-TYPE

SYNTAX SEQUENCE OF TripRouteEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The TRIP route table containing information about reachable routes that are to be added to service by the receiving LS. The objects in this table are volatile and are refreshed when this LS rediscovers its route table."

::= { tripMIBObjects 6 }

tripRouteEntry OBJECT-TYPE

SYNTAX TripRouteEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"Information about a route to a called destination."

INDEX { applIndex,
tripRouteAppProtocol,
tripRouteAddressFamily,
tripRouteAddress,
tripRoutePeer
}

::= { tripRouteTable 1 }

TripRouteEntry ::= SEQUENCE {

tripRouteAppProtocol	TripAppProtocol,
tripRouteAddressFamily	TripAddressFamily,
tripRouteAddress	OCTET STRING,
tripRoutePeer	TripId,
tripRouteTRIBMask	BITS,
tripRouteAddressSequenceNumber	Integer32,
tripRouteAddressOriginatorId	TripId,
tripRouteNextHopServerIAddrType	InetAddressType,
tripRouteNextHopServer	InetAddress,
tripRouteNextHopServerPort	InetPortNumber,

Zinman/Walker/Jiang

25

Internet Draft

August 2003

tripRouteNextHopServerItad	TripItad,
tripRouteMultiExitDisc	Unsigned32,
tripRouteLocalPref	Unsigned32,
tripRouteAdvertisementPath	OCTET STRING,
tripRouteRoutedPath	OCTET STRING,
tripRouteAtomicAggregate	TruthValue,
tripRouteUnknown	OCTET STRING,
tripRouteWithdrawn	TruthValue,
tripRouteConverted	TruthValue,
tripRouteReceivedTime	TimeStamp
}	

tripRouteAppProtocol OBJECT-TYPE

```

SYNTAX      TripAppProtocol
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "The protocol for which this entry of the routing table
    is maintained."
 ::= { tripRouteEntry 1 }

tripRouteAddressFamily OBJECT-TYPE
SYNTAX      TripAddressFamily
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "Specifies the type of address for the destination
    route."
 ::= { tripRouteEntry 2 }

tripRouteAddress OBJECT-TYPE
SYNTAX      OCTET STRING (SIZE(1..105))
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "This is the address (prefix) of the family type given
    by Address Family of the destination. It is the prefix
    of addresses reachable from this gateway via the next
    hop server. The SIZE value of 105 has been assigned due
    to the sub identifier of object types length limitation
    as defined in SMIV2."
REFERENCE
    "RFC 3219, section 5.1.1.1."
 ::= { tripRouteEntry 3 }

tripRoutePeer OBJECT-TYPE
SYNTAX      TripId
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "The identifier of the peer where the route information
    was learned."

```

```
 ::= { tripRouteEntry 4 }
```

```

tripRouteTRIBMask OBJECT-TYPE
SYNTAX      BITS {
                adjTribIns(0),
                extTrib(1),
                locTrib(2),

```

```

        adjTribOut(3)
    }
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "Indicates which Telephony Routing Information Base (TRIB)
    this entry belongs to. This is
    a bit-map of possible types. If the bit has a value of
    1, then the entry is a member of the corresponding TRIB
    type. If the bit has a value of 0 then the entry is not
    a member of the TRIP type. The various bit positions
    are:

    0    adjTribIns    The entry is of type adj-TRIBs-ins,
                        stores routing information that has
                        been learned from inbound UPDATE
                        messages.
    1    extTrib       The entry is of type ext-TRIB, the
                        best route for a given destination.
    2    locTrib       The entry is of type loc-TRIB contains
                        the local TRIP routing information
                        that the LS has selected.
    3    adjTribOut    The entry is of type adj-TRIBs-out,
                        stores the information that the local
                        LS has selected for advertisement to
                        its external peers."

REFERENCE
    "RFC 3291, section 3.5."
::= { tripRouteEntry 5 }

```

```

tripRouteAddressSequenceNumber OBJECT-TYPE
    SYNTAX      Integer32 (1..2147483647)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Indicates the version of the destination route
        originated by the LS identified by
        tripRouteAddressOriginatorId intra-domain attribute."
    ::= { tripRouteEntry 6 }

```

```

tripRouteAddressOriginatorId OBJECT-TYPE
    SYNTAX      TripId
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION

```

```
        internal LS that originated the route into the ITAD."  
 ::= { tripRouteEntry 7 }
```

tripRouteNextHopServerIAAddrType OBJECT-TYPE

```
SYNTAX      InetAddressType  
MAX-ACCESS  read-only  
STATUS      current  
DESCRIPTION  
    "The type of Inet Address of the  
    tripRouteNextHopServer."  
REFERENCE  
    "RFC 3291, section 3."  
 ::= { tripRouteEntry 8 }
```

tripRouteNextHopServer OBJECT-TYPE

```
SYNTAX      InetAddress  
MAX-ACCESS  read-only  
STATUS      current  
DESCRIPTION  
    "Indicates the next hop that messages of a given  
    protocol destined for tripRouteAddress SHOULD  
    be sent to."  
 ::= { tripRouteEntry 9 }
```

tripRouteNextHopServerPort OBJECT-TYPE

```
SYNTAX      InetPortNumber  
MAX-ACCESS  read-only  
STATUS      current  
DESCRIPTION  
    "The port of the next hop server that this route  
    will use."  
 ::= { tripRouteEntry 10 }
```

tripRouteNextHopServerItad OBJECT-TYPE

```
SYNTAX      TripItad  
MAX-ACCESS  read-only  
STATUS      current  
DESCRIPTION  
    "Indicates the domain of the next hop."  
 ::= { tripRouteEntry 11 }
```

tripRouteMultiExitDisc OBJECT-TYPE

```
SYNTAX      Unsigned32 (0..4294967295)  
MAX-ACCESS  read-only  
STATUS      current  
DESCRIPTION  
    "The Multiple Exit Discriminator allows an LS to  
    discriminate between, and indicate preference for,  
    otherwise similar routes to a neighbouring domain.  
    A higher value represents a more preferred routing  
    object."
```

REFERENCE

["RFC 3219, section 5.8"](#)

::= { tripRouteEntry 12 }

tripRouteLocalPref OBJECT-TYPE

SYNTAX Unsigned32 (0..4294967295)

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Indicated the local LS's degree of preference for an advertised route destination."

REFERENCE

["RFC 3219, section 4.3.4.7"](#)

::= { tripRouteEntry 13 }

tripRouteAdvertisementPath OBJECT-TYPE

SYNTAX OCTET STRING (SIZE(4..252))

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Identifies the sequence of domains through which this advertisement has passed.

This object is probably best represented as sequence of TripItads. For SMI compatibility, though, it is represented as an OCTET STRING. This object is a sequence of ITADs where each set of 4 octets corresponds to a TRIP ITAD in network byte order."

REFERENCE

["RFC 3219, section 4.3.4.4"](#)

::= { tripRouteEntry 14 }

tripRouteRoutedPath OBJECT-TYPE

SYNTAX OCTET STRING (SIZE(4..252))

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Identifies the ITADs through which messages sent using this route would pass. These are a subset of tripRouteAdvertisementPath.

This object is probably best represented as sequence of TripItads. For SMI compatibility, though, it is represented as OCTET STRING. This object is a sequence of ITADs where each set of 4 octets corresponds to a TRIP ITAD in network byte order."

REFERENCE

["RFC 3219, section 4.3.4.5"](#)

::= { tripRouteEntry 15 }

tripRouteAtomicAggregate OBJECT-TYPE

SYNTAX TruthValue

Zinman/Walker/Jiang

29

Internet Draft

August 2003

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Indicates that a route MAY traverse domains not listed in tripRouteRoutedPath. If an LS selects the less specific route from a set of overlapping routes, then this value returns TRUE."

REFERENCE

["RFC 3219, section 4.3.4.6"](#)

::= { tripRouteEntry 16 }

tripRouteUnknown OBJECT-TYPE

SYNTAX OCTET STRING (SIZE(0..255))

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"This object contains one or more attributes that were not understood, and because they were transitive, were dropped during aggregation. They take the format of a triple <attribute type, attribute length, attribute value>, of variable length. If no attributes were dropped, this returns an OCTET STRING of size 0."

REFERENCE

["RFC 3219, sections 4.3.1, 4.3.2.3"](#)

::= { tripRouteEntry 17 }

tripRouteWithdrawn OBJECT-TYPE

SYNTAX TruthValue

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Indicates if this route is to be removed from service by the receiving LS."

::= { tripRouteEntry 18 }

tripRouteConverted OBJECT-TYPE

SYNTAX TruthValue

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Indicates if this route has been converted to a
different application protocol than it had originally."
::= { tripRouteEntry 19 }

tripRouteReceivedTime OBJECT-TYPE

SYNTAX TimeStamp

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The value of sysUpTime when this route was received."

::= { tripRouteEntry 20 }

Zinman/Walker/Jiang

30

Internet Draft

August 2003

--
-- TRIP Received Route Community Table.
--

tripRouteCommunityTable OBJECT-TYPE

SYNTAX SEQUENCE OF TripRouteCommunityEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"A table containing a list of TRIP communities associated
with a route. Each instance of tripRouteTypeEntry that has
the tripRouteTypePeer object set to remote(2) has an
instance in the tripRouteTable as a parent. The objects
in this table are volatile and are refreshed after a
reboot."

REFERENCE

["RFC 3219, section 5.9."](#)

::= { tripMIBObjects 7 }

tripRouteCommunityEntry OBJECT-TYPE

SYNTAX TripRouteCommunityEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"Information about communities associated with a route.
An entry with a tripRouteAddress of 00 and a
tripRoutePeer of 0 refers to the local LS."

INDEX { applIndex,
tripRouteAppProtocol,
tripRouteAddressFamily,
tripRouteAddress,
tripRoutePeer,
tripRouteCommunityId
}

```
::= { tripRouteCommunityTable 1 }
```

```
TripRouteCommunityEntry ::= SEQUENCE {  
    tripRouteCommunityId    TripCommunityId,  
    tripRouteCommunityItad  TripItad  
}
```

```
tripRouteCommunityId OBJECT-TYPE  
    SYNTAX      TripCommunityId  
    MAX-ACCESS  not-accessible  
    STATUS      current  
    DESCRIPTION  
        "The community identifier."  
    ::= { tripRouteCommunityEntry 1 }
```

```
tripRouteCommunityItad OBJECT-TYPE  
    SYNTAX      TripItad  
    MAX-ACCESS  read-only
```

Zinman/Walker/Jiang

31

Internet Draft

August 2003

```
STATUS      current  
DESCRIPTION  
    "The ITAD associated with this community."  
    ::= { tripRouteCommunityEntry 2 }
```

```
--  
-- tripItadTopologyTable  
--
```

```
tripItadTopologyTable OBJECT-TYPE  
    SYNTAX      SEQUENCE OF TripItadTopologyEntry  
    MAX-ACCESS  not-accessible  
    STATUS      current  
    DESCRIPTION  
        "The sequence of link connections between peers within an  
        ITAD. The objects in this table are volatile and are  
        refreshed after a reboot."  
    ::= { tripMIBObjects 8 }
```

```
tripItadTopologyEntry OBJECT-TYPE  
    SYNTAX      TripItadTopologyEntry  
    MAX-ACCESS  not-accessible  
    STATUS      current  
    DESCRIPTION  
        "Information about a peer of the LS identified by  
        tripItadTopologyOrigId."  
    INDEX { applIndex, tripItadTopologyOrigId }  
    ::= { tripItadTopologyTable 1 }
```

```

TripItadTopologyEntry ::= SEQUENCE {
    tripItadTopologyOrigId    TripId,
    tripItadTopologySeqNum    Unsigned32
}

tripItadTopologyOrigId OBJECT-TYPE
    SYNTAX      TripId
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Indicates the internal LS that originated the ITAD
        topology information into the ITAD."
    ::= { tripItadTopologyEntry 1 }

```

```

tripItadTopologySeqNum OBJECT-TYPE
    SYNTAX      Unsigned32 (1..2147483647)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Indicates the version of the ITAD topology originated
        by the LS identified by tripItadTopologyOrigId."
    ::= { tripItadTopologyEntry 2 }

```

Zinman/Walker/Jiang

32

Internet Draft

August 2003

```

--
-- tripItadTopologyIdTable
--

```

```

tripItadTopologyIdTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF TripItadTopologyIdEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The list of other LS's within the ITAD domain that the
        LS identified by tripItadTopologyOrigId is currently
        peering. Each instance of tripItadTopologyIdEntry has an
        instance in the tripItadTopologyTable as a parent. The
        objects in this table are volatile and are refreshed
        after a reboot."
    ::= { tripMIBObjects 9 }

```

```

tripItadTopologyIdEntry OBJECT-TYPE
    SYNTAX      TripItadTopologyIdEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Information about a peer to the LS identified by

```

```

        tripItadTopologyOrigId."
INDEX { applIndex,
        tripItadTopologyOrigId,
        tripItadTopologyId }
::= { tripItadTopologyIdTable 1 }

TripItadTopologyIdEntry ::= SEQUENCE {
        tripItadTopologyId          TripId
    }

tripItadTopologyId OBJECT-TYPE
    SYNTAX      TripId
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The index into this entry. Indicates the other location
        servers within the ITAD domain that this LS identified
        by tripItadTopologyOrigId is currently peering."
    ::= { tripItadTopologyIdEntry 1 }

```

```

--
-- Notification objects
--

```

```

tripNotifApplIndex    OBJECT-TYPE
    SYNTAX      Integer32 (1..2147483647)
    MAX-ACCESS  accessible-for-notify
    STATUS      current
    DESCRIPTION

```

Zinman/Walker/Jiang

33

Internet Draft

August 2003

```

        "This object contains the applIndex as described in
        RFC 2788. It is used to bind this notification with a
        specific instance of TRIP entity."
    ::= { tripMIBNotifObjects 1 }

```

```

tripNotifPeerAddrInetType OBJECT-TYPE
    SYNTAX      InetAddressType
    MAX-ACCESS  accessible-for-notify
    STATUS      current
    DESCRIPTION
        "The type of Inet Address of the tripNotifPeerAddr."
    REFERENCE
        "RFC 3291, section 3."
    ::= { tripMIBNotifObjects 2 }

```

```

tripNotifPeerAddr OBJECT-TYPE
    SYNTAX      InetAddress

```

MAX-ACCESS accessible-for-notify
 STATUS current
 DESCRIPTION
 "The IP address of this entry's TRIP peer LS. This object
 contains the value of tripPeerRemoteAddr."
 REFERENCE
 ["RFC 3291, section 3."](#)
 ::= { tripMIBNotifObjects 3 }

tripNotifPeerErrCode OBJECT-TYPE

SYNTAX INTEGER {
 messageHeader(1),
 openMessage(2),
 updateMessage(3),
 holdTimerExpired(4),
 finiteStateMachine(5),
 cease(6),
 tripNotification(7)
 }

MAX-ACCESS accessible-for-notify
 STATUS current
 DESCRIPTION

"Notification message of TRIP error. The meaning of this
 value is applicable to the following functions:

messageHeader(1)

- All errors detected while processing the TRIP message header.

openMessage(2)

- All errors detected while processing the OPEN message.

updateMessage(3)

- All errors detected while processing the UPDATE message.

holdTimerExpired(4)

- A notification generated when the hold timer expires.

finiteStateMachine(5)

- All errors detected by the TRIP Finite State Machine.

cease(6)

- Any fatal error condition that the rest of the values do not cover.

tripNotification(7)

```

        - Any error encountered while sending a notification
        message."
 ::= { tripMIBNotifObjects 4 }

```

```

tripNotifPeerErrSubcode OBJECT-TYPE

```

```

    SYNTAX      Integer32 (1..2147483647)

```

```

    MAX-ACCESS  accessible-for-notify

```

```

    STATUS      current

```

```

    DESCRIPTION

```

```

        "The sub error code associated with error code. The
        meaning of this value is dependent on the value of
        tripNotifPeerErrCode.

```

```

        Message Header (1) Error Subcodes:

```

```

        1 - Bad Message Length.

```

```

        2 - Bad Message Type.

```

```

        OPEN Message (2) Error Subcodes:

```

```

        1 - Unsupported Version Number.

```

```

        2 - Bad Peer ITAD.

```

```

        3 - Bad TRIP Identifier.

```

```

        4 - Unsupported Optional Parameter.

```

```

        5 - Unacceptable Hold Time.

```

```

        6 - Unsupported Capability.

```

```

        7 - Capability Mismatch.

```

```

        UPDATE Message (3) Error Subcodes:

```

```

        1 - Malformed Attribute List.

```

```

        2 - Unrecognized Well-known Attribute.

```

```

        3 - Missing Well-known Mandatory Attribute.

```

```

        4 - Attribute Flags Error.

```

```

        5 - Attribute Length Error.

```

```

        6 - Invalid Attribute."

```

```

 ::= { tripMIBNotifObjects 5 }

```

```

--

```

```

-- Notifications

```

```

--

```

```

tripConnectionEstablished NOTIFICATION-TYPE

```

```

    OBJECTS { tripNotifApplIndex,

```

Zinman/Walker/Jiang

35

Internet Draft

August 2003

```

        tripNotifPeerAddrInetType,

```

```

        tripNotifPeerAddr

```

```

    }

```

```

    STATUS      current

```

```

    DESCRIPTION

```

```

        "The TRIP Connection Established event is generated when

```

```

        the TRIP finite state machine enters the ESTABLISHED
        state."
    ::= { tripMIBNotifications 1 }

tripConnectionDropped NOTIFICATION-TYPE
    OBJECTS { tripNotifApplIndex,
               tripNotifPeerAddrInetType,
               tripNotifPeerAddr
             }
    STATUS current
    DESCRIPTION
        "The TRIP Connection Dropped event is generated when the
        TRIP finite state machine leaves the ESTABLISHED state."
    ::= { tripMIBNotifications 2 }

tripFSM NOTIFICATION-TYPE
    OBJECTS { tripNotifApplIndex,
               tripNotifPeerAddrInetType,
               tripNotifPeerAddr,
               tripNotifPeerErrCode,
               tripNotifPeerErrSubcode,
               tripPeerState
             }
    STATUS current
    DESCRIPTION
        "The trip FSM Event is generated when any error is
        detected by the TRIP Finite State Machine."
    ::= { tripMIBNotifications 3 }

tripOpenMessageError NOTIFICATION-TYPE
    OBJECTS { tripNotifApplIndex,
               tripNotifPeerAddrInetType,
               tripNotifPeerAddr,
               tripNotifPeerErrCode,
               tripNotifPeerErrSubcode,
               tripPeerState
             }
    STATUS current
    DESCRIPTION
        "Errors detected while processing the OPEN message."
    ::= { tripMIBNotifications 4 }

tripUpdateMessageError NOTIFICATION-TYPE
    OBJECTS { tripNotifApplIndex,
               tripNotifPeerAddrInetType,
               tripNotifPeerAddr,

```



```

        tripNotifPeerErrCode,
        tripNotifPeerErrSubcode,
        tripPeerState
    }
STATUS    current
DESCRIPTION
    "Errors detected while processing the UPDATE message."
::= { tripMIBNotifications 5 }

tripHoldTimerExpired NOTIFICATION-TYPE
    OBJECTS { tripNotifApplIndex,
        tripNotifPeerAddrInetType,
        tripNotifPeerAddr,
        tripNotifPeerErrCode,
        tripNotifPeerErrSubcode,
        tripPeerState
    }
STATUS    current
DESCRIPTION
    "The system does not receive successive messages within
    the period specified by the negotiated Hold Time."
::= { tripMIBNotifications 6 }

tripConnectionCollision NOTIFICATION-TYPE
    OBJECTS { tripNotifApplIndex }
STATUS    current
DESCRIPTION
    "A pair of LSs tried to simultaneously to establish a
    transport connection to each other."
::= { tripMIBNotifications 7 }

tripCease NOTIFICATION-TYPE
    OBJECTS { tripNotifApplIndex,
        tripNotifPeerAddrInetType,
        tripNotifPeerAddr,
        tripNotifPeerErrCode,
        tripNotifPeerErrSubcode,
        tripPeerState
    }
STATUS    current
DESCRIPTION
    "A TRIP peer MAY choose at any given time to close its TRIP
    connection by sending this notification message. However,
    the Cease notification message MUST NOT be used when a
    fatal error occurs."

::= { tripMIBNotifications 8 }

tripNotificationErr NOTIFICATION-TYPE
    OBJECTS { tripNotifApplIndex }
STATUS    current

```

DESCRIPTION

Zinman/Walker/Jiang

37

Internet Draft

August 2003

"Generated if there is an error detected in a TRIP notification message sent with another cause. Note that the TRIP notification referred to in this object is not an SNMP notification, it is a specific message described in the TRIP specification."

REFERENCE

"[RFC 3219](#), section 6.4."

::= { tripMIBNotifications 9 }

--

-- Compliance Statements

--

tripCompliance MODULE-COMPLIANCE

STATUS current

DESCRIPTION

"The compliance statement for TRIP entities."

MODULE -- this module

MANDATORY-GROUPS { tripConfigGroup,
tripPeerTableConfigGroup,
tripRouteGroup,
tripItadTopologyGroup,
tripPeerTableStatsGroup }

GROUP tripNotificationGroup

DESCRIPTION

"This group is OPTIONAL. A TRIP entity can choose not to send any notifications. If this group is implemented, the tripNotifObjectGroup MUST also be implemented."

GROUP tripNotifObjectGroup

DESCRIPTION

"This group is OPTIONAL. A TRIP entity can choose not to send any notifications. If this group is implemented, the tripNotificationGroup MUST also be implemented."

MODULE NETWORK-SERVICES-MIB

MANDATORY-GROUPS { applRFC2788Group }

::= { tripMIBCompliance 1 }

--

-- Object and event conformance groups

--

tripConfigGroup OBJECT-GROUP

```
OBJECTS {
    tripCfgProtocolVersion,
    tripCfgItad,
    tripCfgIdentifier,
    tripCfgOperStatus,
    tripCfgAdminStatus,
```

Zinman/Walker/Jiang

38

Internet Draft

August 2003

```
    tripCfgAddrIAddrType,
    tripCfgAddr,
    tripCfgPort,
    tripCfgMinItadOriginationInterval,
    tripCfgMinRouteAdvertisementInterval,
    tripCfgMaxPurgeTime,
    tripCfgDisableTime,
    tripCfgSendReceiveMode,
    tripCfgStorage,
    tripSupportedCommunityItad,
    tripSupportedCommunityStorage,
    tripRouteTypePeer,
    tripSupportedCommunityRowStatus
}
STATUS current
DESCRIPTION
    "The global objects for configuring trip."
 ::= { tripMIBGroups 1 }
```

tripPeerTableConfigGroup OBJECT-GROUP

```
OBJECTS {
    tripPeerIdentifier,
    tripPeerState,
    tripPeerAdminStatus,
    tripPeerNegotiatedVersion,
    tripPeerSendReceiveMode,
    tripPeerRemoteItad,
    tripPeerConnectRetryInterval,
    tripPeerMaxRetryInterval,
    tripPeerHoldTime,
    tripPeerKeepAlive,
    tripPeerHoldTimeConfigured,
    tripPeerKeepAliveConfigured,
    tripPeerMaxPurgeTime,
    tripPeerDisableTime,
    tripPeerLearned,
    tripPeerStorage,
    tripPeerRowStatus
}
```

STATUS current
DESCRIPTION
 "The global objects for configuring the TRIP peer
 table."
::= { tripMIBGroups 2 }

tripPeerTableStatsGroup OBJECT-GROUP
OBJECTS {
 tripPeerInUpdates,
 tripPeerOutUpdates,
 tripPeerInTotalMessages,
 tripPeerOutTotalMessages,

Zinman/Walker/Jiang

39

Internet Draft

August 2003

 tripPeerFsmEstablishedTransitions,
 tripPeerFsmEstablishedTime,
 tripPeerInUpdateElapsedTime,
 tripPeerStateChangeTime
 }
STATUS current
DESCRIPTION
 "The global statistics the TRIP peer table."
::= { tripMIBGroups 3 }

tripRouteGroup OBJECT-GROUP
OBJECTS {
 tripRouteTRIBMask,
 tripRouteAddressSequenceNumber,
 tripRouteAddressOriginatorId,
 tripRouteNextHopServerIAddrType,
 tripRouteNextHopServer,
 tripRouteNextHopServerPort,
 tripRouteNextHopServerItad,
 tripRouteMultiExitDisc,
 tripRouteLocalPref,
 tripRouteAdvertisementPath,
 tripRouteRoutedPath,
 tripRouteAtomicAggregate,
 tripRouteUnknown,
 tripRouteWithdrawn,
 tripRouteConverted,
 tripRouteReceivedTime,
 tripRouteCommunityItad
 }

STATUS current
DESCRIPTION
 "The global objects for configuring route attribute."

```
::= { tripMIBGroups 4 }
```

```
tripItadTopologyGroup OBJECT-GROUP
```

```
OBJECTS {
```

```
    tripItadTopologySeqNum,
```

```
    tripItadTopologyId
```

```
}
```

```
STATUS current
```

```
DESCRIPTION
```

```
    "The objects that define the TRIP ITAD topology."
```

```
::= { tripMIBGroups 5 }
```

```
tripNotificationGroup NOTIFICATION-GROUP
```

```
NOTIFICATIONS {
```

```
    tripConnectionEstablished,
```

```
    tripConnectionDropped,
```

```
    tripFSM,
```

```
    tripOpenMessageError,
```

Zinman/Walker/Jiang

40

Internet Draft

August 2003

```
    tripUpdateMessageError,
```

```
    tripHoldTimerExpired,
```

```
    tripConnectionCollision,
```

```
    tripCease,
```

```
    tripNotificationErr
```

```
}
```

```
STATUS current
```

```
DESCRIPTION
```

```
    "A collection of notifications defined for TRIP."
```

```
::= { tripMIBGroups 6 }
```

```
tripNotifObjectGroup OBJECT-GROUP
```

```
OBJECTS {
```

```
    tripNotifApplIndex,
```

```
    tripNotifPeerAddrInetType,
```

```
    tripNotifPeerAddr,
```

```
    tripNotifPeerErrCode,
```

```
    tripNotifPeerErrSubcode
```

```
}
```

```
STATUS current
```

```
DESCRIPTION
```

```
    "The collection of objects that specify information for  
    TRIP notifications."
```

```
::= { tripMIBGroups 7 }
```

END

[7.](#) Security Considerations

The managed objects in this MIB module contain sensitive information since, collectively, they allow tracing and influencing of connections in TRIP devices and provide information of their connection characteristics. As such, improper manipulation of the objects represented by this MIB module MAY result in denial of service to a large number of available routes.

There are a number of management objects defined in this MIB module that have a MAX-ACCESS clause of read-write and/or read-create. Such objects MAY be considered sensitive or vulnerable in some network environments. The support for SET operations in a non-secure environment without proper protection can have a negative effect on network operations. These objects include:

tripCfgItad:

Improper setting of tripCfgItad value can make all peer connections drop and not be re-established.

tripCfgAdminStatus:

Improper setting of tripCfgAdminStatus from up to down will cause the TRIP Location Server stop processing TRIP messages.

tripCfgPort:

Zinman/Walker/Jiang

41

Internet Draft

August 2003

Improper setting of tripCfgPort can cause the failure of a peer establishing a connection.

tripCfgMinItadOriginationInterval,
tripCfgMinRouteAdvertisementInterval:

Improper configuration of these values MAY adversely affect local and global convergence of the routes advertised by this TRIP Location Server.

tripPeerAdminStatus:

Improper setting of tripPeerAdminStatus from up to down can cause significant disruption of the connectivity to the destination via the applicable remote TRIP Location Server peer.

tripPeerConnectRetryInterval, tripPeerMaxRetryInterval:

Improper configuration of these values can cause connections to be disrupted for extremely long time periods when otherwise they would be restored in a relatively short period of time.

tripPeerHoldTimeConfigured, tripPeerKeepAliveConfigured:

Improper configuration of these value can make TRIP peer sessions more fragile and less resilient to denial of service

attacks.

There are a number of managed objects in this MIB module that contain sensitive information regarding the operation of a network. For example, a TRIP Location Server peer's local and remote addresses might be sensitive for ISPs who want to keep interface addresses on TRIP Location Server confidential so as to prevent TRIP Location Server addresses used for a denial of service attack or address spoofing.

Therefore, it is thus important to control even GET access to these objects and possibly to even encrypt the values of these object when sending them over the network via SNMP. Not all versions of SNMP provide features for such a secure environment.

SNMPv1 by itself is not a secure environment. Even if the network itself is secure (for example by using IPSec), even then, there is no control as to who on the secure network is allowed to access and GET/SET (read/change/create/delete) the objects in this MIB module.

It is RECOMMENDED that the implementers consider the security features as provided by the SNMPv3 framework (see [\[RFC3410\]](#), [section 8](#)), including full support for the SNMPv3 cryptographic mechanisms (for authentication and privacy).

Further, deployment of SNMP versions prior to SNMPv3 is NOT RECOMMENDED. Instead, it is RECOMMENDED to deploy SNMPv3 and to enable cryptographic security. It is then a customer/operator responsibility to ensure that the SNMP entity giving access to an

Zinman/Walker/Jiang

42

Internet Draft

August 2003

instance of this MIB module is properly configured to give access to the objects only to those principals (users) that have legitimate rights to indeed GET or SET (change/create/delete) them.

8. Full Copyright Statement

Copyright (C) The Internet Society (2003). All Rights Reserved. This document and translations of it MAY be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation MAY be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this document itself MAY not be modified in any way, such as by removing the copyright notice or references to the Internet Society or other Internet organizations, except as needed for the purpose of developing Internet standards in which case the procedures for copyrights defined in the Internet Standards process MUST be

followed, or as REQUIRED to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by the Internet Society or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

9. Normative References

- [RFC3219] Rosenberg, J., Salama, H. and Squire, M., "Telephony Routing over IP (TRIP)", [RFC 3219](#) January 2002.
- [RFC3291] Daniele, M., Haberman, B., Routhier, S., Schoenwaelder, J., "Textual Conventions for Internet Network Addresses", [RFC 3291](#), May 2002.
- [RFC1657] Willis, S., Burruss, J., and Chu, J., "Definitions of Managed Objects for the Fourth Version of the Border Gateway Protocol (BGP-4) using SMIV2", [RFC 1657](#), July 1994.
- [RFC2578] McCloghrie, K., Perkins, D., Schoenwaelder, J., Case, J., Rose, M. and S. Waldbusser, "Structure of Management Information Version 2 (SMIV2)", STD 58, [RFC 2578](#), April 1999.
- [RFC2579] McCloghrie, K., Perkins, D., Schoenwaelder, J., Case, J.,

Zinman/Walker/Jiang

43

Internet Draft

August 2003

Rose, M. and S. Waldbusser, "Textual Conventions for SMIV2", STD 58, [RFC 2579](#), April 1999.

- [RFC2580] McCloghrie, K., Perkins, D., Schoenwaelder, J., Case, J., Rose, M. and S. Waldbusser, "Conformance Statements for SMIV2", STD 58, [RFC 2580](#), April 1999.
- [RFC2026] Bradner, S., "The Internet Standards Process _ Revision 3", [BCP 9](#), [RFC 2026](#), October 1996.
- [RFC2788] Freed, N., Kiley, S., "Network Services Monitoring MIB", [RFC 2788](#), March 2000.

10. Informative References

- [RFC1771] Rekhter, Y. and Li, T., "Border Gateway Protocol 4 (BGP-4)", [RFC 1771](#), March 1995.
- [RFC3410] Case, J., Mundy, R., Partain, D. and B. Stewart, "Introduction and Applicability Statements for Internet-Standard Management Framework", [RFC 3410](#), December 2002.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.

11. Intellectual Property Notice

The IETF takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; neither does it represent that it has made any effort to identify any such rights. Information on the IETF's procedures with respect to rights in standards-track and standards-related documentation can be found in [BCP 11](#). Copies of claims of rights made available for publication and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF Secretariat.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights which MAY cover technology that MAY be REQUIRED to practice this standard. Please address the information to the IETF Executive Director.

The IETF has been notified of intellectual property rights claimed in regard to some or all of the specification contained in this

Zinman/Walker/Jiang

44

Internet Draft

August 2003

document. For more information consult the online list of claimed rights.

12. Acknowledgments

The authors wish to thank Bert Wijnen, Dan Romascanu, and Jonathan Rosenberg for their insightful comments and suggestions.

Thanks to Kevin Lingle for his invaluable comments, help with MIB things and great ideas.

13. Author's Addresses

David Zinman
Editor
265 Ridley Blvd
Toronto ON M5M 4N8
Canada
phone: +1 416 433 4298
email: dzinman@rogers.com

Dave Walker
SS8 Networks, Inc.
495 March Road, Suite #500
Ottawa, ON K2K 3G1
Canada
Phone: +1 613 592 2100
Email: drwalker@ss8.com

Jianping Jiang
SS8 Networks, Inc.
495 March Road, Suite #500
Ottawa, ON K2K 3G1
Canada
Phone: +1 613 592 2100
Email: jianping@ss8.com