

Network Working Group
Internet Draft
Expiration Date: July 2002

K. Kompella (Juniper Networks)
Y. Rekhter (Juniper Networks)
A. Banerjee (Calient Networks)
J. Drake (Calient Networks)
G. Bernstein (Ciena)
D. Fedyk (Nortel Networks)
E. Mannie (GTS Network)
D. Saha (Tellium)
V. Sharma (Metanoia, Inc.)

IS-IS Extensions in Support of Generalized MPLS

[draft-ietf-isis-gmpls-extensions-06.txt](#)

1. Status of this Memo

This document is an Internet-Draft and is in full conformance with all provisions of [Section 10 of RFC2026](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as ``work in progress.''

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/1id-abstracts.txt>

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

2. Abstract

This document specifies encoding of extensions to the IS-IS routing protocol in support of Generalized Multi-Protocol Label Switching (GMPLS). The description of the extensions is specified in [GMPLS-ROUTING].

3. Summary for Sub-IP Area

3.1. Summary

This document specifies encoding of extensions to the IS-IS routing protocol in support of Generalized Multi-Protocol Label Switching (GMPLS). The description of the extensions is specified in [GMPLS-ROUTING].

3.2. Where does it fit in the Picture of the Sub-IP Work

This work fits squarely in either CCAMP or IS-IS boxes.

3.3. Why is it Targeted at this WG

This draft is targeted at either the CCAMP or IS-IS WGs, because this draft specifies the extensions to the IS-IS routing protocols in support of GMPLS, because GMPLS is within the scope of CCAMP WG, and because IS-IS is within the scope of the IS-IS WG.

3.4. Justification

The WG should consider this document as it specifies the extensions to the IS-IS routing protocols in support of GMPLS.

4. Introduction

This document specifies extensions to the IS-IS routing protocol in support of carrying link state information for Generalized Multi-Protocol Label Switching (GMPLS). The set of required enhancements to IS-IS are outlined in [\[GMPLS-ROUTING\]](#).

5. IS-IS Routing Enhancements

In this section we define the enhancements to the TE properties of GMPLS TE links that can be announced in IS-IS TE LSAs.

In this document, we enhance the sub-TLVs for the extended IS reachability TLV (see [\[ISIS-TE\]](#)) in support of GMPLS. Specifically, we add sub-TLVs for: Outgoing/Incoming Interface Identifier, Link Protection Type, and Interface Switching Capability Descriptor. This brings the list of sub-TLVs of the extended IS reachability TLV to:

Sub-TLV Type	Length	Name
3	4	Administrative group (color)
4	4	Link Local Identifier
5	4	Link Remote Identifier
6	4	IPv4 interface address
8	4	IPv4 neighbor address
9	4	Maximum link bandwidth
10	4	Reservable link bandwidth
11	32	Unreserved bandwidth
18	3	TE Default metric
20	2	Link Protection Type
21	variable	Interface Switching Capability Descriptor
250-254	-	Reserved for cisco specific extensions
255	-	Reserved for future expansion

We further add one new TLV to the TE LSAs.

TLV Type	Length	Name
138 (TBD)	variable	Shared Risk Link Group

Finally, we add one more TLV to the Hello PDUs.

TLV Type	Length	Name
(TBD)	4	Link Identifier

5.1. Link Local Identifier

A Link Local Interface Identifier is a sub-TLV of the extended IS reachability TLV with type 4, and length 4.

5.2. Link Remote Identifier

A Link Remote Identifier is a sub-TLV of the extended IS reachability TLV with type 5, and length 4.

5.3. Link Protection Type

The Link Protection Type is is a sub-TLV (of type 20) of the extended IS reachability TLV, with length two octets, the first of which is a bit vector describing the protection capabilities of the link. They are:

0x01 Extra Traffic
0x02 Unprotected
0x04 Shared
0x08 Dedicated 1:1
0x10 Dedicated 1+1
0x20 Enhanced
0x40 Reserved
0x80 Reserved

5.4. Interface Switching Capability Descriptor

The Interface Switching Capability Descriptor is a sub-TLV (of type 21) of the extended IS reachability TLV. The length is the length of value field in octets. The format of the value field is as shown below:

0								1								2								3							
0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1
+--+--+--+--+--+--+--+--+--+								+--+--+--+--+--+--+--+--+--+								+--+--+--+--+--+--+--+--+--+								+--+--+--+--+--+--+--+--+--+							
Switching Cap								Encoding								Reserved															
+--+--+--+--+--+--+--+--+--+								+--+--+--+--+--+--+--+--+--+								+--+--+--+--+--+--+--+--+--+								+--+--+--+--+--+--+--+--+--+							
								Max LSP Bandwidth at priority 0																							
+--+--+--+--+--+--+--+--+--+								+--+--+--+--+--+--+--+--+--+								+--+--+--+--+--+--+--+--+--+								+--+--+--+--+--+--+--+--+--+							
								Max LSP Bandwidth at priority 1																							
+--+--+--+--+--+--+--+--+--+								+--+--+--+--+--+--+--+--+--+								+--+--+--+--+--+--+--+--+--+								+--+--+--+--+--+--+--+--+--+							
								Max LSP Bandwidth at priority 2																							
+--+--+--+--+--+--+--+--+--+								+--+--+--+--+--+--+--+--+--+								+--+--+--+--+--+--+--+--+--+								+--+--+--+--+--+--+--+--+--+							
								Max LSP Bandwidth at priority 3																							
+--+--+--+--+--+--+--+--+--+								+--+--+--+--+--+--+--+--+--+								+--+--+--+--+--+--+--+--+--+								+--+--+--+--+--+--+--+--+--+							
								Max LSP Bandwidth at priority 4																							
+--+--+--+--+--+--+--+--+--+								+--+--+--+--+--+--+--+--+--+								+--+--+--+--+--+--+--+--+--+								+--+--+--+--+--+--+--+--+--+							
								Max LSP Bandwidth at priority 5																							
+--+--+--+--+--+--+--+--+--+								+--+--+--+--+--+--+--+--+--+								+--+--+--+--+--+--+--+--+--+								+--+--+--+--+--+--+--+--+--+							
								Max LSP Bandwidth at priority 6																							
+--+--+--+--+--+--+--+--+--+								+--+--+--+--+--+--+--+--+--+								+--+--+--+--+--+--+--+--+--+								+--+--+--+--+--+--+--+--+--+							
								Max LSP Bandwidth at priority 7																							
+--+--+--+--+--+--+--+--+--+								+--+--+--+--+--+--+--+--+--+								+--+--+--+--+--+--+--+--+--+								+--+--+--+--+--+--+--+--+--+							
								Switching Capability-specific information																							
+--+--+--+--+--+--+--+--+--+								+--+--+--+--+--+--+--+--+--+								+--+--+--+--+--+--+--+--+--+								+--+--+--+--+--+--+--+--+--+							
								(variable)																							
+--+--+--+--+--+--+--+--+--+								+--+--+--+--+--+--+--+--+--+								+--+--+--+--+--+--+--+--+--+								+--+--+--+--+--+--+--+--+--+							

The Switching Capability (Switching Cap) field contains one of the following values:

- 1 Packet-Switch Capable-1 (PSC-1)
- 2 Packet-Switch Capable-2 (PSC-2)
- 3 Packet-Switch Capable-3 (PSC-3)
- 4 Packet-Switch Capable-4 (PSC-4)
- 51 Layer-2 Switch Capable (L2SC)
- 100 Time-Division-Multiplex Capable (TDM)
- 150 Lambda-Switch Capable (LSC)
- 200 Fiber-Switch Capable (FSC)

The Encoding field contains one of the values specified in [Section 3.1.1](#) of [\[GMPLS-SIG\]](#).

Maximum LSP Bandwidth is encoded as a list of eight 4 octet fields in the IEEE floating point format, with priority 0 first and priority 7 last. The units are bytes (not bits!) per second.

The content of the Switching Capability specific information field

depends on the value of the Switching Capability field.

When the Switching Capability field is PSC-1, PSC-2, PSC-3, or PSC-4, the specific information includes Interface MTU and Minimum LSP Bandwidth. The Interface MTU is encoded as a two octets integer. The Minimum LSP Bandwidth is encoded in a 4 octets field in the IEEE floating point format. The units are bytes (not bits!) per second.

When the Switching Capability field is L2SC, there is no specific information.

When the Switching Capability field is TDM, the specific information includes Minimum LSP Bandwidth, which is encoded in a 4 octets field in the IEEE floating point format. The units are bytes (not bits!) per second.

When the Switching Capability field is LSC, there is no specific information.

The Interface Switching Capability Descriptor sub-TLV may occur more than once within the extended IS reachability TLV (this is needed to handle interfaces that support multiple switching capabilities).

5.5. Shared Risk Link Group TLV

The proposed SRLG (of type 138 TBD) contains a new data structure consisting of:

- 7 octets of System ID and Pseudonode Number
- 1 octet Flag
- 4 octets of IPv4 interface address or 4 octets of an Outgoing Interface Identifier
- 4 octets of IPv4 neighbor address or 4 octets of an Incoming Interface Identifier

and a list of SRLG values, where each element in the list has 4 octets. The length of this TLV is $16 + 4 * (\text{number of SRLG values})$. The Least Significant Bit of the Flag octet indicates whether the interface is numbered (set to 1), or unnumbered (set to 0). All other bits are reserved and should be set to 0.

5.6. Link Identifier for Unnumbered Interfaces

The Link Identifier TLV is carried as part of the Point-to-point ISIS Hello PDUs. The Type field of this TLV is TBD. The Length field of this TLV is set to 4. The Value field of this TLV contains 4 octets that encode the Identifier assigned to the link over which this PDU is to be transmitted by the LSR that transmits the PDU.

6. Security Considerations

The extensions proposed in this document does not raise any new security concerns.

7. Acknowledgements

The authors would like to thank Suresh Katukam, Jonathan Lang and Quaizar Vohra for their comments on the draft.

8. References

[ISIS-TE] Smit, H., Li, T., "IS-IS Extensions for Traffic Engineering",
[draft-ietf-isis-traffic-03.txt](#) (work in progress)

[GMPLS-SIG] Generalized MPLS Group, "Generalized MPLS - Signaling Functional Description", [draft-ietf-mpls-generalized-signaling-04.txt](#) (work in progress)

[GMPLS-ROUTING] "Routing Extensions in Support of Generalized MPLS",
[draft-many-ccamp-gmpls-routing-00.txt](#)

9. Authors' Information

Kireeti Kompella
Juniper Networks, Inc.
1194 N. Mathilda Ave
Sunnyvale, CA 94089
Email: kireeti@juniper.net

Yakov Rekhter
Juniper Networks, Inc.
[1194 N. Mathilda Ave](#)
Sunnyvale, CA 94089
Email: yakov@juniper.net

Ayan Banerjee
Calient Networks
[5853 Rue Ferrari](#)
San Jose, CA 95138
Phone: +1.408.972.3645
Email: abanerjee@calient.net

John Drake
Calient Networks
[5853 Rue Ferrari](#)
San Jose, CA 95138
Phone: (408) 972-3720
Email: jdrake@calient.net

Greg Bernstein
Ciena Corporation
[10480 Ridgeview Court](#)
Cupertino, CA 94014
Phone: (408) 366-4713
Email: greg@ciena.com

Don Fedyk
Nortel Networks Corp.
[600 Technology Park Drive](#)
Billerica, MA 01821
Phone: +1-978-288-4506
Email: dwfedyk@nortelnetworks.com

Eric Mannie
GTS Network Services
RDI Department, Core Network Technology Group
Terhulpsessesteenweg, 6A
[1560](#) Hoeilaart, Belgium
Phone: +32-2-658.56.52
E-mail: eric.mannie@gtsgroup.com

Debanjan Saha
Tellium Optical Systems
[2](#) Crescent Place
P.O. Box 901
Ocean Port, NJ 07757
Phone: (732) 923-4264
Email: dsaha@tellium.com

Vishal Sharma
Metanoia, Inc.
[335](#) Elan Village Lane, Unit 203
San Jose, CA 95134-2539
Phone: +1 408-943-1794
Email: v.sharma@ieee.org

