

IS-IS Working Group  
Internet-Draft  
Intended status: Standards Track  
Expires: September 11, 2019

S. Litkowski  
Orange  
Y. Qu  
Huawei  
P. Sarkar  
Individual  
I. Chen  
The MITRE Corporation  
J. Tantsura  
Individual  
March 10, 2019

YANG Data Model for IS-IS Segment Routing  
draft-ietf-isis-sr-yang-05

## Abstract

This document defines a YANG data model that can be used to configure and manage IS-IS Segment Routing.

## Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on September 11, 2019.

## Copyright Notice

Copyright (c) 2019 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect

Internet-Draft

isis-sr-yang

March 2019

to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

<a href="#">1.</a>	Overview . . . . .	<a href="#">2</a>
<a href="#">2.</a>	Requirements Language . . . . .	<a href="#">3</a>
<a href="#">3.</a>	Tree Diagrams . . . . .	<a href="#">3</a>
<a href="#">4.</a>	IS-IS Segment Routing . . . . .	<a href="#">3</a>
<a href="#">5.</a>	IS-IS Segment Routing configuration . . . . .	<a href="#">6</a>
<a href="#">5.1.</a>	Segment Routing activation . . . . .	<a href="#">6</a>
<a href="#">5.2.</a>	Advertising mapping server policy . . . . .	<a href="#">6</a>
<a href="#">5.3.</a>	IP Fast reroute . . . . .	<a href="#">6</a>
<a href="#">6.</a>	IS-IS Segment Routing YANG Module . . . . .	<a href="#">6</a>
<a href="#">7.</a>	Security Considerations . . . . .	<a href="#">20</a>
<a href="#">8.</a>	Contributors . . . . .	<a href="#">21</a>
<a href="#">9.</a>	Acknowledgements . . . . .	<a href="#">21</a>
<a href="#">10.</a>	IANA Considerations . . . . .	<a href="#">21</a>
<a href="#">11.</a>	Change log for ietf-isis-sr YANG module . . . . .	<a href="#">21</a>
<a href="#">11.1.</a>	From version -03 to version -04 . . . . .	<a href="#">21</a>
<a href="#">11.2.</a>	From version -02 to version -03 . . . . .	<a href="#">21</a>
<a href="#">11.3.</a>	From isis-sr document version -01 to version -02 . . . . .	<a href="#">22</a>
<a href="#">11.4.</a>	From isis-sr document version -00 to version -01 . . . . .	<a href="#">22</a>
11.5.	From isis document version -12 to isis-sr document version -00 . . . . .	<a href="#">22</a>
<a href="#">11.6.</a>	From isis document version -12 to version -13 . . . . .	<a href="#">22</a>
<a href="#">11.7.</a>	From isis document version -09 to version -11 . . . . .	<a href="#">22</a>
<a href="#">11.8.</a>	From isis document version -08 to version -09 . . . . .	<a href="#">22</a>
<a href="#">11.9.</a>	From isis document version -07 to version -08 . . . . .	<a href="#">22</a>
<a href="#">12.</a>	Normative References . . . . .	<a href="#">22</a>
	Authors' Addresses . . . . .	<a href="#">24</a>

## [1.](#) Overview

YANG [[RFC6020](#)] [[RFC7950](#)] is a data definition language used to define the contents of a conceptual data store that allows networked devices to be managed using NETCONF [[RFC6241](#)]. YANG is proving relevant beyond its initial confines, as bindings to other interfaces (e.g., ReST) and encodings other than XML (e.g., JSON) are being defined. Furthermore, YANG data models can be used as the basis for implementation of other interfaces, such as CLI and programmatic

APIs.

This document defines a YANG data model that can be used to configure and manage IS-IS Segment Routing

Litkowski, et al.

Expires September 11, 2019

[Page 2]

---

Internet-Draft

isis-sr-yang

March 2019

[I-D.ietf-isis-segment-routing-extensions] and it is an augmentation to the IS-IS YANG data model.

The YANG modules in this document conform to the Network Management Datastore Architecture (NMDA) [[RFC8342](#)].

## 2. Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [BCP 14](#) [[RFC2119](#)] [[RFC8174](#)] when, and only when, they appear in all capitals, as shown here.

## 3. Tree Diagrams

This document uses the graphical representation of data models defined in [[RFC8340](#)].

## 4. IS-IS Segment Routing

This document defines a model for IS-IS Segment Routing feature. It is an augmentation of the IS-IS base model.

The IS-IS SR YANG module requires support for the base segment routing module [[I-D.ietf-spring-sr-yang](#)], which defines the global segment routing configuration independent of any specific routing protocol configuration, and support of IS-IS base model [[I-D.ietf-isis-yang-isis-cfg](#)] which defines basic IS-IS configuration and state.

The figure below describes the overall structure of the isis-sr YANG module:

```
module: ietf-isis-sr
  augment /rt:routing/rt:control-plane-protocols
```

```

        /rt:control-plane-protocol/isis:isis:
+---rw segment-routing
|   +---rw enabled?    boolean
|   +---rw bindings
|       +---rw advertise
|           |   +---rw policies*    string
|           +---rw receive?        boolean
+---rw protocol-srgb {sr:protocol-srgb}?
    +---rw srgb* [lower-bound upper-bound]
        +---rw lower-bound    uint32
        +---rw upper-bound    uint32
augment /rt:routing/rt:control-plane-protocols

```

```

        /rt:control-plane-protocol/isis:isis/isis:interfaces
        /isis:interface:
+---rw segment-routing
    +---rw adjacency-sid
        +---rw advertise-adj-group-sid* [group-id]
            |   +---rw group-id    uint32
        +---rw advertise-protection?    enumeration
augment /rt:routing/rt:control-plane-protocols
    /rt:control-plane-protocol/isis:isis/isis:interfaces
    /isis:interface/isis:fast-reroute:
+---rw ti-lfa {ti-lfa}?
    +---rw enable?    boolean
augment /rt:routing/rt:control-plane-protocols
    /rt:control-plane-protocol/isis:isis/isis:interfaces
    /isis:interface/isis:fast-reroute/isis:lfa/isis:remote-lfa:
+---rw use-segment-routing-path?    boolean {remote-lfa-sr}?
augment /rt:routing/rt:control-plane-protocols
    /rt:control-plane-protocol/isis:isis/isis:interfaces
    /isis:interface/isis:adjacencies/isis:adjacency:
+---ro adjacency-sid* [value]
    +---ro af?                                iana-rt-types:address-family
    +---ro value                                uint32
    +---ro weight?                              uint8
    +---ro protection-requested?    boolean
augment /rt:routing/rt:control-plane-protocols
    /rt:control-plane-protocol/isis:isis/isis:database
    /isis:level-db/isis:lsp/isis:router-capabilities:
+---ro sr-capability
|   +---ro flags?                                bits

```

```

|   +--ro global-blocks
|   |   +--ro global-block*
|   |   |   +--ro range-size?    uint32
|   |   |   +--ro sid-sub-tlv
|   |   |   |   +--ro sid?    uint32
+--ro sr-algorithms
|   +--ro sr-algorithm*    uint8
+--ro local-blocks
|   +--ro local-block*
|   |   +--ro range-size?    uint32
|   |   +--ro sid-sub-tlv
|   |   |   +--ro sid?    uint32
+--ro srms-preference
|   +--ro preference?    uint8
augment /rt:routing/rt:control-plane-protocols
|   /rt:control-plane-protocol/isis:isis/isis:database
|   /isis:level-db/isis:lsp/isis:extended-is-neighbor
|   /isis:neighbor:
+--ro sid-list* [value]

```

```

+--ro flags?    bits
+--ro weight?    uint8
+--ro neighbor-id?    isis:system-id
+--ro value    uint32
augment /rt:routing/rt:control-plane-protocols
|   /rt:control-plane-protocol/isis:isis/isis:database
|   /isis:level-db/isis:lsp/isis:mt-is-neighbor/isis:neighbor:
+--ro sid-list* [value]
|   +--ro flags?    bits
|   +--ro weight?    uint8
|   +--ro neighbor-id?    isis:system-id
|   +--ro value    uint32
augment /rt:routing/rt:control-plane-protocols
|   /rt:control-plane-protocol/isis:isis/isis:database
|   /isis:level-db/isis:lsp/isis:extended-ipv4-reachability
|   /isis:prefixes:
+--ro sid-list* [value]
|   +--ro flags?    bits
|   +--ro algorithm?    uint8
|   +--ro value    uint32
augment /rt:routing/rt:control-plane-protocols
|   /rt:control-plane-protocol/isis:isis/isis:database

```

```

        /isis:level-db/isis:lsp/isis:mt-extended-ipv4-reachability
        /isis:prefixes:
+---ro sid-list* [value]
+---ro flags?      bits
+---ro algorithm?  uint8
+---ro value       uint32
augment /rt:routing/rt:control-plane-protocols
        /rt:control-plane-protocol/isis:isis/isis:database
        /isis:level-db/isis:lsp/isis:ipv6-reachability/isis:prefixes:
+---ro sid-list* [value]
+---ro flags?      bits
+---ro algorithm?  uint8
+---ro value       uint32
augment /rt:routing/rt:control-plane-protocols
        /rt:control-plane-protocol/isis:isis/isis:database
        /isis:level-db/isis:lsp/isis:mt-ipv6-reachability
        /isis:prefixes:
+---ro sid-list* [value]
+---ro flags?      bits
+---ro algorithm?  uint8
+---ro value       uint32
augment /rt:routing/rt:control-plane-protocols
        /rt:control-plane-protocol/isis:isis/isis:database
        /isis:level-db/isis:lsp:
+---ro segment-routing-bindings* [fec range]
+---ro fec          string

```

```

+---ro range      uint16
+---ro flags?     bits
+---ro binding
+---ro prefix-sid
+---ro sid-list* [value]
+---ro flags?     bits
+---ro algorithm? uint8
+---ro value      uint32

```

## [5. IS-IS Segment Routing configuration](#)

### [5.1. Segment Routing activation](#)

Activation of segment-routing IS-IS is done by setting the "enable" leaf to true. This triggers advertisement of segment-routing

extensions based on the configuration parameters that have been setup using the base segment routing module.

### [5.2.](#) Advertising mapping server policy

The base segment routing module defines mapping server policies. By default, IS-IS will not advertise nor receive any mapping server entry. The IS-IS segment-routing module allows to advertise one or multiple mapping server policies through the "bindings/advertise/policies" leaf-list. The "bindings/receive" leaf allows to enable the reception of mapping server entries.

### [5.3.](#) IP Fast reroute

IS-IS SR model augments the fast-reroute container under interface. It brings the ability to activate TI-LFA (topology independent LFA) and also enhances remote LFA to use segment-routing tunneling instead of LDP.

## [6.](#) IS-IS Segment Routing YANG Module

```
<CODE BEGINS> file "ietf-isis-sr@2019-03-06.yang"
module ietf-isis-sr {
  namespace "urn:ietf:params:xml:ns:"
    + "yang:ietf-isis-sr";
  prefix isis-sr;

  import ietf-routing {
    prefix "rt";
  }

  import ietf-segment-routing-common {
```

```
  prefix "sr-cmn";
}
```

```
import ietf-segment-routing {
  prefix "sr";
}
```

```

import ietf-isis {
prefix "isis";
}

import iana-routing-types {
prefix "iana-rt-types";
}

organization
  "IETF LSR - LSR Working Group";

contact
  "WG List:  <mailto:lsr@ietf.org>

  Editor:    Stephane Litkowski
             <mailto:stephane.litkowski@orange.com>

  Author:    Acee Lindem
             <mailto:acee@cisco.com>
  Author:    Yingzhen Qu
             <mailto:yingzhen.qu@huawei.com>
  Author:    Pushpasis Sarkar
             <mailto:pushpasis.ietf@gmail.com>
  Author:    Ing-Wher Chen
             <mailto:ingwherchen@mitre.org>
  Author:    Jeff Tantsura
             <mailto:jefftant.ietf@gmail.com>

  ";

description
  "The YANG module defines a generic configuration model for
  Segment routing ISIS extensions common across all of the vendor
  implementations.";

revision 2019-03-06 {
description
  "Initial revision.";
reference "RFC XXXX";
}

```



```

/* Features */

feature remote-lfa-sr {
    description
        "Enhance rLFA to use SR path.";
}

feature ti-lfa {
    description
        "Enhance IPFRR with ti-lfa
        support";
}

/* Groupings */

grouping sid-sub-tlv {
    description "SID/Label sub-TLV grouping.";
    container sid-sub-tlv {
        description
            "Used to advertise the SID/Label associated with a
            prefix or adjacency.";
        leaf sid {
            type uint32;
        }
        description
            "Segment Identifier (SID) - A 20 bit label or
            32 bit SID.";
    }
}

grouping sr-capability {
    description
        "SR capability grouping.";
    container sr-capability {
        description
            "Segment Routing capability.";
        leaf flags {
            type bits {
                bit mpls-ipv4 {
                    position 0;
                }
            }
            description
                "If set, then the router is capable of
                processing SR MPLS encapsulated IPv4 packets
                on all interfaces.";
        }
    }
}

```

```
    }
    bit mpls-ipv6 {
        position 1;
        description
            "If set, then the router is capable of
             processing SR MPLS encapsulated IPv6 packets
             on all interfaces.";
    }
}
description
    "Flags.";
}
container global-blocks {
    description
        "Segment Routing Global Blocks.";
    list global-block {
        description "Segment Routing Global Block.";
        leaf range-size {
            type uint32;
            description "The SID range.";
        }
        uses sid-sub-tlv;
    }
}
}

grouping sr-algorithm {
    description
        "SR algorithm grouping.";
    container sr-algorithms {
        description "All SR algorithms.";
        leaf-list sr-algorithm {
            type uint8;
            description
                "The Segment Routing (SR) algorithms that the router is
                 currently using.";
        }
    }
}

grouping srlb {
    description
        "SR Local Block grouping.";
    container local-blocks {
        description "List of SRLBs.";
    }
}
```

```
list local-block {
  description "Segment Routing Local Block.";
```

```
    leaf range-size {
      type uint32;
      description "The SID range.";
    }
    uses sid-sub-tlv;
  }
}

grouping srms-preference {
  description "The SRMS preference TLV is used to advertise
    a preference associated with the node that acts
    as an SR Mapping Server.";
  container srms-preference {
    description "SRMS Preference TLV.";
    leaf preference {
      type uint8 {
        range "0 .. 255";
      }
      description "SRMS preference TLV, vlaue from 0 to 255.";
    }
  }
}

grouping adjacency-state {
  description
    "This group will extend adjacency state.";
  list adjacency-sid {
    key value;
    config false;
    leaf af {
      type iana-rt-types:address-family;
      description
        "Address-family associated with the
        segment ID";
    }
    leaf value {
      type uint32;
      description
```

```

        "Value of the Adj-SID.";
    }
    leaf weight {
        type uint8;
        description
            "Weight associated with
             the adjacency SID.";
    }
    leaf protection-requested {

```

```

        type boolean;
        description
            "Describe if the adjacency SID
             must be protected.";
    }
    description
        "List of adjacency Segment IDs.";
}
}

grouping prefix-segment-id {
    description
        "This group defines segment routing extensions
         for prefixes.";

    list sid-list {
        key value;

        leaf flags {
            type bits {
                bit readvertisement {
                    position 7;
                    description
                        "If set, then the prefix to
                         which this Prefix-SID is attached,
                         has been propagated by the
                         router either from another level
                         or from redistribution.";
                }
                bit php {
                    position 5;
                    description

```

```

        "If set, then the penultimate hop MUST NOT
        pop the Prefix-SID before delivering the packet
        to the node that advertised the Prefix-SID.";
    }
    bit explicit-null {
        position 4;
        description
            "If set, any upstream neighbor of
            the Prefix-SID originator MUST replace
            the Prefix-SID with a
            Prefix-SID having an
            Explicit-NULL value (0 for IPv4 and 2 for
            IPv6) before forwarding the packet.";
    }
    bit value {
        position 3;

```

```

        description
            "If set, then the Prefix-SID carries a
            value (instead of an index).
            By default the flag is UNSET.";
    }
    bit local {
        position 2;
        description
            "If set, then the value/index carried by
            the Prefix-SID has local significance.
            By default the flag is UNSET.";
    }
}
description
    "Describes flags associated with the
    segment ID.";
}

leaf algorithm {
    type uint8;
    description
        "Algorithm to be used for path computation.";
}
leaf value {
    type uint32;

```

```

        description
            "Value of the prefix-SID.";
    }
    description
        "List of segments.";
}

grouping adjacency-segment-id {
    description
        "This group defines segment routing extensions
        for adjacencies.";

    list sid-list {
        key value;

        leaf flags {
            type bits {
                bit address-family {
                    position 7;
                    description
                        "If unset, then the Adj-SID refers
                        to an adjacency with outgoing IPv4 encapsulation.

```

```

        If set then the Adj-SID refers to an adjacency
        with outgoing IPv6 encapsulation.";
    }
    bit backup {
        position 6;
        description
            "If set, the Adj-SID refers to an
            adjacency being protected
            (e.g.: using IPFRR or MPLS-FRR)";
    }
    bit value {
        position 5;
        description
            "If set, then the SID carries a
            value (instead of an index).
            By default the flag is SET.";
    }
    bit local {

```

```

        position 4;
        description
            "If set, then the value/index carried by
             the SID has local significance.
             By default the flag is SET.";
    }
    bit set {
        position 3;
        description
            "When set, the S-Flag indicates that the
             Adj-SID refers to a set of adjacencies.";
    }
    bit persistent {
        position 2;
        description
            "When set, the P-Flag indicates that the
             Adj-SID is persistently allocated.";
    }
}

description
    "Describes flags associated with the
     segment ID.";
}
leaf weight {
    type uint8;
    description
        "The value represents the weight of the Adj-SID
         for the purpose of load balancing.";
}

```

```

leaf neighbor-id {
    type isis:system-id;
    description
        "Describes the system ID of the neighbor
         associated with the SID value. This is only
         used on LAN adjacencies.";
}
leaf value {
    type uint32;
    description
        "Value of the Adj-SID.";
}

```

```

    }
    description
        "List of segments.";
}
}

grouping segment-routing-binding-tlv {
    list segment-routing-bindings {
        key "fec range";

        leaf fec {
            type string;
            description
                "IP (v4 or v6) range to be bound to SIDs.";
        }

        leaf range {
            type uint16;
            description
                "Describes number of elements to assign
                a binding to.";
        }

        leaf flags {
            type bits {
                bit address-family {
                    position 7;
                    description
                        "If unset, then the Prefix FEC
                        carries an IPv4 Prefix.
                        If set then the Prefix FEC carries an
                        IPv6 Prefix.";
                }
                bit mirror {
                    position 6;
                    description
                        "Set if the advertised SID/path

```

```

        corresponds to a mirrored context.";
    }
    bit flooding {
        position 5;

```



```

    description
        "If the S bit is set(1),
        the IS-IS Router CAPABILITY TLV
        MUST be flooded across the entire routing domain.
        If the S bit is
        not set(0), the TLV MUST NOT be leaked between levels.
        This bit MUST NOT be altered during the TLV leaking.";
    }
    bit down {
        position 4;
        description
            "When the IS-IS Router CAPABILITY TLV is
            leaked from level-2 to level-1, the D bit
            MUST be set. Otherwise, this bit MUST
            be clear. IS-IS Router capability TLVs
            with the D bit set MUST NOT
            be leaked from level-1 to level-2.
            This is to prevent TLV looping.";
    }
    bit attached {
        position 3;
        description
            "The originator of the SID/Label Binding TLV MAY set the
            A bit in order to signal that the prefixes and SIDs
            advertised in the SID/Label Binding TLV are directly
            connected to their originators.";
    }
}
description
    "Flags of the binding.";
}

container binding {
    container prefix-sid {
        uses prefix-segment-id;
        description
            "Binding prefix SID to the range.";
    }
    description
        "Bindings associated with the range.";
}

description

```

```
        "This container describes list of SID/Label bindings.
        ISIS reference is TLV 149.";
    }
    description
        "Defines binding TLV for database.";
}

/* Cfg */

augment "/rt:routing/" +
    "rt:control-plane-protocols/rt:control-plane-protocol"+
    "/isis:isis" {
    when "/rt:routing/rt:control-plane-protocols/"+
        "rt:control-plane-protocol/rt:type = 'isis:isis'" {
        description
            "This augment ISIS routing protocol when used";
    }
    description
        "This augments ISIS protocol configuration
        with segment routing.";

    uses sr:sr-controlplane;
    container protocol-srgb {
        if-feature sr:protocol-srgb;
        uses sr-cmn:srgb;
        description
            "Per-protocol SRGB.";
    }
}

augment "/rt:routing/" +
    "rt:control-plane-protocols/rt:control-plane-protocol"+
    "/isis:isis/isis:interfaces/isis:interface" {
    when "/rt:routing/rt:control-plane-protocols/"+
        "rt:control-plane-protocol/rt:type = 'isis:isis'" {
        description
            "This augment ISIS routing protocol when used";
    }
    description
        "This augments ISIS protocol configuration
        with segment routing.";

    uses sr:igp-interface;
}

augment "/rt:routing/" +
    "rt:control-plane-protocols/rt:control-plane-protocol"+
```

"/isis:isis/isis:interfaces/isis:interface"+

Internet-Draft

isis-sr-yang

March 2019

```
    "/isis:fast-reroute" {
when "/rt:routing/rt:control-plane-protocols/"+
    "rt:control-plane-protocol/rt:type = 'isis:isis'" {
    description
        "This augment ISIS routing protocol when used";
}
description
    "This augments ISIS IP FRR with TILFA.";

container ti-lfa {
    if-feature ti-lfa;
    leaf enable {
        type boolean;
        description
            "Enables TI-LFA computation.";
    }
    description
        "TILFA configuration.";
}
}

augment "/rt:routing/" +
    "rt:control-plane-protocols/rt:control-plane-protocol"+
    "/isis:isis/isis:interfaces/isis:interface"+
    "/isis:fast-reroute/isis:lfa/isis:remote-lfa" {
when "/rt:routing/rt:control-plane-protocols/"+
    "rt:control-plane-protocol/rt:type = 'isis:isis'" {
    description
        "This augment ISIS routing protocol when used";
}
description
    "This augments ISIS remoteLFA config with
        use of segment-routing path.";

leaf use-segment-routing-path {
    if-feature remote-lfa-sr;
    type boolean;
    description
        "force remote LFA to use segment routing
            path instead of LDP path.";
```

```

    }
}

/* Operational states */

augment "/rt:routing/" +
    "rt:control-plane-protocols/rt:control-plane-protocol"+
    "/isis:isis/isis:interfaces/isis:interface" +

```

```

    "/isis:adjacencies/isis:adjacency" {
when "/rt:routing/rt:control-plane-protocols/"+
    "rt:control-plane-protocol/rt:type = 'isis:isis'" {
    description
        "This augment ISIS routing protocol when used";
    }
description
    "This augments ISIS protocol configuration
        with segment routing.";

    uses adjacency-state;
}

augment "/rt:routing/" +
    "rt:control-plane-protocols/rt:control-plane-protocol"+
    "/isis:isis/isis:database/isis:level-db/isis:lsp"+
    "/isis:router-capabilities" {
when "/rt:routing/rt:control-plane-protocols/"+
    "rt:control-plane-protocol/rt:type = 'isis:isis'" {
    description
        "This augment ISIS routing protocol when used";
    }
description
    "This augments ISIS protocol LSDB router capability.";

    uses sr-capability;
    uses sr-algorithm;
    uses srlb;
    uses srms-preference;
}

augment "/rt:routing/" +
    "rt:control-plane-protocols/rt:control-plane-protocol"+

```

```

        "/isis:isis/isis:database/isis:level-db/isis:lsp"+
        "/isis:extended-is-neighbor/isis:neighbor" {
when "/rt:routing/rt:control-plane-protocols/"+
    "rt:control-plane-protocol/rt:type = 'isis:isis'" {
    description
        "This augment ISIS routing protocol when used";
    }
description
    "This augments ISIS protocol LSDB neighbor.";
    uses adjacency-segment-id;
}

augment "/rt:routing/" +
    "rt:control-plane-protocols/rt:control-plane-protocol"+
    "/isis:isis/isis:database/isis:level-db/isis:lsp"+

```

```

        "/isis:mt-is-neighbor/isis:neighbor" {
when "/rt:routing/rt:control-plane-protocols/"+
    "rt:control-plane-protocol/rt:type = 'isis:isis'" {
    description
        "This augment ISIS routing protocol when used";
    }
description
    "This augments ISIS protocol LSDB neighbor.";
    uses adjacency-segment-id;
}

augment "/rt:routing/" +
    "rt:control-plane-protocols/rt:control-plane-protocol"+
    "/isis:isis/isis:database/isis:level-db/isis:lsp"+
    "/isis:extended-ipv4-reachability/isis:prefixes" {
when "/rt:routing/rt:control-plane-protocols/"+
    "rt:control-plane-protocol/rt:type = 'isis:isis'" {
    description
        "This augment ISIS routing protocol when used";
    }
description
    "This augments ISIS protocol LSDB prefix.";
    uses prefix-segment-id;
}

augment "/rt:routing/" +

```

```

        "rt:control-plane-protocols/rt:control-plane-protocol"+
        "/isis:isis/isis:database/isis:level-db/isis:lsp"+
        "/isis:mt-extended-ipv4-reachability/isis:prefixes" {
when "/rt:routing/rt:control-plane-protocols/"+
    "rt:control-plane-protocol/rt:type = 'isis:isis'" {
    description
        "This augment ISIS routing protocol when used";
    }
description
    "This augments ISIS protocol LSDB prefix.";
uses prefix-segment-id;
}

augment "/rt:routing/" +
    "rt:control-plane-protocols/rt:control-plane-protocol"+
    "/isis:isis/isis:database/isis:level-db/isis:lsp"+
    "/isis:ipv6-reachability/isis:prefixes" {
when "/rt:routing/rt:control-plane-protocols/"+
    "rt:control-plane-protocol/rt:type = 'isis:isis'" {
    description
        "This augment ISIS routing protocol when used";
    }
}

```

```

    description
        "This augments ISIS protocol LSDB prefix.";
    uses prefix-segment-id;
}

augment "/rt:routing/" +
    "rt:control-plane-protocols/rt:control-plane-protocol"+
    "/isis:isis/isis:database/isis:level-db/isis:lsp"+
    "/isis:mt-ipv6-reachability/isis:prefixes" {
when "/rt:routing/rt:control-plane-protocols/"+
    "rt:control-plane-protocol/rt:type = 'isis:isis'" {
    description
        "This augment ISIS routing protocol when used";
    }
description
    "This augments ISIS protocol LSDB prefix.";
uses prefix-segment-id;
}

```

```

augment "/rt:routing/" +
    "rt:control-plane-protocols/rt:control-plane-protocol"+
    "/isis:isis/isis:database/isis:level-db/isis:lsp" {
when "/rt:routing/rt:control-plane-protocols/" +
    "rt:control-plane-protocol/rt:type = 'isis:isis'" {
    description
        "This augment ISIS routing protocol when used";
    }
    description
        "This augments ISIS protocol LSDB.";
    uses segment-routing-binding-tlv;
}

/* Notifications */

}
<CODE ENDS>

```

## [7.](#) Security Considerations

Configuration and state data defined in this document are designed to be accessed via the NETCONF protocol [[RFC6241](#)].

As IS-IS is an IGP protocol (critical piece of the network), ensuring stability and security of the protocol is mandatory for the network service.

Litkowski, et al.	Expires September 11, 2019	[Page 20]
-------------------	----------------------------	-----------

---

Internet-Draft	isis-sr-yang	March 2019
----------------	--------------	------------

Authors recommends to implement NETCONF access control model ([[RFC6536](#)]) to restrict access to all or part of the configuration to specific users.

## [8.](#) Contributors

Authors would like to thank Derek Yeung, Acee Lindem, Yi Yang for their major contributions to the draft.

## [9.](#) Acknowledgements

Author affiliation with The MITRE Corporation is provided for

identification purposes only, and is not intended to convey or imply MITRE's concurrence with, or support for, the positions, opinions or viewpoints expressed. MITRE has approved this document for Public Release, Distribution Unlimited, with Public Release Case Number 18-3281.

## 10. IANA Considerations

The IANA is requested to assign two new URIs from the IETF XML registry ([[RFC3688](#)]). Authors are suggesting the following URI:

URI: urn:ietf:params:xml:ns:yang:ietf-isis-sr  
Registrant Contact: IS-IS WG  
XML: N/A, the requested URI is an XML namespace

This document also requests one new YANG module name in the YANG Module Names registry ([[RFC6020](#)]) with the following suggestion :

name: ietf-isis-sr  
namespace: urn:ietf:params:xml:ns:yang:ietf-isis-sr  
prefix: isis-sr  
reference: RFC XXXX

## 11. Change log for ietf-isis-sr YANG module

### 11.1. From version -03 to version -04

- o Fixed yang module indentations.

### 11.2. From version -02 to version -03

- o Change address-family type according to routing types.

### 11.3. From isis-sr document version -01 to version -02

- o NMDA compliancy.
- o Added SRLB in configuration and LSDB.



- o Added SR capability in LSDB.
- o Added SR algorithms in LSDB.
- o Added SRMS preference in LSDB.
- o Alignment with iana-rt-types module.
- o Align binding SID with [draft-ietf-isis-segment-routing-extensions-13](#).

#### [11.4](#). From isis-sr document version -00 to version -01

- o Added P-Flag in Adj-SID.

#### [11.5](#). From isis document version -12 to isis-sr document version -00

- o Separate document for IS-IS SR extensions.

#### [11.6](#). From isis document version -12 to version -13

- o Align with new segment routing common module.

#### [11.7](#). From isis document version -09 to version -11

- o Fixed XPATH in 'when' expressions.

#### [11.8](#). From isis document version -08 to version -09

- o Align to [draft-ietf-netmod-routing-cfg-23](#).

#### [11.9](#). From isis document version -07 to version -08

- o Align to [draft-ietf-netmod-routing-cfg-21](#).

## [12](#). Normative References

[I-D.ietf-isis-segment-routing-extensions]

Previdi, S., Ginsberg, L., Filsfils, C., Bashandy, A., Gredler, H., Litkowski, S., Decraene, B., and J. Tantsura, "IS-IS Extensions for Segment Routing", [draft-ietf-isis-segment-routing-extensions-22](#) (work in progress).

- [I-D.ietf-isis-yang-isis-cfg]  
Litkowski, S., Yeung, D., Lindem, A., Zhang, Z., and L. Lhotka, "YANG Data Model for IS-IS Protocol", [draft-ietf-isis-yang-isis-cfg-35](#) (work in progress), March 2019.
- [I-D.ietf-spring-sr-yang]  
Litkowski, S., Qu, Y., Sarkar, P., and J. Tantsura, "YANG Data Model for Segment Routing", [draft-ietf-spring-sr-yang-08](#) (work in progress), December 2017.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC3688] Mealling, M., "The IETF XML Registry", [BCP 81](#), [RFC 3688](#), DOI 10.17487/RFC3688, January 2004, <<https://www.rfc-editor.org/info/rfc3688>>.
- [RFC6020] Bjorklund, M., Ed., "YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF)", [RFC 6020](#), DOI 10.17487/RFC6020, October 2010, <<https://www.rfc-editor.org/info/rfc6020>>.
- [RFC6241] Enns, R., Ed., Bjorklund, M., Ed., Schoenwaelder, J., Ed., and A. Bierman, Ed., "Network Configuration Protocol (NETCONF)", [RFC 6241](#), DOI 10.17487/RFC6241, June 2011, <<https://www.rfc-editor.org/info/rfc6241>>.
- [RFC6536] Bierman, A. and M. Bjorklund, "Network Configuration Protocol (NETCONF) Access Control Model", [RFC 6536](#), DOI 10.17487/RFC6536, March 2012, <<https://www.rfc-editor.org/info/rfc6536>>.
- [RFC7950] Bjorklund, M., Ed., "The YANG 1.1 Data Modeling Language", [RFC 7950](#), DOI 10.17487/RFC7950, August 2016, <<https://www.rfc-editor.org/info/rfc7950>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in [RFC 2119](#) Key Words", [BCP 14](#), [RFC 8174](#), DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.
- [RFC8340] Bjorklund, M. and L. Berger, Ed., "YANG Tree Diagrams", [BCP 215](#), [RFC 8340](#), DOI 10.17487/RFC8340, March 2018, <<https://www.rfc-editor.org/info/rfc8340>>.

Internet-Draft

isis-sr-yang

March 2019

[RFC8342] Bjorklund, M., Schoenwaelder, J., Shafer, P., Watsen, K., and R. Wilton, "Network Management Datastore Architecture (NMDA)", [RFC 8342](https://www.rfc-editor.org/info/rfc8342), DOI 10.17487/RFC8342, March 2018, <<https://www.rfc-editor.org/info/rfc8342>>.

## Authors' Addresses

Stephane Litkowski  
Orange

Email: [stephane.litkowski@orange.com](mailto:stephane.litkowski@orange.com)

Yinghzen Qu  
Huawei

Email: [yingzhen.qu@huawei.com](mailto:yingzhen.qu@huawei.com)

Pushpasis Sarkar  
Individual

Email: [pushpasis.ietf@gmail.com](mailto:pushpasis.ietf@gmail.com)

Ing-Wher Chen  
The MITRE Corporation

Email: [ingwherchen@mitre.org](mailto:ingwherchen@mitre.org)

Jeff Tantsura  
Individual

Email: [jefftant.ietf@gmail.com](mailto:jefftant.ietf@gmail.com)

