

Network Working Group  
Internet-Draft  
Intended status: Informational  
Expires: 12 January 2023

A. Melnikov  
Isode Ltd  
11 July 2022

JMAP extension for S/MIME signing and encryption  
draft-ietf-jmap-smime-sender-extensions-02

## Abstract

This document specifies an extension to JMAP for sending S/MIME signed and S/MIME encrypted messages.

## Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 12 January 2023.

## Copyright Notice

Copyright (c) 2022 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Revised BSD License text as described in Section 4.e of the [Trust Legal Provisions](#) and are provided without warranty as described in the Revised BSD License.

Internet-Draft

JMAP extension for S/MIME

July 2022

## Table of Contents

<a href="#">1.</a>	Introduction . . . . .	<a href="#">2</a>
<a href="#">2.</a>	Conventions Used in This Document . . . . .	<a href="#">2</a>
<a href="#">3.</a>	Addition to the capabilities object . . . . .	<a href="#">2</a>
4.	Extension to Email/set for S/MIME signing and/or encryption . . . . .	<a href="#">2</a>
<a href="#">5.</a>	IANA Considerations . . . . .	<a href="#">5</a>
<a href="#">5.1.</a>	JMAP capability registration for "smime-advanced" . . . . .	<a href="#">5</a>
<a href="#">5.2.</a>	JMAP Error Codes Registry Updates . . . . .	<a href="#">5</a>
<a href="#">5.2.1.</a>	signedSenderNotAllowed error code . . . . .	<a href="#">5</a>
<a href="#">5.2.2.</a>	validEncryptionKeyNotFound error code . . . . .	<a href="#">6</a>
<a href="#">6.</a>	Security Considerations . . . . .	<a href="#">6</a>
<a href="#">7.</a>	Normative References . . . . .	<a href="#">6</a>
	Author's Address . . . . .	<a href="#">7</a>

[1.](#) Introduction

[RFC8621] is a JSON based application protocol for synchronising email data between a client and a server.

This document describes an extension to JMAP for sending S/MIME signed and encrypted messages . It allows JMAP server to sign/encrypt messages on user's behalf.

[2.](#) Conventions Used in This Document

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

[3.](#) Addition to the capabilities object

The capabilities object is returned as part of the standard JMAP Session object; see the JMAP spec. Servers supporting `_this_` specification MUST add a property called "urn:iETF:params:jmap:smime-advanced" to the capabilities object.

The value of this property is an empty object in both the JMAP session `_capabilities_` property and an account's `_accountCapabilities_` property.

[4.](#) Extension to Email/set for S/MIME signing and/or encryption

[RFC8621] defines Email/set method for creating new email messages. This document defines the following additional request arguments that can be used to create S/MIME signed and/or encrypted messages:

- \* `smimeSign`: "Boolean" (default: false). If included and has the value "true", this requests the JMAP server to create an S/MIME signed message from the message constructed according to other specified arguments (the "original message"). This is done by encapsulating the original message either inside `application/pkcs7-mime` [[RFC8551](#)] or `multipart/signed` [[RFC1847](#)] container. (`smimeSignOpaque` argument (see below) controls which of the two mechanisms is used.) The signature's private key/certificate is associated with the email address in the `Sender` header field, if present; otherwise, it is associated with the email address in the `From` header field, if present.

If multiple addresses are present in one of these header fields, or there is more than one `Sender/From` header field, the server SHOULD reject the `Email/set` as invalid with the "invalidEmail" error code; otherwise, it MUST take the first address in the last `Sender/From` header field. If JMAP account is not authorized to sign message as the selected sender (as above), it SHOULD return "signedSenderNotAllowed" error code.

- \* `smimeEncrypt`: "Boolean" (default: false). If included and has the value "true", this requests the JMAP server to create an S/MIME encrypted message from the constructed message. This is done by encapsulating the message inside `application/pkcs7-mime` [[RFC8551](#)] media type. The message MUST be encrypted to the sender and all `To/Cc/Bcc` recipients. This extension assumes that there is some kind of per user or organizational addressbook, that can be used to lookup public keys of recipients. If lookup of a particular public key fails, or results in an expired or revoked certificate, the `Email/set` operation MUST fail with the "validEncryptionKeyNotFound" error code.
- \* `headerProtect`: "Boolean" (default: true). If has the value "true", this requests the JMAP server to use S/MIME header protection as specified in [draft-ietf-lamps-header-protection](#) when at least one of `smimeEncrypt/smimeSign` is true.

- \* `smimeSignOpaque`: "Boolean" (default: true). If has the value "true", this requests the JMAP server to use application/pkcs7-mime media type for S/MIME signing, otherwise multipart/signed media type.

If both `smimeSign` and `smimeEncrypt` are set to true, the message is first signed and then the signed version is encrypted (in that order).

(Note that this extension doesn't allow management of private keys/certificates. How private keys are managed or configured for a particular user is out of scope for this document.)

```
[[ "Email/set", {
  "accountId": "ue150411c",
  "create": {
    "k192": {
      "mailboxIds": {
        "2ea1ca41b38e": true
      },
      "keywords": {
        "$seen": true,
        "$draft": true
      },
    },
    "from": [{
      "name": "Joe Bloggs",
      "email": "joe@example.com"
    }],
    "subject": "World domination",
    "receivedAt": "2021-07-07T01:03:11Z",
    "sentAt": "2021-07-10T11:03:11+10:00",
    "smimeSign": true,
    "smimeEncrypt": true,
    "bodyStructure": {
      "type": "text/plain",
      "partId": "bd48",
```

```

        "header:Content-Language": "en"
    },
    "bodyValues": {
        "bd48": {
            "value": "I have the most brilliant plan. Let me tell
                you all about it.",
            "isTruncated": false
        }
    }
}
}, "0" ]]

```

This will result in the following response:

```

[[ "Email/set", {
    "accountId": "ue150411c",
    "oldState": "780823",
    "newState": "780839",

```

Melnikov

Expires 12 January 2023

[Page 4]

Internet-Draft

JMAP extension for S/MIME

July 2022

```

    "created": {
        "k192": {
            "id": "Mf40b5f831efa7233b9eb1c7f",
            "blobId": "Gf40b5f831efa7233b9eb1c7f8f97d84eeeeee64f7",
            "threadId": "Td957e72e89f516dc",
            "size": 5096
        }
    },
    ...
}, "0" ]]

```

Figure 1: Example 1:

## [5.](#) IANA Considerations

### [5.1.](#) JMAP capability registration for "smime-advanced"

IANA is requested to register the "smime" JMAP Capability as follows:

Capability Name: "urn:ietf:params:jmap:smime-advanced"

Specification document: this document

Intended use: common

Change Controller: IETF

Security and privacy considerations: this document, [Section 6](#)

## [5.2.](#) JMAP Error Codes Registry Updates

### [5.2.1.](#) signedSenderNotAllowed error code

JMAP Error Code: signedSenderNotAllowed

Intended use: common

Change controller: IETF

Reference: This document, [Section 4](#)

Description: JMAP account is not authorized to S/MIME sign message as the specified sender.

### [5.2.2.](#) validEncryptionKeyNotFound error code

JMAP Error Code: validEncryptionKeyNotFound

Intended use: common

Change controller: IETF

Reference: This document, [Section 4](#)

Description: S/MIME encrypted message can't be generated because no valid certificate (non expired and non revoked) can be found for one of recipients.

## [6.](#) Security Considerations

This JMAP extension assumes trust between the user and the JMAP server for purposes of signing and encrypting messages on user's behalf.

This JMAP extension also relies on access to user's (or organization's) addressbook which contain up-to-date certificates for recipients.

This JMAP extension doesn't support management of user's private keys and corresponding certificates.

## 7. Normative References

- [RFC1847] Galvin, J., Murphy, S., Crocker, S., and N. Freed, "Security Multiparts for MIME: Multipart/Signed and Multipart/Encrypted", [RFC 1847](#), DOI 10.17487/RFC1847, October 1995, <<https://www.rfc-editor.org/info/rfc1847>>.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC8550] Schaad, J., Ramsdell, B., and S. Turner, "Secure/Multipurpose Internet Mail Extensions (S/MIME) Version 4.0 Certificate Handling", [RFC 8550](#), DOI 10.17487/RFC8550, April 2019, <<https://www.rfc-editor.org/info/rfc8550>>.
- [RFC8551] Schaad, J., Ramsdell, B., and S. Turner, "Secure/Multipurpose Internet Mail Extensions (S/MIME) Version 4.0 Message Specification", [RFC 8551](#), DOI 10.17487/RFC8551, April 2019, <<https://www.rfc-editor.org/info/rfc8551>>.

- [RFC8620] Jenkins, N. and C. Newman, "The JSON Meta Application Protocol (JMAP)", [RFC 8620](#), DOI 10.17487/RFC8620, July 2019, <<https://www.rfc-editor.org/info/rfc8620>>.
- [RFC8621] Jenkins, N. and C. Newman, "The JSON Meta Application Protocol (JMAP) for Mail", [RFC 8621](#), DOI 10.17487/RFC8621, August 2019, <<https://www.rfc-editor.org/info/rfc8621>>.

Author's Address

Alexey Melnikov  
Isode Ltd  
14 Castle Mews  
Hampton  
TW12 2NP  
United Kingdom  
Email: Alexey.Melnikov@isode.com