

Network Working Group  
Internet-Draft  
Intended status: Standards Track  
Expires: November 25, 2016

I. Liusvaara  
Independent  
May 24, 2016

CFRG ECDH and signatures in JOSE  
draft-ietf-jose-cfrg-curves-02

## Abstract

This document defines how to use Diffie-Hellman algorithms "X25519" and "X448" as well as signature algorithms "Ed25519" and "Ed448" from IRTF CFRG elliptic curves work in JOSE.

## Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on November 25, 2016.

## Copyright Notice

Copyright (c) 2016 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

<a href="#">1.</a>	Introduction . . . . .	<a href="#">2</a>
<a href="#">1.1.</a>	Requirements Terminology . . . . .	<a href="#">3</a>
<a href="#">2.</a>	Key type 'OKP' . . . . .	<a href="#">3</a>
<a href="#">3.</a>	Algorithms . . . . .	<a href="#">3</a>
<a href="#">3.1.</a>	Signatures . . . . .	<a href="#">3</a>
<a href="#">3.1.1.</a>	Algorithms . . . . .	<a href="#">3</a>
<a href="#">3.1.2.</a>	Signing . . . . .	<a href="#">4</a>
<a href="#">3.1.3.</a>	Verification . . . . .	<a href="#">4</a>
<a href="#">3.2.</a>	ECDH-ES . . . . .	<a href="#">4</a>
<a href="#">3.2.1.</a>	Performing the ECDH operation . . . . .	<a href="#">4</a>
<a href="#">4.</a>	Security considerations . . . . .	<a href="#">5</a>
<a href="#">5.</a>	Acknowledgements . . . . .	<a href="#">5</a>
<a href="#">6.</a>	IANA considerations . . . . .	<a href="#">6</a>
<a href="#">7.</a>	References . . . . .	<a href="#">7</a>
<a href="#">7.1.</a>	Normative References . . . . .	<a href="#">7</a>
<a href="#">7.2.</a>	Informative References . . . . .	<a href="#">8</a>
<a href="#">Appendix A.</a>	Examples . . . . .	<a href="#">8</a>
<a href="#">A.1.</a>	Ed25519 private key . . . . .	<a href="#">8</a>
<a href="#">A.2.</a>	Ed25519 public key . . . . .	<a href="#">8</a>
<a href="#">A.3.</a>	JWK thumbprint canonicalization . . . . .	<a href="#">8</a>
<a href="#">A.4.</a>	Ed25519 Signing . . . . .	<a href="#">9</a>
<a href="#">A.5.</a>	Ed25519 Validation . . . . .	<a href="#">10</a>
<a href="#">A.6.</a>	ECDH-ES with X25519 . . . . .	<a href="#">10</a>
<a href="#">A.7.</a>	ECDH-ES with X448 . . . . .	<a href="#">11</a>
	Author's Address . . . . .	<a href="#">12</a>

[1.](#) Introduction

Internet Research Task Force (IRTF) Crypto Forum Research Group (CFRG) selected new Diffie-Hellman algorithms ("X25519" and "X448"; [\[RFC7748\]](#)) and signature algorithms ("Ed25519" and "Ed448"); [\[I-D.irtf-cfrg-eddsa\]](#)) for asymmetric key cryptography. This document defines how those algorithms are to be used in JOSE in interoperable manner.

This document defines the conventions to be used in context of [\[RFC7517\]](#) and [\[RFC7518\]](#)

While the CFRG also defined two pairs of isogenous elliptic curves that underlie these algorithms, these curves are not directly exposed, as the algorithms laid on top are sufficient for the

purposes of JOSE and are much easier to use (e.g. trying to apply ECDSA to those curves leads to nasty corner-cases and produces odd results).

All inputs to and outputs from the the ECDH and signature functions are defined to be octet strings, with the exception of output of verification function, which is a boolean.

### [1.1](#). Requirements Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

## [2](#). Key type 'OKP'

A new key type (kty) value "OKP" (Octet Key Pair) is defined for public key algorithms that use octet strings as private and public keys. It has the following parameters:

- o The parameter "kty" MUST be "OKP".
- o The parameter "crv" MUST be present, and contain the subtype of the key (from "JSON Web Elliptic curve" registry).
- o The parameter "x" MUST be present, and contain the public key encoded using base64url [[RFC4648](#)] encoding.
- o The parameter "d" MUST be present for private keys, and contain the private key encoded using base64url encoding. This parameter MUST NOT be present for public keys.

Note: Do not assume that there is an underlying elliptic curve, despite the existence of the "crv" and "x" parameters (for instance, this key type could be extended to represent DH algorithms based on hyperelliptic surfaces).

When calculating thumbprints [[RFC7638](#)], the three public key fields are included in the hash. That is, in lexicographic order: "crv", "kty" and "x".

### [3. Algorithms](#)

#### [3.1. Signatures](#)

##### [3.1.1. Algorithms](#)

For EdDSA signatures, algorithm "EdDSA" is defined here, to be applied as value of "alg" parameter.

Liusvaara

Expires November 25, 2016

[Page 3]

---

Internet-Draft

CFRG ECDH and signatures in JOSE

May 2016

The key type for these keys is "OKP" and key subtype for these keys MUST be "Ed25519" for Ed25519 and "Ed448" for Ed448. The keys of these subtypes MUST NOT be used for ECDH-ES.

"crv"	EdDSA variant
Ed25519	Ed25519
Ed448	Ed448

##### [3.1.2. Signing](#)

Signing for these is preformed by applying the signing algorithm defined in [[I-D.irtf-cfrg-eddsa](#)] to the private key (as private key), public key (as public key) and the JWS Signing Input (as message). The resulting signature is the JWS Signature value. All inputs and outputs are octet strings.

##### [3.1.3. Verification](#)

Verification is performed by applying the verification algorithm defined in [[I-D.irtf-cfrg-eddsa](#)] to the public key (as public key), the JWS Signing Input (as message) and the JWS Signature value (as signature). All inputs are octet strings. If the algorithm accepts, the signature is valid, otherwise signature is invalid.

#### [3.2. ECDH-ES](#)

The following key subtypes defined here for purpose of "Key Agreement with Elliptic Curve Diffie-Hellman Ephemeral Static" (ECDH-ES).

"crv"	ECDH Function applied
X25519	X25519
X448	X448

The key type used with these keys is "OKP". These subtypes MUST NOT be used for signing.

[RFC7518] [section 4.6](#) defines the ECDH-ES algorithms "ECDH-ES+A128KW", "ECDH-ES+A192KW", "ECDH-ES+A256KW" and "ECDH-ES".

### [3.2.1](#). Performing the ECDH operation

The "x" parameter of "epk" field is set as follows:

Apply the appropriate ECDH function to the ephemeral private key (as scalar input) and the standard basepoint (as u-coordinate input). The output is the value for "x" parameter of "epk" field. All inputs and outputs are octet strings.

Liusvaara

Expires November 25, 2016

[Page 4]

---

Internet-Draft

CFRG ECDH and signatures in JOSE

May 2016

The Z value (raw key agreement output) for key agreement (to be used in subsequent KDF as per [\[RFC7518\] section 4.6.2](#)) is determined as follows:

Apply the appropriate ECDH function to the ephemeral private key (as scalar input) and receiver public key (as u-coordinate input). The output is the Z value. All inputs and outputs are octet strings.

## [4](#). Security considerations

Security considerations from [\[RFC7748\]](#) and [\[I-D.irtf-cfrg-eddsa\]](#) apply here.

Do not separate key material from information about what key subtype it is for. When using keys, check that the algorithm is compatible with the key subtype for the key. To do otherwise opens system up to attacks via mixing up algorithms. It is particularly dangerous to mix up signature and MAC algorithms.

Although for Ed25519 and Ed448 the signature binds the key used for signing, do not assume this, as there are many signature algorithms that fail to make such binding. If key-binding is desired, include

the key used for signing either inside the JWS protected header or the data to sign.

If key generation or batch signature verification is performed, a well-seed cryptographic random number generator is REQUIRED. Signing and non-batch signature verification are deterministic operations and do not need random numbers of any kind.

The JWA ECDH-ES KDF construction does not mix keys into the final shared secret. While in key exchange such could be a bad mistake, here either receiver public key has to be chosen maliciously or the sender has to be malicious in order to cause problems. And in either case, all security evaporates anyway.

The nominal security strengths of X25519 and X448 are ~126 and ~223 bits. Therefore, using 256-bit symmetric encryption (especially key wrapping and encryption) with X448 is RECOMMENDED.

## [5.](#) Acknowledgements

Mike Jones for comments on initial pre-draft.

## [6.](#) IANA considerations

The following is added to JSON Web Key Types Registry:

- o "kty" Parameter Value: "OKP"
- o Key Type Description: Octet string key pairs
- o JOSE Implementation Requirements: Optional
- o Change Controller: IESG
- o Specification Document(s): [Section 2](#) of [RFC-THIS]

The following is added to JSON Web Key Parameters Registry:

- o Parameter Name: "crv"
- o Parameter Description: The subtype of keypair

- o Parameter Information Class: Public
- o Used with "kty" Value(s): "OKP"
- o Change Controller: IESG
- o Specification Document(s): [Section 2](#) of [RFC-THIS]
  
- o Parameter Name: "d"
- o Parameter Description: The private key
- o Parameter Information Class: Private
- o Used with "kty" Value(s): "OKP"
- o Change Controller: IESG
- o Specification Document(s): [Section 2](#) of [RFC-THIS]
  
- o Parameter Name: "x"
- o Parameter Description: The public key
- o Parameter Information Class: Public
- o Used with "kty" Value(s): "OKP"
- o Change Controller: IESG
- o Specification Document(s): [Section 2](#) of [RFC-THIS]

The following is added to JSON Web Signature and Encryption Algorithms Registry:

- o Algorithm Name: "EdDSA"
- o Algorithm Description: EdDSA signature algorithms
- o Algorithm Usage Location(s): "alg"
- o JOSE Implementation Requirements: Optional
- o Change Controller: IESG
- o Specification Document(s): [Section 3.1](#) of [RFC-THIS]
- o Algorithm Analysis Documents(s): [[I-D.irtf-cfrg-eddsa](#)]

The following is added to JSON Web Key Elliptic Curve Registry:

- o Curve Name: "Ed25519"
- o Curve Description: Ed25519 signature algorithm keypairs
- o JOSE Implementation Requirements: Optional
- o Change Controller: IESG
- o Specification Document(s): [Section 3.1](#) of [RFC-THIS]
  
- o Curve Name: "Ed448"
- o Curve Description: Ed448 signature algorithm keypairs

- o JOSE Implementation Requirements: Optional
- o Change Controller: IESG
- o Specification Document(s): [Section 3.1](#) of [RFC-THIS]
  
- o Curve name: "X25519"
- o Curve Description: X25519 function keypairs
- o JOSE Implementation Requirements: Optional
- o Change Controller: IESG
- o Specification Document(s): [Section 3.2](#) of [RFC-THIS]
- o Analysis Documents(s): [[RFC7748](#)]
  
- o Curve Name: "X448"
- o Curve Description: X448 function keypairs
- o JOSE Implementation Requirements: Optional
- o Change Controller: IESG
- o Specification Document(s): [Section 3.2](#) of [RFC-THIS]
- o Analysis Documents(s): [[RFC7748](#)]

## [7.](#) References

### [7.1.](#) Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<http://www.rfc-editor.org/info/rfc2119>>.
- [RFC4648] Josefsson, S., "The Base16, Base32, and Base64 Data Encodings", [RFC 4648](#), DOI 10.17487/RFC4648, October 2006, <<http://www.rfc-editor.org/info/rfc4648>>.
- [RFC7748] Langley, A., Hamburg, M., and S. Turner, "Elliptic Curves for Security", [RFC 7748](#), DOI 10.17487/RFC7748, January 2016, <<http://www.rfc-editor.org/info/rfc7748>>.
- [I-D.irtf-cfrg-eddsa] Josefsson, S. and I. Liusvaara, "Edwards-curve Digital Signature Algorithm (EdDSA)", [draft-irtf-cfrg-eddsa-05](#) (work in progress), March 2016.

### [7.2.](#) Informative References



- [RFC7517] Jones, M., "JSON Web Key (JWK)", [RFC 7517](#), DOI 10.17487/RFC7517, May 2015, <<http://www.rfc-editor.org/info/rfc7517>>.
- [RFC7518] Jones, M., "JSON Web Algorithms (JWA)", [RFC 7518](#), DOI 10.17487/RFC7518, May 2015, <<http://www.rfc-editor.org/info/rfc7518>>.
- [RFC7638] Jones, M. and N. Sakimura, "JSON Web Key (JWK) Thumbprint", [RFC 7638](#), DOI 10.17487/RFC7638, September 2015, <<http://www.rfc-editor.org/info/rfc7638>>.

## [Appendix A](#). Examples

To the extent possible, the examples use material lifted from test vectors of [[RFC7748](#)] and [[I-D.irtf-cfrg-eddsa](#)]

### [A.1](#). Ed25519 private key

```
{"kty":"OKP","crv":"Ed25519",  
"d":"nWGxne_9WmC6hEr0kuwsxERJxWl7MmkZcDusAxyuf2A"  
"x":"11qYAYKxCrfVS_7TyWQH0g7hcvPapiMlrwIaaPcHURo"}
```

The hexadecimal dump of private key is:

```
9d 61 b1 9d ef fd 5a 60 ba 84 4a f4 92 ec 2c c4  
44 49 c5 69 7b 32 69 19 70 3b ac 03 1c ae 7f 60
```

And of the public key:

```
d7 5a 98 01 82 b1 0a b7 d5 4b fe d3 c9 64 07 3a  
0e e1 72 f3 da a6 23 25 af 02 1a 68 f7 07 51 1a
```

### [A.2](#). Ed25519 public key

This is the public parts of the previous private key (just omits "d"):

```
{"kty":"OKP","crv":"Ed25519",  
"x":"11qYAYKxCrfVS_7TyWQH0g7hcvPapiMlrwIaaPcHURo"}
```

### [A.3](#). JWK thumbprint canonicalization

The JWK thumbprint canonicalization of the two above examples is (linebreak inserted for formatting reasons)

```
{"crv":"Ed25519","kty":"OKP","x":"11qYAYKxCrfVS_7TyWQH0g7hcvPapiMlrwI  
aaPcHURo"}
```

Which has the SHA-256 hash of:

```
90facafea9b1556698540f70c0117a22ea37bd5cf3ed3c47093c1707282b4b89
```

#### [A.4.](#) Ed25519 Signing

The JWS protected header is:

```
{"alg":"EdDSA"}
```

This has base64url encoding of:

```
eyJhbGciOiJFZERTQSJ9
```

The payload is (text):

Example of Ed25519 signing

This has base64url encoding of:

```
RXhhbXBsZSBvZiBFZDI1NTE5IHNPZ25pbmc
```

The JWS signing input is (concatenation of base64url encoding of the (protected) header, a dot and base64url encoding of the payload) is:

```
eyJhbGciOiJFZERTQSJ9.RXhhbXBsZSBvZiBFZDI1NTE5IHNPZ25pbmc
```

Applying Ed25519 signing algorithm to the private key, public key and the JWS signing input yields signature (hex):

```
86 0c 98 d2 29 7f 30 60 a3 3f 42 73 96 72 d6 1b  
53 cf 3a de fe d3 d3 c6 72 f3 20 dc 02 1b 41 1e  
9d 59 b8 62 8d c3 51 e2 48 b8 8b 29 46 8e 0e 41  
85 5b 0f b7 d8 3b b1 5b e9 02 bf cc b8 cd 0a 02
```

Converting this to base64url yields:

```
hgyY0il_MGCjP0JzlnLWG1PP0t7-09PGcvMg3AIbQR6dWbhijcNR4ki4iylGjg5BhVsPt  
9g7sVvpAr_MuM0KAg
```

So the compact serialization of JWS is (concatenation of signing input, a dot and base64url encoding of the signature:

```
eyJhbGciOiJFZERTQSJ9.RXhhbXBsZSBvZiBFZDI1NTE5IHNPZ25pbmc.hgyY0il_MGCj
```

P0JzlnLWG1PP0t7-09PGcvMg3AIbQR6dWbhijcNR4ki4iylGjg5BhVsPt9g7sVvpAr\_Mu  
M0KA

Liusvaara

Expires November 25, 2016

[Page 9]

Internet-Draft

CFRG ECDH and signatures in JOSE

May 2016

#### [A.5.](#) Ed25519 Validation

The JWS from above example is:

```
eyJhbGciOiJFZERTQSJ9.RXhhbXBsZSBvZiBFZDI1NTE5IHNPZ25pbmc.hgyY0il_MGCj  
P0JzlnLWG1PP0t7-09PGcvMg3AIbQR6dWbhijcNR4ki4iylGjg5BhVsPt9g7sVvpAr_Mu  
M0KA
```

This has 2 dots in it, so it might be valid JWS. Base64url decoding the protected header yields:

```
{"alg":"EdDSA"}
```

So this is EdDSA signature. Now the key has: "kty":"OKP" and "crv":"Ed25519", so the signature is Ed25519 signature.

The signing input is the part before second dot:

```
eyJhbGciOiJFZERTQSJ9.RXhhbXBsZSBvZiBFZDI1NTE5IHNPZ25pbmc
```

Applying Ed25519 verification algorithm to the public key, JWS signing input and the signature yields true. So the signature is valid. The message is base64 decoding of the part between the dots:

Example of Ed25519 signing

#### [A.6.](#) ECDH-ES with X25519

The public key to encrypt to is:

```
{"kty":"OKP","crv":"X25519","kid":"Bob"  
"x":"3p7bfXt9wbTTW2HC7OQ1Nz-DQ8hbeGdNrfx-FG-IK08"}
```

The public key from target key is (hex):

```
de 9e db 7d 7b 7d c1 b4 d3 5b 61 c2 ec e4 35 37  
3f 83 43 c8 5b 78 67 4d ad fc 7e 14 6f 88 2b 4f
```

The ephemeral secret happens to be (hex):

```
77 07 6d 0a 73 18 a5 7d 3c 16 c1 72 51 b2 66 45
df 4c 2f 87 eb c0 99 2a b1 77 fb a5 1d b9 2c 2a
```

So the ephemeral public key is X25519(ephkey,G) (hex):

```
85 20 f0 09 89 30 a7 54 74 8b 7d dc b4 3e f7 5a
0d bf 3a 0d 26 38 1a f4 eb a4 a9 8e aa 9b 4e 6a
```

This is packed into ephemeral public key value:

```
{"kty":"OKP","crv":"X25519",
"x":"hSDwCYkwp1R0i33ctD73Wg2_Og0m0Br066SpjqqbTmo"}
```

So the protected header could for example be:

```
{"alg":"ECDH-ES+A128KW","epk":{"kty":"OKP","crv":"X25519",
"x":"hSDwCYkwp1R0i33ctD73Wg2_Og0m0Br066SpjqqbTmo"},
"enc":"A128GCM","kid":"Bob"}
```

And sender computes as the DH Z value as X25519(ephkey,recv\_pub) (hex):

```
4a 5d 9d 5b a4 ce 2d e1 72 8e 3b f4 80 35 0f 25
e0 7e 21 c9 47 d1 9e 33 76 f0 9b 3c 1e 16 17 42
```

The receiver computes as the DH Z value as X25519(seckey,ephkey\_pub) (hex):

```
4a 5d 9d 5b a4 ce 2d e1 72 8e 3b f4 80 35 0f 25
e0 7e 21 c9 47 d1 9e 33 76 f0 9b 3c 1e 16 17 42
```

Which is the same as sender's value (the both sides run this through KDF before using as direct encryption key or AES128-KW key).

#### [A.7.](#) ECDH-ES with X448

The public key to encrypt to is (linebreak inserted for formatting reasons):

```
{"kty":"OKP","crv":"X448","kid":"Dave"}
```

```
"x":"PreoKbDNIPW8_AtZm2_sz22kYnEHvbDU80W0McfYuXL8PjT7QjKhPKcG3LV67D2uB73BxnvzNgk"}
```

The public key from target key is (hex):

```
3e b7 a8 29 b0 cd 20 f5 bc fc 0b 59 9b 6f ec cf
6d a4 62 71 07 bd b0 d4 f3 45 b4 30 27 d8 b9 72
fc 3e 34 fb 42 32 a1 3c a7 06 dc b5 7a ec 3d ae
07 bd c1 c6 7b f3 36 09
```

The ephemeral secret happens to be (hex):

```
9a 8f 49 25 d1 51 9f 57 75 cf 46 b0 4b 58 00 d4
ee 9e e8 ba e8 bc 55 65 d4 98 c2 8d d9 c9 ba f5
74 a9 41 97 44 89 73 91 00 63 82 a6 f1 27 ab 1d
9a c2 d8 c0 a5 98 72 6b
```

So the ephemeral public key is X448(ephkey,G) (hex):

```
9b 08 f7 cc 31 b7 e3 e6 7d 22 d5 ae a1 21 07 4a
27 3b d2 b8 3d e0 9c 63 fa a7 3d 2c 22 c5 d9 bb
c8 36 64 72 41 d9 53 d4 0c 5b 12 da 88 12 0d 53
17 7f 80 e5 32 c4 1f a0
```

This is packed into ephemeral public key value (linebreak inserted for formatting purposes):

```
{"kty":"OKP","crv":"X448",
"x":"mwj3zDG34-Z9ItWuoSEHSic70rg94Jxj-qc9LCLF2bvINmRyQdlT1AxbEtqIEg1
TF3-A5TLEH6A"}
```

So the protected header could for example be (linebreak inserted for formatting purposes):

```
{"alg":"ECDH-ES+A256KW","epk":{"kty":"OKP","crv":"X448",
"x":"mwj3zDG34-Z9ItWuoSEHSic70rg94Jxj-qc9LCLF2bvINmRyQdlT1AxbEtqIEg1
TF3-A5TLEH6A"},"enc":"A256GCM","kid":"Dave"}
```

And sender computes as the DH Z value as X448(ephkey,recv\_pub) (hex):

```
07 ff f4 18 1a c6 cc 95 ec 1c 16 a9 4a 0f 74 d1
2d a2 32 ce 40 a7 75 52 28 1d 28 2b b6 0c 0b 56
```

fd 24 64 c3 35 54 39 36 52 1c 24 40 30 85 d5 9a  
44 9a 50 37 51 4a 87 9d

The receiver computes as the DH Z value as X448(seckey,ephkey\_pub)  
(hex):

07 ff f4 18 1a c6 cc 95 ec 1c 16 a9 4a 0f 74 d1  
2d a2 32 ce 40 a7 75 52 28 1d 28 2b b6 0c 0b 56  
fd 24 64 c3 35 54 39 36 52 1c 24 40 30 85 d5 9a  
44 9a 50 37 51 4a 87 9d

Which is the same as sender's value (the both sides run this through  
KDF before using as direct encryption key or AES256-KW key).

Author's Address

Ilari Liusvaara  
Independent

Email: ilariliusvaara@welho.com