JOSE Working Group
Internet-Draft
Intended status: Standards Track
Expires: April 10, 2014

M. Jones
Microsoft

October 7, 2013

JSON Web Key (JWK)
draft-ietf-jose-json-web-key-17

Abstract

A JSON Web Key (JWK) is a JavaScript Object Notation (JSON) data structure that represents a cryptographic key. This specification also defines a JSON Web Key Set (JWK Set) JSON data structure for representing a set of JWKs. Cryptographic algorithms and identifiers for use with this specification are described in the separate JSON Web Algorithms (JWA) specification and IANA registries defined by that specification.

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at http://datatracker.ietf.org/drafts/current/.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on April 10, 2014.

Copyright Notice

Copyright (c) 2013 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (http://trustee.ietf.org/license-info) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of

the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1. Introduction 4
1.1. Notational Conventions 4
2. Terminology 4
3. JSON Web Key (JWK) Format 5
3.1. "kty" (Key Type) Parameter 5
3.2. "use" (Key Use) Parameter 6
3.3. "alg" (Algorithm) Parameter 6
3.4. "kid" (Key ID) Parameter 6
3.5. "x5u" (X.509 URL) Parameter 6
3.6. "x5t" (X.509 Certificate SHA-1 Thumbprint) Parameter . . . 7
3.7. "x5c" (X.509 Certificate Chain) Parameter 7
4. JSON Web Key Set (JWK Set) Format 7
4.1. "keys" Parameter 8
5. String Comparison Rules 8
6. Encrypted JWK and Encrypted JWK Set Formats 8
7. IANA Considerations 9
7.1. JSON Web Key Parameters Registry 9
7.1.1. Registration Template 10
7.1.2. Initial Registry Contents 10
7.2. JSON Web Key Use Registry 11
7.2.1. Registration Template 12
7.2.2. Initial Registry Contents 12
7.3. JSON Web Key Set Parameters Registry 12
7.3.1. Registration Template 12
7.3.2. Initial Registry Contents 13
7.4. Media Type Registration 13
7.4.1. Registry Contents 13
8. Security Considerations 14
9. References 15
9.1. Normative References 15
9.2. Informative References 16
Appendix A. Example JSON Web Key Sets 17
A.1. Example Public Keys 17
A.2. Example Private Keys 17
A.3. Example Symmetric Keys 19
Appendix B. Example Use of "x5c" (X.509 Certificate Chain) Parameter 19
Appendix C. Example Encrypted RSA Private Key 20
C.1. Plaintext RSA Private Key 21
C.2. JWE Header 24
C.3. Content Encryption Key (CEK) 24
C.4. Key Encryption 25

C.5. Initialization Vector 25
C.6. Additional Authenticated Data 25
C.7. Content Encryption 26
C.8. Complete Representation 29
Appendix D. Acknowledgements 30
Appendix E. Document History 31
Author's Address 35

1. Introduction

A JSON Web Key (JWK) is a JavaScript Object Notation (JSON) [RFC4627] data structure that represents a cryptographic key. This specification also defines a JSON Web Key Set (JWK Set) JSON data structure for representing a set of JWKs. Cryptographic algorithms and identifiers for use with this specification are described in the separate JSON Web Algorithms (JWA) [JWA] specification and IANA registries defined by that specification.

Goals for this specification do not include representing certificate chains, representing certified keys, and replacing X.509 certificates.

JWKs and JWK Sets are used in the JSON Web Signature (JWS) [JWS] and JSON Web Encryption (JWE) [JWE] specifications.

Names defined by this specification are short because a core goal is for the resulting representations to be compact.

1.1. Notational Conventions

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in Key words for use in RFCs to Indicate Requirement Levels [RFC2119]. If these words are used without being spelled in uppercase then they are to be interpreted with their normal natural language meanings.

BASE64URL(OCTETS) denotes the base64url encoding of OCTETS, per Section 2.

UTF8(STRING) denotes the octets of the UTF-8 [RFC3629] representation of STRING.

ASCII(STRING) denotes the octets of the ASCII [USASCII] representation of STRING.

The concatenation of two values A and B is denoted as A || B.

2. Terminology

These terms defined by the JSON Web Signature (JWS) [JWS] specification are incorporated into this specification: "Base64url Encoding" and "Collision Resistant Name".

These terms are defined for use by this specification:

JSON Web Key (JWK) A JSON object that represents a cryptographic key.

JSON Web Key Set (JWK Set) A JSON object that contains an array of JWKs as the value of its "keys" member.

3. JSON Web Key (JWK) Format

A JSON Web Key (JWK) is a JSON object containing specific members, as specified below. Those members that are common to multiple key types are defined below.

In addition to the common parameters, each JWK will have members that are specific to the kind of key being represented. These members represent the parameters of the key. Section 5 of the JSON Web Algorithms (JWA) [JWA] specification defines multiple kinds of cryptographic keys and their associated members.

The member names within a JWK MUST be unique; recipients MUST either reject JWKs with duplicate member names or use a JSON parser that returns only the lexically last duplicate member name, as specified in Section 15.12 (The JSON Object) of ECMAScript 5.1 [ECMAScript].

Additional members MAY be present in the JWK. If not understood by implementations encountering them, they MUST be ignored. Member names used for representing key parameters for different kinds of keys need not be distinct. Any new member name SHOULD either be registered in the IANA JSON Web Key Parameters registry defined in Section 7.1 or be a value that contains a Collision Resistant Name.

3.1. "kty" (Key Type) Parameter

The "kty" (key type) member identifies the cryptographic algorithm family used with the key. "kty" values SHOULD either be registered in the IANA JSON Web Key Types registry defined in [JWA] or be a value that contains a Collision Resistant Name. The "kty" value is a case sensitive string. Use of this member is REQUIRED.

A list of defined "kty" values can be found in the IANA JSON Web Key Types registry defined in [JWA]; the initial contents of this registry are the values defined in Section 5.1 of the JSON Web Algorithms (JWA) [JWA] specification.

Additional members used with these "kty" values can be found in the IANA JSON Web Key Parameters registry defined in Section 7.1; the initial contents of this registry are the values defined in Sections 5.2 and 5.3 of the JSON Web Algorithms (JWA) [JWA] specification.

3.2. "use" (Key Use) Parameter

The "use" (key use) member identifies the intended use of the key. Values defined by this specification are:

o "sig" (signature or MAC operation)

o "enc" (encryption)

Other values MAY be used. Key Use values can be registered in the IANA JSON Web Key Use registry defined in Section 7.2. The "use" value is a case sensitive string. A "use" member SHOULD be present, unless the application uses another means or convention to determine the intended key usage.

When a key is used to wrap another key and a key use designation for the first key is desired, the "enc" (encryption) key use value SHOULD be used, since key wrapping is a kind of encryption. (The "alg" member can be used to specify the particular kind of encryption to be performed, when desired.)

3.3. "alg" (Algorithm) Parameter

The "alg" (algorithm) member identifies the algorithm intended for use with the key. The values used SHOULD either be registered in the IANA JSON Web Signature and Encryption Algorithms registry defined in [JWA] or be a value that contains a Collision Resistant Name. Use of this member is OPTIONAL.

3.4. "kid" (Key ID) Parameter

The "kid" (key ID) member can be used to match a specific key. This can be used, for instance, to choose among a set of keys within a JWK Set during key rollover. The interpretation of the "kid" value is unspecified. When "kid" values are used within a JWK Set, different keys within the JWK Set SHOULD use distinct "kid" values. The "kid" value is a case sensitive string. Use of this member is OPTIONAL.

When used with JWS or JWE, the "kid" value can be used to match a JWS or JWE "kid" Header Parameter value.

3.5. "x5u" (X.509 URL) Parameter

The "x5u" (X.509 URL) member is a URI [RFC3986] that refers to a resource for an X.509 public key certificate or certificate chain [RFC5280]. The identified resource MUST provide a representation of the certificate or certificate chain that conforms to RFC 5280 [RFC5280] in PEM encoded form [RFC1421]. The key in the first

certificate MUST match the bare public key represented by other members of the JWK. The protocol used to acquire the resource MUST provide integrity protection; an HTTP GET request to retrieve the certificate MUST use TLS [RFC2818] [RFC5246]; the identity of the server MUST be validated, as per Section 3.1 of HTTP Over TLS [RFC2818]. Use of this member is OPTIONAL.

3.6. "x5t" (X.509 Certificate SHA-1 Thumbprint) Parameter

The "x5t" (X.509 Certificate SHA-1 Thumbprint) member is a base64url encoded SHA-1 thumbprint (a.k.a. digest) of the DER encoding of an X.509 certificate [RFC5280]. The key in the certificate MUST match the bare public key represented by other members of the JWK. Use of this member is OPTIONAL.

If, in the future, certificate thumbprints need to be computed using hash functions other than SHA-1, it is suggested that additional related JWK parameters be defined for that purpose. For example, it is suggested that a new "x5t#S256" (X.509 Certificate Thumbprint using SHA-256) JWK parameter could be defined by registering it in the IANA JSON Web Key Parameters registry defined in Section 7.1.

3.7. "x5c" (X.509 Certificate Chain) Parameter

The "x5c" (X.509 Certificate Chain) member contains a chain of one or more PKIX certificates [RFC5280]. The certificate chain is represented as a JSON array of certificate value strings. Each string in the array is a base64 encoded ([RFC4648] Section 4 -- not base64url encoded) DER [ITU.X690.1994] PKIX certificate value. The PKIX certificate containing the key value MUST be the first certificate. This MAY be followed by additional certificates, with each subsequent certificate being the one used to certify the previous one. The key in the first certificate MUST match the bare public key represented by other members of the JWK. Use of this member is OPTIONAL.

4. JSON Web Key Set (JWK Set) Format

A JSON Web Key Set (JWK Set) is a JSON object that contains an array of JWK values as the value of its "keys" member.

The member names within a JWK Set MUST be unique; recipients MUST either reject JWK Sets with duplicate member names or use a JSON parser that returns only the lexically last duplicate member name, as specified in Section 15.12 (The JSON Object) of ECMAScript 5.1 [ECMAScript].

Additional members MAY be present in the JWK Set. If not understood by implementations encountering them, they MUST be ignored. Parameters for representing additional properties of JWK Sets SHOULD either be registered in the IANA JSON Web Key Set Parameters registry defined in Section 7.3 or be a value that contains a Collision Resistant Name.

Implementations SHOULD ignore JWKs within a JWK Set that use "kty" (key type) values that are not understood by them.

4.1. "keys" Parameter

The value of the "keys" member is an array of JWK values. By default, the order of the JWK values within the array does not imply an order of preference among them, although applications of JWK Sets can choose to assign a meaning to the order for their purposes, if desired. Use of this member is REQUIRED.

5. String Comparison Rules

The string comparison rules for this specification are the same as those defined in Section 5.3 of [JWS].

6. Encrypted JWK and Encrypted JWK Set Formats

JWKs containing non-public key material will need to be encrypted in some contexts to prevent the disclosure of private or symmetric key values to unintended parties. The use of an Encrypted JWK, which is a JWE with a JWK as its plaintext value, is RECOMMENED for this purpose. The processing of Encrypted JWKs is identical to the processing of other JWEs. A "cty" (content type) Header Parameter value of "jwk+json" MUST be used to indicate that the content of the JWE is a JWK, unless the application knows that the encrypted content is a JWK by another means or convention.

JWK Sets containing non-public key material will similarly need to be encrypted. The use of an Encrypted JWK Set, which is a JWE with a JWK Set as its plaintext value, is RECOMMENED for this purpose. The processing of Encrypted JWK Sets is identical to the processing of other JWEs. A "cty" (content type) Header Parameter value of "jwk-set+json" MUST be used to indicate that the content of the JWE is a JWK Set, unless the application knows that the encrypted content is a JWK Set by another means or convention.

See Appendix C for an example encrypted JWK.

7. IANA Considerations

The following registration procedure is used for all the registries established by this specification.

Values are registered with a Specification Required [RFC5226] after a two-week review period on the [TBD]@ietf.org mailing list, on the advice of one or more Designated Experts. However, to allow for the allocation of values prior to publication, the Designated Expert(s) may approve registration once they are satisfied that such a specification will be published.

Registration requests must be sent to the [TBD]@ietf.org mailing list for review and comment, with an appropriate subject (e.g., "Request for access token type: example"). [[Note to the RFC Editor: The name of the mailing list should be determined in consultation with the IESG and IANA. Suggested name: jose-reg-review.]]

Within the review period, the Designated Expert(s) will either approve or deny the registration request, communicating this decision to the review list and IANA. Denials should include an explanation and, if applicable, suggestions as to how to make the request successful. Registration requests that are undetermined for a period longer than 21 days can be brought to the IESG's attention (using the iesg@iesg.org mailing list) for resolution.

Criteria that should be applied by the Designated Expert(s) includes determining whether the proposed registration duplicates existing functionality, determining whether it is likely to be of general applicability or whether it is useful only for a single application, and whether the registration makes sense.

IANA must only accept registry updates from the Designated Expert(s) and should direct all requests for registration to the review mailing list.

It is suggested that multiple Designated Experts be appointed who are able to represent the perspectives of different applications using this specification, in order to enable broadly-informed review of registration decisions. In cases where a registration decision could be perceived as creating a conflict of interest for a particular Expert, that Expert should defer to the judgment of the other Expert(s).

7.1. JSON Web Key Parameters Registry

This specification establishes the IANA JSON Web Key Parameters registry for JWK parameter names. The registry records the parameter

name, the key type(s) that the parameter is used with, and a reference to the specification that defines it. It also records whether the parameter conveys public or private information. This specification registers the parameter names defined in Section 3. The same JWK parameter name may be registered multiple times, provided that duplicate parameter registrations are only for key type specific JWK parameters; in this case, the meaning of the duplicate parameter name is disambiguated by the "kty" value of the JWK containing it.

7.1.1. Registration Template

Parameter Name:
The name requested (e.g., "example"). Because a core goal of this specification is for the resulting representations to be compact, it is RECOMMENDED that the name be short -- not to exceed 8 characters without a compelling reason to do so. This name is case sensitive. Names may not match other registered names in a case insensitive manner unless the Designated Expert(s) state that there is a compelling reason to allow an exception in this particular case.

Used with "kty" Value(s):
The key type parameter value(s) that the parameter name is to be used with, or the value "*" if the parameter value is used with all key types.

Parameter Information Class:
Registers whether the parameter conveys public or private information. Its value must be one the words Public or Private.

Change Controller:
For Standards Track RFCs, state "IESG". For others, give the name of the responsible party. Other details (e.g., postal address, email address, home page URI) may also be included.

Specification Document(s):
Reference to the document(s) that specify the parameter, preferably including URI(s) that can be used to retrieve copies of the document(s). An indication of the relevant sections may also be included but is not required.

7.1.2. Initial Registry Contents

- Parameter Name: "kty"
- Used with "kty" Value(s): *

- Parameter Information Class: Public
- Change Controller: IESG
- Specification Document(s): Section 3.1 of [[this document]]

- Parameter Name: "use"
- Used with "kty" Value(s): *
- Parameter Information Class: Public
- Change Controller: IESG
- Specification Document(s): Section 3.2 of [[this document]]

- Parameter Name: "alg"
- Used with "kty" Value(s): *
- Parameter Information Class: Public
- Change Controller: IESG
- Specification Document(s): Section 3.3 of [[this document]]

- Parameter Name: "kid"
- Used with "kty" Value(s): *
- Parameter Information Class: Public
- Change Controller: IESG
- Specification Document(s): Section 3.4 of [[this document]]

- Parameter Name: "x5u"
- Used with "kty" Value(s): *
- Parameter Information Class: Public
- Change Controller: IESG
- Specification Document(s): Section 3.5 of [[this document]]

- Parameter Name: "x5t"
- Used with "kty" Value(s): *
- Parameter Information Class: Public
- Change Controller: IESG
- Specification Document(s): Section 3.6 of [[this document]]

- Parameter Name: "x5c"
- Used with "kty" Value(s): *
- Parameter Information Class: Public
- Change Controller: IESG
- Specification Document(s): Section 3.7 of [[this document]]

7.2. JSON Web Key Use Registry

This specification establishes the IANA JSON Web Key Use registry for JWK "use" member values. The registry records the key use value and a reference to the specification that defines it. This specification registers the parameter names defined in Section 3.2.

7.2.1. Registration Template

Use Member Value:
The name requested (e.g., "example"). Because a core goal of this specification is for the resulting representations to be compact, it is RECOMMENDED that the name be short -- not to exceed 8 characters without a compelling reason to do so. This name is case sensitive. Names may not match other registered names in a case insensitive manner unless the Designated Expert(s) state that there is a compelling reason to allow an exception in this particular case.

Change Controller:
For Standards Track RFCs, state "IESG". For others, give the name of the responsible party. Other details (e.g., postal address, email address, home page URI) may also be included.

Specification Document(s):
Reference to the document(s) that specify the parameter, preferably including URI(s) that can be used to retrieve copies of the document(s). An indication of the relevant sections may also be included but is not required.

7.2.2. Initial Registry Contents

- Use Member Value: "sig"
- Change Controller: IESG
- Specification Document(s): Section 3.2 of [[this document]]

- Use Member Value: "enc"
- Change Controller: IESG
- Specification Document(s): Section 3.2 of [[this document]]

7.3. JSON Web Key Set Parameters Registry

This specification establishes the IANA JSON Web Key Set Parameters registry for JWK Set parameter names. The registry records the parameter name and a reference to the specification that defines it. This specification registers the parameter names defined in Section 4.

7.3.1. Registration Template

Parameter Name:
The name requested (e.g., "example"). Because a core goal of this specification is for the resulting representations to be compact, it is RECOMMENDED that the name be short -- not to exceed 8 characters without a compelling reason to do so. This name is

case sensitive. Names may not match other registered names in a case insensitive manner unless the Designated Expert(s) state that there is a compelling reason to allow an exception in this particular case.

Change Controller:
For Standards Track RFCs, state "IESG". For others, give the name of the responsible party. Other details (e.g., postal address, email address, home page URI) may also be included.

Specification Document(s):
Reference to the document(s) that specify the parameter, preferably including URI(s) that can be used to retrieve copies of the document(s). An indication of the relevant sections may also be included but is not required.

7.3.2. Initial Registry Contents

- o Parameter Name: "keys"
- o Change Controller: IESG
- o Specification Document(s): Section 4.1 of [[this document]]

7.4. Media Type Registration

7.4.1. Registry Contents

This specification registers the "application/jwk+json" and "application/jwk-set+json" Media Types [RFC2046] in the MIME Media Types registry [IANA.MediaTypes], which can be used to indicate, respectively, that the content is a JWK or a JWK Set.

- o Type Name: application
- o Subtype Name: jwk+json
- o Required Parameters: n/a
- o Optional Parameters: n/a
- o Encoding considerations: 8bit; application/jwk+json values are represented as JSON object; UTF-8 encoding SHOULD be employed for the JSON object.
- o Security Considerations: See the Security Considerations section of [[this document]]
- o Interoperability Considerations: n/a
- o Published Specification: [[this document]]
- o Applications that use this media type: TBD
- o Additional Information: Magic number(s): n/a, File extension(s): n/a, Macintosh file type code(s): n/a
- o Person & email address to contact for further information: Michael B. Jones, mbj@microsoft.com

- o Intended Usage: COMMON
- o Restrictions on Usage: none
- o Author: Michael B. Jones, mbj@microsoft.com
- o Change Controller: IESG

- o Type Name: application
- o Subtype Name: jwk-set+json
- o Required Parameters: n/a
- o Optional Parameters: n/a
- o Encoding considerations: 8bit; application/jwk-set+json values are represented as a JSON Object; UTF-8 encoding SHOULD be employed for the JSON object.
- o Security Considerations: See the Security Considerations section of [[this document]]
- o Interoperability Considerations: n/a
- o Published Specification: [[this document]]
- o Applications that use this media type: TBD
- o Additional Information: Magic number(s): n/a, File extension(s): n/a, Macintosh file type code(s): n/a
- o Person & email address to contact for further information: Michael B. Jones, mbj@microsoft.com
- o Intended Usage: COMMON
- o Restrictions on Usage: none
- o Author: Michael B. Jones, mbj@microsoft.com
- o Change Controller: IESG

8. Security Considerations

All of the security issues faced by any cryptographic application must be faced by a JWS/JWE/JWK agent. Among these issues are protecting the user's private and symmetric keys, preventing various attacks, and helping the user avoid mistakes such as inadvertently encrypting a message for the wrong recipient. The entire list of security considerations is beyond the scope of this document, but some significant considerations are listed here.

A key is no more trustworthy than the method by which it was received.

Private and symmetric keys MUST be protected from disclosure to unintended parties. One recommended means of doing so is to encrypt JWKs or JWK Sets containing them by using the JWK or JWK Set value as the plaintext of a JWE.

The security considerations in RFC 3447 [RFC3447] and RFC 6030 [RFC6030] about protecting private and symmetric keys also apply to this specification.

The security considerations in XML DSIG 2.0 [W3C.CR-xmldsig-core2-20120124], about key representations also apply to this specification, other than those that are XML specific.

The TLS Requirements in [JWS] also apply to this specification.

9. References

9.1. Normative References

[ECMAScript]
Ecma International, "ECMAScript Language Specification, 5.1 Edition", ECMA 262, June 2011.

[IANA.MediaTypes]
Internet Assigned Numbers Authority (IANA), "MIME Media Types", 2005.

[ITU.X690.1994]
International Telecommunications Union, "Information Technology - ASN.1 encoding rules: Specification of Basic Encoding Rules (BER), Canonical Encoding Rules (CER) and Distinguished Encoding Rules (DER)", ITU-T Recommendation X.690, 1994.

[JWA] Jones, M., "JSON Web Algorithms (JWA)", draft-ietf-jose-json-web-algorithms (work in progress), October 2013.

[JWE] Jones, M., Rescorla, E., and J. Hildebrand, "JSON Web Encryption (JWE)", draft-ietf-jose-json-web-encryption (work in progress), October 2013.

[JWS] Jones, M., Bradley, J., and N. Sakimura, "JSON Web Signature (JWS)", draft-ietf-jose-json-web-signature (work in progress), October 2013.

[RFC1421] Linn, J., "Privacy Enhancement for Internet Electronic Mail: Part I: Message Encryption and Authentication Procedures", RFC 1421, February 1993.

[RFC2046] Freed, N. and N. Borenstein, "Multipurpose Internet Mail Extensions (MIME) Part Two: Media Types", RFC 2046, November 1996.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997.

[RFC2818] Rescorla, E., "HTTP Over TLS", RFC 2818, May 2000.

[RFC3629] Yergeau, F., "UTF-8, a transformation format of ISO 10646", STD 63, RFC 3629, November 2003.

[RFC3986] Berners-Lee, T., Fielding, R., and L. Masinter, "Uniform Resource Identifier (URI): Generic Syntax", STD 66, RFC 3986, January 2005.

[RFC4627] Crockford, D., "The application/json Media Type for JavaScript Object Notation (JSON)", RFC 4627, July 2006.

[RFC4648] Josefsson, S., "The Base16, Base32, and Base64 Data Encodings", RFC 4648, October 2006.

[RFC5226] Narten, T. and H. Alvestrand, "Guidelines for Writing an IANA Considerations Section in RFCs", BCP 26, RFC 5226, May 2008.

[RFC5246] Dierks, T. and E. Rescorla, "The Transport Layer Security (TLS) Protocol Version 1.2", RFC 5246, August 2008.

[RFC5280] Cooper, D., Santesson, S., Farrell, S., Boeyen, S., Housley, R., and W. Polk, "Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile", RFC 5280, May 2008.

[USASCII] American National Standards Institute, "Coded Character Set -- 7-bit American Standard Code for Information Interchange", ANSI X3.4, 1986.

[W3C.CR-xmldsig-core2-20120124]
Eastlake, D., Reagle, J., Yiu, K., Solo, D., Datta, P., Hirsch, F., Cantor, S., and T. Roessler, "XML Signature Syntax and Processing Version 2.0", World Wide Web Consortium CR CR-xmldsig-core2-20120124, January 2012, <http://www.w3.org/TR/2012/CR-xmldsig-core2-20120124>.

9.2. Informative References

[MagicSignatures]
Panzer (editor), J., Laurie, B., and D. Balfanz, "Magic Signatures", January 2011.

[RFC3447] Jonsson, J. and B. Kaliski, "Public-Key Cryptography Standards (PKCS) #1: RSA Cryptography Specifications Version 2.1", RFC 3447, February 2003.

[RFC6030] Hoyer, P., Pei, M., and S. Machani, "Portable Symmetric Key Container (PSKC)", RFC 6030, October 2010.

Appendix A. Example JSON Web Key Sets

A.1. Example Public Keys

The following example JWK Set contains two public keys represented as JWKs: one using an Elliptic Curve algorithm and a second one using an RSA algorithm. The first specifies that the key is to be used for encryption. The second specifies that the key is to be used with the "RS256" algorithm. Both provide a Key ID for key matching purposes. In both cases, integers are represented using the base64url encoding of their big endian representations. (Long lines are broken are for display purposes only.)


```
{"keys":
  [
    {"kty":"EC",
     "crv":"P-256",
     "x":"MKBCTNIcKUSDii11ySs3526iDZ8AiTo7Tu6KPAqv7D4",
     "y":"4Etl6SRW2YiLUrN5vfvVHuhp7x8PxltmWWlbbM4IFyM",
     "use":"enc",
     "kid":"1"},

    {"kty":"RSA",
     "n": "0vx7agoebGcQSuuPiLJXZptN9nndrQmbXEps2aiAFbWhM78LhWx
4cbbfAAtVT86zwu1RK7aPFFxuhDR1L6tSoc_BJECPebWKRXjBZCiFV4n3oknjhMs
tn64tZ_2W-5JsGY4Hc5n9yBXArwl93lqt7_RN5w6Cf0h4QyQ5v-65YGjQR0_FDW2
QvzqY368QQMicAtaSqzs8KJZgnYb9c7d0zgdAZHzu6qMQvRL5hajrn1n91CbOpbI
SD08qNLyrdkt-bFTWhAI4vMQFh6WeZu0fM4lFd2NcRwr3XPksINHaQ-G_xBniIqb
w0Ls1jF44-csFCur-kEgU8awapJzKnqDKgw",
     "e":"AQAB",
     "alg":"RS256",
     "kid":"2011-04-29"}
  ]
}
```


A.2. Example Private Keys

The following example JWK Set contains two keys represented as JWKs containing both public and private key values: one using an Elliptic Curve algorithm and a second one using an RSA algorithm. This example extends the example in the previous section, adding private key values. (Line breaks are for display purposes only.)

```
{"keys":
  [
    {"kty":"EC",
     "crv":"P-256",
     "x":"MKBCTNIcKUSDii11ySs3526iDZ8AiTo7Tu6KPAqv7D4",
     "y":"4Etl6SRW2YiLUrN5vfvVHuhp7x8PxltmWWlbbM4IFyM",
     "d":"870MB6gfuTJ4HtUnUvYMyJpr5eUZNP4Bk43bVdj3eAE",
     "use":"enc",
     "kid":"1"},

    {"kty":"RSA",
     "n":"0vx7agoebGcQSuuPiLJXZptN9nndrQmbXEps2aiAFbWhM78LhWx4
cbbfAAtVT86zwu1RK7aPFFxuhDR1L6tSoc_BJECPebWKRXjBZCiFV4n3oknjhMst
n64tZ_2W-5JsGY4Hc5n9yBXArwl93lqt7_RN5w6Cf0h4QyQ5v-65YGjQR0_FDW2Q
vzqY368QQMicAtaSqzs8KJZgnYb9c7d0zgdAZHzu6qMQvRL5hajrn1n91CbOpbIS
D08qNLyrdkt-bFTWhAI4vMQFh6WeZu0fM4lFd2NcRwr3XPksINHaQ-G_xBniIqbw
0Ls1jF44-csFCur-kEgU8awapJzKnqDKgw",
     "e":"AQAB",
     "d":"X4cTteJY_gn4FYPsXB8rdXix5vwsg1FLN5E3EaG6RJoVH-HLLKD9
M7dx5oo7GURknchnrRweUkC7hT5fJLM0WbFAKNLWY2vv7B6NqXSzUvxT0_YSfqij
wp3RTzlBaCxWp4doFk5N2o8Gy_nHNKroADIkJ46pRUohsXywbReAdYaMwFs9tv8d
_cPVY3i07a3t8MN6TNwm0dSawm9v47UiCl3Sk5ZiG7xojPLu4sbg1U2jx4IBTNBz
nbJSzFHK66jT8bgkuqsk0GjskDJk19Z4qwjwbsnn4j2WBii3RL-Us2lGVkY8fkFz
me1z0HbIkfz0Y6mqnOYtqc0X4jfcKoAC8Q",
     "p":"83i-7IvMGXoMXCskv73TKr8637FiO7Z27zv8oj6pbWUQyLPQBQxtPV
nwD20R-60eTDmD2ujnMt5PoqMrm8RfmNhVWDtjjMmCMjOpSXicFHj7XOuVIYQyqV
WlWEh6dN36GVZYk93N8Bc9vY41xy8B9RzzOGVQzXvNEvn7O0nVbfs",
     "q":"3dfOR9cuYq-0S-mkFLzgItgMEfFzB2q3hWehMuG0oCuqnb3vobLyum
qjVZQO1dIrdwgTnCdpYzBcOfW5r370AFXjiWft_NGEiovonizhKpo9VVS78TzFgx
kIdrecRezsZ-1kYd_s1qDbxtkDEgfAITAG9LUnADun4vIcb6yelxk",
     "dp":"G4sPXkc6Ya9y8oJW9_ILj4xuppu0lzi_H7VTkS8xj5SdX3coE0oim
YwxIi2emTAue0UOa5dpgFGyBJ4c8tQ2VF402XRugKDTP8akYhFo5tAA77Qe_Nmtu
YZc3C3m3I24G2GvR5sSDxUyAN2zq8Lfn9EUms6rY3Ob8YeiKkTiBj0",
     "dq":"s9lAH9fggBsoFR8Oac2R_E2gw282rT2kGOAhvIllETE1efrA6huUU
vMfBcMpn8lqeW6vzznYY5SSQF7pMdC_agI3nG8Ibp1BUb0JUiraRNqUfLhcQb_d9
GF4Dh7e74WbRsobRonujTYN1xCaP6TO61jvWrX-L18txXw494Q_cgk",
     "qi":"GyM_p6JrXySiz1toFgKbWV-JdI3jQ4ypu9rbMWx3rQJBfmt0FoYzg
UIZEVFEcOqwemRN81zoDAaa-Bk0KWNGDjJHZDdDmFhW3AN7lI-puxk_mHZGJ11rx
yR8O55XLSe3SPmRfKwZI6yU24ZxvQKFYItdldUKGzO6Ia6zTKhAVRU",
     "alg":"RS256",
     "kid":"2011-04-29"}
  ]
}
```

A.3. Example Symmetric Keys

The following example JWK Set contains two symmetric keys represented as JWKs: one designated as being for use with the AES Key Wrap algorithm and a second one that is an HMAC key. (Line breaks are for display purposes only.)


```
{"keys":
  [
    {"kty":"oct",
     "alg":"A128KW",
     "k":"GawgguFyGrWKav7AX4VKUg"},

    {"kty":"oct",
     "k":"AyM1SysPpbyDfgZld3umj1qzKObwVMkoqQ-EstJQLr_T-1qS0gZH75
aKtMN3Yj0iPS4hcgUuTwjAzZr1Z9CAow",
     "kid":"HMAC key used in JWS A.1 example"}
  ]
}
```


Appendix B. Example Use of "x5c" (X.509 Certificate Chain) Parameter

The following is an example of a JWK with a RSA signing key represented both as a bare public key and as an X.509 certificate using the "x5c" parameter:


```
{"kty":"RSA",
 "use":"sig",
 "kid":"1b94c",
 "n":"vrjOfz9Ccdgx5nQudyhdoR17V-IubWMeOZCwX_jj0hgAsz2J_pqYW08
 PLbK_PdiVGKPrqzmDIsLI7sA25VEnHU1uCLNwBuUiCO11_-7dYbsr4iJmG0Q
 u2j8DsVyT1azpJC_NG84Ty5KKthuCaPod7iI7w0LK9orSMhBEwwZDCxTWq4a
 YWAchc8t-emd9qOvWtVMDC2BXksRngh6X5bUYLy6AyHKvj-nUy1wgzjYQDwH
 MTplCoLtU-o-8SNnZ1tmRoGE9uJkBLdh5gFENabWnU5m1ZqZPdwS-qo-meMv
 VfJb6jJVWRpl2SUtCnYG2C32qvbWbjZ_jBPD5eunqsIo1vQ",
 "e":"AQAB",
 "x5c":
  ["MIIDQjCCAiqgAwIBAgIGATz/FuLiMA0GCSqGSIb3DQEBBQUAMGIxCzAJB
  gNVBAYTAlVTMQswCQYDVQQIEwJDTzEPMA0GA1UEBxMGRGVudmVyMRwwGgYD
  VQQKExNQaW5nIElkZW50aXR5IENvcnAuMRcwFQYDVQQDEw5CcmlhbiBDYW1
  wYmVsbDAeFw0xMzAyMjEyMzI5MTVaFw0xODA4MTQyMjI5MTVaMGIxCzAJBg
  NVBAYTAlVTMQswCQYDVQQIEwJDTzEPMA0GA1UEBxMGRGVudmVyMRwwGgYDV
  QQKExNQaW5nIElkZW50aXR5IENvcnAuMRcwFQYDVQQDEw5CcmlhbiBDYW1w
  YmVsbDCCASIwDQYJKoZIhvcNAQEBBQADggEPADCCAQoCggEBAL64zn8/QnH
  YMeZ0LncoXaEde1fiLm1jHjmQsF/449IYALM9if6amFtPDy2yvz3YlRij66
  s5gyLCyO7ANuVRJx1NbgizcAblIgjtdf/u3WG7K+IiZhtELto/A7Fck9Ws6
  SQvzRvOE8uSirYbgmj6He4iO8NCyvaK0jIQRMMGQwsU1quGmFgHIXPLfnpn
  fajr1rVTAwtgV5LEZ4Iel+W1GC8ugMhyr4/p1MtcIM42EA8BzE6ZQqC7VPq
  PvEjZ2dbZkaBhPbiZAS3YeYBRDWm1p1OZtWamT3cEvqqPpnjL1XyW+oyVVk
  aZdklLQp2Btgt9qr21m42f4wTw+Xrp6rCKNb0CAwEAATANBgkqhkiG9w0BA
  QUFAAOCAQEAh8zGlfSlcI0o3rYDPBB07aXNswb4ECNIKG0CETTUxmXl9KUL
  +9gGlqCz5iWLOgWsnrcKcY0vXPG9J1r9AqBNTqNgHq2G03X09266X5CpOe1
  zFo+Owb1zxtp3PehFdfQJ610CDLEaS9V9Rqp17hCyybEpOGVwe8fnk+fbEL
  2Bo3UPGrpsHzUoaGpDftmWssZkhpBJKVMJyf/RuP2SmmaIzmnw9JiSlYhzo
  4tpzd5rFXhjRbg4zW9C+2qok+2+qDM1iJ684gPHMIY8aLWrdgQTxkumGmTq
  gawR+N5MDtdPTEQ0XfIBc2cJEUyMTY5MPvACWpkA6SdS4xSvdXK3IVfOWA=="]
}
```


Appendix C. Example Encrypted RSA Private Key

This example encrypts an RSA private key to the recipient using "PBES2-HS256+A128KW" for key encryption and "A128CBC+HS256" for content encryption.

NOTE: Unless otherwise indicated, all line breaks are included solely for readability.

C.1. Plaintext RSA Private Key

The following RSA key is the plaintext for the encryption operation, formatted as a JWK object:


```
{
 "kty":"RSA",
 "kid":"juliet@capulet.lit",
 "use":"enc",
 "n":"t6Q8PWSi1dkJj9hTP8hNYFlvadM7DflW9mWepOJhJ66w7nyoK1gPNqFMSQRy
      O125Gp-TEkodhWr0iujjHVx7BcV0llS4w5ACGgPrcAd6ZcSR0-Iqom-QFcNP
      8Sjg086MwoqQU_LYywlAGZ21WSdS_PERyGFiNnj3QQlO8Yns5jCtLCRwLHL0
      Pb1fEv45AuRIuUfVcPySBWYnDyGxvjYGDSM-AqWS9zIQ2ZilgT-GqUmipg0X
      OC0Cc20rgLe2ymLHjpHciCKVAbY5-L32-lSeZO-Os6U15_aXrk9Gw8cPUaX1
      _I8sLGuSiVdt3C_Fn2PZ3Z8i744FPFGGcG1qs2Wz-Q",
 "e":"AQAB",
 "d":"GRtbIQmhOZtyszfgKdg4u_N-R_mZGU_9k7JQ_jn1DnfTuMdSNprTeaSTyWfS
      NkuaAwnOEbIQVy1IQbWVV25NY3ybc_IhUJtfri7bAXYEReWaCl3hdlPKXy9U
      vqPYGR0kIXTQRqns-dVJ7jahlI7LyckrpTmrM8dWBo4_PMaenNnPiQgO0xnu
      ToxutRZJfJvG4Ox4ka3GORQd9CsCZ2vsUDmsXOfUENOyMqADC6p1M3h33tsu
      rY15k9qMSpG9OX_IJAXmxzAh_tWiZOwk2K4yxH9tS3Lq1yX8C1EWmeRDkK2a
      hecG85-oLKQt5VEpWHKmjOi_gJSdSgqcN96X52esAQ",
 "p":"2rnSOV4hKSN8sS4CgcQHFbs08XboFDqKum3sc4h3GRxrTmQdl1ZK9uw-PIHf
      QP0FkxXVrx-WE-ZEbrqivH_2iCLUS7wAl6XvARt1KkIaUxPPSYB9yk31s0Q8
      UK96E3_OrADAYtAJs-M3JxCLfNgqh56HDnETTQhH3rCT5T3yJws",
 "q":"1u_RiFDP7LBYh3N4GXLT9OpSKYP0uQZyiaZwBtOCBNJgQxaj10RWjsZu0c6I
      edis4S7B_coSKB0Kj9PaPaBzg-IySRvvcQuPamQu66riMhjVtG6TlV8CLCYK
      rYl52ziqK0E_ym2QnkwsUX7eYTB7LbAHRK9GqocDE5B0f808I4s",
 "dp":"KkMTWqBUefVwZ2_Dbj1pPQqyHSHjj90L5x_MOzqYAJMcLMZtbUtwKqvVDq3
      tbEo3ZIcohbDtt6SbfmWzggabpQxNxuBpoOOf_a_HgMXK_lhqigI4y_kqS1w
      Y52IwjUn5rgRrJ-yYo1h41KR-vz2pYhEAeYrhttWtxVqLCRViD6c",
 "dq":"AvfS0-gRxvn0bwJoMSnFxYcK1WnuEjQFluMGfwGitQBWtfZ1Er7t1xDkbN9
      GQTB9yqpDoYaN06H7CFtrkxhJIBQaj6nkF5KKS3TQtQ5qCzkOkmxIe3KRbBy
      mXxkb5qwUpX5ELD5xFc6FeiafWYY63TmmEAu_lRFCOJ3xDea-ots",
 "qi":"lSQi-w9CpyUReMErP1RsBLk7wNtOvs5EQpPqmuMvqW57NBUczScEoPwmUqq
      abu9V0-Py4dQ57_bapoKRu1R90bvuFnU63SHWEFglZQvJDMeAvmj4sm-Fp0o
      Yu_neotgQ0hzbI5gry7ajdYy9-2lNx_76aBZoOUu9HCJ-UsfSOI8"
}
```


The octets representing the Plaintext are:

```
[ 123, 34, 107, 116, 121, 34, 58, 34, 82, 83, 65, 34, 44, 34, 107,
105, 100, 34, 58, 34, 106, 117, 108, 105, 101, 116, 64, 99, 97, 112,
117, 108, 101, 116, 46, 108, 105, 116, 34, 44, 34, 117, 115, 101, 34,
58, 34, 101, 110, 99, 34, 44, 34, 110, 34, 58, 34, 116, 54, 81, 56,
80, 87, 83, 105, 49, 100, 107, 74, 106, 57, 104, 84, 80, 56, 104, 78,
89, 70, 108, 118, 97, 100, 77, 55, 68, 102, 108, 87, 57, 109, 87,
101, 112, 79, 74, 104, 74, 54, 54, 119, 55, 110, 121, 111, 75, 49,
```

103, 80, 78, 113, 70, 77, 83, 81, 82, 121, 79, 49, 50, 53, 71, 112,
45, 84, 69, 107, 111, 100, 104, 87, 114, 48, 105, 117, 106, 106, 72,
86, 120, 55, 66, 99, 86, 48, 108, 108, 83, 52, 119, 53, 65, 67, 71,
103, 80, 114, 99, 65, 100, 54, 90, 99, 83, 82, 48, 45, 73, 113, 111,
109, 45, 81, 70, 99, 78, 80, 56, 83, 106, 103, 48, 56, 54, 77, 119,
111, 113, 81, 85, 95, 76, 89, 121, 119, 108, 65, 71, 90, 50, 49, 87,
83, 100, 83, 95, 80, 69, 82, 121, 71, 70, 105, 78, 110, 106, 51, 81,
81, 108, 79, 56, 89, 110, 115, 53, 106, 67, 116, 76, 67, 82, 119, 76,
72, 76, 48, 80, 98, 49, 102, 69, 118, 52, 53, 65, 117, 82, 73, 117,
85, 102, 86, 99, 80, 121, 83, 66, 87, 89, 110, 68, 121, 71, 120, 118,
106, 89, 71, 68, 83, 77, 45, 65, 113, 87, 83, 57, 122, 73, 81, 50,
90, 105, 108, 103, 84, 45, 71, 113, 85, 109, 105, 112, 103, 48, 88,
79, 67, 48, 67, 99, 50, 48, 114, 103, 76, 101, 50, 121, 109, 76, 72,
106, 112, 72, 99, 105, 67, 75, 86, 65, 98, 89, 53, 45, 76, 51, 50,
45, 108, 83, 101, 90, 79, 45, 79, 115, 54, 85, 49, 53, 95, 97, 88,
114, 107, 57, 71, 119, 56, 99, 80, 85, 97, 88, 49, 95, 73, 56, 115,
76, 71, 117, 83, 105, 86, 100, 116, 51, 67, 95, 70, 110, 50, 80, 90,
51, 90, 56, 105, 55, 52, 52, 70, 80, 70, 71, 71, 99, 71, 49, 113,
115, 50, 87, 122, 45, 81, 34, 44, 34, 101, 34, 58, 34, 65, 81, 65,
66, 34, 44, 34, 100, 34, 58, 34, 71, 82, 116, 98, 73, 81, 109, 104,
79, 90, 116, 121, 115, 122, 102, 103, 75, 100, 103, 52, 117, 95, 78,
45, 82, 95, 109, 90, 71, 85, 95, 57, 107, 55, 74, 81, 95, 106, 110,
49, 68, 110, 102, 84, 117, 77, 100, 83, 78, 112, 114, 84, 101, 97,
83, 84, 121, 87, 102, 83, 78, 107, 117, 97, 65, 119, 110, 79, 69, 98,
73, 81, 86, 121, 49, 73, 81, 98, 87, 86, 86, 50, 53, 78, 89, 51, 121,
98, 99, 95, 73, 104, 85, 74, 116, 102, 114, 105, 55, 98, 65, 88, 89,
69, 82, 101, 87, 97, 67, 108, 51, 104, 100, 108, 80, 75, 88, 121, 57,
85, 118, 113, 80, 89, 71, 82, 48, 107, 73, 88, 84, 81, 82, 113, 110,
115, 45, 100, 86, 74, 55, 106, 97, 104, 108, 73, 55, 76, 121, 99,
107, 114, 112, 84, 109, 114, 77, 56, 100, 87, 66, 111, 52, 95, 80,
77, 97, 101, 110, 78, 110, 80, 105, 81, 103, 79, 48, 120, 110, 117,
84, 111, 120, 117, 116, 82, 90, 74, 102, 74, 118, 71, 52, 79, 120,
52, 107, 97, 51, 71, 79, 82, 81, 100, 57, 67, 115, 67, 90, 50, 118,
115, 85, 68, 109, 115, 88, 79, 102, 85, 69, 78, 79, 121, 77, 113, 65,
68, 67, 54, 112, 49, 77, 51, 104, 51, 51, 116, 115, 117, 114, 89, 49,
53, 107, 57, 113, 77, 83, 112, 71, 57, 79, 88, 95, 73, 74, 65, 88,
109, 120, 122, 65, 104, 95, 116, 87, 105, 90, 79, 119, 107, 50, 75,
52, 121, 120, 72, 57, 116, 83, 51, 76, 113, 49, 121, 88, 56, 67, 49,
69, 87, 109, 101, 82, 68, 107, 75, 50, 97, 104, 101, 99, 71, 56, 53,
45, 111, 76, 75, 81, 116, 53, 86, 69, 112, 87, 72, 75, 109, 106, 79,
105, 95, 103, 74, 83, 100, 83, 103, 113, 99, 78, 57, 54, 88, 53, 50,
101, 115, 65, 81, 34, 44, 34, 112, 34, 58, 34, 50, 114, 110, 83, 79,
86, 52, 104, 75, 83, 78, 56, 115, 83, 52, 67, 103, 99, 81, 72, 70,
98, 115, 48, 56, 88, 98, 111, 70, 68, 113, 75, 117, 109, 51, 115, 99,
52, 104, 51, 71, 82, 120, 114, 84, 109, 81, 100, 108, 49, 90, 75, 57,
117, 119, 45, 80, 73, 72, 102, 81, 80, 48, 70, 107, 120, 88, 86, 114,
120, 45, 87, 69, 45, 90, 69, 98, 114, 113, 105, 118, 72, 95, 50, 105,
67, 76, 85, 83, 55, 119, 65, 108, 54, 88, 118, 65, 82, 116, 49, 75,

107, 73, 97, 85, 120, 80, 80, 83, 89, 66, 57, 121, 107, 51, 49, 115,
48, 81, 56, 85, 75, 57, 54, 69, 51, 95, 79, 114, 65, 68, 65, 89, 116,
65, 74, 115, 45, 77, 51, 74, 120, 67, 76, 102, 78, 103, 113, 104, 53,
54, 72, 68, 110, 69, 84, 84, 81, 104, 72, 51, 114, 67, 84, 53, 84,
51, 121, 74, 119, 115, 34, 44, 34, 113, 34, 58, 34, 49, 117, 95, 82,
105, 70, 68, 80, 55, 76, 66, 89, 104, 51, 78, 52, 71, 88, 76, 84, 57,
79, 112, 83, 75, 89, 80, 48, 117, 81, 90, 121, 105, 97, 90, 119, 66,
116, 79, 67, 66, 78, 74, 103, 81, 120, 97, 106, 49, 48, 82, 87, 106,
115, 90, 117, 48, 99, 54, 73, 101, 100, 105, 115, 52, 83, 55, 66, 95,
99, 111, 83, 75, 66, 48, 75, 106, 57, 80, 97, 80, 97, 66, 122, 103,
45, 73, 121, 83, 82, 118, 118, 99, 81, 117, 80, 97, 109, 81, 117, 54,
54, 114, 105, 77, 104, 106, 86, 116, 71, 54, 84, 108, 86, 56, 67, 76,
67, 89, 75, 114, 89, 108, 53, 50, 122, 105, 113, 75, 48, 69, 95, 121,
109, 50, 81, 110, 107, 119, 115, 85, 88, 55, 101, 89, 84, 66, 55, 76,
98, 65, 72, 82, 75, 57, 71, 113, 111, 99, 68, 69, 53, 66, 48, 102,
56, 48, 56, 73, 52, 115, 34, 44, 34, 100, 112, 34, 58, 34, 75, 107,
77, 84, 87, 113, 66, 85, 101, 102, 86, 119, 90, 50, 95, 68, 98, 106,
49, 112, 80, 81, 113, 121, 72, 83, 72, 106, 106, 57, 48, 76, 53, 120,
95, 77, 79, 122, 113, 89, 65, 74, 77, 99, 76, 77, 90, 116, 98, 85,
116, 119, 75, 113, 118, 86, 68, 113, 51, 116, 98, 69, 111, 51, 90,
73, 99, 111, 104, 98, 68, 116, 116, 54, 83, 98, 102, 109, 87, 122,
103, 103, 97, 98, 112, 81, 120, 78, 120, 117, 66, 112, 111, 79, 79,
102, 95, 97, 95, 72, 103, 77, 88, 75, 95, 108, 104, 113, 105, 103,
73, 52, 121, 95, 107, 113, 83, 49, 119, 89, 53, 50, 73, 119, 106, 85,
110, 53, 114, 103, 82, 114, 74, 45, 121, 89, 111, 49, 104, 52, 49,
75, 82, 45, 118, 122, 50, 112, 89, 104, 69, 65, 101, 89, 114, 104,
116, 116, 87, 116, 120, 86, 113, 76, 67, 82, 86, 105, 68, 54, 99, 34,
44, 34, 100, 113, 34, 58, 34, 65, 118, 102, 83, 48, 45, 103, 82, 120,
118, 110, 48, 98, 119, 74, 111, 77, 83, 110, 70, 120, 89, 99, 75, 49,
87, 110, 117, 69, 106, 81, 70, 108, 117, 77, 71, 102, 119, 71, 105,
116, 81, 66, 87, 116, 102, 90, 49, 69, 114, 55, 116, 49, 120, 68,
107, 98, 78, 57, 71, 81, 84, 66, 57, 121, 113, 112, 68, 111, 89, 97,
78, 48, 54, 72, 55, 67, 70, 116, 114, 107, 120, 104, 74, 73, 66, 81,
97, 106, 54, 110, 107, 70, 53, 75, 75, 83, 51, 84, 81, 116, 81, 53,
113, 67, 122, 107, 79, 107, 109, 120, 73, 101, 51, 75, 82, 98, 66,
121, 109, 88, 120, 107, 98, 53, 113, 119, 85, 112, 88, 53, 69, 76,
68, 53, 120, 70, 99, 54, 70, 101, 105, 97, 102, 87, 89, 89, 54, 51,
84, 109, 109, 69, 65, 117, 95, 108, 82, 70, 67, 79, 74, 51, 120, 68,
101, 97, 45, 111, 116, 115, 34, 44, 34, 113, 105, 34, 58, 34, 108,
83, 81, 105, 45, 119, 57, 67, 112, 121, 85, 82, 101, 77, 69, 114, 80,
49, 82, 115, 66, 76, 107, 55, 119, 78, 116, 79, 118, 115, 53, 69, 81,
112, 80, 113, 109, 117, 77, 118, 113, 87, 53, 55, 78, 66, 85, 99,
122, 83, 99, 69, 111, 80, 119, 109, 85, 113, 113, 97, 98, 117, 57,
86, 48, 45, 80, 121, 52, 100, 81, 53, 55, 95, 98, 97, 112, 111, 75,
82, 117, 49, 82, 57, 48, 98, 118, 117, 70, 110, 85, 54, 51, 83, 72,
87, 69, 70, 103, 108, 90, 81, 118, 74, 68, 77, 101, 65, 118, 109,
106, 52, 115, 109, 45, 70, 112, 48, 111, 89, 117, 95, 110, 101, 111,
116, 103, 81, 48, 104, 122, 98, 73, 53, 103, 114, 121, 55, 97, 106,

100, 89, 121, 57, 45, 50, 108, 78, 120, 95, 55, 54, 97, 66, 90, 111, 79, 85, 117, 57, 72, 67, 74, 45, 85, 115, 102, 83, 79, 73, 56, 34, 125]

C.2. JWE Header

The following example JWE Protected Header declares that:

- o the Content Encryption Key is encrypted to the recipient using the PSE2-HS256+A128KW algorithm to produce the JWE Encrypted Key,
- o the Salt (p2s) is [217, 96, 147, 112, 150, 117, 70, 247, 127, 8, 155, 137, 174, 42, 80, 215],
- o the Iteration Count (p2c) is 4096,
- o the Plaintext is encrypted using the AES_128_CBC_HMAC_SHA_256 algorithm to produce the Ciphertext, and
- o the content type is application/jwk+json.


```
{
 "alg":"PBES2-HS256+A128KW",
 "p2s":"2WCTcJZ1Rvd_CJuJripQ1w",
 "p2c":4096,
 "enc":"A128CBC-HS256",
 "cty":"jwk+json"
}
```


Encoding this JWE Protected Header as BASE64URL(UTF8(JWE Protected Header)) gives this value:


```
eyJhbGciOiJQQkVTMi1IUzI1NitBMTI4S1ciLCJwMnMiOiIyV0NUY0paMVJ2ZF9DSn
VKcmlwUTF3IiwicDJjIjo0MDk2LCJlbmMiOiJBMTI4Q0JDLUhTMjU2IiwiY3R5Ijoi
andrK2pzb24ifQ
```


C.3. Content Encryption Key (CEK)

Generate a 256 bit random Content Encryption Key (CEK). In this example, the value is:

[111, 27, 25, 52, 66, 29, 20, 78, 92, 176, 56, 240, 65, 208, 82, 112, 161, 131, 36, 55, 202, 236, 185, 172, 129, 23, 153, 194, 195, 48, 253, 182]

C.4. Key Encryption

Encrypt the CEK with a shared passphrase using the "PBES2-HS256+A128KW" algorithm and the specified Salt and Iteration Count values to produce the JWE Encrypted Key. This example uses the following passphrase:

Thus from my lips, by yours, my sin is purged.

The octets representing the passphrase are:

[84, 104, 117, 115, 32, 102, 114, 111, 109, 32, 109, 121, 32, 108, 105, 112, 115, 44, 32, 98, 121, 32, 121, 111, 117, 114, 115, 44, 32, 109, 121, 32, 115, 105, 110, 32, 105, 115, 32, 112, 117, 114, 103, 101, 100, 46]

The resulting JWE Encrypted Key value is:

[201, 236, 143, 112, 12, 234, 200, 211, 33, 241, 255, 65, 112, 63, 172, 146, 105, 107, 122, 0, 30, 21, 44, 21, 14, 61, 200, 57, 30, 253, 228, 83, 218, 82, 138, 80, 121, 254, 193, 121]

Encoding this JWE Encrypted Key as BASE64URL(JWE Encrypted Key) gives this value:

yeyPcAzqyNMh8f9BcD-skmlregAeFSwVDj3IOR795FPaUopQef7BeQ

C.5. Initialization Vector

Generate a random 128 bit JWE Initialization Vector. In this example, the value is:

[97, 239, 99, 214, 171, 54, 216, 57, 145, 72, 7, 93, 34, 31, 149, 156]

Encoding this JWE Initialization Vector as BASE64URL(JWE Initialization Vector) gives this value:

Ye9j1qs22DmRSAddIh-VnA

C.6. Additional Authenticated Data

Let the Additional Authenticated Data encryption parameter be ASCII(BASE64URL(UTF8(JWE Protected Header))). This value is:

[123, 34, 97, 108, 103, 34, 58, 34, 80, 66, 69, 83, 50, 45, 72, 83, 50, 53, 54, 43, 65, 49, 50, 56, 75, 87, 34, 44, 34, 112, 50, 115, 34, 58, 34, 50, 87, 67, 84, 99, 74, 90, 49, 82, 118, 100, 95, 67, 74,

117, 74, 114, 105, 112, 81, 49, 119, 34, 44, 34, 112, 50, 99, 34, 58,
52, 48, 57, 54, 44, 34, 101, 110, 99, 34, 58, 34, 65, 49, 50, 56, 67,
66, 67, 45, 72, 83, 50, 53, 54, 34, 44, 34, 99, 116, 121, 34, 58, 34,
106, 119, 107, 43, 106, 115, 111, 110, 34, 125]

C.7. Content Encryption

Encrypt the Plaintext with AES_128_CBC_HMAC_SHA_256 using the CEK as the encryption key, the JWE Initialization Vector, and the Additional Authenticated Data value above. The resulting Ciphertext is:

[3, 8, 65, 242, 92, 107, 148, 168, 197, 159, 77, 139, 25, 97, 42,
131, 110, 199, 225, 56, 61, 127, 38, 64, 108, 91, 247, 167, 150, 98,
112, 122, 99, 235, 132, 50, 28, 46, 56, 170, 169, 89, 220, 145, 38,
157, 148, 224, 66, 140, 8, 169, 146, 117, 222, 54, 242, 28, 31, 11,
129, 227, 226, 169, 66, 117, 133, 254, 140, 216, 115, 203, 131, 60,
60, 47, 233, 132, 121, 13, 35, 188, 53, 19, 172, 77, 59, 54, 211,
158, 172, 25, 60, 111, 0, 80, 201, 158, 160, 210, 68, 55, 12, 67,
136, 130, 87, 216, 197, 95, 62, 20, 155, 205, 5, 140, 27, 168, 221,
65, 114, 78, 157, 254, 46, 206, 182, 52, 135, 87, 239, 3, 34, 186,
126, 220, 151, 17, 33, 237, 57, 96, 172, 183, 58, 45, 248, 103, 241,
142, 136, 7, 53, 16, 173, 181, 7, 93, 92, 252, 1, 53, 212, 242, 8,
255, 11, 239, 181, 24, 148, 136, 111, 24, 161, 244, 23, 106, 69, 157,
215, 243, 189, 240, 166, 169, 249, 72, 38, 201, 99, 223, 173, 229, 9,
222, 82, 79, 157, 176, 248, 85, 239, 121, 163, 1, 31, 48, 98, 206,
61, 249, 104, 216, 201, 227, 105, 48, 194, 193, 10, 36, 160, 159,
241, 166, 84, 54, 188, 211, 243, 242, 40, 46, 45, 193, 193, 160, 169,
101, 201, 1, 73, 47, 105, 142, 88, 28, 42, 132, 26, 61, 58, 63, 142,
243, 77, 26, 179, 153, 166, 46, 203, 208, 49, 55, 229, 34, 178, 4,
109, 180, 204, 204, 115, 1, 103, 193, 5, 91, 215, 214, 195, 1, 110,
208, 53, 144, 36, 105, 12, 54, 25, 129, 101, 15, 183, 150, 250, 147,
115, 227, 58, 250, 5, 128, 232, 63, 15, 14, 19, 141, 124, 253, 142,
137, 189, 135, 26, 44, 240, 27, 88, 132, 105, 127, 6, 71, 37, 41,
124, 187, 165, 140, 34, 200, 123, 80, 228, 24, 231, 176, 132, 171,
138, 145, 152, 116, 224, 50, 141, 51, 147, 91, 186, 7, 246, 106, 217,
148, 244, 227, 244, 45, 220, 121, 165, 224, 148, 181, 17, 181, 128,
197, 101, 237, 11, 169, 229, 149, 199, 78, 56, 15, 14, 190, 91, 216,
222, 247, 213, 74, 40, 8, 96, 20, 168, 119, 96, 26, 24, 52, 37, 82,
127, 57, 176, 147, 118, 59, 7, 224, 33, 117, 72, 155, 29, 82, 26,
215, 189, 140, 119, 28, 152, 118, 93, 222, 194, 192, 148, 115, 83,
253, 216, 212, 108, 88, 83, 175, 172, 220, 97, 79, 110, 42, 223, 170,
161, 34, 164, 144, 193, 76, 122, 92, 160, 41, 178, 175, 6, 35, 96,
113, 96, 158, 90, 129, 101, 26, 45, 70, 180, 189, 230, 15, 5, 247,
150, 209, 94, 171, 26, 13, 142, 212, 129, 1, 176, 5, 0, 112, 203,
174, 185, 119, 76, 233, 189, 54, 172, 189, 245, 223, 253, 205, 12,
88, 9, 126, 157, 225, 90, 40, 229, 191, 63, 30, 160, 224, 69, 3, 140,
109, 70, 89, 37, 213, 245, 194, 210, 180, 188, 63, 210, 139, 221, 2,
144, 200, 20, 177, 216, 29, 227, 242, 106, 12, 135, 142, 139, 144,

82, 225, 162, 171, 176, 108, 99, 6, 43, 193, 161, 116, 234, 216, 1,
242, 21, 124, 162, 98, 205, 124, 193, 38, 12, 242, 90, 101, 76, 204,
184, 124, 58, 180, 16, 240, 26, 76, 195, 250, 212, 191, 185, 191, 97,
198, 186, 73, 225, 75, 14, 90, 123, 121, 172, 101, 50, 160, 221, 141,
253, 205, 126, 77, 9, 87, 198, 110, 104, 182, 141, 120, 51, 25, 232,
3, 32, 80, 6, 156, 8, 18, 4, 135, 221, 142, 25, 135, 2, 129, 132,
115, 227, 74, 141, 28, 119, 11, 141, 117, 134, 198, 62, 150, 254, 97,
75, 197, 251, 99, 89, 204, 224, 226, 67, 83, 175, 89, 0, 81, 29, 38,
207, 89, 140, 255, 197, 177, 164, 128, 62, 116, 224, 180, 109, 169,
28, 2, 59, 176, 130, 252, 44, 178, 81, 24, 181, 176, 75, 44, 61, 91,
12, 37, 21, 255, 83, 130, 197, 16, 231, 60, 217, 56, 131, 118, 168,
202, 58, 52, 84, 124, 162, 185, 174, 162, 226, 242, 112, 68, 246,
202, 16, 208, 52, 154, 58, 129, 80, 102, 33, 171, 6, 186, 177, 14,
195, 88, 136, 6, 0, 155, 28, 100, 162, 207, 162, 222, 117, 248, 170,
208, 114, 87, 31, 57, 176, 33, 57, 83, 253, 12, 168, 110, 194, 59,
22, 86, 48, 227, 196, 22, 176, 218, 122, 149, 21, 249, 195, 178, 174,
250, 20, 34, 120, 60, 139, 201, 99, 40, 18, 177, 17, 54, 54, 6, 3,
222, 128, 160, 88, 11, 27, 0, 81, 192, 36, 41, 169, 146, 8, 47, 64,
136, 28, 64, 209, 67, 135, 202, 20, 234, 182, 91, 204, 146, 195, 187,
0, 72, 77, 11, 111, 152, 204, 252, 177, 212, 89, 33, 50, 132, 184,
44, 183, 186, 19, 250, 69, 176, 201, 102, 140, 14, 143, 212, 212,
160, 123, 208, 185, 27, 155, 68, 77, 133, 198, 2, 126, 155, 215, 22,
91, 30, 217, 176, 172, 244, 156, 174, 143, 75, 90, 21, 102, 1, 160,
59, 253, 188, 88, 57, 185, 197, 83, 24, 22, 180, 174, 47, 207, 52, 1,
141, 146, 119, 233, 68, 228, 224, 228, 193, 248, 155, 202, 90, 7,
213, 88, 33, 108, 107, 14, 86, 8, 120, 250, 58, 142, 35, 164, 238,
221, 219, 35, 123, 88, 199, 192, 143, 104, 83, 17, 166, 243, 247, 11,
166, 67, 68, 204, 132, 23, 110, 103, 228, 14, 55, 122, 88, 57, 180,
178, 237, 52, 130, 214, 245, 102, 123, 67, 73, 175, 1, 127, 112, 148,
94, 132, 164, 197, 153, 217, 87, 25, 89, 93, 63, 22, 66, 166, 90,
251, 101, 10, 145, 66, 17, 124, 36, 255, 165, 226, 97, 16, 86, 112,
154, 88, 105, 253, 56, 209, 229, 122, 103, 51, 24, 228, 190, 3, 236,
48, 182, 121, 176, 140, 128, 117, 87, 251, 224, 37, 23, 248, 21, 218,
85, 251, 136, 84, 147, 143, 144, 46, 155, 183, 251, 89, 86, 23, 26,
237, 100, 167, 32, 130, 173, 237, 89, 55, 110, 70, 142, 127, 65, 230,
208, 109, 69, 19, 253, 84, 130, 130, 193, 92, 58, 108, 150, 42, 136,
249, 234, 86, 241, 182, 19, 117, 246, 26, 181, 92, 101, 155, 44, 103,
235, 173, 30, 140, 90, 29, 183, 190, 77, 53, 206, 127, 5, 87, 8, 187,
184, 92, 4, 157, 22, 18, 105, 251, 39, 88, 182, 181, 103, 148, 233,
6, 63, 70, 188, 7, 101, 216, 127, 77, 31, 12, 233, 7, 147, 106, 30,
150, 77, 145, 13, 205, 48, 56, 245, 220, 89, 252, 127, 51, 180, 36,
31, 55, 18, 214, 230, 254, 217, 197, 65, 247, 27, 215, 117, 247, 108,
157, 121, 11, 63, 150, 195, 83, 6, 134, 242, 41, 24, 105, 204, 5, 63,
192, 14, 159, 113, 72, 140, 128, 51, 215, 80, 215, 39, 149, 94, 79,
128, 34, 5, 129, 82, 83, 121, 187, 37, 146, 27, 32, 177, 167, 71, 9,
195, 30, 199, 196, 205, 252, 207, 69, 8, 120, 27, 190, 51, 43, 75,
249, 234, 167, 116, 206, 203, 199, 43, 108, 87, 48, 155, 140, 228,
210, 85, 25, 161, 96, 67, 8, 205, 64, 39, 75, 88, 44, 238, 227, 16,

```
0, 100, 93, 129, 18, 4, 149, 50, 68, 72, 99, 35, 111, 254, 27, 102,
175, 108, 233, 87, 181, 44, 169, 18, 139, 79, 208, 14, 202, 192, 5,
162, 222, 231, 149, 24, 211, 49, 120, 101, 39, 206, 87, 147, 204,
200, 251, 104, 115, 5, 127, 117, 195, 79, 151, 18, 224, 52, 0, 245,
4, 85, 255, 103, 217, 0, 116, 198, 80, 91, 167, 192, 154, 199, 197,
149, 237, 51, 2, 131, 30, 226, 95, 105, 48, 68, 135, 208, 144, 120,
176, 145, 157, 8, 171, 80, 94, 61, 92, 92, 220, 157, 13, 138, 51, 23,
185, 124, 31, 77, 1, 87, 241, 43, 239, 55, 122, 86, 210, 48, 208,
204, 112, 144, 80, 147, 106, 219, 47, 253, 31, 134, 176, 16, 135,
219, 95, 17, 129, 83, 236, 125, 136, 112, 86, 228, 252, 71, 129, 218,
174, 156, 236, 12, 27, 159, 11, 138, 252, 253, 207, 31, 115, 214,
118, 239, 203, 16, 211, 205, 99, 22, 51, 163, 107, 162, 246, 199, 67,
127, 34, 108, 197, 53, 117, 58, 199, 3, 190, 74, 70, 190, 65, 235,
175, 97, 157, 215, 252, 189, 245, 100, 229, 248, 46, 90, 126, 237, 4,
159, 128, 58, 7, 156, 236, 69, 191, 85, 240, 179, 224, 249, 152, 49,
195, 223, 60, 78, 186, 157, 155, 217, 58, 105, 116, 164, 217, 111,
215, 150, 218, 252, 84, 86, 248, 140, 240, 226, 61, 106, 208, 95, 60,
163, 6, 0, 235, 253, 162, 96, 62, 234, 251, 249, 35, 21, 7, 211, 233,
86, 50, 33, 203, 67, 248, 60, 190, 123, 48, 167, 226, 90, 191, 71,
56, 183, 165, 17, 85, 76, 238, 140, 211, 168, 53, 223, 194, 4, 97,
149, 156, 120, 137, 76, 33, 229, 243, 194, 208, 198, 202, 139, 28,
114, 46, 224, 92, 254, 83, 100, 134, 158, 92, 70, 78, 61, 62, 138,
24, 173, 216, 66, 198, 70, 254, 47, 59, 193, 53, 6, 139, 19, 153,
253, 28, 199, 122, 160, 27, 67, 234, 209, 227, 139, 4, 50, 7, 178,
183, 89, 252, 32, 128, 137, 55, 52, 29, 89, 12, 111, 42, 181, 51,
170, 132, 132, 207, 170, 228, 254, 178, 213, 0, 136, 175, 8 ]
```

The resulting Authentication Tag value is:

```
[ 125, 249, 143, 191, 240, 4, 204, 132, 62, 241, 113, 178, 91, 88,
254, 19 ]
```

Encoding this JWE Ciphertext as BASE64URL(JWE Ciphertext) gives this value:

AwhB8lxrlKjFn02LGWEqg27H4Tg9fyZAbFv3p5ZicHpj64QyHC44qqlZ3JEmnZTgQo
wIqZJ13jbyHB8LgePiqUJ1hf6M2HPLgzw8L-mEeQ0jvDUTrE07NtOerBk8bwBQyZ6g
0kQ3DEOIglfYxV8-FJvNBYwbqN1Bck6d_i7OtjSHV-8DIrp-3JcRIe05YKy3Oi34Z_
GOiAc1EK21B11c_AE11PII_wvvtRiUiG8YofQXakWd1_O98Kap-UgmyWPfreUJ3lJP
nbD4Ve95owEfMGLOPflo2MnjaTDCwQokoJ_xplQ2vNPz8iguLcHBoKllyQFJL2mOWB
wqhBo9Oj-O800as5mmLsvQMTflIrIEbbTMzHMBZ8EFW9fWwwFu0DWQJGkMNhmBZQ-3
lvqTc-M6-gWA6D8PDhONfP2Oib2HGizwG1iEaX8GRyUpfLuljCLIe1DkGOewhKuKkZ
h04DKNM5Nbugf2atmU9OP0Ldx5peCUtRG1gMVl7Qup5ZXHTjgPDr5b2N731UooCGAU
qHdgGhg0JVJ_ObCTdjsH4CF1SJsdUhrXvYx3HJh2Xd7CwJRzU_3Y1GxYU6-s3GFPbi
rfqqEipJDBTHpcoCmyrwYjYHFgnlqBZRotRrS95g8F95bRXqsaDY7UgQGwBQBwy665
d0zpvTasvfXf_c0MWAl-neFaKOW_Px6g4EUDjG1GWSXV9cLStLw_0ovdApDIFLHYHe
PyagyHjouQUuGiq7BsYwYrwaF06tgB8hV8omLNfMEmDPJaZUzMuHw6tBDwGkzD-tS_
ub9hxrpJ4UsOWnt5rGUyoN2N_c1-TQlXxm5oto14MxnoAyBQBpwIEgSH3Y4ZhwKBhH
PjSo0cdwuNdYbGPpb-YUvF-2NZzODiQ1OvWQBRHSbPWYz_xbGkgD504LRtqRwCO7CC
_CyyURi1sEssPVsMJRX_U4LFEOc82TiDdqjKOjRUfKK5rqLi8nBE9soQ0DSaOoFQZi
GrBrqxDsNYiAYAmxxkos-i3nX4qtByVx85sCE5U_0MqG7COxZWMOPEFrDaepUV-cOy
rvoUIng8i8ljKBKxETY2BgPegKBYCxsAUcAkKamSCC9AiBxA0UOHyhTqtlvMksO7AE
hNC2-YzPyx1FkhMoS4LLe6E_pFsMlmjA6P1NSge9C5G5tETYXGAn6b1xZbHtmwrPSc
ro9LWhVmAaA7_bxYObnFUxgWtK4vzzQBjZJ36UTk4OTB-JvKWgfVWCFsaw5WCHj6Oo
4jpO7d2yN7WMfAj2hTEabz9wumQ0TMhBduZ-QON3pYObSy7TSC1vVme0NJrwF_cJRe
hKTFmdlXGVldPxZCplr7ZQqRQhF8JP-l4mEQVnCaWGn9ONHlemczGOS-A-wwtnmwjI
B1V_vgJRf4FdpV-4hUk4-QLpu3-1lWFxrtZKcggq3tWTduRo5_QebQbUUT_VSCgsFc
OmyWKoj56lbxthN19hq1XGWbLGfrrR6MWh23vk01zn8FVwi7uFwEnRYSafsnWLa1Z5
TpBj9GvAdl2H9NHwzpB5NqHpZNkQ3NMDj13Fn8fzO0JB83Etbm_tnFQfcb13X3bJ15
Cz-Ww1MGhvIpGGnMBT_ADp9xSIyAM9dQ1yeVXk-AIgWBUlN5uyWSGyCxp0cJwx7HxM
38z0UIeBu-MytL-eqndM7LxytsVzCbjOTSVRmhYEMIzUAnS1gs7uMQAGRdgRIElTJE
SGMjb_4bZq9s6Ve1LKkSi0_QDsrABaLe55UY0zF4ZSfOV5PMyPtocwV_dcNPlxLgNA
D1BFX_Z9kAdMZQW6fAmsfFle0zAoMe4l9pMESH0JB4sJGdCKtQXj1cXNydDYozF7l8
H00BV_Er7zd6VtIw0MxwkFCTatsv_R-GsBCH218RgVPsfYhwVuT8R4HarpzsDBufC4
r8_c8fc9Z278sQ081jFjOja6L2x0N_ImzFNXU6xwO-Ska-QeuvYZ3X_L31ZOX4Llp-
7QSfgDoHnOxFv1Xws-D5mDHD3zxOup2b2TppdKTZb9eW2vxUVviM8OI9atBfPKMGAO
v9omA-6vv5IxUH0-lWMiHLQ_g8vnswp-Jav0c4t6URVUzujNOoNd_CBGGVnHiJTCHl
88LQxsqLHHIu4Fz-U2SGnlxGTj0-ihit2ELGRv4vO8E1BosTmf0cx3qgG0Pq0eOLBD
IHsrdZ_CCAiTc0HVkMbyq1M6qEhM-q5P6y1QCIrwg

Encoding this JWE Authentication Tag as BASE64URL(JWE Authentication Tag) gives this value:

ffmPv_AEzIQ-8XGyW1j-Ew

C.8. Complete Representation

Assemble the final representation: The Compact Serialization of this result is the string BASE64URL(UTF8(JWE Protected Header)) || '.' || BASE64URL(JWE Encrypted Key) || '.' || BASE64URL(JWE Initialization Vector) || '.' || BASE64URL(JWE Ciphertext) || '.' || BASE64URL(JWE Authentication Tag).

The final result in this example is:


```
eyJhbGciOiJQQkVTMi1IUzI1NitBMTI4S1ciLCJwMnMiOiIyV0NUY0paMVJ2ZF9DSn
VKcmlwUTF3IiwicDJjIjo0MDk2LCJlbmMiOiJBMTI4Q0JDLUhTMjU2IiwiY3R5Ijoi
andrK2pzb24ifQ.
yeyPcAzqyNMh8f9BcD-skmlregAeFSwVDj3IOR795FPaUopQef7BeQ.
Ye9j1qs22DmRSAddIh-VnA.
AwhB8lxrlKjFn02LGWEqg27H4Tg9fyZAbFv3p5ZicHpj64QyHC44qqlZ3JEmnZTgQo
wIqZJ13jbyHB8LgePiqUJ1hf6M2HPLgzw8L-mEeQ0jvDUTrE07NtOerBk8bwBQyZ6g
0kQ3DEOIglfYxV8-FJvNBYwbqN1Bck6d_i7OtjSHV-8DIrp-3JcRIe05YKy3Oi34Z_
GOiAc1EK21B11c_AE11PII_wvvtRiUiG8YofQXakWd1_O98Kap-UgmyWPfreUJ3lJP
nbD4Ve95owEfMGLOPflo2MnjaTDCwQokoJ_xplQ2vNPz8iguLcHBoKllyQFJL2mOWB
wqhBo9Oj-O800as5mmLsvQMTflIrIEbbTMzHMBZ8EFW9fWwwFu0DWQJGkMNhmBZQ-3
lvqTc-M6-gWA6D8PDhONfP2Oib2HGizwG1iEaX8GRyUpfLuljCLIe1DkGOewhKuKkZ
h04DKNM5Nbugf2atmU9OP0Ldx5peCUtRG1gMVl7Qup5ZXHTjgPDr5b2N731UooCGAU
qHdgGhg0JVJ_ObCTdjsH4CF1SJsdUhrXvYx3HJh2Xd7CwJRzU_3Y1GxYU6-s3GFPbi
rfqqEipJDBTHpcoCmyrwYjYHFgnlqBZRotRrS95g8F95bRXqsaDY7UgQGwBQBwy665
d0zpvTasvfXf_c0MWAl-neFaKOW_Px6g4EUDjG1GWSXV9cLStLw_0ovdApDIFLHYHe
PyagyHjouQUuGiq7BsYwYrwaF06tgB8hV8omLNfMEmDPJaZUzMuHw6tBDwGkzD-tS_
ub9hxrpJ4UsOWnt5rGUyoN2N_c1-TQlXxm5oto14MxnoAyBQBpwIEgSH3Y4ZhwKBhH
PjSo0cdwuNdYbGPpb-YUvF-2NZzODiQ1OvWQBRHSbPWYz_xbGkgD504LRtqRwCO7CC
_CyyURi1sEssPVsMJRX_U4LFEOc82TiDdqjKOjRUfKK5rqLi8nBE9soQ0DSaOoFQZi
GrBrqxDsNYiAYAmxxkos-i3nX4qtByVx85sCE5U_0MqG7COxZWMOPEFrDaepUV-cOy
rvoUIng8i8ljKBKxETY2BgPegKBYCxsAUcAkKamSCC9AiBxA0UOHyhTqtlvMksO7AE
hNC2-YzPyx1FkhMoS4LLe6E_pFsMlmjA6P1NSge9C5G5tETYXGAn6b1xZbHtmwrPSc
ro9LWhVmAaA7_bxYObnFUxgWtK4vzzQBjZJ36UTk4OTB-JvKWgfVWCFsaw5WCHj6Oo
4jpO7d2yN7WMfAj2hTEabz9wumQ0TMhBduZ-QON3pYObSy7TSC1vVme0NJrwF_cJRe
hKTFmdlXGVldPxZCplr7ZQqRQhF8JP-l4mEQVnCaWGn9ONHlemczGOS-A-wwtnmwjI
B1V_vgJRf4FdpV-4hUk4-QLpu3-1lWFxrtZKcggq3tWTduRo5_QebQbUUT_VSCgsFc
OmyWKoj56lbxthN19hq1XGWbLGfrrR6MWh23vk01zn8FVwi7uFwEnRYSafsnWLa1Z5
TpBj9GvAdl2H9NHwzpB5NqHpZNkQ3NMDj13Fn8fzO0JB83Etbm_tnFQfcb13X3bJ15
Cz-Ww1MGhvIpGGnMBT_ADp9xSIyAM9dQ1yeVXk-AIgWBUlN5uyWSGyCxp0cJwx7HxM
38z0UIeBu-MytL-eqndM7LxytsVzCbjOTSVRmhYEMIzUAnS1gs7uMQAGRdgRIElTJE
SGMjb_4bZq9s6Ve1LKkSi0_QDsrABaLe55UY0zF4ZSfOV5PMyPtocwV_dcNPlxLgNA
D1BFX_Z9kAdMZQW6fAmsfFle0zAoMe4l9pMESH0JB4sJGdCKtQXj1cXNydDYozF7l8
H00BV_Er7zd6VtIw0MxwkFCTatsv_R-GsBCH218RgVPsfYhwVuT8R4HarpzsDBufC4
r8_c8fc9Z278sQ081jFjOja6L2x0N_ImzFNXU6xwO-Ska-QeuvYZ3X_L31ZOX4Llp-
7QSfgDoHnOxFv1Xws-D5mDHD3zxOup2b2TppdKTZb9eW2vxUVviM8OI9atBfPKMGAO
v9omA-6vv5IxUH0-lWMiHLQ_g8vnswp-Jav0c4t6URVUzujNOoNd_CBGGVnHiJTCHl
88LQxsqLHHIu4Fz-U2SGnlxGTj0-ihit2ELGRv4vO8E1BosTmf0cx3qgG0Pq0eOLBD
IHsrdZ_CCAiTc0HVkMbyq1M6qEhM-q5P6y1QCIrwg.
ffmPv_AEzIQ-8XGyW1j-Ew
```


Appendix D. Acknowledgements

A JSON representation for RSA public keys was previously introduced by John Panzer, Ben Laurie, and Dirk Balfanz in Magic Signatures

[MagicSignatures].

This specification is the work of the JOSE Working Group, which includes dozens of active and dedicated participants. In particular, the following individuals contributed ideas, feedback, and wording that influenced this specification:

Dirk Balfanz, Richard Barnes, John Bradley, Brian Campbell, Breno de Medeiros, Joe Hildebrand, Edmund Jay, Ben Laurie, James Manger, Matt Miller, Tony Nadalin, Axel Nennker, John Panzer, Eric Rescorla, Nat Sakimura, Jim Schaad, Paul Tarjan, Hannes Tschofenig, and Sean Turner.

Jim Schaad and Karen O'Donoghue chaired the JOSE working group and Sean Turner and Stephen Farrell served as Security area directors during the creation of this specification.

Appendix E. Document History

[[to be removed by the RFC Editor before publication as an RFC]]

-17

- Refined the "typ" and "cty" definitions to always be MIME Media Types, with the omission of "application/" prefixes recommended for brevity, addressing issue #50.

- Added an example encrypting an RSA private key with "PBES2-HS256+A128KW" and "A128CBC-HS256". Thanks to Matt Miller for producing this!

- Processing rules occurring in both JWS and JWK are now referenced in JWS by JWK, rather than duplicated, addressing issue #57.

- Terms used in multiple documents are now defined in one place and incorporated by reference. Some lightly used or obvious terms were also removed. This addresses issue #58.

-16

- Changes to address editorial and minor issues #41, #42, #43, #47, #51, #67, #71, #76, #80, #83, #84, #85, #86, #87, and #88.

-15

- Changes to address editorial issues #48, #64, #65, #66, and #91.

-14

- o Relaxed language introducing key parameters since some parameters are applicable to multiple, but not all, key types.

-13

- o Applied spelling and grammar corrections.

-12

- o Stated that recipients MUST either reject JWKs and JWK Sets with duplicate member names or use a JSON parser that returns only the lexically last duplicate member name.

-11

- o Stated that when "kid" values are used within a JWK Set, different keys within the JWK Set SHOULD use distinct "kid" values.
- o Added optional "x5u" (X.509 URL), "x5t" (X.509 Certificate Thumbprint), and "x5c" (X.509 Certificate Chain) JWK parameters.
- o Added section on Encrypted JWK and Encrypted JWK Set Formats.
- o Added a Parameter Information Class value to the JSON Web Key Parameters registry, which registers whether the parameter conveys public or private information.
- o Registered "application/jwk+json" and "application/jwk-set+json" MIME types and "JWK" and "JWK-SET" typ header parameter values, addressing issue #21.

-10

- o No changes were made, other than to the version number and date.

-09

- o Expanded the scope of the JWK specification to include private and symmetric key representations, as specified by draft-jones-jose-json-private-and-symmetric-key-00.
- o Defined that members that are not understood must be ignored.

-08

- o Changed the name of the JWK key type parameter from "alg" to "kty" to enable use of "alg" to indicate the particular algorithm that the key is intended to be used with.

- o Clarified statements of the form "This member is OPTIONAL" to "Use of this member is OPTIONAL".

- o Referenced String Comparison Rules in JWS.

- o Added seriesInfo information to Internet Draft references.

-07

- o Changed the name of the JWK RSA modulus parameter from "mod" to "n" and the name of the JWK RSA exponent parameter from "xpo" to "e", so that the identifiers are the same as those used in RFC 3447.

-06

- o Changed the name of the JWK RSA exponent parameter from "exp" to "xpo" so as to allow the potential use of the name "exp" for a future extension that might define an expiration parameter for keys. (The "exp" name is already used for this purpose in the JWT specification.)

- o Clarify that the "alg" (algorithm family) member is REQUIRED.

- o Correct an instance of "JWK" that should have been "JWK Set".

- o Applied changes made by the RFC Editor to RFC 6749's registry language to this specification.

-05

- o Indented artwork elements to better distinguish them from the body text.

-04

- o Refer to the registries as the primary sources of defined values and then secondarily reference the sections defining the initial contents of the registries.

- o Normatively reference XML DSIG 2.0 [W3C.CR-xmldsig-core2-20120124] for its security considerations.

- o Added this language to Registration Templates: "This name is case sensitive. Names that match other registered names in a case insensitive manner SHOULD NOT be accepted."

- o Described additional open issues.

- o Applied editorial suggestions.

-03

- o Clarified that "kid" values need not be unique within a JWK Set.

- o Moved JSON Web Key Parameters registry to the JWK specification.

- o Added "Collision Resistant Namespace" to the terminology section.

- o Changed registration requirements from RFC Required to Specification Required with Expert Review.

- o Added Registration Template sections for defined registries.

- o Added Registry Contents sections to populate registry values.

- o Numerous editorial improvements.

-02

- o Simplified JWK terminology to get replace the "JWK Key Object" and "JWK Container Object" terms with simply "JSON Web Key (JWK)" and "JSON Web Key Set (JWK Set)" and to eliminate potential confusion between single keys and sets of keys. As part of this change, the top-level member name for a set of keys was changed from "jwk" to "keys".

- o Clarified that values with duplicate member names MUST be rejected.

- o Established JSON Web Key Set Parameters registry.

- o Explicitly listed non-goals in the introduction.

- o Moved algorithm-specific definitions from JWK to JWA.

- o Reformatted to give each member definition its own section heading.

-01

- o Corrected the Magic Signatures reference.

-00

- o Created the initial IETF draft based upon draft-jones-json-web-key-03 with no normative changes.

Author's Address

Michael B. Jones
Microsoft

Email: mbj@microsoft.com
URI: http://self-issued.info/