

**A PRF for the Kerberos V GSS-API Mechanism
draft-ietf-kitten-krb5-gssapi-prf-03.txt**

Status of this Memo

By submitting this Internet-Draft, each author represents that any applicable patent or other IPR claims of which he or she is aware have been or will be disclosed, and any of which he or she becomes aware will be disclosed, in accordance with [Section 6 of BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/1id-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on November 13, 2005.

Copyright Notice

Copyright (C) The Internet Society (2005).

Abstract

This document defines the Pseudo-Random Function (PRF) for the Kerberos V mechanism for the Generic Security Service Application Programming Interface (GSS-API), based on the PRF defined for the Kerberos V cryptographic framework, for keying application protocols given an established Kerberos V GSS-API security context.

Table of Contents

1.	Introduction	3
1.1	Conventions used in this document	3
2.	Kerberos V GSS Mechanism PRF	3
3.	IANA Considerations	4
4.	Security Considerations	4
5.	Normative References	5
	Author's Address	5
	Intellectual Property and Copyright Statements	6

1. Introduction

This document specifies the Kerberos V GSS-API mechanism's pseudo-random function corresponding to [[GSS-PRF](#)]. The function is a "PRF+" style construction.

1.1 Conventions used in this document

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

2. Kerberos V GSS Mechanism PRF

The GSS-API PRF [[GSS-PRF](#)] function for the Kerberos V mechanism [[RFC1964](#)] shall be the output of a PRF+ function based on the encryption type's PRF function keyed with the negotiated session key of the security context corresponding to the 'prf_key' input parameter of GSS_Pseudo_random().

This PRF+ MUST be keyed with the key indicated by the 'prf_key' input parameter as follows:

- o GSS_C_PRF_KEY_FULL -- use the sub-session key asserted by the acceptor, if any, or the sub-session asserted by the initiator, if any, or the Ticket's session key
- o GSS_C_PRF_KEY_PARTIAL -- use the sub-session key asserted by the initiator, if any, or the Ticket's session key

The PRF+ function is a simple counter-based extension of the Kerberos V pseudo-random function [[RFC3961](#)] for the encryption type of the security context's keys:

$$\text{PRF+}(K, L, S) = \text{truncate}(L, T1 || T2 || \dots || Tn)$$
$$Tn = \text{pseudo-random}(K, n || S)$$

where '||' is the concatenation operator, 'n' is encoded as a network byte order 32-bit unsigned binary number, $\text{truncate}(L, S)$ truncates the input octet string S to length L, and $\text{pseudo-random}()$ is the Kerberos V pseudo-random function [[RFC3961](#)].

The maximum output size of the Kerberos V mechanism's GSS-API PRF then is, necessarily, 2^{32} times the output size of the $\text{pseudo-random}()$ function for the encryption type of the given key.

When the input size is longer than 2^{14} octets as per [[GSS-PRF](#)] and

Williams

Expires November 13, 2005

[Page 3]

exceeds an implementation's resources then the mechanism MUST return GSS_S_FAILURE and GSS_KRB5_S_KG_INPUT_TOO_LONG as the minor status code.

3. IANA Considerations

This document has no IANA considerations currently. If and when a relevant IANA registry of GSS-API symbols and constants is created then the GSS_KRB5_S_KG_INPUT_TOO_LONG minor status code should be added to such a registry.

4. Security Considerations

Kerberos V encryption types' PRF functions use a key derived from contexts' session keys and should preserve the forward security properties of the mechanisms' key exchanges.

Legacy Kerberos V encryption types may be weak, particularly the single-DES encryption types.

See also [[GSS-PRF](#)] for generic security considerations of GSS_Pseudo_random().

See also [[RFC3961](#)] for generic security considerations of the Kerberos V cryptographic framework.

Care should be taken not to exceed the useful lifetime of an established security context's session key's useful lifetime as implementations are not required to prevent overuse of the GSS_Pseudo_random() function. This can effectively be achieved by limiting the number of GSS_Pseudo_random() calls to, say, a handful of calls per-security context.

Use of Ticket session keys, rather than sub-session keys, when initiators and acceptors fail to assert sub-session keys, is dangerous as ticket reuse can lead to key reuse, therefore initiators should assert sub-session keys always, and acceptors should assert sub-session keys at least when initiators fail to do so..

The computational cost of computing this PRF+ may vary depending on the Kerberos V encryption types being used, but generally the computation of this PRF+ gets more expensive as the input and output octet string lengths grow (note that the use of a counter in the PRF+ construction allows for parallelization). This means that if an application can be tricked into providing very large input octet strings and requesting very long output octet strings then that may constitute a denial of service attack on the application; therefore applications SHOULD place appropriate limits on the size of any input

Williams

Expires November 13, 2005

[Page 4]

octet strings received from their peers without integrity protection.

5. Normative References

- [CFX] Zhu, L., Jaganathan, K., and S. Hartman, "The Kerberos Version 5 GSS-API Mechanism: Version 2".
- [GSS-PRF] Williams, N., "A PRF API extension for the GSS-API".
- [RFC1964] Linn, J., "The Kerberos Version 5 GSS-API Mechanism", [RFC 1964](#), June 1996.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC2743] Linn, J., "Generic Security Service Application Program Interface Version 2, Update 1", [RFC 2743](#), January 2000.
- [RFC2744] Wray, J., "Generic Security Service API Version 2 : C-bindings", [RFC 2744](#), January 2000.
- [RFC3961] Raeburn, K., "Encryption and Checksum Specifications for Kerberos 5", [RFC 3961](#), February 2005.

Author's Address

Nicolas Williams
Sun Microsystems
5300 Riata Trace Ct
Austin, TX 78727
US

Email: Nicolas.Williams@sun.com

Intellectual Property Statement

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in [BCP 78](#) and [BCP 79](#).

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at ietf-ipr@ietf.org.

Disclaimer of Validity

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Copyright Statement

Copyright (C) The Internet Society (2005). This document is subject to the rights, licenses and restrictions contained in [BCP 78](#), and except as set forth therein, the authors retain all their rights.

Acknowledgment

Funding for the RFC Editor function is currently provided by the Internet Society.

Williams

Expires November 13, 2005

[Page 6]