

**An information model for Kerberos version 5
draft-ietf-krb-wg-kdc-model-14**

Abstract

This document describes an information model for Kerberos version 5 from the point of view of an administrative service. There is no standard for administrating a kerberos 5 KDC. This document describes the services exposed by an administrative interface to a KDC.

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on February 1, 2013.

Copyright Notice

Copyright (c) 2012 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

This document may contain material from IETF Documents or IETF Contributions published or made publicly available before November 10, 2008. The person(s) controlling the copyright in some of this material may not have granted the IETF Trust the right to allow modifications of such material outside the IETF Standards Process. Without obtaining an adequate license from the person(s) controlling the copyright in such materials, this document may not be modified outside the IETF Standards Process, and derivative works of it may not be created outside the IETF Standards Process, except to format it for publication as an RFC or to translate it into languages other than English.

Table of Contents

1.	Introduction	3
2.	Requirements notation	4
3.	Information model demarcation	5
4.	Information model specification	6
4.1.	Principal	6
4.1.1.	Principal: Attributes	6
4.1.2.	Principal: Associations	7
4.2.	KeySet	8
4.2.1.	KeySet: Attributes	8
4.2.2.	KeySet: Associations	8
4.3.	Key	8
4.3.1.	Key: Attributes	9
4.3.2.	Key: Associations	9
4.3.3.	Key: Remarks	10
4.4.	Policy	10
4.4.1.	Policy: Attributes	10
4.4.2.	Mandatory-to-implement Policy	11
5.	Implementation Scenarios	12
5.1.	LDAP backend to KDC	12
5.2.	LDAP frontend to KDC	12
5.3.	SOAP	12
5.4.	Netconf	12
6.	Security Considerations	13
7.	IANA Considerations	14
8.	Acknowledgments	15
9.	References	16
9.1.	Normative References	16
9.2.	Informative References	16
	Author's Address	17

1. Introduction

The Kerberos version 5 authentication service described in [[RFC4120](#)] describes how a Key Distribution Center (KDC) provides authentication to clients. The standard does not stipulate how a KDC is managed and several "kadmin" servers have evolved. This document describes the services required to administer a KDC and the underlying information model assumed by a kadmin-type service.

The information model is written in terms of "attributes" and "services" or "interfaces" but the use of these particular words must not be taken to imply any particular modeling paradigm. Neither an object oriented model nor an LDAP [[RFC4510](#)] schema is intended. The author has attempted to describe in natural language the intended semantics and syntax of the components of the model. An LDAP schema (for instance) based on this model will be more precise in the expression of the syntax while preserving the semantics of this model.

Implementations of this document MAY decide to change the names used (e.g. principalName). If so an implementation MUST provide a name to name mapping to this document. In particular schema languages may have different conventions for caseing, eg camelCase vs use of '_' and '-' to separate 'words' in a name. Implementations MUST call out such conventions explicitly.

Implementations of this document MUST be able to support default values for attributes as well as the ability to specify syntax for attribute values.

2. Requirements notation

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

This document describes an information model for kerberos 5 but does not directly describe any mapping onto a particular schema- or modelling language. Hence an implementation of this model consists of a mapping to such a language - e.g. an LDAP or SQL schema. The precise interpretation of terms from [[RFC2119](#)] therefore require some extra explanation.

The terms MUST or REQUIRED means that schema implementing this model must have a way to represent the feature (i.e that it is mandatory to implement) but that unless otherwise specified the feature may represent an optional element in the chosen schema definition language.

However MUST also means that a KDC or administrative interface implementing this information model MUST provide the feature and associated behavior consistent with schema.

For instance, `principalLastFailedAuthentication` (cf below) represents the last time an authentication failed for a principal. In an LDAP schema (for instance) this may be represented as an optional attribute even though all KDCs implementing this specification must support this attribute.

The terms MAY or OPTIONAL means that the feature is optional to implement by a KDC or administrative interface implementing this information model. MAY also means that the feature is optional to implement in schema.

Implementors of schema should be aware that unless there is a way to represent critical but optional elements in the schema definition language confusion may arise when optional elements are used but not understood by all implementations in a particular deployment.

3. Information model demarcation

The information model specified in the next chapter describes objects, properties of those objects and relations between those objects. These elements comprise an abstract view of the data represented in a KDC. It is important to understand that the information model is not a schema. In particular the way objects are compared for equality beyond that which is implied by the specification of a syntax is not part of this specification. Nor is ordering specified between elements of a particular syntax.

Further work on Kerberos will undoubtedly prompt updates to this information model to reflect changes in the functions performed by the KDC. Such extensions to the information model should always use a normative reference to the relevant RFCs detailing the change in KDC function.

This model describes a number of elements related to password policy management. Not all of the elements in this model are unique to Kerberos; an LDAP implementation of this model should incorporate existing LDAP schema where functional overlap exists, rather than defining additional Kerberos-specific elements.

4. Information model specification

4.1. Principal

The fundamental entity stored in a KDC is the principal. The Principal is associated to keys and generalizes the "user" concept. The Principal MUST be implemented in full and MUST NOT be OPTIONAL in an implementation

4.1.1. Principal: Attributes

4.1.1.1. principalName

The principalName MUST uniquely identify the Principal within the administrative context of the KDC. The principalName MUST be equivalent to the string representation of the Principal name ([section 2.1.1 of \[RFC1964\]](#)) including, if applicable for the name type, the realm.

The attribute MAY be multi-valued if the implementation supports aliases and/or enterprise names. In that case exactly one of the principalName values MAY be designated the canonical principalName and if the implementation supports entypes which require salt then exactly one of the values of principalName MAY be designated as the canonical salting principalName.

Implementations (i.e. schema) that support enterprise names and/or aliases SHOULD provide for efficient lookup of Principal objects based on alias/enterprise name.

4.1.1.2. principalNotUsedBefore

The Principal MUST NOT be used before this date. The syntax of the attribute MUST be Internet Date/Time Format from [\[RFC3339\]](#). The attribute MUST be single-valued.

4.1.1.3. principalNotUsedAfter

The Principal MUST NOT be used after this date. The syntax of the attribute MUST be Internet Date/Time Format from [\[RFC3339\]](#). The attribute MUST be single-valued.

4.1.1.4. principalIsDisabled

A boolean attribute used to disable a Principal. The attribute SHOULD default to boolean FALSE.

4.1.1.5. principalLastCredentialChangeTime

This single-valued attribute contains the time of the last successful change of credential (e.g. password or private key) associated with this Principal. The syntax of the attribute MUST be Internet Date/Time Format from [\[RFC3339\]](#).

4.1.1.6. principalCreateTime

This single-valued attribute contains the time and date when this Principal was created. The syntax of the attribute MUST be Internet Date/Time Format from [\[RFC3339\]](#).

4.1.1.7. principalModifyTime

This single-valued attribute contains the time and date when this Principal was last modified excluding credentials change. The syntax of the attribute MUST be Internet Date/Time Format from [\[RFC3339\]](#).

4.1.1.8. principalMaximumTicketLifetime

This single-valued attribute contains the time in seconds representing the maximum lifetime for tickets issued for this Principal.

4.1.1.9. principalMaximumRenewableTicketLifetime

This single-valued attribute contains the delta time in seconds representing the maximum amount of time a ticket may be renewed for this Principal.

4.1.1.10. principalAllowedEncatype

This OPTIONAL multi-valued attribute lists the encatypes allowed for this principal. If empty or absent any encatype supported by the implementation is allowed for this Principal.

This attribute is intended as a policy attribute and restricts all uses of encatypes including server, client, and session keys. Data models MAY choose to use policy objects in order to represent more complex decision mechanisms.

4.1.2. Principal: Associations

Each Principal MAY be associated with 0 or more KeySet and MAY be associated with 0 or more Policies. The KeySet is represented as an object in this model since it has attributes associated with it (the key version number). In typical situations the Principal is

associated with exactly 1 KeySet but implementations MUST NOT assume this case, i.e. an implementation of this standard MUST be able to handle the general case of multiple KeySet associated with each principal. Multiple KeySets may for instance be useful when performing a key rollover for a principal.

4.2. KeySet

In Kerberos principals are associated with zero or more symmetric secret keys, and each key has a key version number (kvno) and enctype. In this model we group keys by kvno into KeySet objects. A Principal can have zero or more KeySet objects associated with it, each of which MUST have one or more keys. Each KeySet is associated with exactly one principal. Schemas derived from this model MAY lack a direct analogue of KeySet as described in this document.

It is expected that most Kerberos implementations will use a special-purpose interface for setting and changing Principal passwords and keys.

If a server supports an enctype for a Principal that enctype must be present in at least one key for the Principal in question. For any given enctype a KeySet MUST NOT contain more than one Key with that enctype.

The security of Kerberos 5 depends absolutely on the confidentiality and integrity of the Key objects stored in the KDC. Implementations of this standard MUST facilitate, to the extent possible, an administrator's ability to place more restrictive access controls on KeySets than on other Principal data, and to arrange for more secure backup for KeySets.

4.2.1. KeySet: Attributes

4.2.1.1. kvno

Also known as the key version number. This is a single-valued attribute containing a non-negative integer. This number is incremented by one each time a key in the KeySet is changed.

4.2.2. KeySet: Associations

To each KeySet MUST be associated a set of 1 or more Keys.

4.3. Key

Implementations of this model MUST NOT REQUIRE keys to be represented.

4.3.1. Key: Attributes

4.3.1.1. keyEncryptionType

The enctype SHOULD be represented as an enumeration of the encetypes supported by the KDC using the string name ("encryption type") of the enctype from the IANA registry of Kerberos Encryption Type Numbers. One example is 'aes128-cts-hmac-sha1-96'.

4.3.1.2. keyValue

The binary representation of the key data. This MUST be a single-valued octet string.

4.3.1.3. keySaltValue

The binary representation of the key salt. This MUST be a single-valued octet string.

4.3.1.4. keyStringToKeyParameter

This MUST be a single-valued octet string representing an opaque parameter associated with the enctype. This parameter is specified in the "string-to-key" method in [section 3 of \[RFC3961\]](#).

4.3.1.5. keyNotUsedBefore

This key MUST NOT be used before this date. The syntax of the attribute MUST be semantically equivalent with the standard ISO date format. This MUST be a single-valued attribute.

4.3.1.6. keyNotUsedAfter

This key MUST NOT be used after this date. The syntax of the attribute MUST be semantically equivalent with the standard ISO date format. This MUST be a single-valued attribute.

4.3.1.7. keyIsDisabled

This is a boolean attribute which SHOULD be set to false by default. If this attribute is true the key MUST NOT be used. This is used to temporarily disable a key.

4.3.2. Key: Associations

None

4.3.3. Key: Remarks

The security of the keys is an absolute requirement for the operation of Kerberos 5. If keys are implemented adequate protection from unauthorized modification and disclosure MUST be available and REQUIRED by the implementation.

4.4. Policy

Implementations SHOULD implement policy but MAY allow them to be OPTIONAL. The Policy should be thought of as a 'typed hole'. i.e. an opaque binary value paired with an identifier of type of data contained in the binary value. Both attributes (type and value) must be present.

4.4.1. Policy: Attributes

4.4.1.1. policyIdentifier

The policyIdentifier MUST be globally unique. Possible types of identifiers include:

An Object Identifier (OID) [[RFC4517](#)]

A URI [[RFC3986](#)]

A UUID [[RFC4122](#)]

Implementations of this specification are expected to assign globally unique identifiers to the list of standard policy below in accordance with best-practice for identifier-management for the schema-language used.

4.4.1.2. policyIsCritical

This boolean attribute indicates that the KDC MUST be able to correctly interpret and apply this policy for the Principal to be used.

4.4.1.3. policyContent

This is an optional single opaque binary value used to store a representation of the policy. In general a policy cannot be fully expressed using attribute-value pairs. The policyContent is OPTIONAL in the sense that an implementation MAY use it to store an opaque value for those policy-types which are not directly representable in that implementation.

4.4.1.4. policyUse

This is an optional single enumerated string value used to describe the use of the policy. Implementations SHOULD provide this attribute and MUST (if the attribute is implemented) describe the enumerated set of possible values. The intent is that this attribute be useful in providing an initial context-based filtering.

4.4.2. Mandatory-to-implement Policy

All implementations that represent Policy objects MUST be able to represent the policies listed in this section. Implementations are not required to use the same underlying data-representation for the policyContent binary value but SHOULD use the same OIDs as the policyIdentifier. In general the expression of policy may require a Turing-complete language. This specification does not attempt to model policy expression language.

4.4.2.1. Password Quality Policy

Password quality policy controls the requirements placed by the KDC on new passwords.

4.4.2.2. Password Management Policy

Password management policy controls how passwords are changed.

4.4.2.3. Keying Policy

A keying policy specifies the association of encetypes with new principals, e.g. when a Principal is created one of the applicable keying policies is used to determine the set of keys to associate with the principal.

4.4.2.4. Ticket Flag Policy

A ticket flag policy specifies the ticket flags allowed for tickets issued for a principal.

5. Implementation Scenarios

There are several ways to implement an administrative service for Kerberos 5 based on this information model. In this section we list a few of them.

5.1. LDAP backend to KDC

Given an LDAP schema implementation of this information model it would be possible to build an administrative service by back-ending the KDC to a directory server where principals and keys are stored. Using the security mechanisms available on the directory server keys are protected from access by anyone apart from the KDC. Administration of the principals, policy, and other non-key data is done through the directory server while the keys are modified using the set/change password protocol [[I-D.ietf-krb-wg-kerberos-set-passwd](#)].

5.2. LDAP frontend to KDC

An alternative way to provide a directory interface to the KDC is to implement an LDAP-frontend to the KDC which exposes all non-key objects as entries and attributes. As in the example above all keys are modified using the set/change password protocol [[I-D.ietf-krb-wg-kerberos-set-passwd](#)]. In this scenario the implementation would typically not use a traditional LDAP implementation but treat LDAP as an access protocol to data in the native KDC database.

5.3. SOAP

Given an XML schema implementation of this information model it would be possible to build a SOAP interface to the KDC. This demonstrates the value of creating an abstract information model which is mappable to multiple schema representations.

5.4. Netconf

Given a YAML implementation of this information model it would be possible to create a Netconf-based interface to the KDC, enabling management of the KDC from standard network management applications.

6. Security Considerations

This document describes an abstract information model for Kerberos 5. The Kerberos 5 protocol depends on the security of the keys stored in the KDC. The model described here assumes that keys MUST NOT be transported in the clear over the network and furthermore that keys are treated as write-only attributes that SHALL only be modified (using the administrative interface) by the change-password protocol [[I-D.ietf-krb-wg-kerberos-set-passwd](#)].

Exposing the object model of a KDC typically implies that objects can be modified and/or deleted. In a KDC not all principals are created equal, so that for instance deleting `krbtgt/EXAMPLE.COM@EXAMPLE.COM` effectively disables the `EXAMPLE.COM` realm. Hence access control is paramount to the security of any implementation. This document does not mandate access control. This only implies that access control is beyond the scope of the standard information model, i.e. that access control may not be accessible via any protocol based on this model. If access control objects are exposed via an extension to this model the presence of access control may in itself provide points of attack by giving away information about principals with elevated rights etc.

7. IANA Considerations

This document has no IANA actions.

8. Acknowledgments

The author wishes to extend his thanks to Love Hoernquist-Aestrand and Sam Hartman for their important contributions to this document.

9. References

9.1. Normative References

- [RFC1964] Linn, J., "The Kerberos Version 5 GSS-API Mechanism", [RFC 1964](#), June 1996.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC3339] Klyne, G., Ed. and C. Newman, "Date and Time on the Internet: Timestamps", [RFC 3339](#), July 2002.
- [RFC3961] Raeburn, K., "Encryption and Checksum Specifications for Kerberos 5", [RFC 3961](#), February 2005.
- [RFC3986] Berners-Lee, T., Fielding, R., and L. Masinter, "Uniform Resource Identifier (URI): Generic Syntax", STD 66, [RFC 3986](#), January 2005.
- [RFC4120] Neuman, C., Yu, T., Hartman, S., and K. Raeburn, "The Kerberos Network Authentication Service (V5)", [RFC 4120](#), July 2005.
- [RFC4122] Leach, P., Mealling, M., and R. Salz, "A Universally Unique IDentifier (UUID) URN Namespace", [RFC 4122](#), July 2005.
- [RFC4517] Legg, S., "Lightweight Directory Access Protocol (LDAP): Syntaxes and Matching Rules", [RFC 4517](#), June 2006.

9.2. Informative References

- [I-D.ietf-krb-wg-kerberos-set-passwd]
Williams, N., "Kerberos Set/Change Key/Password Protocol Version 2", [draft-ietf-krb-wg-kerberos-set-passwd-08](#) (work in progress), November 2008.
- [RFC4510] Zeilenga, K., "Lightweight Directory Access Protocol (LDAP): Technical Specification Road Map", [RFC 4510](#), June 2006.

Author's Address

Leif Johansson
Swedish University Network
Thulegatan 11
Stockholm

Email: leifj@sunset.se

URI: <http://www.sunet.se>