

Kerberos Working Group
INTERNET-DRAFT
Expires: August 22, 2005

Nicolas Williams
Sun Microsystems
October 2005

Kerberos Set/Change Password: Version 2
<[draft-ietf-krb-wg-kerberos-set-passwd-04.txt](#)>

Status of this Memo

By submitting this Internet-Draft, each author represents that any applicable patent or other IPR claims of which he or she is aware have been or will be disclosed, and any of which he or she becomes aware will be disclosed, in accordance with [Section 6 of BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/lid-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on April 17, 2006.

Copyright Notice

Copyright (C) The Internet Society (2005).

Abstract

This document specifies an extensible protocol for setting keys and changing the passwords of Kerberos V principals.

Table of Contents

- 1 Introduction
- 2 The Protocol
 - 2.1 Transports
 - 2.2 Protocol Framing

- 2.3 Protocol version negotiation
 - 2.3.1 Protocol Major Version Negotiation
 - 2.3.2 Protocol Minor Version Negotiation
- 2.4 Use of Kerberos V

- 2.5 Use of ASN.1
- 2.6 Internationalization
 - 2.6.1 Normalization Forms for UTF-8 Strings
 - 2.6.2 Language Negotiation
- 2.7 Protocol Extensibility
- 2.8 Protocol Subsets
- 3 Protocol Elements
 - 3.1 PDUs
 - 3.2 Operations
 - 3.2.1 Null
 - 3.2.2 Change Kerberos Password
 - 3.2.3 Set Kerberos Password
 - 3.2.4 Set Kerberos Keys
 - 3.2.5 Generate Kerberos Keys
 - 3.2.6 Get New Keys
 - 3.2.7 Commit New Keys
 - 3.2.8 Get Password Quality Policy
 - 3.2.9 Get Principal Aliases
 - 3.2.10 Get Realm's Supported Kerberos V Version and Features
- 4 ASN.1 Module
- 6 IANA Considerations
- 7 Security Considerations
- 8 Acknowledgements
- 9 References
 - 9.1 Normative References
 - 9.2 Informative References
- 10 Authors' Addresses
- 11 Notes to the RFC Editor

Conventions used in this document

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

1 Introduction

Up to this point Kerberos V has lacked a single, standard protocol for changing passwords and keys. While several vendor-specific protocols exist for changing Kerberos passwords/keys, none are

properly internationalized and all are incomplete in one respect or another and none are sufficiently extensible to cope with new features that may be added to Kerberos V at some future time.

This document defines a protocol that is somewhat backward-compatible with the "kpasswd" protocol defined in [[RFC3244](#)] that uses more or less the same protocol framing.

This new protocol is designed to be extensible and properly internationalized.

[2](#) The Protocol

N. Williams

[Page 2]

DRAFT

Kerberos Set/Change Password v2

Expires April 2006

The structure of the protocol is quite similar to that of typical RPC protocols. Each transaction consists of a data structure specific to an operation which is then wrapped in a data structure which is general to all operations of the protocol. These data structures are defined with the Abstract Syntax Notation 1 (ASN.1) [[X680](#)] and they are encoded using the Distinguished Encoding Rules (DER) [[X690](#)].

All protocol data is wrapped KRB-PRIV messages, or, in some cases, a KRB-ERROR, and framed in a header that is backwards compatible with [[RFC3244](#)].

[2.1](#) Transports

The service supports only connection-oriented transports, specifically TCP, and MUST accept requests on TCP port 464, the same as in [[RFC3244](#)].

[2.2](#) Protocol Framing

Requests and responses are exchanged using the same framing as in [[RFC3244](#)], but with the following differences:

- the protocol number field MUST be set to 0x2 (not 0xff80 or 0x1)
- the 'AP-REQ length' field of the request can be set to 0x0, in which case the 'AP-REQ' field of the request is excluded
- the 'KRB-PRIV' field of the request and reply is mutually exclusive with the 'AP-REQ' field of the request
- the 'AP-REP length' field of the reply can be set to 0x0, in

which case the 'AP-REP' field of the reply is excluded

- all errors MUST be sent in a KRB-PRIV if the client's AP-REQ can be or has been accepted by the server
- any KRB-ERROR messages are framed and sent in the 'AP-REP' field of the reply

The initial message from the client MUST carry an AP-REQ and the response to any request bearing an AP-REQ MUST carry an AP-REP or MUST be a KRB-ERROR.

Subsequent messages exchanged on the same TCP connection MAY involve Kerberos V AP exchanges, but generally the client SHOULD NOT initiate a new AP exchange except when it desires to authenticate as a different principal, when the ticket last used for authentication expires or when the server responds with an error indicating that the client must re-authenticate.

[2.3](#) Protocol Version Negotiation

There are several major versions of this protocol. Version 2 also

N. Williams

[Page 3]

DRAFT

Kerberos Set/Change Password v2

Expires April 2006

introduces a notion of protocol minor versions for use in negotiating protocol extensions. As of this time only one minor version is defined for major version 2: minor version 0, defined herein.

[2.3.1](#) Protocol Major Version Negotiation

Version 2 clients that also support other versions, such as 0xff80, as in [[RFC3244](#)], SHOULD attempt to use version 2 of the protocol first.

Servers which do not support version 2 of this protocol typically include their preferred version number in the reply and/or may include a reply in the e-data of a KRB-ERROR, or in a KRB-PRIV with a status code of KRB5_KPASSWD_MALFORMED.

Note that some [[RFC3244](#)] server implementations close the TCP connection without returning any other response. Note also that there is no integrity protection for the major version number in the protocol framing or for any data in a KRB-ERROR.

As a result change password protocol major version negotiation is subject to downgrade attacks. Therefore major version negotiation is

NOT RECOMMENDED.

Where the server indicates that it does not support version 2, the client MAY, but SHOULD NOT, unless configured to do so, fall back on another major version of this protocol.

Version 2 servers MAY respond to non-v2 requests using whatever response is appropriate for the versions used by the clients, but if a server does not do this or know how to do this then it MUST respond with an error framed as in [section 2.2](#), using an AP-REP and KRB-PRIV if the client's AP-REQ can be accepted, or a KRB-ERROR otherwise and using a ProtocolErrorCode value of unsupported-major-version.

It is expected that implementations of as yet unspecified future major versions of this protocol will be required to support version 2 integrity protected error replies for properly indicating no support for version 2 of the protocol. We also hope that no further major versions of this protocol will be needed.

[2.3.2](#) Protocol Minor Version Negotiation

Version 2 clients are free to use whatever protocol minor version and message extensions are available to them in their initial messages to version 2 servers, provided that the minor versions (other than 0) have been defined through IETF documents.

Version 2 servers MUST answer with the highest protocol minor version number supported by the server and the client.

Version 2 clients MUST use the protocol minor version used in a server's reply for any subsequent messages in the same TCP session.

N. Williams

[Page 4]

DRAFT

Kerberos Set/Change Password v2

Expires April 2006

See [section 2.7](#) for further description of the protocol's extensibility and its relation to protocol minor versions and the negotiation thereof.

[2.4](#) Use of Kerberos V and Key Exchange

This protocol makes use of messages defined in [[RFC1510](#)] and [[clarifications](#)]. Specifically, AP-REQ, AP-REP, KRB-ERROR and KRB-PRIV.

All operations are to be performed by the server on behalf of the client principal.

Clients SHOULD use "kadmin/setpw" as the principal name of the server for all requests except when changing the client principal's own expired password, for which they should use "kadmin/changepw". The "kadmin/changepw" service exists to allow KDCs to limit principals with expired passwords to getting initial tickets to the password changing service only and only for changing expired passwords.

Servers MUST limit clients that used the "kadmin/changepw" service principal name to changing the password of the client principal.

The client MUST request mutual authentication and the client MUST MUST request the use of sequence numbers.

Clients SHOULD use INITIAL tickets for requests whose target principal is the client's principal. Servers SHOULD force the use of INITIAL tickets for such requests and MAY force the use of INITIAL for all others - see [section 3.2](#).

Servers MUST specify a sub-session key.

The encrypted part of KRB-PRIVs MUST be encrypted with the server's sub-session key and key usage 20 (client->server) or 21 (server->client).

After each new AP exchange the client and server MUST destroy the session keys, if any, resulting from the previous AP exchange.

[2.5](#) Use of ASN.1

This protocol's messages are defined in ASN.1, using only features from [\[X680\]](#). All ASN.1 types defined herein are to be encoded in DER [\[X690\]](#). A complete ASN.1 module is given in [section 4](#).

The DER encoding of the ASN.1 PDUs are exchanged wrapped in a KRB-PRIV as described above and/or as e-data in KRB-ERROR messages.

[2.6](#) Internationalization

This protocol's request PDU carries an optional field indicating the

languages spoken by the client user; the client SHOULD send its list of spoken languages to the server (once per-TCP session).

The server SHOULD localize all strings intended for display to users

to a language in common with the languages spoken by the client user.

Strings for Kerberos principal and realm names used in this protocol are be constrained as per [[clarifications](#)].

[2.6.1](#) Normalization Forms for UTF-8 Strings

Because Kerberos V [[clarifications](#)] restricts principal names, realm names and passwords to IA5String, this protocol uses UTF8String with an extensible constraint to IA5String.

Future versions of Kerberos may relax this constraint; if so then a minor version of this protocol should relax this constraint accordingly.

[2.6.2](#) Language Negotiation

The server MUST pick a language from the client's input list or the default language tag (see [[RFC3066](#)]) for text in its responses which is meant for the user to read.

The server SHOULD use a language selection algorithm such that consideration is first given to exact matches between the client's spoken languages and the server's available locales, followed by "fuzzy" matches where only the first sub-tags of the client's language tag list are used for matching against the servers available locales.

Servers MUST cache the optional language tag lists from prior requests for use with subsequent requests that exclude the language tag list. Clients MAY expect such server behaviour and send the language tag lists only once per-TCP session. Clients SHOULD send the server the language tag list at least once.

When the server has a message catalog for one of the client's spoken languages the server SHOULD localize any text strings intended for display to users.

[2.7](#) Protocol Extensibility

The protocol is defined in ASN.1 and uses extensibility markers throughout. As such, the module presented herein can be extended within the framework of [[X680](#)].

Typed holes are not used in this protocol as it is very simple and does not require the ability to deal with abstract data types defined in different layers. For this reason, the only way to extend this protocol is by extending the ASN.1 module within the framework of the IETF; all future extensions to this protocol have to be defined in

IETF documents unless otherwise specified in a future IETF revision of this protocol.

A protocol minor version number is used to negotiate use of extensions. See [section 2.3.2](#) for the minor version negotiation.

Servers SHOULD ignore unknown additions to the ASN.1 types, in initial requests, where the syntax allows them, except for extensions to the "Op-req" type, which MUST result in an error.

Servers MUST respond with an error (ProtocolErrorCode value of unsupported-minor-version) to clients that use operations unknown to the server.

[2.8](#) Protocol Subsets

The structure of the protocol is such that the ASN.1 syntaxes for the various operations supported by the protocol are independent of the each other. Client and server implementations MAY implement subsets of the overall protocol by removing some alternatives to the Op-req, Op-rep and Op-err CHOICES from the ASN.1 module given in [section 4](#).

For example, it should be possible to have a password-change only client that cannot set principal's keys - and vice versa.

[3](#) Protocol Elements

The protocol as defined herein supports the following operations relating to the management of Kerberos principal's passwords or keys:

[NOTE: New since last version of this I-D.]

- get principal's current and preferred string-to-key parameters
- change password (or enctypees and string-to-key parameters)
- set password (administrative)
- set new keys
- generate new keys
- get new, un-committed keys
- commit new keys
- get password policy name and/or description of principal
- list aliases of a principal
- list enctypees and version of Kerberos V supported by realm

The operation for retrieving a list of aliases of a principal is needed where KDCs implement aliasing of principal names and allows clients to properly setup their key databases when principal aliasing is in use.

Operations such as creation or deletion of principals are outside the scope of this document, and should be performed via other means, such as through directories or other Kerberos administration protocols.

The individual operations are described in [section 3.2](#).

[3.1](#) PDUs

The types "Request," "Response" and "Error-Response" are the ASN.1 module's PDUs.

The "Request" and "Response" PDUs are always to be sent wrapped in KRB-PRIV messages, except for the "Error-Response" PDU which MUST be sent as KRB-ERROR e-data (see [section 2.4.1](#)) when AP exchanges fail, otherwise it MUST be sent wrapped in a KRB-PRIV.

The ASN.1 syntax for the PDUs is given in [section 4](#).

Note that the first field of each PDU is the major version of the protocol, defaulted to 2, meaning that it is never included in version 2 exchanges. Similarly, the second field of each PDU is the minor version, defaulted to 0.

The request, responses and error PDUs consist of an outer structure ("Request," "Response" and "Error-Response") containing fields common to all requests, responses and errors, respectively, and an inner structure for fields that are specific to each operation's requests/responses. The inner structure is optional in the case of the Error-Response PDU and need not be included when generic errors occur for which there is a suitable ProtocolErrorCode.

Specifically, the outer Request structure has a field for passing a client user's spoken (read) languages to the server. It also has two optional fields for identifying the requested operation's target principal's name and realm (if not sent then the server MUST use the client's principal name and realm as the target). A boolean field for indicating whether or not the request should be dry-run is also included; dry-runs can be used to test server policies, and servers MUST NOT modify any principals when processing dry-run requests.

The Response and Error PDUs' outer structures include a field indicating the language that the server has chosen for localization of text intended to be displayed to users; this field is defaulted to

"i-default". This language tag applies to all UTF8 strings in the inner structure (Op-rep and Op-err) that are meant to be displayed to users.

The protocol error codes are:

- proto-generic-error

An operation-specific error occurred, see the inner Op-error.

- proto-format-error
- proto-unsupported-major-version
- proto-unsupported-minor-version
- proto-unsupported-operation

- proto-wrong-service-principal

Use kadmin/setpw for the server's principal name.

- proto-re-authentication-required

The server demands that the client re-authenticate through a new AP exchange.

- proto-initial-ticket-required

Use of an INITIAL ticket is required for the requested operation.

- proto-client-and-target-realm-mismatch

The server requires that the client's principal name and the target principal of the operation share the same realm name.

- proto-target-principal-unknown
- proto-authorization-failed

[3.2](#) Operations

This section describes the semantics of each operation request and response defined in the ASN.1 module in [section 4](#).

[3.2.1](#) Null

NAME

null - Null or "ping" operation

DESCRIPTION

The null request is intended for use with TCP; its purpose is similar to RPC null procedures and is akin to a "ping" operation.

ERRORS

None.

[3.2.2](#) Change Kerberos Password

NAME

change-pw - Change password operation

SYNOPSIS

```
Req-change-pw(old-pw, [languages], [new-pw],  
              [commit], [etypes]) ->  
Rep-change-pw([info-text], [new-pw], [etypes]) |
```

N. Williams

[Page 9]

DRAFT

Kerberos Set/Change Password v2

Expires April 2006

```
Err-change-pw([help-text], error code, [error info])
```

DESCRIPTION

Change a principal's password.

The change password request has one required, three optional and one defaulted arguments: "old-pw" (required), "languages," "new-pw", "commit" (defaults to "TRUE") and "etypes", corresponding to the target principal's old password, its preferred languages, its new password, a boolean indicating whether or not to make the new long-term key available for immediate use, and the desired encetypes for the new long-term keys.

The server **MUST** validate the old password and **MUST** check the quality of the new password, if sent, according the password quality policy associated with the target principal.

If the old and new passwords in the request are the same strings,

and the principal is not currently required to change its password, then the server MAY permit the password change as way to change a principal's enctypees and string-to-key parameters. This feature provides a way to, for example, add enctypees to a principals' password-derived long-term keys without forcing a password change following an upgrade to the KDC that adds support for new enctypees.

A client MAY request that the server generate a new password by excluding the new password from its request, in which case the server MUST either generate a new password or respond with an error indicating that it does not support this feature.

Server-generated passwords MUST meet the target principal's password quality policy. It is RECOMMENDED that server-generated passwords be user-friendly, that is, memorable and that the target principal's preferred languages be taken into account by the password generation algorithm used by the server.

Uncommitted password changes are committed using the commit-keys operation.

RETURN

Upon successful password changes the server responds with a Rep-change-pw. The fields of Rep-change-pw are all optional and include:

- 'info-text' which the server can use to send a message to the user such as "Your new password will expire in 90 days," for example.
- 'new-pw' which the server MUST include if the client

requested that the server generate a new password; generated passwords MUST pass the target principal's password quality policy.

- 'etypes' which the server MAY include to indicate which types of long-term keys it created for the target principal and which the server MUST include if the client specified a set of enctypees in its request.

ERRORS

The server may respond to change password requests with protocol or operation errors. See [section 3.1](#) for a description of protocol error codes.

All operation errors include an optional 'help-text' field by which the server can describe the error in a human-readable, localized string.

Change password error codes include:

- generic-error
- old-pw-incorrect
- wont-generate-new-pw

The server will not generate a new password for this principal or does not support password generation in general.

- new-pw-rejected-generic

The client's proposed new password failed the target principal's password quality policy.

The server MUST include a description of the password quality policy or aspect of it that the client's proposed new password failed to meet.

The server MAY generate and send a new password that the client can then use as a new password and which is guaranteed to pass the target principal's current password quality policy.

The server MAY include a set of policy error code hints.

- etype-not-supported

The client requested an enctype that the KDC does not support.

[3.2.3](#) Set Kerberos Password

set-pw - Set password operation

SYNOPSIS

```
Req-set-pw([languages], [new-pw], [commit], [etypes]) ->  
  Rep-set-pw([info-text], [new-pw], [etypes]) |  
  Err-set-pw([help-text], error code, [error info])
```

DESCRIPTION

Administratively set a principal's password.

The set password request has three optional and one defaulted arguments: "languages", "new-pw," "commit" (defaulted to "TRUE") and "etypes", corresponding to the target principal's preferred languages, new password, a boolean indicating whether or not to make the new long-term key available for immediate use, and the desired encyptes for the new long-term keys.

The server **MUST** check the quality of the new password, if sent, according the password quality policy associated with the target principal.

The server **SHOULD** require that the client use the change-pw operation instead of set-pw when the client principal and the target principal are the same.

A client **MAY** request that the server generate a new password by excluding the new password from its request, in which case the server **MUST** either generate a new password or respond with an error indicating that it does not support this feature.

Server-generated passwords **MUST** meet the target principal's password quality policy. It is **RECOMMENDED** that server-generated passwords be user-friendly, that is, memorable and that the target principal's preferred languages be taken into account by the password generation algorithm used by the server.

RETURN

Upon successfully setting a password the server responds with a Rep-set-pw. The fields of Rep-set-pw are all optional and include:

- 'info-text' which the server can use to send a message to the user such as "Your new password will expire in 90 days," for example.
- 'new-pw' which the server **MUST** include if the client requested that the server generate a new password; generated passwords **MUST** pass the target principal's password quality

DRAFT

Kerberos Set/Change Password v2

Expires April 2006

policy.

- 'etypes' which the server MAY include to indicate which types of long-term keys it created for the target principal and which the server MUST include if the client specified a set of encytypes in its request.

ERRORS

The server may respond to set password requests with protocol or operation errors. See section XYZ for a description of protocol error codes.

All operation errors include an optional 'help-text' field by which the server can describe the error in a human-readable, localized string.

Set password error codes include:

- generic-error
- use-change-pw

The server demands that the client use the change-pw operation for the target principal of the set-pw request.

- wont-generate-new-pw

The server will not generate a new password for this principal or does not support password generation in general.

- new-pw-rejected-generic

The client's proposed new password failed the target principal's password quality policy.

The server MUST include a description of the password quality policy or aspect of it that the client's proposed new password failed to meet.

The server MAY generate and send a new password that the client can then use as a new password and which is guaranteed to pass the target principal's current password quality policy.

The server MAY include a set of policy error code hints.

- etype-not-supported

The client requested an enctype that the KDC does not support.

[3.2.4](#) Set Kerberos Keys

N. Williams

[Page 13]

DRAFT

Kerberos Set/Change Password v2

Expires April 2006

NAME

set-keys

SYNOPSIS

```
Req-set-keys(new-keys, commit?, [isupport]) ->  
  Rep-set-keys([info-text], kvno, aliases, [isupport])
```

DESCRIPTION

The set-keys request consists of two required fields and one optional field: "new-keys", "commit" (a boolean field - see below) and "isupport", an optional field for indicating to the KDC what Kerberos V features are supported by the target principal.

When "commit" is true the KDC makes the new keys available for issuing tickets encrypted in them immediately. Otherwise the client MUST follow up with a commit-keys request to make the keys available. This feature is useful for changing keys shared by multiple hosts, in clustered services, for example, in an atomic manner; see [section 3.2.6](#) and 3.2.7.

If a principal has keys are awaiting commitment when a new set-keys request for that principal s made then the KDC MUST overwrite the deferred keys.

RETURN

For successful set-keys operations the server returns:

- Informational text, optional.
- The new kvno for the target principal.

- A list of aliases of the target principal known to the KDC (optional).
- The set of Kerberos V features supported by the KDC (optional).

ERRORS

The server may respond with the following errors:

- generic
- deferred-commit-no-support
- etype-no-support

[3.2.5](#) Generate Kerberos Keys

NAME

N. Williams

[Page 14]

DRAFT

Kerberos Set/Change Password v2

Expires April 2006

gen-keys

SYNOPSIS

```
Req-gen-keys(etypes, [entropy], commit?, [isupport]) ->
Rep-set-keys([info-text], key, kvno, aliases, [isupport])
```

DESCRIPTION

The gen-keys is similar to the set-keys request (see [section 3.2.4](#)) but differs in that the server generates keys of client-requested encytypes, rather than the client providing specific keys.

The gen-keys request consists of two required fields and two optional fields: "etypes" (the encytypes of the new keys), "entropy", "commit" and "isupport" (see [section 3.2.4](#)).

If a principal has keys are awaiting commitment when a new set-keys request for that principal s made then the KDC MUST overwrite the deferred keys.

RETURN

For successful set-keys operations the server returns:

- Informational text, optional.
- The new kvno for the target principal.
- The new key (only one is needed).
- A list of aliases of the target principal known to the KDC (optional).
- The set of Kerberos V features supported by the KDC (optional).

ERRORS

The server may respond with the following errors:

- generic
- deferred-commit-no-support
- etype-no-support

[3.2.6](#) Get New Keys

NAME

get-keys

N. Williams

[Page 15]

DRAFT

Kerberos Set/Change Password v2

Expires April 2006

SYNOPSIS

```
Req-get-keys(kvno) ->
  Rep-get-keys([info-text], keys, aliases, [isupport]) |
  Err-get-keys([help-text], error code, [error info])
```

DESCRIPTION

This request allows a client to get the keys set or generated in a previous set-keys or gen-keys request with deferred commitment..

RETURN

If the target principal and kvno correspond to uncommitted keys the server **MUST** respond with the actual keys that would be set by a subsequent commit-keys request. Otherwise the server **MUST** respond with an error (meaning that this operation cannot be used

to extract keys from the KDC that may be in use).

ERRORS

- generic
- kvno-committed
- no-such-kvno

[3.2.7](#) Commit New Keys

NAME

commit-keys

SYNOPSIS

```
Req-commit-keys(kvno) ->
  Rep-commit-keys() |
  Err-commit-keys([help-text], error code, [error info])
```

DESCRIPTION

The commit-keys operation allows a client to bring a principal's new keys into use at the KDC.

Clients should make a commit-keys request corresponding to a deferred commitment set-keys/gen-keys operation as soon as the local key database for the target principal is updated.

The target principal name and the kvno MUST match those from a prior set-keys or gen-keys operation.

Servers MAY expire delayed key commitments at will. Servers SHOULD expire uncommitted new keys after a reasonable amount of time (600 seconds is RECOMMENDED).

Servers MUST respond to new set-keys requests for principals with pending, uncommitted new keys by expiring the uncommitted new keys and proceeding as if there had been no expired new keys.

ERRORS

- generic
- op-kvno-expired

- op-kvno-unknown
- new-keys-conflict (A set-keys or gen-keys request succeeded subsequent to the request that matches this {principal, kvno} tuple.)

[3.2.8](#) Get Password Quality Policy

NAME

get-pw-policy

SYNOPSIS

Req-get-pw-policy() ->
Rep-get-pw-policy([policy name], [policy description])

DESCRIPTION

Returns a description of the target principal's associated password quality policy, if any, as a list of localized UTF8String values.

Clients can use this operation in conjunction with the change-pw operation to obtain text that can be displayed to the user before the user actually enters a new password.

It is common for sites to set policies with respect to password quality. It is beyond the scope of this document to describe such policies. Management of password quality policies' actual content is also beyond the scope of this protocol.

ERRORS

No operation errors are defined.

[3.2.9](#) Get Principal Aliases

NAME

get-print-aliases

SYNOPSIS

Req-get-princ-aliases() ->

Rep-get-princ-aliases(aliases)

DESCRIPTION

Returns a list of aliases of the target principal.

ERRORS

No operation-specific errors.

[3.2.10](#) Get Realm's Supported Kerberos V Version and Features

NAME

get-realm-krb5-support

SYNOPSIS

Req-get-realm-krb5-support() ->
Rep-get-realm-krb5-support(isupport)

DESCRIPTION

Returns set of Kerberos V features support by the target principal's realm's KDCs.

ERRORS

No operation-specific errors.

[3.2.11](#) Retrieve Principal's S2K Params and Preferred Params

NAME

get-s2kparams

SYNOPSIS

Req-get-s2kparams() ->
Rep-get-s2kparams([princ-s2kparams], [preferred-s2kparams])

DESCRIPTION

Returns the string2key parameters for the principal's current password-derived long-term keys, if any, and the parameters that the realm would prefer, if they differ from the former.

This operation is intended for use with the change-pw() operation. When surprised by a KDC's PA-ETYPE-INFO2 a client SHOULD check if the principal's long-term secret keys' string2key parameters (and

entype list) should be changed and, if so, change them.

If the 'princ-s2kparams' return value is missing then the

DRAFT

Kerberos Set/Change Password v2

Expires April 2006

principal does not have a password-derived long-term key.

The 'preferred-s2kparams' MUST be excluded if the principal's string2key parameters satisfy the realm's policy.

ERRORS

No operation-specific errors.

[3.3](#) Principal Aliases

Applications that use Kerberos often have to derive acceptor principal names from hostnames entered by users. Such hostnames may be aliases, they may be fully qualified, partially qualified or not qualified at all. Some implementations have resorted to deriving principal names from such hostnames by utilizing the names services to canonicalize the hostname first; such practices are not secure unless the name service are secure, which often aren't.

One method for securely deriving principal names from hostnames is to alias principals at the KDC such that the KDC will issue tickets for principal names which are aliases of others. It is helpful for principals to know what are their aliases as known by the KDCs.

Note that changing a principal's aliases is out of scope for this protocol.

[3.4](#) Kerberos V Feature Negotiation

Principals and realms' KDCs may need to know about additional Kerberos V features and extensions that they each support. Several operations (see above) provide a way for clients and servers to exchange such information, in the form of lists of types supported for the various typed holes used in Kerberos V.

[4](#) ASN.1 Module

DEFINITIONS EXPLICIT TAGS ::= BEGIN

--

-- Note: EXPLICIT tagging is in use by default throughout this
-- module.

```

-- From [clarifications] with modifications
PrincipalName ::= SEQUENCE {
    name-string [1] SEQUENCE OF UTF8String (IA5String, ...)
}
Realm ::= UTF8String (IA5String, ...)
Salt ::= UTF8String (IA5String, ...)
Password ::= UTF8String (IA5String, ...)

-- NOTE WELL: Principal and realm names MUST be constrained by the
-- specification of the version of Kerberos V used by the
-- client.

```

N. Williams

[Page 19]

DRAFT

Kerberos Set/Change Password v2

Expires April 2006

```

--
-- [Perhaps PrincipalName should be a SEQUENCE of an optional name
-- type and a UTF8String, for simplicity.]

-- From [clarifications]
Int32 ::= INTEGER (-2147483648..2147483647)
UInt32 ::= INTEGER (0..4294967295)

-- Based on [clarifications]
Etype ::= Int32
Etype-Info-Entry ::= SEQUENCE {
    etype [0] Etype,
    salt [1] Salt OPTIONAL,
    s2kparams [2] OCTET STRING OPTIONAL,
    ...
}
Key ::= SEQUENCE {
    enc-type [0] Etype, -- from Kerberos
    key [1] OCTET STRING,
    ...
}

Language-Tag ::= UTF8String -- Constrained by [RFC3066]

-- Empty, extensible SEQUENCES are legal ASN.1
Extensible-NULL ::= SEQUENCE {
    ...
}

```

```

-- Kerberos clients negotiate some parameters relating to their peers
-- indirectly through the KDC. Today this is true of ticket session
-- key encetypes, but in the future this indirect negotiation may also

```

```

-- occur with respect to the minor version of Kerberos V to be used
-- between clients and servers.  Additionally, KDCs may need to know
-- what authorization-data types are supported by service principals,
-- both, for compatibility with legacy software and for optimization.
--
-- Theseore it is important for KDCs to know what features of
-- Kerberos V each service principal supports.
--
-- In version 2.0 of this protocol the clients and servers may notify
-- each other of their support for:
--
-- - enctypees
-- - authorization data types
-- - transited encoding data types
--
-- All authorization-data types defined in [clarifications] are
-- assumed to be supported if the minor version is 1 and do not need
-- to be included in the ad-type list.
--
-- Int32 is used for enctype and transited encoding data type
-- identifiers.

```

```

--
-- An extensible CHOICE of Int32 is used for authorization data
-- types.

```

```

KerberosV-TR-ID          ::= Int32

```

```

KerberosV-AD-ID          ::= CHOICE {
    ad-int                 [0] Int32,
    ...
}

```

```

KerberosVSupportNego     ::= SEQUENCE {
    enc-types              [0] SEQUENCE OF Etype,
    ad-types               [1] SEQUENCE OF KerberosV-AD-ID OPTIONAL,
                          -- authorization data types
    tr-enc-types           [2] SEQUENCE OF KerberosV-TR-ID OPTIONAL,
                          -- transited encoding types
    ...
}

```

```

Request                  ::= [APPLICATION 0] SEQUENCE {
    pvno-minor             [0] INTEGER DEFAULT 0,
    languages              [1] SEQUENCE OF Language-Tag OPTIONAL,

```



```

        -- Should be defaulted to the SEQUENCE of "i-default"
    targ-name      [2] PrincipalName OPTIONAL,
    targ-realm     [3] Realm OPTIONAL,
        -- If targ-name/realm are missing then the request
        -- applies to the principal of the client
    dry-run       [4] BOOLEAN DEFAULT FALSE,
    operation     [5] Op-req,
    ...
}

Response ::= [APPLICATION 1] SEQUENCE {
    pvno-minor [0] INTEGER DEFAULT 0,
    language   [1] Language-Tag DEFAULT "i-default",
    result     [2] Op-req,
    ...
}

Error-Response ::= [APPLICATION 2] SEQUENCE {
    pvno-minor [0] INTEGER DEFAULT 0,
    language   [1] Language-Tag DEFAULT "i-default",
    error-code [2] ProtocolErrorCode,
    help-text  [3] UTF8String OPTIONAL,
    op-error   [4] Op-err OPTIONAL,
    ...
}

Op-req ::= CHOICE {
    null          [0] Req-null,
    change-pw    [1] Req-change-pw,
    set-pw       [2] Req-set-pw,

```

```

    set-keys      [3] Req-set-keys,
    gen-keys     [4] Req-gen-keys,
    get-keys     [5] Req-get-keys,
    commit-keys  [6] Req-commit-keys,
    get-pw-policy [7] Req-get-pw-policy,
    get-princ-aliases [8] Req-get-princ-aliases,
    get-realm-krb5-support [9] Req-get-realm-krb5-support,
    get-s2kparams [10] Req-get-s2kparams,
    ...
}

Op-rep ::= CHOICE {
    null          [0] Rep-null,
    change-pw    [1] Rep-change-pw,

```

```

    set-pw                [2] Rep-set-pw,
    set-keys              [3] Rep-set-keys,
    gen-keys              [4] Req-gen-keys,
    get-keys              [5] Req-get-keys,
    commit-keys          [6] Rep-commit-keys,
    get-pw-policy         [7] Rep-get-pw-policy,
    get-princ-aliases     [8] Rep-get-princ-aliases,
    get-realm-krb5-support [9] Rep-get-realm-krb5-support,
    get-s2kparams         [10] Rep-get-s2kparams,
    ...
}

Op-err ::= CHOICE {
    null                [0] Err-null,
    change-pw          [1] Err-change-pw,
    set-pw             [2] Err-set-pw,
    set-keys           [3] Err-set-keys,
    gen-keys           [4] Err-gen-keys,
    get-keys           [5] Err-get-keys,
    commit-keys        [6] Err-commit-keys,
    get-pw-policy      [7] Err-get-pw-policy,
    get-princ-aliases [8] Err-get-princ-aliases,
    get-realm-krb5-support [9] Err-get-realm-krb5-support,
    get-s2kparams      [10] Err-get-s2kparams,
    ...
}

ProtocolErrorCode ::= ENUM {
    proto-format-error,
    proto-unsupported-major-version,
    proto-unsupported-minor-version,
    proto-unsupported-operation,      -- Request CHOICE tag unknown
    proto-generic-see-op-error,      -- See Op-error
    proto-wrong-service-principal,   -- Use kadmin/setpw
    proto-re-authentication-required,
    proto-initial-ticket-required,
    proto-client-and-target-realm-mismatch,
    proto-target-principal-unknown,
    proto-authorization-failed,

```

```

    proto-dry-run-not-permitted,
    ...
}

```

-- These codes are hints for clients, primarily for when they are

```

-- used for changing the passwords of automated principals; error
-- replies carry password quality policy help text that is more
-- appropriate for clients to display to users.
PW-Quality-Codes ::= ENUM {
    pwq-generic,
    pwq-too-soon,
    pwq-repeated,
    pwq-too-short,
    pwq-dictionary-words,
    pwq-prohibited-codepoints,
    pwq-need-more-char-classes,
    ...
}

--
-- Requests and responses
--

-- NULL request, much like ONC RPC's NULL procedure - NOT extensible
Req-null ::= NULL

Rep-null ::= NULL

Err-null ::= NULL

-- Change password
Req-change-pw ::= SEQUENCE {
    old-pw [0] Password,
    new-pw [1] Password OPTIONAL,
    commit [2] BOOLEAN DEFAULT TRUE,
    etypes [3] SEQUENCE (1..) OF Etype OPTIONAL,
    ...
}

Rep-change-pw ::= SEQUENCE {
    info-text [0] UTF8String OPTIONAL,
    new-pw [1] Password OPTIONAL,
    -- generated by the server if present
    -- (and requested by the client)
    etypes [2] SEQUENCE (1..) OF Etype OPTIONAL,
    ...
}

Err-change-pw ::= SEQUENCE {
    help-text [0] UTF8String OPTIONAL,
    error [1] CHOICE {
        op-generic-error [0] Extensible-NULL,
        op-old-pw-incorrect [1] Extensible-NULL,
    }
}

```

```

op-wont-generate-new-pw    [2] Extensible-NULL,
op-new-pw-rejected-generic [3] SEQUENCE {
    policy                  [1] SEQUENCE OF UTF8String,
    suggested-pw            [2] Password OPTIONAL,
    policy-codes            [3] SET OF PW-Quality-Codes
                            OPTIONAL,
    ...
}
op-etype-not-supported    [4] SEQUENCE {
    supported-etypes       [1] SEQUENCE OF Etype,
    ...
},
...
},
...
}

-- Set password
Req-set-pw ::= SEQUENCE {
    languages      [0] SEQUENCE OF Language-Tag OPTIONAL,
    new-pw         [1] Password OPTIONAL,
    commit         [2] BOOLEAN DEFAULT TRUE,
    etypes         [3] SEQUENCE (1..) OF Etype OPTIONAL,
    ...
}

Rep-set-pw ::= SEQUENCE {
    info-text      [0] UTF8String OPTIONAL,
    new-pw         [1] Password OPTIONAL,
    -- generated by the server if present
    -- (and requested by the client)
    etypes         [2] SEQUENCE (1..) OF Etype OPTIONAL,
    ...
}

Err-set-pw ::= Err-change-pw

-- Set keys
Req-set-keys ::= SEQUENCE {
    keys           [0] SEQUENCE OF Key,
    commit         [1] BOOLEAN DEFAULT TRUE,
    -- TRUE -> install keys now
    --
    -- FALSE -> require set-keys-commit
    --           before issuing tickets
    --           encrypted with these keys.
    --
    -- See commit-keys op

```

```
isupport          [2] KerberosVSupportNego OPTIONAL,
                  -- For future Kerberos V extensions KDCs
                  -- may need to know what krb5 version is
                  -- supported by individual service
                  -- principals. This field provides a
```

DRAFT Kerberos Set/Change Password v2 Expires April 2006

```
                  -- way to tell the KDC what version of
                  -- Kerberos V the target principal
                  -- supports.
...
}
```

```
Rep-set-keys      ::= SEQUENCE {
  info-text       [0] UTF8String OPTIONAL,
  kvno            [1] UInt32,
  aliases        [2] SEQUENCE OF SEQUENCE {
    name          [0] PrincipalName,
    realm        [1] Realm OPTIONAL,
    ...
  },
  isupport       [3] KerberosVSupportNego OPTIONAL,
  ...
  -- Should there be ETYPE-INFO2 stuff here?
}
```

```
Err-set-keys     ::= SEQUENCE {
  help-text      [0] UTF8String OPTIONAL, -- Reason for rejection
  error         [1] CHOICE {
    op-generic           [0] Extensible-NULL,
    op-deferred-commit-no-support [1] Extensible-NULL,
    op-etype-no-support [2] SEQUENCE OF {
      supported-etypes [1] SEQUENCE OF Etype,
      ...
    }
    ...
  }
}
```

```
-- Generate keys
Req-gen-keys     ::= SEQUENCE {
  etypes         [0] SEQUENCE (1..) OF Etype,
  entropy        [1] OCTET STRING OPTIONAL,
  commit        [2] BOOLEAN DEFAULT TRUE,
                -- TRUE -> install keys now
                --
```

```

-- FALSE -> require set-keys-commit
--           before issuing tickets
--           encrypted with these keys.
--
-- See commit-keys op
isupport    [3] KerberosVSupportNego OPTIONAL,
-- For future Kerberos V extensions KDCs
-- may need to know what krb5 version is
-- supported by individual service
-- principals. This field provides a
-- way to tell the KDC what version of
-- Kerberos V the target principal
-- supports.
...

```

```

}

Rep-gen-keys ::= SEQUENCE {
    info-text    [0] UTF8String OPTIONAL,
    kvno         [1] UInt32,
    key          [2] Key,
    aliases     [3] SEQUENCE OF SEQUENCE {
        name      [0] PrincipalName,
        realm     [1] Realm OPTIONAL,
        ...
    },
    isupport    [4] KerberosVSupportNego OPTIONAL,
    ...
    -- Should there be ETYPE-INF02 stuff here?
}

Err-gen-keys ::= Err-set-keys

-- Get un-committed key request
Req-get-keys ::= SEQUENCE {
    kvno        [0] UInt32,
    ...
}

Rep-get-keys ::= SEQUENCE {
    info-text   [0] UTF8String OPTIONAL,
    keys        [1] SEQUENCE OF Key,
    aliases     [2] SEQUENCE OF SEQUENCE {
        name     [0] PrincipalName,
        realm    [1] Realm OPTIONAL,
    }
}

```

```

    ...
  },
  isupport          [3] KerberosVSupportNego OPTIONAL,
  ...
  -- Should there be ETYPE-INFO2 stuff here?
}

Err-get-keys ::= SEQUENCE {
  help-text      [0] UTF8String OPTIONAL, -- Reason for rejection
  error          [1] CHOICE {
    op-generic           [0] Extensible-NULL,
    op-kvno-committed  [1] Extensible-NULL,
    op-no-such-kvno    [1] Extensible-NULL,
    ...
  }
}

-- Commit a set keys request
Req-commit-keys ::= SEQUENCE {
  kvno          [0] UInt32,
  ...
}

```

```

Rep-commit-keys ::= Extensible-NULL

Err-commit-keys ::= SEQUENCE {
  help-text      [0] UTF8String OPTIONAL, -- Reason for rejection
  error          [1] CHOICE {
    op-generic           [0] Extensible-NULL,
    op-kvno-expired     [1] Extensible-NULL,
    -- The client took too long to respond.
    op-kvno-unknown     [2] Extensible-NULL,
    -- The targ princ/kvno is invalid or unknown to the
    -- server (perhaps it lost track of state)
    op-new-keys-conflict [3] Extensible-NULL,
    -- A new-keys/commit-keys request subsequent to the
    -- new-keys that produced the kvno has completed
    -- and incremented the principal's kvno
    ...
  }
  ...
}

-- Get password policy

```

```

Req-get-pw-policy ::= Extensible-NULL

Rep-get-pw-policy ::= SEQUENCE {
    policy-name      [0] UTF8String OPTIONAL,
    description      [1] SEQUENCE OF UTF8String OPTIONAL,
    ...
}

Err-get-pw-policy ::= Extensible-NULL

-- Get principal aliases
Req-get-princ-aliases ::= Extensible-NULL

Rep-get-princ-aliases ::= SEQUENCE {
    help-text      [0] UTF8String OPTIONAL,
    aliases        [1] SEQUENCE OF SEQUENCE {
        name        [0] PrincipalName,
        realm        [1] Realm OPTIONAL,
        ...
    },
    ...
}

Err-get-princ-aliases ::= Extensible-NULL

-- Get list of enctypees supported by KDC for new keys
Req-get-realm-krb5-support ::= Extensible-NULL

Rep-get-realm-krb5-support ::= SEQUENCE {
    isupport      [0] KerberosVSupportNego,
    -- Version of Kerberos V supported by
    -- the target realm.
}

```

```

    ...
}

Err-get-realm-krb5-support ::= Extensible-NULL

-- Get s2kparams
Req-get-s2kparams ::= Extensible-NULL

Rep-get-s2kparams ::= SEQUENCE {
    help-text      [0] UTF8String OPTIONAL,
    s2kparams      [1] SEQUENCE OF Etype-Info-Entry,
    ...
}

```


}

Err-get-s2kparams ::= Extensible-NULL

END

6 IANA Considerations

There are no IANA considerations for this document.

7 Security Considerations

Implementors and site administrators should note that the redundancy of UTF-8 encodings of passwords varies by language. Password quality policies SHOULD, therefore, take this into account when estimating the amount of redundancy and entropy in a proposed new password. [?? It's late at night - I think this is correct.]

Kerberos set/change password/key protocol major version negotiation cannot be done securely; a downgrade attack is possible against clients that attempt to negotiate the protocol major version to use with a server. It is not clear at this time that the attacker would gain much from such a downgrade attack other than denial of service (DoS) by forcing the client to use a protocol version which does not support some feature needed by the client (Kerberos V in general is subject to a variety of DoS attacks anyways [[RFC1510](#)]). Clients SHOULD NOT negotiate support for legacy major versions of this protocol unless configured otherwise.

This protocol does not have Perfect Forward Security (PFS). As a result, any passive network snooper watching password/key changing operations who has stolen a principal's password or long-term keys can find out what the new ones are.

[More text needed?]

8 Acknowledgements

The authors would like to thank original editors/authors Jonathan Trostle, Bill Gossman, Mike Swift, John Brezak, as well as Ken Raeburn, Tom Yu, Martin Rex, Sam Hartman, Tony Andrea, Paul W.

N. Williams

[Page 28]

DRAFT

Kerberos Set/Change Password v2

Expires April 2006

Nelson, Marcus Watts, Love, Joel N. Weber II, Jeffrey Hutzelman and other participants from the IETF Kerberos Working Group for their

assistance.

9 References

9.1 Normative References

[RFC2026]

S. Bradner, [RFC2026](#): "The Internet Standard Process - Revision 3," October 1996, Obsoletes - [RFC 1602](#), Status: Best Current Practice.

[RFC2119]

S. Bradner, [RFC2119](#) ([BCP14](#)): "Key words for use in RFCs to Indicate Requirement Levels," March 1997, Status: Best Current Practice.

[X680]

Abstract Syntax Notation One (ASN.1): Specification of Basic Notation, ITU-T Recommendation X.680 (1997) | ISO/IEC International Standard 8824-1:1998.

http://www.itu.int/ITU-T/studygroups/com17/languages/X680_0702.pdf

[X690]

ASN.1 encoding rules: Specification of Basic Encoding Rules (BER), Canonical Encoding Rules (CER) and Distinguished Encoding Rules (DER), ITU-T Recommendation X.690 (1997) | ISO/IEC International Standard 8825-1:1998.

http://www.itu.int/ITU-T/studygroups/com17/languages/X690_0702.pdf

[clarifications]

RFC-Editor: To be replaced by RFC number for [draft-ietf-krb-wg-kerberos-clarifications](#).

[RFC3066]

H. Alvestrand, [RFC3066](#) ([BCP47](#)): "Tags for the Identification of Languages," January 2001, Obsoletes [RFC1766](#), Status: Best Current Practice.

9.2 Informative References

[RFC3244]

M. Swift, J. Trostle, J. Brezak, [RFC3244](#): "Microsoft Windows 2000 Kerberos Change Password and Set Password Protocols," February 2002, Status: Informational.

10 Authors' Addresses

Nicolas Williams
Sun Microsystems
5300 Riata Trace Ct
Austin, TX 78727

DRAFT

Kerberos Set/Change Password v2

Expires April 2006

Email: nicolas.williams@sun.com

11 Notes to the RFC Editor

This document has two KRB WG drafts as normative references and cannot progress until those drafts progress, but no other draft depends on this one.

12 Change History

-01 -> -02

- Removed Bill Gossman, Mike Swift and John Brezak as authors.
- Removed UDP as a transport for this protocol.
- Replaced redundant copies of framing ASCII art with reference to [RFC3244](#).
- Made all name/password strings UTF8String with an extensible constraint to IA5String.
- Added a method for doing dry runs of operations. This is helpful in testing passwords against password quality policies.
- Added an operation for retrieving a principal's current and preferred string-to-key parameters, and a way to change them without changing the principal's password.
- Added password quality codes as hints for smart clients, but these are optional and not to be used instead of messages to be displayed to users.
- Added a 'commit' option to change-pw and set-pw (as requested by Larry).
- Removed "version" field of the Kerberos V feature negotiation structure.

Intellectual Property Statement

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in [BCP 78](#) and [BCP 79](#).

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at ietf-ipr@ietf.org.

Disclaimer of Validity

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Copyright Statement

Copyright (C) The Internet Society (2005). This document is subject to the rights, licenses and restrictions contained in [BCP 78](#), and except as set forth therein, the authors retain all their rights.

Acknowledgment

Funding for the RFC Editor function is currently provided by the

Internet Society.

Williams

Expires August 22, 2005

[Page 31]