

Networking Working Group  
Internet-Draft  
Intended status: Standards Track  
Expires: May 21, 2016

V. Govindan  
C. Pignataro  
Cisco Systems  
November 18, 2015

**Advertising S-BFD Discriminators in L2TPv3  
draft-ietf-l2tpext-sbfd-discriminator-01.txt**

Abstract

This document defines a new AVP for advertising one or more S-BFD Discriminators using the L2TPv3 Control Protocol AVP.

Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on May 21, 2016.

Copyright Notice

Copyright (c) 2015 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must

include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

<a href="#">1.</a>	Introduction . . . . .	<a href="#">2</a>
<a href="#">2.</a>	S-BFD Target Discriminator ID AVP . . . . .	<a href="#">2</a>
<a href="#">2.1.</a>	Encoding Format . . . . .	<a href="#">2</a>
<a href="#">3.</a>	IANA Considerations . . . . .	<a href="#">3</a>
<a href="#">4.</a>	Security Considerations . . . . .	<a href="#">3</a>
<a href="#">5.</a>	Acknowledgements . . . . .	<a href="#">4</a>
<a href="#">6.</a>	Contributing Authors . . . . .	<a href="#">4</a>
<a href="#">7.</a>	References . . . . .	<a href="#">4</a>
<a href="#">7.1.</a>	Normative References . . . . .	<a href="#">4</a>
<a href="#">7.2.</a>	Informative References . . . . .	<a href="#">5</a>
	Authors' Addresses . . . . .	<a href="#">5</a>

## [1.](#) Introduction

[I-D.ietf-bfd-seamless-base] defines a simplified mechanism to use Bidirectional Forwarding Detection (BFD)[[RFC5880](#)]. This mechanism depends on network nodes knowing the BFD discriminators which each node in the network has reserved for this purpose. Use of the Layer2 Tunneling protocol Version 3 (L2TPv3) [[RFC3931](#)] is one possible means of advertising these discriminators. S-BFD requires the usage of unique discriminators within an administrative domain.

This document specifies the encoding to be used when S-BFD discriminators are advertised using L2TPv3.

## [2.](#) S-BFD Target Discriminator ID AVP

This AVP is exchanged during session negotiation (ICRQ, ICRP, OCRQ, OCRP).

### [2.1.](#) Encoding Format

The S-BFD Target Discriminator ID AVP, Attribute Type TBD, is an identifier used to advertise the S-BFD target discriminators supported by an LCCE for S-BFD Reflector operation. This AVP indicates that the advertiser implements a S-BFD reflector supporting the specified target discriminators and is ready for S-BFD Reflector operation. The receiving LCCE MAY use this AVP if it wants to monitor connectivity to the advertising LCCE using S-BFD or BFD.

The Attribute Value field for this AVP has the following format:



S-BFD Discriminator Advertisement (ICRQ, ICRP, ICCN, OCRQ, OCRP, OCCN):

	No. of octets
+-----+	
Discriminator Value(s)	4/Discriminator
:	:
+-----+	

An LCCE MAY include the S-BFD Discriminator Advertisement AVP in a L2TP Control Protocol message (ICRQ, ICRP, OCRQ, OCRP) [RFC3931]. Multiple S-BFD Discriminators AVPs MAY be advertised by a LCCE. If the other LCCE does not wish to monitor connectivity using S-BFD, it MAY safely discard this AVP without affecting the rest of session negotiation. While current use-cases [I-D.ietf-bfd-seamless-use-case] of S-BFD require advertisement of only one discriminator, the AVP encoding allows specification an arbitrary number of discriminators for extensibility. When multiple S-BFD discriminators are advertised, the mechanism to choose a subset of specific discriminator(s) is out of scope for this document.

The M bit of the L2TP Control Protocol Message (ICRQ, ICRP, OCRQ, OCRP) [RFC3931] MUST NOT be set inside the S-BFD Target Discriminator ID AVP advertisement.

### 3. IANA Considerations

This number space is managed by IANA as per [RFC3438].

A summary of the new AVPs requested for Attribute Type 0 follows:

Control Message Attribute Value Pairs

Attribute Type	Description
-----	-----
TBD	S-BFD Discriminators

### 4. Security Considerations

Security concerns for L2TP are addressed in [RFC3931]. Introduction of the S-BFD Discriminator Advertisement AVP introduces no new security risks for L2TP.

Advertisement of the S-BFD discriminators does make it possible for attackers to initiate S-BFD sessions using the advertised



information. The vulnerabilities this poses and how to mitigate them are discussed in the Security Considerations section of [\[I-D.ietf-bfd-seamless-base\]](#).

## 5. Acknowledgements

Authors would like to thank Nobo Akiya, Stewart Bryant and Pawel Sowinski for providing core inputs for the document and for performing thorough reviews and providing number of comments. Authors would like to thank Nagendra Kumar for his reviews.

## 6. Contributing Authors

Mallik Mudigonda  
Cisco Systems  
Email: mmudigon@cisco.com

## 7. References

### 7.1. Normative References

- [I-D.ietf-bfd-seamless-base]  
Akiya, N., Pignataro, C., Ward, D., Bhatia, M., and J. Networks, "Seamless Bidirectional Forwarding Detection (S-BFD)", [draft-ietf-bfd-seamless-base-05](#) (work in progress), June 2015.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<http://www.rfc-editor.org/info/rfc2119>>.
- [RFC3438] Townsley, W., "Layer Two Tunneling Protocol (L2TP) Internet Assigned Numbers Authority (IANA) Considerations Update", [BCP 68](#), [RFC 3438](#), DOI 10.17487/RFC3438, December 2002, <<http://www.rfc-editor.org/info/rfc3438>>.
- [RFC3931] Lau, J., Ed., Townsley, M., Ed., and I. Goyret, Ed., "Layer Two Tunneling Protocol - Version 3 (L2TPv3)", [RFC 3931](#), DOI 10.17487/RFC3931, March 2005, <<http://www.rfc-editor.org/info/rfc3931>>.
- [RFC5880] Katz, D. and D. Ward, "Bidirectional Forwarding Detection (BFD)", [RFC 5880](#), DOI 10.17487/RFC5880, June 2010, <<http://www.rfc-editor.org/info/rfc5880>>.



## **7.2. Informative References**

[I-D.ietf-bfd-seamless-use-case]

Aldrin, S., Bhatia, M., Matsushima, S., Mirsky, G., and N. Kumar, "Seamless Bidirectional Forwarding Detection (BFD) Use Case", [draft-ietf-bfd-seamless-use-case-03](#) (work in progress), July 2015.

### Authors' Addresses

Vengada Prasad Govindan  
Cisco Systems

Email: [venggovi@cisco.com](mailto:venggovi@cisco.com)

Carlos Pignataro  
Cisco Systems

Email: [cpignata@cisco.com](mailto:cpignata@cisco.com)



