

Network Working Group  
Internet-Draft  
Expires: April 26, 2006

J. Heinanen  
TutPro Inc.  
G. Weber, Ed.  
W. Townsley  
S. Booth  
W. Luo  
Cisco Systems  
October 23, 2005

**Using RADIUS for PE-Based VPN Discovery**  
**draft-ietf-l2vpn-radius-pe-discovery-02.txt**

Status of this Memo

By submitting this Internet-Draft, each author represents that any applicable patent or other IPR claims of which he or she is aware have been or will be disclosed, and any of which he or she becomes aware will be disclosed, in accordance with [Section 6 of BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/1id-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on April 26, 2006.

Copyright Notice

Copyright (C) The Internet Society (2005).

Abstract

This document describes a strategy by which Provider Equipment (PE) can be dynamically provisioned for inclusion in PE-based Layer 2 Virtual Private Networks (L2VPNs). This layered strategy utilizes the Remote Authentication Dial In User Service (RADIUS) protocol as a

centralized control mechanism and can be used in conjunction with other proposed mechanisms. The mechanisms described in this document enhance those established by [RFC 2868](#) and conform to those described by the L2VPN Framework.

## Table of Contents

<a href="#">1.</a>	Terminology . . . . .	<a href="#">3</a>
<a href="#">2.</a>	Acronyms . . . . .	<a href="#">3</a>
<a href="#">3.</a>	Introduction . . . . .	<a href="#">3</a>
<a href="#">4.</a>	Information Model . . . . .	<a href="#">3</a>
<a href="#">5.</a>	New RADIUS Attributes . . . . .	<a href="#">6</a>
<a href="#">5.1.</a>	Router-Distinguisher . . . . .	<a href="#">6</a>
<a href="#">5.2.</a>	VPN-ID . . . . .	<a href="#">7</a>
<a href="#">5.3.</a>	Attachment-Individual-ID . . . . .	<a href="#">7</a>
<a href="#">5.4.</a>	Per-Hop-Behavior . . . . .	<a href="#">8</a>
<a href="#">5.5.</a>	PE-Router-ID . . . . .	<a href="#">9</a>
<a href="#">5.6.</a>	PE-Address . . . . .	<a href="#">9</a>
<a href="#">5.7.</a>	PE-Record . . . . .	<a href="#">10</a>
<a href="#">6.</a>	New Values for Existing RADIUS Attributes . . . . .	<a href="#">11</a>
<a href="#">6.1.</a>	Service-Type . . . . .	<a href="#">11</a>
<a href="#">6.2.</a>	User-Name . . . . .	<a href="#">12</a>
<a href="#">7.</a>	Table of Attributes . . . . .	<a href="#">12</a>
<a href="#">8.</a>	Examples . . . . .	<a href="#">14</a>
<a href="#">9.</a>	Security Considerations . . . . .	<a href="#">14</a>
<a href="#">10.</a>	IANA Considerations . . . . .	<a href="#">15</a>
<a href="#">11.</a>	References . . . . .	<a href="#">15</a>
<a href="#">11.1.</a>	Normative References . . . . .	<a href="#">15</a>
<a href="#">11.2.</a>	Informative References . . . . .	<a href="#">15</a>
	Authors' Addresses . . . . .	<a href="#">17</a>
	Intellectual Property and Copyright Statements . . . . .	<a href="#">18</a>



## **1. Terminology**

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

This document uses terminology from [[I-D.ietf-l2vpn-l2-framework](#)] and [[I-D.ietf-l2vpn-signaling](#)].

## **2. Acronyms**

AII: Attachment Individual Identifier  
AC: Attachment Circuit  
AGI: Attachment Group Identifier  
AS: Autonomous System  
CE: Customer Equipment  
L2VPN: Layer 2 Provider Provisioned Virtual Private Network  
NAI: Network Access Identifier  
NAS: Network Access Server  
PE: Provider Equipment  
SAI: Source Attachment Identifier  
SAII: Source Attachment Individual Identifier  
RADIUS: Remote Authentication Dial In User Service  
TAI: Target Attachment Identifier  
TAII: Target Attachment Individual Identifier  
VPLS: Virtual Private LAN Service  
VPN: Virtual Private Network  
VPWS: Virtual Private Wire Service

## **3. Introduction**

This document describes how in PE-based VPNs a PE of a VPN can use RADIUS [[RFC2865](#)] to authenticate its CEs and discover the other PEs of the VPN. In RADIUS terms, the CEs are users and the PEs are Network Access Servers (NAS) implementing RADIUS client functionality.

A VPN can span multiple Autonomous Systems (AS) and multiple providers. Each PE, however, only needs to be a RADIUS client to a RADIUS server of the "local" provider. In the case in which a CE belongs to a "foreign" VPN, the RADIUS server of the local provider acts as a proxy client to RADIUS of the foreign provider.

## **4. Information Model**



This document presents a model wherein authorization for participation in a PE-based VPN can be divided into three different layers of access.

- o CE or AC Authorization
- o VPN Authorization
- o Pseudowire Authorization

The first layer is AC authorization, in which a first sign of life on a particular AC triggers an authorization resulting in provisioning information particular to the circuit in question. Once the AC is authorized, its VPN membership is authorized separately. This authorization step may result in a number of pseudowire specific connections; each of which may be authorized separately. The relationships between these three data representations are shown in the diagram below.

Using a layered approach allows the different stages of authorization to be satisfied by separate means based on deployment scenario. It also allows one model to apply to various deployment architectures including VPLS and VPWS. If all three authorization stages are accommodated by a RADIUS server, the stages may be combined into a single transaction instead of having three separate transactions.









- o Each pseudowire may have its own per-hop behavior and arbitrary configuration information
- o Each pseudowire is associated with an AII
- o Each PE includes an arbitrary number of AIIs
- o Each PE has one associated next hop address
- o The VPN includes an arbitrary number of PEs

The following two sections define how the components of this data model may be represented as RADIUS attributes so the components of this information model may be communicated from a centralized location out into the network elements.

## 5. New RADIUS Attributes

This document defines several new RADIUS Attributes which are described in detail in this section.

### 5.1. Router-Distinguisher

This attribute represents a Router Distinguisher as described in [[I-D.ietf-l3vpn-rfc2547bis](#)]. It MAY be included in an Access-Request message. This attribute MUST NOT be included in Access-Request messages that also include a "VPN-ID" attribute.

A summary of the Router-Distinguisher attribute format is shown below. The fields are transmitted from left to right.

```

      0                               1                               2
      0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|      Type      |      Length      | Text ...
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+

```

Type

(TBA) for Router-Distinguisher.

Length

>= 7

Text

The Text field is composed of three colon separated parts: a type, an administrator, and an assigned number.

Where the type is "0", the administrator contains a 16-bit Autonomous



System Number (ASN), and the assigned number is a 32-bit value assigned by enterprise responsible for the ASN, e.g. "0:114:23".

Where the type is "1", the administrator contains an IP address, and the assigned number is a 16-bit value assigned by the enterprise controlling the IP address space, e.g. "1:1.2.3.4:10001".

Where the type is "2", the administrator contains a 32-bit ASN, and the assigned number is a 16-bit value assigned by the enterprise responsible for the ASN, e.g. "2:70000:216".

## 5.2. VPN-ID

This attribute represents a VPN-ID as described in [[RFC2685](#)]. It MAY be included in an Access-Request message. This attribute MUST NOT be included in Access-Request messages that also include a Router-Distinguisher attribute.

A summary of the VPN-ID attribute format is shown below. The fields are transmitted from left to right.

```

      0                               1                               2
      0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|      Type      |      Length      |      Text ...
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+

```

Type

(TBA) for VPN-ID.

Length

>= 5

Text

The Text field is composed of two colon separated parts: a VPN authority Organizationally Unique Identifier, and a VPN index, e.g. "101:14".

## 5.3. Attachment-Individual-ID

This attribute indicates a Attachment-Individual-ID as described in [[I-D.ietf-l2vpn-signaling](#)].

A summary of the Attachment-Individual-ID attribute format is shown below. The fields are transmitted from left to right.



```

      0                               1                               2
      0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|   Type   |   Length   |   Text ...
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+

```

Type

(TBA) for Attachment-Individual-ID.

Length

>= 3

Text

The Text field is an encoding of the Source Attachment Individual Identifier, e.g. "2".

#### 5.4. Per-Hop-Behavior

This attribute indicates a Per-Hop-Behavior as described in [\[RFC3140\]](#).

A summary of the Per-Hop-Behavior attribute format is shown below. The fields are transmitted from left to right.

```

      0                               1                               2                               3
      0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|   Type   |   Length   |                               Value
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|                               Value (cont) |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+

```

Type

(TBA) for Per-Hop-Behavior.

Length

6

Integer

The lower 16-bits of the value contains the Per-Hop-Behavior value as described in [\[RFC3140\]](#).



### 5.5. PE-Router-ID

This attribute typically indicates an IPv4 address for a particular PE member of a VPN, though it may be some arbitrary value assigned by the owner of the ID space.

A summary of the PE-Router-ID attribute format is shown below. The fields are transmitted from left to right.

[illegible]

Type

(TBA) for PE-Router-ID.

Length

6

Address

Typically, the value indicates the IPv4 address of a particular PE member of a VPN.

### 5.6. PE-Address

This attribute indicates an IPv4 address for a particular PE member of a VPN. In relation to the PE for which a CE is joining the VPN, this would be the initial's PE's next hop address.

A summary of the PE-Address attribute format is shown below. The fields are transmitted from left to right.





```

      0                               1                               2                               3
      0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|   Type   |   Length   |                               Value
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
                        Value (cont) |
+---+---+---+---+---+---+---+---+

```

Type

(TBA) for PE-Address.

Length

6

Address

The value indicates the IPv4 address of a particular PE member of a VPN.

## 5.7. PE-Record

This attribute represents a single element within a particular PE's description. A group of PE-Records combine to form a complete PE description when returned during VPN authorization.

A summary of the PE-Record attribute format is shown below. The fields are transmitted from left to right.

```

      0                               1                               2
      0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|   Type   |   Length   | Text ...
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+

```

Type

(TBA) for PE-Record.

Length

>= 8

Text

The Text field contains an AII prefixed by a PE-Router-ID and separated by a colon, e.g. "1.1.1.1:14" where the PE-Router-ID is



1.1.1.1 and the AII is 14. This represents a particular pseudowire. The value is optionally suffixed by a colon separated list of attribute value pairs containing pseudowire-specific configuration, e.g. "1.1.1.1:14:PHB=256".

## **6. New Values for Existing RADIUS Attributes**

### **6.1. Service-Type**

This document defines one new value for an existing RADIUS attribute. The Service-Type attribute is defined in [Section 5.6 of RFC 2865](#) [[RFC2865](#)], as follows:

This Attribute indicates the type of service the user has requested, or the type of service to be provided. It MAY be used in both Access-Request and Access-Accept packets.

A NAS is not required to implement all of these service types, and MUST treat unknown or unsupported Service-Types as though an Access-Reject had been received instead.

A summary of the Service-Type Attribute format is shown below.

The fields are transmitted from left to right.







## CE/AC Authorization

Request	Accept	Reject	Challenge	#	Attribute
0	0-1	0	0	TBA	Router-Distinguisher
0	0-1	0	0	TBA	VPN-ID

## VPN Authorization

Request	Accept	Reject	Challenge	#	Attribute
0-1	0	0	0	TBA	Router-Distinguisher
0-1	0	0	0	TBA	VPN-ID
0	0+	0	0	TBA	Attachment-Individual-ID
0	0-1	0	0	TBA	Per-Hop-Behavior
0	0-1	0	0	TBA	PE-Router-ID
0	0-1	0	0	TBA	PE-Address
0	0+	0	0	TBA	PE-Record

## Pseudowire Authorization

## VPN Authorization

Request	Accept	Reject	Challenge	#	Attribute
0-1	0	0	0	TBA	Router-Distinguisher
0-1	0	0	0	TBA	VPN-ID
1	0	0	0	TBA	Attachment-Individual-ID
0	0-1	0	0	TBA	Per-Hop-Behavior

The following table defines the meaning of the above table entries.

- 0    This attribute MUST NOT be present in a packet.
- 0+   Zero or more instances of this attribute MAY be present in a packet.
- 0-1   Zero or one instance of this attribute MAY be present in a packet.
- 1    Exactly one instance of this attribute MUST be present in a packet.





## **8. Examples**

### CE/AC Authorization

#### Request

User-Name = "providerX/atlanta@vpnY.domainZ.net" (CE NAI)  
NAS-IP-Address = "1.1.1.1"

#### Response

VPN-ID = "100:14"

#### Request

User-Name = "ATM14.0.1" (AC Name)  
NAS-IP-Address = "1.1.1.1"

#### Response

Router-Distinguisher = "1:1.2.3.4:10001"

### VPN Authorization

#### Request

User-Name = "100:14" (VPN-ID)  
NAS-IP-Address = "1.1.1.1"

#### Response

PE-Record = "2.2.2.2:14" (PE-Router-ID:AII)  
PE-Record = "2.2.2.2:15"  
PE-Record = "3.3.3.3:24"  
PE-Record = "3.3.3.3:25"

#### Request

User-Name = "100:14" (VPN-ID)  
NAS-IP-Address = "1.1.1.1"

#### Response

PE-Record = "2.2.2.2:14:PHB=256"

### Pseudowire Authorization

#### Request

User-Name = "2.2.2.2" (PE-Router-ID)  
NAS-IP-Address = "1.1.1.1"  
Attachment-Individual-ID = "14"  
VPN-ID = "100:14"

#### Response

Per-Hop-Behavior = "256"

## **9. Security Considerations**

[TBD]



## **10.    IANA Considerations**

[TBD]

## **11.    References**

### **11.1.    Normative References**

- [RFC2119]   Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC2865]   Rigney, C., Willens, S., Rubens, A., and W. Simpson, "Remote Authentication Dial In User Service (RADIUS)", [RFC 2865](#), June 2000.
- [RFC2868]   Zorn, G., Leifer, D., Rubens, A., Shriver, J., Holdrege, M., and I. Goyret, "RADIUS Attributes for Tunnel Protocol Support", [RFC 2868](#), June 2000.
- [RFC2685]   Fox, B. and B. Gleeson, "Virtual Private Networks Identifier", [RFC 2685](#), September 1999.

### **11.2.    Informative References**

- [I-D.ietf-l2vpn-signaling]  
Rosen, E., "Provisioning, Autodiscovery, and Signaling in L2VPNs", [draft-ietf-l2vpn-signaling-06](#) (work in progress), September 2005.
- [I-D.ietf-pwe3-control-protocol]  
Martini, L., "Pseudowire Setup and Maintenance using the Label Distribution Protocol", [draft-ietf-pwe3-control-protocol-17](#) (work in progress), June 2005.
- [I-D.ietf-l3vpn-rfc2547bis]  
Rosen, E., "BGP/MPLS IP VPNs", [draft-ietf-l3vpn-rfc2547bis-03](#) (work in progress), October 2004.
- [RFC2279]   Yergeau, F., "UTF-8, a transformation format of ISO 10646", [RFC 2279](#), January 1998.
- [I-D.ietf-l2vpn-l2-framework]  
Andersson, L. and E. Rosen, "Framework for Layer 2 Virtual Private Networks (L2VPNs)", [draft-ietf-l2vpn-l2-framework-05](#) (work in progress),



June 2004.

[RFC2486] Aboba, B. and M. Beadles, "The Network Access Identifier",  
[RFC 2486](#), January 1999.

[RFC3140] Black, D., Brim, S., Carpenter, B., and F. Le Faucheur,  
"Per Hop Behavior Identification Codes", [RFC 3140](#),  
June 2001.

Authors' Addresses

Juha Heinanen  
TutPro Inc.  
Utsjoki  
Finland

Email: [jh@tutpro.com](mailto:jh@tutpro.com)

Greg Weber (editor)  
Cisco Systems  
10850 Murdock Road  
Knoxville, TN 37932  
US

Email: [gdweber@cisco.com](mailto:gdweber@cisco.com)

W. Mark Townsley  
Cisco Systems  
7025 Kit Creek Road  
Research Triangle Park, NC 27709  
US

Email: [mark@townsley.net](mailto:mark@townsley.net)

Skip Booth  
Cisco Systems  
7025 Kit Creek Road  
Research Triangle Park, NC 27709  
US

Email: [ebooth@cisco.com](mailto:ebooth@cisco.com)

Wei Luo  
Cisco Systems  
170 West Tasman Drive  
San Jose, CA 95134  
US

Email: [luo@cisco.com](mailto:luo@cisco.com)





## Intellectual Property Statement

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in [BCP 78](#) and [BCP 79](#).

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at [ietf-ipr@ietf.org](mailto:ietf-ipr@ietf.org).

## Disclaimer of Validity

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

## Copyright Statement

Copyright (C) The Internet Society (2005). This document is subject to the rights, licenses and restrictions contained in [BCP 78](#), and except as set forth therein, the authors retain all their rights.

## Acknowledgment

Funding for the RFC Editor function is currently provided by the Internet Society.

