

Network Working Group
Internet-Draft
Intended status: Standards Track
Expires: March 13, 2013

P. Dutta
F. Balus
Alcatel-Lucent
O. Stokes
Extreme Networks
G. Calvinac
France Telecom
September 09, 2012

LDP Extensions for Optimized MAC Address Withdrawal in H-VPLS
draft-ietf-l2vpn-vpls-ldp-mac-opt-07

Abstract

[RFC4762] describes a mechanism to remove or unlearn MAC addresses that have been dynamically learned in a VPLS Instance for faster convergence on topology change. The procedure also removes MAC addresses in the VPLS that do not require relearning due to such topology change. This document defines an enhancement to the MAC Address Withdrawal procedure with empty MAC List [RFC4762], which enables a Provider Edge(PE) device to remove only the MAC addresses that need to be relearned. Additional extensions to [RFC4762] MAC Withdrawal procedures are specified to provide optimized MAC flushing for the PBB-VPLS specified in [I-D.ietf-l2vpn-pbb-vpls-pe-model] .

Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC2119].

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on March 13, 2013.

Copyright Notice

Copyright (c) 2012 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Terminology	3
2.	Introduction	3
2.1.	MAC Flush on activation of backup spoke PW	5
2.1.1.	PE-rs initiated MAC Flush	5
2.1.2.	MTU-s initiated MAC flush	6
2.2.	MAC Flush on failure	7
2.3.	MAC Flush in PBB-VPLS	7
3.	Problem Description	7
3.1.	MAC Flush Optimization in VPLS Resiliency	7
3.1.1.	MAC Flush Optimization for regular H-VPLS	8
3.1.2.	MAC Flush Optimization for native Ethernet access	9
3.2.	Black holing issue in PBB-VPLS	10
4.	Solution Description	11
4.1.	MAC Flush Optimization for VPLS Resiliency	11
4.1.1.	MAC Flush Parameters TLV	11
4.1.2.	Application of MAC Flush TLV in Optimized MAC Flush	13
4.1.3.	MAC Flush TLV Processing Rules for Regular VPLS	13
4.1.4.	Optimized MAC Flush Procedures	14
4.2.	LDP MAC Flush Extensions for PBB-VPLS	15
4.2.1.	MAC Flush TLV Processing Rules for PBB-VPLS	16
4.2.2.	Applicability of MAC Flush Parameters TLV	18
5.	Operational Considerations	18
6.	IANA Considerations	18
7.	Security Considerations	18
8.	Contributing Authors	19
9.	Acknowledgements	19
10.	References	19
10.1.	Normative References	19
10.2.	Informative References	20
	Authors' Addresses	20

1. Terminology

This document uses the terminology defined in [\[I-D.ietf-l2vpn-pbb-vpls-pe-model\]](#), [\[RFC5036\]](#), [\[RFC4447\]](#) and [\[RFC4762\]](#).

Throughout this document VPLS means the emulated bridged LAN service offered to a customer. H-VPLS means the hierarchical connectivity or layout of MTU-s and PE-rs devices offering the VPLS [\[RFC4762\]](#).

The terms "Spoke Node" and "MTU-s" in H-VPLS are used interchangeably.

"Spoke PW" means the PW (Pseudowire) that provides connectivity between MTU-s and PE-rs nodes.

"Mesh PW" means the PW that provides connectivity between PE-rs nodes in a VPLS full mesh core.

"MAC Flush Message" means LDP Address Withdraw Message with MAC List TLV.

MAC Flush Message in the "context of a PW" means the Message that has been received over the LDP session that is used to set up the PW used to provide connectivity in VPLS. The MAC Flush Message carries the context of the PW in terms on FEC TLV associated with the PW [\[RFC4762\]](#)[\[RFC4447\]](#).

In general, "MAC Flush" means the method of initiating and processing of MAC Flush Messages across a VPLS instance.

2. Introduction

A method of Virtual Private LAN Service (VPLS), also known as Transparent LAN Service (TLS) is described in [\[RFC4762\]](#). A VPLS is created using a collection of one or more point-to-point pseudowires (PWs) [\[RFC4664\]](#) configured in a flat, full-mesh topology. The mesh topology provides a LAN segment or broadcast domain that is fully capable of learning and forwarding on Ethernet MAC addresses at the PE devices.

This VPLS full mesh core configuration can be augmented with additional non-meshed spoke nodes to provide a Hierarchical VPLS (H-VPLS) service [\[RFC4762\]](#). Throughout this document this configuration is referred to as "regular" H-VPLS.

[\[I-D.ietf-l2vpn-pbb-vpls-pe-model\]](#) describes how Provider Backbone

Bridging (PBB) can be integrated with VPLS to allow for useful PBB capabilities while continuing to avoid the use of MSTP in the backbone. The combined solution referred to as PBB-VPLS results in better scalability in terms of number of service instances, PWs and C-MAC (Customer MAC) Addresses that need to be handled in the VPLS PEs.

A MAC Address Withdrawal mechanism for VPLS is described in [RFC4762] to remove or unlearn MAC addresses for faster convergence on topology change in resilient H-VPLS topologies. Note that the H-VPLS topology in [RFC4762] describes two tier hierarchy to VPLS as the basic building block of H-VPLS, but it is possible to have multi-tier hierarchy in an H-VPLS.

The figure 1. described below is taken from [RFC4762] that describes dual-homing in H-VPLS.




Figure 1: An example of a dual-homed MTU-s

An example of usage of the MAC Flush mechanism is the dual-homed H-VPLS where an edge device termed as MTU-s is connected to two PE devices via primary spoke PW and backup spoke PW respectively. Such redundancy is designed to protect against the failure of primary

spoke PW or primary PE device. There could be multiple methods of dual homing in H-VPLS that are not described in [RFC4762]. For example, note the following statement from [section 10.2.1](#) in .

"How a spoke is designated primary or secondary is outside the scope of this document. For example, a spanning tree instance running between only the MTU-s and the two PE-rs nodes is one possible method. Another method could be configuration".

This document intends to clarify several H-VPLS dual-homing models that are deployed in practice and various use cases of LDP based MAC flush in such models.

When the MTU-s switches over to the backup PW, it is required to flush the MAC addresses learned in the corresponding VSI in peer PE devices participating in full mesh, to avoid black holing of frames to those addresses. This is accomplished by sending an LDP Address Withdraw Message with the list of MAC addresses to be removed to all other PEs over the corresponding LDP sessions [RFC4762].

In order to minimize the impact on LDP convergence time and scalability when a MAC List TLV contains a large number of MAC addresses, many implementations use a LDP Address Withdraw Message with an empty MAC List. Throughout this document the term "MAC Flush Message" is used to specify LDP Address Withdraw Message with empty MAC List described in [RFC4762] unless specified otherwise. The solutions describes in this document are applicable only to LDP Address Withdraw Message with empty MAC List.

As per the MAC Address Withdrawal processing rules in [RFC4762] a PE device on receiving a MAC flush message removes all MAC addresses associated with the specified VPLS instance (as indicated in the FEC TLV) except the MAC addresses learned over the newly activated PW. Throughout this document we use the terminology "Positive" MAC Flush or "Flush-all-but-mine" for this type of MAC Flush Message and its actions.

[2.1.](#) MAC Flush on activation of backup spoke PW

This section describes scenerios where MAC Flush withdrawal is initiated on activation of backup PW in H-VPLS.

[2.1.1.](#) PE-rs initiated MAC Flush

[RFC4762] specifies that on failure of the primary PW, it is the PE3-rs (Figure 1) that initiates MAC flush towards the core. However note that PE3-rs can initiate MAC Flush only when PE3-rs is dual homing "aware" - that is, there is some redundancy management

protocol running between MTU-s and its host PE-rs devices. The scope of this document is not specific to any dual homing protocols. One example could be BGP based multi-homing in LDP based VPLS that uses the procedures defined in [[I-D.ietf-l2vpn-vpls-multihoming](#)]. In this method of dual-homing, PE3-rs would neither forward any traffic to MTU-s neither would receive any traffic from MTU-s while PE1-rs is acting a primary (or designated forwarder).

2.1.2. MTU-s initiated MAC flush

When dual homing is achieved by manual configuration in MTU-S, the hosting PE-rs devices are dual homing "agnostic" and PE3-rs can not initiate MAC Flush message. PE3-rs can send or receive traffic over the backup PW since the dual-homing control is with MTU-s only. When the backup PW is made active by the MTU-s, it triggers MAC Flush Message. The message is sent over the LDP session associated with the newly activated PW. On receiving the MAC Flush Message from MTU-s, PE3-rs (PE-rs device with now-active PW) would flush all the MAC addresses it has learned except the ones learned over the newly activated spoke PW. PE3-rs further forwards the MAC Flush Message to all other PE devices in the core. Note that forced switchover to backup PW can be also performed at MTU-s administratively due to maintenance activities on the "erstwhile" primary spoke PW.

MTU-s initiated method of MAC flushing is modeled after Topology Change Notification (TCN) in Rapid Spanning Tree Protocol (RSTP)[[802.1w](#)]. When a bridge switches from a failed link to the backup link, the bridge sends out a TCN message over the newly activated link. The upstream bridge upon receiving this message flushes its entire MAC addresses except the ones received over this link and sends the TCN message out of its other ports in that spanning tree instance. The message is further relayed along the spanning tree by the other bridges.

The MAC Flush forwarding rules in LDP control plane strictly follow the "split-horizon" forwarding rules in H-VPLS data plane (Refer to [section 4.4 in \[RFC4762\]](#)). So a MAC Flush is forwarded in the context of mesh PW(s) when it is received in the context of a spoke PW. When a PE-rs node receives a MAC Flush in the context of a mesh PW then it is not forwarded to other mesh PWs.

Irrespective of whether a MAC Flush is initiated by a PE-rs or MTU-s, when a PE-rs device in the full-mesh of H-VPLS receives a MAC flush message it also flushes MAC addresses which are not affected due to topology change, thus leading to unnecessary flooding and relearning. This document describes the problem and a solution to optimize the MAC flush procedure in [[RFC4762](#)] so that it flushes only the set of MAC addresses that require relearning when topology changes in

H-VPLS.

2.2. MAC Flush on failure

This is a method of MAC Flush introduced by this document. In this model of dual-homing the MAC Flush is initiated by PE1-rs (Figure 1) on detection of failure of the primary spoke PW and is sent to all participating PE-rs devices in the VPLS full-mesh. It is needless to say that PE1-rs can initiate MAC flush only if PE1-rs is dual homing aware. The dual-homing protocols for this scenerio are outside the scope of this document. For example, the case of PE1-rs initiated MAC flush on failure may arise when the dual-homing segment is native ethernet as opposed to spoke PWs. In this case the PE-rs devices that receives the MAC flush from PE1-rs are required to flush all the MAC addresses learned over the PW connected to PE1-rs. This cannot be achieved with the MAC Flush Mechanism defined in [\[RFC4762\]](#). This document describes extensions to MAC Flush procedures defined in [\[RFC4762\]](#) in order to implement MAC Flush on Failure. We use the term "negative" MAC flush or "Flush-all-from-me" for this kind of flushing action as opposed to "positive" MAC Flush action in [\[RFC4762\]](#)

2.3. MAC Flush in PBB-VPLS

[I-D.ietf-l2vpn-pbb-vpls-pe-model] describes how PBB can be integrated with VPLS to allow for useful PBB capabilities while continuing to avoid the use of MSTP in the backbone. The combined solution referred to as "PBB-VPLS" results in better scalability in terms of number of service instances, PWs and C-MACs that need to be handled in the VPLS PE-rs devices. This document describes extensions to LDP MAC Flush procedures described in [\[RFC4762\]](#) required to build desirable capabilities to PBB-VPLS solution.

The solution proposed in this document is generic and is applicable when MS-PWs are used in interconnecting PE devices in H-VPLS. There could be other H-VPLS models not defined in this document where the solution may be applicable.

3. Problem Description

This document describes the problems in detail with respective to various MAC flush actions described in [section 2](#).

3.1. MAC Flush Optimization in VPLS Resiliency

This section describes the optimizations required in MAC flush procedures when H-VPLS resiliency is provided by primary and backup

spoke PWs.

3.1.1. MAC Flush Optimization for regular H-VPLS

Figure 2. describes a dual-homed H-VPLS scenario for a VPLS instance where the problem with the existing MAC flush method ([section 1.1](#)) in is explained. [[RFC4762](#)]




Figure 2: Dual homed MTU-s in two tier hierarchy H-VPLS

In Figure 2, the MTU-s is dual-homed to PE1-rs and PE2-rs. Only the primary spoke PW is active at MTU-s, thus PE1-rs is acting as the active device (designated forwarder) to reach the full mesh in the VPLS instance. The MAC addresses of nodes located at access sites (behind CE1 and CE2) are learned at PE1-rs over the primary spoke PW. Let's say X represents a set of such MAC addresses located behind CE-1. As packet flows from X to Z, PE2-rs, PE3-rs and PE4-rs learn about X on their respective mesh PWs terminating at PE1-rs. When MTU-s switches to the backup spoke PW and activates it, PE2-rs becomes the active device (designated forwarder) to reach the full mesh core. Traffic entering the H-VPLS from CE-1 and CE-2 is diverted by the MTU-s to the spoke PW to PE2-rs. Traffic destined from PE2-rs,

PE3-rs and PE4-rs to X will be blackholed till MAC address ageing timer expires (default is 5 minutes) or a packet flows from X to Z through PE2-rs. To avoid traffic blackholing the MAC addresses that have been learned in the upstream VPLS full-mesh through PE1-rs, those must be relearned or removed from the MAC FIBs in the VSIs at PE2-rs, PE3-rs and PE4-rs. If PE1-rs and PE2-rs are dual-homing agnostic then on activation of the standby PW from MTU-s, a MAC flush message will be sent by MTU-s to PE2-rs that will flush all the MAC addresses learned in the VPLS from all the other PWs but the PW connected to MTU-s.

PE2-rs further relays MAC flush messages to all other PE-rs devices in the full mesh. Same processing rule applies at all those PE-rs devices: all the MAC addresses are flushed but the ones learned on the PW connected to PE2-rs. For example, at PE3-rs all of the MAC addresses learned from the PWs connected to PE1-rs and PE4-rs are flushed and relearned subsequently. Before the relearning happens flooding of unknown destination MAC addresses takes place throughout the network. As the number of PE-rs devices in the full-mesh increases, the number of unaffected MAC addresses flushed in a VPLS instance also increases, thus leading to unnecessary flooding and relearning. With large number of VPLS instances provisioned in the H-VPLS network topology the amount of unnecessary flooding and relearning increases. An optimization is required that will flush only the MAC addresses learned from the respective PWs between PE1-rs and other PE devices in the full-mesh in order to minimize the relearning and flooding in the network. In the above case, only the MAC addresses in set X and Y needs to be flushed across the core.

The same case is applicable when PE1-rs and PE2-rs are dual homing aware and participates in a designated forwarder election. When PE2-rs becomes the active device for MTU-s then PE2-rs may initiate MAC flush towards the core. The receiving action of the MAC Flush in other PE-rs devices is same as in MTU-s initiated MAC Flush.

3.1.2. MAC Flush Optimization for native Ethernet access

The analysis in [section 2.1.1](#) applies also to the native Ethernet access into a VPLS. In such a scenerio one active and one or more standby endpoints terminate into two or more VPLS or H-VPLS PE-rs devices. Example of these kind of access are ITU-T G.8032 access rings or any proprietary multi-chassis LAG emulations. Upon failure of the active native Ethernet endpoint on PE1-rs, an optimized MAC flush is required to be initiated by PE1-rs to ensure that on PE2-rs, PE3-rs and PE4-rs only the MAC addresses learned from the respective PWs connected to PE1-rs are being flushed.

3.2. Black holing issue in PBB-VPLS

In PBB-VPLS solution a B-component VPLS (B-VPLS) may be used as infrastructure to support one or more I-component instances. B-VPLS control plane (LDP Signaling) replaces I-component control plane throughout the MPLS core. This is raising an additional challenge related to black hole avoidance in the I-component domain as described in this section. Figure 3 describes the case of a CE device (node A) dual-homed to two I-component instances located on two PBB-VPLS PEs (PE1-rs and PE2-rs).

IP/MPLS Core




Figure 3: PBB Black holing Issue - CE Dual-Homing use case

The link between PE1-rs and CE-A is active (marked with A) while the link between CE-A and PE2-rs is in Standby/Blocked status. In the network diagram CMAC X is one of the MAC addresses located behind CE-A in the customer domain, CMAC Y is behind CE-B and the B-VPLS instances on PE1-rs are associated with "Backbone" MAC (BMAC) B1 and PE2-rs with BMAC B2.

As the packets flow from CMAC X to CMAC Y through PE1-rs with BMAC B1, the remote PE-rs devices participating in the I-VPLS (for example, PE3-rs) will learn the CMAC X associated with BMAC B1 on PE1-rs. Under failure of the link between CE-A and PE1-rs and on activation of link to PE2-rs, the remote PE-rs devices (for example, PE3-rs) will black-hole the traffic destined for customer MAC X to BMAC B1 until the aging timer expires or a packet flows from X to Y through the PE B2. This may take a long time (default aging timer is 5 minutes) and may affect a large number of flows across multiple I-components.

A possible solution to this issue is to use the existing LDP MAC Flush as specified in [[RFC4762](#)] to flush the BMAC associated with the PE-rs in the B-VPLS domain where the failure occurred. This will

automatically flush the CMAC to BMAC association in the remote PE-rs devices. This solution though has the disadvantage of producing a lot of unnecessary MAC flush in the B-VPLS domain as there was no failure or topology change affecting the Backbone domain.

A better solution is required to propagate the I-component events through the backbone infrastructure (B-VPLS) in order to flush only the CMAC to BMAC associations in the remote PBB-VPLS capable PE-rs devices. As there are no I-VPLS control plane exchanges across the PBB backbone, extensions to B-VPLS control plane are required to propagate the I-component MAC Flush events across the B-VPLS.

4. Solution Description

This section describes the solution for the requirements described in [section 3](#).

4.1. MAC Flush Optimization for VPLS Resiliency

The basic principle of the optimized MAC flush mechanism is explained with reference to Figure 2. The optimization is achieved by initiating MAC Flush on failure as described in [section 1.2](#)

PE1-rs would initiate MAC Flush towards the core on detection of failure of primary spoke PW between MTU-S and PE1-rs (or status change from active to standby [[I-D.ietf-pwe3-redundancy](#)]). This method is referred as "MAC Flush on Failure" throughout this document. The MAC Flush message would indicate to receiving PE-rs devices to flush all MACs learned over the PW in the context of the VPLS over which the MAC flush message is received. Each PE-rs device in the full mesh that receives the message identifies the VPLS instance and its respective PW that terminates in PE1-rs from the FEC TLV received in the message. Thus the PE-rs device flushes only the MAC addresses learned from that PW connected to PE1-rs, minimizing the required relearning and the flooding throughout the VPLS domain.

This section defines a generic MAC Flush Parameters TLV for LDP [[RFC5036](#)]. Through out this document the MAC Flush Parameters TLV is referred as MAC Flush TLV. A MAC Flush TLV carries information on the desired action at the PE-rs device receiving the message and is used for optimized MAC flushing in VPLS. The MAC Flush TLV can also be used for [[RFC4762](#)] style of MAC Flush as explained in [section 2.1](#).

4.1.1. MAC Flush Parameters TLV

The MAC Flush Parameters TLV is described as below:


```

0               1               2               3
0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|1|1| MAC Flush Params TLV(TBD) |                Length                |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|      Flags      | Sub-TLV Type |      Sub-TLV Length      |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|                                Sub-TLV Variable Length Value          |
|                                "                                       |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+

```

The U and F bits are set to forward if unknown so that potential intermediate VPLS PE-rs devices unaware of the new TLV can just propagate it transparently. The MAC Flush Parameters TLV type is to be assigned by IANA. The encoding of the TLV follows the standard LDP TLV encoding in [[RFC5036](#)]

The TLV value field contains a one byte Flag field used as described below. Further the TLV value may carry one or more sub-TLVs. Any sub-TLV definition to the above TLV MUST address the actions in combination with other existing sub-TLVs.

The detailed format for the Flags bit vector is described below:

```

0 1 2 3 4 5 6 7
+---+---+---+---+---+---+---+
|C|N|    MBZ    | (MBZ = MUST Be Zero)
+---+---+---+---+---+---+---+

```

1 Byte Flag field is mandatory. The following flags are defined:

C flag, used to indicate the context of the PBB-VPLS component in which MAC flush is required. For PBB-VPLS there are two contexts of MAC flushing - The Backbone VPLS (B-component VPLS) and Customer VPLS (I-component VPLS). C flag MUST be ZERO (C=0) when a MAC Flush for the B-VPLS is required. C flag MUST be set (C=1) when the MAC Flush for I-VPLS is required. In the regular H-VPLS case the C flag must be ZERO (C=0) to indicate the flush applies to the current VPLS context.

N flag, used to indicate whether a positive (N=0, Flush-all-but-mine) or negative (N=1 Flush-all-from-me) MAC Flush is required. The source (mine/me) is defined either as the PW associated with the LDP session on which the LDP MAC Withdraw was received or with the BMAC(s) listed in the BMAC Sub-TLV. For the optimized MAC Flush procedure described in this section the flag must be set (N=1).

Detailed usage in the context of PBB-VPLS is explained in section

3.2.

MBZ flags, the rest of the flags should be set to zero on transmission and ignored on reception.

The MAC Flush TLV SHOULD be placed after the existing TLVs in MAC Flush message in [\[RFC4762\]](#).

4.1.2. Application of MAC Flush TLV in Optimized MAC Flush

For optimized MAC flush, the MAC Flush TLV MAY be sent as in existing LDP Address Withdraw Message with empty MAC List but from the core PE-rs on detection of failure of its local/primary spoke PW. The N bit in TLV MUST be set to 1 to indicate Flush-all-from-me. If the optimized MAC Flush procedure is used in a Backbone VPLS or regular VPLS/H-VPLS context the C bit must be ZERO (C=0). If it is used in an I-VPLS context the C bit must be set (C= 1). See [section 3.2](#) for details of its usage in PBB-VPLS context.

Note that if MAC Flush TLV is not understood by a receiver (i.e. a legacy PE-rs then it may result in undesired action. For example if a MAC Flush Parameters TLV is received with N=1 and receiver does not understand that TLV then it would result in flushing of all MACs learned in the VSI except the ones learned over the PW (positive MAC Flushing action).

To emulate the MAC flush initiation procedures defined in [\[RFC4762\]](#), MTU-s or PE2-rs MAY send MAC Flush TLV as an OPTIONAL TLV in the MAC Flush Message with N = 0. This would result in same flushing action at receiving PE-rs devices.

4.1.3. MAC Flush TLV Processing Rules for Regular VPLS

This section describes the processing rules of MAC Flush TLV that SHOULD be followed in the context of MAC flush procedures in VPLS.

For optimized MAC Flush a multi-homing PE-rs initiates MAC flush message towards the other related VPLS PE-rs devices when it detects a transition (failure or to standby) in its active spoke PW. In such case the MAC Flush TLV MUST be sent with N= 1. A PE-rs device receiving the MAC Flush TLV SHOULD follow the same processing rules as described in this section.

Note that if MS-PW is used in VPLS then a MAC flush message is processed only at the T-PE nodes since S-PE(s) traversed by the MS-PW propagate MAC flush messages without any action. In this section, a PE-rsdevice signifies only T-PE in MS-PW case unless specified otherwise.

When a PE-rs device receives a MAC Flush TLV with $N = 1$, it SHOULD flush all the MAC addresses learned from the PW in the VPLS in the context on which the MAC Flush message is received.

If a MAC Flush TLV is received with $N = 0$ in the MAC flush message then the receiving PE-rs SHOULD flush the MAC addresses learned from all PWs in the VPLS instance except the ones learned over the PW on which the message is received.

If a PE-rs device receives a MAC flush with the MAC Flush TLV option and a valid MAC address list, it SHOULD ignore the option and deal with MAC addresses explicitly as per [RFC4762].

If a PE-rs device that doesn't support MAC Flush TLV receives a MAC flush message with this option, it MUST ignore the option and follow the processing rules as per [RFC4762]. However if MAC Flush Parameters TLV was sent with $N = 1$ then it may result in wrong flushing action (Positive MAC Flush).

4.1.4. Optimized MAC Flush Procedures

This section explains the optimized MAC flush procedure in the scenario in Figure 2. When the primary spoke PW transition (failure or standby transition) is detected by PE1-rs, it may send MAC flush messages to PE2-rs, PE3-rs and PE4-rs with MAC Flush TLV and $N = 1$. Upon receipt of the MAC flush message, PE2-rs identifies the VPLS instance that requires MAC flush from the FEC element in the FEC TLV. On receiving $N=1$, PE-2 removes all MAC addresses learned from that PW over which the message is received. Same action is followed by PE3-rs and PE4-rs.

Figure 4 shows another redundant H-VPLS topology to protect against failure of MTU-s device. Provider RSTP may be used as selection algorithm for active and backup PWs in order to maintain the connectivity between MTU devices and PE-rs devices at the edge. It is assumed that PE-rs devices can detect failure on PWs in either direction through OAM mechanisms such as VCCV procedures for instance.




Figure 4: Redundancy with Provider RSTP

MTU-1, MTU-2, PE1-rs and PE2-rs participate in provider RSTP. By configuration in RSTP it is ensured that the PW between MTU-1 and PE1-rs is active and the PW between MTU-2 and PE2-rs is blocked (made backup) at MTU-2 end. When the active PW failure is detected by RSTP, it activates the PW between MTU-2 and PE2-rs. When PE1-rs detects the failing PW to MTU-1, it may trigger MAC flush into the full mesh with MAC Flush TLV that carries N=1. Other PE-rs devices in the full mesh that receive the MAC flush message identify their respective PWs terminating on PE1-rs and flush all the MAC addresses learned from it.

[RFC4762] describes multi-domain VPLS service where fully meshed VPLS networks (domains) are connected together by a single spoke PW per VPLS service between the VPLS "border" PE-rs devices. To provide redundancy against failure of the inter-domain spoke, full mesh of inter-domain spokes can be setup between border PE-rs devices and provider RSTP may be used for selection of the active inter-domain spoke. In case of inter-domain spoke PW failure, PE-rs initiated MAC withdrawal may be used for optimized MAC flushing within individual domains.

Further, the procedures are applicable with any native Ethernet access topologies multi-homed to two or more VPLS PE-rs devices. The text in [section 3.1](#) applies for the native Ethernet case where active/standby PWs are replaced with the active/standby Ethernet endpoints. An optimized MAC Flush message can be generated by the VPLS PE-rs that detects the failure in the primary Ethernet access.

[4.2.](#) LDP MAC Flush Extensions for PBB-VPLS

The use of Address Withdraw message with MAC List TLV is proposed in [\[RFC4762\]](#) as a way to expedite removal of MAC addresses as the result of a topology change (e.g. failure of a primary link of a VPLS PE-rs device and implicitly the activation of an alternate link in a dual-homing use case). These existing procedures apply individually to B-VPLS and I-component domains.

When it comes to reflecting topology changes in access networks connected to I-component across the B-VPLS domain certain additions should be considered as described below.

MAC Switching in PBB is based on the mapping of Customer MACs (CMACs) to Backbone MAC(s) (BMACs). A topology change in the access (I-domain) should just invoke the flushing of CMAC entries in PBB PEs' FIB(s) associated with the I-component(s) impacted by the failure. There is a need to indicate the PBB PE (BMAC source) that originated the MAC Flush message to selectively flush only the MACs that are affected.

These goals can be achieved by including the MAC Flush Parameters TLV in the LDP Address Withdraw message to indicate the particular domain(s) requiring MAC flush. On the other end, the receiving PEs may use the information from the new TLV to flush only the related FIB entry/entries in the I-component instance(s).

At least one of the following sub-TLVs MUST be included in the MAC Flush Parameters TLV if the C-flag is set to 1:

- PBB BMAC List Sub-TLV:

Type: 0x01

Length: value length in octets. At least one BMAC address must be present in the list.

Value: one or a list of 48 bits BMAC addresses. These are the source BMAC addresses associated with the B-VPLS instance that originated the MAC Withdraw message. It will be used to identify the CMAC(s) mapped to the BMAC(s) listed in the sub-TLV.

- PBB ISID List Sub-TLV:

Type: 0x02,

Length: value length in octets. Zero indicates an empty ISID list. An empty ISID list means that the flush applies to all the ISIDs mapped to the B-VPLS indicated by the FEC TLV.

Value: one or a list of 24 bits ISIDs that represent the I-component FIB(s) where the MAC Flush needs to take place.

4.2.1. MAC Flush TLV Processing Rules for PBB-VPLS

The following steps describe the details of the processing rules for MAC Flush TLV in the context of PBB-VPLS:

- The MAC Flush Message, including the MAC Flush Parameters TLV is initiated by the PBB PE(s) experiencing a Topology Change event in one or multiple customer I-component(s).
- The flags are set accordingly to indicate the type of MAC Flush required for this event: N=0 (Flush-all-but-mine), C=1 (Flush only CMAC FIBs).
- The PBB Sub-TLVs (BMAC and ISID Lists) are included according to the context of topology change.
- On reception of the MAC Flush message, the B-VPLS instances corresponding to the FEC TLV in the message must interpret the content of MAC Flush Parameters TLV. If the C-bit is set to 1 then Backbone Core Bridges (BCB) in the PBB-VPLS SHOULD NOT flush their BMAC FIBs. The B-VPLS control plane SHOULD propagate the MAC Flush following the split-horizon grouping and the established B-VPLS topology.
- The usage and processing rules of MAC Flush Parameters TLV in the context of Backbone Edge Bridges (BEB) is as follows:
 - The PBB ISID List is used to determine the particular ISID FIBs (I-VPLS) that need to be considered for flushing action. If the PBB ISID List sub-tlv is not included in a received message then all the ISID FIBs associated with the receiving B-VPLS SHOULD be considered for flushing action.
 - The PBB BMAC List is used to identify from the ISID FIBs in the previous step to selectively flush BMAC to CMAC associations depending on the N flag specified below. If PBB BMAC List Sub-TLV is not included in a received message then all BMAC to CMAC association in all ISID FIBs (I-VPLS) as specified by the ISID List are considered for required flushing action, again depending on the N flag specified below.
- Next, depending on the N flag value the following actions apply:
 - N=0, all the CMACs in the selected ISID FIBs SHOULD be flushed with the exception of the resulted CMAC list from the BMAC List mentioned in the message. ("Flush all but the CMACs associated with the BMAC(s) in the BMAC List Sub-TLV from the FIBs associated with the ISID list").
 - N=1, all the resulted CMACs SHOULD be flushed ("Flush all the CMACs associated with the BMAC(s) in the BMAC List Sub-TLV from the FIBs associated with the ISID list").

4.2.2. Applicability of MAC Flush Parameters TLV

If MAC Flush Parameters TLV is received by a BEB in a PBB-VPLS that does not understand the TLV then it may result in undesirable MAC flushing action. It is RECOMMENDED that all PE-rs devices participating in PBB-VPLS support MAC Flush Parameters TLV.

The MAC Flush Parameters TLV is also applicable to regular VPLS context as well as explained in [section 3.1](#) . To achieve negative MAC Flush (flush-all-from-me) in regular VPLS context, the MAC Flush Parameters TLV SHOULD be encoded with C=0 and N = 1 without inclusion of any Sub-TLVs. Negative MAC flush is highly desirable in scenarios when VPLS access redundancy is provided by Ethernet Ring Protection as specified in ITU-T G.8032 specification etc.

5. Operational Considerations

As mentioned before, if MAC Flush Parameters TLV is not understood by a receiver then it may result in undesired flushing action. An LDP based capability negotiation mechanism may be defined to negotiate support of various MAC Flushing capability between PE-rs devices in a VPLS instance. This is a subject of future study.

In a VPLS instance it is possible that some PE-s devices does not support the solutions defined in this document. From operational standpoint, it is RECOMMENDED that implementations of the solution provide administrative control to selectively desired MAC Flushing action towards a PE-rs device in the VPLS. Thus in the topology figure 2. it is possible that PE1-rs would initiate optimized MAC Flush towards the PE-rs devices that supports the solution , whereas PE2-rs would initiate [[RFC4762](#)] style of MAC Flush towards the PE-rs devices that does not support the optimized solution.

6. IANA Considerations

This document requests code point for following LDP TLV:

- MAC Flush Parameters TLV.

7. Security Considerations

Control plane aspects:

- LDP security (authentication) methods as described in [[RFC5036](#)] is applicable here. Further this document implements security

considerations as in [[RFC4447](#)] and [[RFC4762](#)].

Data plane aspects:

- This specification does not have any impact on the VPLS forwarding plane.

8. Contributing Authors

The authors would like to thank Marc Lasserre and Don Fedyk who made a major contribution to the development of this document.

Marc Lasserre
Alcatel-Lucent

Email: marc.lasserre@alcatel-lucent.com

Don Fedyk
Alcatel-Lucent
Groton, MA 01450 USA

Email: Donald.Fedyk@alcatel-lucent.com

9. Acknowledgements

The authors would like to thank the following people who have provided valuable comments and feedback on the topics discussed in this document: Dimitri Papadimitriou, Jorge Rabadan, Prashanth Ishwar, Vipin Jain, John Rigby, Ali Sajassi, Wim Henderickx, Paul Kwok, Jorge Rabadan, Maarten Vissers, Daniel Cohn, Nabil Bitar and Giles Heron.

10. References

10.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC4447] Martini, L., Rosen, E., El-Aawar, N., Smith, T., and G. Heron, "Pseudowire Setup and Maintenance Using the Label Distribution Protocol (LDP)", [RFC 4447](#), April 2006.

- [RFC4762] Lasserre, M. and V. Kompella, "Virtual Private LAN Service (VPLS) Using Label Distribution Protocol (LDP) Signaling", [RFC 4762](#), January 2007.
- [RFC5036] Andersson, L., Minei, I., and B. Thomas, "LDP Specification", [RFC 5036](#), October 2007.

10.2. Informative References

- [I-D.ietf-l2vpn-pbb-vpls-pe-model]
Balus, F., Bocci, M., Sajassi, A., Bitar, N., and R. Zhang, "Extensions to VPLS PE model for Provider Backbone Bridging", [draft-ietf-l2vpn-pbb-vpls-pe-model-05](#) (work in progress), August 2012.
- [I-D.ietf-l2vpn-vpls-multihoming]
Kothari, B., Kompella, K., Henderickx, W., Balus, F., and J. Uttaro, "BGP based Multi-homing in Virtual Private LAN Service", [draft-ietf-l2vpn-vpls-multihoming-03](#) (work in progress), July 2011.
- [I-D.ietf-pwe3-redundancy]
Muley, P., Aissaoui, M., and M. Bocci, "Pseudowire Redundancy", [draft-ietf-pwe3-redundancy-09](#) (work in progress), June 2012.
- [RFC4664] Andersson, L. and E. Rosen, "Framework for Layer 2 Virtual Private Networks (L2VPNs)", [RFC 4664](#), September 2006.
- [802.1w] "IEEE Standard for Local and metropolitan area networks. Common specifications Part 3: Media Access Control (MAC) Bridges. Amendment 2: Rapid Reconfiguration", IEEE Std 802.1w-2001.
- [G.8032] "Ethernet ring protection switching", ITU-T G.8032.

Authors' Addresses

Pranjal Kumar Dutta
Alcatel-Lucent
701 E Middlefield Road
Mountain View, California 94043
USA

Email: pranjal.dutta@alcatel-lucent.com

Florin Balus
Alcatel-Lucent
701 E Middlefield Road
Mountain View, California 94043
USA

Email: florin.balus@alcatel-lucent.com

Olen Stokes
Extreme Networks
PO Box 14129, RTP
Raleigh, North Carolina 27709
USA

Email: ostokes@extremenetworks.com

Geraldine Calvinac
France Telecom
2, avenue Pierre-Marzin
Lannion Cedex, 22307
France

Email: geraldine.calvignac@orange-ftgroup.com