

Network Working Group  
Internet-Draft  
Intended status: Standards Track  
Expires: December 26, 2015

J. Uttaro  
ATT  
P. Mohapatra  
Sproute Networks  
D. Smith  
Cisco Systems  
R. Raszuk  
Mirantis Inc.  
J. Scudder  
Juniper Networks  
June 24, 2015

**BGP ACCEPT\_OWN Community Attribute**  
**draft-ietf-l3vpn-acceptown-community-10.txt**

Abstract

Under certain conditions it is desirable for a Border Gateway Protocol (BGP) route reflector to be able to modify the Route Target (RT) list of a Virtual Private Network (VPN) route that the route reflector distributes, enabling the route reflector to control how a route originated within one Virtual Routing and Forwarding (VRF) is imported into other VRFs. This technique works effectively as long as the VRF that exports the route is not on the same Provider Edge (PE) router than the VRF(s) that import the route. However, due to the constraints of the BGP protocol, it does not work if the two are on the same PE. This document describes a modification to the BGP protocol allowing this technique to work when the VRFs are on the same PE, and to be used in a standard manner throughout an autonomous system.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on December 26, 2015.

## Copyright Notice

Copyright (c) 2015 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

<a href="#">1.</a>	Introduction . . . . .	<a href="#">2</a>
<a href="#">1.1.</a>	Requirements Language . . . . .	<a href="#">3</a>
<a href="#">2.</a>	ACCEPT_OWN Community . . . . .	<a href="#">3</a>
<a href="#">2.1.</a>	Route Acceptance . . . . .	<a href="#">3</a>
<a href="#">2.2.</a>	Propagating ACCEPT_OWN Between Address Families . . . . .	<a href="#">4</a>
<a href="#">2.3.</a>	Configuration Control . . . . .	<a href="#">4</a>
<a href="#">3.</a>	Decision Process . . . . .	<a href="#">4</a>
<a href="#">4.</a>	Deployment Considerations . . . . .	<a href="#">5</a>
<a href="#">5.</a>	Other Applications . . . . .	<a href="#">5</a>
<a href="#">6.</a>	Security Considerations . . . . .	<a href="#">5</a>
<a href="#">7.</a>	IANA Considerations . . . . .	<a href="#">5</a>
<a href="#">8.</a>	Acknowledgments . . . . .	<a href="#">5</a>
<a href="#">9.</a>	Normative References . . . . .	<a href="#">6</a>
<a href="#">Appendix A.</a>	Local Extranet Application (non-normative) . . . . .	<a href="#">6</a>
	Authors' Addresses . . . . .	<a href="#">7</a>

## [1.](#) Introduction

In certain scenarios, a BGP speaker may maintain multiple VRFs [[RFC4364](#)]. Under certain conditions, it is desirable for a route reflector to be able to modify the RT list of a VPN route that the route reflector distributes, enabling the route reflector to control how a route originated within one VRF is imported into other VRFs. Though it is possible to perform such policy control directly on the originator, it may be operationally cumbersome in an autonomous system with a large number of border routers having complex BGP policies.

The technique of the route reflector modifying the RT list works effectively as long as the VRF that exports the route is not on the same PE as the VRF(s) that import the route. However, due to the



constraints of the BGP protocol, it does not work if the two are on the same PE. This is because per the BGP specification [[RFC4271](#)], a BGP speaker rejects prefix advertisements received that were originated by itself. In an autonomous system with route reflectors, the route reflector attaches the ORIGINATOR\_ID attribute to the UPDATE messages so that if such prefix advertisements reach the originator, the originator can reject them by simply checking the ORIGINATOR\_ID attribute. The BGP specification also mandates that a route should not be accepted from a peer when the NEXT\_HOP attribute matches the receiver's own "IP address".

This document proposes a modification to BGP's behavior by defining a new community [[RFC1997](#)] value, in order to allow the technique of RT list modification by the route reflector to be used in a standard manner throughout an autonomous system, irrespective of whether the VRFs are on the same, or different PEs.

### **[1.1.](#) Requirements Language**

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

## **[2.](#) ACCEPT\_OWN Community**

This memo defines a new well-known BGP community from the First Come First Served range, ACCEPT\_OWN, whose value as assigned by IANA is 0xFFFF0001. Processing of the ACCEPT\_OWN community SHOULD be controlled by configuration. The functionality SHOULD default to being disabled, as further specified in [Section 2.3](#).

### **[2.1.](#) Route Acceptance**

A router MAY accept a route whose ORIGINATOR\_ID or NEXT\_HOP value matches that of the receiving speaker if all of the following are true:

- o Processing of the ACCEPT\_OWN community is enabled by configuration.
- o The route in question carries the ACCEPT\_OWN community.
- o The route in question was originated from a source VRF on the router. The source VRF is a VRF on the router whose configured Route Distinguisher is equal to the Route Distinguisher carried in the route.



- o The route in question is targeted to one or more destination VRFs on the router (as determined by inspecting the Route Target(s)).
- o At least one destination VRF is different from the source VRF.

A route MUST NOT ever be accepted back into its source VRF, even if it carries one or more RTs which match that VRF.

## **2.2. Propagating ACCEPT\_OWN Between Address Families**

The ACCEPT\_OWN community controls propagation of routes which can be associated with a source VRF by inspection of their Route Distinguisher and with a target VRF by inspection of their Route Target list (for example VPN routes with a SAFI of 128). As such, it SHOULD NOT be attached to any routes which cannot be associated with a source VRF. This implies that when propagating routes into a VRF, the ACCEPT\_OWN community SHOULD NOT be propagated. Likewise, if a route carrying the ACCEPT\_OWN community is received in an address family which does not allow the source VRF to be looked up, the ACCEPT\_OWN community MUST be discarded. An OPTIONAL message may be logged in this case.

## **2.3. Configuration Control**

ACCEPT\_OWN handling SHOULD be controlled by configuration, and if controlled by configuration, it MUST default to being disabled. When ACCEPT\_OWN is disabled by configuration (either explicitly or by default), the router MUST NOT apply the special route acceptance rules detailed in [Section 2.1](#). The router SHOULD still apply the propagation rules detailed in [Section 2.2](#).

## **3. Decision Process**

If a BGP speaker supports ACCEPT\_OWN and is configured for the extensions defined in this document, the following step is inserted after the LOCAL\_PREF comparison step in BGP decision process:

When comparing a pair of routes for a BGP destination, the route attached with ACCEPT\_OWN community is preferred over the route that does not have the community.

In all other respects, the decision process remains unchanged. This extra step MUST only be invoked during the best path selection process of VPN-IP routes [[RFC4364](#)] (i.e., it MUST NOT be invoked for the best path selection of "imported" IP routes in a VRF). The purpose of the extra step is to allow the paths advertised by the route reflector with ACCEPT\_OWN community to be selected as best over



other paths that the BGP speaker may have received, hence enabling the applications ACCEPT\_OWN is designed for.

#### **4. Deployment Considerations**

The ACCEPT\_OWN community as described in this document is useful within a single autonomous system which uses a single layer of route reflectors. Its use with hierarchical route reflectors would require further specification and is out of scope for this document. Likewise, its use across multiple autonomous systems is out of scope for this document.

#### **5. Other Applications**

This approach may also be relevant to other scenarios where a BGP speaker maintains multiple routing contexts using an approach different from that of [\[RFC4364\]](#), as long as the specific approach in use has the property that the BGP speaker originates and receives routes within a particular context. In such a case, "VRF" in this document should be understood to mean whatever construct provides a routing context in the specific technology under consideration. Likewise, "Route Distinguisher" should be understood to mean whatever construct allows a route's originator to associate that route with its source context, and "Route Target" should be understood to mean whatever construct allows a route to be targeted for import into a context other than its source.

#### **6. Security Considerations**

ACCEPT\_OWN as described above permits a router's own route prefix to be advertised to a different VRF on that router. In this respect, such a route is similar to any other BGP route and shares the same set of security vulnerabilities and concerns. This extension does not change the underlying security issues inherent in BGP VPN [\[RFC4364\]](#).

#### **7. IANA Considerations**

IANA has assigned the value 0xFFFF0001 from BGP well-known communities registry for ACCEPT\_OWN community. No additional IANA action is required.

#### **8. Acknowledgments**

The authors would like to thank Yakov Rekhter, Jim Guichard, Clarence Filsfils, John Mullooly, Jeff Haas, Pranav Mehta, and Tamas Mondal for their valuable comments and suggestions. The decision process





changes were suggested by Pranav Mehta to solve the remote extranet problem.

## 9. Normative References

- [RFC1997] Chandrasekeran, R., Traina, P., and T. Li, "BGP Communities Attribute", [RFC 1997](#), August 1996.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC4271] Rekhter, Y., Li, T., and S. Hares, "A Border Gateway Protocol 4 (BGP-4)", [RFC 4271](#), January 2006.
- [RFC4364] Rosen, E. and Y. Rekhter, "BGP/MPLS IP Virtual Private Networks (VPNs)", [RFC 4364](#), February 2006.

## [Appendix A](#). Local Extranet Application (non-normative)

One of the applications for this behavior is auto-configuration of extranets within MPLS VPN networks. Consider the following topology:




Figure 1: Extranet Application

Within the above topology, PE1 receives a prefix X from CE1. Prefix X is installed in VRF 1 and is advertised to the route reflector with route distinguisher (RD) 1 and route target (RT) 1 as configured on PE1. The requirement is to import prefix X into VRF 2 and advertise it to CE2 in support of extranet VPN connectivity between CE1/VRF1 and CE2/VRF2. Current BGP mechanisms for MPLS VPNs[RFC4364] require changing the import RT value and/or import policy for VRF 2 on PE1. This is operationally cumbersome in a network with a large number of border routers having complex BGP policies.

Alternatively, using the new ACCEPT\_OWN community value, the route reflector can simply re-advertise prefix X back to PE1 with RT 2 appended. In this way, PE1 will accept prefix X despite its ORIGINATOR\_ID or NEXT\_HOP value, import it into VRF 2 as a result of RT 2, and will then determine the correct adjacency rewrite within



VRF 1 based on the RD value (1) and the prefix. Note that the RT 1 value originally attached to the route will simply be ignored since associated with the source VRF 1. The same operation needs also to happen in the reverse direction (VRF 1 learning a route from VRF 2) to achieve establishment of an extranet VPN strictly via the route reflector without changing the BGP policy of PE1 in any way.

A router performing such an extranet application can accept a route with its own ORIGINATOR\_ID or NEXT\_HOP value only if the VRF in which the router originated the route is different than the VRF in which the router accepts the re-advertised route.

#### Authors' Addresses

James Uttaro  
ATT  
200 S. Laurel Avenue  
Middletown, NJ 07748  
USA

Email: [uttaro@att.com](mailto:uttaro@att.com)

Pradosh Mohapatra  
Sproute Networks

Email: [mpradosh@yahoo.com](mailto:mpradosh@yahoo.com)

David J. Smith  
Cisco Systems  
111 Wood Avenue South  
Iselin, NJ 08830  
USA

Email: [djsmith@cisco.com](mailto:djsmith@cisco.com)

Robert Raszuk  
Mirantis Inc.  
615 National Ave. #100  
Mt View, CA 94043  
USA

Email: [robert@raszuk.net](mailto:robert@raszuk.net)



John Scudder  
Juniper Networks  
1194 N. Mathilda Ave  
Sunnyvale, CA 94089  
USA

Email: [jgs@juniper.net](mailto:jgs@juniper.net)