

Network Working Group  
Internet-Draft  
Expires: March 11, 2005

L. Andersson  
T. Madsen  
Acreo AB  
September 10, 2004

**Provider Provisioned VPN terminology  
draft-ietf-l3vpn-ppvpn-terminology-04.txt**

Status of this Memo

This document is an Internet-Draft and is subject to all provisions of [section 3 of RFC 3667](#). By submitting this Internet-Draft, each author represents that any applicable patent or other IPR claims of which he or she is aware have been or will be disclosed, and any of which he or she become aware will be disclosed, in accordance with [RFC 3668](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/1id-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on March 11, 2005.

Copyright Notice

Copyright (C) The Internet Society (2004).

Abstract

The wide spread interest in provider-provisioned VPN solutions lead to memos proposing different and overlapping solutions. The IETF working groups, first Provider Provisioned VPNs and later Layer 2 VPNs and Layer 3 VPNs, have been discussed these proposals and documented specifications. This has lead to the development of a partly new set of concepts used to describe the set of VPN services. To a certain extent there is more than one term covering the same

concept and sometimes the same term covers more than one concept.  
This document seeks to fill the need to make the terminology in the  
area clearer and more intuitive.

## Table of Contents

<a href="#">1.</a>	<a href="#">Introduction . . . . .</a>	<a href="#">4</a>
<a href="#">2.</a>	<a href="#">PPVPN Terminology . . . . .</a>	<a href="#">5</a>
<a href="#">3.</a>	<a href="#">Provider Provisioned Virtual Private Network services . . . . .</a>	<a href="#">6</a>
<a href="#">3.1</a>	<a href="#">Layer 3 VPN (L3VPN) . . . . .</a>	<a href="#">6</a>
<a href="#">3.2</a>	<a href="#">Layer 2 VPN (L2VPN) . . . . .</a>	<a href="#">6</a>
<a href="#">3.3</a>	<a href="#">Virtual Private LAN Service (VPLS) . . . . .</a>	<a href="#">6</a>
<a href="#">3.4</a>	<a href="#">Virtual Private Wire Service (VPWS) . . . . .</a>	<a href="#">6</a>
<a href="#">3.5</a>	<a href="#">IP-only LAN-like Service (IPLS) . . . . .</a>	<a href="#">7</a>
<a href="#">3.6</a>	<a href="#">Pseudo Wire (PW) . . . . .</a>	<a href="#">7</a>
<a href="#">3.7</a>	<a href="#">Transparent LAN Service (TLS) . . . . .</a>	<a href="#">8</a>
<a href="#">3.8</a>	<a href="#">Virtual LAN (VLAN) . . . . .</a>	<a href="#">8</a>
<a href="#">3.9</a>	<a href="#">Virtual Leased Line Service (VLLS) . . . . .</a>	<a href="#">8</a>
<a href="#">3.10</a>	<a href="#">Virtual Private Network (VPN) . . . . .</a>	<a href="#">8</a>
<a href="#">3.11</a>	<a href="#">Virtual Private Switched Network (VPSN) . . . . .</a>	<a href="#">8</a>
<a href="#">4.</a>	<a href="#">Classification of VPNs . . . . .</a>	<a href="#">9</a>
<a href="#">5.</a>	<a href="#">Building blocks . . . . .</a>	<a href="#">11</a>
<a href="#">5.1</a>	<a href="#">Customer Edge device (CE) . . . . .</a>	<a href="#">11</a>
<a href="#">5.1.1</a>	<a href="#">Device based CE naming . . . . .</a>	<a href="#">11</a>
<a href="#">5.1.2</a>	<a href="#">Service based CE naming . . . . .</a>	<a href="#">12</a>
<a href="#">5.2</a>	<a href="#">Provider Edge (PE) . . . . .</a>	<a href="#">12</a>
<a href="#">5.2.1</a>	<a href="#">Device based PE naming . . . . .</a>	<a href="#">13</a>
<a href="#">5.2.2</a>	<a href="#">Service based PE naming . . . . .</a>	<a href="#">13</a>
<a href="#">5.2.3</a>	<a href="#">Distribution based PE naming . . . . .</a>	<a href="#">13</a>
<a href="#">5.3</a>	<a href="#">Core . . . . .</a>	<a href="#">14</a>
<a href="#">5.3.1</a>	<a href="#">Provider router (P) . . . . .</a>	<a href="#">14</a>
<a href="#">5.4</a>	<a href="#">Naming in specific Internet drafts . . . . .</a>	<a href="#">14</a>
<a href="#">5.4.1</a>	<a href="#">Layer 2 PE (L2PE) . . . . .</a>	<a href="#">14</a>
<a href="#">5.4.2</a>	<a href="#">Logical PE (LPE) . . . . .</a>	<a href="#">14</a>
<a href="#">5.4.3</a>	<a href="#">PE-CLE . . . . .</a>	<a href="#">14</a>
<a href="#">5.4.4</a>	<a href="#">PE-Core . . . . .</a>	<a href="#">14</a>
<a href="#">5.4.5</a>	<a href="#">PE-Edge . . . . .</a>	<a href="#">15</a>
<a href="#">5.4.6</a>	<a href="#">PE-POP . . . . .</a>	<a href="#">15</a>
<a href="#">5.4.7</a>	<a href="#">VPLS Edge (VE) . . . . .</a>	<a href="#">15</a>
<a href="#">6.</a>	<a href="#">Functions . . . . .</a>	<a href="#">16</a>
<a href="#">6.1</a>	<a href="#">Attachment Circuit (AC) . . . . .</a>	<a href="#">16</a>
<a href="#">6.2</a>	<a href="#">Backdoor Links . . . . .</a>	<a href="#">16</a>
<a href="#">6.3</a>	<a href="#">Endpoint discovery . . . . .</a>	<a href="#">16</a>
<a href="#">6.4</a>	<a href="#">Flooding . . . . .</a>	<a href="#">16</a>
<a href="#">6.5</a>	<a href="#">MAC address learning . . . . .</a>	<a href="#">16</a>

<a href="#">6.5.1</a>	Qualified learning . . . . .	<a href="#">16</a>
<a href="#">6.5.2</a>	Unqualified learning . . . . .	<a href="#">17</a>
<a href="#">6.6</a>	Signalling . . . . .	<a href="#">17</a>

<a href="#">7.</a>	<a href="#">'Boxes'</a>	<a href="#">18</a>
<a href="#">7.1</a>	Aggregation box	<a href="#">18</a>
<a href="#">7.2</a>	Customer Premises Equipment (CPE)	<a href="#">18</a>
<a href="#">7.3</a>	Multi Tenant Unit (MTU)	<a href="#">18</a>
<a href="#">8.</a>	Packet Switched Network (PSN)	<a href="#">19</a>
<a href="#">8.1</a>	Route Distinguisher (RD)	<a href="#">19</a>
<a href="#">8.2</a>	Route Reflector	<a href="#">19</a>
<a href="#">8.3</a>	Route Target (RT)	<a href="#">19</a>
<a href="#">8.4</a>	Tunnel	<a href="#">19</a>
<a href="#">8.5</a>	Tunnel multiplexor	<a href="#">20</a>
<a href="#">8.6</a>	Virtual Channel (VC)	<a href="#">20</a>
<a href="#">8.7</a>	VC label	<a href="#">20</a>
<a href="#">8.8</a>	Inner label	<a href="#">20</a>
<a href="#">8.9</a>	VPN Routing and Forwarding (VRF)	<a href="#">20</a>
<a href="#">8.10</a>	VPN Forwarding Instance (VFI)	<a href="#">20</a>
<a href="#">8.11</a>	Virtual Switch Instance (VSI)	<a href="#">20</a>
<a href="#">8.12</a>	Virtual Router (VR)	<a href="#">21</a>
<a href="#">9.</a>	Security Considerations	<a href="#">22</a>
<a href="#">10.</a>	Acknowledgements	<a href="#">23</a>
<a href="#">11.</a>	Informative References	<a href="#">23</a>
	Authors' Addresses	<a href="#">25</a>
	Intellectual Property and Copyright Statements	<a href="#">26</a>



## **1. Introduction**

A comparatively large number of memos has been submitted to the former PPVPN working group, and to the L2VPN, L3VPN and PWE3 working groups that all address the same problem space, provider provisioned virtual private networking for end customers. The memos address a wide range of services, but there is also a great deal of commonality among the proposed solutions.

This has lead to the development of a partly new set of concepts used to describe this set of VPN services. To a certain extent there is more than one term covering the same concept and sometimes the same term covers more than one concept.

This document seeks to fill at least part of the need and proposes a foundation for a unified terminology for the L2VPN, L3VPN working groups; in some cases the parallel concepts within the PWE3 working group are used as references.





## **2. PPVPN Terminology**

The concepts and terms in this list are gathered from Internet Drafts sent to the L2VPN and L3VPN mailing lists (earlier PPVPN mailing list) and RFCs relevant to the L2VPN and L3VPN working groups. The focus is on terminology and concepts that are specific to the PPVPN area, but this is not strictly enforced, e.g. there are concepts and terms within the PWE3 and (Generalized) MPLS areas that are closely related. We've tried to find the earliest use of terms and concepts.

This document intends to fully cover the concepts within the core documents from the L2VPN and L3VPN working groups, i.e. [\[I-D.ietf-l3vpn-requirements\]](#) , [\[I-D.ietf-l2vpn-requirements\]](#), [\[I-D.ietf-l3vpn-framework\]](#), [\[I-D.ietf-l2vpn-l2-framework\]](#), and [\[I-D.ietf-l3vpn-generic-reqts\]](#). The intention is to create a comprehensive and unified set of concepts for these documents, and by extension for the entire PPVPN area. To do so it is also necessary to give some of the development the concepts of the area have been through.

The document is structured in four major sections. [Section 4](#) lists the different services that have been or will be specified, [Section 5](#) lists the building blocks that are used to specify those services, [Section 6](#) lists the functions needed in those services and [Section 7](#) list some typical devices used in customer and provider networks.



### **3.    Provider Provisioned Virtual Private Network services**

In this section we define the terminology that relates the set of services to solutions specified by the L2VPN and L3VPN working groups. The concept "pseudo wire" that belongs to the PWE3 working group is included for reference purposes. For requirements in provider provisioned VPNs see [[I-D.ietf-l3vpn-requirements](#)].

In this section all abbreviations are listed together with short information on the service. The list is structured to give the more general information first and more specific later. The names of services for which IETF are working on solution for have as far as feasible been moved to the top of the list. Older and dated terminology has been pushed toward the end of the list.

#### **3.1    Layer 3 VPN (L3VPN)**

An L3VPN interconnects sets of hosts and routers based on Layer 3 addresses, see [[I-D.ietf-l3vpn-framework](#)].

#### **3.2    Layer 2 VPN (L2VPN)**

Three types of L2VPNs are described in this document, Virtual Private Wire Service (VPWS) ([Section 3.4](#)), Virtual Private LAN Service (VPLS) ([Section 3.3](#)), and IP-only LAN-like Service (IPLS) ([Section 3.5](#)).

#### **3.3    Virtual Private LAN Service (VPLS)**

A VPLS is a provider service that emulates the full functionality of a traditional Local Area Network. A VPLS makes it possible to interconnect several LAN segments over a packet switched network (PSN) and makes the remote LAN segments behave as one single LAN. For an early work on defining a solution and protocol for a VPLS see [[I-D.ietf-l2vpn-requirements](#)], [[I-D.ietf-l2vpn-vpls-ldp](#)], and [[I-D.ietf-l2vpn-vpls-bgp](#)].

In a VPLS, the provider network emulates a learning bridge and forwarding decisions are taken based on MAC addresses or MAC addresses and VLAN tag.

### **3.4 Virtual Private Wire Service (VPWS)**

A Virtual Private Wire Service (VPWS) is a point-to-point circuit (link) connecting two Customer Edge devices. The link is established as a logical through a packet switched Network. The CE in the customer network is connected to a PE in the provider network via an Attachment Circuit (see [Section 6.1](#)); the Attachment Circuit is

either a physical or a logical circuit.

The PE's in the core network are connected via a PW.

The CE devices can be routers, bridges, switches or hosts. In some implementations a set of VPWSs is used to create a multi-site L2VPN network. An example of a VPWS solution is described in [\[I-D.kompella-ppvnp-l2vpn\]](#).

A VPWS differs from a VPLS ([Section 3.3](#)) in that the VPLS is point to multipoint, while the VPWS is point to point. See [\[I-D.ietf-l2vpn-l2-framework\]](#).

### **[3.5](#) IP-only LAN-like Service (IPLS)**

An IPLS is very like a VPLS (see [Section 3.3](#)), except that:

- o it is assumed that the CE devices (see [Section 5.1](#)) are hosts or routers, not switches
- o it is assumed that the service will only need to carry IP packets, and supporting packets such as ICMP and ARP; otherwise layer 2 packets which do not contain IP are not supported.
- o the assumption that only IP packets is carried by the service applies equally to IPv4 and IPv6 packets.

While this service is a functional subset of the VPLS service, it is considered separately because it may be possible to provide it using different mechanisms, which may allow it to run on certain hardware platforms that cannot support the full VPLS functionality [\[I-D.ietf-l2vpn-l2-framework\]](#).

### **[3.6](#) Pseudo Wire (PW)**

The PWE3 working group within the IETF specifies the pseudo wire technology. A pseudo wire is an emulated point-to-point connection over a packet switched network that gives the possibility to interconnect two nodes with any L2 technology. The PW shares some of the building blocks and architecture constructs with the point-to-multipoint solutions, e.g. PE (see [Section 5.2](#)) and CE (see [Section 5.1](#)). An early solution for PWs is described in

[[I-D.martini-l2circuit-trans-mpls](#)]. Encapsulation formats readily used in VPWS, VPLS and PWs are described in [[I-D.martini-l2circuit-encap-mpls](#)]. Requirements for PWs are found in [[I-D.ietf-pwe3-requirements](#)] and [[I-D.ietf-pwe3-arch](#)] presents an architectural framework for PWs.

### **[3.7](#) Transparent LAN Service (TLS)**

TLS was an early name used to describe the VPLS service, it was used e.g., in the now dated [draft-lasserre-tls-mpls-00.txt](#). This draft has been merged into the working group VPLS solution using LDP as a signalling protocol. The term TLS has been replaced by VPLS, which is the current term.

### **[3.8](#) Virtual LAN (VLAN)**

The term VLAN was specified by IEEE 802.1Q; it defines a method to differentiate traffic on a LAN by tagging the Ethernet frames. By extension, VLAN is used to mean the traffic separated by Ethernet frame tagging or similar mechanisms.

### **[3.9](#) Virtual Leased Line Service (VLLS)**

The term VLLS has been replaced by term VPWS. VLLS was used in now dated document intended to create metrics by which it should have been possible to compare different L2VPN solutions. This document has now expired and the work terminated.

### **[3.10](#) Virtual Private Network (VPN)**

VPN is a generic term that covers the use of public or private networks to create groups of users that are separated from other network users and may communicate among them as if they were on a private network. It is possible to enhance the level of separation e.g. by end-to-end encryption, this is however outside the scope of IETF VPN working group charters. This VPN definition is from [\[RFC2764\]](#).

In the [\[I-D.ietf-l3vpn-framework\]](#) the term VPN is used to refer to a specific set of sites as either an intranet or an extranet that have been configured to allow communication. Note that a site is a member of at least one VPN, and may be a member of many VPNs.

In this document "VPN" is also used as a generic name for all services listed in [Section 3](#).


### **3.11 Virtual Private Switched Network (VPSN)**

The term VPSN has been replaced by the term VPLS. The VPSN abbreviation was used e.g. in the now dated [draft-vkompella-ppvpn-vpsn-reqmts-00.txt](#). The requirements has been merged into the L3VPN [[I-D.ietf-l3vpn-requirements](#)] and L2VPN [[I-D.ietf-l2vpn-requirements](#)] requirements.



#### 4. Classification of VPNs

The terminology used in [[I-D.ietf-13vpn-generic-reqts](#)] is defined based on the figure below.



The figure above presents a taxonomy of PPVPN technologies. Some of the definitions are given below:

Figure 1

**CE-based VPN:** A VPN approach in which the shared service provider network does not have any knowledge of the customer VPN. This information is limited to CE equipment. All the VPN-specific procedures are performed in the CE devices, and the PE devices are not aware in any way that some of the traffic they are processing is VPN traffic (see also [[I-D.ietf-13vpn-framework](#)]).

**PE-Based VPNs:** A Layer 3 VPN approach in which a service provider network is used to interconnect customer sites using shared resources. Specifically the PE device maintains VPN state, isolating users of one VPN from users of another VPN. Because the PE device maintains all required VPN state, the CE device may behave as if it were connected to a private network. Specifically, the CE in a PE-based VPN must not require any changes or additional functionality to be connected to a PPVPN instead of a private network.

The PE devices know that certain traffic is VPN traffic. They forward the traffic (through tunnels) based on the destination IP

address of the packet, and optionally based on other information in the IP header of the packet. The PE devices are themselves the tunnel endpoints. The tunnels may make use of various encapsulations to send traffic over the SP network (such as, but not restricted to, GRE, IP-in-IP, IPsec, or MPLS tunnels) [[I-D.ietf-l3vpn-framework](#)].

Virtual Router (VR) style: A PE-based VPN approach in which the PE

router maintains a complete logical router for each VPN that it supports. Each logical router maintains a unique forwarding table and executes a unique instance of the routing protocols. These VPNs are described in [[I-D.ietf-l3vpn-vpn-vr](#)].

BGP/MPLS IP VPNs: A PE-based VPN approach in which the PE router maintains separate forwarding environment for each VPN and a separate forwarding table for each VPN. In order to maintain multiple forwarding table instances while running only a single BGP instance, BGP/MPLS IP VPNs mark route advertisements with attributes that identify their VPN context. These VPNs are based on the approach described in [[I-D.ietf-l3vpn-rfc2547bis](#)].

[RFC 2547](#) Style: The term has been used by the L3VPN to describe the extensions of the VPNs defined in the informational [RFC2547](#). This term has now been replaced by the term BGP/MPLS IP VPNs.



## **5. Building blocks**

Starting with specifications of L3VPNs, e.g. the 2547 specification [[RFC2547](#)] and [[I-D.ietf-l3vpn-rfc2547bis](#)] and Virtual Routers [[I-D.ietf-l3vpn-vpn-vr](#)], a way of describing the building blocks and allocation of functions in VPN solutions was developed. The building blocks are often used in day-to-day talk as if it were physical boxes, common for all services.

However, for different reasons this is an over-simplification. Any of the building blocks could be implemented across more than one physical box. How common the use of such implementations will be is beyond the scope of this document.

### **5.1 Customer Edge device (CE)**

A CE is the name of the device with the functionality needed on the customer premises to access the services specified by the former PPVPN working group in relation to the work done on L3VPNs [[I-D.ietf-l3vpn-framework](#)]. The concept has been modified e.g. when L2VPNs and CE-based VPNs were defined, this is addressed further in the sub- sections of this section.

There are two different aspects that need to be considered in naming CE devices. One could start with the type of device that is used to implement the CE (see [Section 5.1.1](#)). It is also possible to use the service the CE provides and with the result it will be a set of "prefixed CEs", (see [Section 5.1.2](#)).

It is common practice to use "CE" to indicate any of these boxes, since it is very often unambiguous in the specific context.

#### **5.1.1 Device based CE naming**

##### **5.1.1.1 Customer Edge Router (CE-R)**

A CE-R is a router in the customer network interfacing the provider network. There are many reasons to use a router in the customer network, e.g. in an L3VPN using private IP addressing this is the router that is able to do forwarding based on the private addresses.

Another reason to require the use of a CE-R on the customer side is that one want to limit the number on MAC- addresses that needs to be learned in the provider network.

A CE-R could be used to access both L2 and L3 services.

#### [5.1.1.2](#)    **Customer Edge Switch (CE-S)**

A CE-S is a service aware L2 switch in the customer network interfacing the provider network. In a VPWS or a VPLS it is not strictly necessary to use a router in the customer network, a layer 2 switch might very well do the job.

#### [5.1.2](#)    **Service based CE naming**

The list below contains examples of how different functionality has been used to name CE's. There are many examples of this type of naming and we have not had the ambition to cover every possible example, but only cover the most frequently used functional names. As this is functional names it is quite possible that on single piece of equipment are the platform for more than one type of function, e.g. a router might at the same time be both a L2VPN-CE and a L3VPN-CE. It might also be that the functions that is need to for a L2VPN-CE or L3VPN-CE is distributed over more than one platform.

##### [5.1.2.1](#)    **L3VPN-CE**

An L3VPN-CE is the device or set of devices on the customer premises that attaches to a provider provisioned L3VPN, e.g. a 2547bis implementation.

##### [5.1.2.2](#)    **VPLS-CE**

A VPLS-CE is the device or set of devices on the customer premises that attaches to a provider provisioned VPLS.

##### [5.1.2.3](#)    **VPWS-CE**

A VPWS-CE is the device or set of devices on the customer premises that attaches to a provider provisioned VPWS.

#### [5.2](#)    **Provider Edge (PE)**

A PE is the name of the device or set of devices at the edge of the

provider network with the functionality that is needed to interface the customer. PE, without further qualifications, is very often used for naming the devices since it is made unambiguous by the context.

In naming PEs there are three aspects that we need to consider, the service they support, whether the functionality needed for service is distributed across more than one device and the type of device they are build on.



### [5.2.1](#)    **Device based PE naming**

Both routers and switches may be used to implement PEs, however the scaling properties will be radically different depending which type of equipment is chosen.

#### [5.2.1.1](#)    **Provider Edge Router (PE-R)**

A PE-R is a L3 device that participates in the PSN (see [Section 8](#)) routing and forwards packets based on the routing information.

#### [5.2.1.2](#)    **Provider Edge Switch (PE-S)**

A PE-S is a L2 device that participates in e.g. a switched Ethernet taking forwarding decision packets based on L2 address information.

### [5.2.2](#)    **Service based PE naming**

#### [5.2.2.1](#)    **L3VPN-PE**

An L3VPN-PE is a device or set of devices at the edge of the provider network interfacing the customer network, with the functionality needed for an L3VPN.

#### [5.2.2.2](#)    **VPWS-PE**

A VPWS-PE is a device or set of devices at the edge of the provider network interfacing the customer network, with the functionality needed for a VPWS.

#### [5.2.2.3](#)    **VPLS-PE**

A VPLS-PE is a device or set of devices at the edge of the provider network interfacing the customer network, with the functionality needed for a VPLS.

### **5.2.3 Distribution based PE naming**

For scaling reasons it is in the VPLS/VPWS cases sometimes desired to distribute the functions in the VPLS/VPWS-PE across more than one device, e.g. is it feasible to allocate MAC address learning on a comparatively small and in-expensive device close to the customer site, while participation in the PSN signalling and set up of PE to PE tunnels are done by routers closer to the network core.

When distributing functionality across devices a protocol is needed to exchange information between the Network facing PE (N-PE) see [Section 5.2.3.1](#) and the User facing PE (U-PE) see [Section 5.2.3.2](#).

#### [5.2.3.1](#)    **Network facing PE (N-PE)**

The N-PE is the device to which the signalling and control functions are allocated when a VPLS-PE is distributed across more than one box.

#### [5.2.3.2](#)    **User facing PE (U-PE)**

The U-PE is the device to which the functions needed to take forwarding or switching decision at the ingress of the provider network.

### [5.3](#)    **Core**

#### [5.3.1](#)    **Provider router (P)**

The P is defined as a router in the core network that does not have interfaces directly towards a customer. Hence a P router does not need to keep VPN state and is VPN un-aware.

### [5.4](#)    **Naming in specific Internet drafts**

#### [5.4.1](#)    **Layer 2 PE (L2PE)**

L2PE is the joint name of the devices in the provider network that implement L2 functions needed for a VPLS or a VPWS.

#### [5.4.2](#)    **Logical PE (LPE)**

The term Logical PE (LPE) originates from a dated Internet Draft "VPLS/LPE L2VPNs: Virtual Private LAN Services using Logical PE Architecture" and was used to describe a set of devices used in a provider network to implement a VPLS. In a LPE, VPLS functions are distributed across small devices (PE-Edges/U-PE) and devices attached to a network core (PE-Core/N-PE). In an LPE solution the PE-edge and PE-Core can be interconnected by a switched Ethernet transport network(s) or uplinks. The LPE will appear to the core network as a single PE. In this document the devices that constitutes the LPE is called N-PE and U-PE.

### [5.4.3](#) PE-CLE

An alternative name for the U-PE suggested in the now expired Internet Draft "VPLS architectures".

### [5.4.4](#) PE-Core

See the origins and use of this concept in [Section 5.4.2](#).

#### [5.4.5](#)    **PE-Edge**

See the origins and use of this concept in [Section 5.4.2](#).

#### [5.4.6](#)    **PE-POP**

An alternative name for the U-PE suggested in now the expired Internet Draft "VPLS architectures".

#### [5.4.7](#)    **VPLS Edge (VE)**

The term VE originates from a dated Internet Draft on a distributed transparent LAN service and was used to describe the device used by a provider network to hand off a VPLS to a customer. In this document the VE is called a VPLS-PE. This name has dated.



## **6. Functions**

In this section we have grouped a number of concepts and terms that have to be performed to make the VPN services work.

### **6.1 Attachment Circuit (AC)**

In a Layer 2 VPN the CE is attached to PE via an Attachment Circuit (AC). The AC may be a physical or logical link.

### **6.2 Backdoor Links**

Backdoor Links are links between CE devices that are provided by the end customer rather than the SP; may be used to interconnect CE devices in multiple-homing arrangements [[I-D.ietf-l3vpn-framework](#)].

### **6.3 Endpoint discovery**

Endpoint discovery is the process by which the devices that are aware of a specific VPN service will find all customer facing ports that belong to the same service.

The requirements on endpoint discovery and signalling are discussed in [[I-D.ietf-l3vpn-requirements](#)]. It was also the topic in a now dated Internet Draft reporting from a design team activity on VPN discovery.

### **6.4 Flooding**

Flooding is a function related to L2 services; when a PE receives a frame with an unknown destination MAC-address, that frame is send out over (flooded) every other interface.

### **6.5 MAC address learning**

MAC address learning is a function related to L2 services; when PE receives a frame with an unknown source MAC-address the relationship

between that MAC-address and interface is learnt for future forwarding purposes. In a layer 2 VPN solution from the L2VPN WG, this function is allocated to the VPLS-PE.

#### **6.5.1 Qualified learning**

In qualified learning, the learning decisions at the U-PE are based on the customer Ethernet frame's MAC address and VLAN tag, if a VLAN tag exists. If no VLAN tag exists, the default VLAN is assumed.



### **6.5.2 Unqualified learning**

In unqualified learning, learning is based on a customer Ethernet frame's MAC address only.

## **6.6 Signalling**

Signalling is the process by which the PEs that have VPNs behind them exchange information to set up PWs, PSN tunnels and tunnel multiplexers. This process might be automated through a protocol or done by manual configuration. Different protocols may be used to establish the PSN tunnels and exchange the tunnel multiplexers.



## [7.](#) 'Boxes'

We list a set of boxes that will typically be used in an environment that supports different kinds of VPN services. We have chosen to include some names of boxes that originate outside the protocol specifying organisations.

### [7.1](#) Aggregation box

The aggregation box is typically an L2 switch that is service unaware and is used only to aggregate traffic to more function rich points in the network.

### [7.2](#) Customer Premises Equipment (CPE)

The CPE equipment is the box that a provider places with the customer. It serves two purposes, giving the customer ports to plug in to and making it possible for a provider to monitor the connectivity to the customer site. The CPE is typically a low cost box with limited functionality and in most cases not aware of the

VPN services offered by the provider network. The CPE equipment is not necessarily the equipment to which the CE functions are allocated, but is part of the provider network and used for monitoring purposes.

The CPE name is used primarily in network operation and deployment contexts, and should not be used in protocol specifications.

### [7.3](#) Multi Tenant Unit (MTU)

An MTU is typically an L2 switch placed by a service provider in a building where several customers of that service provider are located. The term was introduced in an Internet Draft specifying a VPLS solution with function distributed between the MTU and the PE in the context of a [[I-D.ietf-l2vpn-vpls-bgp](#)].

The MTU device name is used primarily in network operation and deployment contexts, and should not be used in protocol

specifications, as it is also a used abbreviation for Maximum Transmit Units.

## **8. Packet Switched Network (PSN)**

A PSN is the network through which the tunnels supporting the VPN services are set up.

### **8.1 Route Distinguisher (RD)**

A Route Distinguisher [[I-D.ietf-l3vpn-rfc2547bis](#)] is an 8-byte value that together with a 4 byte IPv4 address identifies a VPN-IPv4 address family. If two VPNs use the same IPv4 address prefix, the PE's translate these into unique VPN-IPv4 address prefixes. This ensures that if the same address is used in two different VPNs, it is possible to install two completely different routes to that address, one for each VPN.

### **8.2 Route Reflector**

A route reflector is a network element owned by a Service Provider (SP) that is used to distribute BGP routes to the SP's BGP-enabled routers [[I-D.ietf-l3vpn-framework](#)].

### **8.3 Route Target (RT)**

A Route Target attribute [[I-D.ietf-l3vpn-rfc2547bis](#)] can be thought of as identifying a set of sites, or more precisely a set of VRFs (see [Section 8.9](#)).

Associating a particular Route Target with a route, allows that route to be placed in all VRFs that are used for routing traffic received from the corresponding sites.

A Route Target attribute is also a BGP extended community used in [[RFC2547](#)], and [[I-D.ietf-l3vpn-bgpvpn-auto](#)]. A Route Target community is used to constrain VPN information distribution to the set of VRFs. A route target can be perceived as identifying a set of sites, or more precisely a set of VRFs.

### **8.4 Tunnel**

A tunnel is connectivity through a PSN that is used to send traffic across the network from one PE to another. The tunnel provides a mechanism to transport packets from one PE to another, separation of one customer's traffic from another customer's traffic is done based on tunnel multiplexers (see [Section 8.5](#)). How the tunnel is established depends on the tunnelling mechanisms provided by the PSN, i.e. the tunnel could be based on e.g. the IP-header, an MPLS label, the L2TP Session ID, or on the GRE Key field.

## **[8.5](#) Tunnel multiplexor**

A tunnel multiplexor is an entity that is sent with the packets traversing the tunnel to make it possible to decide to which instance of a service a packet belongs and from which sender it was received. In [[I-D.kompella-ppvnp-l2vpn](#)] the tunnel multiplexor is formatted as an MPLS label.

## **[8.6](#) Virtual Channel (VC)**

A VC is transported within a tunnel and identified by its tunnel multiplexor. A virtual channel is identified by a VCI (Virtual Channel Identifier). In the PPVPN context a VCI is a VC label or tunnel multiplexor and in the Martini case it is equal to the VCID.

## **[8.7](#) VC label**

In an MPLS-enabled IP network a VC label is an MPLS label, used to identify traffic within a tunnel that belongs to a particular VPN, i.e. the VC label is the tunnel multiplexor in networks that use MPLS labels.

## **[8.8](#) Inner label**

"Inner label" is another name for VC label (see [Section 8.6](#)).

## **[8.9](#) VPN Routing and Forwarding (VRF)**

In networks running 2547 VPN's [[RFC2547](#)], PE routers maintain VRF's. A VRF is a per-site forwarding table. Every site to which the PE router is attached is associated with one of these tables. A particular packet's IP destination address is looked up in a particular VRF only if that packet has arrived directly from a site, which is associated with that table.

## **[8.10](#) VPN Forwarding Instance (VFI)**

VPN Forwarding Instance (VFI) is a logical entity that resides in a

PE that includes the router information base and forwarding information base for a VPN instance [[I-D.ietf-l3vpn-framework](#)].

### **8.11 Virtual Switch Instance (VSI)**

In a layer 2 context a VSI is a virtual switching instance that serves one single VPLS [[I-D.ietf-l2vpn-l2-framework](#)]. A VSI performs standard LAN (i.e., Ethernet) bridging functions. Forwarding done by a VSI is based on MAC addresses and VLAN tags, and possibly other relevant information on a per VPLS basis. The VSI is allocated to



VPLS-PE or in the distributed case to the U-PE.

### **8.12 Virtual Router (VR)**

A Virtual Router (VR) is software and hardware based emulation of a physical router. Virtual routers have independent IP routing and forwarding tables and they are isolated from each other, see [[I-D.ietf-l3vpn-vpn-vr](#)].



## **9.   Security Considerations**

This is a terminology document and as such doesn't have direct security implications. Security considerations will be specific to the solutions, framework and specification documents whose terminology is collected and discussed in this document.



## **10. Acknowledgements**

Much of the content in this document is based on discussion in the PPVPN design teams for "auto discovery" and "l2vpn".

Dave McDysan, Adrian Farrel and Thomas Narten have carefully reviewed the document and given many useful suggestions.

Thomas Narten converted an almost final version of this document into XML, after extracting an acceptable version out of Word became to painful. Avri Doria has been very helpful in guiding is in the use of XML.

## **11 Informative References**

[I-D.ietf-l2vpn-l2-framework]

Andersson, L. and E. Rosen, "Framework for Layer 2 Virtual Private Networks (L2VPNs)",  
[draft-ietf-l2vpn-l2-framework-05](#) (work in progress), June 2004.

[I-D.ietf-l2vpn-requirements]

Augustyn, W. and Y. Serbest, "Service Requirements for Layer 2 Provider Provisioned Virtual Private Networks",  
[draft-ietf-l2vpn-requirements-01](#) (work in progress), February 2004.

[I-D.ietf-l2vpn-vpls-bgp]

Kompella, K., "Virtual Private LAN Service",  
[draft-ietf-l2vpn-vpls-bgp-02](#) (work in progress), May 2004.

[I-D.ietf-l2vpn-vpls-ldp]

Lasserre, M. and V. Kompella, "Virtual Private LAN Services over MPLS", [draft-ietf-l2vpn-vpls-ldp-04](#) (work in progress), August 2004.

[I-D.ietf-l3vpn-bgpvpn-auto]

Ould-Brahim, H., Rosen, E. and Y. Rekhter, "Using BGP as an Auto-Discovery Mechanism for Layer-3 and Layer-2 VPNs",  
[draft-ietf-l3vpn-bgpvpn-auto-04](#) (work in progress), May

2004.

[I-D.ietf-l3vpn-framework]

Callon, R. and M. Suzuki, "A Framework for Layer 3  
Provider Provisioned Virtual Private Networks",  
[draft-ietf-l3vpn-framework-00](#) (work in progress), July  
2003.

[I-D.ietf-l3vpn-generic-reqts]

Nagarajan, A., "Generic Requirements for Provider Provisioned Virtual Private Networks",  
[draft-ietf-l3vpn-generic-reqts-03](#) (work in progress),  
February 2004.

[I-D.ietf-l3vpn-requirements]

Carugi, M. and D. McDysan, "Service requirements for Layer 3 Virtual Private Networks",  
[draft-ietf-l3vpn-requirements-02](#) (work in progress), July  
2004.

[I-D.ietf-l3vpn-rfc2547bis]

Rosen, E., "BGP/MPLS IP VPNs",  
[draft-ietf-l3vpn-rfc2547bis-01](#) (work in progress),  
September 2003.

[I-D.ietf-l3vpn-vpn-vr]

Knight, P., Ould-Brahim, H. and B. Gleeson, "Network based IP VPN Architecture using Virtual Routers",  
[draft-ietf-l3vpn-vpn-vr-02](#) (work in progress), April 2004.

[I-D.ietf-pwe3-arch]

Bryant, S. and P. Pate, "PWE3 Architecture",  
[draft-ietf-pwe3-arch-07](#) (work in progress), March 2004.

[I-D.ietf-pwe3-requirements]

Xiao, X., "Requirements for Pseudo-Wire Emulation Edge-to-Edge (PWE3)", [draft-ietf-pwe3-requirements-08](#)  
(work in progress), January 2004.

[I-D.kompella-ppvnp-l2vpn]

Kompella, K., "Layer 2 VPNs Over Tunnels",  
[draft-kompella-ppvnp-l2vpn-02](#) (work in progress), June  
2002.

[I-D.martini-l2circuit-encap-mpls]

Martini, L., "Encapsulation Methods for Transport of Layer 2 Frames Over IP and MPLS Networks",  
[draft-martini-l2circuit-encap-mpls-07](#) (work in progress),  
June 2004.

[I-D.martini-l2circuit-trans-mpls]

Martini, L. and N. El-Aawar, "Transport of Layer 2 Frames Over MPLS", [draft-martini-l2circuit-trans-mpls-14](#) (work in progress), June 2004.

[RFC2547] Rosen, E. and Y. Rekhter, "BGP/MPLS VPNs", [RFC 2547](#), March



1999.

[RFC2764] Gleeson, B., Heinanen, J., Lin, A., Armitage, G. and A. Malis, "A Framework for IP Based Virtual Private Networks", [RFC 2764](#), February 2000.

#### Authors' Addresses

Loa Anderson  
Acreo AB

EMail: loa@pi.se

Tove Madsen  
Acreo AB

EMail: tove.madsen@acreo.se



## Intellectual Property Statement

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in [BCP 78](#) and [BCP 79](#).

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at [ietf-ipr@ietf.org](mailto:ietf-ipr@ietf.org).

## Disclaimer of Validity

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

## Copyright Statement

Copyright (C) The Internet Society (2004). This document is subject to the rights, licenses and restrictions contained in [BCP 78](#), and except as set forth therein, the authors retain all their rights.

## Acknowledgment

Funding for the RFC Editor function is currently provided by the Internet Society.