LAMPS Working Group

Internet-Draft
Undates: PEC7020 (if approx

Updates: <u>RFC7030</u> (if approved)
Intended status: Standards Track

Expires: October 27, 2020

M. Richardson
Sandelman Software Works
T. Werner
Siemens
W. Pan
Huawei Technologies

April 25, 2020

Clarification of Enrollment over Secure Transport (EST): transfer encodings and ASN.1 draft-ietf-lamps-rfc7030est-clarify-03

Abstract

This document updates <u>RFC7030</u>: Enrollment over Secure Transport (EST) to resolve some errata that was reported, and which has proven to cause interoperability issues when <u>RFC7030</u> was extended.

This document deprecates the specification of "Content-Transfer-Encoding" headers for EST endpoints. This document fixes some syntactical errors in ASN.1 that was presented.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of \underline{BCP} 78 and \underline{BCP} 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at https://datatracker.ietf.org/drafts/current/.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on October 27, 2020.

Copyright Notice

Copyright (c) 2020 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to <u>BCP 78</u> and the IETF Trust's Legal Provisions Relating to IETF Documents (https://trustee.ietf.org/license-info) in effect on the date of

publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

<u>1</u> .	Intr	oduction																				2
<u>2</u> .	Tern	ninology .																				<u>3</u>
<u>3</u> .	Char	nges to ES	ST endpo	int	pro	oces	ssi	ing	J													<u>3</u>
3	<u>.1</u> .	Whitespac	e proce	ssin	ıg .																	<u>3</u>
<u>4</u> .	Clar	ification	of ASN	I.1 f	or	Ce	rti	Ĺfi	.ca	ite	. A	ιtt	ri	bu	ıte	9 8	et					<u>4</u>
4	<u>.1</u> .	CSR Attri	butes F	Respo	nse	e .																<u>4</u>
5.	Clar	ification	n of err	orm	iess	sage	es	fo	r	СЕ	ert	if	ic	at	е	er	nro	11	.me	ent	:	
	oper	ations .																				<u>6</u>
5	.1.	Updating	section	4.2	2.3	: S:	imp	ole	: E	nr	ol	.1	ar	nd	Re	: - E	enr	ol	1			
		Response																				<u>6</u>
5	.2.	Updating	section	4.4	. 2	: S	er۱	/er	- S	Sic	le	Ke	y	Ge	ne	era	ıti	Lor	1			
		Response																				<u>6</u>
<u>6</u> .	Priv	acy Consi	deratio	ns																		<u>6</u>
<u>7</u> .	Secu	rity Cons	siderati	ons																		
<u>8</u> .	IANA	Consider	ations																			7
<u>9</u> .		nowledgeme																				
<u> 10</u> .	Refe	erences .																				
10	<u>9.1</u> .	Normativ	e Refer	ence	s																	
10	9.2.	Informat	ive Ref	eren	ices	S .																9
Appe	endix	A. ASN.	1 Modul	.e .																		10
		Addresse																				12

1. Introduction

[RFC7030] defines the Enrollment over Secure Transport, or EST protocol.

This specification defines a number of HTTP end points for certificate enrollment and management. The details of the transaction were defined in terms of MIME headers as defined in [RFC2045], rather than in terms of the HTTP protocol as defined in [RFC2616] and [RFC7230].

[RFC2616] and later <u>[RFC7231] Appendix A.5</u> has text specifically deprecating Content-Transfer-Encoding. However, <u>[RFC7030]</u> incorrectly uses this header.

Changes to [RFC7030] to bring it inline with typical HTTP processing risk changes the on-wire protocol in a way that is not backwards

compatible. However, reports from the implementers suggest that many implementations do not send the Content-Transfer-Encoding, and many of them ignore it. The consequence is that simply deprecating the header would remain compatible with current implementations.

[I-D.ietf-anima-bootstrapping-keyinfra] extends [RFC7030], adding new functionality, and interop testing of the protocol has revealed that unusual processing called out in [RFC7030] causes confusion.

EST is currently specified as part of [IEC62351], and is widely used in Government, Utilities and Financial markets today.

This document therefore revises [RFC7030] to reflect the field reality, deprecating the extranous field.

This document deals with errata numbers [errata4384], [errata5107], [errata5108], and [errata5904].

2. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14 [RFC2119] [RFC8174] when, and only when, they appear in all capitals, as shown here.

3. Changes to EST endpoint processing

The [RFC7030] sections 4.1.3 (CA Certificates Response, /cacerts), 4.3.1/4.3.2 (Full CMC, /fullcmc), 4.4.2 (Server-Side Key Generation, /serverkeygen), and 4.5.2 (CSR Attributes, /csrattrs) specify the use of base64 encoding with a Content-Transfer-Encoding for requests and response.

This document updates [RFC7030] to require the POST request and payload response of all endpoints use Base64 encoding as specified in Section 4 of [RFC4648]. In both cases, the Distinguished Encoding Rules (DER) [X690] are used to produce the input for the Base64 encoding routine. This format is to be used regardless of any Content-Transfer-Encoding header, and any value in such a header MUST be ignored.

3.1. Whitespace processing

Note that "base64" as used in the HTTP [RFC2616] does not permit CRLF, while the "base64" used in MIME [RFC2045] does. This specification clarifies that despite [RFC2616], that white space including CR, LF, spaces (ASCII 32) and, tabs (ASCII 9) should be

tolerated by receivers. Senders are not required to insert any kind of white space.

4. Clarification of ASN.1 for Certificate Attribute set.

Section 4.5.2 of [RFC7030] is to be replaced with the following text:

4.1. CSR Attributes Response

If locally configured policy for an authenticated EST client indicates a CSR Attributes Response is to be provided, the server response MUST include an HTTP 200 response code. An HTTP response code of 204 or 404 indicates that a CSR Attributes Response is not available. Regardless of the response code, the EST server and CA MAY reject any subsequent enrollment requests for any reason, e.g., incomplete CSR attributes in the request.

Responses to attribute request messages MUST be encoded as the content-type of "application/csrattrs", and are to be "base64" [RFC2045] encoded. The syntax for application/csrattrs body is as follows:

```
CsrAttrs ::= SEQUENCE SIZE (0..MAX) OF AttrOrOID

AttrOrOID ::= CHOICE {
  oid         OBJECT IDENTIFIER,
    attribute Attribute {{AttrSet}} }

AttrSet ATTRIBUTE ::= { aa-asymDecryptKeyId, ... }
```

An EST server includes zero or more OIDs or attributes [RFC2986] that it requests the client to use in the certification request. The client MUST ignore any OID or attribute it does not recognize. When the server encodes CSR Attributes as an empty SEQUENCE, it means that the server has no specific additional information it desires in a client certification request (this is functionally equivalent to an HTTP response code of 204 or 404).

If the CA requires a particular cryptographic algorithm or use of a particular signature scheme (e.g., certification of a public key based on a certain elliptic curve, or signing using a certain hash algorithm) it MUST provide that information in the CSR Attribute Response. If an EST server requires the linking of identity and POP information (see Section 3.5), it MUST include the challengePassword OID in the CSR Attributes Response.

The structure of the CSR Attributes Response SHOULD, to the greatest extent possible, reflect the structure of the CSR it is requesting.

Requests to use a particular signature scheme (e.g. using a particular hash function) are represented as an OID to be reflected in the SignatureAlgorithm of the CSR. Requests to use a particular cryptographic algorithm (e.g., certification of a public key based on a certain elliptic curve) are represented as an attribute, to be reflected as the AlgorithmIdentifier of the SubjectPublicKeyInfo, with a type indicating the algorithm and the values indicating the particular parameters specific to the algorithm. Requests for descriptive information from the client are made by an attribute, to be represented as Attributes of the CSR, with a type indicating the [RFC2985] extensionRequest and the values indicating the particular attributes desired to be included in the resulting certificate's extensions.

The sequence is Distinguished Encoding Rules (DER) encoded $[\underline{x690}]$ and then base64 encoded (Section 4 of [RFC4648]). The resulting text forms the application/csrattr body, without headers.

For example, if a CA requests a client to submit a certification request containing the challengePassword (indicating that linking of identity and POP information is requested; see Section 3.5), an extensionRequest with the Media Access Control (MAC) address ([RFC2307]) of the client, and to use the secp384r1 elliptic curve and to sign with the SHA384 hash function. Then, it takes the following:

OID: challengePassword (1.2.840.113549.1.9.7)

Attribute: type = extensionRequest (1.2.840.113549.1.9.14)

value = macAddress (1.3.6.1.1.1.22)

Attribute: type = id-ecPublicKey (1.2.840.10045.2.1)

value = secp384r1 (1.3.132.0.34)

OID: ecdsaWithSHA384 (1.2.840.10045.4.3.3)

and encodes them into an ASN.1 SEQUENCE to produce:

30 41 06 09 2a 86 48 86 f7 0d 01 09 07 30 12 06 07 2a 86 48 ce 3d 02 01 31 07 06 05 2b 81 04 00 22 30 16 06 09 2a 86 48 86 f7 0d 01 09 0e 31 09 06 07 2b 06 01 01 01 01 16 06 08 2a 86 48 ce 3d 04 03 03

and then base64 encodes the resulting ASN.1 SEQUENCE to produce:

MEEGCSqGSIb3DQEJBzASBgcqhkjOPQIBMQcGBSuBBAAiMBYGCSqGSIb3DQEJDjEJ BgcrBgEBAQEWBggqhkjOPQQDAw==

5. Clarification of error messages for certificate enrollment operations

[errata5108] clarifies what format the error messages are to be in. Previously a client might be confused into believing that an error returned with type text/plain was not intended to be an error.

5.1. Updating section 4.2.3: Simple Enroll and Re-enroll Response

Replace:

If the content-type is not set, the response data MUST be a plaintext human-readable error message containing explanatory information describing why the request was rejected (for example, indicating that CSR attributes are incomplete).

with:

If the content-type is not set, the response data must be a plaintext human-readable error message containing explanatory information describing why the request was rejected (for example, indicating that CSR attributes are incomplete). Servers MAY use the "text/plain" content-type [RFC2046] for human-readable errors.

5.2. Updating section 4.4.2: Server-Side Key Generation Response

Replace:

If the content-type is not set, the response data MUST be a plaintext human-readable error message.

with:

If the content-type is not set, the response data must be a plaintext human-readable error message. Servers MAY use the "text/plain" content-type [RFC2046] for human-readable errors.

6. Privacy Considerations

This document does not disclose any additional identifies to either active or passive observer would see with [RFC7030].

7. Security Considerations

This document clarifies an existing security mechanism. It does not create any new protocol mechanism.

8. IANA Considerations

The ASN.1 module in Appendix A of this doucment makes use of object identifiers (OIDs). This document requests that IANA register an OID in the SMI Security for PKIX Arc in the Module identifiers subarc (1.3.6.1.5.5.7.0) for the ASN.1 module. The OID for the Asymmetric Decryption Key Identifier (1.2.840.113549.1.9.16.2.54) was previously defined in [RFC7030].

IANA is requested to update the "Reference" column for the Asymmetric Decryption Key Identifier attribute to also include a reference to this doducment.

9. Acknowledgements

This work was supported by Huawei Technologies.

The ASN.1 Module was assembled by Russ Housley and formatted by Sean Turner. Russ Housley provided editorial review.

10. References

10.1. Normative References

[I-D.ietf-anima-bootstrapping-keyinfra]
Pritikin, M., Richardson, M., Eckert, T., Behringer, M.,
and K. Watsen, "Bootstrapping Remote Secure Key
Infrastructures (BRSKI)", <u>draft-ietf-anima-bootstrapping-keyinfra-41</u> (work in progress), April 2020.

[IEC62351]

International Electrotechnical Commission, "Power systems management and associated information exchange - Data and communications security - Part 9: Cyber security key management for power system equipment", ISO/IEC 62351-9:2017, 2017.

- [RFC2045] Freed, N. and N. Borenstein, "Multipurpose Internet Mail
 Extensions (MIME) Part One: Format of Internet Message
 Bodies", RFC 2045, DOI 10.17487/RFC2045, November 1996,
 https://www.rfc-editor.org/info/rfc2045>.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate
 Requirement Levels", BCP 14, RFC 2119,
 DOI 10.17487/RFC2119, March 1997,
 https://www.rfc-editor.org/info/rfc2119.
- [RFC2986] Nystrom, M. and B. Kaliski, "PKCS #10: Certification Request Syntax Specification Version 1.7", RFC 2986, DOI 10.17487/RFC2986, November 2000, https://www.rfc-editor.org/info/rfc2986.
- [RFC7030] Pritikin, M., Ed., Yee, P., Ed., and D. Harkins, Ed.,
 "Enrollment over Secure Transport", RFC 7030,
 DOI 10.17487/RFC7030, October 2013,
 <https://www.rfc-editor.org/info/rfc7030>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174, May 2017, https://www.rfc-editor.org/info/rfc8174>.
- [RFC8179] Bradner, S. and J. Contreras, "Intellectual Property
 Rights in IETF Technology", BCP 79, RFC 8179,
 DOI 10.17487/RFC8179, May 2017,
 https://www.rfc-editor.org/info/rfc8179.
- [X680] ITU-T, "Information technology Abstract Syntax Notation One.", ISO/IEC 8824-1:2002, 2002.

- [X681] ITU-T, "Information technology Abstract Syntax Notation One: Information Object Specification.", ISO/ IEC 8824-2:2002, 2002.
- [X682] ITU-T, "Information technology Abstract Syntax Notation One: Constraint Specification.", ISO/IEC 8824-2:2002, 2002.
- [X683] ITU-T, "Information technology Abstract Syntax Notation One: Parameterization of ASN.1 Specifications.", ISO/IEC 8824-2:2002, 2002.
- [X690] ITU-T, "Information technology ASN.1 encoding Rules: Specification of Basic Encoding Rules (BER), Canonical Encoding Rules (CER) and Distinguished Encoding Rules (DER).", ISO/IEC 8825-1:2002, 2002.

10.2. Informative References

- [RFC2307] Howard, L., "An Approach for Using LDAP as a Network Information Service", <u>RFC 2307</u>, DOI 10.17487/RFC2307, March 1998, https://www.rfc-editor.org/info/rfc2307>.
- [RFC2985] Nystrom, M. and B. Kaliski, "PKCS #9: Selected Object
 Classes and Attribute Types Version 2.0", RFC 2985,
 DOI 10.17487/RFC2985, November 2000,
 https://www.rfc-editor.org/info/rfc2985.

<u>Appendix A</u>. ASN.1 Module

This annex provides the normative ASN.1 definitions for the structures described in this specification using ASN.1 as defined in $[\underline{X680}]$ through $[\underline{X683}]$.

There is no ASN.1 Module in RFC 7030. This module has been created by combining the lines that are contained in the document body.

```
PKIXEST-2019
     { iso(1) identified-organization(3) dod(6)
       internet(1) security(5) mechanisms(5) pkix(7) id-mod(0)
       id-mod-est-2019(TBD) }
DEFINITIONS IMPLICIT TAGS ::=
BEGIN
-- EXPORTS ALL --
TMPORTS
Attribute
FROM CryptographicMessageSyntax-2010 -- [RFC6268]
      { iso(1) member-body(2) us(840) rsadsi(113549)
        pkcs(1) pkcs-9(9) smime(16) modules(0)
        id-mod-cms-2009(58) }
ATTRIBUTE
FROM PKIX-CommonTypes-2009
    { iso(1) identified-organization(3) dod(6) internet(1) security(5)
      mechanisms(5) pkix(7) id-mod(0) id-mod-pkixCommon-02(57) } ;
-- CSR Attributes
CsrAttrs ::= SEQUENCE SIZE (0..MAX) OF AttrOrOID
AttrOrOID ::= CHOICE {
   oid
              OBJECT IDENTIFIER,
   attribute Attribute {{AttrSet}} }
AttrSet ATTRIBUTE ::= { aa-symmDecrytKeyID, ... }
-- Asymmetric Decrypt Key Identifier Attribute
aa-asymmDecryptKeyID ATTRIBUTE ::=
    { TYPE AsymmetricDecryptKeyIdentifier
      IDENTIFIED BY id-aa-asymmDecryptKeyID }
id-aa-asymmDecryptKeyID OBJECT IDENTIFIER ::= { iso(1) member-body(2)
    us(840) rsadsi(113549) pkcs(1) pkcs9(9) smime(16) aa(2) 54 }
AsymmetricDecryptKeyIdentifier ::= OCTET STRING
END
```

Authors' Addresses

Michael Richardson Sandelman Software Works

Email: mcr+ietf@sandelman.ca

Thomas Werner Siemens

Email: thomas-werner@siemens.com

Wei Pan Huawei Technologies

Email: william.panwei@huawei.com