

Workgroup: LSR Working Group

Internet-Draft:

draft-ietf-lsr-isis-sr-vtn-mt-03

Published: 10 July 2022

Intended Status: Informational

Expires: 11 January 2023

Authors: C. Xie C. Ma J. Dong
 China Telecom China Telecom Huawei Technologies
 Z. Li
 Huawei Technologies

Using IS-IS Multi-Topology (MT) for Segment Routing based Virtual Transport Network

Abstract

Enhanced VPN (VPN+) aims to provide enhanced VPN service to support some application's needs of enhanced isolation and stringent performance requirements. VPN+ requires integration between the overlay VPN connectivity and the characteristics provided by the underlay network. A Virtual Transport Network (VTN) is a virtual underlay network which consists of a subset of network resources allocated on network nodes and links in a customized topology of the physical network. A VTN could be used as the underlay to support one or a group of VPN+ services.

In some network scenarios, each VTN can be associated with a unique logical network topology. This document describes a mechanism to build the SR based VTNs using IS-IS Multi-Topology together with other well-defined IS-IS extensions.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 11 January 2023.

Copyright Notice

Copyright (c) 2022 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Revised BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Revised BSD License.

Table of Contents

- [1. Introduction](#)
- [2. Advertisement of SR VTN Topology Attribute](#)
- [3. Advertisement of SR VTN Resource Attribute](#)
 - [3.1. Advertising Topology-specific TE attributes](#)
- [4. Forwarding Plane Operations](#)
- [5. Scalability Considerations](#)
- [6. Security Considerations](#)
- [7. IANA Considerations](#)
- [8. Acknowledgments](#)
- [9. References](#)
 - [9.1. Normative References](#)
 - [9.2. Informative References](#)
- [Authors' Addresses](#)

1. Introduction

Enhanced VPN (VPN+) is an enhancement to VPN services to support the needs of new applications, particularly the applications that are associated with 5G services. These applications require enhanced isolation and have more stringent performance requirements than that can be provided with traditional overlay VPNs. Thus these properties require integration between the underlay and the overlay networks. [I-D.ietf-teas-enhanced-vpn] specifies the framework of enhanced VPN and describes the candidate component technologies in different network planes and layers. VPN+ can be used to underpin network slicing, but could also be of use in its own right providing enhanced connectivity services between customer sites.

To meet the requirement of VPN+ services, a number of virtual transport networks (VTN) can be created, each with a subset of network resources allocated on network nodes and links in a customized topology of the physical network. A VTN could be used as

the underlay to meet the requirement of one or a group of VPN+ services. Another possible approach is to create a set of point-to-point paths, each with a set of network resources reserved along the path, such paths are called Virtual Transport Path (VTP). Although using a set of dedicated VTPs can provide similar characteristics as a VTN, it has some scalability issues due to the per-path state in the network.

[[I-D.ietf-spring-resource-aware-segments](#)] introduces resource awareness to Segment Routing (SR) [[RFC8402](#)]. The resource-aware SIDs have additional semantics to identify the set of network resources available for the packet processing action associated with the SIDs. As described in [[I-D.ietf-spring-sr-for-enhanced-vpn](#)], the resource-aware SIDs can be used to build SR based VTNs with the required network topology and network resource attributes to support VPN+ services. With segment routing based data plane, Segment Identifiers (SIDs) can be used to represent both the topological instructions and the set of network resources allocated by network nodes to a VTN. The SR SIDs and the associated topology and resource attributes of a VTN need to be distributed using control plane.

[[I-D.dong-lsr-sr-enhanced-vpn](#)] defines the IGP mechanisms with necessary extensions to provide scalable Segment Routing (SR) based VTNs. The VTNs could be used as the underlay of the VPN+ service. The mechanism described in [[I-D.dong-lsr-sr-enhanced-vpn](#)] allows flexible combination of the topology and resource attribute to build a relatively large number of VTNs. In some network scenarios, the required number of VTNs could be small, and it is assumed that each VTN is associated with an independent topology and has a set of dedicated or shared network resources. This document describes a simplified mechanism to build SR based VTNs in those scenarios. The resource-aware segments can be used with this approach to provide resource guaranteed SR VTNs, while the normal SR segments may also be used to provide SR VTNs with shared network resources in the forwarding plane.

The proposed approach is to use IS-IS Multi-Topology [[RFC5120](#)] with segment routing [[RFC8667](#)] to define the independent network topology of each VTN. The network resources and other TE attributes of a VTN can be advertised using IS-IS MT with the Traffic Engineering (TE) extensions defined in [[RFC5305](#)] and [[RFC8570](#)].

2. Advertisement of SR VTN Topology Attribute

IS-IS Multi-Topology Routing (MTR) [[RFC5120](#)] has been defined to create independent topologies in one network. In [[RFC5120](#)], MT-based TLVs are introduced to carry topology-specific link-state information. The MT-specific Link or Prefix TLVs are defined by adding additional two bytes, which includes 12-bit MT-ID field in

front of the ISN TLV and IP or IPv6 Reachability TLVs. This provides the capability of specifying the customized attributes of each topology. When each VTN is associated with an independent network topology, MT-ID could be used as the identifier of VTN in control plane.

MTR can be used with segment routing based data plane. Thus the topology attribute of an SR based VTN could be advertised using MTR with segment routing. The IS-IS extensions to support the advertisement of topology-specific MPLS SIDs are specified in [[RFC8667](#)]. Topology-specific Prefix-SIDs can be advertised by carrying the Prefix-SID sub-TLVs in the IS-IS TLV 235 (MT IP Reachability) and TLV 237 (MT IPv6 IP Reachability). Topology-specific Adj-SIDs can be advertised by carrying the Adj-SID sub-TLVs in IS-IS TLV 222 (MT-ISN) and TLV 223 (MT IS Neighbor Attribute). The topology-specific Prefix-SIDs and Adj-SIDs can be resource-aware segments or normal SR segments.

The IS-IS extensions to support the advertisement of topology-specific SRv6 Locators and SIDs are specified in [[I-D.ietf-lsr-isis-srv6-extensions](#)]. The topology-specific SRv6 locators are advertised using SRv6 Locator TLV, and SRv6 End SIDs inherit the MT-ID from the parent locator. The topology-specific End.X SID are advertised by carrying SRv6 End.X SID sub-TLVs in the IS-IS TLV 222 (MT-ISN) and TLV 223 (MT IS Neighbor Attribute). The topology-specific SRv6 locators can be resource-aware locator or normal SRv6 locator, and accordingly the topology-specific SRv6 SIDs can be resource-aware SRv6 segments or normal SRv6 segments.

3. Advertisement of SR VTN Resource Attribute

In order to perform constraint based path computation for each VTN on the network controller or on the ingress nodes, the network resource attributes and other attributes associated with each VTN need to be advertised.

3.1. Advertising Topology-specific TE attributes

On each network link, the information of the network resources and other attributes associated with a VTN can be specified by carrying the TE attributes sub-TLVs [[RFC5305](#)] and [[RFC8570](#)] in the IS-IS TLV 222 (MT-ISN) and TLV 223 (MT IS Neighbor Attribute) of the corresponding topology.

When Maximum Link Bandwidth sub-TLV is carried in the MT-ISN TLV of a topology, it indicates the amount of link bandwidth allocated to the corresponding VTN. The bandwidth allocated to a VTN can be exclusive for services carried in the corresponding VTN. The usage

of other TE attributes in topology-specific TLVs is for further study.

Editor's note: It is noted that carrying per-topology TE attributes was considered as a possible feature in future when the encoding of IS-IS multi-topology was defined in [[RFC5120](#)].

4. Forwarding Plane Operations

For SR-MPLS data plane, the Adj-SIDs and Prefix-SIDs associated with the same VTN can be used together to build SR-MPLS paths with the topological and resource constraints of the VTN taken into consideration. A Prefix-SID is associated with the paths calculated in the corresponding topology of the VTN. An outgoing interface is determined for each path. In addition, the resource-aware prefix-SID can steer the traffic to use the subset of network resources allocated to the VTN on the outgoing interface for packet forwarding. A forwarding entry is installed in the forwarding plane using the MPLS label that corresponds to the Prefix-SID associated with the topology corresponding to the VTN. A resource-aware Adj-SID is associated with a subset of network resources allocated to the VTN on the link it identifies, and can be used together with the prefix-SIDs of the same VTN to build SR-MPLS TE paths of the VTN.

For SRv6 data plane, the SRv6 SIDs associated with the same VTN can be used together to build SRv6 paths with the topological and resource constraints of the VTN taken into consideration. An SRv6 Locator is a prefix which is associated with the paths calculated in the corresponding topology of the VTN. An outgoing interface is determined for each path. In addition, the resource-aware SRv6 Locator prefix also steers the traffic to use the subset of network resources which are allocated to the VTN on the outgoing interface for packet forwarding. A forwarding entry for the SRv6 Locator prefix is installed in the forwarding plane for the topology corresponding to the VTN. A resource-aware End.X SID is associated with a subset of network resources allocated to the VTN on the link it identifies, and can be used together with other types of SRv6 SIDs of the same VTN to build SRv6 TE paths of the VTN.

5. Scalability Considerations

The mechanism described in this document assumes that each VTN is associated with a unique multi-topology, so that the MT-IDs can be reused to identify the VTNs in the control plane. While this brings the benefit of simplicity, it also has some limitations. For example, it means that even if multiple VTNs share the same topology, they would still need to be identified using different MT-IDs in the control plane, then independent path computation needs to be executed for each VTN. Thus the number of VTNs supported in a

network may be dependent on the number of topologies supported, which is related to both the number of topologies supported in the protocol and the control plane overhead which the network nodes could afford. The mechanism described in this document is applicable to network scenarios where the number of required VTN is relatively small. A detailed analysis about the VTN scalability and the possible optimizations for supporting a large number of VTNs is described in [[I-D.dong-teas-nrp-scalability](#)].

6. Security Considerations

This document introduces no additional security vulnerabilities to IS-IS.

The mechanism proposed in this document is subject to the same vulnerabilities as any other protocol that relies on IGPs.

7. IANA Considerations

This document does not request any IANA actions.

8. Acknowledgments

The authors would like to thank Zhibo Hu, Dean Cheng, Les Ginsberg and Peter Psenak for the review and discussion of this document.

9. References

9.1. Normative References

[I-D.ietf-lsr-isis-srv6-extensions]

Psenak, P., Filsfils, C., Bashandy, A., Decraene, B., and Z. Hu, "IS-IS Extensions to Support Segment Routing over IPv6 Dataplane", Work in Progress, Internet-Draft, draft-ietf-lsr-isis-srv6-extensions-18, 20 October 2021, <<https://www.ietf.org/archive/id/draft-ietf-lsr-isis-srv6-extensions-18.txt>>.

[I-D.ietf-spring-resource-aware-segments]

Dong, J., Bryant, S., Miyasaka, T., Zhu, Y., Qin, F., Li, Z., and F. Clad, "Introducing Resource Awareness to SR Segments", Work in Progress, Internet-Draft, draft-ietf-spring-resource-aware-segments-04, 5 March 2022, <<https://www.ietf.org/archive/id/draft-ietf-spring-resource-aware-segments-04.txt>>.

[I-D.ietf-spring-sr-for-enhanced-vpn]

Dong, J., Bryant, S., Miyasaka, T., Zhu, Y., Qin, F., Li, Z., and F. Clad, "Segment Routing based Virtual Transport Network (VTN) for Enhanced VPN", Work in Progress,

Internet-Draft, draft-ietf-spring-sr-for-enhanced-vpn-02, 5 March 2022, <<https://www.ietf.org/archive/id/draft-ietf-spring-sr-for-enhanced-vpn-02.txt>>.

- [RFC5120] Przygienda, T., Shen, N., and N. Sheth, "M-ISIS: Multi Topology (MT) Routing in Intermediate System to Intermediate Systems (IS-ISs)", RFC 5120, DOI 10.17487/RFC5120, February 2008, <<https://www.rfc-editor.org/info/rfc5120>>.
- [RFC5305] Li, T. and H. Smit, "IS-IS Extensions for Traffic Engineering", RFC 5305, DOI 10.17487/RFC5305, October 2008, <<https://www.rfc-editor.org/info/rfc5305>>.
- [RFC8402] Filsfils, C., Ed., Previdi, S., Ed., Ginsberg, L., Decraene, B., Litkowski, S., and R. Shakir, "Segment Routing Architecture", RFC 8402, DOI 10.17487/RFC8402, July 2018, <<https://www.rfc-editor.org/info/rfc8402>>.
- [RFC8570] Ginsberg, L., Ed., Previdi, S., Ed., Giacalone, S., Ward, D., Drake, J., and Q. Wu, "IS-IS Traffic Engineering (TE) Metric Extensions", RFC 8570, DOI 10.17487/RFC8570, March 2019, <<https://www.rfc-editor.org/info/rfc8570>>.
- [RFC8667] Previdi, S., Ed., Ginsberg, L., Ed., Filsfils, C., Bashandy, A., Gredler, H., and B. Decraene, "IS-IS Extensions for Segment Routing", RFC 8667, DOI 10.17487/RFC8667, December 2019, <<https://www.rfc-editor.org/info/rfc8667>>.

9.2. Informative References

- [I-D.dong-lsr-sr-enhanced-vpn] Dong, J., Hu, Z., Li, Z., Tang, X., Pang, R., JooHeon, L., and S. Bryant, "IGP Extensions for Scalable Segment Routing based Enhanced VPN", Work in Progress, Internet-Draft, draft-dong-lsr-sr-enhanced-vpn-07, 29 January 2022, <<https://www.ietf.org/archive/id/draft-dong-lsr-sr-enhanced-vpn-07.txt>>.
- [I-D.dong-teas-nrp-scalability] Dong, J., Li, Z., Gong, L., Yang, G., Guichard, J. N., Mishra, G., Qin, F., Saad, T., and V. P. Beeram, "Scalability Considerations for Network Resource Partition", Work in Progress, Internet-Draft, draft-dong-teas-nrp-scalability-02, 16 May 2022, <<https://www.ietf.org/archive/id/draft-dong-teas-nrp-scalability-02.txt>>.
- [I-D.ietf-teas-enhanced-vpn] Dong, J., Bryant, S., Li, Z., Miyasaka, T., and Y. Lee, "A Framework for Enhanced Virtual Private

Network (VPN+) Services", Work in Progress, Internet-Draft, draft-ietf-teas-enhanced-vpn-10, 6 March 2022, <<https://www.ietf.org/archive/id/draft-ietf-teas-enhanced-vpn-10.txt>>.

Authors' Addresses

Chongfeng Xie
China Telecom
China Telecom Beijing Information Science & Technology, Beiqijia
Beijing
102209
China

Email: xiechf@chinatelecom.cn

Chenhao Ma
China Telecom
China Telecom Beijing Information Science & Technology, Beiqijia
Beijing
102209
China

Email: machh@chinatelecom.cn

Jie Dong
Huawei Technologies
Huawei Campus, No. 156 Beiqing Road
Beijing
100095
China

Email: jie.dong@huawei.com

Zhenbin Li
Huawei Technologies
Huawei Campus, No. 156 Beiqing Road
Beijing
100095
China

Email: lizhenbin@huawei.com