

Network Working Group
Internet-Draft
Intended status: Standards Track
Expires: March 31, 2019

K. Patel
Arrcus, Inc.
A. Lindem
Cisco Systems
S. Zandi
Linkedin
W. Henderickx
Nokia
September 27, 2018

**Shortest Path Routing Extensions for BGP Protocol
draft-ietf-lsvr-bgp-spf-03.txt**

Abstract

Many Massively Scaled Data Centers (MSDCs) have converged on simplified layer 3 routing. Furthermore, requirements for operational simplicity have lead many of these MSDCs to converge on BGP as their single routing protocol for both their fabric routing and their Data Center Interconnect (DCI) routing. This document describes a solution which leverages BGP Link-State distribution and the Shortest Path First (SPF) algorithm similar to Internal Gateway Protocols (IGPs) such as OSPF.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on March 31, 2019.

Copyright Notice

Copyright (c) 2018 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

This document may contain material from IETF Documents or IETF Contributions published or made publicly available before November 10, 2008. The person(s) controlling the copyright in some of this material may not have granted the IETF Trust the right to allow modifications of such material outside the IETF Standards Process. Without obtaining an adequate license from the person(s) controlling the copyright in such materials, this document may not be modified outside the IETF Standards Process, and derivative works of it may not be created outside the IETF Standards Process, except to format it for publication as an RFC or to translate it into languages other than English.

Table of Contents

1.	Introduction	3
1.1.	BGP Shortest Path First (SPF) Motivation	4
1.2.	Requirements Language	5
2.	BGP Peering Models	5
2.1.	BGP Single-Hop Peering on Network Node Connections	5
2.2.	BGP Peering Between Directly Connected Network Nodes	6
2.3.	BGP Peering in Route-Reflector or Controller Topology	6
3.	BGP-LS Shortest Path Routing (SPF) SAFI	6
4.	Extensions to BGP-LS	7
4.1.	Node NLRI Usage and Modifications	7
4.2.	Link NLRI Usage	8
4.2.1.	BGP-LS Link NLRI Attribute Prefix-Length TLVs	9
4.3.	Prefix NLRI Usage	9
4.4.	BGP-LS Attribute Sequence-Number TLV	9
5.	Decision Process with SPF Algorithm	10
5.1.	Phase-1 BGP NLRI Selection	11
5.2.	Dual Stack Support	12
5.3.	SPF Calculation based on BGP-LS NLRI	12
5.4.	NEXT_HOP Manipulation	15
5.5.	IPv4/IPv6 Unicast Address Family Interaction	15
5.6.	NLRI Advertisement and Convergence	15
5.7.	Error Handling	16
6.	IANA Considerations	16
7.	Security Considerations	16

8.	Management Considerations	16
8.1.	Configuration	16
8.2.	Operational Data	16
9.	Acknowledgements	17
10.	Contributors	17
11.	References	17
11.1.	Normative References	17
11.2.	Information References	18
	Authors' Addresses	20

[1.](#) Introduction

Many Massively Scaled Data Centers (MSDCs) have converged on simplified layer 3 routing. Furthermore, requirements for operational simplicity have lead many of these MSDCs to converge on BGP [[RFC4271](#)] as their single routing protocol for both their fabric routing and their Data Center Interconnect (DCI) routing. Requirements and procedures for using BGP are described in [[RFC7938](#)]. This document describes an alternative solution which leverages BGP-LS [[RFC7752](#)] and the Shortest Path First algorithm similar to Internal Gateway Protocols (IGPs) such as OSPF [[RFC2328](#)].

[[RFC4271](#)] defines the Decision Process that is used to select routes for subsequent advertisement by applying the policies in the local Policy Information Base (PIB) to the routes stored in its Adj-RIBs-In. The output of the Decision Process is the set of routes that are announced by a BGP speaker to its peers. These selected routes are stored by a BGP speaker in the speaker's Adj-RIBs-Out according to policy.

[[RFC7752](#)] describes a mechanism by which link-state and TE information can be collected from networks and shared with external components using BGP. This is achieved by defining NLRI advertised within the BGP-LS/BGP-LS-SPF AFI/SAFI. The BGP-LS extensions defined in [[RFC7752](#)] makes use of the Decision Process defined in [[RFC4271](#)].

This document augments [[RFC7752](#)] by replacing its use of the existing Decision Process. Rather than reusing the BGP-LS SAFI, the BGP-LS-SPF SAFI is introduced to insure backward compatibility. The Phase 1 and 2 decision functions of the Decision Process are replaced with the Shortest Path First (SPF) algorithm also known as the Dijkstra algorithm. The Phase 3 decision function is also simplified since it is no longer dependent on the previous phases. This solution avails the benefits of both BGP and SPF-based IGPs. These include TCP based flow-control, no periodic link-state refresh, and completely incremental NLRI advertisement. These advantages can reduce the overhead in MSDCs where there is a high degree of Equal Cost Multi-Path (ECMPs) and the topology is very stable. Additionally, using a

SPF-based computation can support fast convergence and the computation of Loop-Free Alternatives (LFAs) [[RFC5286](#)] in the event of link failures. Furthermore, a BGP based solution lends itself to multiple peering models including those incorporating route-reflectors [[RFC4456](#)] or controllers.

Support for Multiple Topology Routing (MTR) as described in [[RFC4915](#)] is an area for further study dependent on deployment requirements.

1.1. BGP Shortest Path First (SPF) Motivation

Given that [[RFC7938](#)] already describes how BGP could be used as the sole routing protocol in an MSDC, one might question the motivation for defining an alternate BGP deployment model when a mature solution exists. For both alternatives, BGP offers the operational benefits of a single routing protocol. However, BGP SPF offers some unique advantages above and beyond standard BGP distance-vector routing.

A primary advantage is that all BGP speakers in the BGP SPF routing domain will have a complete view of the topology. This will allow support for ECMP, IP fast-reroute (e.g., Loop-Free Alternatives), Shared Risk Link Groups (SRLGs), and other routing enhancements without advertisement of additional BGP paths or other extensions. In short, the advantages of an IGP such as OSPF [[RFC2328](#)] are available in BGP.

With the simplified BGP decision process as defined in [Section 5.1](#), NLRI changes can be disseminated throughout the BGP routing domain much more rapidly (equivalent to IGPs with the proper implementation).

Another primary advantage is a potential reduction in NLRI advertisement. With standard BGP distance-vector routing, a single link failure may impact 100s or 1000s of prefixes and result in the withdrawal or re-advertisement of the attendant NLRI. With BGP SPF, only the BGP speakers corresponding to the link NLRI need withdraw the corresponding BGP-LS Link NLRI. This advantage will contribute to both faster convergence and better scaling.

With controller and route-reflector peering models, BGP SPF advertisement and distributed computation require a minimal number of sessions and copies of the NLRI since only the latest version of the NLRI from the originator is required. Given that verification of the adjacencies is done outside of BGP (see [Section 2](#)), each BGP speaker will only need as many sessions and copies of the NLRI as required for redundancy (e.g., one for the SPF computation and another for backup). Functions such as Optimized Route Reflection (ORR) are supported without extension by virtue of the primary advantages.

Additionally, a controller could inject topology that is learned outside the BGP routing domain.

Given that controllers are already consuming BGP-LS NLRI [[RFC7752](#)], reusing for the BGP-LS SPF leverages the existing controller implementations.

Another potential advantage of BGP SPF is that both IPv6 and IPv4 can be supported in the same address family using the same topology. Although not described in this version of the document, multi-topology extensions can be used to support separate IPv4, IPv6, unicast, and multicast topologies while sharing the same NLRI.

Finally, the BGP SPF topology can be used as an underlay for other BGP address families (using the existing model) and realize all the above advantages. A simplified peering model using IPv6 link-local addresses as next-hops can be deployed similar to [[RFC5549](#)].

[1.2.](#) Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [BCP 14](#) [[RFC2119](#)] [[RFC8174](#)] when, and only when, they appear in all capitals, as shown here.

[2.](#) BGP Peering Models

Depending on the requirements, scaling, and capabilities of the BGP speakers, various peering models are supported. The only requirement is that all BGP speakers in the BGP SPF routing domain receive link-state NLRI on a timely basis, run an SPF calculation, and update their data plane appropriately. The content of the Link NLRI is described in [Section 4.2](#).

[2.1.](#) BGP Single-Hop Peering on Network Node Connections

The simplest peering model is the one described in [section 5.2.1 of \[RFC7938\]](#). In this model, EBGP single-hop sessions are established over direct point-to-point links interconnecting the SPF domain nodes. For the purposes of BGP SPF, Link NLRI is only advertised if a single-hop BGP session has been established and the Link-State/SPF address family capability has been exchanged [[RFC4790](#)] on the corresponding session. If the session goes down, the corresponding Link NLRI will be withdrawn. Topologically, this would be equivalent to the peering model in [[RFC7938](#)] where there is a BGP session on every link in the data center switch fabric.

2.2. BGP Peering Between Directly Connected Network Nodes

In this model, BGP speakers peer with all directly connected network nodes but the sessions may be multi-hop and the direct connection discovery and liveness detection for those connections are independent of the BGP protocol. How this is accomplished is outside the scope of this document. Consequently, there will be a single session even if there are multiple direct connections between BGP speakers. For the purposes of BGP SPF, Link NLRI is advertised as long as a BGP session has been established, the Link-State/SPF address family capability has been exchanged [[RFC4790](#)] and the corresponding link is considered up and considered operational. This is much like the previous peering model only peering is on a single loopback address and the switch fabric links can be unnumbered. However, there will be the same unnumber of sessions as with the previous peering model unless there are parallel links between switches in the fabric.

2.3. BGP Peering in Route-Reflector or Controller Topology

In this model, BGP speakers peer solely with one or more Route Reflectors [[RFC4456](#)] or controllers. As in the previous model, direct connection discovery and liveness detection for those connections are done outside the BGP protocol. More specifically, the Liveness detection is done using BFD protocol described in [[RFC5880](#)]. For the purposes of BGP SPF, Link NLRI is advertised as long as the corresponding link is up and considered operational.

This peering model, known as sparse peering, allows for many fewer BGP sessions and, consequently, instances of the same NLRI received from multiple peers. It is discussed in greater detail in [[I-D.ietf-lsvr-applicability](#)].

3. BGP-LS Shortest Path Routing (SPF) SAFI

In order to replace the Phase 1 and 2 decision functions of the existing Decision Process with an SPF-based Decision Process and streamline the Phase 3 decision functions in a backward compatible manner, this draft introduces the BGP-LS-SFP SAFI for BGP-LS SPF operation. The BGP-LS-SPF (AF 16388 / SAFI TBD1) [[RFC4790](#)] is allocated by IANA as specified in the [Section 6](#). A BGP speaker using the BGP-LS SPF extensions described herein MUST exchange the AFI/SAFI using Multiprotocol Extensions Capability Code [[RFC4760](#)] with other BGP speakers in the SPF routing domain.

4. Extensions to BGP-LS

[RFC7752] describes a mechanism by which link-state and TE information can be collected from networks and shared with external components using BGP protocol. It describes both the definition of BGP-LS NLRI that describes links, nodes, and prefixes comprising IGP link-state information and the definition of a BGP path attribute (BGP-LS attribute) that carries link, node, and prefix properties and attributes, such as the link and prefix metric or auxiliary Router-IDs of nodes, etc.

The BGP protocol will be used in the Protocol-ID field specified in table 1 of [[I-D.ietf-idr-bgppls-segment-routing-epe](#)]. The local and remote node descriptors for all NLRI will be the BGP Router-ID (TLV 516) and either the AS Number (TLV 512) [[RFC7752](#)] or the BGP Confederation Member (TLV 517) [[RFC8402](#)]. However, if the BGP Router-ID is known to be unique within the BGP Routing domain, it can be used as the sole descriptor.

4.1. Node NLRI Usage and Modifications

The SPF capability is a new Node Attribute TLV that will be added to those defined in table 7 of [[RFC7752](#)]. The new attribute TLV will only be applicable when BGP is specified in the Node NLRI Protocol ID field. The TBD TLV type will be defined by IANA. The new Node Attribute TLV will contain a single-octet SPF algorithm as defined in [[RFC8402](#)].


```

      0               1               2               3
      0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|                                     |                                     |
|           Type                       Length                               |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
| SPF Algorithm |
+---+---+---+---+---+

```

The SPF Algorithm may take the following values:

- 0 - Normal Shortest Path First (SPF) algorithm based on link metric. This is the standard shortest path algorithm as computed by the IGP protocol. Consistent with the deployed practice for link-state protocols, Algorithm 0 permits any node to overwrite the SPF path with a different path based on its local policy.
- 1 - Strict Shortest Path First (SPF) algorithm based on link metric. The algorithm is identical to Algorithm 0 but Algorithm 1 requires that all nodes along the path will honor the SPF routing decision. Local policy at the node claiming support for Algorithm 1 MUST NOT alter the SPF paths computed by Algorithm 1.

Note that usage of Strict Shortest Path First (SPF) algorithm is defined in the IGP algorithm registry but usage is restricted to [\[I-D.ietf-idr-bgppls-segment-routing-epe\]](#). Hence, its usage for BGP-LS SPF is out of scope.

When computing the SPF for a given BGP routing domain, only BGP nodes advertising the SPF capability attribute will be included the Shortest Path Tree (SPT).

4.2. Link NLRI Usage

The criteria for advertisement of Link NLRI are discussed in [Section 2](#).

Link NLRI is advertised with local and remote node descriptors as described above and unique link identifiers dependent on the addressing. For IPv4 links, the links local IPv4 (TLV 259) and remote IPv4 (TLV 260) addresses will be used. For IPv6 links, the local IPv6 (TLV 261) and remote IPv6 (TLV 262) addresses will be used. For unnumbered links, the link local/remote identifiers (TLV 258) will be used. For links supporting having both IPv4 and IPv6 addresses, both sets of descriptors may be included in the same Link NLRI. The link identifiers are described in table 5 of [\[RFC7752\]](#).

The link IGP metric attribute TLV (TLV 1095) as well as any others required for non-SPF purposes SHOULD be advertised. Algorithms such

A new BGP-LS Attribute TLV to BGP-LS NLRI types is defined to assure the most recent version of a given NLRI is used in the SPF computation. The TBD TLV type will be defined by IANA. The new BGP-LS Attribute TLV will contain an 8-octet sequence number. The usage of the Sequence Number TLV is described in [Section 5.1](#).

The SPF based Decision process replaces the BGP best-path Decision process described in [RFC4271]. This process starts with selecting only those Node NLRI whose SPF capability TLV matches with the local

BGP speaker's SPF capability TLV value. Since Link-State NLRI always contains the local descriptor [[RFC7752](#)], it will only be originated by a single BGP speaker in the BGP routing domain. These selected Node NLRI and their Link/Prefix NLRI are used to build a directed graph during the SPF computation. The best paths for BGP prefixes are installed as a result of the SPF process.

When BGP-LS-SPF NLRI is received, all that is required is to determine whether it is the best-path by examining the Node-ID and sequence number as described in [Section 5.1](#). If the received best-path NLRI had changed, it will be advertised to other BGP-LS-SPF peers. If the attributes have changed (other than the sequence number), a BGP SPF calculation will be scheduled. However, a changed NLRI MAY be advertised to other peers almost immediately and propagation of changes can approach IGP convergence times. To accomplish this, the MinRouteAdvertisementIntervalTimer and MinASOriginationIntervalTimer [[RFC4271](#)] are not applicable to the BGP-LS-SPF SAFI. Rather, SPF calculations SHOULD be triggered and dampened consistent with the SPF backoff algorithm specified in [[RFC8405](#)].

The Phase 3 decision function of the Decision Process [[RFC4271](#)] is also simplified since under normal SPF operation, a BGP speaker would advertise the NLRI selected for the SPF to all BGP peers with the BGP-LS/BGP-LS-SPF AFI/SAFI. Application of policy would not be prevented however its usage to best-path process would be limited as the SPF relies solely on link metrics.

[5.1](#). Phase-1 BGP NLRI Selection

The rules for NLRI selection are greatly simplified from [[RFC4271](#)].

1. If the NLRI is received from the BGP speaker originating the NLRI (as determined by the comparing BGP Router ID in the NLRI Node identifiers with the BGP speaker Router ID), then it is preferred over the same NLRI from non-originators. This rule will assure that stale NLRI is updated even if a BGP-LS router loses its sequence number state due to a cold-start.
2. If the Sequence-Number TLV is present in the BGP-LS Attribute, then the NLRI with the most recent, i.e., highest sequence number is selected. BGP-LS NLRI with a Sequence-Number TLV will be considered more recent than NLRI without a BGP-LS Attribute or a BGP-LS Attribute that doesn't include the Sequence-Number TLV.
3. The final tie-breaker is the NLRI from the BGP Speaker with the numerically largest BGP Router ID.

When a BGP speaker completely loses its sequence number state, i.e., due to a cold start, or in the unlikely possibility that that sequence number wraps, the BGP routing domain will still converge. This is due to the fact that BGP speakers adjacent to the router will always accept self-originated NLRI from the associated speaker as more recent (rule # 1). When BGP speaker reestablishes a connection with its peers, any existing session will be taken down and stale NLRI will be replaced by the new NLRI and stale NLRI will be discarded independent of whether or not BGP graceful restart is deployed, [RFC4724]. The adjacent BGP speaker will update their NLRI advertisements in turn until the BGP routing domain has converged.

The modified SPF Decision Process performs an SPF calculation rooted at the BGP speaker using the metrics from Link and Prefix NLRI Attribute TLVs [RFC7752]. As a result, any attributes that would influence the Decision process defined in [RFC4271] like ORIGIN, MULTI_EXIT_DISC, and LOCAL_PREF attributes are ignored by the SPF algorithm. Furthermore, the NEXT_HOP attribute value is preserved but otherwise ignored during the SPF or best-path.

5.2. Dual Stack Support

The SPF-based decision process operates on Node, Link, and Prefix NLRIs that support both IPv4 and IPv6 addresses. Whether to run a single SPF instance or multiple SPF instances for separate AFs is a matter of a local implementation. Normally, IPv4 next-hops are calculated for IPv4 prefixes and IPv6 next-hops are calculated for IPv6 prefixes. However, an interesting use-case is deployment of [RFC5549] where IPv6 next-hops are calculated for both IPv4 and IPv6 prefixes. As stated in [Section 1](#), support for Multiple Topology Routing (MTR) is an area for future study.

5.3. SPF Calculation based on BGP-LS NLRI

This section details the BGP-LS SPF local routing information base (RIB) calculation. The router will use BGP-LS Node, Link, and Prefix NLRI to populate the local RIB using the following algorithm. This calculation yields the set of intra-area routes associated with the BGP-LS domain. A router calculates the shortest-path tree using itself as the root. Variations and optimizations of the algorithm are valid as long as it yields the same set of routes. The algorithm below supports Equal Cost Multi-Path (ECMP) routes. Weighted Unequal Cost Multi-Path are out of scope. The organization of this section owes heavily to [section 16 of \[RFC2328\]](#).

The following abstract data structures are defined in order to specify the algorithm.

- o Local Route Information Base (RIB) - This is abstract contains reachability information (i.e., next hops) for all prefixes (both IPv4 and IPv6) as well as the Node NLRI reachability. Implementations may choose to implement this as separate RIBs for each address family and/or Node NLRI.
- o Link State NLRI Database (LSNDB) - Database of BGP-LS NLRI that facilitates access to all Node, Link, and Prefix NLRI as well as all the Link and Prefix NLRI corresponding to a given Node NLRI. Other optimization, such as, resolving bi-directional connectivity associations between Link NLRI are possible but of scope of this document.
- o Candidate List - This is a list of candidate Node NLRI with the lowest cost Node NLRI at the front of the list. It is typically implemented as a heap but other concrete data structures have also been used.

The algorithm is comprised of the steps below:

1. The current local RIB is invalidated. The local RIB is built again from scratch. The existing routing entries are preserved for comparison to determine changes that need to be installed in the global RIB.
2. The computing router's Node NLRI is installed in the local RIB with a cost of 0 and as the sole entry in the candidate list.
3. The Node NLRI with the lowest cost is removed from the candidate list for processing. The Node corresponding to this NLRI will be referred to as the Current Node. If the candidate list is empty, the SPF calculation has completed and the algorithm proceeds to step 6.
4. All the Prefix NLRI with the same Node Identifiers as the Current Node will be considered for installation. The cost for each prefix is the metric advertised in the Prefix NLRI added to the cost to reach the Current Node.
 - * If the prefix is not in the local RIB, the prefix is installed and will inherit the Current Node's next hops.
 - * If the prefix is in the local RIB and the cost is greater than the Current route's metric, the Prefix NLRI does not contribute to the route and is ignored.
 - * If the prefix is in the local RIB and the cost is less than the current route's metric, the Prefix is installed with the

Current Node's next-hops replacing the local RIB route's next-hops and the metric being updated.

- * If the prefix is in the local RIB and the cost is same as the current route's metric, the Prefix is installed with the Current Node's next-hops being merged with local RIB route's next-hops.
5. All the Link NLRI with the same Node Identifiers as the Current Node will be considered for installation. Each link will be examined and will be referred to in the following text as the Current Link. The cost of the Current Link is the advertised metric in the Link NLRI added to the cost to reach the Current Node.
- * Optionally, the prefix(es) associated with the Current Link are installed into the local RIB using the same rules as were used for Prefix NLRI in the previous steps.
 - * The Current Link's endpoint Node NLRI is accessed (i.e., the Node NLRI with the same Node identifiers as the Link endpoint). If it exists, it will be referred to as the Endpoint Node NLRI and the algorithm will proceed as follows:
 - + All the Link NLRI corresponding the Endpoint Node NLRI will be searched for a back-link NLRI pointing to the current node. Both the Node identifiers and the Link endpoint identifiers in the Endpoint Node's Link NLRI must match for a match. If there is no corresponding Link NLRI corresponding to the Endpoint Node NLRI, the Endpoint Node NLIR fails the bi-directional connectivity test and is not processed further.
 - + If the Endpoint Node NLRI is not on the candidate list, it is inserted based on the link cost and BGP Identifier (the latter being used as a tie-breaker).
 - + If the Endpoint Node NLRI is already on the candidate list with a lower cost, it need not be inserted again.
 - + If the Endpoint Node NLRI is already on the candidate list with a higher cost, it must be removed and reinserted with a lower cost.
 - * Return to step 3 to process the next lowest cost Node NLRI on the candidate list.

6. The local RIB is examined and changes (adds, deletes, modifications) are installed into the global RIB.

5.4. NEXT_HOP Manipulation

A BGP speaker that supports SPF extensions MAY interact with peers that don't support SPF extensions. If the BGP-LS address family is advertised to a peer not supporting the SPF extensions described herein, then the BGP speaker MUST conform to the NEXT_HOP rules specified in [\[RFC4271\]](#) when announcing the Link-State address family routes to those peers.

All BGP peers that support SPF extensions would locally compute the Loc-RIB next-hops as a result of the SPF process. Consequently, the NEXT_HOP attribute is always ignored on receipt. However, BGP speakers SHOULD set the NEXT_HOP address according to the NEXT_HOP attribute rules specified in [\[RFC4271\]](#).

5.5. IPv4/IPv6 Unicast Address Family Interaction

While the BGP-LS SPF address family and the IPv4/IPv6 unicast address families install routes into the same device routing tables, they will operate independently much the same as OSPF and IS-IS would operate today (i.e., "Ships-in-the-Night" mode). There will be no implicit route redistribution between the BGP address families. However, implementation specific redistribution mechanisms SHOULD be made available with the restriction that redistribution of BGP-LS SPF routes into the IPv4 address family applies only to IPv4 routes and redistribution of BGP-LS SPF route into the IPv6 address family applies only to IPv6 routes.

Given the fact that SPF algorithms are based on the assumption that all routers in the routing domain calculate the precisely the same SPF tree and install the same set of routes, it is RECOMMENDED that BGP-LS SPF IPv4/IPv6 routes be given priority by default when installed into their respective RIBs. In common implementations the prioritization is governed by route preference or administrative distance with lower being more preferred.

5.6. NLRI Advertisement and Convergence

A local failure will prevent a link from being used in the SPF calculation due to the IGP bi-directional connectivity requirement. Consequently, local link failures should always be given priority over updates (e.g., withdrawing all routes learned on a session) in order to ensure the highest priority propagation and optimal convergence.

Delaying the withdrawal of non-local routes is an area for further study as more IGP-like mechanisms would be required to prevent usage of stale NLRI.

5.7. Error Handling

When a BGP speaker receives a BGP Update containing a malformed SPF Capability TLV in the Node NLRI BGP-LS Attribute [[RFC7752](#)], it MUST ignore the received TLV and the Node NLRI and not pass it to other BGP peers as specified in [[RFC7606](#)]. When discarding a Node NLRI with malformed TLV, a BGP speaker SHOULD log an error for further analysis.

6. IANA Considerations

This document defines an AFI/SAFI for BGP-LS SPF operation and requests IANA to assign the BGP-LS/BGP-LS-SPF (AFI 16388 / SAFI TBD1) as described in [[RFC4750](#)].

This document also defines four attribute TLVs for BGP LS NLRI. We request IANA to assign TLVs for the SPF capability, Sequence Number, IPv4 Link Prefix-Length, and IPv6 Link Prefix-Length from the "BGP-LS Node Descriptor, Link Descriptor, Prefix Descriptor, and Attribute TLVs" Registry.

7. Security Considerations

This extension to BGP does not change the underlying security issues inherent in the existing [[RFC4271](#)], [[RFC4724](#)], and [[RFC7752](#)].

8. Management Considerations

This section includes unique management considerations for the BGP-LS SPF address family.

8.1. Configuration

In addition to configuration of the BGP-LS SPF address family, implementations SHOULD support the configuratio of the INITIAL_SPF_DELAY, SHORT_SPF_DELAY, LONG_SPF_DELAY, TIME_TO_LEARN, and HOLDDOWN_INTERVAL as documented in [[RFC8405](#)].

8.2. Operational Data

In order to troubleshoot SPF issues, implementations SHOULD support an SPF log including entries for previous SPF computations, Each SPF log entry would include the BGP-LS NLRI SPF triggering the SPF, SPF scheduled time, SPF start time, SPF end time, and SPF type if

different types of SPF are supported. Since the size of the log will be finite, implementations SHOULD also maintain counters for the total number of SPF computations of each type and the total number of SPF triggering events. Additionally, to troubleshoot SPF scheduling and backoff [[RFC8405](#)], the current SPF backoff state, remaining time-to-learn, remaining holddown, last trigger event time, last SPF time, and next SPF time should be available.

9. Acknowledgements

The authors would like to thank Sue Hares, Jorge Rabadan, Boris Hassanov, Dan Frost, and Fred Baker for their review and comments.

10. Contributors

In addition to the authors listed on the front page, the following co-authors have contributed to the document.

Derek Yeung
Arrcus, Inc.
derek@arrcus.com

Gunter Van De Velde
Nokia
gunter.van_de_velde@nokia.com

Abhay Roy
Cisco Systems
akr@cisco.com

Venu Venugopal
Cisco Systems
venuv@cisco.com

11. References

11.1. Normative References

- [I-D.ietf-idr-bgpls-segment-routing-epe]
Previdi, S., Filsfils, C., Patel, K., Ray, S., and J. Dong, "BGP-LS extensions for Segment Routing BGP Egress Peer Engineering", [draft-ietf-idr-bgpls-segment-routing-epe-15](#) (work in progress), March 2018.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.

- [RFC4271] Rekhter, Y., Ed., Li, T., Ed., and S. Hares, Ed., "A Border Gateway Protocol 4 (BGP-4)", [RFC 4271](#), DOI 10.17487/RFC4271, January 2006, <<https://www.rfc-editor.org/info/rfc4271>>.
- [RFC7606] Chen, E., Ed., Scudder, J., Ed., Mohapatra, P., and K. Patel, "Revised Error Handling for BGP UPDATE Messages", [RFC 7606](#), DOI 10.17487/RFC7606, August 2015, <<https://www.rfc-editor.org/info/rfc7606>>.
- [RFC7752] Gredler, H., Ed., Medved, J., Previdi, S., Farrel, A., and S. Ray, "North-Bound Distribution of Link-State and Traffic Engineering (TE) Information Using BGP", [RFC 7752](#), DOI 10.17487/RFC7752, March 2016, <<https://www.rfc-editor.org/info/rfc7752>>.
- [RFC7938] Lapukhov, P., Premji, A., and J. Mitchell, Ed., "Use of BGP for Routing in Large-Scale Data Centers", [RFC 7938](#), DOI 10.17487/RFC7938, August 2016, <<https://www.rfc-editor.org/info/rfc7938>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in [RFC 2119](#) Key Words", [BCP 14](#), [RFC 8174](#), DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.
- [RFC8402] Filsfils, C., Ed., Previdi, S., Ed., Ginsberg, L., Decraene, B., Litkowski, S., and R. Shakir, "Segment Routing Architecture", [RFC 8402](#), DOI 10.17487/RFC8402, July 2018, <<https://www.rfc-editor.org/info/rfc8402>>.
- [RFC8405] Decraene, B., Litkowski, S., Gredler, H., Lindem, A., Francois, P., and C. Bowers, "Shortest Path First (SPF) Back-Off Delay Algorithm for Link-State IGPs", [RFC 8405](#), DOI 10.17487/RFC8405, June 2018, <<https://www.rfc-editor.org/info/rfc8405>>.

11.2. Information References

- [I-D.ietf-lsvr-applicability]
Patel, K., Lindem, A., Zandi, S., and G. Dawra, "Usage and Applicability of Link State Vector Routing in Data Centers", [draft-ietf-lsvr-applicability-00](#) (work in progress), July 2018.
- [RFC2328] Moy, J., "OSPF Version 2", STD 54, [RFC 2328](#), DOI 10.17487/RFC2328, April 1998, <<https://www.rfc-editor.org/info/rfc2328>>.

- [RFC4456] Bates, T., Chen, E., and R. Chandra, "BGP Route Reflection: An Alternative to Full Mesh Internal BGP (IBGP)", [RFC 4456](#), DOI 10.17487/RFC4456, April 2006, <<https://www.rfc-editor.org/info/rfc4456>>.
- [RFC4724] Sangli, S., Chen, E., Fernando, R., Scudder, J., and Y. Rekhter, "Graceful Restart Mechanism for BGP", [RFC 4724](#), DOI 10.17487/RFC4724, January 2007, <<https://www.rfc-editor.org/info/rfc4724>>.
- [RFC4750] Joyal, D., Ed., Galecki, P., Ed., Giacalone, S., Ed., Coltun, R., and F. Baker, "OSPF Version 2 Management Information Base", [RFC 4750](#), DOI 10.17487/RFC4750, December 2006, <<https://www.rfc-editor.org/info/rfc4750>>.
- [RFC4760] Bates, T., Chandra, R., Katz, D., and Y. Rekhter, "Multiprotocol Extensions for BGP-4", [RFC 4760](#), DOI 10.17487/RFC4760, January 2007, <<https://www.rfc-editor.org/info/rfc4760>>.
- [RFC4790] Newman, C., Duerst, M., and A. Gulbrandsen, "Internet Application Protocol Collation Registry", [RFC 4790](#), DOI 10.17487/RFC4790, March 2007, <<https://www.rfc-editor.org/info/rfc4790>>.
- [RFC4915] Psenak, P., Mirtorabi, S., Roy, A., Nguyen, L., and P. Pillay-Esnault, "Multi-Topology (MT) Routing in OSPF", [RFC 4915](#), DOI 10.17487/RFC4915, June 2007, <<https://www.rfc-editor.org/info/rfc4915>>.
- [RFC5286] Atlas, A., Ed. and A. Zinin, Ed., "Basic Specification for IP Fast Reroute: Loop-Free Alternates", [RFC 5286](#), DOI 10.17487/RFC5286, September 2008, <<https://www.rfc-editor.org/info/rfc5286>>.
- [RFC5549] Le Faucheur, F. and E. Rosen, "Advertising IPv4 Network Layer Reachability Information with an IPv6 Next Hop", [RFC 5549](#), DOI 10.17487/RFC5549, May 2009, <<https://www.rfc-editor.org/info/rfc5549>>.
- [RFC5880] Katz, D. and D. Ward, "Bidirectional Forwarding Detection (BFD)", [RFC 5880](#), DOI 10.17487/RFC5880, June 2010, <<https://www.rfc-editor.org/info/rfc5880>>.

Authors' Addresses

Keyur Patel
Arrcus, Inc.

Email: keyur@arrcus.com

Acee Lindem
Cisco Systems
301 Midenhall Way
Cary, NC 27513
USA

Email: acee@cisco.com

Shawn Zandi
Linkedin
222 2nd Street
San Francisco, CA 94105
USA

Email: szandi@linkedin.com

Wim Henderickx
Nokia
Antwerp
Belgium

Email: wim.henderickx@nokia.com

