

Network Working Group
Internet-Draft
Intended status: Standards Track
Expires: September 25, 2020

K. Patel
Arrcus, Inc.
A. Lindem
Cisco Systems
S. Zandi
LinkedIn
W. Henderickx
Nokia
March 24, 2020

**Shortest Path Routing Extensions for BGP Protocol
draft-ietf-lsvr-bgp-spf-08**

Abstract

Many Massively Scaled Data Centers (MSDCs) have converged on simplified layer 3 routing. Furthermore, requirements for operational simplicity have led many of these MSDCs to converge on BGP as their single routing protocol for both their fabric routing and their Data Center Interconnect (DCI) routing. This document describes a solution which leverages BGP Link-State distribution and the Shortest Path First (SPF) algorithm similar to Internal Gateway Protocols (IGPs) such as OSPF.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on September 25, 2020.

Copyright Notice

Copyright (c) 2020 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	3
1.1.	BGP Shortest Path First (SPF) Motivation	4
1.2.	Requirements Language	5
2.	BGP Peering Models	5
2.1.	BGP Single-Hop Peering on Network Node Connections	5
2.2.	BGP Peering Between Directly Connected Network Nodes	5
2.3.	BGP Peering in Route-Reflector or Controller Topology	6
3.	BGP-LS Shortest Path Routing (SPF) SAFI	6
4.	Extensions to BGP-LS	6
4.1.	Node NLRI Usage	7
4.1.1.	Node NLRI Attribute SPF Capability TLV	7
4.1.2.	BGP-LS Node NLRI Attribute SPF Status TLV	8
4.2.	Link NLRI Usage	8
4.2.1.	BGP-LS Link NLRI Attribute Prefix-Length TLVs	9
4.2.2.	BGP-LS Link NLRI Attribute SPF Status TLV	9
4.3.	Prefix NLRI Usage	10
4.3.1.	BGP-LS Prefix NLRI Attribute SPF Status TLV	10
4.4.	BGP-LS Attribute Sequence-Number TLV	10
5.	Decision Process with SPF Algorithm	11
5.1.	Phase-1 BGP NLRI Selection	12
5.2.	Dual Stack Support	13
5.3.	SPF Calculation based on BGP-LS NLRI	13
5.4.	NEXT_HOP Manipulation	16
5.5.	IPv4/IPv6 Unicast Address Family Interaction	16
5.6.	NLRI Advertisement and Convergence	17
5.6.1.	Link/Prefix Failure Convergence	17
5.6.2.	Node Failure Convergence	17
5.7.	Error Handling	18
6.	IANA Considerations	18
7.	Security Considerations	18
8.	Management Considerations	18
8.1.	Configuration	18
8.2.	Operational Data	19
9.	Acknowledgements	19
10.	Contributors	19
11.	References	20

11.1.	Normative References	20
11.2.	Information References	21
Authors' Addresses	22

1. Introduction

Many Massively Scaled Data Centers (MSDCs) have converged on simplified layer 3 routing. Furthermore, requirements for operational simplicity have led many of these MSDCs to converge on BGP [[RFC4271](#)] as their single routing protocol for both their fabric routing and their Data Center Interconnect (DCI) routing. Requirements and procedures for using BGP are described in [[RFC7938](#)]. This document describes an alternative solution which leverages BGP-LS [[RFC7752](#)] and the Shortest Path First algorithm similar to Internal Gateway Protocols (IGPs) such as OSPF [[RFC2328](#)].

[[RFC4271](#)] defines the Decision Process that is used to select routes for subsequent advertisement by applying the policies in the local Policy Information Base (PIB) to the routes stored in its Adj-RIBs-In. The output of the Decision Process is the set of routes that are announced by a BGP speaker to its peers. These selected routes are stored by a BGP speaker in the speaker's Adj-RIBs-Out according to policy.

[[RFC7752](#)] describes a mechanism by which link-state and TE information can be collected from networks and shared with external components using BGP. This is achieved by defining NLRI advertised within the BGP-LS/BGP-LS-SPF AFI/SAFI. The BGP-LS extensions defined in [[RFC7752](#)] makes use of the Decision Process defined in [[RFC4271](#)].

This document augments [[RFC7752](#)] by replacing its use of the existing Decision Process. Rather than reusing the BGP-LS SAFI, the BGP-LS-SPF SAFI is introduced to insure backward compatibility. The Phase 1 and 2 decision functions of the Decision Process are replaced with the Shortest Path First (SPF) algorithm also known as the Dijkstra algorithm. The Phase 3 decision function is also simplified since it is no longer dependent on the previous phases. This solution avails the benefits of both BGP and SPF-based IGPs. These include TCP based flow-control, no periodic link-state refresh, and completely incremental NLRI advertisement. These advantages can reduce the overhead in MSDCs where there is a high degree of Equal Cost Multi-Path (ECMPs) and the topology is very stable. Additionally, using an SPF-based computation can support fast convergence and the computation of Loop-Free Alternatives (LFAs) [[RFC5286](#)] in the event of link failures. Furthermore, a BGP based solution lends itself to multiple peering models including those incorporating route-reflectors [[RFC4456](#)] or controllers.

Support for Multiple Topology Routing (MTR) as described in [\[RFC4915\]](#) is an area for further study dependent on deployment requirements.

[1.1.](#) BGP Shortest Path First (SPF) Motivation

Given that [\[RFC7938\]](#) already describes how BGP could be used as the sole routing protocol in an MSDC, one might question the motivation for defining an alternate BGP deployment model when a mature solution exists. For both alternatives, BGP offers the operational benefits of a single routing protocol. However, BGP SPF offers some unique advantages above and beyond standard BGP distance-vector routing.

A primary advantage is that all BGP speakers in the BGP SPF routing domain will have a complete view of the topology. This will allow support for ECMP, IP fast-reroute (e.g., Loop-Free Alternatives), Shared Risk Link Groups (SRLGs), and other routing enhancements without advertisement of additional BGP paths or other extensions. In short, the advantages of an IGP such as OSPF [\[RFC2328\]](#) are available in BGP.

With the simplified BGP decision process as defined in [Section 5.1](#), NLRI changes can be disseminated throughout the BGP routing domain much more rapidly (equivalent to IGPs with the proper implementation).

Another primary advantage is a potential reduction in NLRI advertisement. With standard BGP distance-vector routing, a single link failure may impact 100s or 1000s prefixes and result in the withdrawal or re-advertisement of the attendant NLRI. With BGP SPF, only the BGP speakers corresponding to the link NLRI need withdraw the corresponding BGP-LS Link NLRI. This advantage will contribute to both faster convergence and better scaling.

With controller and route-reflector peering models, BGP SPF advertisement and distributed computation require a minimal number of sessions and copies of the NLRI since only the latest version of the NLRI from the originator is required. Given that verification of the adjacencies is done outside of BGP (see [Section 2](#)), each BGP speaker will only need as many sessions and copies of the NLRI as required for redundancy (e.g., one for the SPF computation and another for backup). Functions such as Optimized Route Reflection (ORR) are supported without extension by virtue of the primary advantages. Additionally, a controller could inject topology that is learned outside the BGP routing domain.

Given that controllers are already consuming BGP-LS NLRI [\[RFC7752\]](#), reusing for the BGP-LS SPF leverages the existing controller implementations.

Another potential advantage of BGP SPF is that both IPv6 and IPv4 can be supported in the same address family using the same topology. Although not described in this version of the document, multi-topology extensions can be used to support separate IPv4, IPv6, unicast, and multicast topologies while sharing the same NLRI.

Finally, the BGP SPF topology can be used as an underlay for other BGP address families (using the existing model) and realize all the above advantages. A simplified peering model using IPv6 link-local addresses as next-hops can be deployed similar to [\[RFC5549\]](#).

1.2. Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [BCP 14](#) [\[RFC2119\]](#) [\[RFC8174\]](#) when, and only when, they appear in all capitals, as shown here.

2. BGP Peering Models

Depending on the requirements, scaling, and capabilities of the BGP speakers, various peering models are supported. The only requirement is that all BGP speakers in the BGP SPF routing domain receive link-state NLRI on a timely basis, run an SPF calculation, and update their data plane appropriately. The content of the Link NLRI is described in [Section 4.2](#).

2.1. BGP Single-Hop Peering on Network Node Connections

The simplest peering model is the one described in [section 5.2.1 of \[RFC7938\]](#). In this model, EBGP single-hop sessions are established over direct point-to-point links interconnecting the SPF domain nodes. For the purposes of BGP SPF, Link NLRI is only advertised if a single-hop BGP session has been established and the Link-State/SPF address family capability has been exchanged [\[RFC4790\]](#) on the corresponding session. If the session goes down, the corresponding Link NLRI will be withdrawn. Topologically, this would be equivalent to the peering model in [\[RFC7938\]](#) where there is a BGP session on every link in the data center switch fabric.

2.2. BGP Peering Between Directly Connected Network Nodes

In this model, BGP speakers peer with all directly connected network nodes but the sessions may be multi-hop and the direct connection discovery and liveness detection for those connections are independent of the BGP protocol. How this is accomplished is outside the scope of this document. Consequently, there will be a single

session even if there are multiple direct connections between BGP speakers. For the purposes of BGP SPF, Link NLRI is advertised as long as a BGP session has been established, the Link-State/SPF address family capability has been exchanged [[RFC4790](#)] and the corresponding link is considered up and considered operational. This is much like the previous peering model only peering is on a single loopback address and the switch fabric links can be unnumbered. However, there will be the same number of sessions as with the previous peering model unless there are parallel links between switches in the fabric.

2.3. BGP Peering in Route-Reflector or Controller Topology

In this model, BGP speakers peer solely with one or more Route Reflectors [[RFC4456](#)] or controllers. As in the previous model, direct connection discovery and liveness detection for those connections are done outside the BGP protocol. More specifically, the Liveness detection is done using BFD protocol described in [[RFC5880](#)]. For the purposes of BGP SPF, Link NLRI is advertised as long as the corresponding link is up and considered operational.

This peering model, known as sparse peering, allows for many fewer BGP sessions and, consequently, instances of the same NLRI received from multiple peers. It is discussed in greater detail in [[I-D.ietf-lsvr-applicability](#)].

3. BGP-LS Shortest Path Routing (SPF) SAFI

In order to replace the Phase 1 and 2 decision functions of the existing Decision Process with an SPF-based Decision Process and streamline the Phase 3 decision functions in a backward compatible manner, this draft introduces the BGP-LS-SPF SAFI for BGP-LS SPF operation. The BGP-LS-SPF (AFI 16388 / SAFI TBD1) [[RFC4790](#)] is allocated by IANA as specified in the [Section 6](#). A BGP speaker using the BGP-LS SPF extensions described herein MUST exchange the AFI/SAFI using Multiprotocol Extensions Capability Code [[RFC4760](#)] with other BGP speakers in the SPF routing domain.

4. Extensions to BGP-LS

[RFC7752] describes a mechanism by which link-state and TE information can be collected from networks and shared with external components using BGP protocol. It describes both the definition of BGP-LS NLRI that describes links, nodes, and prefixes comprising IGP link-state information and the definition of a BGP path attribute (BGP-LS attribute) that carries link, node, and prefix properties and attributes, such as the link and prefix metric or auxiliary Router-IDs of nodes, etc.

Note that usage of Strict Shortest Path First (SPF) algorithm is defined in the IGP algorithm registry but usage is restricted to [[I-D.ietf-idr-bgpls-segment-routing-epe](#)]. Hence, its usage for BGP-LS SPF is out of scope.

The link IGP metric attribute TLV (TLV 1095) as well as any others required for non-SPF purposes SHOULD be advertised. The metric value in this TLV is variable length dependent on specific protocol usage (refer to [section 3.3.2.4 in \[RFC7752\]](#)). For simplicity, the BGP-LS

SPF metric length will be 4 octets. Algorithms such as setting the metric inversely to the link speed as done in the OSPF MIB [[RFC4750](#)] MAY be supported. However, this is beyond the scope of this document.

4.2.1. BGP-LS Link NLRI Attribute Prefix-Length TLVs

Two BGP-LS Attribute TLVs to BGP-LS Link NLRI are defined to advertise the prefix length associated with the IPv4 and IPv6 link prefixes. The prefix length is used for the optional installation of prefixes corresponding to Link NLRI as defined in [Section 5.3](#).

```

      0                   1                   2                   3
      0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|           TBD IPv4 or IPv6 Type           |           Length           |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
| Prefix-Length |
+---+---+---+---+---+

```

Prefix-length - A one-octet length restricted to 1-32 for IPv4 Link NLRI endpoint prefixes and 1-128 for IPv6 Link NLRI endpoint prefixes.

4.2.2. BGP-LS Link NLRI Attribute SPF Status TLV

A BGP-LS Attribute TLV to BGP-LS Link NLRI is defined to indicate the status of the link with respect to the BGP SPF calculation. This will be used to expedite convergence for link failures as discussed in [Section 5.6.1](#). If the SPF Status TLV is not included with the Link NLRI, the link is considered up and available.

```

      0                   1                   2                   3
      0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|   TBD Type   |           Length           |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
| SPF Status   |
+---+---+---+---+---+

```

BGP Status Values: 0 - Reserved

1 - Link Unreachable with respect to BGP SPF

2-254 - Undefined

255 - Reserved

4.3. Prefix NLRI Usage

Prefix NLRI is advertised with a local node descriptor as described above and the prefix and length used as the descriptors (TLV 265) as described in [\[RFC7752\]](#). The prefix metric attribute TLV (TLV 1155) as well as any others required for non-SPF purposes SHOULD be advertised. For loopback prefixes, the metric should be 0. For non-loopback prefixes, the setting of the metric is a local matter and beyond the scope of this document.

4.3.1. BGP-LS Prefix NLRI Attribute SPF Status TLV

A BGP-LS Attribute TLV to BGP-LS Prefix NLRI is defined to indicate the status of the prefix with respect to the BGP SPF calculation. This will be used to expedite convergence for prefix unreachability as discussed in [Section 5.6.1](#). If the SPF Status TLV is not included with the Prefix NLRI, the prefix is considered reachable.

```

      0                   1                   2                   3
    0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|   TBD Type   |                                     Length       |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|  SPF Status  |
+---+---+---+---+---+

```

BGP Status Values: 0 - Reserved

1 - Prefix down with respect to SPF

2-254 - Undefined

255 - Reserved

4.4. BGP-LS Attribute Sequence-Number TLV

A new BGP-LS Attribute TLV to BGP-LS NLRI types is defined to assure the most recent version of a given NLRI is used in the SPF computation. The TBD TLV type will be defined by IANA. The new BGP-LS Attribute TLV will contain an 8-octet sequence number. The usage of the Sequence Number TLV is described in [Section 5.1](#).

The SPF based Decision process replaces the BGP best-path Decision process described in [RFC4271]. This process starts with selecting only those Node NLRI whose SPF capability TLV matches with the local

BGP speaker's SPF capability TLV value. Since Link-State NLRI always contains the local descriptor [[RFC7752](#)], it will only be originated by a single BGP speaker in the BGP routing domain. These selected Node NLRI and their Link/Prefix NLRI are used to build a directed graph during the SPF computation. The best paths for BGP prefixes are installed as a result of the SPF process.

When BGP-LS-SPF NLRI is received, all that is required is to determine whether it is the best-path by examining the Node-ID and sequence number as described in [Section 5.1](#). If the received best-path NLRI had changed, it will be advertised to other BGP-LS-SPF peers. If the attributes have changed (other than the sequence number), a BGP SPF calculation will be scheduled. However, a changed NLRI MAY be advertised to other peers almost immediately and propagation of changes can approach IGP convergence times. To accomplish this, the MinRouteAdvertisementIntervalTimer and MinASOriginationIntervalTimer [[RFC4271](#)] are not applicable to the BGP-LS-SPF SAFI. Rather, SPF calculations SHOULD be triggered and dampened consistent with the SPF back-off algorithm specified in [[RFC8405](#)].

The Phase 3 decision function of the Decision Process [[RFC4271](#)] is also simplified since under normal SPF operation, a BGP speaker would advertise the NLRI selected for the SPF to all BGP peers with the BGP-LS/BGP-LS-SPF AFI/SAFI. Application of policy would not be prevented however its usage to best-path process would be limited as the SPF relies solely on link metrics.

[5.1](#). Phase-1 BGP NLRI Selection

The rules for NLRI selection are greatly simplified from [[RFC4271](#)].

1. If the NLRI is received from the BGP speaker originating the NLRI (as determined by the comparing BGP Router ID in the NLRI Node identifiers with the BGP speaker Router ID), then it is preferred over the same NLRI from non-originators. This rule will assure that stale NLRI is updated even if a BGP-LS router loses its sequence number state due to a cold-start.
2. If the Sequence-Number TLV is present in the BGP-LS Attribute, then the NLRI with the most recent, i.e., highest sequence number is selected. BGP-LS NLRI with a Sequence-Number TLV will be considered more recent than NLRI without a BGP-LS Attribute or a BGP-LS Attribute that doesn't include the Sequence-Number TLV.
3. The final tie-breaker is the NLRI from the BGP Speaker with the numerically largest BGP Router ID.

When a BGP speaker completely loses its sequence number state, i.e., due to a cold start, or in the unlikely possibility that that sequence number wraps, the BGP routing domain will still converge. This is due to the fact that BGP speakers adjacent to the router will always accept self-originated NLRI from the associated speaker as more recent (rule # 1). When BGP speaker reestablishes a connection with its peers, any existing session will be taken down and stale NLRI will be replaced by the new NLRI and stale NLRI will be discarded independent of whether or not BGP graceful restart is deployed, [RFC4724]. The adjacent BGP speaker will update their NLRI advertisements in turn until the BGP routing domain has converged.

The modified SPF Decision Process performs an SPF calculation rooted at the BGP speaker using the metrics from Link and Prefix NLRI Attribute TLVs [RFC7752]. As a result, any attributes that would influence the Decision process defined in [RFC4271] like ORIGIN, MULTI_EXIT_DISC, and LOCAL_PREF attributes are ignored by the SPF algorithm. Furthermore, the NEXT_HOP attribute value is preserved but otherwise ignored during the SPF or best-path.

5.2. Dual Stack Support

The SPF-based decision process operates on Node, Link, and Prefix NLRIs that support both IPv4 and IPv6 addresses. Whether to run a single SPF instance or multiple SPF instances for separate AFs is a matter of a local implementation. Normally, IPv4 next-hops are calculated for IPv4 prefixes and IPv6 next-hops are calculated for IPv6 prefixes. However, an interesting use-case is deployment of [RFC5549] where IPv6 next-hops are calculated for both IPv4 and IPv6 prefixes. As stated in [Section 1](#), support for Multiple Topology Routing (MTR) is an area for future study.

5.3. SPF Calculation based on BGP-LS NLRI

This section details the BGP-LS SPF local routing information base (RIB) calculation. The router will use BGP-LS Node, Link, and Prefix NLRI to populate the local RIB using the following algorithm. This calculation yields the set of intra-area routes associated with the BGP-LS domain. A router calculates the shortest-path tree using itself as the root. Variations and optimizations of the algorithm are valid as long as it yields the same set of routes. The algorithm below supports Equal Cost Multi-Path (ECMP) routes. Weighted Unequal Cost Multi-Path are out of scope. The organization of this section owes heavily to [section 16 of \[RFC2328\]](#).

The following abstract data structures are defined in order to specify the algorithm.

- o Local Route Information Base (RIB) - This is abstract contains reachability information (i.e., next hops) for all prefixes (both IPv4 and IPv6) as well as the Node NLRI reachability. Implementations may choose to implement this as separate RIBs for each address family and/or Node NLRI.
- o Link State NLRI Database (LSNDB) - Database of BGP-LS NLRI that facilitates access to all Node, Link, and Prefix NLRI as well as all the Link and Prefix NLRI corresponding to a given Node NLRI. Other optimization, such as, resolving bi-directional connectivity associations between Link NLRI are possible but of scope of this document.
- o Candidate List - This is a list of candidate Node NLRI with the lowest cost Node NLRI at the front of the list. It is typically implemented as a heap but other concrete data structures have also been used.

The algorithm is comprised of the steps below:

1. The current local RIB is invalidated. The local RIB is rebuilt during the course of the SPF computation. The existing routing entries are preserved for comparison to determine changes that need to be installed in the global RIB.
2. The computing router's Node NLRI is installed in the local RIB with a cost of 0 and as the sole entry in the candidate list.
3. The Node NLRI with the lowest cost is removed from the candidate list for processing. If the BGP-LS Node attribute includes an SPF Status TLV ([Section 4.1.2](#)) indicating the node is unreachable, the Node NLRI is ignored and the next lowest cost Node NLRI is selected from candidate list. The Node corresponding to this NLRI will be referred to as the Current Node. If the candidate list is empty, the SPF calculation has completed and the algorithm proceeds to step 6.
4. All the Prefix NLRI with the same Node Identifiers as the Current Node will be considered for installation. The cost for each prefix is the metric advertised in the Prefix NLRI added to the cost to reach the Current Node.
 - * If the BGP-LS Prefix attribute includes an SPF Status TLV indicating the prefix is unreachable, the BGP-LS Prefix NLRI is considered unreachable and the next BGP-LS Prefix NLRI is examined.

- * If the prefix is in the local RIB and the cost is greater than the Current route's metric, the Prefix NLRI does not contribute to the route and is ignored.
 - * If the prefix is in the local RIB and the cost is less than the current route's metric, the Prefix is installed with the Current Node's next-hops replacing the local RIB route's next-hops and the metric being updated.
 - * If the prefix is in the local RIB and the cost is same as the current route's metric, the Prefix is installed with the Current Node's next-hops being merged with local RIB route's next-hops.
5. All the Link NLRI with the same Node Identifiers as the Current Node will be considered for installation. Each link will be examined and will be referred to in the following text as the Current Link. The cost of the Current Link is the advertised metric in the Link NLRI added to the cost to reach the Current Node.
- * Optionally, the prefix(es) associated with the Current Link are installed into the local RIB using the same rules as were used for Prefix NLRI in the previous steps.
 - * If the current Node NLRI attributes includes the SPF status TLV ([Section 4.1.2](#)) and the status indicates that the Node doesn't support transit, the next link for the current node is processed.
 - * The Current Link's endpoint Node NLRI is accessed (i.e., the Node NLRI with the same Node identifiers as the Link endpoint). If it exists, it will be referred to as the Endpoint Node NLRI and the algorithm will proceed as follows:
 - + If the BGP-LS Link NLRI attribute includes an SPF Status TLV indicating the link is down, the BGP-LS Link NLRI is considered down and the next BGP-LS Link NLRI is examined.
 - + All the Link NLRI corresponding the Endpoint Node NLRI will be searched for a back-link NLRI pointing to the current node. Both the Node identifiers and the Link endpoint identifiers in the Endpoint Node's Link NLRI must match for a match. If there is no corresponding Link NLRI corresponding to the Endpoint Node NLRI, the Endpoint Node NLRI fails the bi-directional connectivity test and is not processed further.

- + If the Endpoint Node NLRI is not on the candidate list, it is inserted based on the link cost and BGP Identifier (the latter being used as a tie-breaker).
 - + If the Endpoint Node NLRI is already on the candidate list with a lower cost, it need not be inserted again.
 - + If the Endpoint Node NLRI is already on the candidate list with a higher cost, it must be removed and reinserted with a lower cost.
- * Return to step 3 to process the next lowest cost Node NLRI on the candidate list.
6. The local RIB is examined and changes (adds, deletes, modifications) are installed into the global RIB.

5.4. NEXT_HOP Manipulation

A BGP speaker that supports SPF extensions MAY interact with peers that don't support SPF extensions. If the BGP-LS address family is advertised to a peer not supporting the SPF extensions described herein, then the BGP speaker MUST conform to the NEXT_HOP rules specified in [[RFC4271](#)] when announcing the Link-State address family routes to those peers.

All BGP peers that support SPF extensions would locally compute the Loc-RIB next-hops as a result of the SPF process. Consequently, the NEXT_HOP attribute is always ignored on receipt. However, BGP speakers SHOULD set the NEXT_HOP address according to the NEXT_HOP attribute rules specified in [[RFC4271](#)].

5.5. IPv4/IPv6 Unicast Address Family Interaction

While the BGP-LS SPF address family and the IPv4/IPv6 unicast address families install routes into the same device routing tables, they will operate independently much the same as OSPF and IS-IS would operate today (i.e., "Ships-in-the-Night" mode). There will be no implicit route redistribution between the BGP address families. However, implementation specific redistribution mechanisms SHOULD be made available with the restriction that redistribution of BGP-LS SPF routes into the IPv4 address family applies only to IPv4 routes and redistribution of BGP-LS SPF route into the IPv6 address family applies only to IPv6 routes.

Given the fact that SPF algorithms are based on the assumption that all routers in the routing domain calculate the precisely the same SPF tree and install the same set of routes, it is RECOMMENDED that

BGP-LS SPF IPv4/IPv6 routes be given priority by default when installed into their respective RIBs. In common implementations the prioritization is governed by route preference or administrative distance with lower being more preferred.

5.6. NLRI Advertisement and Convergence

5.6.1. Link/Prefix Failure Convergence

A local failure will prevent a link from being used in the SPF calculation due to the IGP bi-directional connectivity requirement. Consequently, local link failures should always be given priority over updates (e.g., withdrawing all routes learned on a session) in order to ensure the highest priority propagation and optimal convergence.

An IGP such as OSPF [[RFC2328](#)] will stop using the link as soon as the Router-LSA for one side of the link is received. With normal BGP advertisement, the link would continue to be used until the last copy of the BGP-LS Link NLRI is withdrawn. In order to avoid this delay, the originator of the Link NLRI will advertise a more recent version of the BGP-LS Link NLRI including the SPF Status TLV [Section 4.2.2](#) indicating the link is down with respect to BGP SPF. After some configurable period of time, e.g., 2-3 seconds, the BGP-LS Link NLRI can be withdrawn with no consequence. If the link becomes available in that period, the originator of the BGP-LS LINK NLRI will simply advertise a more recent version of the BGP-LS Link NLRI without the SPF Status TLV in the BGP-LS Link Attributes.

Similarly, when a prefix becomes unreachable, a more recent version of the BGP-LS Prefix NLRI will be advertised with the SPF Status TLV [Section 4.3.1](#) indicating the prefix is unreachable in the BGP-LS Prefix Attributes and the prefix will be considered unreachable with respect to BGP SPF. After some configurable period of time, e.g., 2-3 seconds, the BGP-LS Prefix NLRI can be withdrawn with no consequence. If the prefix becomes reachable in that period, the originator of the BGP-LS Prefix NLRI will simply advertise a more recent version of the BGP-LS Prefix NLRI without the SPF Status TLV in the BGP-LS Prefix Attributes.

5.6.2. Node Failure Convergence

With BGP without graceful restart [[RFC4724](#)], all the NLRI advertised by node are implicitly withdrawn when a session failure is detected. If fast failure detection such as BFD is utilized, and the node is on the fastest converging path, the most recent versions of BGP-LS NLRI may be withdrawn while these versions are in-flight on longer paths. This will result the older version of the NLRI being used until the

new versions arrive and, potentially, unnecessary route flaps. Therefore, BGP-LS SPF NLRI SHOULD always be retained before being implicitly withdrawn for a brief configurable interval, e.g., 2-3 seconds. This will not delay convergence since the adjacent nodes will detect the link failure and advertise a more recent NLRI indicating the link is down with respect to BGP SPF [Section 5.6.1](#) and the BGP-SPF calculation will failure the bi-directional connectivity check.

[5.7.](#) Error Handling

When a BGP speaker receives a BGP Update containing a malformed SPF Capability TLV in the Node NLRI BGP-LS Attribute [[RFC7752](#)], it MUST ignore the received TLV and the Node NLRI and not pass it to other BGP peers as specified in [[RFC7606](#)]. When discarding a Node NLRI with malformed TLV, a BGP speaker SHOULD log an error for further analysis.

[6.](#) IANA Considerations

This document defines an AFI/SAFI for BGP-LS SPF operation and requests IANA to assign the BGP-LS/BGP-LS-SPF (AFI 16388 / SAFI TBD1) as described in [[RFC4750](#)].

This document also defines five attribute TLVs for BGP-LS NLRI. We request IANA to assign types for the SPF capability TLV, Sequence Number TLV, IPv4 Link Prefix-Length TLV, IPv6 Link Prefix-Length TLV, and SPF Status TLV from the "BGP-LS Node Descriptor, Link Descriptor, Prefix Descriptor, and Attribute TLVs" Registry.

[7.](#) Security Considerations

This extension to BGP does not change the underlying security issues inherent in the existing [[RFC4271](#)], [[RFC4724](#)], and [[RFC7752](#)].

[8.](#) Management Considerations

This section includes unique management considerations for the BGP-LS SPF address family.

[8.1.](#) Configuration

In addition to configuration of the BGP-LS SPF address family, implementations SHOULD support the configuration of the INITIAL_SPF_DELAY, SHORT_SPF_DELAY, LONG_SPF_DELAY, TIME_TO_LEARN, and HOLDDOWN_INTERVAL as documented in [[RFC8405](#)].

8.2. Operational Data

In order to troubleshoot SPF issues, implementations SHOULD support an SPF log including entries for previous SPF computations. Each SPF log entry would include the BGP-LS NLRI SPF triggering the SPF, SPF scheduled time, SPF start time, SPF end time, and SPF type if different types of SPF are supported. Since the size of the log will be finite, implementations SHOULD also maintain counters for the total number of SPF computations of each type and the total number of SPF triggering events. Additionally, to troubleshoot SPF scheduling and back-off [[RFC8405](#)], the current SPF back-off state, remaining time-to-learn, remaining holddown, last trigger event time, last SPF time, and next SPF time should be available.

9. Acknowledgements

The authors would like to thank Sue Hares, Jorge Rabadan, Boris Hassanov, Dan Frost, Matt Anderson, and Fred Baker for their review and comments. Thanks to Chaitanya Yadlapalli and Pushpais Sarkar for discussions on preventing a BGP SPF Router from being used for non-local traffic (i.e., transit traffic).

The authors extend special thanks to Eric Rosen for fruitful discussions on BGP-LS SPF convergence as compared to IGP.

10. Contributors

In addition to the authors listed on the front page, the following co-authors have contributed to the document.

Derek Yeung
Arrcus, Inc.
derek@arrcus.com

Gunter Van De Velde
Nokia
gunter.van_de_velde@nokia.com

Abhay Roy
Cisco Systems
akr@cisco.com

Venu Venugopal
Cisco Systems
venuv@cisco.com

11. References

11.1. Normative References

- [I-D.ietf-idr-bgppls-segment-routing-epe]
Previdi, S., Talaulikar, K., Filsfils, C., Patel, K., Ray, S., and J. Dong, "BGP-LS extensions for Segment Routing BGP Egress Peer Engineering", [draft-ietf-idr-bgppls-segment-routing-epe-19](#) (work in progress), May 2019.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC4271] Rekhter, Y., Ed., Li, T., Ed., and S. Hares, Ed., "A Border Gateway Protocol 4 (BGP-4)", [RFC 4271](#), DOI 10.17487/RFC4271, January 2006, <<https://www.rfc-editor.org/info/rfc4271>>.
- [RFC7606] Chen, E., Ed., Scudder, J., Ed., Mohapatra, P., and K. Patel, "Revised Error Handling for BGP UPDATE Messages", [RFC 7606](#), DOI 10.17487/RFC7606, August 2015, <<https://www.rfc-editor.org/info/rfc7606>>.
- [RFC7752] Gredler, H., Ed., Medved, J., Previdi, S., Farrel, A., and S. Ray, "North-Bound Distribution of Link-State and Traffic Engineering (TE) Information Using BGP", [RFC 7752](#), DOI 10.17487/RFC7752, March 2016, <<https://www.rfc-editor.org/info/rfc7752>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in [RFC 2119](#) Key Words", [BCP 14](#), [RFC 8174](#), DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.
- [RFC8402] Filsfils, C., Ed., Previdi, S., Ed., Ginsberg, L., Decraene, B., Litkowski, S., and R. Shakir, "Segment Routing Architecture", [RFC 8402](#), DOI 10.17487/RFC8402, July 2018, <<https://www.rfc-editor.org/info/rfc8402>>.
- [RFC8405] Decraene, B., Litkowski, S., Gredler, H., Lindem, A., Francois, P., and C. Bowers, "Shortest Path First (SPF) Back-Off Delay Algorithm for Link-State IGPs", [RFC 8405](#), DOI 10.17487/RFC8405, June 2018, <<https://www.rfc-editor.org/info/rfc8405>>.

11.2. Information References

- [I-D.ietf-lsvr-applicability]
Patel, K., Lindem, A., Zandi, S., and G. Dawra, "Usage and Applicability of Link State Vector Routing in Data Centers", [draft-ietf-lsvr-applicability-04](#) (work in progress), November 2019.
- [RFC2328] Moy, J., "OSPF Version 2", STD 54, [RFC 2328](#), DOI 10.17487/RFC2328, April 1998, <<https://www.rfc-editor.org/info/rfc2328>>.
- [RFC4456] Bates, T., Chen, E., and R. Chandra, "BGP Route Reflection: An Alternative to Full Mesh Internal BGP (IBGP)", [RFC 4456](#), DOI 10.17487/RFC4456, April 2006, <<https://www.rfc-editor.org/info/rfc4456>>.
- [RFC4724] Sangli, S., Chen, E., Fernando, R., Scudder, J., and Y. Rekhter, "Graceful Restart Mechanism for BGP", [RFC 4724](#), DOI 10.17487/RFC4724, January 2007, <<https://www.rfc-editor.org/info/rfc4724>>.
- [RFC4750] Joyal, D., Ed., Galecki, P., Ed., Giacalone, S., Ed., Coltun, R., and F. Baker, "OSPF Version 2 Management Information Base", [RFC 4750](#), DOI 10.17487/RFC4750, December 2006, <<https://www.rfc-editor.org/info/rfc4750>>.
- [RFC4760] Bates, T., Chandra, R., Katz, D., and Y. Rekhter, "Multiprotocol Extensions for BGP-4", [RFC 4760](#), DOI 10.17487/RFC4760, January 2007, <<https://www.rfc-editor.org/info/rfc4760>>.
- [RFC4790] Newman, C., Duerst, M., and A. Gulbrandsen, "Internet Application Protocol Collation Registry", [RFC 4790](#), DOI 10.17487/RFC4790, March 2007, <<https://www.rfc-editor.org/info/rfc4790>>.
- [RFC4915] Psenak, P., Mirtorabi, S., Roy, A., Nguyen, L., and P. Pillay-Esnault, "Multi-Topology (MT) Routing in OSPF", [RFC 4915](#), DOI 10.17487/RFC4915, June 2007, <<https://www.rfc-editor.org/info/rfc4915>>.
- [RFC5286] Atlas, A., Ed. and A. Zinin, Ed., "Basic Specification for IP Fast Reroute: Loop-Free Alternates", [RFC 5286](#), DOI 10.17487/RFC5286, September 2008, <<https://www.rfc-editor.org/info/rfc5286>>.

- [RFC5549] Le Faucheur, F. and E. Rosen, "Advertising IPv4 Network Layer Reachability Information with an IPv6 Next Hop", [RFC 5549](#), DOI 10.17487/RFC5549, May 2009, <<https://www.rfc-editor.org/info/rfc5549>>.
- [RFC5880] Katz, D. and D. Ward, "Bidirectional Forwarding Detection (BFD)", [RFC 5880](#), DOI 10.17487/RFC5880, June 2010, <<https://www.rfc-editor.org/info/rfc5880>>.
- [RFC7938] Lapukhov, P., Premji, A., and J. Mitchell, Ed., "Use of BGP for Routing in Large-Scale Data Centers", [RFC 7938](#), DOI 10.17487/RFC7938, August 2016, <<https://www.rfc-editor.org/info/rfc7938>>.

Authors' Addresses

Keyur Patel
Arrcus, Inc.

Email: keyur@arrcus.com

Acee Lindem
Cisco Systems
301 Midenhall Way
Cary, NC 27513
USA

Email: acee@cisco.com

Shawn Zandi
LinkedIn
222 2nd Street
San Francisco, CA 94105
USA

Email: szandi@linkedin.com

Wim Henderickx
Nokia
Antwerp
Belgium

Email: wim.henderickx@nokia.com

