

Internet Draft

Document:

[draft-ietf-magma-rfc2933-update-00.txt](#)

Expires: December 2002

J. Chesterfield,

Draft Editor

AT&T Labs - Research

June 2002

## **Internet Group Management Protocol MIB**

### Status of this Memo

This document is an Internet-Draft and is in full conformance with all provisions of [Section 10 of RFC2026](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at

<http://www.ietf.org/ietf/1id-abstracts.txt>

The list of Internet-Draft Shadow Directories can be accessed at

<http://www.ietf.org/shadow.html>.

### Abstract

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it describes objects used for managing the Internet Group Management Protocol (IGMP).

### Table of Contents

<a href="#"><u>1. Introduction</u></a> .....	<a href="#"><u>2</u></a>
<a href="#"><u>2. The SNMP Management Framework</u></a> .....	<a href="#"><u>2</u></a>
<a href="#"><u>3. Overview</u></a> .....	<a href="#"><u>3</u></a>
<a href="#"><u>4. Definitions</u></a> .....	<a href="#"><u>3</u></a>
<a href="#"><u>5. Security Considerations</u></a> .....	<a href="#"><u>17</u></a>
<a href="#"><u>6. Contributors</u></a> .....	<a href="#"><u>17</u></a>
<a href="#"><u>7. Acknowledgements</u></a> .....	<a href="#"><u>18</u></a>
<a href="#"><u>8. Author's Addresses</u></a> .....	<a href="#"><u>18</u></a>
<a href="#"><u>9. References</u></a> .....	<a href="#"><u>18</u></a>
<a href="#"><u>10. Full Copyright Statement</u></a> .....	<a href="#"><u>19</u></a>



## Internet Group Management Protocol MIB

### [1. Introduction](#)

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it describes objects used for managing the Internet Group Management Protocol (IGMP), version 1 [[17](#)], version 2 [[18](#)] or version 3 [[19](#)]. This version of the MIB is an update to [rfc2933](#) incorporating IGMPv3 changes to enable "source filtering" in routers and hosts. All of this MIB module is applicable to IPv4 multicast routers; a subset is applicable to hosts implementing IGMP. Since IGMP is specific to IPv4, this MIB does not support management of equivalent functionality for other address families, such as IPv6. Such management may be supported by other MIBs.

### [2. The SNMP Management Framework](#)

The SNMP Management Framework presently consists of five major components:

- . An overall architecture, described in [RFC 2571](#) [[RFC2571](#)].
- . Mechanisms for describing and naming objects and events for the purpose of management. The first version of this Structure of Management Information (SMI) is called SMIv1 and described in STD 16, [RFC 1155](#) [[1](#)], STD 16, [RFC 1212](#) [[3](#)] and [RFC 1215](#) [[4](#)]. The second version, called SMIv2, is described in STD 58, [RFC 2578](#) [[5](#)], STD 58, [RFC 2579](#) [[6](#)] and STD 58, [RFC 2580](#) [[7](#)].
- . Message protocols for transferring management information. The first version of the SNMP message protocol is called SNMPv1 and described in STD 15, [RFC 1157](#) [[8](#)]. A second version of the SNMP message protocol, which is not an Internet standards track protocol, is called SNMPv2c and described in [RFC 1901](#) [[9](#)] and [RFC 1906](#) [[10](#)]. The third version of the message protocol is called SNMPv3 and described in [RFC 1906](#) [[10](#)], [RFC 2572](#) [[11](#)] and [RFC 2574](#) [[12](#)].
- . Protocol operations for accessing management information. The first set of protocol operations and associated PDU formats is described in STD 15, [RFC 1157](#) [[8](#)]. A second set of protocol operations and associated PDU formats is described in [RFC 1905](#) [[13](#)].
- . A set of fundamental applications described in [RFC 2573](#) [[14](#)] and the view-based access control mechanism described in [RFC 2575](#) [[15](#)].

A more detailed introduction to the current SNMP Management Framework can be found in [RFC 2570](#) [[16](#)].

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. Objects in the MIB are defined using the mechanisms defined in the SMI.

## Internet Group Management Protocol MIB

This memo specifies a MIB module that is compliant to the SMIv2. A MIB conforming to the SMIv1 can be produced through the appropriate translations. The resulting translated MIB must be semantically equivalent, except where objects or events are omitted because no translation is possible (use of Counter64). Some machine readable information in SMIv2 will be converted into textual descriptions in SMIv1 during the translation process. However, this loss of machine readable information is not considered to change the semantics of the MIB.

### 3. Overview

This MIB module contains three tables:

1. the IGMP Interface Table which contains one row for each interface on which IGMP is enabled,
2. the IGMP Cache Table which contains one row for each IP multicast group for which there are members on a particular interface, and
3. the IGMP SrcList Table which contains one row for each entry in the source filter record for an interface and multicast group pair.

All tables are intended to be implemented by hosts and routers, but some columnar objects in the first and second tables apply only to routers.

### 4. Definitions

IGMP-STD-MIB DEFINITIONS ::= BEGIN

#### IMPORTS

```
MODULE-IDENTITY, OBJECT-TYPE, mib-2, Counter32, Gauge32,  
Unsigned32, IpAddress, TimeTicks FROM SNMPv2-SMI  
RowStatus, TruthValue FROM SNMPv2-TC  
MODULE-COMPLIANCE, OBJECT-GROUP FROM SNMPv2-CONF  
InterfaceIndexOrZero,  
InterfaceIndex FROM IF-MIB;
```

igmpStdMIB MODULE-IDENTITY

LAST-UPDATED "200206140000Z" -- June 14, 2002

ORGANIZATION "IETF MAGMA Working Group."

CONTACT-INFO

```
" Dave Thaler  
Microsoft Corporation  
One Microsoft Way  
Redmond, WA 98052-6399  
US
```

Phone: +1 425 703 8835  
EMail: dthaler@microsoft.com

Chesterfield    Internet Draft - Expires December 2002

[Page 3]

Internet Group Management Protocol MIB

Julian Chesterfield  
AT&T Research-Labs  
75 Willow Road  
Menlo Park, CA 94025  
US

Phone: +1 650 330 7762  
EMail: julian@research.att.com"

DESCRIPTION  
"The MIB module for IGMP Management."

REVISION "200009280000Z" -- September 28, 2000

DESCRIPTION  
"Initial version, published as [RFC 2933](#).?"

REVISION "200206140000Z" -- June 14, 2002

DESCRIPTION  
"[RFC 2933](#) revised 6/02 to incorporate IGMPv3 changes."

::= { mib-2 85 }

igmpMIBObjects OBJECT IDENTIFIER ::= { igmpStdMIB 1 }

--  
-- The IGMP Interface Table  
--

igmpInterfaceTable OBJECT-TYPE  
SYNTAX SEQUENCE OF IgmpInterfaceEntry  
MAX-ACCESS not-accessible  
STATUS current  
DESCRIPTION  
"The (conceptual) table listing the interfaces on which IGMP  
is enabled."  
 ::= { igmpMIBObjects 1 }

igmpInterfaceEntry OBJECT-TYPE  
SYNTAX IgmpInterfaceEntry  
MAX-ACCESS not-accessible  
STATUS current  
DESCRIPTION  
"An entry (conceptual row) representing an interface on  
which IGMP is enabled."  
INDEX { igmpInterfaceIfIndex }  
 ::= { igmpInterfaceTable 1 }

IgmpInterfaceEntry ::= SEQUENCE {

igmpInterfaceIfIndex	InterfaceIndex,
igmpInterfaceQueryInterval	Unsigned32,
igmpInterfaceStatus	RowStatus,
igmpInterfaceVersion	Unsigned32,
igmpInterfaceQuerier	IpAddress,

Internet Group Management Protocol MIB

```
igmpInterfaceQueryMaxResponseTime Unsigned32,
igmpInterfaceQuerierUpTime      TimeTicks,
igmpInterfaceQuerierExpiryTime   TimeTicks,
igmpInterfaceVersion1QuerierTimer TimeTicks,
igmpInterfaceWrongVersionQueries Counter32,
igmpInterfaceJoins              Counter32,
igmpInterfaceProxyIfIndex        InterfaceIndexOrZero,
igmpInterfaceGroups             Gauge32,
igmpInterfaceRobustness         Unsigned32,
igmpInterfaceLastMembQueryIntvl Unsigned32,
igmpInterfaceVersion2QuerierTimer TimeTicks
}
```

```
igmpInterfaceIfIndex OBJECT-TYPE
    SYNTAX      InterfaceIndex
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The ifIndex value of the interface for which IGMP is
         enabled."
::= { igmpInterfaceEntry 1 }
```

```
igmpInterfaceQueryInterval OBJECT-TYPE
    SYNTAX      Unsigned32
    UNITS      "seconds"
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The frequency at which IGMP Host-Query packets are
         transmitted on this interface."
    DEFVAL    { 125 }
::= { igmpInterfaceEntry 2 }
```

```
igmpInterfaceStatus OBJECT-TYPE
    SYNTAX      RowStatus
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The activation of a row enables IGMP on the interface.  The
         destruction of a row disables IGMP on the interface."
::= { igmpInterfaceEntry 3 }
```

```
igmpInterfaceVersion OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The version of IGMP which is running on this interface.
```

This object can be used to configure a router capable of running either value. For IGMP to function correctly, all routers on a LAN must be configured to run the same version of IGMP on that LAN."

DEFVAL { 2 }

Internet Group Management Protocol MIB

```
::= { igmpInterfaceEntry 4 }

igmpInterfaceQuerier OBJECT-TYPE
    SYNTAX      IpAddress
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The address of the IGMP Querier on the IP subnet to which
         this interface is attached."
::= { igmpInterfaceEntry 5 }

igmpInterfaceQueryMaxResponseTime OBJECT-TYPE
    SYNTAX      Unsigned32 (0..255)
    UNITS      "tenths of seconds"
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The maximum query response time advertised in IGMPv2
         queries on this interface."
    DEFVAL     { 100 }
::= { igmpInterfaceEntry 6 }

igmpInterfaceQuerierUpTime OBJECT-TYPE
    SYNTAX      TimeTicks
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The time since igmpInterfaceQuerier was last changed."
::= { igmpInterfaceEntry 7 }

igmpInterfaceQuerierExpiryTime OBJECT-TYPE
    SYNTAX      TimeTicks
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The amount of time remaining before the Other Querier
         Present Timer expires. If the local system is the querier,
         the value of this object is zero."
::= { igmpInterfaceEntry 8 }

igmpInterfaceVersion1QuerierTimer OBJECT-TYPE
    SYNTAX      TimeTicks
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The time remaining until the host assumes that there are no
         IGMPv1 routers present on the interface. While this is non-
         zero, the host will reply to all queries with version 1
         membership reports."
```

```
::= { igmpInterfaceEntry 9 }
```

```
igmpInterfaceWrongVersionQueries OBJECT-TYPE  
    SYNTAX      Counter32  
    MAX-ACCESS read-only
```

Internet Group Management Protocol MIB

STATUS current

DESCRIPTION

"The number of queries received whose IGMP version does not match igmpInterfaceVersion, over the lifetime of the row entry. IGMP requires that all routers on a LAN be configured to run the same version of IGMP. Thus, if any queries are received with the wrong version, this indicates a configuration error."

::= { igmpInterfaceEntry 10 }

igmpInterfaceJoins OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of times a group membership has been added on this interface; that is, the number of times an entry for this interface has been added to the Cache Table. This object gives an indication of the amount of IGMP activity over the lifetime of the row entry."

::= { igmpInterfaceEntry 11 }

igmpInterfaceProxyIfIndex OBJECT-TYPE

SYNTAX InterfaceIndexOrZero

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"Some devices implement a form of IGMP proxying whereby memberships learned on the interface represented by this row, cause IGMP Host Membership Reports to be sent on the interface whose ifIndex value is given by this object. Such a device would implement the igmpV2RouterMIBGroup only on its router interfaces (those interfaces with non-zero igmpInterfaceProxyIfIndex). Typically, the value of this object is 0, indicating that no proxying is being done."

DEFVAL { 0 }

::= { igmpInterfaceEntry 12 }

igmpInterfaceGroups OBJECT-TYPE

SYNTAX Gauge32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The current number of entries for this interface in the Cache Table."

::= { igmpInterfaceEntry 13 }

igmpInterfaceRobustness OBJECT-TYPE

SYNTAX Unsigned32 (1..255)

MAX-ACCESS read-create

STATUS current

DESCRIPTION

Internet Group Management Protocol MIB

"The Robustness Variable allows tuning for the expected packet loss on a subnet. If a subnet is expected to be lossy, the Robustness Variable may be increased. IGMP is robust to (Robustness Variable-1) packet losses."

DEFVAL { 2 }  
 ::= { igmpInterfaceEntry 14 }

igmpInterfaceLastMembQueryIntvl OBJECT-TYPE  
SYNTAX Unsigned32 (0..255)  
UNITS "tenths of seconds"  
MAX-ACCESS read-create  
STATUS current  
DESCRIPTION  
"The Last Member Query Interval is the Max Response Time inserted into Group-Specific Queries sent in response to Leave Group messages, and is also the amount of time between Group-Specific Query messages. This value may be tuned to modify the leave latency of the network. A reduced value results in reduced time to detect the loss of the last member of a group. The value of this object is irrelevant if igmpInterfaceVersion is 1."  
DEFVAL { 10 }  
 ::= { igmpInterfaceEntry 15 }

igmpInterfaceVersion2QuerierTimer OBJECT-TYPE  
SYNTAX TimeTicks  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION  
"The time remaining until the host assumes that there are no IGMPv2 routers present on the interface. While this is non-zero, the host will reply to all queries with version 1 or 2 membership reports."  
 ::= { igmpInterfaceEntry 16 }

--  
-- The IGMP Cache Table  
--

igmpCacheTable OBJECT-TYPE  
SYNTAX SEQUENCE OF IgmpCacheEntry  
MAX-ACCESS not-accessible  
STATUS current  
DESCRIPTION  
"The (conceptual) table listing the IP multicast groups for which there are members on a particular interface."  
 ::= { igmpMIBObjects 2 }

igmpCacheEntry OBJECT-TYPE

SYNTAX IgmpCacheEntry  
MAX-ACCESS not-accessible  
STATUS current  
DESCRIPTION  
"An entry (conceptual row) in the igmpCacheTable."

Internet Group Management Protocol MIB

INDEX { igmpCacheAddress, igmpCacheIfIndex }  
 ::= { igmpCacheTable 1 }

IgmpCacheEntry ::= SEQUENCE {  
 igmpCacheAddress InetAddress,  
 igmpCacheIfIndex InterfaceIndex,  
 igmpCacheSelf TruthValue,  
 igmpCacheLastReporter InetAddress,  
 igmpCacheUpTime TimeTicks,  
 igmpCacheExpiryTime TimeTicks,  
 igmpCacheStatus RowStatus,  
 igmpCacheVersion1HostTimer TimeTicks,  
 igmpCacheVersion2HostTimer TimeTicks,  
 igmpCacheSourceFilterMode Integer32  
}

igmpCacheAddress OBJECT-TYPE  
 SYNTAX InetAddress  
 MAX-ACCESS not-accessible  
 STATUS current  
 DESCRIPTION  
 "The IP multicast group address for which this entry  
 contains information."  
 ::= { igmpCacheEntry 1 }

igmpCacheIfIndex OBJECT-TYPE  
 SYNTAX InterfaceIndex  
 MAX-ACCESS not-accessible  
 STATUS current  
 DESCRIPTION  
 "The interface for which this entry contains information for  
 an IP multicast group address."  
 ::= { igmpCacheEntry 2 }

igmpCacheSelf OBJECT-TYPE  
 SYNTAX TruthValue  
 MAX-ACCESS read-create  
 STATUS current  
 DESCRIPTION  
 "An indication of whether the local system is a member of  
 this group address on this interface."  
 DEFVAL { true }  
 ::= { igmpCacheEntry 3 }

igmpCacheLastReporter OBJECT-TYPE  
 SYNTAX InetAddress  
 MAX-ACCESS read-only  
 STATUS current

**DESCRIPTION**

"The IP address of the source of the last membership report received for this IP Multicast group address on this interface. If no membership report has been received, this object has the value 0.0.0.0."

Internet Group Management Protocol MIB

```
::= { igmpCacheEntry 4 }

igmpCacheUpTime OBJECT-TYPE
    SYNTAX      TimeTicks
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The time elapsed since this entry was created."
::= { igmpCacheEntry 5 }

igmpCacheExpiryTime OBJECT-TYPE
    SYNTAX      TimeTicks
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The minimum amount of time remaining before this entry will
        be aged out. A value of 0 indicates that the entry is only
        present because igmpCacheSelf is true and that if the router
        left the group, this entry would be aged out immediately.
        Note that some implementations may process membership
        reports from the local system in the same way as reports
        from other hosts, so a value of 0 is not required."
::= { igmpCacheEntry 6 }

igmpCacheStatus OBJECT-TYPE
    SYNTAX      RowStatus
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The status of this entry."
::= { igmpCacheEntry 7 }

igmpCacheVersion1HostTimer OBJECT-TYPE
    SYNTAX      TimeTicks
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The time remaining until the local router will assume that
        there are no longer any IGMP version 1 members on the IP
        subnet attached to this interface. Upon hearing any IGMPv1
        Membership Report, this value is reset to the group
        membership timer. While this time remaining is non-zero,
        the local router ignores any IGMPv2 Leave messages for this
        group that it receives on this interface."
::= { igmpCacheEntry 8 }

igmpCacheVersion2HostTimer OBJECT-TYPE
    SYNTAX      TimeTicks
```

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The time remaining until the local router will assume that there are no longer any IGMP version 2 members on the IP

Internet Group Management Protocol MIB

subnet attached to this interface. Upon hearing any IGMPv2 Membership Report, this value is reset to the group membership timer."

::= { igmpCacheEntry 9 }

igmpCacheSourceFilterMode OBJECT-TYPE

SYNTAX Integer32 {include (1),  
exclude (2)}

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The state in which the interface is currently set. The value indicates the relevance of the corresponding source list entries in the SrcList Table for IGMPv3 interfaces."

::= { igmpCacheEntry 10 }

--  
-- The IGMP Source list Table  
--

igmpSrcListTable OBJECT-TYPE

SYNTAX SEQUENCE OF IgmpSrcListEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The (conceptual) table listing the Source List entries corresponding to each Interface filter mode record."

::= { igmpMIBObjects 3 }

igmpSrcListEntry OBJECT-TYPE

SYNTAX IgmpSrcListEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"An entry (conceptual row) in the igmpSrcListTable."

INDEX { igmpSrcListAddress, igmpSrcListIfIndex,  
igmpSrcListHostAddress }

::= { igmpSrcListTable 1 }

IgmpSrcListEntry ::= SEQUENCE {

  igmpSrcListAddress         IpAddress,  
  igmpSrcListIfIndex         InterfaceIndex,  
  igmpSrcListHostAddress     IpAddress,  
  igmpSrcListStatus         RowStatus

}

igmpSrcListAddress OBJECT-TYPE

SYNTAX      IpAddress  
MAX-ACCESS not-accessible  
STATUS      current

Chesterfield    Internet Draft - Expires December 2002                [Page 11]

Internet Group Management Protocol MIB

DESCRIPTION

"The IP multicast group address for which this entry contains information."

::= { igmpSrcListEntry 1 }

igmpSrcListIfIndex OBJECT-TYPE

SYNTAX InterfaceIndex

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The interface for which this entry contains information for an IP multicast group address."

::= { igmpSrcListEntry 2 }

igmpSrcListHostAddress OBJECT-TYPE

SYNTAXIpAddress

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The host address to which this entry corresponds. The CacheSourceFilterMode value for this Group address and interface indicates whether this Host address is included or excluded."

::= { igmpSrcListEntry 3 }

igmpSrcListStatus OBJECT-TYPE

SYNTAX RowStatus

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The status of this entry."

::= { igmpSrcListEntry 4 }

-- conformance information

igmpMIBConformance

OBJECT IDENTIFIER ::= { igmpStdMIB 2 }

igmpMIBCompliances

OBJECT IDENTIFIER ::= { igmpMIBConformance 1 }

igmpMIBGroups OBJECT IDENTIFIER ::= { igmpMIBConformance 2 }

-- compliance statements

igmpV1HostMIBCompliance MODULE-COMPLIANCE

STATUS current

DESCRIPTION

"The compliance statement for hosts running IGMPv1 and implementing the IGMP MIB."

```
MODULE -- this module
MANDATORY-GROUPS { igmpBaseMIBGroup }
```

```
OBJECT      igmpInterfaceStatus
```

Internet Group Management Protocol MIB

MIN-ACCESS read-only

DESCRIPTION

"Write access is not required."

OBJECT igmpCacheStatus

MIN-ACCESS read-only

DESCRIPTION

"Write access is not required."

::= { igmpMIBCompliances 1 }

igmpV1RouterMIBCompliance MODULE-COMPLIANCE

STATUS current

DESCRIPTION

"The compliance statement for routers running IGMPv1 and implementing the IGMP MIB."

MODULE -- this module

MANDATORY-GROUPS { igmpBaseMIBGroup,  
                  igmpRouterMIBGroup  
                  }

OBJECT igmpInterfaceStatus

MIN-ACCESS read-only

DESCRIPTION

"Write access is not required."

OBJECT igmpCacheStatus

MIN-ACCESS read-only

DESCRIPTION

"Write access is not required."

::= { igmpMIBCompliances 2 }

igmpV2HostMIBCompliance MODULE-COMPLIANCE

STATUS current

DESCRIPTION

"The compliance statement for hosts running IGMPv2 and implementing the IGMP MIB."

MODULE -- this module

MANDATORY-GROUPS { igmpBaseMIBGroup,  
                  igmpV2HostMIBGroup  
                  }

OBJECT igmpInterfaceStatus

MIN-ACCESS read-only

DESCRIPTION

"Write access is not required."

OBJECT igmpCacheStatus

MIN-ACCESS read-only

DESCRIPTION  
    "Write access is not required."  
 ::= { igmpMIBCompliances 3 }

Internet Group Management Protocol MIB

```
igmpV2RouterMIBCompliance MODULE-COMPLIANCE
    STATUS current
    DESCRIPTION
        "The compliance statement for routers running IGMPv2 and
         implementing the IGMP MIB."
    MODULE -- this module
    MANDATORY-GROUPS { igmpBaseMIBGroup,
                        igmpRouterMIBGroup,
                        igmpV2RouterMIBGroup
                    }

OBJECT      igmpInterfaceStatus
MIN-ACCESS  read-only
DESCRIPTION
    "Write access is not required."
OBJECT      igmpCacheStatus
MIN-ACCESS  read-only
DESCRIPTION
    "Write access is not required.

 ::= { igmpMIBCompliances 4 }

igmpV3HostMIBCompliance MODULE-COMPLIANCE
    STATUS current
    DESCRIPTION
        "The compliance statement for hosts running IGMPv3 and
         implementing the IGMP MIB."
    MODULE -- this module
    MANDATORY-GROUPS { igmpBaseMIBGroup,
                        igmpV2HostMIBGroup,
                        igmpV3HostMIBGroup
                    }

OBJECT      igmpInterfaceStatus
MIN-ACCESS  read-only
DESCRIPTION
    "Write access is not required.

OBJECT      igmpCacheStatus
MIN-ACCESS  read-only
DESCRIPTION
    "Write access is not required.

 ::= { igmpMIBCompliances 5 }

igmpV3RouterMIBCompliance MODULE-COMPLIANCE
    STATUS current
    DESCRIPTION
        "The compliance statement for routers running IGMPv3 and
```

```
    implementing the IGMP MIB."  
MODULE -- this module  
MANDATORY-GROUPS { igmpBaseMIBGroup,  
                  igmpRouterMIBGroup,  
                  igmpV2RouterMIBGroup,
```

Internet Group Management Protocol MIB

```

        igmpV3RouterMIBGroup
    }

OBJECT      igmpInterfaceStatus
MIN-ACCESS  read-only
DESCRIPTION
    "Write access is not required."
OBJECT      igmpCacheStatus
MIN-ACCESS  read-only
DESCRIPTION
    "Write access is not required."

 ::= { igmpMIBCompliances 6 }

-- units of conformance

igmpBaseMIBGroup OBJECT-GROUP
    OBJECTS { igmpCacheSelf,
              igmpCacheStatus, igmpInterfaceStatus
            }
    STATUS   current
    DESCRIPTION
        "The basic collection of objects providing management of
         IGMP version 1, 2 or 3."
 ::= { igmpMIBGroups 1 }

igmpRouterMIBGroup OBJECT-GROUP
    OBJECTS { igmpCacheUpTime, igmpCacheExpiryTime,
              igmpInterfaceJoins, igmpInterfaceGroups,
              igmpCacheLastReporter, igmpInterfaceQuerierUpTime,
              igmpInterfaceQuerierExpiryTime,
              igmpInterfaceQueryInterval
            }
    STATUS   current
    DESCRIPTION
        "A collection of additional objects for management of IGMP
         version 1, 2 or 3 in routers."
 ::= { igmpMIBGroups 2 }

igmpV2HostMIBGroup OBJECT-GROUP
    OBJECTS { igmpInterfaceVersion1QuerierTimer }
    STATUS   current
    DESCRIPTION
        "A collection of additional objects for management of IGMP
         version 2 in hosts."
 ::= { igmpMIBGroups 3 }

igmpHostOptMIBGroup OBJECT-GROUP

```

```
OBJECTS { igmpCacheLastReporter, igmpInterfaceQuerier }
STATUS current
DESCRIPTION
    "A collection of optional objects for IGMP hosts.
```

Internet Group Management Protocol MIB

Supporting this group can be especially useful in an environment with a router which does not support the IGMP MIB."

::= { igmpMIBGroups 4 }

igmpV2RouterMIBGroup OBJECT-GROUP

OBJECTS { igmpInterfaceVersion, igmpInterfaceQuerier, igmpInterfaceQueryMaxResponseTime, igmpInterfaceRobustness, igmpInterfaceWrongVersionQueries, igmpInterfaceLastMembQueryIntvl, igmpCacheVersion1HostTimer }

STATUS current

DESCRIPTION

"A collection of additional objects for management of IGMP version 2 in routers."

::= { igmpMIBGroups 5 }

igmpV2ProxyMIBGroup OBJECT-GROUP

OBJECTS { igmpInterfaceProxyIfIndex }

STATUS current

DESCRIPTION

"A collection of additional objects for management of IGMP proxy devices."

::= { igmpMIBGroups 6 }

igmpV3HostMIBGroup OBJECT-GROUP

OBJECTS { igmpCacheSourceFilterMode, igmpInterfaceVersion2QuerierTimer, igmpSrcListAddress, igmpSrcListIfIndex, igmpSrcListHostAddress }

STATUS current

DESCRIPTION

"A collection of additional objects for management of IGMP version 3 in hosts."

::= { igmpMIBGroups 7 }

igmpV3RouterMIBGroup OBJECT-GROUP

OBJECTS { igmpCacheSourceFilterMode, igmpCacheVersion2HostTimer, igmpSrcListAddress, igmpSrcListIfIndex, igmpSrcListHostAddress }

STATUS current

DESCRIPTION

```
"A collection of additional objects for management of IGMP  
version 3 in routers."  
 ::= { igmpMIBGroups 8 }
```

END

## **5. Security Considerations**

This MIB contains readable objects whose values provide information related to multicast sessions. Some of these objects could contain sensitive information. In particular, the igmpCacheSelf and igmpCacheLastReporter can be used to identify machines which are listening to a given group address. There are also a number of objects that have a MAX-ACCESS clause of read-write and/or read-create, which allow an administrator to configure IGMP in the router.

While unauthorized access to the readable objects is relatively innocuous, unauthorized access to the write-able objects could cause a denial of service. Hence, the support for SET operations in a non-secure environment without proper protection can have a negative effect on network operations.

SNMPv1 by itself is such an insecure environment. Even if the network itself is secure (for example by using IPSec), even then, there is no control as to who on the secure network is allowed to access and SET (change/create/delete) the objects in this MIB.

It is recommended that the implementers consider the security features as provided by the SNMPv3 framework. Specifically, the use of the User-based Security Model [RFC 2574](#) [12] and the View-based Access Control Model [RFC 2575](#) [15] is recommended.

It is then a customer/user responsibility to ensure that the SNMP entity giving access to this MIB, is properly configured to give access to those objects only to those principals (users) that have legitimate rights to access them.

## **6. Contributors**

The authors of [RFC 2933](#) from which this document is derived are:

Keith McCloghrie  
cisco Systems, Inc.  
170 West Tasman Drive  
San Jose, CA 95134-1706

Phone: +1 408 526 5260  
EMail: [kzm@cisco.com](mailto:kzm@cisco.com)

Dino Farinacci  
Procket Networks  
3850 North First Street  
San Jose, CA 95134

Phone: +1 408-954-7909  
Email: dino@procket.com

Chesterfield    Internet Draft - Expires December 2002                  [Page 17]

## Internet Group Management Protocol MIB

Dave Thaler  
Microsoft Corporation  
One Microsoft Way  
Redmond, WA 48105-6399

Phone: +1 425 703 8835  
EMail: dthaler@microsoft.com

### 7. Acknowledgements

Thanks to Bill Fenner for feedback and suggestions regarding the MIB.

### 8. Author's Address

Julian Chesterfield  
AT&T Labs - Research  
75 Willow Road  
Menlo Park  
CA, 94301

### 9. References

- [1] Harrington, D., Presuhn, R., and B. Wijnen, "An Architecture for Describing SNMP Management Frameworks", [RFC 2571](#), April 1999.
- [2] Rose, M., and K. McCloghrie, "Structure and Identification of Management Information for TCP/IP-based Internets", STD 16, [RFC 1155](#), May 1990.
- [3] Rose, M., and K. McCloghrie, "Concise MIB Definitions", STD 16, [RFC 1212](#), March 1991.
- [4] M. Rose, "A Convention for Defining Traps for use with the SNMP", [RFC 1215](#), March 1991.
- [5] McCloghrie, K., Perkins, D., Schoenwaelder, J., Case, J., Rose, M., and S. Waldbusser, "Structure of Management Information Version 2 (SMIV2)", STD 58, [RFC 2578](#), April 1999.
- [6] McCloghrie, K., Perkins, D., Schoenwaelder, J., Case, J., Rose, M., and S. Waldbusser, "Textual Conventions for SMIV2", STD 58, [RFC 2579](#), April 1999.
- [7] McCloghrie, K., Perkins, D., Schoenwaelder, J., Case, J., Rose, M., and S. Waldbusser, "Conformance Statements for SMIV2", STD 58, [RFC 2580](#), April 1999.
- [8] Case, J., Fedor, M., Schoffstall, M., and J. Davin, "Simple

Network Management Protocol", STD 15, [RFC 1157](#), May 1990.

Chesterfield    Internet Draft - Expires December 2002                [Page 18]

## Internet Group Management Protocol MIB

- [9] Case, J., McCloghrie, K., Rose, M., and S. Waldbusser, "Introduction to Community-based SNMPv2", [RFC 1901](#), January 1996.
- [10] Case, J., McCloghrie, K., Rose, M., and S. Waldbusser, "Transport Mappings for Version 2 of the Simple Network Management Protocol (SNMPv2)", [RFC 1906](#), January 1996.
- [11] Case, J., Harrington D., Presuhn R., and B. Wijnen, "Message Processing and Dispatching for the Simple Network Management Protocol (SNMP)", [RFC 2572](#), April 1999.
- [12] Blumenthal, U., and B. Wijnen, "User-based Security Model (USM) for version 3 of the Simple Network Management Protocol (SNMPv3)", [RFC 2574](#), April 1999.
- [13] Case, J., McCloghrie, K., Rose, M., and S. Waldbusser, "Protocol Operations for Version 2 of the Simple Network Management Protocol (SNMPv2)", [RFC 1905](#), January 1996.
- [14] Levi, D., Meyer, P., and B. Stewart, "SNMPv3 Applications", [RFC 2573](#), April 1999.
- [15] Wijnen, B., Presuhn, R., and K. McCloghrie, "View-based Access Control Model (VACM) for the Simple Network Management Protocol (SNMP)", [RFC 2575](#), April 1999.
- [16] Case, J., Mundy, R., Partain, D., and B. Stewart, "Introduction to Version 3 of the Internet-standard Network Management Framework", [RFC 2570](#), April 1999.
- [17] Deering, S., "Host Extensions for IP Multicasting", STD 5, [RFC 1112](#), August 1989.
- [18] Fenner, W., "Internet Group Management Protocol, Version 2", [RFC 2236](#), November 1997.
- [19] Cain, B., Deering, S., Fenner, W., Kouvelas, I., Thyagarajan, A., ?Internet Group Management Protocol, Version 3?, <[draft-ietf-idmr-igmp](#)>, May 2002.

### [10. Full Copyright Statement](#)

Copyright (C) The Internet Society (2000). All Rights Reserved.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any

kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to the Internet Society or other

Internet Group Management Protocol MIB

Internet organizations, except as needed for the purpose of developing Internet standards in which case the procedures for copyrights defined in the Internet languages other than English.

The limited permissions granted above are perpetual and will not be revoked by the Internet Society or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE."