

Mobile Ad hoc Networking (MANET)
Internet-Draft
Updates: [RFC6130](#), OLSRV2
(if approved)
Intended status: Standards Track
Expires: September 5, 2014

C. Dearlove
BAE Systems ATC
T. Clausen
LIX, Ecole Polytechnique
March 4, 2014

**Optimized Link State Routing Protocol version 2 (OLSRv2) and MANET
Neighborhood Discovery Protocol (NHDP) Extension TLVs
draft-ietf-manet-nhdp-olsrv2-tlv-extension-04**

Abstract

This specification describes extensions to definitions of TLVs used by the Optimized Link State Routing Protocol version 2 (OLSRv2) and the MANET Neighborhood Discovery Protocol (NHDP), to increase their abilities to accommodate protocol extensions. This document updates OLSRV2 and [RFC6130](#).

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on September 5, 2014.

Copyright Notice

Copyright (c) 2014 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must

include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	3
2.	Terminology	3
3.	Applicability Statement	3
4.	TLV Values	4
4.1.	Unrecognized TLV Values	4
4.2.	TLV Value Lengths	5
4.3.	Undefined TLV Values	5
4.3.1.	NHDP TLVs: LOCAL_IF, LINK_STATUS and OTHER_NEIGHB . .	6
4.3.2.	OLSRv2 TLVs: MPR and NBR_ADDR_TYPE	6
4.3.3.	Unspecified TLV Values	6
5.	IANA Considerations	7
5.1.	LOCAL_IF Address Block TLVs	7
5.1.1.	Create New Registry	7
5.1.2.	Modification to Existing Registry	8
5.2.	LINK_STATUS Address Block TLVs	9
5.2.1.	Create New Registry	9
5.2.2.	Modification to Existing Registry	10
5.3.	OTHER_NEIGHB Address Block TLVs	11
5.3.1.	Create New Registry	11
5.3.2.	Modification to Existing Registry	12
5.4.	MPR Address Block TLVs	12
5.4.1.	Create New Registry	12
5.4.2.	Modification to Existing Registry	13
5.5.	NBR_ADDR_TYPE Address Block TLVs	14
5.5.1.	Create New Registry	14
5.5.2.	Modification to Existing Registry	15
6.	Security Considerations	15
7.	Acknowledgments	16
8.	References	16
8.1.	Normative References	16
8.2.	Informative References	16
	Authors' Addresses	17

1. Introduction

The MANET Neighborhood Discovery Protocol (NHDP) [[RFC6130](#)] and the Optimized Link State Routing Protocol, version 2 (OLSRv2) [[OLSRv2](#)] are protocols for use in mobile ad hoc networks (MANETs) [[RFC2501](#)], based on the Generalized Mobile Ad Hoc Network (MANET) Packet/Message Format [[RFC5444](#)].

This document updates [[RFC6130](#)] and [[OLSRv2](#)], specifically their use of TLV (Type-Length-Value) elements, to increase the extensibility of these protocols, and to enable some improvements in their implementation.

This specification reduces the latitude of implementations of [[OLSRv2](#)] and [[RFC6130](#)] to consider some messages, which will not be created by implementations simply following those specifications, as a reason to consider the message as "badly formed", and thus as a reason to reject the message. This gives greater latitude to the creation of extensions of these protocols, in particular extensions that will interoperate with unextended implementations of those protocols. As part of that, it indicates how TLVs (Type-Length-Value elements) [[RFC5444](#)] with unexpected value fields must be handled, and adds some additional options to those TLVs.

Note that TLVs with unknown type or type extension are already specified as to be ignored by [[RFC6130](#)] and [[OLSRv2](#)], and also are not a reason to reject a message.

2. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

Additionally, this document uses the terminology of [[RFC5444](#)], [[RFC6130](#)], and [[OLSRv2](#)].

3. Applicability Statement

This document updates the specification of the protocols [[OLSRv2](#)] and [[RFC6130](#)].

Specifically, this specification updates [[RFC6130](#)] and [[OLSRv2](#)] in the following way:

- o Removes the latitude of rejecting a message with a TLV with a known type, but with an unexpected TLV Value field, for the TLV Types defined in [[RFC6130](#)] and [[OLSRv2](#)].
- o Specifies the handling of a TLV Value field with unexpected length.
- o Sets up IANA registries for TLV Values for the Address Block TLVs:
 - * LOCAL_IF, defined in [[RFC6130](#)].
 - * LINK_STATUS, defined in [[RFC6130](#)].
 - * OTHER_NEIGHB, defined in [[RFC6130](#)].
 - * MPR, defined in [[OLSRv2](#)], now considered as a bit field.
 - * NBR_ADDR_TYPE, defined in [[OLSRv2](#)], now considered as a bit field.
- o Defines a well-known TLV Value for "UNSPECIFIED" for the Address Block TLV Types LOCAL_IF, LINK_STATUS, and OTHER_NEIGHB, all defined in [[RFC6130](#)].

4. TLV Values

NHDP [[RFC6130](#)] and OLSRv2 [[OLSRv2](#)] define a number of TLVs within the framework of [[RFC5444](#)]. These TLVs define the meaning of only some of the contents that can be found in a TLV Value field. This limitation may be either only defining certain TLV Values, or considering only some lengths of the TLV Value fields (or single value field in a multi value Address-Block TLV). This specification describes how NHDP [[RFC6130](#)] and OLSRv2 [[OLSRv2](#)] are to handle TLVs with other TLV Value fields.

4.1. Unrecognized TLV Values

NHDP and OLSRv2 specify that, in addition to well-defined reasons (in the respective protocol specifications), an implementation of these protocols MAY recognize a message as "badly formed" and therefore "invalid for processing" for other reasons ([Section 12.1 of \[RFC6130\]](#) and [Section 16.3.1 of \[OLSRv2\]](#)). These sections could be interpreted as allowing rejection of a message because a TLV Value field is unrecognized. This specification removes that latitude:

- o An implementation MUST NOT reject a message because it contains an unrecognized TLV value. Instead, any unrecognized TLV Value field

MUST be processed or ignored by an unextended implementation of NHDP or OLSRv2, as described in the following sections.

It should be stressed that this is not a change to [\[RFC6130\]](#) or [\[OLSRv2\]](#), except with regard to not allowing this to be a reason for rejection of a message. [\[RFC6130\]](#) or [\[OLSRv2\]](#) are specified in terms such as "if an address is associated with a value of LOST by a LINK_STATUS TLV". Association with an unrecognized value has no effect on any implementation strictly following such a specification.

4.2. TLV Value Lengths

The TLVs specified in [\[RFC6130\]](#) and [\[OLSRv2\]](#) may be either single-value or multi-value TLVs. In either case, the length of each item of information encoded in the TLV Value field is the "single-length", defined and calculated as in [section 5.4.1 in \[RFC5444\]](#). All TLVs specified in [\[RFC6130\]](#) and [\[OLSRv2\]](#) have a one or two octet single-length. These are considered the expected single-lengths of such a received TLV.

Other single-length TLV Value fields may be introduced by extensions to [\[RFC6130\]](#) and [\[OLSRv2\]](#). This document specifies how implementations of [\[RFC6130\]](#) and [\[OLSRv2\]](#), or extensions thereof, MUST behave on receiving TLVs of the TLV types defined in [\[RFC6130\]](#) and [\[OLSRv2\]](#), but with TLV Value fields with other single-length values.

The following principles apply:

- o If the received single-length is greater than the expected single-length, then the excess octets MUST be ignored.
- o If the received single-length is less than the expected single-length, then the absent octets MUST be considered to have all bits cleared (0).

Exceptions:

- o A received CONT_SEQ_NUM with a single-length < 2 SHOULD be considered an error.

4.3. Undefined TLV Values

[\[RFC6130\]](#) and [\[OLSRv2\]](#) define a number of TLVs, but for some of these TLVs specify meanings for only some TLV Values. This document establishes IANA registries for these TLV Values, with initial registrations reflecting those used by [\[RFC6130\]](#) and [\[OLSRv2\]](#), and as specified in [Section 4.3.3](#).

There are different cases of TLV Values with different characteristics. These cases are considered in this section.

4.3.1. NHDP TLVs: LOCAL_IF, LINK_STATUS and OTHER_NEIGHB

For the Address-Block TLVs LOCAL_IF, LINK_STATUS and OTHER_NEIGHB TLVs, defined in [\[RFC6130\]](#), only a limited number of values are specified for each. These are converted, by this specification, into extensible registries with initial registrations for values defined and used by [\[RFC6130\]](#) - see [Section 5](#).

An implementation of [\[RFC6130\]](#), receiving a LOCAL_IF, LINK_STATUS, or OTHER_NEIGHB TLV with any TLV Value other than the values which are defined in [\[RFC6130\]](#) MUST ignore that TLV Value, as well as any corresponding attribute association to the address.

4.3.2. OLSRv2 TLVs: MPR and NBR_ADDR_TYPE

The Address-Block TLVs MPR and NBR_ADDR_TYPE, defined in [\[OLSRv2\]](#), are similar to those defined in [\[RFC6130\]](#) in having only limited values specified (1, 2 and 3): 1 and 2, represent presence of two different attributes associated to an address, and 3 represents "both 1 and 2".

These TLV Value fields, are by this specification, converted to bit fields, and MUST be interpreted as such. As the existing definitions of values 1, 2, and 3 behave in that manner, it is likely that this will involve no change to an implementation, but any test of (for example) Value = 1 or Value = 3 MUST be converted to a test of (for example) Value bitand 1 = 1, where "bitand" denotes a bitwise and operation.

This specification creates registries for recording reservations of the individual bits in these bitfields, with initial registrations for values defined and used by [\[OLSRv2\]](#) - see [Section 5](#).

Other TLVs defined by [\[OLSRv2\]](#) are not affected by this specification.

4.3.3. Unspecified TLV Values

The registries defined in [Section 5](#) for the LOCAL_IF, LINK_STATUS and OTHER_NEIGHB TLVs each include an additional TLV Value UNSPECIFIED. This TLV Value represents a defined value that, like currently undefined TLV Values, indicates that no information is associated with this address, but will always have this meaning. Such a TLV Value may be used to enable the creation of more efficient multivalue Address Block TLVs, or to simplify an implementation.

The similar requirement for the MPR and NBR_ADDR_TYPES TLVs is already satisfied by the TLV Value zero, provided that each bit in the TLV Value is defined as set ('1') when indicating the presence of an attribute, or clear ('0') when indicating the absence of an attribute; this is therefore required for registrations from the relevant registries, see [Section 5](#).

For the LINK_METRIC TLV, this is already possible by clearing the most significant bits (0 to 3) of the first octet of the TLV Value. It is RECOMMENDED that in this case the remaining bits of the TLV Value are either all clear ('0') or all set ('1').

5. IANA Considerations

IANA is requested to take a total of ten actions as set out in the following sections.

5.1. LOCAL_IF Address Block TLVs

5.1.1. Create New Registry

IANA maintains a registry called "Mobile Ad hoc NETwork (MANET) Parameters". IANA is requested to create a new sub-registry called "LOCAL_IF TLV Values".

IANA is requested to populate this registry as specified in Table 1.

Value	Name	Description	Reference
0	THIS_IF	The network address is associated with this local interface of the sending router	[This.I-D]
1	OTHER_IF	The network address is associated with another local interface of the sending router	[This.I-D]
2-223		Unallocated: Expert Review	
224-254		Experimental Use	[This.I-D]
255	UNSPECIFIED	No information about this network address is provided	[This.I-D]

Table 1: LOCAL_IF TLV Values

New assignments are to be made by Expert Review [[RFC5226](#)].

The Designated Experts are required to use the guidelines specified in [RFC6130] and [OLSRv2]. IANA is not expected to record this fact in the registry.

5.1.2. Modification to Existing Registry

IANA maintains a registry called "Mobile Ad hoc NETwork (MANET) Parameters" with a sub-registry called "LOCAL_IF Address Block TLV Type Extensions". This sub-registry currently has an entry for value 0. IANA is requested to replace the entry in the Description column for this value with the text "The value is to be interpreted according to the registry LOCAL_IF TLV Values". The resulting table should look as specified in Table 2.

Type Extension	Description	Reference
0	The value is to be interpreted according to the registry LOCAL_IF TLV Values	[RFC6130] [This.I-D]
1-255	Unassigned	[This.I-D]

Table 2: LOCAL_IF Address Block TLV Type Extensions Modifications

5.2. LINK_STATUS Address Block TLVs

5.2.1. Create New Registry

IANA maintains a registry called "Mobile Ad hoc NETWORK (MANET) Parameters". IANA is requested to create a new sub-registry called "LINK_STATUS TLV Values".

IANA is requested to populate this registry as specified in Table 3.

Value	Name	Description	Reference
0	LOST	The link on this interface from the router with that network address has been lost	[This.I-D]
1	SYMMETRIC	The link on this interface from the router with that network address has the status of symmetric	[This.I-D]
2	HEARD	The link on this interface from the router with that network address has the status of heard	[This.I-D]
3-223		Unallocated: Expert Review	
224-254		Experimental Use	[This.I-D]
255	UNSPECIFIED	No information about this network address is provided	[This.I-D]

Table 3: LINK_STATUS TLV Values

New assignments are to be made by Expert Review [[RFC5226](#)].

The Designated Experts are required to use the guidelines specified in [[RFC6130](#)] and [[OLSRv2](#)]. IANA is not expected to record this fact in the registry.

5.2.2. Modification to Existing Registry

IANA maintains a registry called "Mobile Ad hoc NETwork (MANET) Parameters" with a sub-registry called "LINK_STATUS Address Block TLV Type Extensions". This sub-registry currently has an entry for value 0. IANA is requested to replace the entry in the Description column for this value with the text "The value is to be interpreted according to the registry LINK_STATUS TLV Values". The resulting table should look as specified in Table 4.

Type Extension	Description	Reference
0	The value is to be interpreted according to the registry LINK_STATUS TLV Values	[RFC6130] [This.I-D]
1-255	Unassigned	[This.I-D]

Table 4: LINK_STATUS Address Block TLV Type Extensions Modifications

5.3. OTHER_NEIGHB Address Block TLVs

5.3.1. Create New Registry

IANA maintains a registry called "Mobile Ad hoc NETWORK (MANET) Parameters". IANA is requested to create a new sub-registry called "OTHER_NEIGHB TLV Values".

IANA is requested to populate this registry as specified in Table 5.

Value	Name	Description	Reference
0	LOST	The neighbor relationship with the router with that network address has been lost	[This.I-D]
1	SYMMETRIC	The neighbor relationship with the router with that network address is symmetric	[This.I-D]
2-223		Unallocated: Expert Review	
224-254		Experimental Use	[This.I-D]
255	UNSPECIFIED	No information about this network address is provided	[This.I-D]

Table 5: OTHER_NEIGHB Address Block TLV Values

New assignments are to be made by Expert Review [[RFC5226](#)].

The Designated Experts are required to use the guidelines specified in [[RFC6130](#)] and [[OLSRv2](#)]. IANA is not expected to record this fact in the registry.

5.3.2. Modification to Existing Registry

IANA maintains a registry called "Mobile Ad hoc NETwork (MANET) Parameters" with a sub-registry called "OTHER_NEIGHB Address Block TLV Type Extensions". This sub-registry currently has an entry for value 0. IANA is requested to replace the entry in the Description column for this value with the text "The value is to be interpreted according to the registry OTHER_NEIGHB TLV Values". The resulting table should look as specified in Table 6.

Type Extension	Description	Reference
0	The value is to be interpreted according to the registry OTHER_NEIGHB TLV Values	[RFC6130] [This.I-D]
1-255	Unassigned	[This.I-D]

Table 6: OTHER_NEIGHB Address Block TLV Type Extensions Modifications

5.4. MPR Address Block TLVs

5.4.1. Create New Registry

IANA maintains a registry called "Mobile Ad hoc NETwork (MANET) Parameters". IANA is requested to create a new sub-registry called "MPR TLV Bit Values".

IANA is requested to populate this registry as specified in Table 7.

Bit	Value	Name	Description	Reference
7	0x01	Flooding	The neighbor with that network address has been selected as flooding MPR	[This.I-D]
6	0x02	Routing	The neighbor with that network address has been selected as routing MPR	[This.I-D]
0-5			Unallocated: Expert Review	

Table 7: MPR Address Block TLV Bit Values

New assignments are to be made by Expert Review [[RFC5226](#)].

The Designated Experts are required to use the guidelines specified in [RFC6130] and [OLSRv2]. Additionally, the Designated Experts are required to ensure that the following sense is preserved:

- o For each bit in the field, a set bit (1) means that the address has the designated property, while an unset bit (0) means that no information about the designated property is provided. In particular, an unset bit must not be used to convey any specific information about the designated property. IANA is not expected to record these facts in the registry.

5.4.2. Modification to Existing Registry

IANA maintains a registry called "Mobile Ad hoc NETwork (MANET) Parameters" with a sub-registry called "MPR Address Block TLV Type Extensions". This sub-registry currently has an entry for value 0. IANA is requested to replace the entry in the Description column for this value with the text "The value is to be interpreted according to the registry MPR TLV Bit Values". The resulting table should look as specified in Table 8.

Type	Description	Reference
Extension		
0	The value is to be interpreted according to the registry MPR TLV Bit Values	[OLSRv2] [This.I-D]
1-255	Unassigned	[This.I-D]

Table 8: MPR Address Block TLV Type Extensions Modifications

5.5. NBR_ADDR_TYPE Address Block TLVs

5.5.1. Create New Registry

IANA maintains a registry called "Mobile Ad hoc NETWORK (MANET) Parameters". IANA is requested to create a new sub-registry called "NBR_ADDR_TYPE Address Block TLV Bit Values".

IANA is requested to populate this registry as specified in Table 9.

Bit	Value	Name	Description	Reference
7	0x01	ORIGINATOR	The network address is an originator address reachable via the originating router	[This.I-D]
6	0x02	ROUTABLE	The network address is a routable address reachable via the originating router	[This.I-D]
0-5			Unallocated: Expert Review	

Table 9: NBR_ADDR_TYPE Address Block TLV Bit Values

New assignments are to be made by Expert Review [[RFC5226](#)].

The Designated Experts are required to use the guidelines specified in [[RFC6130](#)] and [[OLSRv2](#)]. Additionally, the Designated Experts are required to ensure that the following sense is preserved:

- o For each bit in the field, a set bit (1) means that the address has the designated property, while an unset bit (0) means that no information about the designated property is provided. In particular, an unset bit must not be used to convey any specific information about the designated property. IANA is not expected to record these facts in the registry.

5.5.2. Modification to Existing Registry

IANA maintains a registry called "Mobile Ad hoc NETwork (MANET) Parameters" with a sub-registry called "NBR_ADDR_TYPE Address Block TLV Type Extensions". This sub-registry currently has an entry for value 0. IANA is requested to replace the entry in the Description column for this value with the text "The value is to be interpreted according to the registry NBR_ADDR_TYPE TLV Bit Values". The resulting table should look as specified in Table 10.

Type Extension	Description	Reference
0	The value is to be interpreted according to the registry NBR_ADDR_TYPE Address Block TLV Bit Values	[OLSRv2] [This.I-D]
1-255	Unassigned	[This.I-D]

Table 10: NBR_ADDR_TYPE Address Block TLV Type Extensions Modifications

6. Security Considerations

The presented updates to [[RFC6130](#)] and [[OLSRv2](#)]:

- o Create IANA registries for retaining TLV values for TLVs, already defined in the already published specifications of the two protocols, and with initial registrations for the TLV values defined by these specifications. This does not give rise to any additional security considerations.
- o Enable protocol extensions to be able to register TLV values in the created IANA registries. Such extensions MUST specify appropriate security considerations.
- o Create, in some registries, a registration for "UNSPECIFIED" values, for more efficient use of multi-value Address Block TLVs. The interpretation of an address being associated with a TLV of a given type and with the value "UNSPECIFIED" is identical to that address not being associated with a TLV of that type. Thus, this update does not give rise to any additional security considerations.
- o Reduces the latitude of implementations of the two protocols to reject a message as "badly formed", due to the value field of a

TLV being unexpected. These protocols are specified in terms such as "if an address is associated with a value of LOST by a LINK_STATUS TLV". Association with an unknown value (or a value newly defined to mean no link status information) has no effect on such a specification. Thus, this update does not give rise to any additional security considerations.

- o Do not introduce any opportunities for attacks on the protocols through signal modification that are not already present in the two protocols.

7. Acknowledgments

The authors would like to gratefully acknowledge the following people for intense technical discussions, early reviews, and comments on the specification (listed alphabetically): Ulrich Herberg (Fujitsu Laboratories of America) and Henning Rogge (Frauenhofer FKIE).

The authors would also like to express their gratitude to Adrian Farrel, for his assistance and contributions to successful and timely completion of this specification.

8. References

8.1. Normative References

- [OLSRV2] Clausen, T., Dearlove, C., Jacquet, P., and U. Herberg, "The Optimized Link State Routing Protocol version 2", work in progress [draft-ietf-manet-olsrv2-19](#), March 2013.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC5444] Clausen, T., Dearlove, C., Dean, J., and C. Adjih, "Generalized MANET Packet/Message Format", [RFC 5444](#), February 2009.
- [RFC6130] Clausen, T., Dean, J., and C. Dearlove, "Mobile Ad Hoc Network (MANET) Neighborhood Discovery Protocol (NHDP)", [RFC 6130](#), April 2011.

8.2. Informative References

- [RFC2501] Macker, J. and S. Corson, "Mobile Ad hoc Networking (MANET): Routing Protocol Performance Issues and Evaluation Considerations", [RFC 2501](#), January 1999.

[RFC5226] Narten, T. and H. Alvestrand, "Guidelines for Writing an IANA Considerations Section in RFCs", [BCP 26](#), [RFC 5226](#), May 2008.

Authors' Addresses

Christopher Dearlove
BAE Systems Advanced Technology Centre
West Hanningfield Road
Great Baddow, Chelmsford
United Kingdom

Phone: +44 1245 242194
Email: chris.dearlove@baesystems.com
URI: <http://www.baesystems.com/>

Thomas Heide Clausen
LIX, Ecole Polytechnique

Phone: +33 6 6058 9349
Email: T.Clausen@computer.org
URI: <http://www.ThomasClausen.org/>

