

Network Working Group
INTERNET DRAFT

Zaid Albanna
Juniper Networks
Kevin Almeroth
UCSB
David Meyer
Cisco Systems
Michelle Schipper
IANA
Best Current Practices
April, 2001

Category

IANA Guidelines for IPv4 Multicast Address Allocation
<[draft-ietf-mboned-iana-ipv4-mcast-guidelines-01.txt](#)>

1. Status of this Memo

This document specifies an Internet Best Current Practices for the Internet Community, and requests discussion and suggestions for improvements. Distribution of this memo is unlimited.

This document is an Internet-Draft and is in full conformance with all provisions of [Section 10 of RFC 2026](#).

Internet Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/lid-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

Internet Draft [draft-ietf-mboned-iana-IPv4-mcast-guidelines-01.txt](#) April, 2001

2. Copyright Notice

Copyright (C) The Internet Society (2001). All Rights Reserved.

3. Abstract

This memo provides guidance for the IANA in assigning IPv4 multicast addresses.

4. Introduction

The Internet Assigned Numbers Authority (IANA) (www.iana.org) is charged with allocating parameter values for fields in protocols which have been designed, created or are maintained by the Internet Engineering Task Force (IETF). [RFC 2780](#) [[RFC2780](#)] provides the IANA guidance in the assignment of parameters for fields in newly developed protocols. This memo expands on [section 4.4.2 of RFC 2780](#) and attempts to codify existing IANA practice used in the assignment IPv4 multicast addresses.

The terms "Specification Required", "Expert Review", "IESG Approval", "IETF Consensus", and "Standards Action", are used in this memo to refer to the processes described in [[RFC2434](#)]. The keywords MUST, MUST NOT, MAY, OPTIONAL, REQUIRED, RECOMMENDED, SHALL, SHALL NOT, SHOULD, SHOULD NOT are to be interpreted as defined in [RFC 2119](#) [[RFC2119](#)].

In general, due to the relatively small size of the IPv4 multicast addresses space, further allocation of IPv4 multicast address space is not recommended. Specifically, the IANA should only assign addresses in those cases where the dynamic selection (SDP/SAP), GLOP, SSM or Administratively Scoped address spaces cannot be used. The guidelines described below are reflected in <http://www.iana.org>.

Internet Draft-draft-ietf-mboned-iana-IPv4-mcast-guidelines-01.txt-April, 2001

5. Definition of Current Assignment Practice

Unlike IPv4 unicast address assignment, where blocks of addresses are delegated to regional registries, IPv4 multicast addresses are assigned directly by the IANA. Current allocations appear as follows [[IANA](#)]:

224.0.0.0	- 224.0.0.255	(224.0.0/24)	Local Network Control Block
224.0.1.0	- 224.0.1.255	(224.0.1/24)	Internetwork Control Block
224.0.2.0	- 224.0.255.0		AD-HOC Block
224.1.0.0	- 224.1.255.255	(224.1/16)	ST Multicast Groups
224.2.0.0	- 224.2.255.255	(224.2/16)	SDP/SAP Block
224.252.0.0	- 224.255.255.255		DIS Transient Block
225.0.0.0	- 225.255.255.255	(225/8)	MALLOC Block
226.0.0.0	- 231.255.255.255		RESERVED
232.0.0.0	- 232.255.255.255	(232/8)	Source Specific Multicast Block
233.0.0.0	- 233.255.255.255	(233/8)	GLOP Block
234.0.0.0	- 238.255.255.255		RESERVED
239.0.0.0	- 239.255.255.255	(239/8)	Administratively Scoped Block

The IANA generally allocates addresses from the Local Network Control, Internetwork Control, and AD-HOC blocks. Allocation guidelines for each of these blocks, as well as for the MALLOC, Source Specific Multicast, GLOP and Administratively Scoped Blocks, are described below.

Note that while some applications may informally use arbitrary parts of the IPv4 multicast address space (e.g., 229/8), an application MUST NOT use address space that is not allocated as described in this memo.

6. Local Network Control Block (224.0.0/24)

Addresses in the Local Network Control block are used for protocol

control traffic that is not forwarded off link. Examples of this type of use include OSPFIGP All Routers (224.0.0.5) [[RFC2328](#)].

6.1. Allocation Guidelines

Allocation of addresses in the Local Network Configuration Block SHOULD BE accompanied by a specification ("Specification Required"). This specification will typically take the form of an internet draft or RFC.

Internet Draft-draft-ietf-mboned-iana-IPv4-mcast-guidelines-01.txt April, 2001

7. Internetwork Control Block (224.0.1/24)

Addresses in the Internetwork Control block are used for protocol control that must be forwarded through the Internet. Examples include 224.0.1.1 (NTP [[RFC2030](#)]) and 224.0.1.68 (mdhcpdiscover [[RFC2730](#)]).

7.1. Allocation Guidelines

Allocation of addresses in the Internetwork Control block SHOULD BE accompanied by a specification ("Specification Required"). This specification will typically take the form of an internet draft or RFC.

8. AD-HOC Block (224.0.2.0/24 - 224.0.255.0/24)

Addresses in the AD-HOC block have traditionally been allocated for those applications that don't fit in either the Local or Internetwork Control blocks. These addresses are globally routed and are typically used by applications that require small blocks of addressing (e.g., less than a /24).

8.1. Allocation Guidelines

Allocation of addresses in the AD-HOC Block SHOULD BE accompanied by a specification ("Specification Required"). This specification will

typically take the form of an internet draft or RFC. In general, the IANA SHOULD NOT assign addressing in the AD-HOC Block.

9. SDP/SAP Block (224.2/16)

Addresses in the SDP/SAP block are used by applications that receive addresses through the Session Announcement Protocol [[RFC2974](#)] for use via applications like the session directory tool (such as SDR [[SDR](#)]).

9.1. Allocation Guidelines

Since addresses in the SDP/SAP block are chosen randomly from the range of addresses not already in use [[RFC2974](#)], no IANA allocation policy is required. Note that while no additional IANA allocation is required, addresses in the SDP/SAP block are explicitly for use by SDP/SAP and MUST NOT be used for other purposes.

10. MALLOC Block (225/8)

Addresses in the MALLOC block are dynamically allocated by the MALLOC suite of protocols [[RFC2908](#)]. This assignment is temporary and MUST BE reviewed annually.

10.1. Allocation Guidelines

Since addresses in the MALLOC block are chosen by elements of the MALLOC architecture, no IANA allocation policy is required. Note that while no additional IANA allocation is required, addresses in the MALLOC block are explicitly for allocation by MALLOC servers and MUST NOT be used for other purposes.

11. Source Specific Multicast Block (232/8)

The Source Specific Multicast (SSM) is an extension of IP Multicast in which traffic is forwarded to receivers from only those multicast sources for which the receivers have explicitly expressed interest, and is primarily targeted at one-to-many (broadcast) applications.

[11.1. Allocation Guidelines](#)

Because the SSM model essentially makes the entire multicast address space local to the host, no IANA allocation policy is required. Note, however, that while no additional IANA allocation is required, addresses in the SSM block are explicitly for use by SSM and MUST NOT be used for other purposes.

[12. GLOP Block \(233/8\)](#)

Addresses in the GLOP block are globally scoped statically assigned addresses. The assignment is made by mapping a domain's autonomous system number into the middle two octets of 233.X.Y.0/24. The mapping and allocation is defined in [[RFC2770](#)].

[12.1. Allocation Guidelines](#)

Because addresses in the GLOP block are algorithmically preassigned, no IANA allocation policy is required. Note that while no additional IANA allocation is required, addresses in the GLOP block are allocated for use as defined in [RFC 2770](#) and MUST NOT be used for other purposes.

[13. Administratively Scoped Address Block \(239/8\)](#)

Addresses in the Administratively Scoped Address block are for local use within a domain and are described in [[RFC2365](#)].

[13.1. Allocation Guidelines](#)

Since addresses in this block are local to a domain, no IANA allocation policy is required.

[13.1.1. Relative Offsets](#)

The relative offsets [[RFC2365](#)] are used to ensure that a service can

be located independent of the extent of the enclosing scope (see [RFC 2770](#) for details). Since there are only 256 such offsets, the IANA should only assign a relative offset to a protocol that provides an infra-structure supporting service. Examples of such services include the Session Announcement Protocol [[RFC2974](#)]. See [[IANA](#)] for the current set of assignments.

[14.](#) Annual Review

Given the dynamic nature of IPv4 multicast and its associated infra-structure, and the previously undocumented IPv4 multicast address assignment guidelines, the IANA should conduct an annual review of currently assigned addresses.

[14.1.](#) Address Reclamation

During the review described above, addresses that were mis-assigned should, where possible, be reclaimed or reassigned. An example of an address block that might be reclaimed is 224.1.0/24 [[RFC1190](#)], as this was an experimental allocation and is not in use. In addition, those allocations in 224.0.1/24 that are not used for Internet-wide protocol control messages (as described above) above might be reclaimed.

The IANA should also review assignments in the AD-HOC, DIS Transient Groups, and ST Multicast Groups blocks and reclaim those addresses that are not in use on the global Internet (i.e, those applications which can use SSM, GLOP, or Administratively Scoped addressing, or are not globally routed).

[15.](#) Use of IANA Reserved Addresses

Applications MUST NOT use addressing in the IANA reserved blocks.

[16.](#) Appeals Process

Appeals of this process are to be handled in accordance with [Section](#)

[6.5 of RFC 2026](#) [[RFC2026](#)].

[17.](#) Security Considerations

The allocation guidelines described in this document do not alter the security properties of either the Any Source or Source Specific multicast service models.

[18.](#) Acknowledgments

The authors would like to thank Joe St. Sauver, John Meylor, and Randy Bush for their constructive feedback and comments.

[19.](#) Author's Address:

Zaid Albanna
1149 N. Mathilda Ave
Sunnyvale, CA. 94089
zaid@juniper.net

Kevin Almeroth
UC Santa Barbara
Santa Barbara, CA.
Email: almeroth@cs.ucsb.edu

David Meyer
Cisco Systems, Inc.
170 Tasman Drive
San Jose, CA, 95134
Email: dmm@cisco.com

Michelle Schipper
IANA Administrator
iana@iana.org

[20.](#) References

- [IANA] <http://www.iana.org>
- [RFC1190] C. Topolcic, "Experimental Internet Stream Protocol, Version 2 (ST-II)", [RFC 1190](#), October, 1990.
- [RFC2026] S. Bradner, "The Internet Standards Process -- Revision 3", [RFC2026](#), October 1996.
- [RFC2030] Mills, D., Simple Network Time Protocol (SNTP) Version 4 for IPv4, IPv6 and OSI", D. Mills, October 1996.
- [RFC2119] S. Bradner, "Key words for use in RFCs to Indicate Requirement Levels", [RFC 2119](#), March, 1997.
- [RFC2328] J. Moy, "OSPF Version 2", [RFC 2328](#), April, 1998.
- [RFC2365] D. Meyer, "Administratively Scoped IP Multicast", [RFC 2365](#), July, 1998.
- [RFC2434] Narten, T. and H. Alvestrand, "Guidelines for Writing an IANA Considerations Section in RFCs", [BCP 26](#), [RFC 2434](#), October 1998.
- [RFC2730] Hanna, S., Patel, B. and M. Shah, "Multicast Address Dynamic Client Allocation Protocol (MADCAP)", December 1999.
- [RFC2770] D. Meyer, and P. Lothberg, "GLOP Addressing in 233/8", [RFC 2770](#), February, 2000
- [RFC2780] S. Bradner and V. Paxson, "IANA Allocation Guidelines For Values In the Internet Protocol and Related Headers", [RFC2780](#), March, 2000
- [RFC2908] D. Thaler, M. Handley, D.Estrin, "The Internet Multicast Address Allocation Architecture", [RFC 2908](#), September 2000.
- [RFC2974] M. Handley, C. Perkins, E. Whelan, "Session Announcement Protocol", [RFC 2974](#), October 2000.
- [SDR] <http://www.aciri.org/sdr/>

[21](#). Full Copyright Statement

Copyright (C) The Internet Society (2001). All Rights Reserved.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to the Internet Society or other Internet organizations, except as needed for the purpose of developing Internet standards in which case the procedures for copyrights defined in the Internet Standards process must be followed, or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by the Internet Society or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

