

Network Working Group
Internet-Draft
Intended status: Informational
Expires: April 27, 2012

S. Venaas
R. Parekh
G. Van de Velde
cisco Systems
T. Chown
University of Southampton
M. Eubanks
Iformata Communications
October 25, 2011

Multicast Addresses for Documentation
draft-ietf-mboned-mcaddrdoc-02.txt

Abstract

This document discusses which multicast addresses should be used for documentation purposes and reserves multicast addresses for such use. Some multicast addresses are derived from AS numbers or unicast addresses. This document also explains how these can be used for documentation purposes.

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on April 27, 2012.

Copyright Notice

Copyright (c) 2011 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents

Internet-Draft Multicast Addresses for Documentation October 2011

carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	3
2.	IPv4 multicast documentation addresses	4
2.1.	Administratively scoped IPv4 multicast addresses	4
2.2.	GLOP multicast addresses	4
2.3.	Unicast prefix based IPv4 multicast addresses	4
3.	IPv6 multicast documentation addresses	6
3.1.	Unicast prefix based IPv6 multicast addresses	6
3.2.	Embedded-RP IPv6 multicast addresses	6
4.	Security Considerations	8
5.	IANA Considerations	9
6.	Acknowledgments	10
7.	Informative References	11
	Authors' Addresses	12

1. Introduction

It is often useful in documentation, IETF documents, etc., to provide examples containing IP multicast addresses. For documentation where examples of general purpose multicast addresses are needed, one should use multicast addresses that never will be assigned or in actual use. There is a risk that addresses used in examples may accidentally be used. It is then important that the same addresses are not used by other multicast applications or services. It may also be beneficial to filter out such addresses from multicast signalling and multicast data sent to such addresses.

For unicast there are both IPv4 and IPv6 addresses reserved for this purpose, see [[RFC5737](#)] and [[RFC3849](#)] respectively. This document reserves multicast addresses for this purpose.

There are also some multicast addresses that are derived from AS numbers or unicast addresses. For examples where such addresses are desired, one should derive them from the AS numbers and unicast addresses reserved for documentation purposes. This document also discusses the use of these.

[2.](#) IPv4 multicast documentation addresses

The type of multicast addresses most commonly used today, are addresses used for so-called ASM (Any-Source Multicast). For ASM, the IPv4 multicast addresses allocated for documentation purposes are 233.252.0.0 - 233.252.0.255 (233.252.0.0/24).

Another type of multicast is SSM (Source-Specific Multicast). For SSM it is less important which multicast addresses are used, since a host/application joins a channel identified by both source and group. Any source addresses used in SSM examples should be unicast addresses reserved for documentation purposes. There are three unicast address ranges provided for documentation use in [\[RFC5737\]](#). The ranges are 192.0.2.0/24, 198.51.100.0/24 and 203.0.113.0/24.

Sometimes one wants to give examples where a specific type of address is desired. E.g. for text about multicast scoping, one might want the examples to use addresses that are to be used for administrative scoping. See below for guidance on how to construct specific types of example addresses.

[2.1.](#) Administratively scoped IPv4 multicast addresses

Administratively scoped IPv4 multicast addresses [\[RFC2365\]](#) are reserved for scoped multicast. They can be used within a site or an organization. Apart from a small set of scope relative addresses, these addresses are not assigned. There are no specific scoped addresses available for documentation purposes. Except for examples detailing the use of scoped multicast, one should avoid using them.

2.2. GLOP multicast addresses

GLOP [[RFC3180](#)] is a method for deriving IPv4 multicast group addresses from 16 bit AS numbers. For examples where GLOP addresses are desired, the addresses should be derived from the AS numbers reserved for documentation use.

The 16 bit AS numbers reserved for documentation use in [[RFC5398](#)] are 64496 - 64511. By use of [[RFC3180](#)], we then get 16 /24 multicast prefixes for documentation use. The first one 233.251.240.0/24, and the last 233.251.255.0/24.

2.3. Unicast prefix based IPv4 multicast addresses

IPv4 multicast addresses can be derived from IPv4 unicast prefixes, see [[RFC6034](#)]. For examples where this type of addresses are desired, the addresses should be derived from the unicast addresses reserved for documentation purposes, see [[RFC5737](#)].

There are three unicast address ranges provided for documentation use in [[RFC5737](#)]. The ranges are 192.0.2.0/24, 198.51.100.0/24 and 203.0.113.0/24. Using [[RFC6034](#)] this leaves us with the unicast prefix based IPv4 multicast addresses 234.192.0.2, 234.198.51.100 and 234.203.0.113.

[3.](#) IPv6 multicast documentation addresses

The type of multicast addresses most commonly used today, are addresses used for so-called ASM (Any-Source Multicast). For ASM, the IPv6 multicast addresses allocated for documentation purposes are TBD.

Another type of multicast is SSM (Source-Specific Multicast). For SSM it is less important which multicast addresses are used, since a host/application joins a channel identified by both source and group. Any source addresses used in SSM examples should be unicast addresses reserved for documentation purposes. The IPv6 unicast prefix reserved for documentation purposes is 2001:DB8::/32, see [[RFC3849](#)].

Sometimes one wants to give examples where a specific type of address

is desired. E.g. for text about multicast scoping, one might want the examples to use addresses that are to be used for administrative scoping. See below for guidance on how to construct specific types of example addresses.

3.1. Unicast prefix based IPv6 multicast addresses

IPv6 multicast addresses can be derived from IPv6 unicast prefixes, see [[RFC3306](#)]. For examples where this type of addresses is desired, the addresses should be derived from the unicast addresses reserved for documentation purposes.

The IPv6 unicast prefix reserved for documentation purposes is 2001:DB8::/32, see [[RFC3849](#)]. This allows a wide range of different IPv6 multicast addresses. Using just the base /32 prefix, one get the IPv6 multicast prefixes FF3X:20:2001:DB8::/64, one for each available scope X. One can also produce longer prefixes from this. Just as an example, one can pick say a /64 prefix 2001:DB8:DEAD:BEEF::/64 which gives the multicast prefixes FF3X:40:2001:DB8:DEAD:BEEF::/96, one for each available scope X.

3.2. Embedded-RP IPv6 multicast addresses

There is a type of IPv6 multicast addresses called Embedded-RP addresses where the IPv6 address of a Rendezvous-Point is embedded inside the multicast address, see [[RFC3956](#)]. For examples where this type of addresses is desired, the addresses should be derived from the unicast addresses reserved for documentation purposes, see see [[RFC3849](#)].

For documentation purposes, the RP address can be any address from the range 2001:DB8::/32 that follows the constraints specified in [[RFC3956](#)]. One example address could be 2001:DB8::1. The

embedded-RP multicast prefixes might then be FF7X:120:2001:DB8::/96. Another example could be the RP address 2001:DB8:BEEF:FEED::7 which gives the prefixes FF7X:740:2001:DB8:BEEF:FEED::/96. See also the examples in [[RFC3956](#)].

[4.](#) Security Considerations

The use of specific multicast addresses for documentation purposes has no impact on security.

5. IANA Considerations

IANA is requested to assign "variable scope" IPv6 multicast addresses for documentation purposes. This should be a /96 prefix of the form FF0X:.... The word TBD in this text should be replaced with the assigned prefix, and this sentence should be deleted before publishing.

[6.](#) Acknowledgments

The authors thank Roberta Maglione and Leonard Giuliano for providing comments on this document.

Internet-Draft Multicast Addresses for Documentation October 2011

7. Informative References

- [RFC2365] Meyer, D., "Administratively Scoped IP Multicast", [BCP 23](#), [RFC 2365](#), July 1998.
- [RFC3180] Meyer, D. and P. Lothberg, "GLOP Addressing in 233/8", [BCP 53](#), [RFC 3180](#), September 2001.
- [RFC3306] Haberman, B. and D. Thaler, "Unicast-Prefix-based IPv6 Multicast Addresses", [RFC 3306](#), August 2002.
- [RFC3307] Haberman, B., "Allocation Guidelines for IPv6 Multicast Addresses", [RFC 3307](#), August 2002.
- [RFC3849] Huston, G., Lord, A., and P. Smith, "IPv6 Address Prefix Reserved for Documentation", [RFC 3849](#), July 2004.
- [RFC3956] Savola, P. and B. Haberman, "Embedding the Rendezvous Point (RP) Address in an IPv6 Multicast Address", [RFC 3956](#), November 2004.
- [RFC5398] Huston, G., "Autonomous System (AS) Number Reservation for Documentation Use", [RFC 5398](#), December 2008.
- [RFC5737] Arkko, J., Cotton, M., and L. Vegoda, "IPv4 Address Blocks Reserved for Documentation", [RFC 5737](#), January 2010.
- [RFC6034] Thaler, D., "Unicast-Prefix-Based IPv4 Multicast Addresses", [RFC 6034](#), October 2010.

Authors' Addresses

Stig Venaas
cisco Systems
Tasman Drive
San Jose, CA 95134
USA

Email: stig@cisco.com

Rishabh Parekh
cisco Systems
Tasman Drive
San Jose, CA 95134
USA

Email: riparekh@cisco.com

Gunter Van de Velde
cisco Systems
De Kleetlaan 6a
Diegem 1831
Belgium

Phone: +32 476 476 022
Email: gvandevere@cisco.com

Tim Chown
University of Southampton
Highfield
Southampton, Hampshire S017 1BJ
United Kingdom

Email: tjc@ecs.soton.ac.uk

Venaas, et al.

Expires April 27, 2012

[Page 12]

Internet-Draft

Multicast Addresses for Documentation

October 2011

Marshall Eubanks
Iformata Communications
130 W. Second Street
Dayton, Ohio 45402
US

Phone: +1 703 501 4376
Email: marshall.eubanks@iformata.com
URI: <http://www.iformata.com/>

