

Network Working Group
INTERNET DRAFT

David Meyer
Sprint
Rob Rockell
Sprint
Greg Shepherd
Procket
Best Current Practices
January, 2003

Category

Source-Specific Protocol Independent Multicast in 232/8

<[draft-ietf-mboned-ssm232-04.txt](#)>

1. Status of this Memo

This document specifies an Internet Best Current Practices for the Internet Community, and requests discussion and suggestions for improvements. Distribution of this memo is unlimited.

This document is an Internet-Draft and is in full conformance with all provisions of [Section 10 of RFC 2026](#).

Internet Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/1id-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

2. Copyright Notice

Copyright (C) The Internet Society (2003). All Rights Reserved.

3. Abstract

IP Multicast group addresses in the 232/8 (232.0.0.0 to 232.255.255.255) range are designated as source-specific multicast [[SSM](#)] destination addresses and are reserved for use by source-specific applications and protocols [[IANA](#)]. This document defines operational recommendations to ensure source-specific behavior within the 232/8 range.

The keywords MUST, MUST NOT, MAY, OPTIONAL, REQUIRED, RECOMMENDED, SHALL, SHALL NOT, SHOULD, SHOULD NOT are to be interpreted as defined in [RFC 2119](#) [[RFC2119](#)].

4. Introduction

Current PIM Sparse Mode [[RFC2362](#)] relies on the shared Rendezvous Point (RP) tree to learn about active sources for a group and to support group-generic (not source specific) data distribution. The IP Multicast group address range 232/8 has been designated for source-specific [[SSM](#)] applications and protocols [[IANA](#)] and SHOULD support source-only trees only, precluding the requirement of an RP and a shared tree; active sources in the 232/8 range will be discovered out of band. PIM Sparse Mode Designated Routers (DR), with local membership, are capable of joining the shortest path tree for the source directly using Source-Specific PIM [[SSM](#)].

Operational best common practices in the 232/8 group address range are necessary to ensure shortest path source-only trees across multiple domains in the Internet [[SSM](#)], and to prevent data from sources sending to groups in the 232/8 range from arriving via shared trees. This avoids unwanted data arrival, and allows several sources to use the same group address without conflict at the receivers.

The operational practices SHOULD

- o Prevent local sources from sending to shared tree
- o Prevent remote sources from being learned/joined via MSDP [[MSDP](#)]
- o Prevent receivers from joining the shared tree

- o Prevent RP's as candidates for 232/8

5. Operational practices in 232/8

5.1. Preventing local sources from sending to shared tree

Eliminating the use of shared trees for groups in 232/8, while maintaining coexistence with PIM-SM, behavior of the RP and/or the DR needs to be modified. This can be accomplished by

- preventing data for 232/8 groups from being sent encapsulated to the RP by the DR
- preventing the RP from accepting registers for 232/8 groups from the DR
- preventing the RP from forwarding accepted data down (*,G) tree for 232/8 groups

5.2. Preventing remote sources from being learned/joined via MSDP

PIM-SS does not require active source announcements via MSDP. All source announcements are received out of band, the the last hop router is responsible for sending (S,G) joins directly to the source. To prevent propagation of SAs in the 232/8 range, an RP SHOULD

- never originate an SA for any 232/8 groups
- never accept or forward an SA for any 232/8 groups.

5.3. Preventing receivers from joining the shared tree

Local PIM domain practices need to be enforced to prevent local receivers from joining the shared tree for 232/8 groups. This can be accomplished by

- preventing DR from sending (*,G) joins for 232/8 groups
- preventing RP from accepting (*,G) join for 232/8 groups

However, within a local PIM domain, any last-hop router NOT

preventing (*,G) joins may trigger unwanted (*,G) state toward the RP which intersects an existing (S,G) tree, allowing the receiver on the shared tree to receive the data, breaking the source-specific [SSM] service model. It is therefore recommended that ALL routers in the domain MUST reject AND never originate (*,G) joins for 232/8 groups.

5.4. Preventing RP's as candidates for 232/8

Because PIM-SS does not require an RP, all RPs SHOULD NOT offer themselves as candidates in the 232/8 range. This can be accomplished by

- preventing RP/BSR from announcing in the 232/8 range
- preventing ALL routers from accepting RP delegations in the 232/8 range
- precluding RP functionality on RP for the 232/8 range

6. Informative References

- [IANA] <http://www.iana.org>
- [RFC2119] S. Bradner, "Key words for use in RFCs to Indicate Requirement Levels", [RFC 2119](http://rfc2119.ietf.org/), March, 1997.

7. Normative References

- [MSDP] D. Meyer and Bill Fenner (Editors), "The Multicast Source Discovery Protocol (MSDP)", draft-ietf-msdp-spec-14.txt, November 2002.
- [SSM] Holbrook, H., Cain, B., "Source-Specific Multicast", draft-ietf-ssm-arch-01.txt, November, 2002.
- [RFC2362] D. Estrin, et. al., "Protocol Independent Multicast-Sparse Mode (PIM-SM): Protocol Specification", [RFC 2362](http://rfc2362.ietf.org/), June, 1998.

8. Author's Addresses

David Meyer
Sprint
Email: dmm@sprint.net

Robert Rockell
Sprint
Email: rrockell@sprint.net

Greg Shepherd
Procket
Email: shep@procket.com

9. Full Copyright Statement

Copyright (C) The Internet Society (2003). All Rights Reserved.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to the Internet Society or other Internet organizations, except as needed for the purpose of developing Internet standards in which case the procedures for copyrights defined in the Internet Standards process must be followed, or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by the Internet Society or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

