

Network Working Group
Internet-Draft
Updates: [5763](#), 7345 (if approved)
Intended status: Standards Track
Expires: May 4, 2017

C. Holmberg
Ericsson
R. Shpount
TurboBridge
October 31, 2016

Using the SDP Offer/Answer Mechanism for DTLS
draft-ietf-mmusic-dtls-sdp-15.txt

Abstract

This document defines the SDP offer/answer procedures for negotiating and establishing a DTLS association. The document also defines the criteria for when a new DTLS association must be established. The document updates [RFC 5763](#) and [RFC 7345](#), by replacing common SDP offer/answer procedures with a reference to this specification.

This document defines a new SDP media-level attribute, 'dtls-id'.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on May 4, 2017.

Copyright Notice

Copyright (c) 2016 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must

include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	2
2.	Conventions	3
3.	Establishing a new DTLS Association	3
3.1.	General	3
3.2.	Change of Local Transport Parameters	4
3.3.	Change of ICE ufrag value	4
4.	SDP dtls-id Attribute	4
5.	SDP Offer/Answer Procedures	6
5.1.	General	6
5.2.	Generating the Initial SDP Offer	8
5.3.	Generating the Answer	8
5.4.	Offerer Processing of the SDP Answer	9
5.5.	Modifying the Session	10
6.	ICE Considerations	10
7.	Transport Protocol Considerations	11
7.1.	Transport Re-Usage	11
8.	SIP Considerations	11
9.	RFC Updates	12
9.1.	General	12
9.2.	Update to RFC 5763	12
9.3.	Update to RFC 7345	17
10.	Security Considerations	20
11.	IANA Considerations	20
12.	Acknowledgements	20
13.	Change Log	20
14.	References	23
14.1.	Normative References	23
14.2.	Informative References	24
	Authors' Addresses	25

[1.](#) Introduction

[RFC5763] defines SDP Offer/Answer procedures for SRTP-DTLS. [RFC7345] defines SDP offer/answer procedures for UDPTL-DTLS. This specification defines general offer/answer procedures for DTLS, based on the procedures in [RFC5763]. Other specifications, defining specific DTLS usages, can then reference this specification, in order to ensure that the DTLS aspects are common among all usages. Having common procedures is essential when multiple usages share the same DTLS association [[I-D.ietf-mmusic-sdp-bundle-negotiation](#)]. The document updates [RFC5763] and [RFC7345], by replacing common SDP offer/answer procedures with a reference to this specification.

As defined in [[RFC5763](#)], a new DTLS association MUST be established when transport parameters are changed. Transport parameter change is not well defined when Interactive Connectivity Establishment (ICE) [[I-D.ietf-ice-rfc5245bis](#)] is used. One possible way to determine a transport change is based on ufrag change, but the ufrag value is changed both when ICE is negotiated and when ICE restart [[I-D.ietf-ice-rfc5245bis](#)] occurs. These events do not always require a new DTLS association to be established, but currently there is no way to explicitly indicate in an SDP offer or answer whether a new DTLS association is required. To solve that problem, this document defines a new SDP attribute, 'dtls-id'. The 'dtls-id' attribute pair in combination with 'fingerprint' attribute values from offer and answer SDP uniquely identifies the DTLS association. Providing a new value of 'dtls-id' attribute in SDP offer or answers can be used to indicate whether a new DTLS association is to be established.

2. Conventions

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

3. Establishing a new DTLS Association

3.1. General

A new DTLS association MUST be established after a successful SDP offer/answer transaction in the following cases::

- o The negotiated DTLS setup roles change; or
- o One or more fingerprint values are modified, added or removed in either an SDP offer or answer; or
- o The intent to establish a new DTLS association is explicitly signaled by changing the value of the SDP 'dtls-id' attribute defined in this document;

NOTE: The first two items list above are based on the procedures in [[RFC5763](#)]. This specification adds the support for explicit signaling using the SDP 'dtls-id' attribute.

A new DTLS association can only be established as a result of the successful SDP offer/answer transaction. Whenever an entity determines that a new DTLS association is required, the entity MUST initiate an SDP offer/answer transaction, following the procedures in [Section 5](#).

The sections below describe typical cases where a new DTLS association needs to be established.

[3.2.](#) Change of Local Transport Parameters

If an endpoint modifies its local transport parameters (address and/or port), and if the modification requires a new DTLS association, the endpoint MUST change its set of fingerprints and SDP 'dtls-id' attribute so that together they represent a new unique set of values [Section 4](#).

If the underlying transport explicitly prohibits a DTLS association to span multiple transports, and if the transport is changed, the endpoint MUST change its set of fingerprints and SDP 'dtls-id' attribute so that together they represent a new unique set of values [Section 4](#). An example of such case is when DTLS is carried over SCTP, as described in [[RFC6083](#)].

[3.3.](#) Change of ICE ufrag value

If an endpoint uses ICE, and modifies a local ufrag value, and if the modification requires a new DTLS association, the endpoint MUST change its set of fingerprints and SDP 'dtls-id' attribute so that together they represent a new unique set of values [Section 4](#).

[4.](#) SDP dtls-id Attribute

The 'dtls-id' attribute pair in combination with 'fingerprint' attribute values from offer and answer SDP uniquely identifies the DTLS association.

Name: dtls-id

Value: dtls-id-value

Usage Level: media

Charset Dependent: no

Default Value: empty value

Syntax:

dtls-id-value = 0*256 <alpha-numeric defined in [[RFC4566](#)]>

Example:

a=dtls-id:abc3dl

Every time end point requests to establish a new DTLS association using the same set of fingerprints, a new unique value of 'dtls-id' attribute is allocated. A combination of the previously used 'dtls-id' attribute in combination with the same fingerprint set indicates an intention to reuse the existing association.

The default value for the SDP 'dtls-id' attribute is an empty value. Implementations that wish to use the attribute MUST explicitly include it in SDP offers and answers. If an offer or answer does not contain an attribute (this could happen if the offerer or answerer represents an existing implementation that has not been updated to support the attribute defined in this specification or an implementation which allocates a new temporary certificate for each association and uses change in fingerprint to indicate new association), it should be treated as if 'dtls-id' attribute with an empty value were included in SDP and procedures defined in this specification should be used to determine if new DTLS association should be established.

The mux category [[I-D.ietf-mmusic-sdp-mux-attributes](#)] for the 'dtls-id' attribute is 'IDENTICAL', which means that the attribute value must be identical across all media descriptions being multiplexed [[I-D.ietf-mmusic-sdp-bundle-negotiation](#)].

For RTP-based media, the 'dtls-id' attribute apply to whole associated media description. The attribute MUST NOT be defined per source (using the SDP 'ssrc' attribute [[RFC5576](#)]).

The SDP offer/answer [[RFC3264](#)] procedures associated with the attribute are defined in [Section 5](#)

5. SDP Offer/Answer Procedures

5.1. General

This section defines the generic SDP offer/answer procedures for negotiating a DTLS association. Additional procedures (e.g., regarding usage of specific SDP attributes etc) for individual DTLS usages (e.g., SRTP-DTLS) are outside the scope of this specification, and need to be specified in a usage specific specification.

NOTE: The procedures in this section are generalizations of procedures first specified in SRTP-DTLS [[RFC5763](#)], with the addition of usage of the SDP 'dtls-id' attribute. That document is herein updated to make use of these new procedures.

The procedures in this section apply to an SDP media description ("m=" line) associated with DTLS-protected media/data.

When an offerer or answerer indicates that it wants to establish a new DTLS association, it needs to make sure that media packets in the existing DTLS association and new DTLS association can be de-multiplexed. In case of ordered transport (e.g., SCTP) this can be done simply by sending packets for new DTLS association after all packets for existing DTLS association have been sent. In case of unordered transport, such as UDP, packets for the old DTLS association can arrive after the answer SDP was received and after first packets for the new DTLS association were received. The only way to de-multiplex packets belonging to old and new DTLS association is on the basis of transport 5-tuple. Because of this, if unordered transport is used for DTLS association, new transport (3-tuple) MUST be allocated by at least on the end points so that DTLS packets can be de-multiplexed.

When an offerer needs to establish a new DTLS association, and if an unordered transport (e.g., UDP) is used, the offerer MUST allocate a new transport (3-tuple) for the offer in such a way that the offerer can disambiguate any packets associated with the new DTLS association from any packets associated with any other DTLS association. This typically means using a local address and/or port, or a set of ICE candidates (see [Section 6](#)), which were not recently used for any other DTLS association.

When an answerer needs to establish a new DTLS association, if an unordered transport is used, and if the offerer did not allocate a new transport, the answerer MUST allocate a new transport for the

offer in answer a way that it can disambiguate any packets associated with new DTLS association from any packets associated with any other DTLS association. This typically means using a local address and/or port, or a set of ICE candidates (see [Section 6](#)), which were not recently used for any other DTLS association.

In order to negotiate a DTLS association, the following SDP attributes are used:

- o The SDP 'setup' attribute, defined in [\[RFC4145\]](#), is used to negotiate the DTLS roles;
- o The SDP 'fingerprint' attribute, defined in [\[RFC4572\]](#), is used to provide a fingerprint values; and
- o The SDP 'dtls-id' attribute, defined in this specification, which, if fingerprints are reused, can be assigned a new value to explicitly indicate the intention to establishing a new DTLS association.

This specification does not define the usage of the SDP 'connection' attribute [\[RFC4145\]](#) for negotiating a DTLS connection. However, the attribute MAY be used if the DTLS association is used together with another protocol (e.g., SCTP or TCP) for which the usage of the attribute has been defined.

Unlike for TCP and TLS connections, endpoints MUST NOT use the SDP 'setup' attribute 'holdconn' value when negotiating a DTLS association.

Endpoints MUST support SHA-256 for generating and verifying any fingerprint value associated with the DTLS association. The use of SHA-256 is preferred.

Endpoints MUST, at a minimum, support TLS_DHE_RSA_WITH_AES_128_GCM_SHA256 and MUST support TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256. UDPTL over DTLS MUST prefer TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256 and any other Perfect Forward Secrecy (PFS) cipher suites over non-PFS cipher suites. Implementations SHOULD disable TLS-level compression.

The certificate received during the DTLS handshake MUST match the certificate fingerprints received in SDP 'fingerprint' attributes according to procedures defined in [\[I-D.ietf-mmusic-4572-update\]](#). If fingerprints do not match the hashed certificate, then an endpoint MUST tear down the media session immediately. Note that it is permissible to wait until the other side's fingerprint has been

received before establishing the connection; however, this may have undesirable latency effects.

SDP offerers and answerers might reuse certificates across multiple DTLS associations, and provide identical fingerprint values for each DTLS association. It MUST be ensured that the combination of the fingerprint values and the SDP 'dtls-id' attribute value is unique across all DTLS associations.

If an SDP offerer or answerer generates a new temporary self-signed certificate for each new DTLS association, they can omit the SDP 'dtls-id' attribute.

5.2. Generating the Initial SDP Offer

When an offerer sends the initial offer, the offerer MUST insert an SDP 'setup' attribute according to the procedures in [\[RFC4145\]](#), and one or more SDP 'fingerprint' attributes according to the procedures in [\[RFC4572\]](#) and [\[I-D.ietf-mmusic-4572-update\]](#). In addition, the offerer MUST insert in the offer an SDP 'dtls-id' attribute with a unique value for the offer fingerprint set. If the fingerprint set is not unique due the certificate reuse across multiple SDP sessions or endpoints, the 'dtls-id' attribute value MUST be generated in a way that guarantees uniqueness across all current DTLS association established using this fingerprint set, including DTLS association established by other SDP sessions or other endpoints.

If the offerer inserts the SDP 'setup' attribute with an 'actpass' or 'passive' attribute value, the offerer MUST be prepared to receive a DTLS ClientHello message (if a new DTLS association is established by the answerer) from the answerer before the offerer receives the SDP answer.

5.3. Generating the Answer

When an answerer sends an answer, the answerer MUST insert in the answer an SDP 'setup' attribute according to the procedures in [\[RFC4145\]](#), and one or more SDP 'fingerprint' attributes according to the procedures in [\[RFC4572\]](#) and [\[I-D.ietf-mmusic-4572-update\]](#). If the answerer determines, based on the criteria specified in [Section 3.1](#), that a new DTLS association is to be established, the answerer MUST insert in the associated answer an SDP 'dtls-id' attribute with a unique value for the answer fingerprint set. If the fingerprint set is not unique due the certificate reuse across multiple SDP sessions or endpoints, 'dtls-id' value MUST be generated in a way that guarantees uniqueness across all current DTLS association established using this fingerprint set, including DTLS association established by other SDP sessions or other endpoints.

If the answerer receives an offer that requires establishing a new DTLS association, and if the answerer does not accept the establishment of a new DTLS association, the answerer MUST reject the "m=" lines associated with the suggested DTLS association [[RFC3264](#)].

If an answerer receives an offer that does not require to establish a new DTLS association, and if the answerer determines that a new DTLS association is not to be established, the answerer MUST insert an SDP 'dtls-id' attribute with the previously assigned value in the associated answer. In addition, the answerer MUST insert an SDP 'setup' attribute with a value that does not change the previously negotiated DTLS roles, and one or more SDP 'fingerprint' attributes values that do not change the previously sent fingerprints, in the answer.

If the answerer receives an offer that does not contain an SDP 'dtls-id' attribute, the answerer MUST NOT insert a 'dtls-id' attribute in the answer.

If a new DTLS association is to be established, and if the answerer inserts an SDP 'setup' attribute with an 'active' value in the answer, the answerer MUST initiate a DTLS handshake by sending a DTLS ClientHello message towards the offerer.

[5.4.](#) Offerer Processing of the SDP Answer

When an offerer receives an answer that establishes a new DTLS association based on criteria defined in [Section 3.1](#), and if the offerer becomes DTLS client (based on the value of the SDP 'setup' attribute value [[RFC4145](#)]), the offerer MUST establish a DTLS association. If the offerer becomes DTLS server, it MUST wait for the answerer to establish the DTLS association.

If the answer does not establish a new DTLS association, the offerer will continue using the previously established DTLS association.

NOTE: New DTLS association can be established based on changes in either offer or answer SDP. When communicating with legacy end points, offerer can receive the answer that uses the same fingerprint values and negotiate the same setup roles. The new DTLS association MUST still be established if such an answer was received as a response to an offer which requested to establish a new DTLS association.

5.5. Modifying the Session

When the offerer sends a subsequent offer, and if the offerer wants to establish a new DTLS association, the offerer MUST insert an SDP 'setup' attribute according to the procedures in [\[RFC4145\]](#), and one or more SDP 'fingerprint' attributes according to the procedures in [\[RFC4572\]](#) and [\[I-D.ietf-mmusic-4572-update\]](#). In addition, offerer MUST insert in the offer an SDP 'dtls-id' attribute with a new unique value for the offer fingerprint set. If the fingerprint set is not unique due the certificate reuse across multiple SDP sessions or endpoints, the 'dtls-id' attribute value MUST be generated in a way that guarantees uniqueness across all current DTLS association established using this fingerprint set, including DTLS association established by other SDP sessions or other endpoints.

When the offerer sends a subsequent offer, and the offerer does not want to establish a new DTLS association, and if a previously established DTLS association exists, the offerer MUST insert an SDP 'dtls-id' attribute with the previously assigned value in the offer. In addition, the offerer MUST insert an SDP 'setup' attribute with a value that does not change the previously negotiated DTLS roles, and one or more SDP 'fingerprint' attributes with values that do not change the previously sent fingerprints, in the offer.

NOTE: When a new DTLS association is being established, each endpoint needs to be prepared to receive data on both the new and old DTLS associations as long as both are alive.

6. ICE Considerations

When the Interactive Connectivity Establishment (ICE) mechanism [\[I-D.ietf-ice-rfc5245bis\]](#) is used, the ICE connectivity checks are performed before the DTLS handshake begins. Note that if aggressive nomination mode is used, multiple candidate pairs may be marked valid before ICE finally converges on a single candidate pair.

NOTE: Aggressive nomination has been deprecated from ICE, but must still be supported for backwards compatibility reasons.

When new DTLS association is established over an unordered transport, in order to disambiguate any packets associated with the newly established DTLS association, at least one of the endpoints MUST allocate a completely new set of ICE candidates which were not recently used for any other DTLS association. This means the answerer cannot initiate a new DTLS association unless the offerer initiated ICE restart [\[I-D.ietf-ice-rfc5245bis\]](#). If the answerer wants to initiate a new DTLS association, it needs to initiate an ICE restart and a new offer/answer exchange on its own. However, an ICE

restart does not by default require a new DTLS association to be established.

NOTE: Simple Traversal of the UDP Protocol through NAT (STUN) packets are sent directly over UDP, not over DTLS. [\[RFC5764\]](#) describes how to demultiplex STUN packets from DTLS packets and SRTP packets.

Each ICE candidate associated with a component is treated as being part of the same DTLS association. Therefore, from a DTLS perspective it is not considered a change of local transport parameters when an endpoint switches between those ICE candidates.

[7.](#) Transport Protocol Considerations

[7.1.](#) Transport Re-Usage

If DTLS is transported on top of a connection-oriented transport protocol (e.g., TCP or SCTP), where all IP packets are acknowledged, all DTLS packets associated with a previous DTLS association **MUST** be acknowledged (or timed out) before a new DTLS association can be established on the same transport.

[8.](#) SIP Considerations

When the Session Initiation Protocol (SIP) [\[RFC3261\]](#) is used as the signal protocol for establishing a multimedia session, dialogs [\[RFC3261\]](#) might be established between the caller and multiple callees. This is referred to as forking. If forking occurs, separate DTLS associations **MUST** be established between the caller and each callee.

It is possible to send an INVITE request which does not contain an SDP offer. Such an INVITE request is often referred to as an 'empty INVITE', or an 'offer-less INVITE'. The receiving endpoint will include the SDP offer in a response to the request. When the endpoint generates such SDP offer, if a previously established DTLS association exists, the offerer **SHOULD** insert an SDP 'dtls-id' attribute, and one or more SDP 'fingerprint' attributes, with previously assigned attribute values. If a previously established DTLS association did not exist, the offer **SHOULD** be generated based on the same rules as a new offer [Section 5.2](#). Regardless of the previous existence of a DTLS association, the SDP 'setup' attribute **MUST** be included according to the rules defined in [\[RFC4145\]](#) and if ICE is used, ICE restart **MUST** be initiated.

9. RFC Updates

9.1. General

This section updates specifications that use DTLS-protected media, in order to reflect the procedures defined in this specification.

9.2. Update to [RFC 5763](#)

Update to [section 5](#):

OLD TEXT:

5. Establishing a Secure Channel

The two endpoints in the exchange present their identities as part of the DTLS handshake procedure using certificates. This document uses certificates in the same style as described in "Connection-Oriented Media Transport over the Transport Layer Security (TLS) Protocol in the Session Description Protocol (SDP)" [[RFC4572](#)].

If self-signed certificates are used, the content of the subjectAltName attribute inside the certificate MAY use the uniform resource identifier (URI) of the user. This is useful for debugging purposes only and is not required to bind the certificate to one of the communication endpoints. The integrity of the certificate is ensured through the fingerprint attribute in the SDP. The subjectAltName is not an important component of the certificate verification.

The generation of public/private key pairs is relatively expensive. Endpoints are not required to generate certificates for each session.

The offer/answer model, defined in [[RFC3264](#)], is used by protocols like the Session Initiation Protocol (SIP) [[RFC3261](#)] to set up multimedia sessions. In addition to the usual contents of an SDP [[RFC4566](#)] message, each media description ("m=" line and associated parameters) will also contain several attributes as specified in [[RFC5764](#)], [[RFC4145](#)], and [[RFC4572](#)].

When an endpoint wishes to set up a secure media session with another endpoint, it sends an offer in a SIP message to the other endpoint. This offer includes, as part of the SDP payload, the fingerprint of the certificate that the endpoint wants to use. The endpoint SHOULD send the SIP message containing the offer to the offerer's SIP proxy over an integrity protected channel. The proxy SHOULD add an

Identity header field according to the procedures outlined in [\[RFC4474\]](#). The SIP message containing the offer SHOULD be sent to the offerer's SIP proxy over an integrity protected channel. When the far endpoint receives the SIP message, it can verify the identity of the sender using the Identity header field. Since the Identity header field is a digital signature across several SIP header fields, in addition to the body of the SIP message, the receiver can also be certain that the message has not been tampered with after the digital signature was applied and added to the SIP message.

The far endpoint (answerer) may now establish a DTLS association with the offerer. Alternately, it can indicate in its answer that the offerer is to initiate the TLS association. In either case, mutual DTLS certificate-based authentication will be used. After completing the DTLS handshake, information about the authenticated identities, including the certificates, are made available to the endpoint application. The answerer is then able to verify that the offerer's certificate used for authentication in the DTLS handshake can be associated to the certificate fingerprint contained in the offer in the SDP. At this point, the answerer may indicate to the end user that the media is secured. The offerer may only tentatively accept the answerer's certificate since it may not yet have the answerer's certificate fingerprint.

When the answerer accepts the offer, it provides an answer back to the offerer containing the answerer's certificate fingerprint. At this point, the offerer can accept or reject the peer's certificate and the offerer can indicate to the end user that the media is secured.

Note that the entire authentication and key exchange for securing the media traffic is handled in the media path through DTLS. The signaling path is only used to verify the peers' certificate fingerprints.

The offer and answer MUST conform to the following requirements.

- o The endpoint MUST use the setup attribute defined in [\[RFC4145\]](#). The endpoint that is the offerer MUST use the setup attribute value of setup:actpass and be prepared to receive a client_hello before it receives the answer. The answerer MUST use either a setup attribute value of setup:active or setup:passive. Note that if the answerer uses setup:passive, then the DTLS handshake will not begin until the answerer is received, which adds additional latency. setup:active allows the answer and the DTLS handshake to occur in parallel. Thus, setup:active is RECOMMENDED. Whichever party is active MUST initiate a DTLS handshake by sending a ClientHello over each flow (host/port quartet).

- o The endpoint MUST NOT use the connection attribute defined in [\[RFC4145\]](#).
- o The endpoint MUST use the certificate fingerprint attribute as specified in [\[RFC4572\]](#).
- o The certificate presented during the DTLS handshake MUST match the fingerprint exchanged via the signaling path in the SDP. The security properties of this mechanism are described in [Section 8](#).
- o If the fingerprint does not match the hashed certificate, then the endpoint MUST tear down the media session immediately. Note that it is permissible to wait until the other side's fingerprint has been received before establishing the connection; however, this may have undesirable latency effects.

NEW TEXT:

[5](#). Establishing a Secure Channel

The two endpoints in the exchange present their identities as part of the DTLS handshake procedure using certificates. This document uses certificates in the same style as described in "Connection-Oriented Media Transport over the Transport Layer Security (TLS) Protocol in the Session Description Protocol (SDP)" [\[RFC4572\]](#).

If self-signed certificates are used, the content of the subjectAltName attribute inside the certificate MAY use the uniform resource identifier (URI) of the user. This is useful for debugging purposes only and is not required to bind the certificate to one of the communication endpoints. The integrity of the certificate is ensured through the fingerprint attribute in the SDP.

The generation of public/private key pairs is relatively expensive. Endpoints are not required to generate certificates for each session.

The offer/answer model, defined in [\[RFC3264\]](#), is used by protocols like the Session Initiation Protocol (SIP) [\[RFC3261\]](#) to set up multimedia sessions.

When an endpoint wishes to set up a secure media session with another endpoint, it sends an offer in a SIP message to the other endpoint. This offer includes, as part of the SDP payload, a fingerprint of a certificate that the endpoint wants to use. The endpoint SHOULD send the SIP message containing the offer to the offerer's SIP proxy over an integrity protected channel. The proxy SHOULD add an Identity header field according to the procedures outlined in

[RFC4474]. The SIP message containing the offer SHOULD be sent to the offerer's SIP proxy over an integrity protected channel. When the far endpoint receives the SIP message, it can verify the identity of the sender using the Identity header field. Since the Identity header field is a digital signature across several SIP header fields, in addition to the body of the SIP message, the receiver can also be certain that the message has not been tampered with after the digital signature was applied and added to the SIP message.

The far endpoint (answerer) may now establish a DTLS association with the offerer. Alternately, it can indicate in its answer that the offerer is to initiate the DTLS association. In either case, mutual DTLS certificate-based authentication will be used. After completing the DTLS handshake, information about the authenticated identities, including the certificates, are made available to the endpoint application. The answerer is then able to verify that the offerer's certificate used for authentication in the DTLS handshake can be associated to the certificate fingerprint contained in the offer in the SDP. At this point, the answerer may indicate to the end user that the media is secured. The offerer may only tentatively accept the answerer's certificate since it may not yet have the answerer's certificate fingerprint.

When the answerer accepts the offer, it provides an answer back to the offerer containing the answerer's certificate fingerprint. At this point, the offerer can accept or reject the peer's certificate and the offerer can indicate to the end user that the media is secured.

Note that the entire authentication and key exchange for securing the media traffic is handled in the media path through DTLS. The signaling path is only used to verify the peers' certificate fingerprints.

The offerer and answerer MUST follow the SDP offer/answer procedures defined in [RFCXXXX].

Update to [section 6.6](#):

OLD TEXT:

[6.6](#). Session Modification

Once an answer is provided to the offerer, either endpoint MAY request a session modification that MAY include an updated offer. This session modification can be carried in either an INVITE or

UPDATE request. The peers can reuse the existing associations if they are compatible (i.e., they have the same key fingerprints and transport parameters), or establish a new one following the same rules as for initial exchanges, tearing down the existing association as soon as the offer/answer exchange is completed. Note that if the active/passive status of the endpoints changes, a new connection MUST be established.

NEW TEXT:

6.6. Session Modification

Once an answer is provided to the offerer, either endpoint MAY request a session modification that MAY include an updated offer. This session modification can be carried in either an INVITE or UPDATE request. The peers can reuse an existing DTLS association, or establish a new one, following the procedures in [RFCXXXX].

Update to [section 6.7.1](#):

OLD TEXT:

6.7.1. ICE Interaction

Interactive Connectivity Establishment (ICE), as specified in [\[RFC5245\]](#), provides a methodology of allowing participants in multimedia sessions to verify mutual connectivity. When ICE is being used, the ICE connectivity checks are performed before the DTLS handshake begins. Note that if aggressive nomination mode is used, multiple candidate pairs may be marked valid before ICE finally converges on a single candidate pair. Implementations MUST treat all ICE candidate pairs associated with a single component as part of the same DTLS association. Thus, there will be only one DTLS handshake even if there are multiple valid candidate pairs. Note that this may mean adjusting the endpoint IP addresses if the selected candidate pair shifts, just as if the DTLS packets were an ordinary media stream.

Note that Simple Traversal of the UDP Protocol through NAT (STUN) packets are sent directly over UDP, not over DTLS. [\[RFC5764\]](#) describes how to demultiplex STUN packets from DTLS packets and SRTP packets.

NEW TEXT:

6.7.1. ICE Interaction

The Interactive Connectivity Establishment (ICE) [[RFC5245](#)] considerations for DTLS-protected media are described in [RFCXXXX].

9.3. Update to [RFC 7345](#)

Update to [section 4](#):

OLD TEXT:

4. SDP Offerer/Answerer Procedures

4.1. General

An endpoint (i.e., both the offerer and the answerer) MUST create an SDP media description ("m=" line) for each UDPTL-over-DTLS media stream and MUST assign a UDP/TLS/UDPTL value (see Table 1) to the "proto" field of the "m=" line.

The procedures in this section apply to an "m=" line associated with a UDPTL-over-DTLS media stream.

In order to negotiate a UDPTL-over-DTLS media stream, the following SDP attributes are used:

- o The SDP attributes defined for UDPTL over UDP, as described in [ITU.T38.2010]; and
- o The SDP attributes, defined in [[RFC4145](#)] and [[RFC4572](#)], as described in this section.

The endpoint MUST NOT use the SDP "connection" attribute [[RFC4145](#)].

In order to negotiate the TLS roles for the UDPTL-over-DTLS transport connection, the endpoint MUST use the SDP "setup" attribute [[RFC4145](#)].

If the endpoint supports, and is willing to use, a cipher suite with an associated certificate, the endpoint MUST include an SDP "fingerprint" attribute [[RFC4572](#)]. The endpoint MUST support SHA-256 for generating and verifying the SDP "fingerprint" attribute value. The use of SHA-256 is preferred. UDPTL over DTLS, at a minimum, MUST support TLS_DHE_RSA_WITH_AES_128_GCM_SHA256 and MUST support TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256. UDPTL over DTLS MUST prefer TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256 and any other Perfect Forward Secrecy (PFS) cipher suites over non-PFS cipher suites.

Implementations SHOULD disable TLS-level compression.

If a cipher suite with an associated certificate is selected during the DTLS handshake, the certificate received during the DTLS handshake MUST match the fingerprint received in the SDP "fingerprint" attribute. If the fingerprint does not match the hashed certificate, then the endpoint MUST tear down the media session immediately. Note that it is permissible to wait until the other side's fingerprint has been received before establishing the connection; however, this may have undesirable latency effects.

4.2. Generating the Initial Offer

The offerer SHOULD assign the SDP "setup" attribute with a value of "actpass", unless the offerer insists on being either the sender or receiver of the DTLS ClientHello message, in which case the offerer can use either a value of "active" (the offerer will be the sender of ClientHello) or "passive" (the offerer will be the receiver of ClientHello). The offerer MUST NOT assign an SDP "setup" attribute with a "holdconn" value.

If the offerer assigns the SDP "setup" attribute with a value of "actpass" or "passive", the offerer MUST be prepared to receive a DTLS ClientHello message before it receives the SDP answer.

4.3. Generating the Answer

If the answerer accepts the offered UDPTL-over-DTLS transport connection, in the associated SDP answer, the answerer MUST assign an SDP "setup" attribute with a value of either "active" or "passive", according to the procedures in [\[RFC4145\]](#). The answerer MUST NOT assign an SDP "setup" attribute with a value of "holdconn".

If the answerer assigns an SDP "setup" attribute with a value of "active" value, the answerer MUST initiate a DTLS handshake by sending a DTLS ClientHello message on the negotiated media stream, towards the IP address and port of the offerer.

4.4. Offerer Processing of the Answer

When the offerer receives an SDP answer, if the offerer ends up being active it MUST initiate a DTLS handshake by sending a DTLS ClientHello message on the negotiated media stream, towards the IP address and port of the answerer.

4.5. Modifying the Session

Once an offer/answer exchange has been completed, either endpoint MAY

send a new offer in order to modify the session. The endpoints can reuse the existing DTLS association if the key fingerprint values and transport parameters indicated by each endpoint are unchanged. Otherwise, following the rules for the initial offer/answer exchange, the endpoints can negotiate and create a new DTLS association and, once created, delete the previous DTLS association, following the same rules for the initial offer/answer exchange. Each endpoint needs to be prepared to receive data on both the new and old DTLS associations as long as both are alive.

NEW TEXT:

4. SDP Offerer/Answerer Procedures

An endpoint (i.e., both the offerer and the answerer) MUST create an SDP media description ("m=" line) for each UDPTL-over-DTLS media stream and MUST assign a UDP/TLS/UDPTL value (see Table 1) to the "proto" field of the "m=" line.

The offerer and answerer MUST follow the SDP offer/answer procedures defined in [RFCXXXX] in order to negotiate the DTLS association associated with the UDPTL-over-DTLS media stream. In addition, the offerer and answerer MUST use the SDP attributes defined for UDPTL over UDP, as defined in [ITU.T38.2010].

Update to [section 5.2.1](#):

OLD TEXT:

[5.2.1](#). ICE Usage

When Interactive Connectivity Establishment (ICE) [[RFC5245](#)] is being used, the ICE connectivity checks are performed before the DTLS handshake begins. Note that if aggressive nomination mode is used, multiple candidate pairs may be marked valid before ICE finally converges on a single candidate pair. User Agents (UAs) MUST treat all ICE candidate pairs associated with a single component as part of the same DTLS association. Thus, there will be only one DTLS handshake even if there are multiple valid candidate pairs. Note that this may mean adjusting the endpoint IP addresses if the selected candidate pair shifts, just as if the DTLS packets were an ordinary media stream. In the case of an ICE restart, the DTLS handshake procedure is repeated, and a new DTLS association is created. Once the DTLS handshake is completed and the new DTLS association has been created, the previous DTLS association is deleted.

NEW TEXT:

5.2.1. ICE Usage

The Interactive Connectivity Establishment (ICE) [[RFC5245](#)] considerations for DTLS-protected media are described in [RFCXXXX].

10. Security Considerations

This specification does not modify the security considerations associated with DTLS, or the SDP offer/answer mechanism. In addition to the introduction of the SDP 'dtls-id' attribute, the specification simply clarifies the procedures for negotiating and establishing a DTLS association.

11. IANA Considerations

This document updates the "Session Description Protocol Parameters" registry as specified in [Section 8.2.2 of \[RFC4566\]](#). Specifically, it adds the SDP dtls-id attribute to the table for SDP media level attributes.

Attribute name: dtls-id
Type of attribute: media-level
Subject to charset: no
Purpose: Indicate whether a new DTLS association is to be established/re-established.
Appropriate Values: see [Section 4](#)
Contact name: Christer Holmberg
Mux Category: IDENTICAL

12. Acknowledgements

Thanks to Justin Uberti, Martin Thomson, Paul Kyzivat, Jens Guballa, Charles Eckel and Gonzalo Salgueiro for providing comments and suggestions on the document.

13. Change Log

[RFC EDITOR NOTE: Please remove this section when publishing]

Changes from [draft-ietf-mmusic-sdp-dtls-14](#)

- o Changes based on comments from Flemming:

- o - Additional dtls-is clarifications
- o - Editorial fixes

Changes from [draft-ietf-mmusic-sdp-dtls-13](#)

- o Text about the updated RFCs added to Abstract and Introduction
- o Reference to [RFC 5763](#) removed from [section 6](#) (ICE Considerations)
- o Reference to [RFC 5763](#) removed from [section 8](#) (SIP Considerations)

Changes from [draft-ietf-mmusic-sdp-dtls-12](#)

- o "unreliable" changed to "unordered"

Changes from [draft-ietf-mmusic-sdp-dtls-11](#)

- o Attribute name changed to dtls-id
- o Additional text based on comments from Roman Shpount.

Changes from [draft-ietf-mmusic-sdp-dtls-10](#)

- o Modified document to use dtls-id instead of dtls-connection
- o Changes are based on comments from Eric Rescorla, Justin Uberti, and Paul Kyzivat.

Changes from [draft-ietf-mmusic-sdp-dtls-08](#)

- o Offer/Answer section modified in order to allow sending of multiple SDP 'fingerprint' attributes.
- o Terminology made consistent: 'DTLS connection' replaced with 'DTLS association'.
- o Editorial changes based on comments from Paul Kyzivat.

Changes from [draft-ietf-mmusic-sdp-dtls-07](#)

- o Reference to [RFC 7315](#) replaced with reference to [RFC 7345](#).

Changes from [draft-ietf-mmusic-sdp-dtls-06](#)

- o Text on restrictions regarding spanning a DTLS association over multiple transports added.

- o Mux category added to IANA Considerations.
- o Normative text regarding mux category and source-specific applicability added.
- o Reference to [RFC 7315](#) added.
- o Clarified that offerer/answerer that has not been updated to support this specification will not include the dtls-id attribute in offers and answers.
- o Editorial corrections based on WGLC comments from Charles Eckel.

Changes from [draft-ietf-mmusic-sdp-dtls-05](#)

- o Text on handling offer/answer error conditions added.

Changes from [draft-ietf-mmusic-sdp-dtls-04](#)

- o Editorial nits fixed based on comments from Paul Kyzivat:

Changes from [draft-ietf-mmusic-sdp-dtls-03](#)

- o Changes based on comments from Paul Kyzivat:
 - o - Modification of dtls-id attribute section.
 - o - Removal of IANA considerations subsection.
 - o - Making note into normative text in o/a section.
- o Changes based on comments from Martin Thompson:
 - o - Abbreviations section removed.
 - o - Clarify that a new DTLS association requires a new o/a transaction.

Changes from [draft-ietf-mmusic-sdp-dtls-02](#)

- o - Updated RFCs added to boilerplate.

Changes from [draft-ietf-mmusic-sdp-dtls-01](#)

- o - Annex regarding 'dtls-id-id' attribute removed.
- o - Additional SDP offer/answer procedures, related to certificates, added.

- o - Updates to [RFC 5763](#) and [RFC 7345](#) added.
- o - Transport protocol considerations added.

Changes from [draft-ietf-mmusic-sdp-dtls-00](#)

- o - SDP 'connection' attribute replaced with new 'dtls-id' attribute.
- o - IANA Considerations added.
- o - E-mail regarding 'dtls-id-id' attribute added as Annex.

Changes from [draft-holmberg-mmusic-sdp-dtls-01](#)

- o - [draft-ietf-mmusic](#) version of draft submitted.
- o - Draft file name change (sdp-dtls -> dtls-sdp) due to collision with another expired draft.
- o - Clarify that if ufrag in offer is unchanged, it must be unchanged in associated answer.
- o - SIP Considerations section added.
- o - Section about multiple SDP fingerprint attributes added.

Changes from [draft-holmberg-mmusic-sdp-dtls-00](#)

- o - Editorial changes and clarifications.

[14.](#) References

[14.1.](#) Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<http://www.rfc-editor.org/info/rfc2119>>.
- [RFC3261] Rosenberg, J., Schulzrinne, H., Camarillo, G., Johnston, A., Peterson, J., Sparks, R., Handley, M., and E. Schooler, "SIP: Session Initiation Protocol", [RFC 3261](#), DOI 10.17487/RFC3261, June 2002, <<http://www.rfc-editor.org/info/rfc3261>>.

- [RFC3264] Rosenberg, J. and H. Schulzrinne, "An Offer/Answer Model with Session Description Protocol (SDP)", [RFC 3264](#), DOI 10.17487/RFC3264, June 2002, <<http://www.rfc-editor.org/info/rfc3264>>.
- [RFC4145] Yon, D. and G. Camarillo, "TCP-Based Media Transport in the Session Description Protocol (SDP)", [RFC 4145](#), DOI 10.17487/RFC4145, September 2005, <<http://www.rfc-editor.org/info/rfc4145>>.
- [RFC4566] Handley, M., Jacobson, V., and C. Perkins, "SDP: Session Description Protocol", [RFC 4566](#), DOI 10.17487/RFC4566, July 2006, <<http://www.rfc-editor.org/info/rfc4566>>.
- [RFC4572] Lennox, J., "Connection-Oriented Media Transport over the Transport Layer Security (TLS) Protocol in the Session Description Protocol (SDP)", [RFC 4572](#), DOI 10.17487/RFC4572, July 2006, <<http://www.rfc-editor.org/info/rfc4572>>.
- [RFC5763] Fischl, J., Tschofenig, H., and E. Rescorla, "Framework for Establishing a Secure Real-time Transport Protocol (SRTP) Security Context Using Datagram Transport Layer Security (DTLS)", [RFC 5763](#), DOI 10.17487/RFC5763, May 2010, <<http://www.rfc-editor.org/info/rfc5763>>.
- [RFC7345] Holmberg, C., Sedlacek, I., and G. Salgueiro, "UDP Transport Layer (UDPTL) over Datagram Transport Layer Security (DTLS)", [RFC 7345](#), DOI 10.17487/RFC7345, August 2014, <<http://www.rfc-editor.org/info/rfc7345>>.
- [I-D.ietf-mmusic-4572-update] Holmberg, C., "SDP Fingerprint Attribute Usage Clarifications", [draft-ietf-mmusic-4572-update-07](#) (work in progress), September 2016.

14.2. Informative References

- [RFC5576] Lennox, J., Ott, J., and T. Schierl, "Source-Specific Media Attributes in the Session Description Protocol (SDP)", [RFC 5576](#), DOI 10.17487/RFC5576, June 2009, <<http://www.rfc-editor.org/info/rfc5576>>.
- [RFC5764] McGrew, D. and E. Rescorla, "Datagram Transport Layer Security (DTLS) Extension to Establish Keys for the Secure Real-time Transport Protocol (SRTP)", [RFC 5764](#), DOI 10.17487/RFC5764, May 2010, <<http://www.rfc-editor.org/info/rfc5764>>.

[RFC6083] Tuexen, M., Seggelmann, R., and E. Rescorla, "Datagram Transport Layer Security (DTLS) for Stream Control Transmission Protocol (SCTP)", [RFC 6083](https://www.rfc-editor.org/info/rfc6083), DOI 10.17487/RFC6083, January 2011, <<http://www.rfc-editor.org/info/rfc6083>>.

[I-D.ietf-ice-rfc5245bis] Keranen, A., Holmberg, C., and J. Rosenberg, "Interactive Connectivity Establishment (ICE): A Protocol for Network Address Translator (NAT) Traversal", [draft-ietf-ice-rfc5245bis-04](https://datatracker.ietf.org/doc/draft-ietf-ice-rfc5245bis-04) (work in progress), June 2016.

[I-D.ietf-mmusic-sdp-mux-attributes] Nandakumar, S., "A Framework for SDP Attributes when Multiplexing", [draft-ietf-mmusic-sdp-mux-attributes-14](https://datatracker.ietf.org/doc/draft-ietf-mmusic-sdp-mux-attributes-14) (work in progress), September 2016.

[I-D.ietf-mmusic-sdp-bundle-negotiation] Holmberg, C., Alvestrand, H., and C. Jennings, "Negotiating Media Multiplexing Using the Session Description Protocol (SDP)", [draft-ietf-mmusic-sdp-bundle-negotiation-36](https://datatracker.ietf.org/doc/draft-ietf-mmusic-sdp-bundle-negotiation-36) (work in progress), October 2016.

Authors' Addresses

Christer Holmberg
Ericsson
Hirsalantie 11
Jorvas 02420
Finland

Email: christer.holmberg@ericsson.com

Roman Shpount
TurboBridge
4905 Del Ray Avenue, Suite 300
Bethesda, MD 20814
USA

Phone: +1 (240) 292-6632
Email: rshpount@turbobridge.com

