

MMUSIC
Internet-Draft
Intended status: Standards Track
Expires: September 21, 2013

A. Begen
Cisco
Y. Cai
Microsoft
H. Ou
Cisco
March 20, 2013

**Duplication Grouping Semantics in the Session Description Protocol
draft-ietf-mmusic-duplication-grouping-01**

Abstract

Packet loss is undesirable for real-time multimedia sessions, but can occur due to congestion, or other unplanned network outages. This is especially true for IP multicast networks, where packet loss patterns can vary greatly between receivers. One technique that can be used to recover from packet loss without incurring unbounded delay for all the receivers is to duplicate the packets and send them in separate redundant streams. This document defines the semantics for grouping redundant streams in the Session Description Protocol (SDP). The semantics defined in this document are to be used with the SDP Grouping Framework [[RFC5888](#)]. SSRC-level (Synchronization Source) grouping semantics are also defined in this document for RTP streams using SSRC multiplexing.

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on September 21, 2013.

Copyright Notice

Copyright (c) 2013 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	3
2.	Requirements Notation	3
3.	Duplication Grouping	3
3.1.	"DUP" Grouping Semantics	3
3.2.	Duplication Grouping for SSRC-Multiplexed RTP Streams	4
3.3.	SDP Offer/Answer Model Considerations	4
4.	SDP Examples	5
4.1.	Separate Source Addresses	5
4.2.	Separate Destination Addresses	5
4.3.	Temporal Redundancy	6
5.	Security Considerations	7
6.	IANA Considerations	7
7.	Acknowledgments	7
8.	References	8
8.1.	Normative References	8
8.2.	Informative References	8
	Authors' Addresses	9

1. Introduction

The Real-time Transport Protocol (RTP) [[RFC3550](#)] is widely used today for delivering IPTV traffic, and other real-time multimedia sessions. Many of these applications support very large numbers of receivers, and rely on intra-domain UDP/IP multicast for efficient distribution of traffic within the network.

While this combination has proved successful, there does exist a weakness. As [[RFC2354](#)] noted, packet loss is not avoidable, even in a carefully managed network. This loss might be due to congestion, it might also be a result of an unplanned outage caused by a flapping link, link or interface failure, a software bug, or a maintenance person accidentally cutting the wrong fiber. Since UDP/IP flows do not provide any means for detecting loss and retransmitting packets, it leaves up to the RTP layer and the applications to detect, and recover from, packet loss.

One technique to recover from packet loss without incurring unbounded delay for all the receivers is to duplicate the packets and send them in separate redundant streams. Variations on this idea have been implemented and deployed today [[IC2011](#)].

[[I-D.ietf-avtext-rtp-duplication](#)] explains how duplication can be achieved for RTP streams without breaking the RTP and RTP Control Protocol (RTCP) functionality. In this document, we describe the semantics needed in the Session Description Protocol (SDP) [[RFC4566](#)] to support this technique.

2. Requirements Notation

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

3. Duplication Grouping

3.1. "DUP" Grouping Semantics

Each "a=group" line is used to indicate an association relationship between the redundant streams. The streams included in one "a=group" line are called a Duplication Group.

Using the framework in [[RFC5888](#)], this document defines "DUP" as the grouping semantics for redundant streams.

The "a=group:DUP" semantics MUST be used to group the redundant streams except when the streams are specified in the same media description, i.e., in the same "m" line (See [Section 3.2](#)). In an "a=group:DUP" line, the order of the listed redundant streams does not strictly indicate the order of transmission, although it is RECOMMENDED that the stream listed first is sent first, with the other stream(s) being the (time-delayed) duplicate(s).

3.2. Duplication Grouping for SSRC-Multiplexed RTP Streams

[RFC5576] defines an SDP media-level attribute, called 'ssrc-group', for grouping the RTP streams that are SSRC multiplexed and carried in the same RTP session. The grouping is based on the SSRC identifiers. Since SSRC-multiplexed RTP streams are defined in the same "m" line, the 'group' attribute cannot be used.

This section explains how duplication is used with SSRC-multiplexed streams using the 'ssrc-group' attribute [[RFC5576](#)].

The semantics of "DUP" for the 'ssrc-group' attribute are the same as the one defined for the 'group' attribute except that the SSRC identifiers are used to designate the duplication grouping associations: a=ssrc-group:DUP *(SP ssrc-id) [[RFC5576](#)]. As above, while in an "a=ssrc-group:DUP" line, the order of the listed redundant streams does not necessarily indicate the order of transmission, it is RECOMMENDED that the stream listed first is sent first, with the other stream(s) being the (time-delayed) duplicate(s).

3.3. SDP Offer/Answer Model Considerations

When offering duplication grouping using SDP in an Offer/Answer model [[RFC3264](#)], the following considerations apply.

A node that is receiving an offer from a sender may or may not understand line grouping. It is also possible that the node understands line grouping but it does not understand the "DUP" semantics. From the viewpoint of the sender of the offer, these cases are indistinguishable.

When a node is offered a session with the "DUP" grouping semantics but it does not support line grouping or the duplication grouping semantics, as per [[RFC5888](#)], the node responds to the offer either (1) with an answer that ignores the grouping attribute or (2) with a refusal to the request (e.g., 488 Not Acceptable Here or 606 Not Acceptable in SIP).

In the first case, the original sender of the offer must send a new

offer without any duplication grouping. In the second case, if the sender of the offer still wishes to establish the session, it should retry the request with an offer without the duplication grouping. This behavior is specified in [[RFC5888](#)].

4. SDP Examples

4.1. Separate Source Addresses

In this example, the redundant streams use the same IP destination address (232.252.0.1) but they are sourced from different addresses (198.51.100.1 and 198.51.100.2). Thus, the receiving host needs to join both SSM sessions separately.

```
v=0
o=ali 1122334455 1122334466 IN IP4 dup.example.com
s=DUP Grouping Semantics
t=0 0
m=video 30000 RTP/AVP 100
c=IN IP4 232.252.0.1/127
a=source-filter:incl IN IP4 232.252.0.1 198.51.100.1 198.51.100.2
a=rtpmap:100 MP2T/90000
a=ssrc:1000 cname:ch1@example.com
a=ssrc:1010 cname:ch1@example.com
a=ssrc-group:DUP 1000 1010
a=mid:Ch1
```

Note that in actual use, SSRC values, which are random 32-bit numbers, can be much larger than the ones shown in this example. Also note that this SDP description does not use the 'duplication-delay' attribute (defined in [[I-D.ietf-mmusic-delayed-duplication](#)]) since the sender does not apply any delay between the redundant streams upon transmission. Alternatively, one could be more explicit and insert an "a=duplication-delay:0" line before the "a=mid:Ch1" line.

4.2. Separate Destination Addresses

In this example, the redundant streams have different IP destination addresses. The example shows the same UDP port number and IP source address for each stream, but either or both could have been different for the two streams.


```
v=0
o=ali 1122334455 1122334466 IN IP4 dup.example.com
s=DUP Grouping Semantics
t=0 0
a=group:DUP S1a S1b
m=video 30000 RTP/AVP 100
c=IN IP4 233.252.0.1/127
a=source-filter:incl IN IP4 233.252.0.1 198.51.100.1
a=rtpmap:100 MP2T/90000
a=mid:S1a
m=video 30000 RTP/AVP 101
c=IN IP4 233.252.0.2/127
a=source-filter:incl IN IP4 233.252.0.2 198.51.100.1
a=rtpmap:101 MP2T/90000
a=mid:S1b
```

Optionally, one could be more explicit and insert an "a=duplication-delay:0" line before the first "m" line.

4.3. Temporal Redundancy

In this example, the redundant streams have the same IP source and destination addresses (i.e., they are transmitted in the same SSM session). Due to the same source and destination addresses, the packets in both streams will be routed over the same path. To provide resiliency against packet loss, the duplicate of an original packet is transmitted 50 ms later as indicated by the 'duplication-delay' attribute (defined in [[I-D.ietf-mmusic-delayed-duplication](#)]).

```
v=0
o=ali 1122334455 1122334466 IN IP4 dup.example.com
s=Delayed Duplication
t=0 0
m=video 30000 RTP/AVP 100
c=IN IP4 233.252.0.1/127
a=source-filter:incl IN IP4 233.252.0.1 198.51.100.1
a=rtpmap:100 MP2T/90000
a=ssrc:1000 cname:ch1a@example.com
a=ssrc:1010 cname:ch1a@example.com
a=ssrc-group:DUP 1000 1010
a=duplication-delay:50
a=mid:Ch1
```


5. Security Considerations

There is a weak threat for the receiver that the duplication grouping can be modified to indicate relationships that do not exist. Such attacks might result in failure of the duplication mechanisms, and/or mishandling of the media streams by the receivers.

In order to avoid attacks of this sort, the SDP description needs to be integrity protected and provided with source authentication. This can, for example, be achieved on an end-to-end basis using S/MIME [RFC5652] [RFC5751] when the SDP is used in a signaling packet using MIME types (application/sdp). Alternatively, HTTPS [RFC2818] or the authentication method in the Session Announcement Protocol (SAP) [RFC2974] could be used as well.

6. IANA Considerations

This document registers the following semantics with IANA in Semantics for the 'group' SDP Attribute under SDP Parameters:

Note to the RFC Editor: In the following registrations, please replace "XXXX" with the number of this document prior to publication as an RFC.

Semantics	Token	Reference
-----	-----	-----
Duplication	DUP	[RFCXXXX]

This document also registers the following semantics with IANA in Semantics for the 'ssrc-group' SDP Attribute under SDP Parameters:

Token	Semantics	Reference
-----	-----	-----
DUP	Duplication	[RFCXXXX]

7. Acknowledgments

The authors would like to thank Colin Perkins, Bill Ver Steeg, Dave Oran and Toerless Eckert for their inputs and suggestions.

8. References

8.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC3264] Rosenberg, J. and H. Schulzrinne, "An Offer/Answer Model with Session Description Protocol (SDP)", [RFC 3264](#), June 2002.
- [RFC3550] Schulzrinne, H., Casner, S., Frederick, R., and V. Jacobson, "RTP: A Transport Protocol for Real-Time Applications", STD 64, [RFC 3550](#), July 2003.
- [RFC4566] Handley, M., Jacobson, V., and C. Perkins, "SDP: Session Description Protocol", [RFC 4566](#), July 2006.
- [RFC5576] Lennox, J., Ott, J., and T. Schierl, "Source-Specific Media Attributes in the Session Description Protocol (SDP)", [RFC 5576](#), June 2009.
- [RFC5888] Camarillo, G. and H. Schulzrinne, "The Session Description Protocol (SDP) Grouping Framework", [RFC 5888](#), June 2010.

8.2. Informative References

- [I-D.ietf-avtext-rtp-duplication]
Begen, A. and C. Perkins, "Duplicating RTP Streams", [draft-ietf-avtext-rtp-duplication-01](#) (work in progress), December 2012.
- [I-D.ietf-mmusic-delayed-duplication]
Begen, A., Cai, Y., and H. Ou, "Delayed Duplication Attribute in the Session Description Protocol", [draft-ietf-mmusic-delayed-duplication-00](#) (work in progress), October 2012.
- [IC2011] Evans, J., Begen, A., Greengrass, J., and C. Filsfils, "Toward Lossless Video Transport (to appear in IEEE Internet Computing)", November 2011.
- [RFC2354] Perkins, C. and O. Hodson, "Options for Repair of Streaming Media", [RFC 2354](#), June 1998.
- [RFC2818] Rescorla, E., "HTTP Over TLS", [RFC 2818](#), May 2000.
- [RFC2974] Handley, M., Perkins, C., and E. Whelan, "Session Announcement Protocol", [RFC 2974](#), October 2000.

[RFC5652] Housley, R., "Cryptographic Message Syntax (CMS)", STD 70, [RFC 5652](#), September 2009.

[RFC5751] Ramsdell, B. and S. Turner, "Secure/Multipurpose Internet Mail Extensions (S/MIME) Version 3.2 Message Specification", [RFC 5751](#), January 2010.

Authors' Addresses

Ali Begen
Cisco
181 Bay Street
Toronto, ON M5J 2T3
Canada

Email: abegen@cisco.com

Yiqun Cai
Microsoft
1065 La Avenida
Mountain View, CA 94043
USA

Email: yiqunc@microsoft.com

Heidi Ou
Cisco
170 W. Tasman Dr.
San Jose, CA 95134
USA

Email: hou@cisco.com

