Network Working Group Internet-Draft Updates: <u>5761</u> (if approved) Intended status: Standards Track Expires: December 12, 2016

# Indicating Exclusive Support of RTP/RTCP Multiplexing using SDP draft-ietf-mmusic-mux-exclusive-07

#### Abstract

This document defines a new SDP media-level attribute, 'rtcp-muxonly', that can be used by an endpoint to indicate exclusive support of RTP/RTCP multiplexing. The document also updates <u>RFC 5761</u>, by clarifying that an offerer can use a mechanism to indicate that it is not able to send and receive RTCP on separate ports.

### Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of <u>BCP 78</u> and <u>BCP 79</u>.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <a href="http://datatracker.ietf.org/drafts/current/">http://datatracker.ietf.org/drafts/current/</a>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on December 12, 2016.

## Copyright Notice

Copyright (c) 2016 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to <u>BCP 78</u> and the IETF Trust's Legal Provisions Relating to IETF Documents (<u>http://trustee.ietf.org/license-info</u>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in <u>Section 4</u>.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

This document may contain material from IETF Documents or IETF Contributions published or made publicly available before November 10, 2008. The person(s) controlling the copyright in some of this material may not have granted the IETF Trust the right to allow modifications of such material outside the IETF Standards Process. Without obtaining an adequate license from the person(s) controlling the copyright in such materials, this document may not be modified outside the IETF Standards Process, and derivative works of it may not be created outside the IETF Standards Process, except to format it for publication as an RFC or to translate it into languages other than English.

# Table of Contents

<u>1</u> . ]	ntroduction
<u>2</u> . (	onventions
<u>3</u> . 9	DP rtcp-mux-only Attribute
<u>4</u> . S	DP Offer/Answer Procedures
4.1	. General
4.2	. Generating the Initial SDP Offer
4.3	. Generating the Answer
4.4	. Offerer Processing of the SDP Answer
4.5	. Modifying the Session
<u>5</u> . ເ	pdate to <u>RFC 5761</u>
5.2	. General
5.2	. Update to 4th paragraph of <u>section 5.1.1</u>
<u>5.3</u>	. Update to 2nd paragraph of <u>section 5.1.3</u>
<u>6</u> . ]	CE Considerations
<u>7</u> . s	ecurity Considerations
<u>8</u> . ]	ANA Considerations
<u>9</u> . A	cknowledgments
<u>10</u> . (	hange Log
<u>11</u> . F	eferences
11	<u>1</u> . Normative References
11	2. Informative References
Autho	r's Address

## 1. Introduction

[RFC5761] defines how to multiplex RTP and RTCP on a single IP address and port, referred to as RTP/RTCP multiplexing. [RFC5761] also defines an Session Description Protocol (SDP) [RFC4566] attribute, 'rtcp-mux' that can be used by entities to indicate support, and negotiate usage of, RTP/RTCP multiplexing.

Internet-Draft

Exclusive RTP/RTCP Mux

As defined in [<u>RFC5761</u>], if the peer endpoint does not support RTP/ RTCP multiplexing, both endpoints should use separate ports for sending and receiving of RTCP (referred to as fallback to usage of separate ports for RTP and RTCP).

Some newer applications that do not require backward compatibility with peers that cannot multiplex RTCP might choose to not implement separation of RTP and RTCP. For those applications, this document defines an SDP attribute to signal intent to require multiplexing.

This document defines a new SDP media-level attribute, 'rtcp-muxonly', that can be used by an endpoint to indicate exclusive support of RTP/RTCP multiplexing. The document also updates <u>RFC 5761</u>, by clarifying that an offerer can use a mechanism to indicate that it is not able to send and receive RTCP on separate ports.

The document also describes the Interactive Connectivity Establishment (ICE) [<u>RFC5245</u>] considerations when indicating exclusive support of RTP/RTCP multiplexing.

## 2. Conventions

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC2119].

### 3. SDP rtcp-mux-only Attribute

This section defines a new SDP media-level attribute, 'rtcp-mux-only'.

Name: rtcp-mux-only Value: N/A Usage Level: media Charset Dependent: no Syntax:

rtcp-mux-only

Example:

a=rtcp-mux-only

Holmberg Expires December 12, 2016 [Page 3]

In an SDP offer, the offerer uses the SDP 'rtcp-mux-only' attribute to indicate exclusive support of RTP/RTCP multiplexing for the RTP-based media associated with the SDP media description ("m=" line).

In an SDP answer, the 'rtcp-mux-only' attribute indicates that the answerer supports, and accepts usage of, RTP/RTCP multiplexing for the RTP-based media associated with the SDP media description ("m=" line).

The usage of the SDP 'rtcp-mux-only' attribute is only defined for RTP-based media.

The mux category [<u>I-D.ietf-mmusic-sdp-mux-attributes</u>] for the 'rtcpmux-only' attribute is 'IDENTICAL', which means that the attribute, if used within a BUNDLE group [<u>I-D.ietf-mmusic-sdp-bundle-negotiation</u>], must be associated with all multiplexed RTP-based media descriptions within the BUNDLE group.

The 'rtcp-mux-only' attribute applies to the whole associated media description. The attribute MUST NOT be defined per source (using the SDP 'ssrc' attribute [<u>RFC5576</u>]).

The SDP offer/answer [RFC3264] procedures associated with the attribute are defined in Section 4

## 4. SDP Offer/Answer Procedures

#### 4.1. General

This section defines the SDP offer/answer [<u>RFC3264</u>] procedures for indicating exclusive support of, and negotiating usage of, RTP/RTCP multiplexing.

The procedures in this section apply to individual RTP-based SDP media descriptions ("m=" lines).

### 4.2. Generating the Initial SDP Offer

When an offerer sends the initial offer, if the offerer wants to indicate exclusive RTP/RTCP multiplexing for RTP-based media, the offerer MUST associate an SDP 'rtcp-mux-only' attribute with the associated SDP media description ("m=" line).

In addition, if the offerer associates an SDP 'rtcp-mux-only' attribute with an SDP media description ("m=" line), the offerer MAY also associate an SDP 'rtcp-mux' attribute with the same SDP media description ("m=" line), following the procedures in [<u>RFC5761</u>].

If the offerer associates an SDP 'rtcp' attribute [<u>RFC3605</u>] with an SDP media description ("m=" line), and if the offerer also associates an SDP 'rtcp-mux-only' attribute with the same SDP media description ("m=" line), the address and port values of the SDP 'rtcp' attribute MUST match the corresponding values for RTP.

NOTE: This specification does not mandate the usage of the SDP 'rtcp' attribute for RTP/RTCP multiplexing.

#### 4.3. Generating the Answer

When an answerer receives an offer that contains an SDP 'rtcp-muxonly' attribute, associated with an RTP-based SDP media description ("m=" line), if the answerer accepts the usage of RTP/RTCP multiplexing, the answerer MUST associate an SDP 'rtcp-mux-only' attribute with the corresponding SDP media description ("m=") in the associated answer. If the answerer does not accept the usage of RTP/ RTCP multiplexing, the answerer MUST either reject the SDP media description ("m=") by setting the port value to zero in the associated answer, or reject the whole offer, following the procedures in [RFC3264].

In addition, if the answerer associates an SDP 'rtcp-mux-only' attribute with an SDP media description ("m=" line) in the answer, and if the corresponding "m=" line in the associated offer contained an SDP 'rtcp-mux' attribute, the answerer MUST in addition associate an SDP 'rtcp-mux' attribute with the same "m=" line, following the procedures in [RFC5761].

### 4.4. Offerer Processing of the SDP Answer

If an offerer associated an SDP 'rtcp-mux-only' attribute with an RTP-based SDP media description ("m=" line) in an offer, and if the corresponding SDP media description ("m=" line) in the associated answer contains an SDP 'rtcp-mux-only' attribute, and/or an SDP 'rtcp-mux' attribute, the offerer MUST apply the RTP/RTCP multiplexing procedures [RFC5761] to the associated RTP-based media. If the corresponding SDP media description ("m=" line) in the associated answer does not contain an SDP 'rtcp-mux-only' attribute, nor an SDP 'rtcp-mux' attribute, the offerer MUST either take appropriate actions in order to disable the associated RTP-based media, or send a new offer without associating an SDP 'rtcp-mux-only' attribute with the SDP media description ("m=" line).

NOTE: This document does not mandate specific actions on how to terminate the RTP media. The offerer might e.g. send a new offer, where the port value of the SDP media description is set to zero, in order to terminate the RTP media.

# <u>4.5</u>. Modifying the Session

When an offerer sends a subsequent offer, if the offerer and answerer have previously negotiated usage of exclusive RTP/RTCP multiplexing for the media associated with an RTP-based SDP media description ("m=" line), the offerer SHOULD associate an SDP 'rtcp-mux-only' with the corresponding SDP media description ("m=" line).

In addition, if the offerer associates an SDP 'rtcp-mux-only' attribute with an SDP media description ("m=" line), the offerer MAY also associate an SDP 'rtcp-mux' attribute with the same SDP media description ("m=" line), following the procedures in [RFC5761].

If the offerer does not associate the attributes with the corresponding SDP media description ("m=" line) it is an indication that the offerer no longer wants to use RTP/RTCP multiplexing, and instead MUST fallback to usage of separate ports for RTP and RTCP once the offer has been accepted by the answerer.

When an offerer sends a subsequent offer, if the offerer and answerer have not previously negotiated usage of RTP/RTCP multiplexing for the media associated with an RTP-based SDP media description ("m=" line), the offerer MAY indicate exclusive support of RTP/RTCP multiplexing, following the procedures in <u>Section 4.2</u>. The offerer MUST process the associated answer following the procedures in <u>Section 4.4</u>.

NOTE: It is RECOMMENDED to not switch between usage of RTP/RTCP multiplexing and usage of separate ports for RTP and RTCP in a subsequent offer, unless there is a use-case that mandates it.

## 5. Update to <u>RFC 5761</u>

## 5.1. General

This section updates sections <u>5.1.1</u> and <u>5.1.3</u> of <u>RFC 5761</u>, by clarifying that an offerer can use a mechanism to indicate that it is not able to send and receive RTCP on separate ports, and that the offerer shall terminate the affected streams if the answerer does not indicate support of RTP/RTCP multiplexing. It also clarifies that, when the offerer is not able to send and receive RTCP on separate ports, the offerer will not provide an SDP 'candidate' attribute for RTCP, nor will the offerer provide a fallback port for RTCP (using the SDP 'rtcp' attribute).

# 5.2. Update to 4th paragraph of section 5.1.1

### OLD TEXT:

If the answer does not contain an "a=rtcp-mux" attribute, the offerer MUST NOT multiplex RTP and RTCP packets on a single port. Instead, it should send and receive RTCP on a port allocated according to the usual port-selection rules (either the port pair, or a signalled port if the "a=rtcp:" attribute [10] is also included). This will occur when talking to a peer that does not understand the "a=rtcp-mux" attribute.

## NEW TEXT:

If the answer does not contain an "a=rtcp-mux" attribute, the offerer MUST NOT multiplex RTP and RTCP packets on a single port. Instead, it should send and receive RTCP on a port allocated according to the usual port-selection rules (either the port pair, or a signalled port if the "a=rtcp:" attribute [10] is also included). This will occur when talking to a peer that does not understand the "a=rtcp-mux" attribute. However, if the offerer indicated in the offer that it is not able to send and receive RTCP on a separate port, the offerer MUST disable the media streams associated with the attribute. The mechanism for indicating that the offerer is not able to send and receive RTCP on a separate port is outside the scope of this specification.

5.3. Update to 2nd paragraph of section 5.1.3

Expires December 12, 2016 [Page 7]

## OLD TEXT:

If it is desired to use both ICE and multiplexed RTP and RTCP, the initial offer MUST contain an "a=rtcp-mux" attribute to indicate that RTP and RTCP multiplexing is desired and MUST contain "a=candidate:" lines for both RTP and RTCP along with an "a=rtcp:" line indicating a fallback port for RTCP in the case that the answerer does not support RTP and RTCP multiplexing. This MUST be done for each media where RTP and RTCP multiplexing is desired.

# NEW TEXT:

If it is desired to use both ICE and multiplexed RTP and RTCP, the initial offer MUST contain an "a=rtcp-mux" attribute to indicate that RTP and RTCP multiplexing is desired and MUST contain "a=candidate:" lines for both RTP and RTCP along with an "a=rtcp:" line indicating a fallback port for RTCP in the case that the answerer does not support RTP and RTCP multiplexing. This MUST be done for each media where RTP and RTCP multiplexing is desired. However, if the offerer indicates in the offer that it is not able to send and receive RTCP on a separate port, the offerer MUST NOT include "a=candidiate:" lines for RTCP, and the offerer MUST NOT provide a fallback port for RTCP using the "a=rtcp:" line.

## **<u>6</u>**. ICE Considerations

As defined in [RFC5245], if an entity is aware that the remote peer supports, and is willing to use, RTP/RTCP multiplexing, the entity will only provide RTP candidates (component ID 1). However, only providing RTP candidates does not as such imply exclusive support of RTP/RTCP multiplexing. RTCP candidates would not be provided also in cases where RTCP is not supported at all. Therefore, additional information is needed in order to indicate support of exclusive RTP/ RTCP multiplexing. This document defines such mechanism using the SDP 'rtcp-mux-only' attributes.

### 7. Security Considerations

This document does not introduce new security considerations in additions to those specified in [<u>RFC3605</u>] and [<u>RFC5761</u>].

## 8. IANA Considerations

This document updates the "Session Description Protocol Parameters" registry as specified in <u>Section 8.2.2 of [RFC4566]</u>. Specifically,

## Internet-Draft

it adds the SDP 'rtcp-mux-only' attribute to the table for SDP media level attributes.

Attribute name: rtcp-mux-only Type of attribute: media-level Subject to charset: no Purpose: Indicate exclusive support of RTP/RTCP multiplexing Appropriate Values: N/A Contact name: Christer Holmberg (christert.holmberg@ericsson.com) Mux Category: IDENTICAL

## 9. Acknowledgments

Thanks to Roman Shpount, Paul Kyzivat, Ari Keranen, Bo Burman, Tomas Frankkila and Martin Thomson for their comments and input on the document.

# **10**. Change Log

[RFC EDITOR NOTE: Please remove this section when publishing]

Changes from <u>draft-ietf-mmusic-rtcp-mux-exclusive-06</u>

- o Editorial fix.
- o Addition of pre-RFC5378 disclaimer.

Changes from <u>draft-ietf-mmusic-rtcp-mux-exclusive-05</u>

o Editorial fix.

Changes from draft-ietf-mmusic-rtcp-mux-exclusive-04

- o Changes based on comments from Flemming Andreasen.
- o Attribute mux category changed to IDENTICAL.
- o Reference to draft-5245bis changed to RFC 5245.

Changes from <u>draft-ietf-mmusic-rtcp-mux-exclusive-03</u>

- o Editorial changes based on comments from Martin Thomson.
- o Change of attribute name.

Holmberg Expires December 12, 2016 [Page 9]

- o <u>RFC 5761</u> updates added.
- Changes from draft-ietf-mmusic-rtcp-mux-exclusive-02
- o Minor editorial fix.
- Changes from <u>draft-ietf-mmusic-rtcp-mux-exclusive-01</u>
- o Mux category and source-specific applicability added.

Changes from <u>draft-ietf-mmusic-rtcp-mux-exclusive-00</u>

- o Defined new SDP attribute for indicating rtcp-mux-exclusive.
- o Updates to <u>RFC 5761</u> removed.
- o IANA considerations added.

Changes from draft-holmberg-mmusic-rtcp-mux-exclusive-03

o Submitted as <u>draft-ietf-mmusic-rtcp-mux-exclusive-00</u>.

Changes from <u>draft-holmberg-mmusic-rtcp-mux-exclusive-02</u>

o Intended status changed to "Standards track".

Changes from <u>draft-holmberg-mmusic-rtcp-mux-exclusive-01</u>

o Clarified that the SDP rtcp attribute may contain the optional IP address part.

Changes from <u>draft-holmberg-mmusic-rtcp-mux-exclusive-00</u>

- o Additional updates to <u>Section 5.1.1 of RFC 5761</u>.
- o ICE considerations added.

### **<u>11</u>**. References

## <u>**11.1</u>**. Normative References</u>

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", <u>BCP 14</u>, <u>RFC 2119</u>, DOI 10.17487/RFC2119, March 1997, <<u>http://www.rfc-editor.org/info/rfc2119</u>>.

Expires December 12, 2016 [Page 10]

- [RFC3264] Rosenberg, J. and H. Schulzrinne, "An Offer/Answer Model with Session Description Protocol (SDP)", <u>RFC 3264</u>, DOI 10.17487/RFC3264, June 2002, <<u>http://www.rfc-editor.org/info/rfc3264</u>>.
- [RFC4566] Handley, M., Jacobson, V., and C. Perkins, "SDP: Session Description Protocol", <u>RFC 4566</u>, DOI 10.17487/RFC4566, July 2006, <<u>http://www.rfc-editor.org/info/rfc4566</u>>.
- [RFC5245] Rosenberg, J., "Interactive Connectivity Establishment (ICE): A Protocol for Network Address Translator (NAT) Traversal for Offer/Answer Protocols", <u>RFC 5245</u>, DOI 10.17487/RFC5245, April 2010, <<u>http://www.rfc-editor.org/info/rfc5245</u>>.
- [RFC5761] Perkins, C. and M. Westerlund, "Multiplexing RTP Data and Control Packets on a Single Port", <u>RFC 5761</u>, DOI 10.17487/RFC5761, April 2010, <<u>http://www.rfc-editor.org/info/rfc5761</u>>.

### <u>11.2</u>. Informative References

- [RFC3605] Huitema, C., "Real Time Control Protocol (RTCP) attribute in Session Description Protocol (SDP)", <u>RFC 3605</u>, DOI 10.17487/RFC3605, October 2003, <<u>http://www.rfc-editor.org/info/rfc3605</u>>.
- [RFC5576] Lennox, J., Ott, J., and T. Schierl, "Source-Specific Media Attributes in the Session Description Protocol (SDP)", <u>RFC 5576</u>, DOI 10.17487/RFC5576, June 2009, <<u>http://www.rfc-editor.org/info/rfc5576</u>>.
- [I-D.ietf-mmusic-sdp-mux-attributes]
  Nandakumar, S., "A Framework for SDP Attributes when
  Multiplexing", draft-ietf-mmusic-sdp-mux-attributes-12
  (work in progress), January 2016.

[I-D.ietf-mmusic-sdp-bundle-negotiation] Holmberg, C., Alvestrand, H., and C. Jennings, "Negotiating Media Multiplexing Using the Session Description Protocol (SDP)", <u>draft-ietf-mmusic-sdp-bundle-negotiation-30</u> (work in progress), June 2016.

Author's Address

Christer Holmberg Ericsson Hirsalantie 11 Jorvas 02420 Finland

Email: christer.holmberg@ericsson.com