

MPLS Working Group
Internet-Draft
Intended status: Standards Track
Expires: March 15, 2020

T. Saad
Juniper Networks
K. Raza
R. Gandhi
Cisco Systems Inc
X. Liu
Volta Networks
V. Beeram
Juniper Networks
September 12, 2019

A YANG Data Model for MPLS Base draft-ietf-mpls-base-yang-11

Abstract

This document contains a specification of the MPLS base YANG model. The MPLS base YANG model serves as a base framework for configuring and managing an MPLS switching subsystem on an MPLS-enabled router. It is expected that other MPLS YANG models (e.g. MPLS LSP Static, LDP or RSVP-TE YANG models) will augment the MPLS base YANG model.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on March 15, 2020.

Copyright Notice

Copyright (c) 2019 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of

publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	2
1.1.	Terminology	3
1.2.	Acronyms and Abbreviations	3
2.	MPLS Base Model	3
2.1.	Model Overview	3
2.2.	Model Organization	4
2.3.	Model Tree Diagram	5
2.4.	Model YANG Module	7
3.	IANA Considerations	15
4.	Security Considerations	16
5.	Acknowledgement	16
6.	Contributors	16
7.	References	17
7.1.	Normative References	17
7.2.	Informative References	18
	Authors' Addresses	18

[1.](#) Introduction

A core routing data model is defined in [[RFC8349](#)], and it provides a basis for the development of data models for routing protocols. The MPLS base model augments core routing data model with additional data specific to MPLS technology as described in the MPLS architecture document [[RFC3031](#)].

The MPLS base model serves as a basis for future development of MPLS data models covering more-sophisticated MPLS feature(s) and sub-system(s). The main purpose is to provide essential building blocks for the more-complicated data models involving different control-plane protocols, and advanced MPLS functions.

To this end, it is expected that the MPLS base data model will be augmented by a number of other modules developed at IETF (e.g. by TEAS and MPLS working groups).

The YANG module in this document conforms to the Network Management Datastore Architecture (NMDA) [[RFC8342](#)].

1.1. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [BCP 14](#) [[RFC2119](#)] [[RFC8174](#)] when, and only when, they appear in all capitals, as shown here.

The terminology for describing YANG data models is found in [[RFC7950](#)].

1.2. Acronyms and Abbreviations

MPLS: Multiprotocol Label Switching

RIB: Routing Information Base

LSP: Label Switched Path

LSR: Label Switching Router

LER: Label Edge Router

FEC: Forwarding Equivalence Class

NHLFE: Next Hop Label Forwarding Entry

ILM: Incoming Label Map

2. MPLS Base Model


This document describes the ietf-mpls YANG module that provides base components of the MPLS data model. It is expected that other MPLS YANG modules will augment the ietf-mpls base module for other MPLS extension to provision LSP(s) (e.g. MPLS Static, MPLS LDP or MPLS RSVP-TE LSP(s)).

2.1. Model Overview

This document defines a mechanism to model MPLS labeled routes as an augmentation of the routing RIB data model defined in [[RFC8349](#)] for IP prefix routes that are MPLS labeled.

The other MPLS route(s) that are non-IP prefix routes are modelled by introducing a new "mpls" address-family RIB as per recommendation .

2.2. Model Organization



@: not in this document, shown for illustration only

Figure 1: Relationship between MPLS modules

ietf-mpls module contains the following high-level types and groupings:

label-block-alloc-mode:

A base YANG identity for supported label block allocation mode(s).

mpls-operations-type:

An enumeration type that represents support possible MPLS operation types (impose-and-forward, pop-and-forward, pop-impose-and-forward, and pop-and-lookup)

nhlfe-role:

An enumeration type that represents the role of the NHLFE entry.

nhlfe-single-contents:

A YANG grouping that describes single NHLFE and its associated parameters as described in the MPLS architecture document [[RFC3031](#)].

nhlfe-multiple-contents:

A YANG grouping that describes a set of NHLFE(s) and their associated parameters as described in the MPLS architecture document [[RFC3031](#)].

interface-mpls-properties:

A YANG grouping that describes the properties of an MPLS interface on a device.

interfaces-mpls:

A YANG grouping that describes the list of MPLS enabled interfaces on a device.

label-block-properties:

A YANG grouping that describes the properties of an MPLS label block.

label-blocks:

A YANG grouping that describes the list of MPLS enabled interfaces on a device.

[2.3.](#) Model Tree Diagram

The MPLS base tree diagram that follows the notation defined in [[RFC8340](#)] is shown in Figure 2.

```
module: ietf-mpls
  augment /rt:routing:
    +--rw mpls
      +--rw ttl-propagate?  boolean
      +--rw label-blocks
      |  +--rw label-block* [index]
      |  |  +--rw index                string
      |  |  +--rw start-label?         rt-types:mpls-label
      |  |  +--rw end-label?           rt-types:mpls-label
      |  |  +--rw block-allocation-mode? identityref
      |  |  +--ro free-labels-count?   yang:counter32
      |  |  +--ro inuse-labels-count?  yang:counter32
      |  +--rw interface* [name]
      |  |  +--rw name                if:interface-ref
      |  |  +--rw enabled?            boolean
      |  |  +--rw mtu?                uint32
      +--ro mpls-enabled?  boolean
      +--ro local-label?   rt-types:mpls-label
```



```

augment /rt:routing/rt:ribs/rt:rib/rt:routes/rt:route/rt:next-hop
  /rt:next-hop-options/rt:simple-next-hop:
  +--ro mpls-label-stack
    +--ro entry* [id]
      +--ro id          uint8
      +--ro label?      rt-types:mpls-label
      +--ro ttl?        uint8
      +--ro traffic-class? uint8
augment /rt:routing/rt:ribs/rt:rib/rt:routes/rt:route/rt:next-hop
  /rt:next-hop-options/rt:next-hop-list/rt:next-hop-list
  /rt:next-hop:
  +--ro index?          string
  +--ro backup-index?   string
  +--ro loadshare?      uint16
  +--ro role?           nhlfe-role
  +--ro mpls-label-stack
    +--ro entry* [id]
      +--ro id          uint8
      +--ro label?      rt-types:mpls-label
      +--ro ttl?        uint8
      +--ro traffic-class? uint8
augment /rt:routing/rt:ribs/rt:rib/rt:active-route/rt:input:
  +---w local-label?    rt-types:mpls-label
augment /rt:routing/rt:ribs/rt:rib/rt:active-route/rt:output/rt:route
  /rt:next-hop/rt:next-hop-options/rt:simple-next-hop:
  +-- mpls-label-stack
    +-- entry* [id]
      +-- id          uint8
      +-- label?      rt-types:mpls-label
      +-- ttl?        uint8
      +-- traffic-class? uint8
augment /rt:routing/rt:ribs/rt:rib/rt:active-route/rt:output/rt:route
  /rt:next-hop/rt:next-hop-options/rt:next-hop-list
  /rt:next-hop-list/rt:next-hop:
  +-- index?          string
  +-- backup-index?   string
  +-- loadshare?      uint16
  +-- role?           nhlfe-role
  +-- mpls-label-stack
    +-- entry* [id]
      +-- id          uint8
      +-- label?      rt-types:mpls-label
      +-- ttl?        uint8
      +-- traffic-class? uint8

```

Figure 2: MPLS Base tree diagram

2.4. Model YANG Module

This section describes the "ietf-mpls" YANG module that provides base components of the MPLS data model. Other YANG module(s) may import and augment the base MPLS module to add feature specific data.

The ietf-mpls module imports the following modules:

- o ietf-routing defined in [[RFC8349](#)]
- o ietf-routing-types defined in [[RFC8294](#)]
- o ietf-interfaces defined in [[RFC8343](#)]

```
<CODE BEGINS> file "ietf-mpls@2019-09-11.yang"
module ietf-mpls {
  yang-version 1.1;

  namespace "urn:ietf:params:xml:ns:yang:ietf-mpls";

  /* Replace with IANA when assigned */
  prefix "mpls";

  import ietf-routing {
    prefix "rt";
    reference "RFC8349: A YANG Data Model for Routing Management";
  }

  import ietf-routing-types {
    prefix "rt-types";
    reference "RFC8294: Common YANG Data Types for the Routing Area";
  }

  import ietf-yang-types {
    prefix "yang";
    reference "RFC6991: Common YANG Data Types";
  }

  import ietf-interfaces {
    prefix "if";
    reference "RFC8343: A YANG Data Model for Interface Management";
  }

  organization "IETF MPLS Working Group";

  contact
    "WG Web:  <http://tools.ietf.org/wg/mpls/>
```


WG List: <mailto:mpls@ietf.org>

Editor: Tarek Saad
<mailto:tsaad@cisco.com>

Editor: Kamran Raza
<mailto:skraza@cisco.com>

Editor: Rakesh Gandhi
<mailto:rgandhi@cisco.com>

Editor: Xufeng Liu
<mailto:xufeng.liu.ietf@gmail.com>

Editor: Vishnu Pavan Beeram
<mailto:vbeeram@juniper.net>;

description

"This YANG module defines the essential components for the management of the MPLS subsystem. The model fully conforms to the Network Management Datastore Architecture (NMDA).

Copyright (c) 2018 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Simplified BSD License set forth in [Section 4.c](#) of the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>).

This version of this YANG module is part of RFC XXXX; see the RFC itself for full legal notices."

// RFC Ed.: replace XXXX with actual RFC number and remove this
// note.

// RFC Ed.: update the date below with the date of RFC publication
// and remove this note.

```
revision "2019-09-11" {  
  description  
    "Latest revision:  
     - Addressed review comments";  
  reference "RFC XXXX: A YANG Data Model for base MPLS";  
}
```

/* Identities */


```
identity mpls {
  base rt:address-family;
  description
    "This identity represents the MPLS address family.";
}

identity label-block-alloc-mode {
  description
    "Base identity label-block allocation mode";
}

identity label-block-alloc-mode-manager {
  base label-block-alloc-mode;
  description
    "Label block allocation on reserved block
    is managed by label manager";
}

identity label-block-alloc-mode-application {
  base label-block-alloc-mode;
  description
    "Label block allocation on reserved block
    is managed by application";
}

/**
 * Typedefs
 */
typedef mpls-operations-type {
  type enumeration {
    enum impose-and-forward {
      description
        "Operation impose outgoing label(s) and forward to
        next-hop";
    }
    enum pop-and-forward {
      description
        "Operation pop incoming label and forward to next-hop";
    }
    enum pop-impose-and-forward {
      description
        "Operation pop incoming label, impose one or more
        outgoing label(s) and forward to next-hop";
    }
    enum swap-and-forward {
      description
        "Operation swap incoming label, with outgoing label and
        forward to next-hop";
    }
  }
}
```



```
    }
    enum pop-and-lookup {
      description
        "Operation pop incoming label and perform a lookup";
    }
  }
  description "MPLS operations types";
}
```

```
typedef nhlfe-role {
  type enumeration {
    enum PRIMARY {
      description
        "Next-hop acts as primary traffic carrying";
    }
    enum BACKUP {
      description
        "Next-hop acts as backup";
    }
    enum PRIMARY_AND_BACKUP {
      description
        "Next-hop acts as primary and backup simultaneously";
    }
  }
  description "The next-hop role";
}
```

```
grouping nhlfe-single-contents {
  description
    "MPLS simple NHLFE contents";
  uses rt-types:mpls-label-stack;
}
```

```
grouping nhlfe-multiple-contents {
  description
    "MPLS NHLFE contents";
  leaf index {
    type string;
    description
      "A user-specified identifier utilised to uniquely
       reference the next-hop entry in the next-hop list.
       The value of this index has no semantic meaning
       other than for referencing the entry.";
  }
}
```

```
leaf backup-index {
  type string;
  description
```



```
    "A user-specified identifier utilised to uniquely
    reference the backup next-hop entry in the NHLFE list.
    The value of this index has no semantic meaning
    other than for referencing the entry.";
}

leaf loadshare {
    type uint16;
    description
        "This value is used to compute a loadshare to perform un-equal
        load balancing when multiple outgoing next-hop(s) are
        specified. A share is computed as a ratio of this number to the
        total under all next-hops(s).";
}

leaf role {
    type nhlfe-role;
    description "NHLFE role";
}

uses nhlfe-single-contents;
}

grouping interface-mpls-properties {
    description "MPLS interface contents grouping";
    leaf enabled {
        type boolean;
        description
            "'true' if mpls encapsulation is enabled on the
            interface. 'false' if mpls encapsulation is enabled
            on the interface.";
    }
    leaf mtu {
        type uint32;
        description
            "MPLS Maximum Transmission Unit (MTU) in bytes";
    }
}

grouping interfaces-mpls {
    description "List of MPLS interfaces";
    list interface {
        key "name";
        description "List of MPLS interfaces";
        leaf name {
            type if:interface-ref;
            description
                "The name of a configured MPLS interface";
        }
    }
}
```



```
    }
    uses interface-mpls-properties;
  }
}

grouping label-block-properties {
  description "Label-block configuration items";
  leaf index {
    type string;
    description
      "A user-specified identifier utilised to uniquely
       reference an MPLS label block";
  }
  leaf start-label {
    type rt-types:mpls-label;
    must '. >= ../end-label' {
      error-message
        "The start-label must be less than or equal " +
        "to end-label";
    }
    description "Label-block start";
  }
  leaf end-label {
    type rt-types:mpls-label;
    must '. <= ../start-label' {
      error-message
        "The end-label must be greater than or equal " +
        "to start-label";
    }
    description "Label-block end";
  }
  leaf block-allocation-mode {
    type identityref {
      base label-block-alloc-mode;
    }
    description "Label-block allocation mode";
  }
}

grouping label-block_state {
  description "Label-block state items";
  leaf free-labels-count {
    when "../block-allocation-mode = " +
      "'label-block-alloc-mode-manager'";
    type yang:counter32;
    config false;
    description "Label-block free labels count";
  }
}
```



```
    leaf inuse-labels-count {
      when "../block-allocation-mode = " +
        "'label-block-alloc-mode-manager'";
      type yang:counter32;
      config false;
      description "Label-block inuse labels count";
    }
  }

  grouping globals {
    description "MPLS global configuration grouping";
    leaf ttl-propagate {
      type boolean;
      default 'true';
      description "Propagate TTL between IP and MPLS";
    }
  }

  grouping label-blocks {
    description "Label-block allocation grouping";
    container label-blocks {
      description "Label-block allocation container";
      list label-block {
        key index;
        unique "start-label end-label";
        description "List of MPLS label-blocks";
        uses label-block-properties;
        uses label-block_state;
      }
    }
  }

  augment "/rt:routing" {
    description "MPLS augmentation.";
    container mpls {
      description
        "MPLS container, to be used as an augmentation target node
        other MPLS sub-features config, e.g. MPLS static LSP, MPLS
        LDP LSPs, and Traffic Engineering MPLS LSP Tunnels, etc.";
      uses globals;
      uses label-blocks;
      uses interfaces-mpls;
    }
  }

  /* MPLS routes augmentation */
  augment "/rt:routing/rt:ribs/rt:rib/rt:routes/rt:route" {
    description
      "This is augmentation for all MPLS routes.";
```



```
    leaf mpls-enabled {
        type boolean;
        default 'false';
        description
            "Indicates whether MPLS is enabled for this route";
    }
    leaf local-label {
        when "../mpls-enabled = 'true'";
        type rt-types:mpls-label;
        description "MPLS local label associated with the route.";
    }
}

/* MPLS simple-next-hop augmentation */
augment "/rt:routing/rt:ribs/rt:rib/rt:routes/rt:route/"
    + "rt:next-hop/rt:next-hop-options/rt:simple-next-hop" {
    description
        "Augment 'simple-next-hop' case in IP unicast routes.";
    uses nhlfe-single-contents {
        when "/rt:routing/rt:ribs/rt:rib/rt:routes/rt:route" +
            "/mpls:mpls-enabled = 'true'";
    }
}

/* MPLS next-hop-list augmentation */
augment "/rt:routing/rt:ribs/rt:rib/rt:routes/rt:route/"
    + "rt:next-hop/rt:next-hop-options/rt:next-hop-list/"
    + "rt:next-hop-list/rt:next-hop" {
    description
        "This leaf augments the 'next-hop-list' case of IP unicast
        routes.";
    uses nhlfe-multiple-contents {
        when "/rt:routing/rt:ribs/rt:rib/rt:routes/rt:route" +
            "/mpls:mpls-enabled = 'true'";
    }
}

/* MPLS RPC input augmentation */
augment
    "/rt:routing/rt:ribs/rt:rib/rt:active-route/rt:input" {
    description
        "Input MPLS augmentation for the 'active-route' action
        statement.";
    leaf local-label {
        type rt-types:mpls-label;
        description
            "MPLS local label.";
    }
}
```



```
}

/* MPLS RPC output augmentation */
augment "/rt:routing/rt:ribs/rt:rib/rt:active-route/"
  + "rt:output/rt:route/"
  + "rt:next-hop/rt:next-hop-options/rt:simple-next-hop" {
  description
    "Output MPLS augmentation for the 'active-route' action
    statement.";
  uses nhlfe-single-contents;
}
augment "/rt:routing/rt:ribs/rt:rib/rt:active-route/"
  + "rt:output/rt:route/"
  + "rt:next-hop/rt:next-hop-options/rt:next-hop-list/"
  + "rt:next-hop-list/rt:next-hop" {
  description
    "Output MPLS augmentation for the 'active-route' action
    statement.";
  uses nhlfe-multiple-contents;
}
}
<CODE ENDS>
```

Figure 3: MPLS base YANG module

3. IANA Considerations

This document registers the following URIs in the IETF XML registry [[RFC3688](#)]. Following the format in [[RFC3688](#)], the following registration is requested to be made.

URI: urn:ietf:params:xml:ns:yang:ietf-mpls
Registrant Contact: The MPLS WG of the IETF.
XML: N/A, the requested URI is an XML namespace.

This document registers a YANG module in the YANG Module Names registry [[RFC6020](#)].

name: ietf-mpls
namespace: urn:ietf:params:xml:ns:yang:ietf-mpls
prefix: ietf-mpls
// RFC Ed.: replace XXXX with RFC number and remove this note
reference: RFCXXXX

4. Security Considerations

The YANG modules specified in this document define a schema for data that is designed to be accessed via network management protocols such as NETCONF [RFC6241] or RESTCONF [RFC8040]. The lowest NETCONF layer is the secure transport layer, and the mandatory-to-implement secure transport is Secure Shell (SSH) [RFC6242]. The lowest RESTCONF layer is HTTPS, and the mandatory-to-implement secure transport is TLS [RFC8446].

The NETCONF access control model [RFC8341] provides the means to restrict access for particular NETCONF or RESTCONF users to a preconfigured subset of all available NETCONF or RESTCONF protocol operations and content.

Some of the readable data nodes in these YANG modules may be considered sensitive or vulnerable in some network environments. It is thus important to control read access (e.g., via get, get-config, or notification) to these data nodes. These are the subtrees and data nodes and their sensitivity/vulnerability:

/rt:routing/rt:ribs/rt:rib/rt:active-route/rt:output/rt:route: this path is augmented by additional MPLS leaf(s) defined in this model. Access to this information may disclose the per prefix and/or other information.

/rt:routing/rt:ribs/rt:rib/rt:active-route/rt:output/rt:route/
rt:next-hop/rt:next-hop-options/rt:simple-next-hop: this path is augmented by additional MPLS leaf(s) defined in this model. Access to this information may disclose the next-hop or path per prefix and/or other information.

5. Acknowledgement

The authors would like to thank the members of the multi-vendor YANG design team who are involved in the definition of this model.

6. Contributors

Igor Bryskin
Huawei Technologies
email: Igor.Bryskin@huawei.com

Himanshu Shah
Ciena
email: hshah@ciena.com

7. References

7.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC3688] Mealling, M., "The IETF XML Registry", [BCP 81](#), [RFC 3688](#), DOI 10.17487/RFC3688, January 2004, <<https://www.rfc-editor.org/info/rfc3688>>.
- [RFC6020] Bjorklund, M., Ed., "YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF)", [RFC 6020](#), DOI 10.17487/RFC6020, October 2010, <<https://www.rfc-editor.org/info/rfc6020>>.
- [RFC6241] Enns, R., Ed., Bjorklund, M., Ed., Schoenwaelder, J., Ed., and A. Bierman, Ed., "Network Configuration Protocol (NETCONF)", [RFC 6241](#), DOI 10.17487/RFC6241, June 2011, <<https://www.rfc-editor.org/info/rfc6241>>.
- [RFC6242] Wasserman, M., "Using the NETCONF Protocol over Secure Shell (SSH)", [RFC 6242](#), DOI 10.17487/RFC6242, June 2011, <<https://www.rfc-editor.org/info/rfc6242>>.
- [RFC7950] Bjorklund, M., Ed., "The YANG 1.1 Data Modeling Language", [RFC 7950](#), DOI 10.17487/RFC7950, August 2016, <<https://www.rfc-editor.org/info/rfc7950>>.
- [RFC8040] Bierman, A., Bjorklund, M., and K. Watsen, "RESTCONF Protocol", [RFC 8040](#), DOI 10.17487/RFC8040, January 2017, <<https://www.rfc-editor.org/info/rfc8040>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in [RFC 2119](#) Key Words", [BCP 14](#), [RFC 8174](#), DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.
- [RFC8294] Liu, X., Qu, Y., Lindem, A., Hopps, C., and L. Berger, "Common YANG Data Types for the Routing Area", [RFC 8294](#), DOI 10.17487/RFC8294, December 2017, <<https://www.rfc-editor.org/info/rfc8294>>.
- [RFC8340] Bjorklund, M. and L. Berger, Ed., "YANG Tree Diagrams", [BCP 215](#), [RFC 8340](#), DOI 10.17487/RFC8340, March 2018, <<https://www.rfc-editor.org/info/rfc8340>>.

- [RFC8341] Bierman, A. and M. Bjorklund, "Network Configuration Access Control Model", STD 91, [RFC 8341](#), DOI 10.17487/RFC8341, March 2018, <<https://www.rfc-editor.org/info/rfc8341>>.
- [RFC8342] Bjorklund, M., Schoenwaelder, J., Shafer, P., Watsen, K., and R. Wilton, "Network Management Datastore Architecture (NMDA)", [RFC 8342](#), DOI 10.17487/RFC8342, March 2018, <<https://www.rfc-editor.org/info/rfc8342>>.
- [RFC8343] Bjorklund, M., "A YANG Data Model for Interface Management", [RFC 8343](#), DOI 10.17487/RFC8343, March 2018, <<https://www.rfc-editor.org/info/rfc8343>>.
- [RFC8349] Lhotka, L., Lindem, A., and Y. Qu, "A YANG Data Model for Routing Management (NMDA Version)", [RFC 8349](#), DOI 10.17487/RFC8349, March 2018, <<https://www.rfc-editor.org/info/rfc8349>>.
- [RFC8446] Rescorla, E., "The Transport Layer Security (TLS) Protocol Version 1.3", [RFC 8446](#), DOI 10.17487/RFC8446, August 2018, <<https://www.rfc-editor.org/info/rfc8446>>.

7.2. Informative References

- [RFC3031] Rosen, E., Viswanathan, A., and R. Callon, "Multiprotocol Label Switching Architecture", [RFC 3031](#), DOI 10.17487/RFC3031, January 2001, <<https://www.rfc-editor.org/info/rfc3031>>.

Authors' Addresses

Tarek Saad
Juniper Networks

Email: tsaad@juniper.net

Kamran Raza
Cisco Systems Inc

Email: skraza@cisco.com

Rakesh Gandhi
Cisco Systems Inc

Email: rgandhi@cisco.com

Xufeng Liu
Volta Networks

Email: xufeng.liu.ietf@gmail.com

Vishnu Pavan Beeram
Juniper Networks

Email: vbeeram@juniper.net