

MPLS Working Group
Internet-Draft
Updates: [5036](#) (if approved)
Intended status: Standards Track
Expires: May 16, 2012

C. Pignataro
R. Asati
Cisco Systems
November 13, 2011

**The Generalized TTL Security Mechanism (GTSM) for Label Distribution
Protocol (LDP)
draft-ietf-mpls-ldp-gtsm-04**

Abstract

The Generalized TTL Security Mechanism (GTSM) describes a generalized use of a packets Time to Live (TTL) (IPv4) or Hop Limit (IPv6) to verify that the packet was sourced by a node on a connected link, thereby protecting the router's IP control-plane from CPU utilization based attacks. This technique improves security and is used by many protocols. This document defines the GTSM use for Label Distribution Protocol (LDP).

This specification uses a bit reserved in [RFC 5036](#) and therefore updates [RFC 5036](#).

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on May 16, 2012.

Copyright Notice

Copyright (c) 2011 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents

(<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	3
1.1.	Specification of Requirements	3
1.2.	Scope	4
2.	GTSM Procedures for LDP	4
2.1.	GTSM Flag in Common Hello Parameter TLV	4
2.2.	GTSM Sending and Receiving Procedures for LDP Link Hello	5
2.3.	GTSM Sending and Receiving Procedures for LDP Initialization	5
3.	LDP Peering Scenarios and GTSM Considerations	6
4.	IANA Considerations	7
5.	Security Considerations	7
6.	Acknowledgments	7
7.	References	7
7.1.	Normative References	7
7.2.	Informative References	8
	Authors' Addresses	8

1. Introduction

LDP [[RFC5036](#)] specifies two peer discovery mechanisms, a Basic one and an Extended one, both using UDP transport. The Basic Discovery mechanism is used to discover LDP peers that are directly connected at the link level, whereas the Extended Discovery mechanism is used to locate LSR neighbors that are not directly connected at the link level. Once discovered, the LSR neighbors can establish the LDP peering session, using the TCP transport connection.

The Generalized TTL Security Mechanism (GTSM) [[RFC5082](#)] is a mechanism based on IPv4 Time To Live (TTL) or (IPv6) Hop Limit value verification so as to provide a simple and reasonably robust defense from infrastructure attacks using forged protocol packets from outside the network. GTSM can be applied to any protocol peering session that is established between routers that are adjacent. Therefore, GTSM can fully benefit LDP protocol peering session established using Basic Discovery.

This document specifies LDP enhancements to accommodate GTSM. In particular, this document specifies the enhancements in the following areas:

1. Common Hello Parameter TLV of LDP Link Hello message
2. Sending and Receiving procedures for LDP Link Hello message
3. Sending and Receiving procedures for LDP Initialization message

GTSM specifies that it SHOULD NOT be enabled by default in order to remain backward-compatible with the unmodified protocol; this document specifies having a built-in dynamic GTSM capability negotiation for LDP to suggest the use of GTSM, provided GTSM is not enabled unless both peers can detect each others' support for GTSM procedures and agree on its usage as described in this document.

This specification uses a bit reserved in [Section 3.5.2 of \[RFC5036\]](#) and therefore updates [[RFC5036](#)].

1.1. Specification of Requirements

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

1.2. Scope


This document defines procedures for LDP using IPv4 routing, but not for LDP using IPv6 routing, since the latter has GTSM built into the protocol definition [[I-D.ietf-mpls-ldp-ipv6](#)].

Additionally, the GTSM for LDP specified in this document applies only to single-hop LDP peering sessions, and not to multi-hop LDP peering sessions, in line with [Section 5.5 of \[RFC5082\]](#). Consequently, any LDP method or feature that relies on multi-hop LDP peering sessions would not work with GTSM and will require (statically or dynamically) disabling GTSM. See [Section 3](#).

2. GTSM Procedures for LDP

2.1. GTSM Flag in Common Hello Parameter TLV

A new flag in Common Hello Parameter TLV, named G flag (for GTSM), is defined by this document in a previously reserved bit. An LSR indicates that it is capable of applying GTSM procedures, as defined in this document, to the subsequent LDP peering session, by setting the GTSM flag to 1. The Common Hello Parameters TLV, defined in [Section 3.5.2 of \[RFC5036\]](#), is updated as shown in Figure 1.



T, Targeted Hello

As specified in [[RFC5036](#)].

R, Request Send Targeted Hellos

As specified in [[RFC5036](#)].

G, GTSM

A value of 1 specifies that this LSR supports GTSM procedures, where a value of 0 specifies that this LSR does not support GTSM.

Reserved

This field is reserved. It MUST be set to zero on transmission and ignored on receipt.

Figure 1: GTSM Flag in Common Hello Parameter TLV

The G flag is meaningful only if T and R flags are set to 0 (which must be the case for Basic Discovery), otherwise, the value of G flag SHOULD be ignored on receipt.

Any LSR not supporting GTSM for LDP, as defined in this document, would continue to ignore the G flag, independent of T and R flags' value, as per [Section 3.5.2 of \[RFC5036\]](#).

2.2. GTSM Sending and Receiving Procedures for LDP Link Hello

Firstly, LSRs using LDP Basic Discovery [[RFC5036](#)] send LDP Hello messages to link-level multicast address (224.0.0.2 or "all routers"). Such messages are never forwarded beyond one hop and assumed to have their IP TTL or Hop Count = 1.

An LSR that is capable of applying GTSM procedures to the subsequent TCP/LDP peering session MUST set the G flag (for GTSM) to 1 in Common Hello Parameter TLV in the LDP Link Hello message [[RFC5036](#)].

An LSR, upon receiving an LDP Link Hello message, would recognize the presence of G flag (in Common Hello Parameter TLV) only if it supports GTSM for LDP, as specified in this document. If an LSR recognizes the presence of G flag with the value =1 in the received LDP Link Hello message, then it MUST enforce GTSM for LDP in the subsequent TCP/LDP peering session with the neighbor that sent the Hello message, as specified in [Section 2.3](#) of this document.

If an LSR does not recognize the presence of G flag (in Common Hello Parameter TLV of Link Hello message), or recognizes the presence of G flag with the value = 0, then the LSR MUST NOT enforce GTSM for LDP in the subsequent TCP/LDP peering session with the neighbor that sent the Hello message. This ensures backward compatibility as well as automatic GTSM de-activation.

If an LSR that has sent the LDP Link Hello with G flag = 1, then the LSR MUST set IP TTL or Hop Count = 255 in the forthcoming TCP Transport Connection(s) with that neighbor (e.g., LSR2). Please see [Section 2.3](#) for more details about the TCP transport connection specifics.

2.3. GTSM Sending and Receiving Procedures for LDP Initialization

If an LSR that has sent and received LDP Link Hello with G flag = 1 from the directly-connected neighbor (LSR2), then the LSR MUST enforce GTSM procedures, as defined in [Section 3 of \[RFC5082\]](#), in the forthcoming TCP Transport Connection with that neighbor (LSR2). This means that the LSR MUST check for the incoming unicast packets' TTL or Hop Count to be 255 for the particular LDP/TCP peering session and

decide the further processing as per the [\[RFC5082\]](#).

If an LSR that has sent LDP Link Hello with G flag = 1, but received LDP Link Hello with G flag = 0 from the directly-connected neighbor (LSR2), then the LSR MUST NOT enforce GTSM procedures, as defined in [Section 3 of \[RFC5082\]](#), in the forthcoming TCP Transport Connection with that neighbor (LSR2).

3. LDP Peering Scenarios and GTSM Considerations

This section discusses GTSM considerations arising from the LDP peering scenarios used, including single-hop versus multi-hop LDP neighbors, as well as the use of LDP basic discovery versus extended discovery.

The reason GTSM is enabled for Basic Discovery by default, but not for Extended Discovery is that the usage of Basic Discovery typically results in a single-hop LDP peering session, whereas the usage of Extended Discovery typically results in a multi-hop LDP peering session. GTSM protection for multi-hop LDP sessions is outside the scope of this specification (see [Section 1.2](#)). However, it is worth clarifying the following exceptions that may occur with Basic or Extended Discovery usage:

- a. Two adjacent LSRs (i.e., back-to-back PE routers) forming a single-hop LDP peering session after doing an Extended Discovery (e.g., for Pseudowire signaling)
- b. Two adjacent LSRs forming a multi-hop LDP peering session after doing a Basic Discovery, due to the way IP routing is setup between them (either temporarily or permanently)
- c. Two adjacent LSRs (i.e. back-to-back PE routers) forming a single-hop LDP peering session after doing both Basic and Extended Discovery.

In the first case (a), GTSM is not enabled for the LDP peering session by default. In the second case (b), GTSM is actually enabled by default and enforced for the LDP peering session, and hence, it would prohibit the LDP peering session from getting established. In the third case (c), GTSM is enabled by default for Basic Discovery and enforced on the subsequent LDP peering, and not for Extended Discovery. However, if each LSR uses the same IPV4 transport address object value in both Basic and Extended discoveries, then it would result in a single LDP peering session and that would be enabled with GTSM. Otherwise, GTSM would not be enforced on the second LDP peering session corresponding to the Extended Discovery.

This document allows for the implementation to provide an option to statically (e.g., via configuration) and/or dynamically override the default behavior and enable/disable GTSM on a per-peer basis. This would address all the exceptions listed above.

4. IANA Considerations

This document has no IANA actions.

5. Security Considerations

This document increases the security for LDP, making it more resilient to off-link attacks.

6. Acknowledgments

The authors of this document do not make any claims on the originality of the ideas described. The concept of GTSM for LDP has been proposed a number of times, and is documented in both the Experimental and Standards Track specifications of GTSM. Among other people, we would like to acknowledge Enke Chen and Albert Tian for their document "TTL-Based Security Option for the LDP Hello Message".

The authors would like to thank Loa Andersson, Bin Mo, Mach Chen, Vero Zheng, Adrian Farrel, and Eric Rosen for a thorough review and most useful comments and suggestions.

7. References

7.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC5036] Andersson, L., Minei, I., and B. Thomas, "LDP Specification", [RFC 5036](#), October 2007.
- [RFC5082] Gill, V., Heasley, J., Meyer, D., Savola, P., and C. Pignataro, "The Generalized TTL Security Mechanism (GTSM)", [RFC 5082](#), October 2007.

7.2. Informative References

[I-D.ietf-mpls-ldp-ipv6]

Asati, R., Manral, V., Papneja, R., and C. Pignataro,
"Updates to LDP for IPv6", [draft-ietf-mpls-ldp-ipv6-05](#)
(work in progress), August 2011.

Authors' Addresses

Carlos Pignataro
Cisco Systems
7200-12 Kit Creek Road
Research Triangle Park, NC 27709
US

Email: cpignata@cisco.com

Rajiv Asati
Cisco Systems
7025-6 Kit Creek Road
Research Triangle Park, NC 27709
US

Email: rajiva@cisco.com

