

Network Working Group  
Internet-Draft  
Intended status: Standards Track  
Expires: May 3, 2012

R. Winter, Ed.  
NEC  
E. Gray, Ed.  
Ericsson  
H. van Helvoort  
Huawei Technologies Co., Ltd.  
M. Betts  
ZTE  
October 31, 2011

MPLS-TP Identifiers Following ITU-T Conventions  
draft-ietf-mpls-tp-itu-t-identifiers-02

## Abstract

This document specifies an extension to the identifiers to be used in the Transport Profile of Multiprotocol Label Switching (MPLS-TP). Identifiers that follow IP/MPLS conventions have already been defined. This memo augments that set of identifiers for MPLS-TP management and OAM functions to include identifier information in a format typically used by the ITU-T.

## Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on May 3, 2012.

## Copyright Notice

Copyright (c) 2011 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of

publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

<a href="#">1.</a>	<a href="#">Introduction</a>	<a href="#">3</a>
<a href="#">1.1.</a>	<a href="#">Terminology</a>	<a href="#">3</a>
<a href="#">1.2.</a>	<a href="#">Requirements notation</a>	<a href="#">4</a>
<a href="#">2.</a>	<a href="#">Uniquely Identifying an Operator - the ICC_Operator_ID</a>	<a href="#">4</a>
<a href="#">3.</a>	<a href="#">Use of the ICC_Operator_ID</a>	<a href="#">4</a>
<a href="#">4.</a>	<a href="#">ICC_Operator_ID-based MEG Identifiers</a>	<a href="#">5</a>
<a href="#">5.</a>	<a href="#">ICC_Operator_ID-based MEP Identifiers</a>	<a href="#">5</a>
<a href="#">6.</a>	<a href="#">Security Considerations</a>	<a href="#">6</a>
<a href="#">7.</a>	<a href="#">IANA Considerations</a>	<a href="#">6</a>
<a href="#">8.</a>	<a href="#">References</a>	<a href="#">6</a>
<a href="#">8.1.</a>	<a href="#">Normative References</a>	<a href="#">6</a>
<a href="#">8.2.</a>	<a href="#">Informative References</a>	<a href="#">7</a>
	<a href="#">Authors' Addresses</a>	<a href="#">7</a>

## 1. Introduction

This document augments the initial set of identifiers to be used in the Transport Profile of Multiprotocol Label Switching (MPLS-TP) specified in [RFC 6370](#) [[RFC6370](#)].

[RFC 6370](#) [[RFC6370](#)] defines a set of MPLS-TP transport and management entity identifiers to support bidirectional (co-routed and associated) point-to-point MPLS-TP LSPs, including PWs and Sections which follow the IP/MPLS conventions.

This document specifies an alternative way to uniquely identify an operator/service provider based on ITU-T conventions and specifies how this operator/service provider identifier can be used to make the existing set of MPLS-TP transport and management entity identifiers, defined by [RFC 6370](#) [[RFC6370](#)], globally unique.

This document solely defines those identifiers. Their use and possible protocols extensions to carry them is out of scope in this document.

In this document, we follow the notational convention laid out in [RFC 6370](#) [[RFC6370](#)].

### 1.1. Terminology

CC: Country Code

ICC: ITU-T Carrier Code

ITU-T: International Telecommunication Union Telecommunication Standardization Sector

LSP: Label Switched Path

MEG: Maintenance Entity Group

MEP: Maintenance Entity Group End Point

MPLS: Multi-Protocol Label Switching

PW: Pseudowire

TSB: (ITU-T) Telecommunication Standardization Bureau

UMC: Unique MEG ID Code

Winter, et al.

Expires May 3, 2012

[Page 3]

---

Internet-Draft

MPLS-TP ITU-T IDs

October 2011

## [1.2.](#) Requirements notation

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

## [2.](#) Uniquely Identifying an Operator - the ICC\_Operator\_ID

In [RFC 6370](#) [[RFC6370](#)] an operator is uniquely identified by the Global\_ID which is based on the AS number of the operator. The ITU-T however traditionally identifies operators/service providers based on the ITU-T Carrier Code (ICC) as specified in [[M1400](#)].

The ITU-T Telecommunication Standardization Bureau (TSB) maintains a list of assigned ICCs [[ICC-list](#)]. Note that ICCs can be assigned to both, ITU-T members as well as non-members, all of which are referenced at [[ICC-list](#)]. The national regulatory authorities act as an intermediary between the ITU/TSB and operators/service providers. Amongst the things that the national authorities are responsible for in the process of assigning an ICC is to ensure that the Carrier Codes are unique within their country.

The ICC itself is a string of one to six characters, each character being either alphabetic (i.e. A-Z) or numeric (i.e. 0-9). Alphabetic characters in the ICC SHOULD be represented with upper case letters.

Global uniqueness is assured by concatenating the ICC with a Country

Code (CC). The Country Code (alpha-2) is a string of two alphabetic characters represented with upper case letters (i.e., A-Z). The Country Code format is defined in ISO 3166-1 [[IS03166-1](#)]. Together, the CC and the ICC form the ICC\_Operator\_ID as CC::ICC.

### 3. Use of the ICC\_Operator\_ID

The ICC\_Operator\_ID is used as a replacement for the Global\_ID as specified in [RFC 6370](#) [[RFC6370](#)], i.e. its purpose is to provide a globally unique context for other MPLS-TP identifiers.

As an example, an Interface Identifier (IF\_ID) in [RFC 6370](#) [[RFC6370](#)] is specified as the concatenation of the Node\_ID (a unique 32-bit value assigned by the operator) and the Interface Number (IF\_Num, a 32-bit unsigned integer assigned by the operator that is unique within the scope of a Node\_ID). To make this IF\_ID globally unique the Global\_ID is prefixed. This memo specifies the ICC\_Operator\_ID as an alternative format which, just like the Global\_ID, is prefixed

to the IF\_ID. Using the notation from [RFC 6370](#) [[RFC6370](#)]:

Global\_ID::Node\_ID::IF\_Num

is functionally equivalent to:

ICC\_Operator\_ID::Node\_ID::IF\_Num

The same substitution procedure applies to all identifiers specified in [RFC 6370](#) [[RFC6370](#)] except for the other alternatives mentioned in this document.

### 4. ICC\_Operator\_ID-based MEG Identifiers

The ITU-T format of MEG\_IDs for MPLS-TP Sections, LSPs and Pseudowires is based on the globally unique ICC\_Operator\_ID. In this case, the MEG\_ID is a string of up to 15 characters. It consists of three subfields: the Country Code (as described in [Section 2](#)), the ICC (as described in [Section 2](#)) which together form the ICC\_Operator\_ID, followed by a Unique MEG ID Code (UMC) as defined in [[Y.1731\\_cor1](#)].

The resulting MEG\_ID therefore looks like the following:

CC:ICC:UMC

To avoid the potential for a short (i.e. less than 6 Character) ICC code in combination with a UMC not being unique the UMC MUST start with a special character that is not allowed in the ICC such as the "/" character. A side effect of this is that the MEG\_ID can be decomposed into its individual components by a receiver.

The UMC MUST be unique within the organization identified by the combination of CC and ICC.

The ICC\_Operator\_ID-based MEG\_ID may be applied equally to a single MPLS-TP Section, LSP or Pseudowire.

## 5. ICC\_Operator\_ID-based MEP Identifiers

ICC\_Operator\_ID-based MEP\_IDs for MPLS-TP LSPs and Pseudowires are formed by appending a 16-bit index to the MEG\_ID defined in [Section 4](#) above. Within the context of a particular MEG, we call the identifier associated with a MEP the MEP Index (MEP\_Index). The MEP\_Index is administratively assigned. It is encoded as a 16-bit unsigned integer and MUST be unique within the MEG. An

ICC\_Operator\_ID-based MEP\_ID is structured as:

MEG\_ID::MEP\_Index

An ICC\_Operator\_ID-based MEP ID is globally unique by construction given the ICC\_Operator\_ID-based MEG\_ID's global uniqueness.

## 6. Security Considerations

This document extends an existing information model and, as such, does in itself not introduce new security concerns. But, as mentioned in the security considerations section of the document that is being augmented, protocol specifications that describe use of this information model may introduce security risks and concerns about

authentication of participants. For this reason, these protocol specifications need to describe security and authentication concerns that may be raised by the particular mechanisms defined and how those concerns may be addressed.

## 7. IANA Considerations

There are no IANA actions resulting from this document.

## 8. References

### 8.1. Normative References

- [IS03166-1] "Codes for the representation of names of countries and their subdivisions -- Part 1: Country codes", ISO 3166-1.
- [M1400] "Designations for interconnections among operators' networks", ITU-T Recommendation M.1400, July 2006, <<http://www.itu.int/rec/T-REC-M.1400-200607-I/en>>.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC6370] Bocci, M., Swallow, G., and E. Gray, "MPLS Transport Profile (MPLS-TP) Identifiers", [RFC 6370](#), September 2011.
- [Y.1731\_cor1] "OAM functions and mechanisms for Ethernet based networks - Corrigendum 1", ITU-T Recommendation ITU-T G.8013/Y.1731 (2011) Corrigendum 1.

Winter, et al.

Expires May 3, 2012

[Page 6]

---

Internet-Draft

MPLS-TP ITU-T IDs

October 2011

### 8.2. Informative References

- [ICC-list] "List of ITU Carrier Codes (ICCs)", <<http://www.itu.int/oth/T0201>>.

Authors' Addresses

Rolf Winter (editor)  
NEC

Email: [rolf.winter@neclab.eu](mailto:rolf.winter@neclab.eu)

Eric Gray (editor)  
Ericsson

Email: [eric.gray@ericsson.com](mailto:eric.gray@ericsson.com)

Huub van Helvoort  
Huawei Technologies Co., Ltd.

Email: [huub.van.helvoort@huawei.com](mailto:huub.van.helvoort@huawei.com)

Malcolm Betts  
ZTE

Email: [malcolm.betts@zte.com.cn](mailto:malcolm.betts@zte.com.cn)