

NEMO Working Group
Internet-Draft
Expires: April 27, 2006

T. Ernst
Keio University / WIDE
October 24, 2005

Network Mobility Support Goals and Requirements
draft-ietf-nemo-requirements-05

Status of this Memo

By submitting this Internet-Draft, each author represents that any applicable patent or other IPR claims of which he or she is aware have been or will be disclosed, and any of which he or she becomes aware will be disclosed, in accordance with [Section 6 of BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/lid-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on April 27, 2006.

Copyright Notice

Copyright (C) The Internet Society (2005).

Abstract

Network mobility arises when a router connecting a network to the Internet dynamically changes its point of attachment to the Internet thereby causing the reachability of the said network to be changed in relation to the fixed Internet topology. Such kind of network is referred to as a mobile network. With appropriate mechanisms, sessions established between nodes in the mobile network and the global Internet can be maintained after the mobile router changes its point of attachment. This document outlines the goals expected from network mobility support and defines the requirements that must be

Internet-Draft

NEMO Goals

October 2005

met by the NEMO Basic Support solution.

Table of Contents

1.	Introduction	3
2.	NEMO Working Group Objectives and Methodology	4
3.	NEMO Support Design Goals	5
3.1.	Migration Transparency	5
3.2.	Performance Transparency and Seamless Mobility	5
3.3.	Network Mobility Support Transparency	6
3.4.	Operational Transparency	6
3.5.	Arbitrary Configurations	6
3.6.	Local Mobility and Global Mobility	7
3.7.	Scalability	7
3.8.	Backward Compatibility	7
3.9.	Secure Signaling	8
3.10.	Location Privacy	8
3.11.	IPv4 and NAT Traversal	8
4.	NEMO Basic Support One-Liner Requirements	8
5.	Security Considerations	10
6.	IANA Considerations	10
7.	Acknowledgments	10
8.	References	11
8.1.	Normative References	11
8.2.	Informative References	11
Appendix A.	Change Log From Earlier Versions	13
A.1.	Changes between version -04 and -05	13
A.2.	Changes between version -03 and -04	13
A.3.	Changes between version -02 and -03	13
A.4.	Changes Between Version -01 and -02	14
A.5.	Changes Between Version -00 and -01	14
	Author's Address	15
	Intellectual Property and Copyright Statements	16

[1.](#) Introduction

Network mobility support (see [\[1\]](#) for the related terminology) is concerned with managing the mobility of an entire network, viewed as a single unit, which changes its point of attachment to the Internet and thus its reachability in the Internet topology. Such a network is referred to as a mobile network and includes one or more mobile routers (MRs) which connect it to the global Internet. Nodes behind the MR(s) (MNNs) are both fixed (LFNs) and mobile (VMNs or LMNs). In most cases, the internal structure of the mobile network will be relatively stable (no dynamic change of the topology), but this is not always true.

Cases of mobile networks include, for instance:

- o Networks attached to people (Personal Area Networks or PANs): a cell-phone with one cellular interface and one Bluetooth interface together with a Bluetooth-enabled PDA constitute a very simple instance of a mobile network. The cell-phone is the mobile router while the PDA is used for web browsing or runs a personal web server.
- o Networks of sensors and computers deployed in vehicles: vehicles are increasingly embedded with a number of processing units for safety and ease of driving reasons, as advocated by ITS (Intelligent Transportation Systems) applications ([\[4\]](#), [\[5\]](#)).
- o Access networks deployed in public transportation (buses, trains, taxis, aircrafts): they provide Internet access to IP devices carried by passengers: laptop, camera, mobile phone: host mobility within network mobility or PANs: network mobility within network mobility, i.e. nested mobility (see [\[1\]](#) for the definition of nested mobility).
- o Ad-hoc networks connected to the Internet via an MR: for instance students in a train that need both to set up an ad-hoc network

among themselves, and get Internet connectivity through the MR connecting the train to the Internet.

Mobility of networks does not cause MNNs to change their own physical point of attachment; however they do change their topological location with respect to the global Internet. If network mobility is not explicitly supported by some mechanisms, the mobility of the MR results in MNNs losing Internet access and breaking ongoing sessions between arbitrary correspondent node (CNs) in the global Internet and those MNNs located within the mobile network. In addition, the communication path between MNNs and correspondent nodes becomes sub-optimal, and multiple levels of mobility will cause extremely sub-

Ernst

Expires April 27, 2006

[Page 3]

Internet-Draft

NEMO Goals

October 2005

optimal routing.

Mobility-related terms used in this document are defined in [2], whereas terms specifically pertaining to network mobility are defined in [1]. This document is structured as follows: in [Section 2](#) we define the rough objectives and methodology of the NEMO working group to handle network mobility issues and we emphasize the stepwise approach the working group has decided to follow. A number of desirable design goals are listed in [Section 3](#). Those design goals then serve as guidelines to define the requirements listed in [Section 4](#) for basic network mobility support [3].

[2.](#) NEMO Working Group Objectives and Methodology

The mechanisms required for handling network mobility issues were lacking within the IETF standards when the NEMO working group was set up at the IETF. At that time, work conducted on mobility support (particularly in the Mobile IP working group) was to provide continuous Internet connectivity and optimal routing to mobile hosts only (host mobility support). Such mechanisms specified in Mobile IPv6 [6] are unable to support network mobility. The NEMO working group has therefore been set up to deal with issues specific to network mobility.

The primary objective of the NEMO work is to specify a solution which allows mobile network nodes (MNNs) to remain connected to the Internet and continuously reachable at all times while the mobile router serving the mobile network changes its point of attachment.

The secondary goals of the work is to investigate the effects of network mobility on various aspects of internet communication such as routing protocol changes, implications of real-time traffic and fast handovers, and optimizations. This should support the primary goal of reachability for mobile network nodes. Security is an important consideration too, and efforts should be made to use existing security solutions if they are appropriate. Although a well-designed solution may include security inherent in other protocols, mobile networks also introduce new challenges.

To complete these tasks, the NEMO working group has decided to take a stepwise approach. The steps in this approach include standardizing a basic solution to preserve session continuity (NEMO Basic Support) (see [3]), and studying the possible approaches and issues with providing more optimal routing with potentially nested mobile networks (NEMO Extended Support) (see [7]). However, the working group is not chartered to actually standardize a solution for extended support at this point in time. If deemed necessary, the working group will be rechartered based on the conclusions of the

discussions.

For NEMO Basic Support, the working group will assume that none of the nodes behind the MR will be aware of the network's mobility; thus, the network's movement needs to be completely transparent to the nodes inside the mobile network. This assumption accommodates nodes inside the network that are not generally aware of mobility.

The efforts of the Mobile IP working group have resulted in the Mobile IPv4 and Mobile IPv6 protocols, which have already solved the issue of host mobility support. Since challenges to enabling mobile networks are vastly reduced by this work, basic network mobility support will adopt the methods for host mobility support used in Mobile IP, and extend them in the simplest way possible to achieve its goals. The basic support solution, now defined in [3] following the requirements stated in [Section 4](#) of the present document, is for each MR to have a Home Agent, and use bi-directional tunneling between the MR and HA to preserve session continuity while the MR moves. The MR will acquire a care-of address at its attachment point much like what is done for mobile nodes (MN), using Mobile IP. This approach allows nested mobile networks, since each MR will appear to its attachment point as a single node.

[3.](#) NEMO Support Design Goals

This section details the fundamental design goals the solutions will intend to achieve. Those design goals serve to define the issues and to impose a list of requirements for forthcoming solutions. Actual requirements for NEMO Basic Support are in [Section 4](#); NEMO Extended Support is not yet considered at the time of this writing.

[3.1.](#) Migration Transparency

Permanent connectivity to the Internet has to be provided to all MNNs, since continuous sessions are expected to be maintained as the mobile router changes its point of attachment. For maintaining those sessions, MNNs are expected to be reachable via their permanent IP addresses.

[3.2.](#) Performance Transparency and Seamless Mobility

NEMO support is expected to be provided with limited signaling overhead and to minimize the impact of handovers on applications, in terms of packet loss or delay. However, although variable delays of transmission and losses between MNNs and their respective CNs could be perceived as the network is displaced, it would not be considered a lack of performance transparency.

[3.3.](#) Network Mobility Support Transparency

MNNs behind the MR(s) do not change their own physical point of attachment as a result of the mobile network's displacement in the Internet topology. Consequently, NEMO support is expected to be performed only by the MR(s). Specific support functions on any other node than the MR(s) would better be avoided.

[3.4.](#) Operational Transparency

NEMO support is to be implemented at the level of IP layer. It is expected to be transparent to upper layers so that any upper layer protocol can run unchanged on top of an IP layer extended with NEMO support.

3.5. Arbitrary Configurations

The formation of a mobile network can occur in various levels of complexity. In the simplest case, a mobile network contains just a mobile router and a host. In the most complicated case, a mobile network is multihomed and is itself a multi-level aggregation of mobile networks with collectively thousands of mobile routers and hosts. While the list of potential configurations of mobile networks cannot be limited, at least the following ones are desirable:

- o Mobile networks of any size, ranging from a sole subnet with a few IP devices to a collection of subnets with a large number of IP devices.
- o Nodes that change their point of attachment within the mobile network.
- o Foreign mobile nodes that attach to the mobile network.
- o Multihomed mobile network: either when a single MR has multiple attachments to the internet, or when the mobile network is attached to the Internet by means of multiple MRs (see definition in [1] and the analysis in [8]).
- o Nested mobile networks (mobile networks attaching to other mobile networks (see definition in [1])). Although the complexity requirements of those nested networks is not clear, it is desirable to support arbitrary levels of recursive networks. The solution should only impose restrictions on nesting (e.g. path MTU) when this is impractical and protocol concerns preclude such support.

- o Distinct mobility frequencies (see mobility factor in [2]).
- o Distinct access media.

In order to keep complexity minimal, transit networks are excluded from this list. A transit network is one in which data would be forwarded between two endpoints outside of the network, so that the network itself simply serves as a transitional conduit for packet

forwarding. A stub network (leaf network), on the other hand, does not serve as a data forwarding path. Data on a stub network is either sent by or addressed to a node located within that network.

[3.6.](#) Local Mobility and Global Mobility

Mobile networks and mobile nodes owned by different administrative entities are expected to be displaced within a domain boundary or between domain boundaries. Multihoming, vertical and horizontal handoffs, and access control mechanisms are desirable to achieve this goal. Such mobility is not expected to be limited for any consideration other than administrative and security policies.

[3.7.](#) Scalability

NEMO support signaling and processing is expected to scale to a potentially large number of mobile networks irrespective of their configuration, mobility frequency, size and number of CNs.

[3.8.](#) Backward Compatibility

NEMO support will have to co-exist with established IPv6 standards and not interfere with them. Standards defined in other IETF working groups have to be reused as much as possible and extended only if deemed necessary. For instance, the following mechanisms defined by other working groups are expected to function without modification:

- o Address allocation and configuration mechanisms.
- o Host mobility support: mobile nodes and correspondent nodes, either located within or outside the mobile network, are expected to continue operating protocols defined by the Mobile IP working group. This includes mechanisms for host mobility support (Mobile IPv6) and seamless mobility (FMIPv6).
- o Multicast support intended for MNNs is expected to be maintained while the mobile router changes its point of attachment.
- o Access control protocols and mechanisms used by visiting mobile hosts and routers to be authenticated and authorized, gaining

(MRs).

- o Security protocols and mechanisms.
- o Mechanisms performed by routers deployed in both the visited networks and in mobile networks (routing protocols, Neighbor Discovery, ICMP, Router Renumbering).

[3.9.](#) Secure Signaling

NEMO support will have to comply with the usual IETF security policies and recommendations and is expected to have its specific security issues fully addressed. In practice, all NEMO support control messages transmitted in the network will have to be protected with an acceptable level of security to prevent intruders to usurp identities and forge data. Specifically, the following issues have to be considered:

- o Authentication of the sender to prevent identity usurpation.
- o Authorization, to make sure the sender is granted permission to perform the operation as indicated in the control message.
- o Confidentiality of the data contained in the control message.

[3.10.](#) Location Privacy

Location privacy means to hide the actual location of MNNS to third parties other than the HA are desired. It is not clear to which extend this has to be enforced, since it is always possible to determine the topological location by analysing IPv6 headers. It would thus require some kind of encryption of the IPv6 header to prevent third parties from monitoring IPv6 addresses between the MR and the HA. On the other hand, it is at the very least desirable to provide a means for MNNS to hide their real topological location to their CNs.

[3.11.](#) IPv4 and NAT Traversal

IPv4 clouds and NAT are likely to co-exist with IPv6 for a long time, so it is desirable to ensure mechanisms developed for NEMO will be able to traverse such clouds.

[4.](#) NEMO Basic Support One-Liner Requirements

The NEMO WG is to specify a unified and unique "Network Mobility

Basic Support" solution, hereafter referred to as "the solution". This solution is to allow all nodes in the mobile network to be reachable via permanent IP addresses, as well as maintain ongoing sessions as the MR changes its point of attachment to the Internet topology. This is to be done by maintaining a bi-directional tunnel between an MR and its Home Agent.

The NEMO Working Group, after some investigation of alternatives, has decided to reuse the existing Mobile IPv6 [6] mechanisms for tunnel management, or extend it if deemed necessary.

The list of requirements below has been imposed on the NEMO Basic Support solution. The requirements have mostly been met by the resulting specification which can now be found in [3].

R01: The solution MUST be implemented at the IP layer level.

R02: The solution MUST set up a bi-directional tunnel between a Mobile Router and its Home Agent (MRHA tunnel)

R03: All traffic exchanged between an MNN and a CN in the global Internet MUST transit through the bi-directional MRHA tunnel.

R04: MNNs MUST be reachable at a permanent IP address and name.

R05: The solution MUST maintain continuous sessions (both unicast and multicast) between MNNs and arbitrary CNs after IP handover of (one of) the MR.

R06: The solution MUST not require modifications to any node other than MRs and HAs.

R07: The solution MUST support fixed nodes, mobile hosts and mobile routers in the mobile network.

R08: The solution MUST allow MIPv6-enabled MNNs to use a mobile network link as either a home link or a foreign link.

R09: The solution MUST ensure backward compatibility with other standards defined by the IETF. In particular, this includes:

R09:1: The solution MUST not prevent the proper operation of Mobile IPv6 (i.e. the solution MUST allow MIPv6-enabled MNNs to operate either the CN, HA, or MN operations defined in [6])

R10: The solution MUST treat all the potential configurations the

same way (whatever the number of subnets, MNNs, nested levels of MRs, egress interfaces)

R11: The solution MUST support at least 2 levels of nested mobile networks, while, in principle, arbitrary levels of recursive mobile networks SHOULD be supported.

R12: The solution MUST function for multihomed MRs and multihomed mobile networks as defined in [\[1\]](#).

R13: NEMO Support signaling over the bi-directional MUST be minimized

R14: Signaling messages between the HA and the MR MUST be secured:

R14.1: The receiver MUST be able to authenticate the sender.

R14.2: The function performed by the sender MUST be authorized for the content carried.

R14.3: Anti-replay MUST be provided.

R14.4: The signaling messages MAY be encrypted.

R15: The solution MUST ensure transparent continuation of routing and management operations over the bi-directional tunnel (this includes e.g. unicast and multicast routing protocols, router renumbering, DHCPv6)

R16: When one egress interface fails, the solution MAY preserve sessions established through another egress interface.

[5.](#) Security Considerations

As this document only provides a discussion about design goals and describes neither a protocol nor an implementation or a procedure, there are no security considerations associated with it.

[6.](#) IANA Considerations

This document requires no IANA actions.

7. Acknowledgments

The material presented in this document takes most of its text from discussions and previous documents submitted to the NEMO working group. This includes initial contributions from Motorola, INRIA, Ericsson and Nokia. We are particularly grateful to Hesham Soliman

Ernst

Expires April 27, 2006

[Page 10]

Internet-Draft

NEMO Goals

October 2005

(Ericsson) and the IETF ADs at the time (Erik Nordmark and Thomas Narten) who greatly helped to set up the NEMO working group. We are also grateful to all the following people whose comments highly contributed to the present document: T.J. Kniveton (Nokia), Alexandru Petrescu (Motorola), Christophe Janneteau (Motorola), Pascal Thubert (Cisco), Hong-Yon Lach (Motorola), Mattias Petterson (Ericsson) and all the others people who have expressed their opinions on the NEMO mailing lists (formely known as MONET). Thierry Ernst wishes to personally acknowledge his previous employers, INRIA, and Motorola for their support and direction in bringing this topic up to the IETF -- particularly Claude Castelluccia (INRIA) and Hong-Yon Lach (Motorola).

8. References

8.1. Normative References

- [1] Ernst, T. and H. Lach, "Network Mobility Support Terminology", [draft-ietf-nemo-terminology-04](#) (work in progress), October 2005.
- [2] Manner, J. and M. Kojo, "Mobility Related Terminology", [RFC 3753](#), June 2004.
- [3] Devarapalli, V., Wakikawa, R., Petrescu, A., and P. Thubert, "Network Mobility (NEMO) Basic Support Protocol", [RFC 3963](#), January 2005.

8.2. Informative References

- [4] "CALM - Medium and Long Range, High Speed, Air Interfaces parameters and protocols for broadcast, point to point, vehicle

to vehicle, and vehicle to point communication in the ITS sector - Networking Protocol - Complementary Element", ISO Draft ISO/WD 21210, February 2005.

- [5] Ernst, T. and K. Uehara, "Connecting Automobiles to the Internet", Proceedings 3rd International Workshop on ITS Telecommunications (ITST), November 2002.
- [6] Johnson, D., Perkins, C., and J. Arkko, "Mobility Support in IPv6", [RFC 3775](#), June 2004.
- [7] Ng, C., "Network Mobility Route Optimization Problem Statement", [draft-ietf-nemo-ro-problem-statement-01](#) (work in progress), October 2005.
- [8] Ng, C., Ernst, T., Paik, E., and M. Bagnulo, "Analysis of

Ernst

Expires April 27, 2006

[Page 11]

Internet-Draft

NEMO Goals

October 2005

Multihoming in Network Mobility Support",
[draft-ietf-nemo-multihoming-issues-04](#) (work in progress),
October 2005.

- [9] Thubert, P., Wakikawa, R., and V. Devarapalli, "NEMO Home Network Models", [draft-ietf-nemo-home-network-models-05](#) (work in progress), June 2005.
- [10] Deering, S. and R. Hinden, "Internet Protocol Version 6 (IPv6)", IETF [RFC 2460](#), December 1998.

Appendix A. Change Log From Earlier Versions

The discussions behind the changes in the latest versions of this documents are reflected in the "issue" web page:

<http://www.sfc.wide.ad.jp/~ernst/nemo/>

A.1. Changes between version -04 and -05

Added a reference to [\[7\]](#)

Split references into Normative and Informational

Cosmetics changes

A.2. Changes between version -03 and -04

- Issue B1: English brush up

- Issue B2: Added a reference to [\[4\]](#) and [\[5\]](#) when speaking about usages.
- Issue B3: The following paragraph from [section 1](#) was partly removed; the remaining part was moved to [section 2](#) and rephrased: "The mechanisms required for handling such mobility issues are currently lacking within the IETF standards. Traditional work conducted on mobility support (particularly in the Mobile IP working group) is to provide continuous Internet connectivity and optimal routing to mobile hosts only (host mobility support) and are unable to support network mobility. The NEMO working group has therefore been set up to deal with issues specific to network mobility. The purpose of this document is thus to detail the methodology that will be followed by the NEMO working group, its goals, and to define requirements for network mobility support."
- Issue B4: Effectively removed former requirements about "impact on the routing fabric".

[A.3.](#) Changes between version -02 and -03

- Mostly cosmetic changes
- Merged section Terminology into Introduction
- Cross-references with other NEMO WG docs
- Changed the introduction of section [Section 4](#) and added reference to NEMO Basic Support's resulting specification.

Ernst

Expires April 27, 2006

[Page 13]

Internet-Draft

NEMO Goals

October 2005

[A.4.](#) Changes Between Version -01 and -02

- removed sub-items in R12 (sub-cases are contained into the definition of multihoming)
- minor typos
- R15: Added "multicast"
- R14.4: SHOULD softened to MAY according to discussion at IETF56th meeting.

- R17 moved to R09 and contains former R09 as a sub-case.
- R18: relaxed from "SHOULD" to may based on Vijay Devarapalli comment (030718)

[A.5.](#) Changes Between Version -00 and -01

- title of documents: included the word "goals"
- entire document: some rewording
- [section 4](#): changed title of section to "NEMO Design Goals".
- [section 4](#): removed "MUST" and "MAY"
- [section 4](#): more text about location privacy
- [section 4](#): changed "Administration" paragraph to "Local and Global Mobility". Text enhanced.
- [section 5](#): R02: replace "between MR and MR's HA" with "an MR and its HA" R11: specified at least 2 levels R12: replaced "support" with "function" and add "multihomed MR" R13.x renumbered to R12.x since part of R12 (editing mistake) R13 and R18: new requirements proposed by editor and minor changes in the formulation of other Requirements

Jun Murai Lab., Keio University.
K-square Town Campus, 1488-8 Ogura, Saiwa-Ku
Kawasaki, Kanagawa 212-0054
Japan

Phone: +81-44-580-1600

Fax: +81-44-580-1437

Email: ernst@sfc.wide.ad.jp

URI: <http://www.sfc.wide.ad.jp/~ernst/>

Intellectual Property Statement

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in [BCP 78](#) and [BCP 79](#).

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at ietf-ipr@ietf.org.

Disclaimer of Validity

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Copyright Statement

Copyright (C) The Internet Society (2005). This document is subject to the rights, licenses and restrictions contained in [BCP 78](#), and except as set forth therein, the authors retain all their rights.

Acknowledgment

Funding for the RFC Editor function is currently provided by the Internet Society.

