

NETCONF Working Group  
Internet-Draft  
Intended status: Standards Track  
Expires: December 9, 2019

K. Watsen  
Watsen Networks  
June 7, 2019

A YANG Data Model for a Keystore  
draft-ietf-netconf-keystore-10

## Abstract

This document defines a YANG 1.1 module called "ietf-keystore" that enables centralized configuration of asymmetric keys and their associated certificates, and notification for when configured certificates are about to expire.

## Editorial Note (To be removed by RFC Editor)

This draft contains many placeholder values that need to be replaced with finalized values at the time of publication. This note summarizes all of the substitutions that are needed. No other RFC Editor instructions are specified elsewhere in this document.

Artwork in this document contains shorthand references to drafts in progress. Please apply the following replacements:

- o "VVVV" --> the assigned RFC value for this draft

Artwork in this document contains placeholder values for the date of publication of this draft. Please apply the following replacement:

- o "2019-06-07" --> the publication date of this draft

The following Appendix section is to be removed prior to publication:

- o [Appendix A](#). Change Log

## Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on December 9, 2019.

Copyright Notice

Copyright (c) 2019 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](https://trustee.ietf.org/bcp78) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

- [1. Introduction](#) . . . . . [3](#)
- [2. Requirements Language](#) . . . . . [4](#)
- [3. The Keystore Model](#) . . . . . [4](#)
  - [3.1. Tree Diagram](#) . . . . . [4](#)
  - [3.2. Example Usage](#) . . . . . [6](#)
  - [3.3. YANG Module](#) . . . . . [11](#)
- [4. Security Considerations](#) . . . . . [16](#)
- [5. IANA Considerations](#) . . . . . [17](#)
  - [5.1. The IETF XML Registry](#) . . . . . [17](#)
  - [5.2. The YANG Module Names Registry](#) . . . . . [17](#)
- [6. References](#) . . . . . [17](#)
  - [6.1. Normative References](#) . . . . . [17](#)
  - [6.2. Informative References](#) . . . . . [18](#)
- [Appendix A. Change Log](#) . . . . . [19](#)
  - [A.1. 00 to 01](#) . . . . . [19](#)
  - [A.2. 01 to 02](#) . . . . . [19](#)
  - [A.3. 02 to 03](#) . . . . . [19](#)
  - [A.4. 03 to 04](#) . . . . . [19](#)
  - [A.5. 04 to 05](#) . . . . . [20](#)

<a href="#">A.6.</a>	05 to 06	. . . . .	<a href="#">20</a>
<a href="#">A.7.</a>	06 to 07	. . . . .	<a href="#">20</a>
<a href="#">A.8.</a>	07 to 08	. . . . .	<a href="#">20</a>
<a href="#">A.9.</a>	08 to 09	. . . . .	<a href="#">20</a>
<a href="#">A.10.</a>	09 to 10	. . . . .	<a href="#">21</a>

Acknowledgements	. . . . .	<a href="#">21</a>
Author's Address	. . . . .	<a href="#">21</a>

[1.](#) Introduction

This document defines a YANG 1.1 [[RFC7950](#)] module called "ietf-keystore" that enables centralized configuration of asymmetric keys and their associated certificates, and notification for when configured certificates are about to expire.

This module also defines Six groupings designed for maximum reuse. These groupings include one for the public half of an asymmetric key, one for both the public and private halves of an asymmetric key, one for both halves of an asymmetric key and a list of associated certificates, one for an asymmetric key that may be configured locally or via a reference to an asymmetric key in the keystore, one for a trust anchor certificate and, lastly, one for an end entity certificate.

Special consideration has been given for systems that have cryptographic hardware, such as a Trusted Protection Module (TPM). These systems are unique in that the cryptographic hardware completely hides the private keys and must perform all private key operations. To support such hardware, the "private-key" can be the special value "permanently-hidden" and the actions "generate-hidden-key" and "generate-certificate-signing-request" can be used to direct these operations to the hardware .

This document is compliant with Network Management Datastore Architecture (NMDA) [[RFC8342](#)]. For instance, to support keys and associated certificates installed during manufacturing (e.g., for a IDevID [[Std-802.1AR-2009](#)] certificate), it is expected that such data may appear only in <operational>.

While only asymmetric keys are currently supported, the module has been designed to enable other key types to be introduced in the

future.

The module does not support protecting the contents of the keystore (e.g., via encryption), though it could be extended to do so in the future.

It is not required that a system has an operating system level keystore utility to implement this module.

## [2.](#) Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [BCP 14](#) [[RFC2119](#)] [[RFC8174](#)] when, and only when, they appear in all capitals, as shown here.

## [3.](#) The Keystore Model

### [3.1.](#) Tree Diagram

This section provides a tree diagrams [[RFC8340](#)] for the "ietf-keystore" module that presents both the protocol-accessible "keystore" as well the all the groupings intended for external usage.

```
module: ietf-keystore
  +--rw keystore
    +--rw asymmetric-keys
      +--rw asymmetric-key* [name]
        +--rw name string
        +--rw algorithm
          | asymmetric-key-algorithm-ref
        +--rw public-key binary
        +--rw private-key union
      +--rw certificates
        | +--rw certificate* [name]
        |   +--rw name string
        |   +--rw cert? end-entity-cert-cms
```

```

    |      +---n certificate-expiration
    |      +--- expiration-date      yang:date-and-time
+---x generate-certificate-signing-request
    +---w input
    |   +---w subject      binary
    |   +---w attributes?  binary
    +---ro output
        +---ro certificate-signing-request  binary

grouping local-or-keystore-asymmetric-key-grouping
+-- (local-or-keystore)
+--:(local) {local-definitions-supported}?
| +-- local-definition
|   +-- algorithm      asymmetric-key-algorithm-ref
|   +-- public-key     binary
|   +-- private-key    union
+--:(keystore) {keystore-supported}?
+-- keystore-reference?  ks:asymmetric-key-ref
grouping local-or-keystore-asymmetric-key-with-certs-grouping

```

```

+-- (local-or-keystore)
+--:(local) {local-definitions-supported}?
| +-- local-definition
|   +-- algorithm
|   |   asymmetric-key-algorithm-ref
|   +-- public-key      binary
|   +-- private-key     union
|   +-- certificates
|   |   +-- certificate* [name]
|   |   |   +-- name?      string
|   |   |   +-- cert?     end-entity-cert-cms
|   |   |   +---n certificate-expiration
|   |   |   |   +-- expiration-date      yang:date-and-time
|   |   +---x generate-certificate-signing-request
|   |   +---w input
|   |   |   +---w subject      binary
|   |   |   +---w attributes?  binary
|   |   +---ro output
|   |   |   +---ro certificate-signing-request  binary
+--:(keystore) {keystore-supported}?
+-- keystore-reference?  ks:asymmetric-key-ref
grouping local-or-keystore-end-entity-cert-with-key-grouping

```

```

+-- (local-or-keystore)
  +--:(local) {local-definitions-supported}?
  |   +-- local-definition
  |       +-- algorithm
  |           |   asymmetric-key-algorithm-ref
  |       +-- public-key                               binary
  |       +-- private-key                             union
  |       +-- cert?
  |           |   end-entity-cert-cms
  |       +---n certificate-expiration
  |           |   +-- expiration-date   yang:date-and-time
  |       +---x generate-certificate-signing-request
  |           +---w input
  |               |   +---w subject       binary
  |               |   +---w attributes?   binary
  |           +---ro output
  |               +---ro certificate-signing-request   binary
  +--:(keystore) {keystore-supported}?
  +-- keystore-reference?   ks:asymmetric-key-certificate-ref
grouping keystore-grouping
+-- asymmetric-keys
  +-- asymmetric-key* [name]
  +-- name?                 string
  +-- algorithm
  |   asymmetric-key-algorithm-ref
  +-- public-key           binary

```

```

+-- private-key                               union
+-- certificates
  |   +-- certificate* [name]
  |       +-- name?                             string
  |       +-- cert?                             end-entity-cert-cms
  |       +---n certificate-expiration
  |           +-- expiration-date   yang:date-and-time
  +---x generate-certificate-signing-request
  +---w input
  |   +---w subject       binary
  |   +---w attributes?   binary
  +---ro output
  |   +---ro certificate-signing-request   binary

```

### [3.2.](#) Example Usage

The following example illustrates what a fully configured keystore might look like in <operational>, as described by [Section 5.3 in \[RFC8342\]](#). This datastore view illustrates data set by the manufacturing process alongside conventional configuration. This keystore instance has four keys, two having one associated certificate, one having two associated certificates, and one empty key.

```
<keystore xmlns="urn:ietf:params:xml:ns:yang:ietf-keystore"
  xmlns:or="urn:ietf:params:xml:ns:yang:ietf-origin"
  xmlns:ct="urn:ietf:params:xml:ns:yang:ietf-crypto-types"
  or:origin="or:intended">
  <asymmetric-keys>

    <asymmetric-key>
      <name>ex-rsa-key</name>
      <algorithm>ct:rsa2048</algorithm>
      <public-key>base64encodedvalue==</public-key>
      <private-key>base64encodedvalue==</private-key>
      <certificates>
        <certificate>
          <name>ex-rsa-cert</name>
          <cert>base64encodedvalue==</cert>
        </certificate>
      </certificates>
    </asymmetric-key>

    <asymmetric-key>
      <name>tls-ec-key</name>
      <algorithm>ct:secp256r1</algorithm>
      <public-key>base64encodedvalue==</public-key>
      <private-key>base64encodedvalue==</private-key>
```

```
    <certificates>
      <certificate>
        <name>tls-ec-cert</name>
        <cert>base64encodedvalue==</cert>
      </certificate>
    </certificates>
  </asymmetric-key>
```

```

<!-- all except 'my-ldevid-cert' copied from <operational> -->
<asymmetric-key>
  <name>tpm-protected-key</name>
  <algorithm>ct:rsa2048</algorithm>
  <public-key>base64encodedvalue==</public-key>
  <private-key>permanently-hidden</private-key>
  <certificates>
    <certificate>
      <name>builtin-idevid-cert</name>
    </certificate>
    <certificate>
      <name>my-ldevid-cert</name>
      <cert>base64encodedvalue==</cert>
    </certificate>
  </certificates>
</asymmetric-key>

</asymmetric-keys>
</keystore>

```

The following example module has been constructed to illustrate the "local-or-keystore-asymmetric-key-grouping" grouping defined in the "ietf-keystore" module.

```

module ex-keystore-usage {
  yang-version 1.1;

  namespace "http://example.com/ns/example-keystore-usage";
  prefix "eku";

  import ietf-keystore {
    prefix ks;
    reference
      "RFC VVVV: YANG Data Model for a 'Keystore' Mechanism";
  }

  organization
    "Example Corporation";

```



```

"Author: YANG Designer <mailto:yang.designer@example.com>";

description
  "This module illustrates the grouping in the keystore draft called
  'local-or-keystore-asymmetric-key-with-certs-grouping.'";

revision "YYYY-MM-DD" {
  description
    "Initial version";
  reference
    "RFC XXXX: YANG Data Model for a 'Keystore' Mechanism";
}

container keystore-usage {
  description
    "An illustration of the various keystore groupings.";

  list just-a-key {
    key name;
    leaf name {
      type string;
      description
        "An arbitrary name for this key.";
    }
    uses ks:local-or-keystore-asymmetric-key-grouping;
    description
      "An asymmetric key, with no certs, that may be configured
      locally or be a reference to an asymmetric key in the
      keystore. The intent is to reference just the asymmetric
      key, not any certificates that may also be associated
      with the asymmetric key.";
  }

  list key-with-certs {
    key name;
    leaf name {
      type string;
      description
        "An arbitrary name for this key.";
    }
    uses ks:local-or-keystore-asymmetric-key-with-certs-grouping;
    description
      "An asymmetric key and its associated certs, that may be
      configured locally or be a reference to an asymmetric key
      (and its associated certs) in the keystore.";
  }
}

```

```

list end-entity-cert-with-key {
  key name;
  leaf name {
    type string;
    description
      "An arbitrary name for this key.";
  }
  uses ks:local-or-keystore-end-entity-cert-with-key-grouping;
  description
    "An end-entity certificate, and its associated private key,
    that may be configured locally or be a reference to a
    specific certificate (and its associated private key) in
    the keystore.";
}
}
}

```

The following example illustrates what two configured keys, one local and the other remote, might look like. This example consistent with other examples above (i.e., the referenced key is in an example above).

===== NOTE: '\' line wrapping per BCP XX (RFC XXXX) =====

```

<keystore-usage xmlns="http://example.com/ns/example-keystore-usage">

  <!-- ks:local-or-keystore-asymmetric-key-grouping -->

  <just-a-key>
    <name>a locally-defined key</name>
    <local-definition>
      <algorithm
        xmlns:ct="urn:ietf:params:xml:ns:yang:ietf-crypto-types">
        ct:rsa2048
      </algorithm>
      <private-key>base64encodedvalue==</private-key>
      <public-key>base64encodedvalue==</public-key>
    </local-definition>
  </just-a-key>

  <just-a-key>
    <name>a keystore-defined key (and its associated certs)</name>
    <keystore-reference>ex-rsa-key</keystore-reference>
  </just-a-key>

```

<!-- ks:local-or-keystore-key-and-end-entity-cert-grouping -->

```
<key-with-certs>
  <name>a locally-defined key with certs</name>
  <local-definition>
    <algorithm
      xmlns:ct="urn:ietf:params:xml:ns:yang:ietf-crypto-types">
      ct:rsa2048
    </algorithm>
    <private-key>base64encodedvalue==</private-key>
    <public-key>base64encodedvalue==</public-key>
    <certificates>
      <certificate>
        <name>a locally-defined cert</name>
        <cert>base64encodedvalue==</cert>
      </certificate>
    </certificates>
  </local-definition>
</key-with-certs>

<key-with-certs>
  <name>a keystore-defined key (and its associated certs)</name>
  <keystore-reference>ex-rsa-key</keystore-reference>
</key-with-certs>

<!-- ks:local-or-keystore-end-entity-cert-with-key-grouping -->

<end-entity-cert-with-key>
  <name>a locally-defined end-entity cert with key</name>
  <local-definition>
    <algorithm
      xmlns:ct="urn:ietf:params:xml:ns:yang:ietf-crypto-types">
      ct:rsa2048
    </algorithm>
    <private-key>base64encodedvalue==</private-key>
    <public-key>base64encodedvalue==</public-key>
    <cert>base64encodedvalue==</cert>
  </local-definition>
</end-entity-cert-with-key>

<end-entity-cert-with-key>
```

```
<name>a keystore-defined certificate (and its associated key)</n\
ame>
  <keystore-reference>ex-rsa-cert</keystore-reference>
</end-entity-cert-with-key>

</keystore-usage>
```

### [3.3.](#) YANG Module

This YANG module has normative references to [[RFC8341](#)] and [[I-D.ietf-netconf-crypto-types](#)], and an informative reference to [[RFC8342](#)].

```
<CODE BEGINS> file "ietf-keystore@2019-06-07.yang"
module ietf-keystore {
  yang-version 1.1;
  namespace "urn:ietf:params:xml:ns:yang:ietf-keystore";
  prefix ks;

  import ietf-crypto-types {
    prefix ct;
    reference
      "RFC CCCC: Common YANG Data Types for Cryptography";
  }

  import ietf-netconf-acm {
    prefix nacm;
    reference
      "RFC 8341: Network Configuration Access Control Model";
  }

  organization
    "IETF NETCONF (Network Configuration) Working Group";

  contact
    "WG Web:  <http://datatracker.ietf.org/wg/netconf/>
    WG List:  <mailto:netconf@ietf.org>
    Author:   Kent Watsen <mailto:kent+ietf@watsen.net>;
```

description

"This module defines a keystore to centralize management of security credentials.

Copyright (c) 2019 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Simplified BSD License set forth in [Section 4.c](#) of the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>).

This version of this YANG module is part of RFC XXXX (<https://www.rfc-editor.org/info/rfcXXXX>); see the RFC

Watsen

Expires December 9, 2019

[Page 11]

---

Internet-Draft

A YANG Data Model for a Keystore

June 2019

itself for full legal notices.;

The key words 'MUST', 'MUST NOT', 'REQUIRED', 'SHALL', 'SHALL NOT', 'SHOULD', 'SHOULD NOT', 'RECOMMENDED', 'NOT RECOMMENDED', 'MAY', and 'OPTIONAL' in this document are to be interpreted as described in [BCP 14](#) ([RFC 2119](#)) ([RFC 8174](#)) when, and only when, they appear in all capitals, as shown here.";

```
revision 2019-06-07 {
  description
    "Initial version";
  reference
    "RFC VVVV: A YANG Data Model for a Keystore";
}
```

```
/*
*****
/*  Features  */
*****
*/
```

```
feature keystore-supported {
  description
    "The 'keystore-supported' feature indicates that the server
    supports the keystore.";
}
```

```

feature local-definitions-supported {
  description
    "The 'local-definitions-supported' feature indicates that the
    server supports locally-defined keys.";
}

/*****/
/*  Typedefs  */
/*****/

typedef asymmetric-key-ref {
  type leafref {
    path "/ks:keystore/ks:asymmetric-keys/ks:asymmetric-key"
      + "/ks:name";
  }
  description
    "This typedef enables modules to easily define a reference
    to an asymmetric key stored in the keystore.";
}

typedef asymmetric-key-certificate-ref {
  type leafref {

```

```

    path "/ks:keystore/ks:asymmetric-keys/ks:asymmetric-key"
      + "/ks:certificates/ks:certificate/ks:name";
  }
  description
    "This typedef enables modules to easily define a reference
    to a specific certificate associated with an asymmetric key
    stored in the keystore.";
}

/*****/
/*  Groupings  */
/*****/

grouping local-or-keystore-asymmetric-key-grouping {
  description
    "A grouping that expands to allow the asymmetric key to be
    either stored locally, within the using data model, or be
    a reference to an asymmetric key stored in the keystore.";

```

```

choice local-or-keystore {
  mandatory true;
  case local {
    if-feature "local-definitions-supported";
    container local-definition {
      description
        "Container to hold the local key definition.";
      uses ct:asymmetric-key-pair-grouping;
    }
  }
  case keystore {
    if-feature "keystore-supported";
    leaf keystore-reference {
      type ks:asymmetric-key-ref;
      description
        "A reference to an asymmetric key that exists in
        the keystore. The intent is to reference just the
        asymmetric key, not any certificates that may also
        be associated with the asymmetric key.";
    }
  }
  description
    "A choice between an inlined definition and a definition
    that exists in the keystore.";
}
}

```

```

grouping local-or-keystore-asymmetric-key-with-certs-grouping {
  description
    "A grouping that expands to allow an asymmetric key and its

```

```

associated certificates to be either stored locally, within
the using data model, or be a reference to an asymmetric key
(and its associated certificates) stored in the keystore.";
choice local-or-keystore {
  mandatory true;
  case local {
    if-feature "local-definitions-supported";
    container local-definition {
      description
        "Container to hold the local key definition.";
      uses ct:asymmetric-key-pair-with-certs-grouping;

```

```

    }
  }
  case keystore {
    if-feature "keystore-supported";
    leaf keystore-reference {
      type ks:asymmetric-key-ref;
      description
        "A reference to an asymmetric-key (and all of its
        associated certificates) in the keystore.";
    }
  }
  description
    "A choice between an inlined definition and a definition
    that exists in the keystore.";
}
}

grouping local-or-keystore-end-entity-cert-with-key-grouping {
  description
    "A grouping that expands to allow an end-entity certificate
    (and its associated private key) to be either stored locally,
    within the using data model, or be a reference to a specific
    certificate in the keystore.";
  choice local-or-keystore {
    mandatory true;
    case local {
      if-feature "local-definitions-supported";
      container local-definition {
        description
          "Container to hold the local key definition.";
        uses ct:asymmetric-key-pair-with-cert-grouping;
      }
    }
    case keystore {
      if-feature "keystore-supported";
      leaf keystore-reference {
        type ks:asymmetric-key-certificate-ref;

```

```

  description
    "A reference to a specific certificate (and its
    associated private key) in the keystore.";
}

```



```

    }
    description
        "A choice between an inlined definition and a definition
        that exists in the keystore.";
    }
}

grouping keystore-grouping {
    description
        "Grouping definition enables use in other contexts. If ever
        done, implementations SHOULD augment new 'case' statements
        into local-or-keystore 'choice' statements to supply leafrefs
        to the new location.";
    container asymmetric-keys {
        description
            "A list of asymmetric keys.";
        list asymmetric-key {
            key "name";
            description
                "An asymmetric key.";
            leaf name {
                type string;
                description
                    "An arbitrary name for the asymmetric key.";
            }
            uses ct:asymmetric-key-pair-with-certs-grouping;
        }
    }
}

/*****
/*  Protocol accessible nodes  */
*****/

container keystore {
    nacm:default-deny-write;
    description
        "The keystore contains a list of keys.";
    uses keystore-grouping;
}

}
<CODE ENDS>

```

#### 4. Security Considerations

The YANG module defined in this document is designed to be accessed via YANG based management protocols, such as NETCONF [[RFC6241](#)] and RESTCONF [[RFC8040](#)]. Both of these protocols have mandatory-to-implement secure transport layers (e.g., SSH, TLS) with mutual authentication.

The NETCONF access control model (NACM) [[RFC8341](#)] provides the means to restrict access for particular users to a pre-configured subset of all available protocol operations and content.

There are a number of data nodes defined in this YANG module that are writable/creatable/deletable (i.e., config true, which is the default). These data nodes may be considered sensitive or vulnerable in some network environments. Write operations (e.g., edit-config) to these data nodes without proper protection can have a negative effect on network operations. These are the subtrees and data nodes and their sensitivity/vulnerability:

- /: The entire data tree defined by this module is sensitive to write operations. For instance, the addition or removal of keys, certificates, etc., can dramatically alter the implemented security policy. For this reason, the NACM extension "default-deny-write" has been set for the entire data tree.

- /keystore/asymmetric-keys/asymmetric-key/private-key: When writing this node, implementations MUST ensure that the strength of the key being configured is not greater than the strength of the underlying secure transport connection over which it is communicated. Implementations SHOULD fail the write-request if ever the strength of the private key is greater than the strength of the underlying transport, and alert the client that the strength of the key may have been compromised. Additionally, when deleting this node, implementations SHOULD automatically (without explicit request) zeroize these keys in the most secure manner available, so as to prevent the remnants of their persisted storage locations from being analyzed in any meaningful way.

Some of the readable data nodes in this YANG module may be considered sensitive or vulnerable in some network environments. It is thus important to control read access (e.g., via get, get-config, or notification) to these data nodes. These are the subtrees and data nodes and their sensitivity/vulnerability:

/keystore/asymmetric-keys/asymmetric-key/private-key: This node is additionally sensitive to read operations such that, in normal use cases, it should never be returned to a client. The best reason for returning this node is to support backup/restore type workflows. For this reason, the NACM extension "default-deny-all" has been set for this data node.

## [5.](#) IANA Considerations

### [5.1.](#) The IETF XML Registry

This document registers one URI in the "ns" subregistry of the IETF XML Registry [[RFC3688](#)]. Following the format in [[RFC3688](#)], the following registration is requested:

URI: urn:ietf:params:xml:ns:yang:ietf-keystore  
Registrant Contact: The NETCONF WG of the IETF.  
XML: N/A, the requested URI is an XML namespace.

### [5.2.](#) The YANG Module Names Registry

This document registers one YANG module in the YANG Module Names registry [[RFC6020](#)]. Following the format in [[RFC6020](#)], the the following registration is requested:

name: ietf-keystore  
namespace: urn:ietf:params:xml:ns:yang:ietf-keystore  
prefix: ks  
reference: RFC VVVV

## [6.](#) References

### [6.1.](#) Normative References

[I-D.ietf-netconf-crypto-types]

Watsen, K. and H. Wang, "Common YANG Data Types for Cryptography", [draft-ietf-netconf-crypto-types-06](#) (work in progress), April 2019.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.

[RFC6020] Bjorklund, M., Ed., "YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF)", [RFC 6020](#), DOI 10.17487/RFC6020, October 2010, <<https://www.rfc-editor.org/info/rfc6020>>.

[RFC7950] Bjorklund, M., Ed., "The YANG 1.1 Data Modeling Language", [RFC 7950](#), DOI 10.17487/RFC7950, August 2016, <<https://www.rfc-editor.org/info/rfc7950>>.

[RFC8341] Bierman, A. and M. Bjorklund, "Network Configuration Access Control Model", STD 91, [RFC 8341](#), DOI 10.17487/RFC8341, March 2018, <<https://www.rfc-editor.org/info/rfc8341>>.

## 6.2. Informative References

[RFC3688] Mealling, M., "The IETF XML Registry", [BCP 81](#), [RFC 3688](#), DOI 10.17487/RFC3688, January 2004, <<https://www.rfc-editor.org/info/rfc3688>>.

[RFC6241] Enns, R., Ed., Bjorklund, M., Ed., Schoenwaelder, J., Ed., and A. Bierman, Ed., "Network Configuration Protocol (NETCONF)", [RFC 6241](#), DOI 10.17487/RFC6241, June 2011, <<https://www.rfc-editor.org/info/rfc6241>>.

[RFC8040] Bierman, A., Bjorklund, M., and K. Watsen, "RESTCONF Protocol", [RFC 8040](#), DOI 10.17487/RFC8040, January 2017, <<https://www.rfc-editor.org/info/rfc8040>>.

[RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in [RFC 2119](#) Key Words", [BCP 14](#), [RFC 8174](#), DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.

- [RFC8340] Bjorklund, M. and L. Berger, Ed., "YANG Tree Diagrams", [BCP 215](#), [RFC 8340](#), DOI 10.17487/RFC8340, March 2018, <<https://www.rfc-editor.org/info/rfc8340>>.
- [RFC8342] Bjorklund, M., Schoenwaelder, J., Shafer, P., Watsen, K., and R. Wilton, "Network Management Datastore Architecture (NMDA)", [RFC 8342](#), DOI 10.17487/RFC8342, March 2018, <<https://www.rfc-editor.org/info/rfc8342>>.
- [Std-802.1AR-2009] Group, W. -. H. L. L. P. W., "IEEE Standard for Local and metropolitan area networks - Secure Device Identity", December 2009, <<http://standards.ieee.org/findstds/standard/802.1AR-2009.html>>.

Watsen

Expires December 9, 2019

[Page 18]

---

Internet-Draft

A YANG Data Model for a Keystore

June 2019

## [Appendix A](#). Change Log

### [A.1](#). 00 to 01

- o Replaced the 'certificate-chain' structures with PKCS#7 structures. (Issue #1)
- o Added 'private-key' as a configurable data node, and removed the 'generate-private-key' and 'load-private-key' actions. (Issue #2)
- o Moved 'user-auth-credentials' to the ietf-ssh-client module. (Issues #4 and #5)

### [A.2](#). 01 to 02

- o Added back 'generate-private-key' action.
- o Removed 'RESTRICTED' enum from the 'private-key' leaf type.
- o Fixed up a few description statements.

### [A.3](#). 02 to 03

- o Changed draft's title.
- o Added missing references.

- o Collapsed sections and levels.
- o Added [RFC 8174](#) to Requirements Language Section.
- o Renamed 'trusted-certificates' to 'pinned-certificates'.
- o Changed 'public-key' from config false to config true.
- o Switched 'host-key' from OneAsymmetricKey to definition from [RFC 4253](#).

#### [A.4.](#) 03 to 04

- o Added typedefs around leafrefs to common keystore paths
- o Now tree diagrams reference ietf-netmod-yang-tree-diagrams
- o Removed Design Considerations section
- o Moved key and certificate definitions from data tree to groupings

#### [A.5.](#) 04 to 05

- o Removed trust anchors (now in their own draft)
- o Added back global keystore structure
- o Added groupings enabling keys to either be locally defined or a reference to the keystore.

#### [A.6.](#) 05 to 06

- o Added feature "local-keys-supported"
- o Added nacm:default-deny-all and nacm:default-deny-write
- o Renamed generate-asymmetric-key to generate-hidden-key
- o Added an install-hidden-key action

- o Moved actions inside fo the "asymmetric-key" container
- o Moved some groupings to [draft-ietf-netconf-crypto-types](#)

[A.7.](#) 06 to 07

- o Removed a "require-instance false"
- o Clarified some description statements
- o Improved the keystore-usage examples

[A.8.](#) 07 to 08

- o Added "local-definition" containers to avoid possibility of the action/notification statements being under a "case" statement.
- o Updated copyright date, boilerplate template, affiliation, folding algorithm, and reformatted the YANG module.

[A.9.](#) 08 to 09

- o Added a 'description' statement to the 'must' in the /keystore/asymmetric-key node explaining that the descendent values may exist in <operational> only, and that implementation MUST assert that the values are either configured or that they exist in <operational>.

- o Copied above 'must' statement (and description) into the local-or-keystore-asymmetric-key-grouping, local-or-keystore-asymmetric-key-with-certs-grouping, and local-or-keystore-end-entity-cert-with-key-grouping statements.

[A.10.](#) 09 to 10

- o Updated draft title to match new truststore draft title
- o Moved everything under a top-level 'grouping' to enable use in other contexts.

- o Renamed feature from 'local-keys-supported' to 'local-definitions-supported' (same name used in truststore)
- o Removed the either-all-or-none 'must' expressions for the key's 3-tuple values (since the values are now 'mandatory true' in crypto-types)
- o Example updated to reflect 'mandatory true' change in crypto-types draft

#### Acknowledgements

The authors would like to thank for following for lively discussions on list and in the halls (ordered by last name): Andy Bierman, Martin Bjorklund, Benoit Claise, Ramkumar Dhanapal, Mehmet Ersue, Balazs Kovacs, David Lamparter, Ladislav Lhotka, Alan Luchuk, Mahesh Jethanandani, Radek Krejci, Reshad Rahman, Tom Petch, Juergen Schoenwaelder, Phil Shafer, Sean Turner, Eric Voit, Bert Wijnen, and Liang Xia.

#### Author's Address

Kent Watsen  
Watsen Networks

EMail: kent+ietf@watsen.net