

**NETCONF Client and Server Models**  
**draft-ietf-netconf-netconf-client-server-07**

Abstract

This document defines two YANG modules, one module to configure a NETCONF client and the other module to configure a NETCONF server. Both modules support both the SSH and TLS transport protocols, and support both standard NETCONF and NETCONF Call Home connections.

Editorial Note (To be removed by RFC Editor)

This draft contains many placeholder values that need to be replaced with finalized values at the time of publication. This note summarizes all of the substitutions that are needed. No other RFC Editor instructions are specified elsewhere in this document.

This document contains references to other drafts in progress, both in the Normative References section, as well as in body text throughout. Please update the following references to reflect their final RFC assignments:

- o I-D.ietf-netconf-keystore
- o I-D.ietf-netconf-ssh-client-server
- o I-D.ietf-netconf-tls-client-server

Artwork in this document contains shorthand references to drafts in progress. Please apply the following replacements:

- o "XXXX" --> the assigned RFC value for this draft
- o "YYYY" --> the assigned RFC value for I-D.ietf-netconf-ssh-client-server
- o "ZZZZ" --> the assigned RFC value for I-D.ietf-netconf-tls-client-server

Artwork in this document contains placeholder values for the date of publication of this draft. Please apply the following replacement:

- o "2018-09-20" --> the publication date of this draft

The following Appendix section is to be removed prior to publication:

- o [Appendix A](#). Change Log

#### Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on March 24, 2019.

#### Copyright Notice

Copyright (c) 2018 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

#### Table of Contents

<a href="#">1.</a>	<a href="#">Introduction</a>	<a href="#">3</a>
<a href="#">2.</a>	<a href="#">Terminology</a>	<a href="#">3</a>
<a href="#">3.</a>	<a href="#">The NETCONF Client Model</a>	<a href="#">4</a>
<a href="#">3.1.</a>	<a href="#">Tree Diagram</a>	<a href="#">4</a>
<a href="#">3.2.</a>	<a href="#">Example Usage</a>	<a href="#">11</a>
<a href="#">3.3.</a>	<a href="#">YANG Module</a>	<a href="#">14</a>
<a href="#">4.</a>	<a href="#">The NETCONF Server Model</a>	<a href="#">24</a>
<a href="#">4.1.</a>	<a href="#">Tree Diagram</a>	<a href="#">25</a>



4.2.	Example Usage . . . . .	32
4.3.	YANG Module . . . . .	37
5.	Design Considerations . . . . .	49
5.1.	Support all NETCONF transports . . . . .	49
5.2.	Enable each transport to select which keys to use . . . . .	49
5.3.	Support authenticating NETCONF clients certificates . . . . .	49
5.4.	Support mapping authenticated NETCONF client certificates to usernames . . . . .	49
5.5.	Support both listening for connections and call home . . . . .	50
5.6.	For Call Home connections . . . . .	50
5.6.1.	Support more than one NETCONF client . . . . .	50
5.6.2.	Support NETCONF clients having more than one endpoint . . . . .	50
5.6.3.	Support a reconnection strategy . . . . .	50
5.6.4.	Support both persistent and periodic connections . . . . .	50
5.6.5.	Reconnection strategy for periodic connections . . . . .	51
5.6.6.	Keep-alives for persistent connections . . . . .	51
5.6.7.	Customizations for periodic connections . . . . .	51
6.	Security Considerations . . . . .	51
7.	IANA Considerations . . . . .	52
7.1.	The IETF XML Registry . . . . .	52
7.2.	The YANG Module Names Registry . . . . .	53
8.	References . . . . .	53
8.1.	Normative References . . . . .	53
8.2.	Informative References . . . . .	54
Appendix A.	Change Log . . . . .	56
A.1.	00 to 01 . . . . .	56
A.2.	01 to 02 . . . . .	56
A.3.	02 to 03 . . . . .	56
A.4.	03 to 04 . . . . .	56
A.5.	04 to 05 . . . . .	56
A.6.	05 to 06 . . . . .	57
A.7.	06 to 07 . . . . .	57
	Acknowledgements . . . . .	57
	Author's Address . . . . .	57

## 1. Introduction

This document defines two YANG [RFC7950] modules, one module to configure a NETCONF [RFC6241] client and the other module to configure a NETCONF server. Both modules support both NETCONF over SSH [RFC6242] and NETCONF over TLS [RFC7589] and NETCONF Call Home connections [RFC8071].

## 2. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP

Watsen

Expires March 24, 2019

[Page 3]

14 [[RFC2119](#)] [[RFC8174](#)] when, and only when, they appear in all capitals, as shown here.

### 3. The NETCONF Client Model

The NETCONF client model presented in this section supports both clients initiating connections to servers, as well as clients listening for connections from servers calling home.

This model supports both the SSH and TLS transport protocols, using the SSH client and TLS client groupings defined in [[I-D.ietf-netconf-ssh-client-server](#)] and [[I-D.ietf-netconf-tls-client-server](#)] respectively.

All private keys and trusted certificates are held in the keystore model defined in [[I-D.ietf-netconf-keystore](#)].

YANG feature statements are used to enable implementations to advertise which parts of the model the NETCONF client supports.

#### 3.1. Tree Diagram

The following tree diagram [[RFC8340](#)] provides an overview of the data model for the "ietf-netconf-client" module. Just the container is displayed below, but there is also a reusable grouping called "netconf-client-grouping" that the container is using.

[Note: '\\' line wrapping for formatting only]

```

module: ietf-netconf-client
  +--rw netconf-client
    +--rw initiate! {initiate}?
      | +--rw netconf-server* [name]
      |   +--rw name string
      |   +--rw endpoints
      |     | +--rw endpoint* [name]
      |     |   +--rw name string
      |     |   +--rw (transport)
      |     |     +--:(ssh) {ssh-initiate}?
      |     |       | +--rw ssh
      |     |         | +--rw address? inet:host
      |     |         | +--rw port? inet:port-number
      |     |         | +--rw client-identity
      |     |         |   +--rw username? string
      |     |         |   +--rw (auth-type)
      |     |         |     +--:(password)
      |     |         |       | +--rw password? string

```



					+++:(public-key)
					+--rw public-key
					+--rw (local-or-keystore)
					+--:(local)
					{local-keys-suppor\
ted}?					
					+--rw algorithm?
					ct:key-algorithm\
-ref					
					+--rw public-key?
					binary
					+--rw private-key?
					union
					+---x generate-hidden-key
					+---w input
					+---w algorithm
					ct:key-alg\
orithm-ref					
					+---x install-hidden-key
					+---w input
					+---w algorithm
					ct:key-alg\
orithm-ref					
					+---w public-key?
					binary
					+---w private-key?
					binary
					+--:(keystore)
					{keystore-supporte\
d}?					
					+--rw reference?
					ks:asymmetric-ke\
y-ref					
					+++:(certificate)
					+--rw certificate
					{sshcmn:ssh-x509-certs}?
					+--rw (local-or-keystore)
					+--:(local)
					{local-keys-suppor\
ted}?					
					+--rw algorithm?
					ct:key-algorithm\
-ref					
					+--rw public-key?
					binary
					+--rw private-key?
					union
					+---x generate-hidden-key



								+---w input
								+---w algorithm
								ct:key-alg\
orithm-ref								
								+---x install-hidden-key
								+---w input
								+---w algorithm
								ct:key-alg\
orithm-ref								
								+---w public-key?
								binary
								+---w private-key?
								binary
								+---rw cert
								ct:end-entity-ce\
rt-cms								
								+---n certificate-expira\
tion								
								+-- expiration-date?
								yang:date-and\
-time								
								+--:(keystore)
								{keystore-supporte\
d}?								
								+--rw reference?
								ks:asymmetric-ke\
y-certificate-ref								
								+--rw server-auth
								+--rw pinned-ssh-host-keys?
								ta:pinned-host-keys-ref
								{ta:ssh-host-keys}?
								+--rw pinned-ca-certs?
								ta:pinned-certificates-ref
								{sshcmn:ssh-x509-certs,ta:x509-\
certificates}?								
								+--rw pinned-server-certs?
								ta:pinned-certificates-ref
								{sshcmn:ssh-x509-certs,ta:x509-\
certificates}?								
								+--rw transport-params
								{ssh-client-transport-params-confi\
g}?								
								+--rw host-key
								+--rw host-key-alg* identityref
								+--rw key-exchange
								+--rw key-exchange-alg* identityref
								+--rw encryption
								+--rw encryption-alg* identityref

Watsen

Expires March 24, 2019

[Page 6]

				+--rw mac	
				+--rw mac-alg* identityref	
				+---:(tls) {tls-initiate}?	
				+--rw tls	
				+--rw address? inet:host	
				+--rw port? inet:port-number	
				+--rw client-identity	
				+--rw (auth-type)	
				+---:(certificate)	
				+--rw certificate	
				+--rw (local-or-keystore)	
				+---:(local)	
				{local-keys-suppor\	
ted}?					
				+--rw algorithm?	
				ct:key-algorithm\	
-ref					
				+--rw public-key?	
				binary	
				+--rw private-key?	
				union	
				+---x generate-hidden-key	
				+---w input	
				+---w algorithm	
				ct:key-alg\	
orithm-ref					
				+---x install-hidden-key	
				+---w input	
				+---w algorithm	
				ct:key-alg\	
orithm-ref					
				+---w public-key?	
				binary	
				+---w private-key?	
				binary	
				+--rw cert	
				ct:end-entity-ce\	
rt-cms					
				+---n certificate-expira\	
tion					
				+-- expiration-date?	
				yang:date-and\	
-time					
				+---:(keystore)	
				{keystore-supporte\	
d}?					
				+--rw reference?	
				ks:asymmetric-ke\	



}?



					+++rw algorithm?
					ct:key-algorithm-ref
					+++rw public-key?
					binary
					+++rw private-key?
					union
					+++x generate-hidden-key
					+++w input
					+++w algorithm
					ct:key-algorithm\
-ref					
					+++x install-hidden-key
					+++w input
					+++w algorithm
					ct:key-algorithm\
-ref					
					+++w public-key?    bin\
ary					
					+++w private-key?   bin\
ary					
					+++:(keystore) {keystore-supporte\
d}??					
					+++rw reference?
					ks:asymmetric-key-ref
					+++:(certificate)
					+++rw certificate {sshcmn:ssh-x509-cert\
s}??					
					+++rw (local-or-keystore)
					+++:(local) {local-keys-supported\
}??					
					+++rw algorithm?
					ct:key-algorithm-ref
					+++rw public-key?
					binary
					+++rw private-key?
					union
					+++x generate-hidden-key
					+++w input
					+++w algorithm
					ct:key-algorithm\
-ref					
					+++x install-hidden-key
					+++w input
					+++w algorithm
					ct:key-algorithm\
-ref					
					+++w public-key?    bin\
ary					



```

    |         |         | |      +---w private-key?   bin\
ary
    |         |         | +--rw cert
    |         |         | |      ct:end-entity-cert-cms
    |         |         | +---n certificate-expiration
    |         |         |   +-- expiration-date?
    |         |         |   yang:date-and-time
    |         |         +---:(keystore) {keystore-supporte\
d}?
    |         |         +--rw reference?
    |         |         ks:asymmetric-key-cert\
ificate-ref
    |         +--rw server-auth
    |         | +--rw pinned-ssh-host-keys?
    |         | |      ta:pinned-host-keys-ref
    |         | |      {ta:ssh-host-keys}?
    |         | +--rw pinned-ca-certs?
    |         | |      ta:pinned-certificates-ref
    |         | |      {sshcmn:ssh-x509-certs,ta:x509-certif\
icates}?
    |         | +--rw pinned-server-certs?
    |         | |      ta:pinned-certificates-ref
    |         | |      {sshcmn:ssh-x509-certs,ta:x509-certif\
icates}?
    |         +--rw transport-params
    |         | {ssh-client-transport-params-config}?
    |         +--rw host-key
    |         | +--rw host-key-alg*   identityref
    |         +--rw key-exchange
    |         | +--rw key-exchange-alg*   identityref
    |         +--rw encryption
    |         | +--rw encryption-alg*   identityref
    |         +--rw mac
    |         | +--rw mac-alg*   identityref
    +---:(tls) {tls-listen}?
    +--rw tls
    +--rw address?          inet:ip-address
    +--rw port?             inet:port-number
    +--rw client-identity
    | +--rw (auth-type)
    |   +---:(certificate)
    |     +--rw certificate
    |     +--rw (local-or-keystore)
    |     +---:(local) {local-keys-supported\
}?
    |         | +--rw algorithm?
    |         | |      ct:key-algorithm-ref
    |         | +--rw public-key?

```

Watsen

Expires March 24, 2019

[Page 10]

```

|           | |      binary
|           | +--rw private-key?
|           | |      union
|           | +---x generate-hidden-key
|           | |      +---w input
|           | |      +---w algorithm
|           | |      ct:key-algorithm\
-ref
|           | +---x install-hidden-key
|           | |      +---w input
|           | |      +---w algorithm
|           | |      |      ct:key-algorithm\
-ref
|           | |      +---w public-key?    bin\
ary
|           | |      +---w private-key?    bin\
ary
|           | +--rw cert
|           | |      ct:end-entity-cert-cms
|           | +---n certificate-expiration
|           | |      +-- expiration-date?
|           | |      yang:date-and-time
|           | +---:(keystore) {keystore-supporte\
d}?
|           | +--rw reference?
|           | |      ks:asymmetric-key-cert\
ificate-ref
+--rw server-auth
| +--rw pinned-ca-certs?
| |      ta:pinned-certificates-ref
| |      {ta:x509-certificates}?
| +--rw pinned-server-certs?
| |      ta:pinned-certificates-ref
| |      {ta:x509-certificates}?
+--rw hello-params
| {tls-client-hello-params-config}?
+--rw tls-versions
| +--rw tls-version*    identityref
+--rw cipher-suites
| +--rw cipher-suite*    identityref

```

### 3.2. Example Usage

The following example illustrates configuring a NETCONF client to initiate connections, using both the SSH and TLS transport protocols, as well as listening for call-home connections, again using both the SSH and TLS transport protocols.

Watsen

Expires March 24, 2019

[Page 11]

This example is consistent with the examples presented in Section 3.2 of [[I-D.ietf-netconf-keystore](#)].

[Note: '\\' line wrapping for formatting only]

```
<netconf-client
  xmlns="urn:ietf:params:xml:ns:yang:ietf-netconf-client">

  <!-- NETCONF servers to initiate connections to -->
  <initiate>
    <netconf-server>
      <name>corp-fw1</name>
      <endpoints>
        <endpoint>
          <name>corp-fw1.example.com</name>
          <ssh>
            <address>corp-fw1.example.com</address>
            <client-identity>
              <username>foobar</username>
              <public-key>
                <algorithm xmlns:ct="urn:ietf:params:xml:ns:yang:ietf-
f-crypto-types">ct:secp521r1</algorithm>
                <private-key>base64encodedvalue==</private-key>
                <public-key>base64encodedvalue==</public-key>
              </public-key>
            </client-identity>
            <server-auth>
              <pinned-ca-certs>explicitly-trusted-server-ca-certs</p\
inned-ca-certs>
              <pinned-server-certs>explicitly-trusted-server-certs</\
pinned-server-certs>
            </server-auth>
          </ssh>
        </endpoint>
        <endpoint>
          <name>corp-fw2.example.com</name>
          <ssh>
            <address>corp-fw2.example.com</address>
            <client-identity>
              <username>foobar</username>
              <public-key>
                <algorithm xmlns:ct="urn:ietf:params:xml:ns:yang:ietf-
f-crypto-types">ct:secp521r1</algorithm>
                <private-key>base64encodedvalue==</private-key>
                <public-key>base64encodedvalue==</public-key>
              </public-key>
            </client-identity>
```

Watsen

Expires March 24, 2019

[Page 12]

```

        <server-auth>
          <pinned-ca-certs>explicitly-trusted-server-ca-certs</p\
innetd-ca-certs>
          <pinned-server-certs>explicitly-trusted-server-certs</\
pinned-server-certs>
        </server-auth>
      </ssh>
    </endpoint>
  </endpoints>
  <connection-type>
    <persistent/>
  </connection-type>
  <reconnect-strategy>
    <start-with>last-connected</start-with>
  </reconnect-strategy>
</netconf-server>
</initiate>

<!-- endpoints to listen for NETCONF Call Home connections on -->
<listen>
  <endpoint>
    <name>Intranet-facing listener</name>
    <ssh>
      <address>192.0.2.7</address>
      <client-identity>
        <username>foobar</username>
        <public-key>
          <algorithm xmlns:ct="urn:ietf:params:xml:ns:yang:ietf-cr\
ypto-types">ct:secp521r1</algorithm>
          <private-key>base64encodedvalue==</private-key>
          <public-key>base64encodedvalue==</public-key>
        </public-key>
      </client-identity>
      <server-auth>
        <pinned-ca-certs>explicitly-trusted-server-ca-certs</pinne\
d-ca-certs>
        <pinned-server-certs>explicitly-trusted-server-certs</pinn\
ed-server-certs>
        <pinned-ssh-host-keys>explicitly-trusted-ssh-host-keys</pi\
nnetd-ssh-host-keys>
      </server-auth>
    </ssh>
  </endpoint>
</listen>
</netconf-client>

```

Watsen

Expires March 24, 2019

[Page 13]

### 3.3. YANG Module

This YANG module has normative references to [\[RFC6242\]](#), [\[RFC6991\]](#), [\[RFC7589\]](#), [\[RFC8071\]](#), [\[I-D.ietf-netconf-ssh-client-server\]](#), and [\[I-D.ietf-netconf-tls-client-server\]](#).

```
<CODE BEGINS> file "ietf-netconf-client@2018-09-20.yang"
module ietf-netconf-client {
  yang-version 1.1;

  namespace "urn:ietf:params:xml:ns:yang:ietf-netconf-client";
  prefix "ncc";

  import ietf-yang-types {
    prefix yang;
    reference
      "RFC 6991: Common YANG Data Types";
  }

  import ietf-inet-types {
    prefix inet;
    reference
      "RFC 6991: Common YANG Data Types";
  }

  import ietf-ssh-client {
    prefix ss;
    revision-date 2018-09-20; // stable grouping definitions
    reference
      "RFC YYYY: YANG Groupings for SSH Clients and SSH Servers";
  }

  import ietf-tls-client {
    prefix ts;
    revision-date 2018-09-20; // stable grouping definitions
    reference
      "RFC ZZZZ: YANG Groupings for TLS Clients and TLS Servers";
  }

  organization
    "IETF NETCONF (Network Configuration) Working Group";

  contact
    "WG Web:  <http://datatracker.ietf.org/wg/netconf/>
    WG List:  <mailto:netconf@ietf.org>

    Author:   Kent Watsen
              <mailto:kwatsen@juniper.net>
```



Author: Gary Wu  
<mailto:garywu@cisco.com>;

description

"This module contains a collection of YANG definitions for configuring NETCONF clients.

Copyright (c) 2017 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Simplified BSD License set forth in [Section 4.c](#) of the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>).

This version of this YANG module is part of RFC XXXX; see the RFC itself for full legal notices.";

```
revision "2018-09-20" {  
  description  
    "Initial version";  
  reference  
    "RFC XXXX: NETCONF Client and Server Models";  
}
```

// Features

```
feature initiate {  
  description  
    "The 'initiate' feature indicates that the NETCONF client  
    supports initiating NETCONF connections to NETCONF servers  
    using at least one transport (e.g., SSH, TLS, etc.).";  
}
```

```
feature ssh-initiate {  
  description  
    "The 'ssh-initiate' feature indicates that the NETCONF client  
    supports initiating SSH connections to NETCONF servers.";  
  reference  
    "RFC 6242:  
    Using the NETCONF Protocol over Secure Shell (SSH)";  
}
```

```
feature tls-initiate {  
  description
```



```
    "The 'tls-initiate' feature indicates that the NETCONF client
    supports initiating TLS connections to NETCONF servers.";
  reference
    "RFC 7589: Using the NETCONF Protocol over Transport
    Layer Security (TLS) with Mutual X.509
    Authentication";
}

feature listen {
  description
    "The 'listen' feature indicates that the NETCONF client
    supports opening a port to accept NETCONF server call
    home connections using at least one transport (e.g.,
    SSH, TLS, etc.).";
}

feature ssh-listen {
  description
    "The 'ssh-listen' feature indicates that the NETCONF client
    supports opening a port to listen for incoming NETCONF
    server call-home SSH connections.";
  reference
    "RFC 8071: NETCONF Call Home and RESTCONF Call Home";
}

feature tls-listen {
  description
    "The 'tls-listen' feature indicates that the NETCONF client
    supports opening a port to listen for incoming NETCONF
    server call-home TLS connections.";
  reference
    "RFC 8071: NETCONF Call Home and RESTCONF Call Home";
}

container netconf-client {
  uses netconf-client-grouping;
  description
    "Top-level container for NETCONF client configuration.";
}

grouping netconf-client-grouping {
  description
    "Top-level grouping for NETCONF client configuration.";

  container initiate {
    if-feature initiate;
    presence "Enables client to initiate TCP connections";
    description
```

Watsen

Expires March 24, 2019

[Page 16]

```
"Configures client initiating underlying TCP connections.";
list netconf-server {
  key name;
  min-elements 1;
  description
    "List of NETCONF servers the NETCONF client is to
    initiate connections to in parallel.";
  leaf name {
    type string;
    description
      "An arbitrary name for the NETCONF server.";
  }
  container endpoints {
    description
      "Container for the list of endpoints.";
    list endpoint {
      key name;
      min-elements 1;
      ordered-by user;
      description
        "A user-ordered list of endpoints that the NETCONF
        client will attempt to connect to in the specified
        sequence. Defining more than one enables
        high-availability.";
      leaf name {
        type string;
        description
          "An arbitrary name for the endpoint.";
      }
    }
    choice transport {
      mandatory true;
      description
        "Selects between available transports.";
      case ssh {
        if-feature ssh-initiate;
        container ssh {
          description
            "Specifies IP and SSH specific configuration
            for the connection.";
          leaf address {
            type inet:host;
            description
              "The IP address or hostname of the endpoint.
              If a domain name is configured, then the
              DNS resolution should happen on each usage
              attempt. If the DNS resolution results in
              multiple IP addresses, the IP addresses will
              be tried according to local preference order
```

Watsen

Expires March 24, 2019

[Page 17]

```
        until a connection has been established or
        until all IP addresses have failed.";
    }
    leaf port {
        type inet:port-number;
        default 830;
        description
            "The IP port for this endpoint. The NETCONF
            client will use the IANA-assigned well-known
            port for 'netconf-ssh' (830) if no value is
            specified.";
    }
    uses ss:ssh-client-grouping;
}
} // end ssh
case tls {
    if-feature tls-initiate;
    container tls {
        description
            "Specifies IP and TLS specific configuration
            for the connection.";
        leaf address {
            type inet:host;
            description
                "The IP address or hostname of the endpoint.
                If a domain name is configured, then the
                DNS resolution should happen on each usage
                attempt. If the DNS resolution results in
                multiple IP addresses, the IP addresses will
                be tried according to local preference order
                until a connection has been established or
                until all IP addresses have failed.";
        }
        leaf port {
            type inet:port-number;
            default 6513;
            description
                "The IP port for this endpoint. The NETCONF
                client will use the IANA-assigned well-
                known port for 'netconf-tls' (6513) if no
                value is specified.";
        }
        uses ts:tls-client-grouping {
            refine "client-identity/auth-type" {
                mandatory true;
                description
                    "NETCONF/TLS clients MUST pass some
                    authentication credentials.";
            }
        }
    }
}
```



```

    }
  }
} // end tls
}
}
}

```

```

container connection-type {
  description
    "Indicates the kind of connection to use.";
  choice connection-type {
    mandatory true;
    description
      "Selects between available connection types.";
    case persistent-connection {
      container persistent {
        presence
          "Indicates that a persistent connection is to be
            maintained.";
        description
          "Maintain a persistent connection to the NETCONF
            server. If the connection goes down, immediately
            start trying to reconnect to it, using the
            reconnection strategy.

            This connection type minimizes any NETCONF server
            to NETCONF client data-transfer delay, albeit at
            the expense of holding resources longer.";
        container keep-alives {
          description
            "Configures the keep-alive policy, to
              proactively test the aliveness of the SSH/TLS
              server. An unresponsive SSH/TLS server will
              be dropped after approximately max-attempts *
              max-wait seconds.";
          leaf max-wait {
            type uint16 {
              range "1..max";
            }
            units seconds;
            default 30;
            description
              "Sets the amount of time in seconds after
                which if no data has been received from the
                SSH/TLS server, a SSH/TLS-level message will
                be sent to test the aliveness of the SSH/TLS
                server.";

```



```
    }
    leaf max-attempts {
      type uint8;
      default 3;
      description
        "Sets the maximum number of sequential keep-
        alive messages that can fail to obtain a
        response from the SSH/TLS server before
        assuming the SSH/TLS server is no longer
        alive.";
    }
  }
}

case periodic-connection {
  container periodic {
    presence
      "Indicates that a periodic connection is to be
      maintained.";
    description
      "Periodically connect to the NETCONF server. The
      NETCONF server should close the connection upon
      completing planned activities.

      This connection type increases resource
      utilization, albeit with increased delay in
      NETCONF server to NETCONF client interactions.";
    leaf period {
      type uint16;
      units "minutes";
      default 60;
      description
        "Duration of time between periodic connections.";
    }
    leaf anchor-time {
      type yang:date-and-time {
        // constrained to minute-level granularity
        pattern '\d{4}-\d{2}-\d{2}T\d{2}:\d{2}'
          + '(Z|[\+|-]\d{2}:\d{2})';
      }
      description
        "Designates a timestamp before or after which a
        series of periodic connections are determined.
        The periodic connections occur at a whole
        multiple interval from the anchor time. For
        example, for an anchor time is 15 minutes past
        midnight and a period interval of 24 hours, then
        a periodic connection will occur 15 minutes past
```



```
        midnight everyday.";
    }
    leaf idle-timeout {
        type uint16;
        units "seconds";
        default 120; // two minutes
        description
            "Specifies the maximum number of seconds that
             a NETCONF session may remain idle. A NETCONF
             session will be dropped if it is idle for an
             interval longer than this number of seconds.
             If set to zero, then the NETCONF client will
             never drop a session because it is idle.";
    }
}
}
}
}
container reconnect-strategy {
    description
        "The reconnection strategy directs how a NETCONF client
         reconnects to a NETCONF server, after discovering its
         connection to the server has dropped, even if due to a
         reboot. The NETCONF client starts with the specified
         endpoint and tries to connect to it max-attempts times
         before trying the next endpoint in the list (round
         robin).";
    leaf start-with {
        type enumeration {
            enum first-listed {
                description
                    "Indicates that reconnections should start with
                     the first endpoint listed.";
            }
            enum last-connected {
                description
                    "Indicates that reconnections should start with
                     the endpoint last connected to. If no previous
                     connection has ever been established, then the
                     first endpoint configured is used. NETCONF
                     clients SHOULD be able to remember the last
                     endpoint connected to across reboots.";
            }
            enum random-selection {
                description
                    "Indicates that reconnections should start with
                     a random endpoint.";
            }
        }
    }
}
```

Watsen

Expires March 24, 2019

[Page 21]

```
    }
    default first-listed;
    description
      "Specifies which of the NETCONF server's endpoints
       the NETCONF client should start with when trying
       to connect to the NETCONF server.";
  }
  leaf max-attempts {
    type uint8 {
      range "1..max";
    }
    default 3;
    description
      "Specifies the number times the NETCONF client tries
       to connect to a specific endpoint before moving on
       to the next endpoint in the list (round robin).";
  }
}
} // end netconf-server
} // end initiate

container listen {
  if-feature listen;
  presence "Enables client to accept call-home connections";
  description
    "Configures client accepting call-home TCP connections.";

  leaf idle-timeout {
    type uint16;
    units "seconds";
    default 3600; // one hour
    description
      "Specifies the maximum number of seconds that a NETCONF
       session may remain idle. A NETCONF session will be
       dropped if it is idle for an interval longer than this
       number of seconds. If set to zero, then the server
       will never drop a session because it is idle. Sessions
       that have a notification subscription active are never
       dropped.";
  }
}

list endpoint {
  key name;
  min-elements 1;
  description
    "List of endpoints to listen for NETCONF connections.";
  leaf name {
    type string;
```



```
    description
      "An arbitrary name for the NETCONF listen endpoint.";
  }
  choice transport {
    mandatory true;
    description
      "Selects between available transports.";
    case ssh {
      if-feature ssh-listen;
      container ssh {
        description
          "SSH-specific listening configuration for inbound
            connections.";
        leaf address {
          type inet:ip-address;
          description
            "The IP address to listen on for incoming call-
              home connections. The NETCONF client will listen
              on all configured interfaces if no value is
              specified. INADDR_ANY (0.0.0.0) or INADDR6_ANY
              (0:0:0:0:0:0:0:0 a.k.a. ::) MUST be used when
              the server is to listen on all IPv4 or IPv6
              addresses, respectively.";
        }
        leaf port {
          type inet:port-number;
          default 4334;
          description
            "The port number to listen on for call-home
              connections. The NETCONF client will listen
              on the IANA-assigned well-known port for
              'netconf-ch-ssh' (4334) if no value is
              specified.";
        }
      }
      uses ss:ssh-client-grouping;
    }
  }
  case tls {
    if-feature tls-listen;
    container tls {
      description
        "TLS-specific listening configuration for inbound
          connections.";
      leaf address {
        type inet:ip-address;
        description
          "The IP address to listen on for incoming call-
            home connections. The NETCONF client will listen
```



```
        on all configured interfaces if no value is
        specified.  INADDR_ANY (0.0.0.0) or INADDR6_ANY
        (0:0:0:0:0:0:0:0 a.k.a. ::) MUST be used when
        the server is to listen on all IPv4 or IPv6
        addresses, respectively.";
    }
    leaf port {
        type inet:port-number;
        default 4335;
        description
            "The port number to listen on for call-home
            connections.  The NETCONF client will listen
            on the IANA-assigned well-known port for
            'netconf-ch-tls' (4335) if no value is
            specified.";
    }
    uses ts:tls-client-grouping {
        refine "client-identity/auth-type" {
            mandatory true;
            description
                "NETCONF/TLS clients MUST pass some
                authentication credentials.";
        }
    }
} // end transport
} // end endpoint
} // end listen

} // end netconf-client
}
<CODE ENDS>
```

#### 4. The NETCONF Server Model

The NETCONF server model presented in this section supports servers both listening for connections as well as initiating call-home connections.

This model supports both the SSH and TLS transport protocols, using the SSH server and TLS server groupings defined in [\[I-D.ietf-netconf-ssh-client-server\]](#) and [\[I-D.ietf-netconf-tls-client-server\]](#) respectively.

All private keys and trusted certificates are held in the keystore model defined in [\[I-D.ietf-netconf-keystore\]](#).

Watsen

Expires March 24, 2019

[Page 24]

YANG feature statements are used to enable implementations to advertise which parts of the model the NETCONF server supports.

#### 4.1. Tree Diagram

The following tree diagram [RFC8340] provides an overview of the data model for the "ietf-netconf-server" module. Just the container is displayed below, but there is also a reusable grouping called "netconf-server-grouping" that the container is using.

[Note: '\\' line wrapping for formatting only]

```

module: ietf-netconf-server
+--rw netconf-server
  +--rw listen! {listen}?
  |   +--rw idle-timeout?   uint16
  |   +--rw endpoint* [name]
  |       +--rw name          string
  |       +--rw (transport)
  |           +--:(ssh) {ssh-listen}?
  |               +--rw ssh
  |                   +--rw address          inet:ip-address
  |                   +--rw port?            inet:port-number
  |                   +--rw server-identity
  |                       +--rw host-key* [name]
  |                           +--rw name          string
  |                           +--rw (host-key-type)
  |                               +--:(public-key)
  |                                   +--rw public-key
  |                                       +--rw (local-or-keystore)
  |                                           +--:(local)
  |                                               {local-keys-supported\
  }?
  |   +--rw algorithm?
  |       |   ct:key-algorithm-ref
  |   +--rw public-key?
  |       |   binary
  |   +--rw private-key?
  |       |   union
  |       +--x generate-hidden-key
  |           +--w input
  |               +--w algorithm
  |                   ct:key-algori\
  thm-ref
  |   +--x install-hidden-key
  |       +--w input
  |           +--w algorithm

```



						ct:key-algori\
thm-ref						+++w public-key?
						binary
						+++w private-key?
						binary
					+++:(keystore)	
						{keystore-supported}?
					+-rw reference?	
						ks:asymmetric-key-r\
ef					+++:(certificate)	
					+-rw certificate	
						{sshcmn:ssh-x509-certs}?
					+-rw (local-or-keystore)	
					+++:(local)	
						{local-keys-supported\
}?					+-rw algorithm?	
						ct:key-algorithm-ref
					+-rw public-key?	
						binary
					+-rw private-key?	
						union
					+++x generate-hidden-key	
						+++w input
						+++w algorithm
						ct:key-algori\
thm-ref					+++x install-hidden-key	
						+++w input
						+++w algorithm
						ct:key-algori\
thm-ref						+++w public-key?
						binary
						+++w private-key?
						binary
					+-rw cert	
						ct:end-entity-cert-\
cms					+++n certificate-expiration	
					+- expiration-date?	
						yang:date-and-ti\
me					+++:(keystore)	
						{keystore-supported}?
					+-rw reference?	

Watsen

Expires March 24, 2019

[Page 26]

```

| | | | | ks:asymmetric-key-c\
ertificate-ref
| | | | |
| | | | | +--rw client-cert-auth {sshcmn:ssh-x509-certs}?
| | | | | | +--rw pinned-ca-certs?
| | | | | | | ta:pinned-certificates-ref
| | | | | | | {ta:x509-certificates}?
| | | | | | +--rw pinned-client-certs?
| | | | | | | ta:pinned-certificates-ref
| | | | | | | {ta:x509-certificates}?
| | | | | +--rw transport-params
| | | | | | {ssh-server-transport-params-config}?
| | | | | +--rw host-key
| | | | | | +--rw host-key-alg* identityref
| | | | | +--rw key-exchange
| | | | | | +--rw key-exchange-alg* identityref
| | | | | +--rw encryption
| | | | | | +--rw encryption-alg* identityref
| | | | | +--rw mac
| | | | | | +--rw mac-alg* identityref
| | | | | +---:(tls) {tls-listen}?
| | | | | +--rw tls
| | | | | | +--rw address inet:ip-address
| | | | | | +--rw port? inet:port-number
| | | | | +--rw server-identity
| | | | | | +--rw (local-or-keystore)
| | | | | | | +---:(local) {local-keys-supported}?
| | | | | | | | +--rw algorithm?
| | | | | | | | | ct:key-algorithm-ref
| | | | | | | +--rw public-key? binary
| | | | | | | +--rw private-key? union
| | | | | | | +---x generate-hidden-key
| | | | | | | | +---w input
| | | | | | | | +---w algorithm
| | | | | | | | | ct:key-algorithm-ref
| | | | | | | +---x install-hidden-key
| | | | | | | | +---w input
| | | | | | | | +---w algorithm
| | | | | | | | | ct:key-algorithm-ref
| | | | | | | | +---w public-key? binary
| | | | | | | | +---w private-key? binary
| | | | | | +--rw cert
| | | | | | | ct:end-entity-cert-cms
| | | | | | +---n certificate-expiration
| | | | | | | +-- expiration-date?
| | | | | | | yang:date-and-time
| | | | | +---:(keystore) {keystore-supported}?
| | | | | +--rw reference?
| | | | | ks:asymmetric-key-certificate-r\

```



ef

```

|         +--rw client-auth
|         |   +--rw pinned-ca-certs?
|         |   |   ta:pinned-certificates-ref
|         |   |   {ta:x509-certificates}?
|         |   +--rw pinned-client-certs?
|         |   |   ta:pinned-certificates-ref
|         |   |   {ta:x509-certificates}?
|         |   +--rw cert-maps
|         |   |   +--rw cert-to-name* [id]
|         |   |   |   +--rw id          uint32
|         |   |   |   +--rw fingerprint
|         |   |   |   |   x509c2n:tls-fingerprint
|         |   |   |   +--rw map-type      identityref
|         |   |   |   +--rw name          string
|         |   +--rw hello-params
|         |   |   {tls-server-hello-params-config}?
|         |   +--rw tls-versions
|         |   |   +--rw tls-version*      identityref
|         |   +--rw cipher-suites
|         |   |   +--rw cipher-suite*      identityref
+--rw call-home! {call-home}?
+--rw netconf-client* [name]
+--rw name          string
+--rw endpoints
| +--rw endpoint* [name]
| |   +--rw name          string
| |   +--rw (transport)
| |   |   +--:(ssh) {ssh-call-home}?
| |   |   |   +--rw ssh
| |   |   |   |   +--rw address          inet:host
| |   |   |   |   +--rw port?            inet:port-number
| |   |   |   +--rw server-identity
| |   |   |   |   +--rw host-key* [name]
| |   |   |   |   |   +--rw name          string
| |   |   |   |   |   +--rw (host-key-type)
| |   |   |   |   |   +--:(public-key)
| |   |   |   |   |   |   +--rw public-key
| |   |   |   |   |   |   |   +--rw (local-or-keystore)
| |   |   |   |   |   |   |   +--:(local)
| |   |   |   |   |   |   |   |   {local-keys-sup\
ported}?
| |   |   |   |   |   |   |   |   +--rw algorithm?
| |   |   |   |   |   |   |   |   |   ct:key-algori\
thm-ref
| |   |   |   |   |   |   |   |   |   +--rw public-key?
| |   |   |   |   |   |   |   |   |   |   binary
| |   |   |   |   |   |   |   |   |   +--rw private-key?

```







						+++w input
						+++w algorithm
algorithm-ref						ct:key-\
y?						+++w public-ke\
						binary
ey?						+++w private-k\
						binary
-cert-cms					+-rw cert	
						ct:end-entity\
iration					+++n certificate-exp\	
e?					+++ expiration-dat\	
and-time						yang:date-\
					+++:(keystore)	
rted}?						{keystore-suppo\
					+-rw reference?	
-key-certificate-ref						ks:asymmetric\
				+-rw client-cert-auth		
					{sshcmn:ssh-x509-certs}?	
				+-rw pinned-ca-certs?		
					ta:pinned-certificates-ref	
					{ta:x509-certificates}?	
				+-rw pinned-client-certs?		
					ta:pinned-certificates-ref	
					{ta:x509-certificates}?	
				+-rw transport-params		
g}?					{ssh-server-transport-params-confi\	
				+-rw host-key		
					+-rw host-key-alg* identityref	
				+-rw key-exchange		
					+-rw key-exchange-alg* identityref	
				+-rw encryption		
					+-rw encryption-alg* identityref	
				+-rw mac		
					+-rw mac-alg* identityref	
				+++:(tls) {tls-call-home}?		
				+-rw tls		
				+-rw address	inet:host	
				+-rw port?	inet:port-number	



```

|         +--rw server-identity
|         |   +--rw (local-or-keystore)
|         |   |   +--:(local) {local-keys-supported}?
|         |   |   |   +--rw algorithm?
|         |   |   |   |       ct:key-algorithm-ref
|         |   |   |   +--rw public-key?
|         |   |   |   |       binary
|         |   |   |   +--rw private-key?
|         |   |   |   |       union
|         |   |   |   +---x generate-hidden-key
|         |   |   |   |   +---w input
|         |   |   |   |   +---w algorithm
|         |   |   |   |   |       ct:key-algorithm-ref
|         |   |   |   +---x install-hidden-key
|         |   |   |   |   +---w input
|         |   |   |   |   +---w algorithm
|         |   |   |   |   |       ct:key-algorithm-ref
|         |   |   |   |   +---w public-key?    binary
|         |   |   |   |   +---w private-key?    binary
|         |   |   +--rw cert
|         |   |   |       ct:end-entity-cert-cms
|         |   |   +---n certificate-expiration
|         |   |   |   +-- expiration-date?
|         |   |   |   |       yang:date-and-time
|         |   +--:(keystore) {keystore-supported}?
|         |   +--rw reference?
|         |       ks:asymmetric-key-certifi\
cate-ref
|
|         +--rw client-auth
|         |   +--rw pinned-ca-certs?
|         |   |       ta:pinned-certificates-ref
|         |   |       {ta:x509-certificates}?
|         |   +--rw pinned-client-certs?
|         |   |       ta:pinned-certificates-ref
|         |   |       {ta:x509-certificates}?
|         |   +--rw cert-maps
|         |   |   +--rw cert-to-name* [id]
|         |   |   |   +--rw id                uint32
|         |   |   |   +--rw fingerprint
|         |   |   |   |       x509c2n:tls-fingerprint
|         |   |   |   +--rw map-type            identityref
|         |   |   |   +--rw name                string
|         +--rw hello-params
|         |   {tls-server-hello-params-config}?
|         +--rw tls-versions
|         |   +--rw tls-version*    identityref
|         +--rw cipher-suites
|         |   +--rw cipher-suite*    identityref

```



```

+--rw connection-type
| +--rw (connection-type)
|   +--:(persistent-connection)
|   | +--rw persistent!
|   |   +--rw keep-alives
|   |   +--rw max-wait?      uint16
|   |   +--rw max-attempts? uint8
|   +--:(periodic-connection)
|   +--rw periodic!
|     +--rw period?      uint16
|     +--rw anchor-time? yang:date-and-time
|     +--rw idle-timeout? uint16
+--rw reconnect-strategy
  +--rw start-with?  enumeration
  +--rw max-attempts? uint8

```

#### 4.2. Example Usage

The following example illustrates configuring a NETCONF server to listen for NETCONF client connections using both the SSH and TLS transport protocols, as well as configuring call-home to two NETCONF clients, one using SSH and the other using TLS.

This example is consistent with the examples presented in Section 3.2 of [[I-D.ietf-netconf-keystore](#)].

[Note: '\\' line wrapping for formatting only]

```

<netconf-server
  xmlns="urn:ietf:params:xml:ns:yang:ietf-netconf-server"
  xmlns:x509c2n="urn:ietf:params:xml:ns:yang:ietf-x509-cert-to-name">

  <!-- endpoints to listen for NETCONF connections on -->
  <listen>
    <endpoint> <!-- listening for SSH connections -->
      <name>netconf/ssh</name>
      <ssh>
        <address>192.0.2.7</address>
        <server-identity>
          <host-key>
            <name>deployment-specific-certificate</name>
            <public-key>
              <algorithm xmlns:ct="urn:ietf:params:xml:ns:yang:ietf-
crypto-types">ct:secp521r1</algorithm>
              <private-key>base64encodedvalue==</private-key>
              <public-key>base64encodedvalue==</public-key>
            </public-key>

```



```

        </host-key>
      </server-identity>
    <client-cert-auth>
      <pinned-ca-certs>explicitly-trusted-client-ca-certs</pinne\
d-ca-certs>
      <pinned-client-certs>explicitly-trusted-client-certs</pinn\
ed-client-certs>
    </client-cert-auth>
  </ssh>
</endpoint>
<endpoint> <!-- listening for TLS sessions -->
  <name>netconf/tls</name>
  <tls>
    <address>192.0.2.7</address>
    <server-identity>
      <algorithm xmlns:ct="urn:ietf:params:xml:ns:yang:ietf-cryp\
to-types">ct:secp521r1</algorithm>
      <private-key>base64encodedvalue==</private-key>
      <public-key>base64encodedvalue==</public-key>
      <cert>base64encodedvalue==</cert>
    </server-identity>
    <client-auth>
      <pinned-ca-certs>explicitly-trusted-client-ca-certs</pinne\
d-ca-certs>
      <pinned-client-certs>explicitly-trusted-client-certs</pinn\
ed-client-certs>
      <cert-maps>
        <cert-to-name>
          <id>1</id>
          <fingerprint>11:0A:05:11:00</fingerprint>
          <map-type>x509c2n:san-any</map-type>
        </cert-to-name>
        <cert-to-name>
          <id>2</id>
          <fingerprint>B3:4F:A1:8C:54</fingerprint>
          <map-type>x509c2n:specified</map-type>
          <name>scooby-doo</name>
        </cert-to-name>
      </cert-maps>
    </client-auth>
  </tls>
</endpoint>
</listen>

<!-- calling home to SSH and TLS based NETCONF clients -->
<call-home>
  <netconf-client> <!-- SSH-based client -->
    <name>config-mgr</name>

```



```

<endpoints>
  <endpoint>
    <name>east-data-center</name>
    <ssh>
      <address>east.config-mgr.example.com</address>
      <server-identity>
        <host-key>
          <name>deployment-specific-certificate</name>
          <public-key>
            <algorithm xmlns:ct="urn:ietf:params:xml:ns:yang:i\
etf-crypto-types">ct:secp521r1</algorithm>
            <private-key>base64encodedvalue==</private-key>
            <public-key>base64encodedvalue==</public-key>
          </public-key>
        </host-key>
      </server-identity>
      <client-cert-auth>
        <pinned-ca-certs>explicitly-trusted-client-ca-certs</p\
inned-ca-certs>
        <pinned-client-certs>explicitly-trusted-client-certs</\
pinned-client-certs>
      </client-cert-auth>
    </ssh>
  </endpoint>
  <endpoint>
    <name>west-data-center</name>
    <ssh>
      <address>west.config-mgr.example.com</address>
      <server-identity>
        <host-key>
          <name>deployment-specific-certificate</name>
          <public-key>
            <algorithm xmlns:ct="urn:ietf:params:xml:ns:yang:i\
etf-crypto-types">ct:secp521r1</algorithm>
            <private-key>base64encodedvalue==</private-key>
            <public-key>base64encodedvalue==</public-key>
          </public-key>
        </host-key>
      </server-identity>
      <client-cert-auth>
        <pinned-ca-certs>explicitly-trusted-client-ca-certs</p\
inned-ca-certs>
        <pinned-client-certs>explicitly-trusted-client-certs</\
pinned-client-certs>
      </client-cert-auth>
    </ssh>
  </endpoint>
</endpoints>

```



```

    <connection-type>
      <periodic>
        <idle-timeout>300</idle-timeout>
        <period>60</period>
      </periodic>
    </connection-type>
    <reconnect-strategy>
      <start-with>last-connected</start-with>
      <max-attempts>3</max-attempts>
    </reconnect-strategy>
  </netconf-client>
  <netconf-client> <!-- TLS-based client -->
    <name>data-collector</name>
    <endpoints>
      <endpoint>
        <name>east-data-center</name>
        <tls>
          <address>east.analytics.example.com</address>
          <server-identity>
            <algorithm xmlns:ct="urn:ietf:params:xml:ns:yang:ietf-
crypto-types">ct:secp521r1</algorithm>
            <private-key>base64encodedvalue==</private-key>
            <public-key>base64encodedvalue==</public-key>
            <cert>base64encodedvalue==</cert>
          </server-identity>
          <client-auth>
            <pinned-ca-certs>explicitly-trusted-client-ca-certs</p\
inned-ca-certs>
            <pinned-client-certs>explicitly-trusted-client-certs</\
pinned-client-certs>
            <cert-maps>
              <cert-to-name>
                <id>1</id>
                <fingerprint>11:0A:05:11:00</fingerprint>
                <map-type>x509c2n:san-any</map-type>
              </cert-to-name>
              <cert-to-name>
                <id>2</id>
                <fingerprint>B3:4F:A1:8C:54</fingerprint>
                <map-type>x509c2n:specified</map-type>
                <name>scooby-doo</name>
              </cert-to-name>
            </cert-maps>
          </client-auth>
        </tls>
      </endpoint>
      <endpoint>
        <name>west-data-center</name>

```



```
<tls>
  <address>west.analytics.example.com</address>
  <server-identity>
    <algorithm xmlns:ct="urn:ietf:params:xml:ns:yang:ietf-\
crypto-types">ct:secp521r1</algorithm>
    <private-key>base64encodedvalue==</private-key>
    <public-key>base64encodedvalue==</public-key>
    <cert>base64encodedvalue==</cert>
  </server-identity>
  <client-auth>
    <pinned-ca-certs>explicitly-trusted-client-ca-certs</p\
inned-ca-certs>
    <pinned-client-certs>explicitly-trusted-client-certs</\
pinned-client-certs>
    <cert-maps>
      <cert-to-name>
        <id>1</id>
        <fingerprint>11:0A:05:11:00</fingerprint>
        <map-type>x509c2n:san-any</map-type>
      </cert-to-name>
      <cert-to-name>
        <id>2</id>
        <fingerprint>B3:4F:A1:8C:54</fingerprint>
        <map-type>x509c2n:specified</map-type>
        <name>scooby-doo</name>
      </cert-to-name>
    </cert-maps>
  </client-auth>
</tls>
</endpoint>
</endpoints>
<connection-type>
  <persistent>
    <keep-alives>
      <max-wait>30</max-wait>
      <max-attempts>3</max-attempts>
    </keep-alives>
  </persistent>
</connection-type>
<reconnect-strategy>
  <start-with>first-listed</start-with>
  <max-attempts>3</max-attempts>
</reconnect-strategy>
</netconf-client>
</call-home>
</netconf-server>
```



### 4.3. YANG Module

This YANG module has normative references to [\[RFC6242\]](#), [\[RFC6991\]](#), [\[RFC7407\]](#), [\[RFC7589\]](#), [\[RFC8071\]](#), [\[I-D.ietf-netconf-ssh-client-server\]](#), and [\[I-D.ietf-netconf-tls-client-server\]](#).

This YANG module imports YANG types from [\[RFC6991\]](#), and YANG groupings from [\[RFC7407\]](#), [\[I-D.ietf-netconf-ssh-client-server\]](#) and [\[I-D.ietf-netconf-ssh-client-server\]](#).

```
<CODE BEGINS> file "ietf-netconf-server@2018-09-20.yang"
module ietf-netconf-server {
  yang-version 1.1;

  namespace "urn:ietf:params:xml:ns:yang:ietf-netconf-server";
  prefix "ncs";

  import ietf-yang-types {
    prefix yang;
    reference
      "RFC 6991: Common YANG Data Types";
  }

  import ietf-inet-types {
    prefix inet;
    reference
      "RFC 6991: Common YANG Data Types";
  }

  import ietf-x509-cert-to-name {
    prefix x509c2n;
    reference
      "RFC 7407: A YANG Data Model for SNMP Configuration";
  }

  import ietf-ssh-server {
    prefix ss;
    revision-date 2018-09-20; // stable grouping definitions
    reference
      "RFC YYYY: YANG Groupings for SSH Clients and SSH Servers";
  }

  import ietf-tls-server {
    prefix ts;
    revision-date 2018-09-20; // stable grouping definitions
    reference
      "RFC ZZZZ: YANG Groupings for TLS Clients and TLS Servers";
```



```
}
```

```
organization
```

```
"IETF NETCONF (Network Configuration) Working Group";
```

```
contact
```

```
"WG Web: <http://datatracker.ietf.org/wg/netconf/>
```

```
WG List: <mailto:netconf@ietf.org>
```

```
Author: Kent Watsen
```

```
<mailto:kwatsen@juniper.net>
```

```
Author: Gary Wu
```

```
<mailto:garywu@cisco.com>
```

```
Author: Juergen Schoenwaelder
```

```
<mailto:j.schoenwaelder@jacobs-university.de>;
```

```
description
```

```
"This module contains a collection of YANG definitions for  
configuring NETCONF servers.
```

```
Copyright (c) 2017 IETF Trust and the persons identified as  
authors of the code. All rights reserved.
```

```
Redistribution and use in source and binary forms, with or  
without modification, is permitted pursuant to, and subject  
to the license terms contained in, the Simplified BSD  
License set forth in Section 4.c of the IETF Trust's  
Legal Provisions Relating to IETF Documents  
(http://trustee.ietf.org/license-info).
```

```
This version of this YANG module is part of RFC XXXX; see  
the RFC itself for full legal notices.";
```

```
revision "2018-09-20" {
```

```
description
```

```
"Initial version";
```

```
reference
```

```
"RFC XXXX: NETCONF Client and Server Models";
```

```
}
```

```
// Features
```

```
feature listen {
```

```
description
```



```
    "The 'listen' feature indicates that the NETCONF server
    supports opening a port to accept NETCONF client connections
    using at least one transport (e.g., SSH, TLS, etc.).";
}

feature ssh-listen {
  description
    "The 'ssh-listen' feature indicates that the NETCONF server
    supports opening a port to accept NETCONF over SSH
    client connections.";
  reference
    "RFC 6242:
    Using the NETCONF Protocol over Secure Shell (SSH)";
}

feature tls-listen {
  description
    "The 'tls-listen' feature indicates that the NETCONF server
    supports opening a port to accept NETCONF over TLS
    client connections.";
  reference
    "RFC 7589: Using the NETCONF Protocol over Transport
    Layer Security (TLS) with Mutual X.509
    Authentication";
}

feature call-home {
  description
    "The 'call-home' feature indicates that the NETCONF server
    supports initiating NETCONF call home connections to
    NETCONF clients using at least one transport (e.g., SSH,
    TLS, etc.).";
  reference
    "RFC 8071: NETCONF Call Home and RESTCONF Call Home";
}

feature ssh-call-home {
  description
    "The 'ssh-call-home' feature indicates that the NETCONF
    server supports initiating a NETCONF over SSH call
    home connection to NETCONF clients.";
  reference
    "RFC 8071: NETCONF Call Home and RESTCONF Call Home";
}

feature tls-call-home {
  description
    "The 'tls-call-home' feature indicates that the NETCONF
```



```
    server supports initiating a NETCONF over TLS call
    home connection to NETCONF clients.";
reference
  "RFC 8071: NETCONF Call Home and RESTCONF Call Home";
}

// protocol accessible nodes

container netconf-server {
  uses netconf-server-grouping;
  description
    "Top-level container for NETCONF server configuration.";
}

// reusable groupings

grouping netconf-server-grouping {
  description
    "Top-level grouping for NETCONF server configuration.";
  container listen {
    if-feature listen;
    presence "Enables server to listen for TCP connections";
    description "Configures listen behavior";
    leaf idle-timeout {
      type uint16;
      units "seconds";
      default 3600; // one hour
      description
        "Specifies the maximum number of seconds that a NETCONF
        session may remain idle. A NETCONF session will be
        dropped if it is idle for an interval longer than this
        number of seconds. If set to zero, then the server
        will never drop a session because it is idle. Sessions
        that have a notification subscription active are never
        dropped.";
    }
  }
  list endpoint {
    key name;
    min-elements 1;
    description
      "List of endpoints to listen for NETCONF connections.";
    leaf name {
      type string;
      description
        "An arbitrary name for the NETCONF listen endpoint.";
    }
  }
  choice transport {
```



```
mandatory true;
description
  "Selects between available transports.";
case ssh {
  if-feature ssh-listen;
  container ssh {
    description
      "SSH-specific listening configuration for inbound
      connections.";
    leaf address {
      type inet:ip-address;
      mandatory true;
      description
        "The IP address to listen on for incoming
        connections. The NETCONF server will listen
        on all configured interfaces if no value is
        specified. INADDR_ANY (0.0.0.0) or INADDR6_ANY
        (0:0:0:0:0:0:0:0 a.k.a. ::) MUST be used when
        the server is to listen on all IPv4 or IPv6
        addresses, respectively.";
    }
    leaf port {
      type inet:port-number;
      default 830;
      description
        "The local port number to listen on. If no value
        is specified, the IANA-assigned port value for
        'netconf-ssh' (830) is used.";
    }
    uses ss:ssh-server-grouping;
  }
}
case tls {
  if-feature tls-listen;
  container tls {
    description
      "TLS-specific listening configuration for inbound
      connections.";
    leaf address {
      type inet:ip-address;
      mandatory true;
      description
        "The IP address to listen on for incoming
        connections. The NETCONF server will listen
        on all configured interfaces if no value is
        specified. INADDR_ANY (0.0.0.0) or INADDR6_ANY
        (0:0:0:0:0:0:0:0 a.k.a. ::) MUST be used when
        the server is to listen on all IPv4 or IPv6
```

Watsen

Expires March 24, 2019

[Page 41]

```

        addresses, respectively.";
    }
    leaf port {
        type inet:port-number;
        default 6513;
        description
            "The local port number to listen on.  If no value
            is specified, the IANA-assigned port value for
            'netconf-tls' (6513) is used.";
    }
    uses ts:tls-server-grouping {
        refine "client-auth" {
            must 'pinned-ca-certs or pinned-client-certs';
            description
                "NETCONF/TLS servers MUST validate client
                certificates.";
        }
        augment "client-auth" {
            description
                "Augments in the cert-to-name structure.";
            container cert-maps {
                uses x509c2n:cert-to-name;
                description
                    "The cert-maps container is used by a TLS-
                    based NETCONF server to map the NETCONF
                    client's presented X.509 certificate to a
                    NETCONF username.  If no matching and valid
                    cert-to-name list entry can be found, then
                    the NETCONF server MUST close the connection,
                    and MUST NOT accept NETCONF messages over
                    it.";
                reference
                    "RFC WWW: NETCONF over TLS, Section 7";
            }
        }
    }
}

container call-home {
    if-feature call-home;
    presence "Enables server to initiate TCP connections";
    description "Configures call-home behavior";
    list netconf-client {
        key name;
    }
}

```



```
min-elements 1;
description
  "List of NETCONF clients the NETCONF server is to
  initiate call-home connections to in parallel.";
leaf name {
  type string;
  description
    "An arbitrary name for the remote NETCONF client.";
}
container endpoints {
  description
    "Container for the list of endpoints.";
  list endpoint {
    key name;
    min-elements 1;
    ordered-by user;
    description
      "A non-empty user-ordered list of endpoints for this
      NETCONF server to try to connect to in sequence.
      Defining more than one enables high-availability.";
    leaf name {
      type string;
      description
        "An arbitrary name for this endpoint.";
    }
    choice transport {
      mandatory true;
      description
        "Selects between available transports.";
      case ssh {
        if-feature ssh-call-home;
        container ssh {
          description
            "Specifies SSH-specific call-home transport
            configuration.";
          leaf address {
            type inet:host;
            mandatory true;
            description
              "The IP address or hostname of the endpoint.
              If a domain name is configured, then the
              DNS resolution should happen on each usage
              attempt. If the the DNS resolution results
              in multiple IP addresses, the IP addresses
              will be tried according to local preference
              order until a connection has been established
              or until all IP addresses have failed.";
          }
        }
      }
    }
  }
}
```



```
leaf port {
  type inet:port-number;
  default 4334;
  description
    "The IP port for this endpoint. The NETCONF
    server will use the IANA-assigned well-known
    port for 'netconf-ch-ssh' (4334) if no value
    is specified.";
}
uses ss:ssh-server-grouping;
}
}
case tls {
  if-feature tls-call-home;
  container tls {
    description
      "Specifies TLS-specific call-home transport
      configuration.";
    leaf address {
      type inet:host;
      mandatory true;
      description
        "The IP address or hostname of the endpoint.
        If a domain name is configured, then the
        DNS resolution should happen on each usage
        attempt. If the the DNS resolution results
        in multiple IP addresses, the IP addresses
        will be tried according to local preference
        order until a connection has been established
        or until all IP addresses have failed.";
    }
    leaf port {
      type inet:port-number;
      default 4335;
      description
        "The IP port for this endpoint. The NETCONF
        server will use the IANA-assigned well-known
        port for 'netconf-ch-tls' (4335) if no value
        is specified.";
    }
  }
  uses ts:tls-server-grouping {
    refine "client-auth" {
      must 'pinned-ca-certs or pinned-client-certs';
      description
        "NETCONF/TLS servers MUST validate client
        certificates.";
    }
    augment "client-auth" {
```

Watsen

Expires March 24, 2019

[Page 44]

```

        description
        "Augments in the cert-to-name structure.";
    container cert-maps {
        uses x509c2n:cert-to-name;
        description
        "The cert-maps container is used by a
        TLS-based NETCONF server to map the
        NETCONF client's presented X.509
        certificate to a NETCONF username. If
        no matching and valid cert-to-name list
        entry can be found, then the NETCONF
        server MUST close the connection, and
        MUST NOT accept NETCONF messages over
        it.";
        reference
        "RFC WWW: NETCONF over TLS, Section 7";
    }
}

} // end tls
} // end choice
} // end endpoint
}

container connection-type {
    description
    "Indicates the kind of connection to use.";
    choice connection-type {
        mandatory true;
        description
        "Selects between available connection types.";
        case persistent-connection {
            container persistent {
                presence
                "Indicates that a persistent connection is to be
                maintained.";
                description
                "Maintain a persistent connection to the NETCONF
                client. If the connection goes down, immediately
                start trying to reconnect to it, using the
                reconnection strategy.

                This connection type minimizes any NETCONF client
                to NETCONF server data-transfer delay, albeit at
                the expense of holding resources longer.";
            }
        }
    }
}

```



```
    proactively test the aliveness of the SSH/TLS
    client.  An unresponsive SSH/TLS client will
    be dropped after approximately max-attempts *
    max-wait seconds.";
  reference
    "RFC 8071: NETCONF Call Home and RESTCONF
    Call Home, Section 4.1, item S7";
  leaf max-wait {
    type uint16 {
      range "1..max";
    }
    units seconds;
    default 30;
    description
      "Sets the amount of time in seconds after
      which if no data has been received from
      the SSH/TLS client, a SSH/TLS-level message
      will be sent to test the aliveness of the
      SSH/TLS client.";
  }
  leaf max-attempts {
    type uint8;
    default 3;
    description
      "Sets the maximum number of sequential keep-
      alive messages that can fail to obtain a
      response from the SSH/TLS client before
      assuming the SSH/TLS client is no longer
      alive.";
  }
}
}
}

case periodic-connection {
  container periodic {
    presence
      "Indicates that a periodic connection is to be
      maintained.";
    description
      "Periodically connect to the NETCONF client.  The
      NETCONF client should close the underlying TLS
      connection upon completing planned activities.

      This connection type increases resource
      utilization, albeit with increased delay in
      NETCONF client to NETCONF client interactions.";
    leaf period {
```

Watsen

Expires March 24, 2019

[Page 46]

```
        type uint16;
        units "minutes";
        default 60;
        description
            "Duration of time between periodic connections.";
    }
    leaf anchor-time {
        type yang:date-and-time {
            // constrained to minute-level granularity
            pattern '\d{4}-\d{2}-\d{2}T\d{2}:\d{2}'
                + '(Z|[\+\-]\d{2}:\d{2})';
        }
        description
            "Designates a timestamp before or after which a
            series of periodic connections are determined.
            The periodic connections occur at a whole
            multiple interval from the anchor time. For
            example, for an anchor time is 15 minutes past
            midnight and a period interval of 24 hours, then
            a periodic connection will occur 15 minutes past
            midnight everyday.";
    }
    leaf idle-timeout {
        type uint16;
        units "seconds";
        default 120; // two minutes
        description
            "Specifies the maximum number of seconds that
            a NETCONF session may remain idle. A NETCONF
            session will be dropped if it is idle for an
            interval longer than this number of seconds.
            If set to zero, then the server will never
            drop a session because it is idle.";
    }
}
}
}
}
}
container reconnect-strategy {
    description
        "The reconnection strategy directs how a NETCONF server
        reconnects to a NETCONF client, after discovering its
        connection to the client has dropped, even if due to a
        reboot. The NETCONF server starts with the specified
        endpoint and tries to connect to it max-attempts times
        before trying the next endpoint in the list (round
        robin).";
    leaf start-with {
```

Watsen

Expires March 24, 2019

[Page 47]

```
    type enumeration {
      enum first-listed {
        description
          "Indicates that reconnections should start with
           the first endpoint listed.";
      }
      enum last-connected {
        description
          "Indicates that reconnections should start with
           the endpoint last connected to.  If no previous
           connection has ever been established, then the
           first endpoint configured is used.  NETCONF
           servers SHOULD be able to remember the last
           endpoint connected to across reboots.";
      }
      enum random-selection {
        description
          "Indicates that reconnections should start with
           a random endpoint.";
      }
    }
    default first-listed;
    description
      "Specifies which of the NETCONF client's endpoints
       the NETCONF server should start with when trying
       to connect to the NETCONF client.";
  }
  leaf max-attempts {
    type uint8 {
      range "1..max";
    }
    default 3;
    description
      "Specifies the number times the NETCONF server tries
       to connect to a specific endpoint before moving on
       to the next endpoint in the list (round robin).";
  }
}
}
```

<CODE ENDS>



## **5. Design Considerations**

Editorial: this section is a hold over from before, previously called "Objectives". It was only written to support the "server" (not the "client"). The question is if it's better to add the missing "client" parts, or remove this section altogether.

The primary purpose of the YANG modules defined herein is to enable the configuration of the NETCONF client and servers. This scope includes the following objectives:

### **5.1. Support all NETCONF transports**

The YANG module should support all current NETCONF transports, namely NETCONF over SSH [[RFC6242](#)], NETCONF over TLS [[RFC7589](#)], and to be extensible to support future transports as necessary.

Because implementations may not support all transports, the modules should use YANG "feature" statements so that implementations can accurately advertise which transports are supported.

### **5.2. Enable each transport to select which keys to use**

Servers may have a multiplicity of host-keys or server-certificates from which subsets may be selected for specific uses. For instance, a NETCONF server may want to use one set of SSH host-keys when listening on port 830, and a different set of SSH host-keys when calling home. The data models provided herein should enable configuration of which keys to use on a per-use basis.

### **5.3. Support authenticating NETCONF clients certificates**

When a certificate is used to authenticate a NETCONF client, there is a need to configure the server to know how to authenticate the certificates. The server should be able to authenticate the client's certificate either by using path-validation to a configured trust anchor or by matching the client-certificate to one previously configured.

### **5.4. Support mapping authenticated NETCONF client certificates to usernames**

When a client certificate is used for TLS client authentication, the NETCONF server must be able to derive a username from the authenticated certificate. Thus the modules defined herein should enable this mapping to be configured.



### **5.5. Support both listening for connections and call home**

The NETCONF protocols were originally defined as having the server opening a port to listen for client connections. More recently the NETCONF working group defined support for call-home ([\[RFC8071\]](#)), enabling the server to initiate the connection to the client. Thus the modules defined herein should enable configuration for both listening for connections and calling home. Because implementations may not support both listening for connections and calling home, YANG "feature" statements should be used so that implementation can accurately advertise the connection types it supports.

### **5.6. For Call Home connections**

The following objectives only pertain to call home connections.

#### **5.6.1. Support more than one NETCONF client**

A NETCONF server may be managed by more than one NETCONF client. For instance, a deployment may have one client for provisioning and another for fault monitoring. Therefore, when it is desired for a server to initiate call home connections, it should be able to do so to more than one client.

#### **5.6.2. Support NETCONF clients having more than one endpoint**

A NETCONF client managing a NETCONF server may implement a high-availability strategy employing a multiplicity of active and/or passive endpoint. Therefore, when it is desired for a server to initiate call home connections, it should be able to connect to any of the client's endpoints.

#### **5.6.3. Support a reconnection strategy**

Assuming a NETCONF client has more than one endpoint, then it becomes necessary to configure how a NETCONF server should reconnect to the client should it lose its connection to one the client's endpoints. For instance, the NETCONF server may start with first endpoint defined in a user-ordered list of endpoints or with the last endpoints it was connected to.

#### **5.6.4. Support both persistent and periodic connections**

NETCONF clients may vary greatly on how frequently they need to interact with a NETCONF server, how responsive interactions need to be, and how many simultaneous connections they can support. Some clients may need a persistent connection to servers to optimize real-time interactions, while others prefer periodic interactions in order



to minimize resource requirements. Therefore, when it is necessary for server to initiate connections, it should be configurable if the connection is persistent or periodic.

#### **5.6.5. Reconnection strategy for periodic connections**

The reconnection strategy should apply to both persistent and periodic connections. How it applies to periodic connections becomes clear when considering that a periodic "connection" is a logical connection to a single server. That is, the periods of unconnectedness are intentional as opposed to due to external reasons. A periodic "connection" should always reconnect to the same server until it is no longer able to, at which time the reconnection strategy guides how to connect to another server.

#### **5.6.6. Keep-alives for persistent connections**

If a persistent connection is desired, it is the responsibility of the connection initiator to actively test the "aliveness" of the connection. The connection initiator must immediately work to reestablish a persistent connection as soon as the connection is lost. How often the connection should be tested is driven by NETCONF client requirements, and therefore keep-alive settings should be configurable on a per-client basis.

#### **5.6.7. Customizations for periodic connections**

If a periodic connection is desired, it is necessary for the NETCONF server to know how often it should connect. This frequency determines the maximum amount of time a NETCONF client may have to wait to send data to a server. A server may connect to a client before this interval expires if desired (e.g., to send data to a client).

### **6. Security Considerations**

The YANG module defined in this document uses groupings defined in [\[I-D.ietf-netconf-ssh-client-server\]](#) and [\[I-D.ietf-netconf-tls-client-server\]](#). Please see the Security Considerations section in those documents for concerns related those groupings.

The YANG module defined in this document is designed to be accessed via YANG based management protocols, such as NETCONF [\[RFC6241\]](#) and RESTCONF [\[RFC8040\]](#). Both of these protocols have mandatory-to-implement secure transport layers (e.g., SSH, TLS) with mutual authentication.



The NETCONF access control model (NACM) [[RFC8341](#)] provides the means to restrict access for particular users to a pre-configured subset of all available protocol operations and content.

There are a number of data nodes defined in this YANG module that are writable/creatable/deletable (i.e., config true, which is the default). These data nodes may be considered sensitive or vulnerable in some network environments. Write operations (e.g., edit-config) to these data nodes without proper protection can have a negative effect on network operations. These are the subtrees and data nodes and their sensitivity/vulnerability:

/: The entire data trees defined by the modules defined in this draft are sensitive to write operations. For instance, the addition or removal of references to keys, certificates, trusted anchors, etc., can dramatically alter the implemented security policy. However, no NACM annotations are applied as the data SHOULD be editable by users other than a designated 'recovery session'.

Some of the readable data nodes in this YANG module may be considered sensitive or vulnerable in some network environments. It is thus important to control read access (e.g., via get, get-config, or notification) to these data nodes. These are the subtrees and data nodes and their sensitivity/vulnerability:

NONE

Some of the RPC operations in this YANG module may be considered sensitive or vulnerable in some network environments. It is thus important to control access to these operations. These are the operations and their sensitivity/vulnerability:

NONE

## **[7.](#) IANA Considerations**

### **[7.1.](#) The IETF XML Registry**

This document registers two URIs in the "ns" subregistry of the IETF XML Registry [[RFC3688](#)]. Following the format in [[RFC3688](#)], the following registrations are requested:



URI: urn:ietf:params:xml:ns:yang:ietf-netconf-client  
Registrant Contact: The NETCONF WG of the IETF.  
XML: N/A, the requested URI is an XML namespace.

URI: urn:ietf:params:xml:ns:yang:ietf-netconf-server  
Registrant Contact: The NETCONF WG of the IETF.  
XML: N/A, the requested URI is an XML namespace.

## **7.2. The YANG Module Names Registry**

This document registers two YANG modules in the YANG Module Names registry [[RFC6020](#)]. Following the format in [[RFC6020](#)], the the following registrations are requested:

name:	ietf-netconf-client
namespace:	urn:ietf:params:xml:ns:yang:ietf-netconf-client
prefix:	ncc
reference:	RFC XXXX
name:	ietf-netconf-server
namespace:	urn:ietf:params:xml:ns:yang:ietf-netconf-server
prefix:	ncs
reference:	RFC XXXX

## **8. References**

### **8.1. Normative References**

- [I-D.ietf-netconf-keystore]  
Watsen, K., "YANG Data Model for a Centralized Keystore Mechanism", [draft-ietf-netconf-keystore-06](#) (work in progress), September 2018.
- [I-D.ietf-netconf-ssh-client-server]  
Watsen, K. and G. Wu, "YANG Groupings for SSH Clients and SSH Servers", [draft-ietf-netconf-ssh-client-server-06](#) (work in progress), June 2018.
- [I-D.ietf-netconf-tls-client-server]  
Watsen, K. and G. Wu, "YANG Groupings for TLS Clients and TLS Servers", [draft-ietf-netconf-tls-client-server-06](#) (work in progress), June 2018.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<http://www.rfc-editor.org/info/rfc2119>>.



- [RFC6020] Bjorklund, M., Ed., "YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF)", [RFC 6020](#), DOI 10.17487/RFC6020, October 2010, <<https://www.rfc-editor.org/info/rfc6020>>.
- [RFC6241] Enns, R., Ed., Bjorklund, M., Ed., Schoenwaelder, J., Ed., and A. Bierman, Ed., "Network Configuration Protocol (NETCONF)", [RFC 6241](#), DOI 10.17487/RFC6241, June 2011, <<https://www.rfc-editor.org/info/rfc6241>>.
- [RFC6242] Wasserman, M., "Using the NETCONF Protocol over Secure Shell (SSH)", [RFC 6242](#), DOI 10.17487/RFC6242, June 2011, <<https://www.rfc-editor.org/info/rfc6242>>.
- [RFC6991] Schoenwaelder, J., Ed., "Common YANG Data Types", [RFC 6991](#), DOI 10.17487/RFC6991, July 2013, <<https://www.rfc-editor.org/info/rfc6991>>.
- [RFC7407] Bjorklund, M. and J. Schoenwaelder, "A YANG Data Model for SNMP Configuration", [RFC 7407](#), DOI 10.17487/RFC7407, December 2014, <<https://www.rfc-editor.org/info/rfc7407>>.
- [RFC7589] Badra, M., Luchuk, A., and J. Schoenwaelder, "Using the NETCONF Protocol over Transport Layer Security (TLS) with Mutual X.509 Authentication", [RFC 7589](#), DOI 10.17487/RFC7589, June 2015, <<https://www.rfc-editor.org/info/rfc7589>>.
- [RFC7950] Bjorklund, M., Ed., "The YANG 1.1 Data Modeling Language", [RFC 7950](#), DOI 10.17487/RFC7950, August 2016, <<https://www.rfc-editor.org/info/rfc7950>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in [RFC 2119](#) Key Words", [BCP 14](#), [RFC 8174](#), DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.

## 8.2. Informative References

- [RFC3688] Mealling, M., "The IETF XML Registry", [BCP 81](#), [RFC 3688](#), DOI 10.17487/RFC3688, January 2004, <<https://www.rfc-editor.org/info/rfc3688>>.
- [RFC8040] Bierman, A., Bjorklund, M., and K. Watsen, "RESTCONF Protocol", [RFC 8040](#), DOI 10.17487/RFC8040, January 2017, <<https://www.rfc-editor.org/info/rfc8040>>.



- [RFC8071] Watsen, K., "NETCONF Call Home and RESTCONF Call Home", [RFC 8071](#), DOI 10.17487/RFC8071, February 2017, <<https://www.rfc-editor.org/info/rfc8071>>.
- [RFC8340] Bjorklund, M. and L. Berger, Ed., "YANG Tree Diagrams", [BCP 215](#), [RFC 8340](#), DOI 10.17487/RFC8340, March 2018, <<https://www.rfc-editor.org/info/rfc8340>>.
- [RFC8341] Bierman, A. and M. Bjorklund, "Network Configuration Access Control Model", STD 91, [RFC 8341](#), DOI 10.17487/RFC8341, March 2018, <<https://www.rfc-editor.org/info/rfc8341>>.



## [Appendix A](#). Change Log

### [A.1](#). 00 to 01

- o Renamed "keychain" to "keystore".

### [A.2](#). 01 to 02

- o Added to ietf-netconf-client ability to connected to a cluster of endpoints, including a reconnection-strategy.
- o Added to ietf-netconf-client the ability to configure connection-type and also keep-alive strategy.
- o Updated both modules to accomodate new groupings in the ssh/tls drafts.

### [A.3](#). 02 to 03

- o Refined use of tls-client-grouping to add a must statement indicating that the TLS client must specify a client-certificate.
- o Changed 'netconf-client' to be a grouping (not a container).

### [A.4](#). 03 to 04

- o Added [RFC 8174](#) to Requirements Language Section.
- o Replaced refine statement in ietf-netconf-client to add a mandatory true.
- o Added refine statement in ietf-netconf-server to add a must statement.
- o Now there are containers and groupings, for both the client and server models.

### [A.5](#). 04 to 05

- o Now tree diagrams reference ietf-netmod-yang-tree-diagrams
- o Updated examples to inline key and certificates (no longer a leafref to keystore)



**A.6. 05 to 06**

- o Fixed change log missing section issue.
- o Updated examples to match latest updates to the crypto-types, trust-anchors, and keystore drafts.
- o Reduced line length of the YANG modules to fit within 69 columns.

**A.7. 06 to 07**

- o Removed "idle-timeout" from "persistent" connection config.
- o Added "random-selection" for reconnection-strategy's "starts-with" enum.
- o Replaced "connection-type" choice default (persistent) with "mandatory true".
- o Reduced the periodic-connection's "idle-timeout" from 5 to 2 minutes.
- o Replaced reconnect-timeout with period/anchor-time combo.

**Acknowledgements**

The authors would like to thank for following for lively discussions on list and in the halls (ordered by last name): Andy Bierman, Martin Bjorklund, Benoit Claise, Mehmet Ersue, Balazs Kovacs, David Lamparter, Alan Luchuk, Ladislav Lhotka, Radek Krejci, Tom Petch, Juergen Schoenwaelder, Phil Shafer, Sean Turner, and Bert Wijnen.

**Author's Address**

Kent Watsen  
Juniper Networks

EMail: kwatsen@juniper.net

