Network Working Group	M. Wasserman
Internet-Draft	Painless Security, LLC
Obsoletes: <u>4742</u> (if approved)	T. Goddard
Intended status: Standards Track	ICEsoft Technologies, Inc.
Expires: April 23, 2011	October 20, 2010

Using the NETCONF Configuration Protocol over Secure Shell (SSH) draft-ietf-netconf-rfc4742bis-03.txt

#### Abstract

This document describes a method for invoking and running the NETCONF protocol within a Secure Shell (SSH) session as an SSH subsystem.

#### Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at http://datatracker.ietf.org/drafts/current/.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on April 23, 2011.

### Copyright Notice

Copyright (c) 2010 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (http://trustee.ietf.org/license-info) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

#### Table of Contents

- Introduction
- 2. Requirements Terminology
- 3. Starting NETCONF over SSH
  - 3.1. Capabilities Exchange
- 4. Using NETCONF over SSH
- <u>5.</u> Exiting the NETCONF Subsystem
- <u>6.</u> Security Considerations
- 7. IANA Considerations
- 8. Acknowledgements
- 9. Change Log
  - 9.1. Changes from RFC4742bis-02 to RFC4742-bis-03
  - 9.2. Changes from RFC4742bis-01 to RFC4742-bis-02
  - 9.3. Changes from RFC4742bis-00 to RFC4742-bis-01
  - 9.4. Changes from RFC4742 to RFC4742bis-00
- 10. References
  - 10.1. Normative References
  - 10.2. Informative References
- § Authors' Addresses

1. Introduction TOC

The NETCONF protocol [I-D.ietf-netconf-4741bis] (Enns, R., Bjorklund, M., Schoenwaelder, J., and A. Bierman, "Network Configuration Protocol (NETCONF)," August 2010.) is an XML-based protocol used to manage the configuration of networking equipment. NETCONF is defined to be session-layer and transport independent, allowing mappings to be defined for multiple session-layer or transport protocols. This document defines how NETCONF can be used within a Secure Shell (SSH) session, using the SSH connection protocol [RFC4254] (Ylonen, T. and C. Lonvick, "The Secure Shell (SSH) Connection Protocol," January 2006.) over the SSH transport protocol [RFC4253] (Ylonen, T. and C. Lonvick, "The Secure Shell (SSH) Transport Layer Protocol," January 2006.). This mapping will allow NETCONF to be executed from a secure shell session by a user or application.

Although this document gives specific examples of how NETCONF messages are sent over an SSH connection, use of this transport is not restricted to the messages shown in the examples below. This transport can be used for any NETCONF message.

## 2. Requirements Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC 2119 [RFC2119] (Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels," March 1997.).

### 3. Starting NETCONF over SSH

TOC

To run NETCONF over SSH, the SSH client will first establish an SSH transport connection using the SSH transport protocol, and the SSH client and SSH server will exchange keys for message integrity and encryption. The SSH client will then invoke the "ssh-userauth" service to authenticate the user, as described in the SSH authentication protocol [RFC4252] (Ylonen, T. and C. Lonvick, "The Secure Shell (SSH) Authentication Protocol," January 2006.). Once the user has been successfully authenticated, the SSH client will invoke the "ssh-connection" service, also known as the SSH connection protocol. How the NETCONF Server extracts the SSH user name from the SSH layer is implementation-dependent.

After the ssh-connection service is established, the SSH client will open a channel of type "session", which will result in an SSH session. Once the SSH session has been established, the NETCONF client will invoke NETCONF as an SSH subsystem called "netconf". Subsystem support is a feature of SSH version 2 (SSHv2) and is not included in SSHv1. Running NETCONF as an SSH subsystem avoids the need for the script to recognize shell prompts or skip over extraneous information, such as a system message that is sent at shell start-up.

In order to allow NETCONF traffic to be easily identified and filtered by firewalls and other network devices, NETCONF servers MUST default to providing access to the "netconf" SSH subsystem only when the SSH session is established using the IANA-assigned TCP port 830. Servers SHOULD be configurable to allow access to the netconf SSH subsystem over other ports.

A user (or application) could use the following command line to invoke NETCONF as an SSH subsystem on the IANA-assigned port:

[user@client]\$ ssh -s server.example.org -p 830 netconf

Note that the -s option causes the command ("netconf") to be invoked as an SSH subsystem.

## 3.1. Capabilities Exchange

The NETCONF server MUST indicate its capabilities by sending an XML document containing a <hello> element as soon as the NETCONF session is established. The NETCONF client can parse this message to determine which NETCONF capabilities are supported by the NETCONF server. The NETCONF client must also send an XML document containing a <hello> element to indicate the NETCONF client's capabilities to the NETCONF server. The document containing the <hello> element MUST be the first XML document that the NETCONF client sends after the NETCONF session is established.

The following example shows a capability exchange. Data sent by the NETCONF client are marked with "C:" and data sent by the NETCONF server are marked with "S:".

```
S: <?xml version="1.0" encoding="UTF-8"?>
S: <hello xmlns="urn:ietf:params:xml:ns:netconf:base:1.0">
S:
    <capabilities>
S:
       <capability>
S:
         urn:ietf:params:xml:ns:netconf:base:1.0
S:
       </capability>
S:
       <capability>
         urn:ietf:params:ns:netconf:capability:startup:1.0
S:
S:
       </capability>
S:
     </capabilities>
     <session-id>4<session-id>
S: </hello>
S: ]]>]]>
C: <?xml version="1.0" encoding="UTF-8"?>
C: <hello xmlns="urn:ietf:params:xml:ns:netconf:base:1.0">
C: <capabilities>
C:
       <capability>
C:
         urn:ietf:params:xml:ns:netconf:base:1.0
C:
       </capability>
     </capabilities>
C: </hello>
C: ]]>]]>
```

Although the example shows the NETCONF server sending a <hello> message followed by the NETCONF client's <hello> message, both sides will send the message as soon as the NETCONF subsystem is initialized, perhaps simultaneously.

As the previous example illustrates, a special character sequence, ]]>]]>, MUST be sent by both the NETCONF client and the NETCONF server after each XML document in the NETCONF exchange. This character sequence cannot legally appear outside of a comment in an XML document, so it can be unambigiously used to identify the end of the current

document, allowing resynchronization of the NETCONF exchange in the event of an XML syntax or parsing error.

## 4. Using NETCONF over SSH

TOC

A NETCONF over SSH session consists of a NETCONF client and NETCONF server exchanging complete XML documents. Once the session has been established and capabilities have been exchanged, the NETCONF client will send complete XML documents containing <rpc> elements to the server, and the NETCONF server will respond with complete XML documents containing <rpc-reply> elements.

To continue the example given above, a NETCONF over SSH session to retrieve a set of configuration information might look like this:

```
C: <?xml version="1.0" encoding="UTF-8"?>
C: <rpc message-id="105"
C: xmlns="urn:ietf:params:xml:ns:netconf:base:1.0">
C:
     <get-config>
       <source><running/></source>
C:
C:
       <config xmlns="http://example.com/schema/1.2/config">
C:
        <users/>
C:
       </config>
C:
    </get-config>
C: </rpc>
C: ]]>]]>
S: <?xml version="1.0" encoding="UTF-8"?>
S: <rpc-reply message-id="105"
S: xmlns="urn:ietf:params:xml:ns:netconf:base:1.0">
     <config xmlns="http://example.com/schema/1.2/config">
S:
S:
       <users>
S:
         <user><name>root</name><type>superuser</type></user>
S:
         <user><name>fred</name><type>admin</type></user>
S:
         <user><name>barney</name><type>admin</type></user>
S:
       </users>
    </config>
S: </rpc-reply>
S: ]]>]]>
```

## 5. Exiting the NETCONF Subsystem

Exiting NETCONF is accomplished using the <close-session> operation. A NETCONF server will process NETCONF messages from the NETCONF client in the order in which they are received. When the NETCONF server processes a <close-session> operation, the NETCONF server SHALL respond and close the SSH session channel. The NETCONF server MUST NOT process any NETCONF messages received after the <close-session> operation.
To continue the example used in previous sections, an existing NETCONF subsystem session could be closed as follows:

```
C: <?xml version="1.0" encoding="UTF-8"?>
C: <rpc message-id="106"
C: xmlns="urn:ietf:params:xml:ns:netconf:base:1.0">
C: <close-session/>
C: </rpc>
C: ]]>]]>
S: <?xml version="1.0" encoding="UTF-8"?>
S: <rpc-reply id="106"
S: xmlns="urn:ietf:params:xml:ns:netconf:base:1.0">
S: <ok/>
S: </rpc-reply>
S: ]]>]]>
```

# 6. Security Considerations

TOC

NETCONF is used to access configuration and state information and to modify configuration information, so the ability to access this protocol should be limited to users and systems that are authorized to view the NETCONF server's configuration and state or to modify the NETCONF server's configuration.

The identity of the SSH server MUST be verified and authenticated by the SSH client according to local policy before password-based authentication data or any configuration or state data is sent to or received from the SSH server. The identity of the SSH client MUST also be verified and authenticated by the SSH server according to local policy to ensure that the incoming SSH client request is legitimate before any configuration or state data is sent to or received from the SSH client. Neither side should establish a NETCONF over SSH connection with an unknown, unexpected or incorrect identity on the opposite side. Configuration or state data may include sensitive information, such as usernames or security keys. So, NETCONF should only be used over communications channels that provide strong encryption for data

privacy. This document defines a NETCONF over SSH mapping which provides for support of strong encryption and authentication. This document requires that SSH servers default to allowing access to the "netconf" SSH subsystem only when using a specific TCP port assigned by IANA for this purpose. This will allow NETCONF over SSH traffic to be easily identified and filtered by firewalls and other network nodes. However, it will also allow NETCONF over SSH traffic to be more easily identified by attackers.

This document also recommends that SSH servers be configurable to allow access to the "netconf" SSH subsystem over other ports. Use of that configuration option without corresponding changes to firewall or network device configuration may unintentionally result in the ability for nodes outside of the firewall or other administrative boundary to gain access to "netconf" SSH subsystem.

#### 7. IANA Considerations

TOC

Based on the previous version of this document, RFC 4742, IANA assigned port 830 as the default port for NETCONF over SSH sessions.

IANA has also assigned "netconf" as an SSH Subsystem Name, as defined in [RFC4250] (Lehtinen, S. and C. Lonvick, "The Secure Shell (SSH) Protocol Assigned Numbers," January 2006.), as follows:

Subsystem Name Reference ----netconf RFC 4742

IANA is requested to update these allocations to reference this document when it is published as an RFC.

# 8. Acknowledgements

TOC

This document was written using the xml2rfc tool described in RFC 2629 [RFC2629] (Rose, M., "Writing I-Ds and RFCs using XML," June 1999.). Extensive input was received from the other members of the NETCONF design team, including: Andy Bierman, Weijing Chen, Rob Enns, Wes Hardaker, David Harrington, Eliot Lear, Simon Leinen, Phil Shafer, Juergen Schoenwaelder and Steve Waldbusser. The following people have also reviewed this document and provided valuable input: Olafur Gudmundsson, Sam Hartman, Scott Hollenbeck, Bill Sommerfeld, Bert Wijnen, Balazs Lengyel and Martin Bjorklund.

9. Change Log TOC

[RFC Editor: Please remove this section before publication as an RFC.]

# 9.1. Changes from RFC4742bis-02 to RFC4742-bis-03

TOC

\*Added intended status and "obsoletes" to headers.

\*Very minor editorial changes.

### 9.2. Changes from RFC4742bis-01 to RFC4742-bis-02

TOC

- \*Removied unneeded wording about client/server, made unnecessary by previous changes.
- \*Stated that how a server extracts the SSH user name is implementation-dependent.
- \*Further fixes to operation/message/data wording.

# 9.3. Changes from RFC4742bis-00 to RFC4742-bis-01

TOC

- \*Changed use of client/server, manager/agent to SSH client/server and NETCONF client/server.
- \*Consistently used term operation, instead of command or message.
- \*Clarified some sections based on review feedback.
- \*Fixed several typos.

# 9.4. Changes from RFC4742 to RFC4742bis-00

TOC

\*Integrated previously-approved errata from http://rfc-editor.org/ errata\_search.php?rfc=4742 \*Removed text requiring implementations to skip to an XML start directive at the beginning of a session.

\*Made it clear the ]]>]]> is illegal in XML documents only outside of comments.

# 10. References

TOC

### 10.1. Normative References

TOC

[I-D.ietf- netconf-4741bis]	Enns, R., Bjorklund, M., Schoenwaelder, J., and A. Bierman, "Network Configuration Protocol (NETCONF)," draft-ietf-netconf-4741bis-04 (work in progress), August 2010 (TXT).
[RFC2119]	Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels," BCP 14, RFC 2119, March 1997 (TXT, HTML, XML).
[RFC4250]	Lehtinen, S. and C. Lonvick, "The Secure Shell (SSH) Protocol Assigned Numbers," RFC 4250, January 2006 (TXT).
[RFC4252]	Ylonen, T. and C. Lonvick, "The Secure Shell (SSH) Authentication Protocol," RFC 4252, January 2006 (TXT).
[RFC4253]	Ylonen, T. and C. Lonvick, "The Secure Shell (SSH) Transport Layer Protocol," RFC 4253, January 2006 (TXT).
[RFC4254]	Ylonen, T. and C. Lonvick, "The Secure Shell (SSH) Connection Protocol," RFC 4254, January 2006 (TXT).

# **10.2.** Informative References

TOC

[RFC2629] Rose, M., "Writing I-Ds and RFCs using XML," RFC 2629, June 1999 (TXT, HTML, XML).

# **Authors' Addresses**

TOC

Margaret Wasserman	
Painless Security, LLC	

	356 Abbott Street
	North Andover, MA 01845
	USA
Phone:	+1 781 405-7464
Email:	mrw@painless-security.com
URI:	http://www.painless-security.com
	Ted Goddard
	ICEsoft Technologies, Inc.
	Suite 300, 1717 10th St. NW
	Calgary, AB T2M 4S2
	Canada
Phone:	+1 403 663-3322
Email:	ted.goddard@icesoft.com
URI:	http://www.icesoft.com