

Network Working Group
Internet-Draft
Obsoletes: [rfc7895](#) (if approved)
Intended status: Standards Track
Expires: March 4, 2018

A. Bierman
YumaWorks
M. Bjorklund
Tail-f Systems
K. Watsen
Juniper Networks
August 31, 2017

YANG Library
draft-ietf-netconf-rfc7895bis-01

Abstract

This document describes a YANG library that provides information about all the YANG modules used by a network management server (e.g., a Network Configuration Protocol (NETCONF) server). Simple caching mechanisms are provided to allow clients to minimize retrieval of this information.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on March 4, 2018.

Copyright Notice

Copyright (c) 2017 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must

include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	2
1.1.	Terminology	3
1.2.	Tree Diagrams	4
1.3.	Motivation for rfc7895bis	4
1.4.	Summary of Changes from RFC 7895	5
2.	YANG Library	5
2.1.	yang-library	6
2.1.1.	yang-library/modules/module	6
2.1.2.	yang-library/module-sets/module-set	7
2.1.3.	yang-library/datastores/datastore	7
2.2.	YANG Library Module	7
3.	IANA Considerations	18
3.1.	YANG Module Registry	18
4.	Security Considerations	18
5.	Acknowledgements	19
6.	References	19
6.1.	Normative References	19
6.2.	Informative References	20
	Authors' Addresses	21

[1.](#) Introduction

There is a need for standard mechanisms to provide the operational state of the server. This includes, for instance, identifying the YANG modules and datastores that are in use by a server and how they relate to each other.

If a large number of YANG modules are utilized by the server, then the YANG library contents needed can be relatively large. This information changes very infrequently, so it is important that clients be able to cache the YANG library contents and easily identify whether their cache is out of date.

YANG library information can be different on every server and can change at runtime or across a server reboot.

If the server implements multiple protocols to access the YANG-defined data, each such protocol has its own conceptual instantiation of the YANG library.

The following information is needed by a client application (for each YANG module in the library) to fully utilize the YANG data modeling language:

- o identifier: a unique identifier for the module that includes the module's name, revision, submodules, features, and deviations.
- o name: The name of the YANG module.
- o revision: Each YANG module and submodule within the library has a revision. This is derived from the most recent revision statement within the module or submodule. If no such revision statement exists, the module's or submodule's revision is the zero-length string.
- o submodule list: The name and revision of each submodule used by the module MUST be identified.
- o feature list: The name of each YANG feature supported by the server, in a given context, MUST be identified.
- o deviation list: The name of each YANG module used for deviation statements, in a given context, MUST be identified.

The following information is needed by a client application (for each datastore supported by the server) to fully access all the YANG-modelled data available on the server:

- o identity: the YANG identity for the datastore.
- o modules: modules supported by the datastore, including any features and deviations.

1.1. Terminology

The keywords "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [BCP 14](#), [[RFC2119](#)].

The following terms are defined in [[RFC6241](#)]:

- o client
- o server

The following terms are defined in [[RFC7950](#)]:

- o module
- o submodule

The following terms are used within this document:

- o YANG library: A collection of metadata describing the server's operational state.

1.2. Tree Diagrams

A simplified graphical representation of the data model is used in this document. The meaning of the symbols in these diagrams is as follows:

- o Brackets "[" and "]" enclose list keys.
- o Abbreviations before data node names: "rw" means configuration data (read-write) and "ro" state data (read-only).
- o Symbols after data node names: "?" means an optional node, "!" means a presence container, and "*" denotes a list and leaf-list.
- o Parentheses enclose choice and case nodes, and case nodes are also marked with a colon (":").
- o Ellipsis ("...") stands for contents of subtrees that are not shown.

1.3. Motivation for rfc7895bis

RFC Ed.: delete this section, including this note, at time of publication.

All NETCONF servers supporting YANG 1.1 [[RFC7950](#)] MUST support YANG Library (see [Section 5.6.4 of RFC 7950](#)). Similarly, all RESTCONF servers MUST support YANG Library (see [Section 10 of RFC 8040](#)). These requirements are independent of if the server supports NMDA or not.

[RFC 7895](#) has a mandatory to implement 'modules-state' tree that a server uses to advertise all the modules it supports. However, this module was designed assuming the all modules would be in all datastores, and with the same number of features and deviations. However, this is not the case with NMDA-compatible servers that may have some modules that only appear in <operational> (e.g., ietf-network-topo) or only also appear in a dynamic datastore (e.g., i2rs-ephemeral-rib). It is also possible that a server only implements a

module in <running>, at it hasn't yet coded support for returning the module's opstate yet. Presumably, an NMDA-supporting server would return all modules implemented in every datastore, but this would be misleading to existing clients and unhelpful to NMDA-aware clients.

In the end, it appears that the 'modules-state' node should be for non-NMDA aware clients. For backwards compatability, an NMDA-supporting server SHOULD populate 'modules-state' in a backwards-compatible manner. The new 'yang-library' node would be ignored by legacy clients, while providing all the data needed for NMDA-aware clients, which would themselves ignore the 'modules-state' tree.

In addition to resolving the 'modules-state' node NMDA-incompatibility issue described above, the solution presented in this document is further motivated by the following desires:

- o leverage [Section 5.6.4 of RFC 7950](#) and [Section 10 of RFC 8040](#).
- o indicate which modules are supported by each datastore
- o enable the features and deviations to vary by datastore
- o structure extensible to support schema-mount
- o provide a top-level container for all server metadata

1.4. Summary of Changes from [RFC 7895](#)

This document updates [[RFC7895](#)] in the following ways:

- o Renames document title from "YANG Module Library" to "YANG Library".
- o Adds a new top-level "yang-library" container to hold many types of server metadata: modules supported, datastores supported, relationships between datastores and modules, etc.
- o Deprecates the "modules-state" tree.
- o Deprecates the "module-list" grouping.
- o Deprecates the "yang-library-change" notification.

2. YANG Library

The "ietf-yang-library" module provides information about the modules used by a server. This module is defined using YANG version 1, but

it supports the description of YANG modules written in any revision of YANG.

Following is the YANG Tree Diagram for the "ietf-yang-library" module, excluding the deprecated 'modules-state' tree:

```

module: ietf-yang-library
  +--ro yang-library
    +--ro modules
      | +--ro module* [id]
      |   +--ro id          string
      |   +--ro name        yang:yang-identifier
      |   +--ro revision     union
      |   +--ro schema?      inet:uri
      |   +--ro namespace    inet:uri
      |   +--ro feature*     yang:yang-identifier
      |   +--ro deviation* [name revision]
      |     | +--ro name      yang:yang-identifier
      |     | +--ro revision  union
      |   +--ro conformance-type enumeration
      |   +--ro submodule* [name revision]
      |     +--ro name        yang:yang-identifier
      |     +--ro revision     union
      |     +--ro schema?     inet:uri
    +--ro module-sets
      | +--ro module-set* [id]
      |   +--ro id          string
      |   +--ro module*     -> ../../../../modules/module/id
    +--ro datastores
      | +--ro datastore* [name]
      |   +--ro name          identityref
      |   +--ro module-set?
      |     -> ../../../../module-sets/module-set/id
    +--ro checksum          string

notifications:
  +---n yang-library-update

```

[2.1. yang-library](#)

This mandatory container holds all of the server's metadata.

[2.1.1. yang-library/modules/module](#)

This mandatory list contains one entry for each unique instance of a module in use by the server. Each entry is distinguished by the module's name, revisions, features, and deviations.

2.1.2. yang-library/module-sets/module-set

This mandatory list contains one entry for each module-set in use by the server (e.g., presented by a datastore).

2.1.3. yang-library/datastores/datastore

This mandatory list contains one entry for each datastore supported by the server. Each datastore entry both identifies any special properties it has and any module-sets it uses.

2.2. YANG Library Module

The "ietf-yang-library" module defines monitoring information for the YANG modules used by a server.

The modules "ietf-yang-types" and "ietf-inet-types" from [[RFC6991](#)] and the module "ietf-datastores" from [[I-D.ietf-netmod-revised-datastores](#)] are used by this module for some type definitions.

RFC Ed.: update the date below with the date of RFC publication and remove this note.

<CODE BEGINS> file "ietf-yang-library@2017-08-17.yang"

```
module ietf-yang-library {
  yang-version 1.1;
  namespace "urn:ietf:params:xml:ns:yang:ietf-yang-library";
  prefix "yanglib";

  import ietf-yang-types {
    prefix yang;
    reference "RFC 6991: Common YANG Data Types.";
  }
  import ietf-inet-types {
    prefix inet;
    reference "RFC 6991: Common YANG Data Types.";
  }
  import ietf-datastores {
    prefix ds;
    reference "I-D.ietf-revised-datastores:
              Network Management Datastore Architecture.";
  }

  organization
    "IETF NETCONF (Network Configuration) Working Group";
```


contact

"WG Web: <<http://tools.ietf.org/wg/netconf/>>
WG List: <<mailto:netconf@ietf.org>>

Author: Andy Bierman
<<mailto:andy@yumaworks.com>>

Author: Martin Bjorklund
<<mailto:mbj@tail-f.com>>

Author: Kent Watsen
<<mailto:kwatsen@juniper.net>>;

description

"This module contains information about the YANG server instance, including the modules and datastores the server supports, and which modules are present in which datastores.

Copyright (c) 2017 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Simplified BSD License set forth in [Section 4.c](#) of the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>).

This version of this YANG module is part of RFC XXXX; see the RFC itself for full legal notices.";

```
// RFC Ed.: update the date below with the date of RFC publication
// and remove this note.
// RFC Ed.: replace XXXX with actual RFC number and remove this
// note.
revision 2017-08-17 {
  description
    "Updated revision.";
  reference
    "RFC XXXX: YANG Library.";
}
revision 2016-04-09 {
  description
    "Initial revision.";
  reference
    "RFC 7895: YANG Module Library.";
}
```



```
/*
 * Typedefs
 */

typedef revision-identifier {
  type string {
    pattern '\d{4}-\d{2}-\d{2}';
  }
  description
    "Represents a specific date in YYYY-MM-DD format.";
}

/*
 * Groupings
 */

grouping module-identification-leafs {
  description
    "Parameters for identifying YANG modules and submodules.";

  leaf name {
    type yang:yang-identifier;
    mandatory true;
    description
      "The YANG module or submodule name.";
  }
  leaf revision {
    type union {
      type revision-identifier;
      type string { length 0; }
    }
    mandatory true;
    description
      "The YANG module or submodule revision date.
       A zero-length string is used if no revision statement
       is present in the YANG module or submodule.";
  }
}

grouping schema-leaf {
  description
    "Common schema leaf parameter for modules and submodules.";

  leaf schema {
    type inet:uri;
    description
      "Contains a URL that represents the YANG schema
       resource for this module or submodule."
  }
}
```



```
        This leaf will only be present if there is a URL
        available for retrieval of the schema for this entry.";
    }
}

grouping implementation-parameters {
    description
        "Parameters for describing the implementation of a module.";

    leaf-list feature {
        type yang:yang-identifier;
        description
            "List of YANG feature names from this module that are
            supported by the server, regardless whether they are defined
            in the module or any included submodule.";
    }
    list deviation {
        key "name revision";
        description
            "List of YANG deviation module names and revisions used by
            this server to modify the conformance of the module
            associated with this entry. Note that the same module can
            be used for deviations for multiple modules, so the same
            entry MAY appear within multiple 'module' entries.

            The deviation module MUST be present in the 'module' list,
            with the same name and revision values. The
            'conformance-type' value will be 'implement' for the
            deviation module.";

        uses module-identification-leafs;
    }
    leaf conformance-type {
        type enumeration {
            enum implement {
                description
                    "Indicates that the server implements one or more
                    protocol-accessible objects defined in the YANG module
                    identified in this entry. This includes deviation
                    statements defined in the module.

                    For YANG version 1.1 modules, there is at most one
                    module entry with conformance type 'implement' for a
                    particular module name, since YANG 1.1 requires that at
                    most one revision of a module is implemented.

                    For YANG version 1 modules, there SHOULD NOT be more
                    than one module entry for a particular module name.";
            }
        }
    }
}
```



```
    }
    enum import {
      description
        "Indicates that the server imports reusable definitions
        from the specified revision of the module, but does not
        implement any protocol accessible objects from this
        revision.

        Multiple module entries for the same module name MAY
        exist. This can occur if multiple modules import the
        same module, but specify different revision-dates in the
        import statements.";
    }
  }
  mandatory true;
  description
    "Indicates the type of conformance the server is claiming
    for the YANG module identified by this entry.";
}
}

grouping yang-library-parameters {
  description
    "The YANG library data structure is represented as a grouping
    so it can be reused in configuration or another monitoring
    data structure.";

  container modules {
    description
      "A container holding a list of modules. Note, modules being
      listed here does not mean that they are supported by any
      particular datastore.";

    list module {
      key "id";
      description
        "Each entry represents one revision of one module
        currently supported by the server.";

      leaf id {
        type string;
        description
          "A stable identifier, independent of any other part
          of this module instance.";
      }
    }

    uses module-identification-leafs;
    uses schema-leaf;
```



```
    leaf namespace {
      type inet:uri;
      mandatory true;
      description
        "The XML namespace identifier for this module.";
    }

    uses implementation-parameters;

    list submodule {
      key "name revision";
      description
        "Each entry represents one submodule within the
        parent module.";
      uses module-identification-leafs;
      uses schema-leaf;
    }
  }
}

container module-sets {
  description
    "A container for a list of module-sets. Module-sets being
    listed here does not mean that they are used by any
    particular datastore.";
  list module-set {
    key "id";
    description
      "An arbitrary module-set definition provided by the
      server.";

    leaf id {
      type string;
      description
        "A system-generated value that uniquely represents the
        referenced set of modules. Any change to the number
        of modules referenced, or to the modules themselves,
        generates a different value.";
    }

    leaf-list module {
      type leafref {
        path "../../modules/module/id";
      }
      description
        "A module-instance supported by the server, including its
        features and deviations.";
    }
  }
}
```



```
    }

    container datastores {
      description
        "A container for a list of datastores supported by the
        server. Each datastore indicates which module-sets it
        supports.";

      list datastore {
        key "name";

        leaf name {
          type identityref {
            base ds:datastore;
          }
          description
            "The identity of the datastore.";
        }
        leaf module-set {
          type leafref {
            path "../.../module-sets/module-set/id";
          }
          description
            "A reference to a module-set supported by this
            datastore";
        }
        description
          "A datastore supported by this server.";
      }
    }
  }
}

/*
 * Top-level container
 */

container yang-library {
  config false;
  description
    "Container providing all the YANG meta information the
    server possesses.";

  uses yang-library-parameters;

  leaf checksum {
    type string;
    config false;
    mandatory true;
  }
}
```



```
    description
      "A server-generated checksum of the contents of the
       'yang-library' tree. The server MUST change the value of
       this leaf if the information represented by the
       'yang-library' tree, except yang-library/checksum, has
       changed.";
  }
}

/*
 * Notifications
 */

notification yang-library-update {
  description
    "Generated when any YANG library information on the
     server has changed.";
}

/*
 * Legacy groupings
 */

grouping module-list {
  status deprecated;
  description
    "The module data structure is represented as a grouping
     so it can be reused in configuration or another monitoring
     data structure.";

  grouping common-leafs {
    status deprecated;
    description
      "Common parameters for YANG modules and submodules.";

    leaf name {
      type yang:yang-identifier;
      status deprecated;
      description
        "The YANG module or submodule name.";
    }
    leaf revision {
      type union {
        type revision-identifier;
        type string {
          length 0;
        }
      }
    }
  }
}
```



```
    status deprecated;
    description
      "The YANG module or submodule revision date.
      A zero-length string is used if no revision statement
      is present in the YANG module or submodule.";
  }
}

list module {
  key "name revision";
  status deprecated;
  description
    "Each entry represents one revision of one module
    currently supported by the server.";

  uses common-leafs {
    status deprecated;
  }
  uses schema-leaf {
    status deprecated;
  }

  leaf namespace {
    type inet:uri;
    mandatory true;
    status deprecated;
    description
      "The XML namespace identifier for this module.";
  }
  leaf-list feature {
    type yang:yang-identifier;
    status deprecated;
    description
      "List of YANG feature names from this module that are
      supported by the server, regardless whether they are
      defined in the module or any included submodule.";
  }
}
list deviation {
  key "name revision";
  status deprecated;
  description
    "List of YANG deviation module names and revisions
    used by this server to modify the conformance of
    the module associated with this entry. Note that
    the same module can be used for deviations for
    multiple modules, so the same entry MAY appear
    within multiple 'module' entries.
```



```

    The deviation module MUST be present in the 'module'
    list, with the same name and revision values.
    The 'conformance-type' value will be 'implement' for
    the deviation module.";
  uses common-leafs {
    status deprecated;
  }
}
leaf conformance-type {
  type enumeration {
    enum implement {
      description
        "Indicates that the server implements one or more
        protocol-accessible objects defined in the YANG module
        identified in this entry. This includes deviation
        statements defined in the module.

        For YANG version 1.1 modules, there is at most one
        module entry with conformance type 'implement' for a
        particular module name, since YANG 1.1 requires that
        at most one revision of a module is implemented.

        For YANG version 1 modules, there SHOULD NOT be more
        than one module entry for a particular module name.";
    }
    enum import {
      description
        "Indicates that the server imports reusable definitions
        from the specified revision of the module, but does
        not implement any protocol accessible objects from
        this revision.

        Multiple module entries for the same module name MAY
        exist. This can occur if multiple modules import the
        same module, but specify different revision-dates in
        the import statements.";
    }
  }
}
mandatory true;
status deprecated;
description
  "Indicates the type of conformance the server is claiming
  for the YANG module identified by this entry.";
}
list submodule {
  key "name revision";
  status deprecated;
  description
```



```
        "Each entry represents one submodule within the
        parent module.";
    uses common-leafs {
        status deprecated;
    }
    uses schema-leaf {
        status deprecated;
    }
}
}
}

/*
 * Legacy operational state data nodes
 */

container modules-state {
    config false;
    status deprecated;
    description
        "Contains YANG module monitoring information.";

    leaf module-set-id {
        type string;
        mandatory true;
        status deprecated;
        description
            "Contains a server-specific identifier representing
            the current set of modules and submodules. The
            server MUST change the value of this leaf if the
            information represented by the 'module' list instances
            has changed.";
    }

    uses module-list {
        status deprecated;
    }
}

/*
 * Legacy notifications
 */

notification yang-library-change {
    status deprecated;
    description
        "Generated when the set of modules and submodules supported
        by the server has changed.";
```



```
leaf module-set-id {  
  type leafref {  
    path "/yanglib:modules-state/yanglib:module-set-id";  
  }  
  mandatory true;  
  status deprecated;  
  description  
    "Contains the module-set-id value representing the  
    set of modules and submodules supported at the server  
    at the time the notification is generated.";  
}  
}  
  
<CODE ENDS>
```

3. IANA Considerations

3.1. YANG Module Registry

[RFC 7895](#) previously registered one URI in the IETF XML registry [[RFC3688](#)]. Following the format in [RFC 3688](#), the following registration was made:

```
URI: urn:ietf:params:xml:ns:yang:ietf-yang-library  
Registrant Contact: The NETCONF WG of the IETF.  
XML: N/A, the requested URI is an XML namespace.
```

This document takes over this registration entry made by [RFC 7895](#).

[RFC 7895](#) previously registered one YANG module in the "YANG Module Names" registry [[RFC6020](#)] as follows:

```
name:          ietf-yang-library  
namespace:     urn:ietf:params:xml:ns:yang:ietf-yang-library  
prefix:        yanglib  
reference:     RFC 7895
```

This document takes over this registration entry made by [RFC 7895](#).

4. Security Considerations

The YANG module defined in this memo is designed to be accessed via the NETCONF protocol [[RFC6241](#)]. The lowest NETCONF layer is the secure transport layer and the mandatory-to-implement secure transport is SSH [[RFC6242](#)]. The NETCONF access control model [[RFC6536](#)] provides the means to restrict access for particular

NETCONF users to a pre-configured subset of all available NETCONF protocol operations and content.

Some of the readable data nodes in this YANG module may be considered sensitive or vulnerable in some network environments. It is thus important to control read access (e.g., via get, get-config, or notification) to these data nodes. These are the subtrees and data nodes and their sensitivity/vulnerability:

- o /modules-state/module: The module list used in a server implementation may help an attacker identify the server capabilities and server implementations with known bugs. Although some of this information may be available to all users via the NETCONF <hello> message (or similar messages in other management protocols), this YANG module potentially exposes additional details that could be of some assistance to an attacker. Server vulnerabilities may be specific to particular modules, module revisions, module features, or even module deviations. This information is included in each module entry. For example, if a particular operation on a particular data node is known to cause a server to crash or significantly degrade device performance, then the module list information will help an attacker identify server implementations with such a defect, in order to launch a denial-of-service attack on the device.

5. Acknowledgements

Contributions to this material by Andy Bierman are based upon work supported by the The Space & Terrestrial Communications Directorate (S&TCD) under Contract No. W15P7T-13-C-A616. Any opinions, findings and conclusions or recommendations expressed in this material are those of the author(s) and do not necessarily reflect the views of The Space & Terrestrial Communications Directorate (S&TCD).

6. References

6.1. Normative References

- [I-D.ietf-netmod-revised-datastores]
Bjorklund, M., Schoenwaelder, J., Shafer, P., Watsen, K., and R. Wilton, "Network Management Datastore Architecture", [draft-ietf-netmod-revised-datastores-03](#) (work in progress), July 2017.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.

- [RFC3688] Mealling, M., "The IETF XML Registry", [BCP 81](#), [RFC 3688](#), DOI 10.17487/RFC3688, January 2004, <<https://www.rfc-editor.org/info/rfc3688>>.
- [RFC6020] Bjorklund, M., Ed., "YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF)", [RFC 6020](#), DOI 10.17487/RFC6020, October 2010, <<https://www.rfc-editor.org/info/rfc6020>>.
- [RFC6241] Enns, R., Ed., Bjorklund, M., Ed., Schoenwaelder, J., Ed., and A. Bierman, Ed., "Network Configuration Protocol (NETCONF)", [RFC 6241](#), DOI 10.17487/RFC6241, June 2011, <<https://www.rfc-editor.org/info/rfc6241>>.
- [RFC6242] Wasserman, M., "Using the NETCONF Protocol over Secure Shell (SSH)", [RFC 6242](#), DOI 10.17487/RFC6242, June 2011, <<https://www.rfc-editor.org/info/rfc6242>>.
- [RFC6536] Bierman, A. and M. Bjorklund, "Network Configuration Protocol (NETCONF) Access Control Model", [RFC 6536](#), DOI 10.17487/RFC6536, March 2012, <<https://www.rfc-editor.org/info/rfc6536>>.
- [RFC6991] Schoenwaelder, J., Ed., "Common YANG Data Types", [RFC 6991](#), DOI 10.17487/RFC6991, July 2013, <<https://www.rfc-editor.org/info/rfc6991>>.
- [RFC7895] Bierman, A., Bjorklund, M., and K. Watsen, "YANG Module Library", [RFC 7895](#), DOI 10.17487/RFC7895, June 2016, <<https://www.rfc-editor.org/info/rfc7895>>.
- [RFC7950] Bjorklund, M., Ed., "The YANG 1.1 Data Modeling Language", [RFC 7950](#), DOI 10.17487/RFC7950, August 2016, <<https://www.rfc-editor.org/info/rfc7950>>.
- [RFC8040] Bierman, A., Bjorklund, M., and K. Watsen, "RESTCONF Protocol", [RFC 8040](#), DOI 10.17487/RFC8040, January 2017, <<https://www.rfc-editor.org/info/rfc8040>>.

6.2. Informative References

- [RFC5277] Chisholm, S. and H. Trevino, "NETCONF Event Notifications", [RFC 5277](#), DOI 10.17487/RFC5277, July 2008, <<https://www.rfc-editor.org/info/rfc5277>>.
- [RFC6470] Bierman, A., "Network Configuration Protocol (NETCONF) Base Notifications", [RFC 6470](#), DOI 10.17487/RFC6470, February 2012, <<https://www.rfc-editor.org/info/rfc6470>>.

Authors' Addresses

Andy Bierman
YumaWorks

Email: andy@yumaworks.com

Martin Bjorklund
Tail-f Systems

Email: mbj@tail-f.com

Kent Watsen
Juniper Networks

Email: kwatsen@juniper.net

