

**Network Configuration Protocol (NETCONF) Base Notifications
draft-ietf-netconf-system-notifications-07**

Abstract

The NETCONF protocol provides mechanisms to manipulate configuration datastores. However, client applications often need to be aware of common events such as a change in NETCONF server capabilities, that may impact management applications. Standard mechanisms are needed to support the monitoring of the base system events within the NETCONF server. This document defines a YANG module that allows a NETCONF client to receive notifications for some common system events.

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on June 11, 2012.

Copyright Notice

Copyright (c) 2011 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must

include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	3
1.1.	Terminology	3
2.	YANG Module for NETCONF Base Notifications	3
2.1.	Overview	3
2.2.	Definitions	4
3.	IANA Considerations	12
4.	Security Considerations	12
5.	Acknowledgements	14
6.	Normative References	14
Appendix A.	Change Log	15
A.1.	06-07	15
A.2.	05-06	15
A.3.	04-05	15
A.4.	03-04	16
A.5.	02-03	16
A.6.	01-02	16
A.7.	00-01	17
A.8.	00	17
	Author's Address	17

1. Introduction

The NETCONF protocol [[RFC6241](#)] provides mechanisms to manipulate configuration datastores. However, client applications often need to be aware of common events such as a change in NETCONF server capabilities, that may impact management applications. Standard mechanisms are needed to support the monitoring of the base system events within the NETCONF server. This document defines a YANG module [[RFC6020](#)] that allows a NETCONF client to receive notifications for some common system events.

1.1. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

The following terms are defined in [[RFC6241](#)]:

- o client
- o datastore
- o protocol operation
- o server

The following terms are defined in [[RFC5277](#)]:

- o event
- o stream
- o subscription

The following term is defined in [[RFC6020](#)]:

- o data node

2. YANG Module for NETCONF Base Notifications

2.1. Overview

The YANG module defined within this document specifies a small number of event notification messages for use within the 'NETCONF' stream, and accessible to clients via the subscription mechanism in [[RFC5277](#)]. This module imports data types from the 'ietf-netconf' module defined in [[RFC6241](#)] and 'ietf-inet-types' module defined in [[RFC6021](#)].

These notifications pertain to configuration and monitoring portion of the managed system, not the entire system. A server MUST report events that are directly related to the NETCONF protocol. A server MAY report events for non-NETCONF management sessions, using the 'session-id' value of zero.

This module defines the following notifications for the 'NETCONF' stream to notify a client application that the NETCONF server state has changed:

netconf-config-change:

Generated when the NETCONF server detects that the <running> or <startup> configuration datastore has changed. Summarizes the edits that have been detected.

netconf-capability-change:

Generated when the NETCONF server detects that the server capabilities have changed. Indicates which capabilities have been added, deleted, and/or modified. The manner in which a server capability is changed is outside the scope of this document.

netconf-session-start:

Generated when a NETCONF server detects that a NETCONF session has started. A server MAY generate this event for non-NETCONF management sessions. For example, a CLI-based session could be detected and monitored by the server. Indicates the identity of the user that started the session.

netconf-session-end:

Generated when a NETCONF server detects that a NETCONF session has terminated. A server MAY optionally generate this event for non-NETCONF management sessions. For example, a CLI-based session could be detected and monitored by the server. Indicates the identity of the user that owned the session, and why the session was terminated.

netconf-confirmed-commit:

Generated when a NETCONF server detects that a confirmed-commit event has occurred. Indicates the event and the current state of the confirmed-commit procedure in progress.

2.2. Definitions

```
<CODE BEGINS> file="ietf-netconf-notifications@2011-12-09.yang"
```

```
module ietf-netconf-notifications {  
  
    namespace  
        "urn:ietf:params:xml:ns:yang:ietf-netconf-notifications";  
  
    prefix ncn;  
  
    import ietf-inet-types { prefix inet; }  
    import ietf-netconf { prefix nc; }  
  
    organization
```


"IETF NETCONF (Network Configuration Protocol) Working Group";

contact

"WG Web: <<http://tools.ietf.org/wg/netconf/>>

WG List: <<mailto:netconf@ietf.org>>

WG Chair: Bert Wijnen

<<mailto:bertietf@bwijnen.net>>

WG Chair: Mehmet Ersue

<<mailto:mehmet.ersue@nsn.com>>

Editor: Andy Bierman

<<mailto:andy.bierman@brocade.com>>;

description

"This module defines a YANG data model for use with the NETCONF protocol that allows the NETCONF client to receive common NETCONF base event notifications.

Copyright (c) 2011 IETF Trust and the persons identified as the document authors. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Simplified BSD License set forth in [Section 4.c](#) of the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>).

This version of this YANG module is part of RFC XXXX; see the RFC itself for full legal notices.";

// RFC Ed.: replace XXXX with actual RFC number and remove this note

// RFC Ed.: remove this note

// Note: extracted from

// [draft-ietf-netconf-system-notifications-07.txt](#)

```
revision "2011-12-09" {
  description
    "Initial version.";
  reference
    "RFC XXXX: NETCONF Base Notifications";
}
// RFC Ed.: replace XXXX with actual
// RFC number and remove this note
```



```
grouping common-session-parms {
  description
    "Common session parameters to identify a
    management session.";

  leaf username {
    type string;
    mandatory true;
    description
      "Name of the user for the session.";
  }

  leaf session-id {
    type nc:session-id-or-zero-type;
    mandatory true;
    description
      "Identifier of the session.
      A NETCONF session MUST be identified by a non-zero value.
      A non-NETCONF session MAY be identified by the value zero.";
  }

  leaf source-host {
    type inet:ip-address;
    description
      "Address of the remote host for the session.";
  }
}

grouping changed-by-parms {
  description
    "Common parameters to identify the source
    of a change event, such as a configuration
    or capability change.";

  container changed-by {
    description
      "Indicates the source of the change.
      If caused by internal action, then the
      empty leaf 'server' will be present.
      If caused by a management session, then
      the name, remote host address, and session ID
      of the session that made the change will be reported.";
    choice server-or-user {
      mandatory true;
      leaf server {
        type empty;
        description
```



```
        "If present, the change was caused
        by the server.";
    }

    case by-user {
        uses common-session-parms;
    }
} // choice server-or-user
} // container changed-by-parms
}

notification netconf-config-change {
    description
        "Generated when the NETCONF server detects that the
        <running> or <startup> configuration datastore
        has been changed by a management session.
        The notification summarizes the edits that
        have been detected.

        The server MAY choose to also generate this
        notification while loading a datastore during the
        boot process for the device.";

    uses changed-by-parms;

    leaf datastore {
        type enumeration {
            enum running {
                description "The <running> datastore has changed.";
            }
            enum startup {
                description "The <startup> datastore has changed";
            }
        }
        default "running";
        description
            "Indicates which configuration datastore has changed.";
    }

    list edit {
        description
            "An edit record SHOULD be present for each distinct
            edit operation that the server has detected on
            the target datastore. This list MAY be omitted
            if the detailed edit operations are not known.
            The server MAY report entries in this list for
            changes not made by a NETCONF session (e.g., CLI).";
```



```
leaf target {
  type instance-identifier;
  description
    "Topmost node associated with the configuration change.
    A server SHOULD set this object to the node within
    the datastore that is being altered. A server MAY
    set this object to one of the ancestors of the actual
    node that was changed, or omit this object, if the
    exact node is not known.";
}

leaf operation {
  type nc:edit-operation-type;
  description
    "Type of edit operation performed.
    A server MUST set this object to the NETCONF edit
    operation performed on the target datastore.";
}
} // list edit
} // notification netconf-config-change

notification netconf-capability-change {
  description
    "Generated when the NETCONF server detects that
    the server capabilities have changed.
    Indicates which capabilities have been added, deleted,
    and/or modified. The manner in which a server
    capability is changed is outside the scope of this
    document.";

  uses changed-by-parms;

  leaf-list added-capability {
    type inet:uri;
    description
      "List of capabilities that have just been added.";
  }

  leaf-list deleted-capability {
    type inet:uri;
    description
      "List of capabilities that have just been deleted.";
  }

  leaf-list modified-capability {
    type inet:uri;
    description
```



```
    "List of capabilities that have just been modified.
    A capability is considered to be modified if the
    base URI for the capability has not changed, but
    one or more of the parameters encoded at the end of
    the capability URI has changed.
    The new modified value of the complete URI is returned.";
  }
} // notification netconf-capability-change

notification netconf-session-start {
  description
    "Generated when a NETCONF server detects that a
    NETCONF session has started. A server MAY generate
    this event for non-NETCONF management sessions.
    Indicates the identity of the user that started
    the session.";
  uses common-session-parms;
} // notification netconf-session-start

notification netconf-session-end {
  description
    "Generated when a NETCONF server detects that a
    NETCONF session has terminated.
    A server MAY optionally generate this event for
    non-NETCONF management sessions. Indicates the
    identity of the user that owned the session,
    and why the session was terminated.";

  uses common-session-parms;

  leaf killed-by {
    when "../termination-reason = 'killed'";
    type nc:session-id-type;
    description
      "The ID of the session that directly caused this session
      to be abnormally terminated. If this session was abnormally
      terminated by a non-NETCONF session unknown to the server,
      then this leaf will not be present.";
  }

  leaf termination-reason {
    type enumeration {
      enum "closed" {
        description
          "The session was terminated by the client in normal
          fashion, e.g., by the NETCONF <close-session>
```



```
        protocol operation.";
    }
    enum "killed" {
        description
            "The session was terminated in abnormal
            fashion, e.g., by the NETCONF <kill-session>
            protocol operation.";
    }
    enum "dropped" {
        description
            "The session was terminated because the transport layer
            connection was unexpectedly closed.";
    }
    enum "timeout" {
        description
            "The session was terminated because of inactivity,
            e.g., waiting for the <hello> message or <rpc>
            messages.";
    }
    enum "bad-hello" {
        description
            "The client's <hello> message was invalid.";
    }
    enum "other" {
        description
            "The session was terminated for some other reason.";
    }
}
mandatory true;
description
    "Reason the session was terminated.";
}
} // notification netconf-session-end

notification netconf-confirmed-commit {
    description
        "Generated when a NETCONF server detects that a confirmed-commit
        event has occurred. Indicates the event and the current state
        of the confirmed-commit procedure in progress.";
    reference
        "RFC 6241, section 8.4";

    uses common-session-parms {
        when "../confirm-event != 'timeout'";
    }

    leaf confirm-event {
```



```
type enumeration {
  enum "start" {
    description
      "The confirmed-commit procedure has started.";
  }
  enum "cancel" {
    description
      "The confirmed-commit procedure has been canceled,
      e.g., due to the session being terminated, or an
      explicit <cancel-commit> operation.";
  }
  enum "timeout" {
    description
      "The confirmed-commit procedure has been canceled,
      due to the confirm-timeout interval expiring.
      The common session parameters will not be present
      in this sub-mode.";
  }
  enum "extend" {
    description
      "The confirmed-commit timeout has been extended,
      e.g., by a new <confirmed-commit> operation.";
  }
  enum "complete" {
    description
      "The confirmed-commit procedure has been completed.";
  }
}
mandatory true;
description
  "Indicates the event that caused the notification.";
}

leaf timeout {
  when
    "../confirm-event = 'start' or ../confirm-event = 'extend'";
  type uint32;
  units "seconds";
  description
    "The configured timeout value if the event type
    is 'start' or 'extend'. This value represents the
    the approximate number of seconds from the event
    time when the 'timeout' event might occur.";
}
} // notification netconf-confirmed-commit
}
```


<CODE ENDS>

3. IANA Considerations

This document registers one XML namespace URN in the 'IETF XML registry', following the format defined in [[RFC3688](#)].

URI: urn:ietf:params:xml:ns:yang:ietf-netconf-notifications

Registrant Contact: The IESG.

XML: N/A, the requested URI is an XML namespace.

This document registers one module name in the 'YANG Module Names' registry, defined in [[RFC6020](#)] .

name: ietf-netconf-notifications
prefix: ncn
namespace: urn:ietf:params:xml:ns:yang:ietf-netconf-notifications
RFC: XXXX // RFC Ed.: replace XXXX and remove this comment

4. Security Considerations

The YANG module defined in this memo is designed to be accessed via the NETCONF protocol [[RFC6241](#)]. The lowest NETCONF layer is the secure transport layer and the mandatory-to-implement secure transport is SSH, defined in [[RFC6242](#)].

Some of the readable data nodes in this YANG module may be considered sensitive or vulnerable in some network environments. It is thus important to control read access (e.g., via <get>, <get-config>, or <notification>) to these data nodes. These are the subtrees and data nodes and their sensitivity/vulnerability:

/netconf-config-change:

Event type itself indicates that the system configuration has changed. This event could alert an attacker that specific configuration data nodes have been altered.

/netconf-config-change/changed-by:

Indicates whether the server or a specific user management session made the configuration change. Identifies the user name, session-id, and source host address associated with the configuration change, if any.

/netconf-config-change/datastore:

Indicates which datastore has been changed. This data can be used to determine if the non-volatile startup configuration data has been changed.

/netconf-config-change/edit:

Identifies the specific edit operations and specific datastore subtree(s) that have changed. This data could be used to determine if specific server vulnerabilities may now be present.

/netconf-capability-change:

Event type itself indicates that the system capabilities have changed, and may now be vulnerable to unspecified attacks. An attacker will likely need to understand the content represented by specific capability URI strings. For example, knowing that a packet capture monitoring capability has been added to the system might help an attacker identify the device for possible unauthorized eavesdropping.

/netconf-capability-change/changed-by:

Indicates whether the server or a specific user management session made the capability change. Identifies the user name, session-id, and source host address associated with the capability change, if any.

/netconf-capability-change/added-capability:

Indicates the specific capability URIs that have been added. This data could be used to determine if specific server vulnerabilities may now be present.

/netconf-capability-change/deleted-capability:

Indicates the specific capability URIs that have been deleted. This data could be used to determine if specific server vulnerabilities may now be present.

/netconf-capability-change/modified-capability:

Indicates the specific capability URIs that have been modified. This data could be used to determine if specific server vulnerabilities may now be present.

/netconf-session-start:

Event type itself indicates that a NETCONF or other management session may start altering the device configuration and/or state. It may be possible for an attacker to alter the configuration, by taking advantage somehow of another session concurrently editing an unlocked datastore.

/netconf-session-start/username:

Indicates the user name associated with the session.

/netconf-session-start/source-host:

Indicates the source host address associated with the session.

/netconf-session-end:

Event type itself indicates that a NETCONF or other management session may be finished altering the device configuration. This event could alert an attacker that a datastore may have been altered.

/netconf-session-end/username:

Indicates the user name associated with the session.

/netconf-session-end/source-host:

Indicates the source host address associated with the session.

/netconf-confirmed-commit:

Event type itself indicates that the <running> datastore may have changed. This event could alert an attacker that the device behavior has changed.

/netconf-confirmed-commit/username:

Indicates the user name associated with the session.

/netconf-confirmed-commit/source-host:

Indicates the source host address associated with the session.

/netconf-confirmed-commit/confirm-event:

Indicates the specific confirmed-commit state change that occurred. A value of 'complete' probably indicates that the <running> datastore has changed.

/netconf-confirmed-commit/timeout:

Indicates the number of seconds in the future when the <running> datastore may change, due to the server reverting to an older configuration.

5. Acknowledgements

Thanks to Martin Bjorklund, Juergen Schoenwaelder, Kent Watsen, and many other members of the NETCONF WG for providing important input to this document.

6. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC3688] Mealling, M., "The IETF XML Registry", [BCP 81](#), [RFC 3688](#), January 2004.
- [RFC5277] Chisholm, S. and H. Trevino, "NETCONF Event Notifications", [RFC 5277](#), July 2008.
- [RFC6020] Bjorklund, M., "YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF)", [RFC 6020](#),

October 2010.

[RFC6021] Schoenwaelder, J., "Common YANG Data Types", [RFC 6021](#), October 2010.

[RFC6241] Enns, R., Bjorklund, M., Schoenwaelder, J., and A. Bierman, "Network Configuration Protocol (NETCONF)", [RFC 6241](#), June 2011.

[RFC6242] Wasserman, M., "Using the NETCONF Protocol over Secure Shell (SSH)", [RFC 6242](#), June 2011.

[Appendix A](#). Change Log

-- RFC Ed.: remove this section before publication.

[A.1](#). 06-07

Add clarifications resulting from IESG review.

Add text mentioning that `ietf-netconf` and `ietf-inet-types` are imported to reuse types, to resolve idnits for 'unused reference' error.

[A.2](#). 05-06

Changed YANG statements to canonical order.

Corrected `when-stmt` for `killed-by` leaf.

Corrected IANA Considerations text.

Removed redundant `value-stmts` from `confirm-event` leaf.

[A.3](#). 04-05

The module is now `ietf-netconf-notifications`. The namespace and prefix are now changed as well.

The `target-datastore` has been renamed to `datastore`.

Clarified behavior for non-NETCONF sessions.

Minor editorial comments from WG Last Call.

[A.4.](#) 03-04

Renamed module to NETCONF Base Notifications. The module is now `ietf-netconf-base-notifications`. The namespace and prefix are now changed as well.

Changed notifications so a server can report non-NETCONF initiated events.

Replaced security considerations, according to template in [RFC 6087](#).

Added Acknowledgements section.

[A.5.](#) 02-03

Renamed module back to NETCONF system notifications. The module is now `ietf-netconf-system-notifications`. The namespace and prefix are now changed as well.

Leaf `user-name` is now `username`, and is now mandatory, to be consistent with `netconf` monitoring module.

Leaf `remote-host` is now `source-host` to be consistent with `netconf` monitoring module.

The `changed-by` choice (`server-or-user`) is now mandatory.

The `netconf-config-change` description was updated and leaf `target-database` is now named `target-datastore`.

Term 'database' changed to term 'datastore' in text.

`netconf-confirmed-commit`: changed uses `common-session-parms` to use `when-stmt` not `refine-stmt`.

`netconf-capability-change`: updated description text.

[A.6.](#) 01-02

Renamed module NETCONF Events instead of NETCONF system notifications. Note that `ietf-netconf-notifications` is being reserved for the XML content defined in [RFC 5277](#).

Made changes based on mailing list comments and latest WG consensus.

Filled in IANA section.

A.7. 00-01

Removed sys-startup notification.

Make changed-by into a grouping, and added usage to sys-config-change notification.

Added target-database leaf to sys-config-change to distinguish between running and startup changes.

Removed 'bad-start' from termination-reason leaf in sys-session-end notification.

A.8. 00

Initial version, based on
[draft-bierman-netconf-system-monitoring-00.txt](#).

Author's Address

Andy Bierman
Brocade

Email: andy.bierman@brocade.com

