

Network Working Group
Internet-Draft
Intended status: Standards Track
Expires: November 21, 2011

M. Bjorklund
Tail-f Systems
May 20, 2011

A YANG Data Model for Interface Configuration
draft-ietf-netmod-interfaces-cfg-01

Abstract

This document defines a YANG data model for the configuration of network interfaces. It is expected that interface type specific configuration data models augment the generic interfaces data model defined in this document.

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on November 21, 2011.

Copyright Notice

Copyright (c) 2011 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	3
2.	Objectives	4
3.	Interfaces Data Model	5
3.1.	The interface List	5
3.2.	Interface References	6
3.3.	Interface Layering	6
4.	Interfaces YANG Module	7
5.	IANA Considerations	12
6.	Security Considerations	13
7.	Acknowledgments	14
8.	Normative References	15
Appendix A.	Example: Ethernet Interface Module	16
Appendix B.	Example: Ethernet Bonding Interface Module	18
Appendix C.	Example: VLAN Interface Module	19
Appendix D.	Example: IP Module	20
Appendix E.	Example: NETCONF <get> reply	21
Appendix F.	ChangeLog	22
F.1.	Version -01	22
	Author's Address	23

1. Introduction

This document defines a YANG [[RFC6020](#)] data model for the configuration of network interfaces. It is expected that interface type specific configuration data models augment the generic interfaces data model defined in this document.

Network interfaces are central to the configuration of many Internet protocols. Thus, it is important to establish a common data model for how interfaces are identified and configured.

The keywords "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [BCP 14](#), [[RFC2119](#)].

2. Objectives

This section describes some of the design objectives for the model presented in [Section 4](#).

- o It is recognized that existing implementations will have to map the interface data model defined in this memo to their proprietary native data model. The new data model should be simple to facilitate such mappings.
- o The data model should be suitable for new implementations to use as-is, without requiring a mapping to a different native model.
- o The data model must be extensible for different specific interface types, including vendor-specific types.
- o References to interfaces should be as simple as possible, preferably by using a single leafref.
- o The mapping to ifIndex [[RFC2863](#)] used by SNMP to identify interfaces must be clear.
- o The model must support interface layering, both simple layering where one interface is layered on top of exactly one other interface, and more complex scenarios where one interface is aggregated over N other interfaces, or when N interfaces are multiplexed over one other interface.
- o The data model should support the pre-provisioning of interface

configuration, i.e., it should be possible to configure an interface whose physical interface hardware is not present on the device. It is recommended that devices that support dynamic addition and removal of physical interfaces also support pre-provisioning.

[3.](#) Interfaces Data Model

The module "ietf-interfaces" has the following structure:

```
+--rw interfaces
  +--rw interface [name]
    +--rw name                string
    +--rw description?        string
    +--rw type                 ift:iana-if-type
    +--rw location?           string
    +--rw enabled?            boolean
    +--ro if-index*           int32
    +--rw mtu?                uint32
    +--rw link-up-down-trap-enable? enumeration
```

This module defines one YANG feature:

snmp-if-mib: Indicates that the server implements IF-MIB [[RFC2863](#)].

[3.1.](#) The interface List

The data model for interface configuration presented in this document

uses a flat list of interfaces. Each interface in the list is identified by its name. Furthermore, each interface has a mandatory "type" leaf, and a "location" leaf. The combination of "type" and "location" is unique within the interface list.

It is expected that interface type specific data models augment the interface list, and use the "type" leaf to make the augmentation conditional.

As an example of such an interface type specific augmentation, consider this YANG snippet. For a more complete example, see [Appendix A](#).

```
import interfaces {
  prefix "if";
}

augment "/if:interfaces/if:interface" {
  when "if:type = 'ethernetCsmacd'";

  container ethernet {
    leaf duplex {
      ...
    }
  }
}
```

The "location" leaf is a string. It is optional in the data model, but if the type represents a physical interface, it is mandatory. The format of this string is device- and type-dependent. The device uses the location string to identify the physical or logical entity that the configuration applies to. For example, if a device has a single array of 8 ethernet ports, the location can be one of the strings "1" to "8". As another example, if a device has N cards of M ports, the location can be on the form "n/m", such as "1/0".

How a client can learn which types and locations are present on a certain device is outside the scope of this document.

[3.2](#). Interface References

An interface is uniquely identified by its name. This property is

captured in the "interface-ref" typedef, which other YANG modules SHOULD use when they need to reference an existing interface.

[3.3.](#) Interface Layering

There is no generic mechanism for how an interface is configured to be layered on top of some other interface. It is expected that interface type specific models define their own objects for interface layering, by using "interface-ref" types to reference lower layers.

Below is an example of a model with such objects. For a more complete example, see [Appendix B](#).

```
augment "/if:interfaces/if:interface" {
  when "if:type = 'ieee8023adLag'";

  leaf-list slave-if {
    type if:interface-ref;
    must "/if:interfaces/if:interface[if:name = current()]"
      + "/if:type = 'eth:ethernet'" {
      description
        "The type of a slave interface must be ethernet";
    }
  }
  // other bonding config params, failover times etc.
}
```

[4.](#) Interfaces YANG Module

RFC Ed.: update the date below with the date of RFC publication and remove this note.

```
<CODE BEGINS> file "ietf-interfaces@2011-05-20.yang"
```

```
module ietf-interfaces {
```

```
namespace "urn:ietf:params:xml:ns:yang:ietf-interfaces";
prefix if;

import iana-if-type {
  prefix ift;
}

organization
  "IETF NETMOD (NETCONF Data Modeling Language) Working Group";

contact
  "WG Web:  <http://tools.ietf.org/wg/netmod/>
  WG List:  <mailto:netmod@ietf.org>

  WG Chair: David Kessens
             <mailto:david.kessens@nsn.com>

  WG Chair: Juergen Schoenwaelder
             <mailto:j.schoenwaelder@jacobs-university.de>

  Editor:   Martin Bjorklund
             <mailto:mbj@tail-f.com>";

description
  "This module contains a collection of YANG definitions for
  configuring network interfaces.

  Copyright (c) 2011 IETF Trust and the persons identified as
  authors of the code.  All rights reserved.

  Redistribution and use in source and binary forms, with or
  without modification, is permitted pursuant to, and subject
  to the license terms contained in, the Simplified BSD License
  set forth in Section 4.c of the IETF Trust's Legal Provisions
  Relating to IETF Documents
  (http://trustee.ietf.org/license-info).

  This version of this YANG module is part of RFC XXXX; see
  the RFC itself for full legal notices.";
```



```

// note.

// RFC Ed.: update the date below with the date of RFC publication
// and remove this note.
revision 2011-05-20 {
  description
    "Initial revision.";
  reference
    "RFC XXXX: A YANG Data Model for Interface Configuration";
}

/* Typedefs */

typedef interface-ref {
  type leafref {
    path "/if:interfaces/if:interface/if:name";
  }
  description
    "This type is used by data models that need to reference
    interfaces.";
}

/* Features */

feature snmp-if-mib {
  description
    "This feature indicates that the server implements IF-MIB.";
  reference
    "RFC 2863: The Interfaces Group MIB";
}

/* Data nodes */

container interfaces {
  description
    "Interface parameters.";

  list interface {
    key "name";
    unique "type location";

    description
      "The list of configured interfaces on the device.";

    leaf name {
      type string {
        length "1..255";
      }
    }
  }
}

```

```
}
description
  "An arbitrary name for the interface.

  A device MAY restrict the allowed values for this leaf,
  possibly depending on the type and location.

  For example, if a device has a single array of 8 ethernet
  ports, the name might be restricted to be on the form
  'ethN', where N is an integer between '1' and '8'.";
}

leaf description {
  type string;
  description
    "A textual description of the interface.

    This leaf MAY be mapped to ifAlias by an implementation.
    Such an implementation MAY restrict the length of the
    value of this leaf so that it matches the restrictions
    of ifAlias.";
  reference
    "RFC 2863: The Interfaces Group MIB - ifAlias";
}

leaf type {
  type ift:iana-if-type;
  mandatory true;
  description
    "The type of the interface.

    When an interface entry is created, a server MAY
    initialize the type leaf with a valid value, e.g., if it
    is possible to derive the type from the name of the
    interface.";
}

leaf location {
  type string;
  description
    "The device-specific location of the interface of a
    particular type. The format of the location string
    depends on the interface type and the device.

    Media-specific modules must specify if the location
    is needed for the given type.
```

For example, if a device has a single array of 8 ethernet

ports, the location can be one of '1' to '8'. As another example, if a device has N cards of M ports, the location can be on the form 'n/m'.

When an interface entry is created, a server MAY initialize the location leaf with a valid value, e.g., if it is possible to derive the location from the name of the interface.";

}

```
leaf enabled {
  type boolean;
  default "true";
  description
    "The desired state of the interface.
```

This leaf contains the configured, desired state of the interface. Systems that implement the IF-MIB use the value of this leaf to set IF-MIB.ifAdminStatus after an ifEntry has been initialized, as described in [RFC 2863](#).";

```
reference
  "RFC 2863: The Interfaces Group MIB - ifAdminStatus";
```

```
}
```

```
leaf-list if-index {
  if-feature snmp-if-mib;
  type int32 {
    range "1..2147483647";
  }
  config false;
  description
    "The list of ifIndex values for all ifEntries that are
    represented by this interface. If there is a one-to-one
    mapping between the interface and entries in the ifTable,
    this leaf-list will have a single value.
```

```
Media-specific modules must specify how the type is
mapped to entries in the ifTable.";
```

```
reference
```

```
    "RFC 2863: The Interfaces Group MIB - ifIndex";
}

leaf mtu {
    type uint32;
    description
        "The size, in octets, of the largest packet that the
        interface can send and receive. This node might not be
        valid for all interface types.
```

Bjorklund

Expires November 21, 2011

[Page 10]

Internet-Draft

YANG Interface Configuration

May 2011

```
        Media-specific modules must specify any restrictions on
        the mtu for their interface type.";
}

leaf link-up-down-trap-enable {
    if-feature snmp-if-mib;
    type enumeration {
        enum enabled {
            value 1;
        }
        enum disabled {
            value 2;
        }
    }
    description
        "Indicates whether linkUp/linkDown SNMP traps should be
        generated for this interface.

        If this node is not configured, the value 'enabled' is
        operationally used by the server for interfaces which do
        not operate on top of any other interface (as defined in
        the ifStackTable), and 'disabled' otherwise.";
    reference
        "RFC 2863: The Interfaces Group MIB -
        ifLinkUpDownTrapEnable";
}
}
}
}
```

<CODE ENDS>

5. IANA Considerations

This document registers a URI in the IETF XML registry [[RFC3688](#)]. Following the format in [RFC 3688](#), the following registration is requested to be made.

URI: urn:ietf:params:xml:ns:yang:ietf-interfaces

Registrant Contact: The NETMOD WG of the IETF.

XML: N/A, the requested URI is an XML namespace.

This document registers a YANG module in the YANG Module Names registry [[RFC6020](#)].

name: ietf-interfaces
namespace: urn:ietf:params:xml:ns:yang:ietf-interfaces
prefix: if
reference: RFC XXXX

6. Security Considerations

The YANG module and submodules defined in this memo are designed to be accessed via the NETCONF protocol [[I-D.ietf-netconf-4741bis](#)]. The lowest NETCONF layer is the secure transport layer and the mandatory-to-implement secure transport is SSH [[I-D.ietf-netconf-rfc4742bis](#)].

There are a number of data nodes defined in the YANG module and submodules which are writable/creatable/deletable (i.e., config true, which is the default). These data nodes may be considered sensitive or vulnerable in some network environments. Write operations (e.g., edit-config) to these data nodes without proper protection can have a negative effect on network operations. These are the subtrees and data nodes and their sensitivity/vulnerability:

`/interfaces/interface`: This list specify the configured interfaces on a device. Unauthorized access to this list could cause the device to ignore packets destined to it.

/interfaces/interface/enabled: This leaf controls if an interface is enabled or not. Unauthorized access to this leaf could cause the device to ignore packets destined to it.

[7.](#) Acknowledgments

The author wishes to thank Per Hedeland, Ladislav Lhotka, and Juergen Schoenwaelder for their helpful comments.

[8.](#) Normative References

[I-D.ietf-netconf-4741bis]

Enns, R., Bjorklund, M., Schoenwaelder, J., and A.

Bierman, "Network Configuration Protocol (NETCONF)",
[draft-ietf-netconf-4741bis-10](#) (work in progress),
March 2011.

[I-D.ietf-netconf-rfc4742bis]

Wasserman, M. and T. Goddard, "Using the NETCONF
Configuration Protocol over Secure Shell (SSH)",
[draft-ietf-netconf-rfc4742bis-08](#) (work in progress),
March 2011.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate
Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.

[RFC2863] McCloghrie, K. and F. Kastenholz, "The Interfaces Group
MIB", [RFC 2863](#), June 2000.

[RFC3688] Mealling, M., "The IETF XML Registry", [BCP 81](#), [RFC 3688](#),
January 2004.

[RFC6020] Bjorklund, M., "YANG - A Data Modeling Language for the
Network Configuration Protocol (NETCONF)", [RFC 6020](#),
October 2010.

[Appendix A](#). Example: Ethernet Interface Module

This section gives a simple example of how an Ethernet interface module could be defined. It demonstrates how media-specific configuration parameters can be conditionally augmented to the generic interface list. It is not intended as a complete module for ethernet configuration.

```
module ex-ethernet {
  namespace "http://example.com/ethernet";
  prefix "eth";

  import ietf-interfaces {
    prefix if;
  }

  augment "/if:interfaces/if:interface" {
    when "if:type = 'ethernetCsmacd'";

    container ethernet {
      must "../if:location" {
        description
          "An ethernet interface must specify the physical location
          of the ethernet hardware.";
      }
      choice transmission-params {
        case auto {
          leaf auto-negotiate {
            type empty;
          }
        }
        case manual {
          leaf duplex {
            type enumeration {
              enum "half";
              enum "full";
            }
          }
          leaf speed {
            type enumeration {
              enum "10Mb";
              enum "100Mb";
              enum "1Gb";
              enum "10Gb";
            }
          }
        }
      }
    }
  }
}
```

```
    // other ethernet specific params...
  }
}
}
```

[Appendix B](#). Example: Ethernet Bonding Interface Module

This section gives an example of how interface layering can be defined. An ethernet bonding interface is defined, which bonds several ethernet interfaces into one logical interface.

```
module ex-ethernet-bonding {
  namespace "http://example.com/ethernet-bonding";
  prefix "bond";

  import ietf-interfaces {
    prefix if;
  }

  augment "/if:interfaces/if:interface" {
    when "if:type = 'ieee8023adLag'";

    leaf-list slave-if {
      type if:interface-ref;
      must "/if:interfaces/if:interface[if:name = current()]"
        + "/if:type = 'ethernetCsmacd'" {
        description
          "The type of a slave interface must be ethernet.";
      }
    }
  }
  leaf bonding-mode {
    type enumeration {
      enum round-robin;
      enum active-backup;
      enum broadcast;
    }
  }
  // other bonding config params, failover times etc.
}
```

```
}  
}
```

[Appendix C](#). Example: VLAN Interface Module

This section gives an example of how a vlan interface module can be defined.

```
module ex-vlan {  
  namespace "http://example.com/vlan";  
  prefix "vlan";  
  
  import ietf-interfaces {  
    prefix if;  
  }  
  
  augment "/if:interfaces/if:interface" {  
    when "if:type = 'ethernetCsmacd' or  
         if:type = 'ieee8023adLag';  
    leaf vlan-tagging {  
      type boolean;  
      default false;  
    }  
  }  
}  
  
augment "/if:interfaces/if:interface" {  
  when "if:type = 'l2vlan';  
  
  leaf base-interface {
```

```

    type if:interface-ref;
    must "/if:interfaces/if:interface[if:name = current()]"
      + "/vlan:vlan-tagging = true" {
      description
        "The base interface must have vlan tagging enabled.";
    }
  }
leaf vlan-id {
  type uint16 {
    range "1..4094";
  }
  must "../base-interface";
}
}
}

```

[Appendix D](#). Example: IP Module

This section gives an example how an IP module can be defined.

```

module ex-ip {

  namespace "http://example.com/ip";
  prefix "ip";

  import ietf-interfaces {
    prefix if;
  }

  import ietf-inet-types {
    prefix inet;
  }

  augment "/if:interfaces/if:interface" {
    container ip {

```

```
list address {
  key "ip";
  leaf ip {
    type inet:ip-address;
  }
  leaf prefix-length {
    type uint16;
    // range depends on type of address
  }
}
}
}
}
```

[Appendix E](#). Example: NETCONF <get> reply

This section gives an example of a reply to the NETCONF <get> request for a device that implements the example data models above.

```
<rpc-reply
  xmlns="urn:ietf:params:xml:ns:netconf:base:1.0"
  message-id="101">
  <data>
    <interfaces
      xmlns="urn:ietf:params:xml:ns:yang:ietf-interfaces">
      <interface>
```

```
<name>eth0</name>
<type>ethernetCsmacd</type>
<location>0</location>
<admin-status>up</admin-status>
<if-index>2</if-index>
<ip xmlns="http://example.com/ip">
  <address>
    <ip>192.0.2.1</ip>
    <prefix-length>24</prefix-length>
  </address>
</ip>
</interface>
<interface>
  <name>eth1</name>
  <type>ethernetCsmacd</type>
  <location>1</location>
  <admin-status>up</admin-status>
  <if-index>7</if-index>
  <ip xmlns="http://example.com/ip">
    <address>
      <ip>192.168.1.1</ip>
      <prefix-length>24</prefix-length>
    </address>
  </ip>
</interface>
</interfaces>
</data>
</rpc-reply>
```

[Appendix F](#). ChangeLog

RFC Editor: remove this section upon publication as an RFC.

[F.1](#). Version -01

- o Changed leaf "if-admin-status" to leaf "enabled".
- o Added Security Considerations

Author's Address

Martin Bjorklund
Tail-f Systems

Email: mbj@tail-f.com

