

Network Working Group  
Internet-Draft  
Intended status: Standards Track  
Expires: September 29, 2014

M. Bjorklund  
Tail-f Systems  
March 28, 2014

A YANG Data Model for IP Management  
draft-ietf-netmod-ip-cfg-14

## Abstract

This document defines a YANG data model for management of IP implementations. The data model includes configuration data and state data.

## Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on September 29, 2014.

## Copyright Notice

Copyright (c) 2014 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Internet-Draft

YANG IP Management

March 2014

## Table of Contents

<a href="#">1.</a>	Introduction . . . . .	<a href="#">3</a>
<a href="#">1.1.</a>	Terminology . . . . .	<a href="#">3</a>
<a href="#">1.2.</a>	Tree Diagrams . . . . .	<a href="#">3</a>
<a href="#">2.</a>	IP Data Model . . . . .	<a href="#">5</a>
<a href="#">3.</a>	Relationship to IP-MIB . . . . .	<a href="#">7</a>
<a href="#">4.</a>	IP management YANG Module . . . . .	<a href="#">9</a>
<a href="#">5.</a>	IANA Considerations . . . . .	<a href="#">24</a>
<a href="#">6.</a>	Security Considerations . . . . .	<a href="#">25</a>
<a href="#">7.</a>	Acknowledgments . . . . .	<a href="#">27</a>
<a href="#">8.</a>	References . . . . .	<a href="#">28</a>
<a href="#">8.1.</a>	Normative References . . . . .	<a href="#">28</a>
<a href="#">8.2.</a>	Informative References . . . . .	<a href="#">28</a>
<a href="#">Appendix A.</a>	Example: NETCONF <get> reply . . . . .	<a href="#">30</a>
	Author's Address . . . . .	<a href="#">32</a>

## 1. Introduction

This document defines a YANG [[RFC6020](#)] data model for management of IP implementations.

The data model covers configuration of per-interface IPv4 and IPv6 parameters, and mappings of IP addresses to link-layer addresses. It also provides information about which IP addresses are operationally used, and which link-layer mappings exist. Per-interface parameters are added through augmentation of the interface data model defined in [[I-D.ietf-netmod-interfaces-cfg](#)].

### 1.1. Terminology

The keywords "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [BCP 14](#), [[RFC2119](#)].

The following terms are defined in [[RFC6241](#)] and are not redefined here:

- o client
- o configuration data
- o server
- o state data

The following terms are defined in [[RFC6020](#)] and are not redefined here:

- o augment
- o data model

- o data node

The terminology for describing YANG data models is found in [\[RFC6020\]](#).

## [1.2.](#) Tree Diagrams

A simplified graphical representation of the data model is used in this document. The meaning of the symbols in these diagrams is as follows:

- o Brackets "[" and "]" enclose list keys.
- o Abbreviations before data node names: "rw" means configuration data (read-write) and "ro" state data (read-only).
- o Symbols after data node names: "?" means an optional node, "!" means a presence container, and "\*" denotes a list and leaf-list.
- o Parentheses enclose choice and case nodes, and case nodes are also marked with a colon (":").
- o Ellipsis ("...") stands for contents of subtrees that are not shown.

## [2. IP Data Model](#)

This document defines the YANG module "ietf-ip", which augments the "interface" and "interface-state" lists defined in the "ietf-interfaces" module [[I-D.ietf-netmod-interfaces-cfg](#)] with IP specific data nodes, and adds IP specific state data.

The data model has the following structure for IP configuration per interface:

```
+--rw if:interfaces
  +--rw if:interface* [name]
    ...
  +--rw ipv4!
    | +--rw enabled?          boolean
    | +--rw forwarding?      boolean
    | +--rw mtu?             uint16
    | +--rw address* [ip]
    | | +--rw ip              inet:ipv4-address-no-zone
    | | +--rw (subnet)
    | |   +--:(prefix-length)
    | |   | +--rw ip:prefix-length?  uint8
```

```

| |      +---:(netmask)
| |      +---rw ip:netmask?          yang:dotted-quad
| +---rw neighbor* [ip]
|     +---rw ip                      inet:ipv4-address-no-zone
|     +---rw link-layer-address      yang:phys-address
+---rw ipv6!
    +---rw enabled?                  boolean
    +---rw forwarding?               boolean
    +---rw mtu?                      uint32
    +---rw address* [ip]
    | +---rw ip                      inet:ipv6-address-no-zone
    | +---rw prefix-length           uint8
    +---rw neighbor* [ip]
    | +---rw ip                      inet:ipv6-address-no-zone
    | +---rw link-layer-address      yang:phys-address
    +---rw dup-addr-detect-transmits? uint32
    +---rw autoconf
        +---rw create-global-addresses?    boolean
        +---rw create-temporary-addresses?  boolean
        +---rw temporary-valid-lifetime?    uint32
        +---rw temporary-preferred-lifetime? uint32

```

The data model defines two configuration containers per interface, "ipv4" and "ipv6", representing the IPv4 and IPv6 address families. In each container, there is a leaf "enabled" that controls if the address family is enabled on that interface, and a leaf "forwarding"

that controls if IP packet forwarding for the address family is enabled on the interface. In each container, there is also a list of configured addresses, and a list of configured mappings from IP addresses to link-layer addresses.

The data model has the following structure for IP state per interface:

```

+---ro if:interfaces-state
  +---ro if:interface* [name]
  ...
  +---ro ipv4!
  | +---ro forwarding?    boolean
  | +---ro mtu?          uint16
  | +---ro address* [ip]

```

```

| | +--ro ip                inet:ipv4-address-no-zone
| | +--ro (subnet)?
| | | +--:(prefix-length)
| | | | +--ro prefix-length?  uint8
| | | +--:(netmask)
| | | | +--ro netmask?        yang:dotted-quad
| | +--ro origin?           ip-address-origin
+--ro neighbor* [ip]
|   +--ro ip                inet:ipv4-address-no-zone
|   +--ro link-layer-address? yang:phys-address
|   +--ro origin?           neighbor-origin
+--ro ipv6!
|   +--ro forwarding?      boolean
|   +--ro mtu?             uint32
|   +--ro address* [ip]
|   | +--ro ip                inet:ipv6-address-no-zone
|   | +--ro prefix-length  uint8
|   | +--ro origin?        ip-address-origin
|   | +--ro status?        enumeration
+--ro neighbor* [ip]
|   +--ro ip                inet:ipv6-address-no-zone
|   +--ro link-layer-address? yang:phys-address
|   +--ro origin?           neighbor-origin
|   +--ro is-router?       empty
|   +--ro state?           enumeration

```

The data model defines two state containers per interface, "ipv4" and "ipv6", representing the IPv4 and IPv6 address families. In each container, there is a leaf "forwarding" that indicates if IP packet forwarding is enabled on that interface. In each container there is also a list of all addresses in use, and a list of known mappings from IP addresses to link-layer addresses.

### [3.](#) Relationship to IP-MIB

If the device implements IP-MIB [[RFC4293](#)], each entry in the "ipv4/address" and "ipv6/address" lists is mapped to one ipAddressEntry, where the ipAddressIfIndex refers to the "address" entry's interface.

The IP-MIB defines objects to control IPv6 Router Advertisement. The corresponding YANG data nodes are defined in

[I-D.ietf-netmod-routing-cfg].

The entries in "ipv4/neighbor" and "ipv6/neighbor" are mapped to ipNetToPhysicalTable.

The following tables list the YANG data nodes with corresponding objects in the IP-MIB.

YANG data node in /if:interfaces/if:interface	IP-MIB object
ipv4/enabled	ipv4InterfaceEnableStatus
ipv4/address	ipAddressEntry
ipv4/address/ip	ipAddressAddrType ipAddressAddr
ipv4/neighbor	ipNetToPhysicalEntry
ipv4/neighbor/ip	ipNetToPhysicalNetAddressType ipNetToPhysicalNetAddressAddr
ipv4/neighbor/link-layer-address	ipNetToPhysicalPhysAddress
ipv6/enabled	ipv6InterfaceEnableStatus
ipv6/forwarding	ipv6InterfaceForwarding
ipv6/address	ipAddressEntry
ipv6/address/ip	ipAddressAddrType ipAddressAddr
ipv6/neighbor	ipNetToPhysicalEntry
ipv6/neighbor/link-layer-address	ipNetToPhysicalPhysAddress
ipv6/neighbor/origin	ipNetToPhysicalType

YANG interface configuration data nodes and related IP-MIB objects

YANG data node in /if:interfaces-state/if:interface	IP-MIB object
ipv4	ipv4InterfaceEnableStatus
ipv4/address	ipAddressEntry
ipv4/address/ip	ipAddressAddrType
	ipAddressAddr
ipv4/address/origin	ipAddressOrigin
ipv4/neighbor	ipNetToPhysicalEntry
ipv4/neighbor/ip	ipNetToPhysicalNetAddressType
	ipNetToPhysicalNetAddressAddr
ipv4/neighbor/link-layer-address	ipNetToPhysicalPhysAddress
ipv4/neighbor/origin	ipNetToPhysicalType
ipv6	ipv6InterfaceEnableStatus
ipv6/forwarding	ipv6InterfaceForwarding
ipv6/address	ipAddressEntry
ipv6/address/ip	ipAddressAddrType
	ipAddressAddr
ipv6/address/origin	ipAddressOrigin
ipv6/address/status	ipAddressStatus
ipv6/neighbor	ipNetToPhysicalEntry
ipv6/neighbor/ip	ipNetToPhysicalNetAddressType
	ipNetToPhysicalNetAddressAddr
ipv6/neighbor/link-layer-address	ipNetToPhysicalPhysAddress
ipv6/neighbor/origin	ipNetToPhysicalType
ipv6/neighbor/state	ipNetToPhysicalState

YANG interface state data nodes and related IP-MIB objects

#### 4. IP management YANG Module

This module imports typedefs from [[RFC6991](#)] and [[I-D.ietf-netmod-interfaces-cfg](#)], and references [[RFC0791](#)], [[RFC0826](#)], [[RFC2460](#)], [[RFC4861](#)], [[RFC4862](#)], [[RFC4941](#)] and [[I-D.ietf-6man-stable-privacy-addresses](#)].

RFC Ed.: update the date below with the date of RFC publication and remove this note.

```
<CODE BEGINS> file "ietf-ip@2014-03-28.yang"
```

```
module ietf-ip {

    namespace "urn:ietf:params:xml:ns:yang:ietf-ip";
    prefix ip;

    import ietf-interfaces {
        prefix if;
    }
    import ietf-inet-types {
        prefix inet;
    }
    import ietf-yang-types {
        prefix yang;
    }

    organization
        "IETF NETMOD (NETCONF Data Modeling Language) Working Group";

    contact
        "WG Web: <http://tools.ietf.org/wg/netmod/>
        WG List: <mailto:netmod@ietf.org>

        WG Chair: Thomas Nadeau
                 <mailto:tnadeau@lucidvision.com>

        WG Chair: Juergen Schoenwaelder
                 <mailto:j.schoenwaelder@jacobs-university.de>

        Editor: Martin Bjorklund
               <mailto:mbj@tail-f.com>";

    description
        "This module contains a collection of YANG definitions for
        configuring IP implementations."
```

authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Simplified BSD License set forth in [Section 4.c](#) of the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>).

This version of this YANG module is part of RFC XXXX; see the RFC itself for full legal notices.";

```
// RFC Ed.: replace XXXX with actual RFC number and remove this
// note.

// RFC Ed.: update the date below with the date of RFC publication
// and remove this note.
revision 2014-03-28 {
  description
    "Initial revision.";
  reference
    "RFC XXXX: A YANG Data Model for IP Management";
}

/*
 * Features
 */

feature ipv4-non-contiguous-netmasks {
  description
    "Indicates support for configuring non-contiguous
    subnet masks.";
}

feature ipv6-privacy-autoconf {
  description
    "Indicates support for Privacy Extensions for Stateless Address
    Autoconfiguration in IPv6.";
  reference
```

```
    "RFC 4941: Privacy Extensions for Stateless Address
        Autoconfiguration in IPv6";
}

/*
 * Typedefs
 */

typedef ip-address-origin {
```

```
type enumeration {
  enum other {
    description
      "None of the following.";
  }
  enum static {
    description
      "Indicates that the address has been statically
      configured, for example using NETCONF or a Command Line
      Interface.";
  }
  enum dhcp {
    description
      "Indicates an address that has been assigned to this
      system by a DHCP server.";
  }
  enum link-layer {
    description
      "Indicates an address created by IPv6 stateless
      auto-configuration that embeds a link-layer address in its
      interface identifier.";
  }
  enum random {
    description
      "Indicates an address chosen by the system at
      random, e.g., an IPv4 address within 169.254/16, an
      RFC 4941 temporary address, or a semantically opaque
      address [I-D.ietf-6man-stable-privacy-addresses]";
  }
}
description
  "The origin of an address.";
```

```

}

typedef neighbor-origin {
  type enumeration {
    enum other {
      description
        "None of the following.";
    }
    enum static {
      description
        "Indicates that the mapping has been statically
        configured, for example using NETCONF or a Command Line
        Interface.";
    }
    enum dynamic {
      description

```

```

        "Indicates that the mapping has been dynamically resolved
        using e.g., IPv4 ARP or the IPv6 Neighbor Discovery
        protocol.";
    }
}
description
  "The origin of a neighbor entry.";
}

/*
 * Configuration datanodes
 */

augment "/if:interfaces/if:interface" {
  description
    "Parameters for configuring IP on interfaces.

    If an interface is not capable of running IP, the server
    must not allow the client to configure these parameters.";

  container ipv4 {
    presence
      "Enables IPv4 unless the 'enabled' leaf
      (which defaults to 'true') is set to 'false'";
    description

```

```

    "Parameters for the IPv4 address family.";

leaf enabled {
    type boolean;
    default true;
    description
        "Controls if IPv4 is enabled or disabled on this
        interface.  When IPv4 is enabled, this interface is
        connected to an IPv4 stack, and the interface can send
        and receive IPv4 packets.";
}
leaf forwarding {
    type boolean;
    default false;
    description
        "Controls IPv4 packet forwarding of datagrams received by,
        but not addressed to, this interface.  IPv4 routers
        forward datagrams.  IPv4 hosts do not (except those
        source-routed via the host)";
}
leaf mtu {
    type uint16 {
        range "68..max";

```

```

}
units octets;
description
    "The size, in octets, of the largest IPv4 packet that the
    interface will send and receive.

    The server may restrict the allowed values for this leaf
    depending on the interface's type.

    If this leaf is not configured, the operationally used mtu
    depends on the interface's type.";
reference
    "RFC 791: Internet Protocol";
}
list address {
    key "ip";
    description
        "The list of configured IPv4 addresses on the interface.";

```

```

leaf ip {
  type inet:ipv4-address-no-zone;
  description
    "The IPv4 address on the interface.";
}
choice subnet {
  mandatory true;
  description
    "The subnet can be specified as a prefix-length, or,
    if the server supports non-contiguous netmasks, as
    a netmask.";
  leaf prefix-length {
    type uint8 {
      range "0..32";
    }
    description
      "The length of the subnet prefix.";
  }
  leaf netmask {
    if-feature ipv4-non-contiguous-netmasks;
    type yang:dotted-quad;
    description
      "The subnet specified as a netmask.";
  }
}
}
list neighbor {
  key "ip";
  description

```

"A list of mappings from IPv4 addresses to link-layer addresses.

Entries in this list are used as static entries in the ARP cache.";

reference

"[RFC 826](#): An Ethernet Address Resolution Protocol";

```

leaf ip {
  type inet:ipv4-address-no-zone;
  description

```

```

        "The IPv4 address of the neighbor node.";
    }
    leaf link-layer-address {
        type yang:phys-address;
        mandatory true;
        description
            "The link-layer address of the neighbor node.";
    }
}
container ipv6 {
    presence
        "Enables IPv6 unless the 'enabled' leaf
        (which defaults to 'true') is set to 'false'";
    description
        "Parameters for the IPv6 address family.";

    leaf enabled {
        type boolean;
        default true;
        description
            "Controls if IPv6 is enabled or disabled on this
            interface.  When IPv6 is enabled, this interface is
            connected to an IPv6 stack, and the interface can send
            and receive IPv6 packets.";
    }
    leaf forwarding {
        type boolean;
        default false;
        description
            "Controls IPv6 packet forwarding of datagrams received by,
            but not addressed to, this interface.  IPv6 routers
            forward datagrams.  IPv6 hosts do not (except those
            source-routed via the host)";
        reference
            "RFC 4861: Neighbor Discovery for IP version 6 (IPv6)";
    }
}

```

```

        Section 6.2.1, IsRouter";
    }
    leaf mtu {
        type uint32 {

```

```

    range "1280..max";
  }
  units octets;
  description
    "The size, in octets, of the largest IPv6 packet that the
    interface will send and receive.

    The server may restrict the allowed values for this leaf
    depending on the interface's type.

    If this leaf is not configured, the operationally used mtu
    depends on the interface's type.";
  reference
    "RFC 2460: IPv6 Specification
    Section 5";
}
list address {
  key "ip";
  description
    "The list of configured IPv6 addresses on the interface.";

  leaf ip {
    type inet:ipv6-address-no-zone;
    description
      "The IPv6 address on the interface.";
  }
  leaf prefix-length {
    type uint8 {
      range "0..128";
    }
    mandatory true;
    description
      "The length of the subnet prefix.";
  }
}
list neighbor {
  key "ip";
  description
    "A list of mappings from IPv6 addresses to
    link-layer addresses.

    Entries in this list are used as static entries in the
    Neighbor Cache.";
  reference

```

```
    "RFC 4861: Neighbor Discovery for IP version 6 (IPv6)";

  leaf ip {
    type inet:ipv6-address-no-zone;
    description
      "The IPv6 address of the neighbor node.";
  }
  leaf link-layer-address {
    type yang:phys-address;
    mandatory true;
    description
      "The link-layer address of the neighbor node.";
  }
}
leaf dup-addr-detect-transmits {
  type uint32;
  default 1;
  description
    "The number of consecutive Neighbor Solicitation messages
     sent while performing Duplicate Address Detection on a
     tentative address. A value of zero indicates that
     Duplicate Address Detection is not performed on
     tentative addresses. A value of one indicates a single
     transmission with no follow-up retransmissions.";
  reference
    "RFC 4862: IPv6 Stateless Address Autoconfiguration";
}
container autoconf {
  description
    "Parameters to control the autoconfiguration of IPv6
     addresses, as described in RFC 4862.";
  reference
    "RFC 4862: IPv6 Stateless Address Autoconfiguration";

  leaf create-global-addresses {
    type boolean;
    default true;
    description
      "If enabled, the host creates global addresses as
       described in section 5.5 of RFC 4862.";
    reference
      "RFC 4862: IPv6 Stateless Address Autoconfiguration";
  }
  leaf create-temporary-addresses {
    if-feature ipv6-privacy-autoconf;
    type boolean;
    default false;
  }
}
```

description

```
        "If enabled, the host creates temporary addresses as
        described in RFC 4941.";
    reference
        "RFC 4941: Privacy Extensions for Stateless Address
        Autoconfiguration in IPv6";
    }
    leaf temporary-valid-lifetime {
        if-feature ipv6-privacy-autoconf;
        type uint32;
        units "seconds";
        default 604800;
        description
            "The time period during which the temporary address
            is valid.";
        reference
            "RFC 4941: Privacy Extensions for Stateless Address
            Autoconfiguration in IPv6
            - TEMP_VALID_LIFETIME";
    }
    leaf temporary-preferred-lifetime {
        if-feature ipv6-privacy-autoconf;
        type uint32;
        units "seconds";
        default 86400;
        description
            "The time period during which the temporary address is
            preferred.";
        reference
            "RFC 4941: Privacy Extensions for Stateless Address
            Autoconfiguration in IPv6
            - TEMP_PREFERRED_LIFETIME";
    }
    }
}

/*
 * Operational state data nodes
 */
```

```
augment "/if:interfaces-state/if:interface" {
  description
    "Data nodes for the operational state of IP on interfaces.";

  container ipv4 {
    presence "Present if IPv4 is enabled on this interface";
    config false;
    description
```

Bjorklund

Expires September 29, 2014

[Page 17]

---

Internet-Draft

YANG IP Management

March 2014

```
    "Interface specific parameters for the IPv4 address family.";

  leaf forwarding {
    type boolean;
    description
      "Indicates if IPv4 packet forwarding is enabled or disabled
      on this interface.";
  }
  leaf mtu {
    type uint16 {
      range "68..max";
    }
    units octets;
    description
      "The size, in octets, of the largest IPv4 packet that the
      interface will send and receive.";
    reference
      "RFC 791: Internet Protocol";
  }
  list address {
    key "ip";
    description
      "The list of IPv4 addresses on the interface.";

    leaf ip {
      type inet:ipv4-address-no-zone;
      description
        "The IPv4 address on the interface.";
    }
    choice subnet {
      description
        "The subnet can be specified as a prefix-length, or,
        if the server supports non-contiguous netmasks, as
```

```

        a netmask.";
leaf prefix-length {
  type uint8 {
    range "0..32";
  }
  description
    "The length of the subnet prefix.";
}
leaf netmask {
  if-feature ipv4-non-contiguous-netmasks;
  type yang:dotted-quad;
  description
    "The subnet specified as a netmask.";
}
}

```

```

leaf origin {
  type ip-address-origin;
  description
    "The origin of this address.";
}
}
list neighbor {
  key "ip";
  description
    "A list of mappings from IPv4 addresses to
    link-layer addresses.

    This list represents the ARP Cache.";
  reference
    "RFC 826: An Ethernet Address Resolution Protocol";
leaf ip {
  type inet:ipv4-address-no-zone;
  description
    "The IPv4 address of the neighbor node.";
}
leaf link-layer-address {
  type yang:phys-address;
  description
    "The link-layer address of the neighbor node.";
}
}

```

```

    leaf origin {
      type neighbor-origin;
      description
        "The origin of this neighbor entry.";
    }
  }
}

container ipv6 {
  presence "Present if IPv6 is enabled on this interface";
  config false;
  description
    "Parameters for the IPv6 address family.";

  leaf forwarding {
    type boolean;
    default false;
    description
      "Indicates if IPv6 packet forwarding is enabled or disabled
      on this interface.";
    reference

```

```

    "RFC 4861: Neighbor Discovery for IP version 6 (IPv6)
    Section 6.2.1, IsRouter";
  }
  leaf mtu {
    type uint32 {
      range "1280..max";
    }
    units octets;
    description
      "The size, in octets, of the largest IPv6 packet that the
      interface will send and receive.";
    reference
      "RFC 2460: IPv6 Specification
      Section 5";
  }
  list address {
    key "ip";
    description
      "The list of IPv6 addresses on the interface.";

```

```

leaf ip {
  type inet:ipv6-address-no-zone;
  description
    "The IPv6 address on the interface.";
}
leaf prefix-length {
  type uint8 {
    range "0..128";
  }
  mandatory true;
  description
    "The length of the subnet prefix.";
}
leaf origin {
  type ip-address-origin;
  description
    "The origin of this address.";
}
leaf status {
  type enumeration {
    enum preferred {
      description
        "This is a valid address that can appear as the
        destination or source address of a packet.";
    }
    enum deprecated {
      description
        "This is a valid but deprecated address that should

```

```

    no longer be used as a source address in new
    communications, but packets addressed to such an
    address are processed as expected.";
}
enum invalid {
  description
    "This isn't a valid address and it shouldn't appear
    as the destination or source address of a packet.";
}
enum inaccessible {
  description
    "The address is not accessible because the interface

```

```

        to which this address is assigned is not
        operational.";
    }
    enum unknown {
        description
            "The status cannot be determined for some reason.";
    }
    enum tentative {
        description
            "The uniqueness of the address on the link is being
            verified.  Addresses in this state should not be
            used for general communication and should only be
            used to determine the uniqueness of the address.";
    }
    enum duplicate {
        description
            "The address has been determined to be non-unique on
            the link and so must not be used.";
    }
    enum optimistic {
        description
            "The address is available for use, subject to
            restrictions, while its uniqueness on a link is
            being verified.";
    }
}
description
    "The status of an address.  Most of the states correspond
    to states from the IPv6 Stateless Address
    Autoconfiguration protocol.";
reference
    "RFC 4293: Management Information Base for the
    Internet Protocol (IP)
    - IpAddressStatusTC
    RFC 4862: IPv6 Stateless Address Autoconfiguration";
}

```

```

}
list neighbor {
    key "ip";
    description
        "A list of mappings from IPv6 addresses to

```

link-layer addresses.

This list represents the Neighbor Cache.";  
reference

"[RFC 4861](#): Neighbor Discovery for IP version 6 (IPv6)";

```
leaf ip {
  type inet:ipv6-address-no-zone;
  description
    "The IPv6 address of the neighbor node.";
}
leaf link-layer-address {
  type yang:phys-address;
  description
    "The link-layer address of the neighbor node.";
}
leaf origin {
  type neighbor-origin;
  description
    "The origin of this neighbor entry.";
}
leaf is-router {
  type empty;
  description
    "Indicates that the neighbor node acts as a router.";
}
leaf state {
  type enumeration {
    enum incomplete {
      description
        "Address resolution is in progress and the link-layer
        address of the neighbor has not yet been
        determined.";
    }
    enum reachable {
      description
        "Roughly speaking, the neighbor is known to have been
        reachable recently (within tens of seconds ago).";
    }
    enum stale {
      description
        "The neighbor is no longer known to be reachable but
        until traffic is sent to the neighbor, no attempt
```

```

        should be made to verify its reachability.";
    }
    enum delay {
        description
            "The neighbor is no longer known to be reachable, and
            traffic has recently been sent to the neighbor.
            Rather than probe the neighbor immediately, however,
            delay sending probes for a short while in order to
            give upper-layer protocols a chance to provide
            reachability confirmation.";
    }
    enum probe {
        description
            "The neighbor is no longer known to be reachable, and
            unicast Neighbor Solicitation probes are being sent
            to verify reachability.";
    }
    }
    description
        "The Neighbor Unreachability Detection state of this
        entry.";
    reference
        "RFC 4861: Neighbor Discovery for IP version 6 (IPv6)
        Section 7.3.2";
    }
    }
    }
    }
}

```

<CODE ENDS>

---

Internet-Draft

YANG IP Management

March 2014

## 5. IANA Considerations

This document registers a URI in the IETF XML registry [[RFC3688](#)]. Following the format in [RFC 3688](#), the following registration is requested to be made.

URI: urn:ietf:params:xml:ns:yang:ietf-ip

Registrant Contact: The NETMOD WG of the IETF.

XML: N/A, the requested URI is an XML namespace.

This document registers a YANG module in the YANG Module Names registry [[RFC6020](#)].

name: ietf-ip  
namespace: urn:ietf:params:xml:ns:yang:ietf-ip  
prefix: ip  
reference: RFC XXXX

## 6. Security Considerations

The YANG module defined in this memo is designed to be accessed via the NETCONF protocol [[RFC6241](#)]. The lowest NETCONF layer is the secure transport layer and the mandatory-to-implement secure transport is SSH [[RFC6242](#)]. The NETCONF access control model [[RFC6536](#)] provides the means to restrict access for particular NETCONF users to a pre-configured subset of all available NETCONF protocol operations and content.

There are a number of data nodes defined in the YANG module which are writable/creatable/deletable (i.e., config true, which is the default). These data nodes may be considered sensitive or vulnerable in some network environments. Write operations (e.g., edit-config) to these data nodes without proper protection can have a negative effect on network operations. These are the subtrees and data nodes and their sensitivity/vulnerability:

`ipv4/enabled` and `ipv6/enabled`: These leafs are used to enable or disable IPv4 and IPv6 on a specific interface. By enabling a protocol on an interface, an attacker might be able to create an unsecured path into a node (or through it if routing is also enabled). By disabling a protocol on an interface, an attacker might be able to force packets to be routed through some other interface or deny access to some or all of the network via that protocol.

`ipv4/address` and `ipv6/address`: These lists specify the configured IP addresses on an interface. By modifying this information, an attacker can cause a node to either ignore messages destined to it or accept (at least at the IP layer) messages it would otherwise ignore. The use of filtering or security associations may reduce the potential damage in the latter case.

`ipv4/forwarding` and `ipv6/forwarding`: These leafs allow a client to

enable or disable the forwarding functions on the entity. By disabling the forwarding functions, an attacker would possibly be able to deny service to users. By enabling the forwarding functions, an attacker could open a conduit into an area. This might result in the area providing transit for packets it shouldn't or might allow the attacker access to the area bypassing security safeguards.

ipv6/autoconf: The leafs in this branch control the autoconfiguration of IPv6 addresses and in particular whether temporary addresses are used or not. By modifying the corresponding leafs, an attacker might impact the addresses used by a node and thus indirectly the privacy of the users using the

node.

ipv4/mtu and ipv6/mtu: Setting these leafs to very small values can be used to slow down interfaces.

## [7.](#) Acknowledgments

The author wishes to thank Jeffrey Lange, Ladislav Lhotka, Juergen Schoenwaelder, and Dave Thaler for their helpful comments.

## [8.](#) References

### [8.1.](#) Normative References

[I-D.ietf-netmod-interfaces-cfg]

Bjorklund, M., "A YANG Data Model for Interface Configuration", [draft-ietf-netmod-interfaces-cfg-12](#) (work in progress), July 2012.

[RFC0791] Postel, J., "Internet Protocol", STD 5, [RFC 791](#), September 1981.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.

- [RFC2460] Deering, S. and R. Hinden, "Internet Protocol, Version 6 (IPv6) Specification", [RFC 2460](#), December 1998.
- [RFC3688] Mealling, M., "The IETF XML Registry", [BCP 81](#), [RFC 3688](#), January 2004.
- [RFC4861] Narten, T., Nordmark, E., Simpson, W., and H. Soliman, "Neighbor Discovery for IP version 6 (IPv6)", [RFC 4861](#), September 2007.
- [RFC4862] Thomson, S., Narten, T., and T. Jinmei, "IPv6 Stateless Address Autoconfiguration", [RFC 4862](#), September 2007.
- [RFC4941] Narten, T., Draves, R., and S. Krishnan, "Privacy Extensions for Stateless Address Autoconfiguration in IPv6", [RFC 4941](#), September 2007.
- [RFC6020] Bjorklund, M., "YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF)", [RFC 6020](#), October 2010.
- [RFC6241] Enns, R., Bjorklund, M., Schoenwaelder, J., and A. Bierman, "Network Configuration Protocol (NETCONF)", [RFC 6241](#), June 2011.
- [RFC6991] Schoenwaelder, J., "Common YANG Data Types", [RFC 6991](#), July 2013.

## [8.2](#). Informative References

- [I-D.ietf-6man-stable-privacy-addresses]  
Gont, F., "A Method for Generating Semantically Opaque Interface Identifiers with IPv6 Stateless Address

Bjorklund Expires September 29, 2014 [Page 28]

---

Internet-Draft YANG IP Management March 2014

Autoconfiguration (SLAAC)",  
[draft-ietf-6man-stable-privacy-addresses-17](#) (work in progress), January 2014.

- [I-D.ietf-netmod-routing-cfg]  
Lhotka, L., "A YANG Data Model for Routing Configuration",  
[draft-ietf-netmod-routing-cfg-10](#) (work in progress),

July 2012.

- [RFC0826] Plummer, D., "Ethernet Address Resolution Protocol: Or converting network protocol addresses to 48.bit Ethernet address for transmission on Ethernet hardware", STD 37, [RFC 826](#), November 1982.
  
- [RFC4293] Routhier, S., "Management Information Base for the Internet Protocol (IP)", [RFC 4293](#), April 2006.
  
- [RFC6242] Wasserman, M., "Using the NETCONF Protocol over Secure Shell (SSH)", [RFC 6242](#), June 2011.
  
- [RFC6536] Bierman, A. and M. Bjorklund, "Network Configuration Protocol (NETCONF) Access Control Model", [RFC 6536](#), March 2012.

## [Appendix A](#). Example: NETCONF <get> reply

This section gives an example of a reply to the NETCONF <get> request for a device that implements the data model defined in this document.

```
<rpc-reply
  xmlns="urn:ietf:params:xml:ns:netconf:base:1.0"
  message-id="101">
  <data>
    <interfaces
      xmlns="urn:ietf:params:xml:ns:yang:ietf-interfaces"
      xmlns:ianaift="urn:ietf:params:xml:ns:yang:iana-if-type">
      <interface>
        <name>eth0</name>
        <type>ianaift:ethernetCsmacd</type>
        <ipv4 xmlns="urn:ietf:params:xml:ns:yang:ietf-ip">
          <address>
            <ip>192.0.2.1</ip>
            <prefix-length>24</prefix-length>
          </address>
        </ipv4>
        <ipv6 xmlns="urn:ietf:params:xml:ns:yang:ietf-ip">
          <mtu>1280</mtu>
          <address>
            <ip>2001:db8::10</ip>
            <prefix-length>32</prefix-length>
          </address>
          <dup-addr-detect-transmits>0</dup-addr-detect-transmits>
        </ipv6>
      </interface>
    </interfaces>

    <interfaces-state
      xmlns="urn:ietf:params:xml:ns:yang:ietf-interfaces"
      xmlns:ianaift="urn:ietf:params:xml:ns:yang:iana-if-type">
      <interface>
        <name>eth0</name>
        <type>ianaift:ethernetCsmacd</type>
        <!-- other parameters from ietf-interfaces omitted -->

        <ipv4 xmlns="urn:ietf:params:xml:ns:yang:ietf-ip">
          <forwarding>false</forwarding>
          <mtu>1500</mtu>
          <address>
            <ip>192.0.2.1</ip>
            <prefix-length>24</prefix-length>
            <origin>static</origin>
          </address>
```

```
    <neighbor>
      <ip>192.0.2.2</ip>
      <link-layer-address>00:01:02:03:04:05</link-layer-address>
    </neighbor>
  </ipv4>
  <ipv6 xmlns="urn:ietf:params:xml:ns:yang:ietf-ip">
    <forwarding>false</forwarding>
    <mtu>1500</mtu>
    <address>
      <ip>2001:db8::10</ip>
      <prefix-length>32</prefix-length>
      <origin>static</origin>
      <status>preferred</status>
    </address>
    <address>
      <ip>2001:db8::1:100</ip>
      <prefix-length>32</prefix-length>
      <origin>dhcp</origin>
      <status>preferred</status>
    </address>
    <neighbor>
      <ip>2001:db8::1</ip>
      <link-layer-address>00:01:02:03:04:05</link-layer-address>
      <origin>dynamic</origin>
      <is-router/>
      <state>reachable</state>
    </neighbor>
    <neighbor>
      <ip>2001:db8::4</ip>
      <origin>dynamic</origin>
      <state>incomplete</state>
    </neighbor>
  </ipv6>
</interface>
</interfaces-state>
</data>
</rpc-reply>
```

Bjorklund

Expires September 29, 2014

[Page 31]

---

Internet-Draft

YANG IP Management

March 2014

Author's Address

Martin Bjorklund  
Tail-f Systems

Email: [mbj@tail-f.com](mailto:mbj@tail-f.com)

Bjorklund

Expires September 29, 2014

[Page 32]