

Guidelines for Authors and Reviewers of YANG Data Model Documents
draft-ietf-netmod-rfc6087bis-02

Abstract

This memo provides guidelines for authors and reviewers of Standards Track specifications containing YANG data model modules. Applicable portions may be used as a basis for reviews of other YANG data model documents. Recommendations and procedures are defined, which are intended to increase interoperability and usability of Network Configuration Protocol (NETCONF) implementations that utilize YANG data model modules.

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on October 26, 2015.

Copyright Notice

Copyright (c) 2015 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in [Section 4](#).e of

the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	4
2.	Terminology	5
2.1.	Requirements Notation	5
2.2.	NETCONF Terms	5
2.3.	YANG Terms	5
2.4.	Terms	6
3.	YANG Tree Diagrams	7
4.	General Documentation Guidelines	8
4.1.	Module Copyright	8
4.2.	Terminology Section	9
4.3.	Tree Diagrams	9
4.4.	Narrative Sections	9
4.5.	Definitions Section	10
4.6.	Security Considerations Section	10
4.7.	IANA Considerations Section	11
4.7.1.	Documents that Create a New Namespace	11
4.7.2.	Documents that Extend an Existing Namespace	11
4.8.	Reference Sections	11
4.9.	Validation Tools	12
5.	YANG Usage Guidelines	13
5.1.	Module Naming Conventions	13
5.2.	Identifiers	13
5.3.	Defaults	13
5.4.	Conditional Statements	14
5.5.	XPath Usage	15
5.5.1.	Function Library	15
5.5.2.	Axes	15
5.5.3.	Types	16
5.5.4.	Wildcards	17
5.6.	Lifecycle Management	17
5.7.	Module Header, Meta, and Revision Statements	18
5.8.	Namespace Assignments	19
5.9.	Top-Level Data Definitions	20
5.10.	Data Types	20
5.11.	Reusable Type Definitions	21
5.12.	Data Definitions	21
5.13.	Operation Definitions	23
5.14.	Notification Definitions	23
5.15.	Feature Definitions	24
5.16.	Data Correlation	24
6.	IANA Considerations	26
7.	Security Considerations	27

7.1.	Security Considerations Section Template	27
8.	Acknowledgments	29
9.	Changes Since RFC 6087	30
10.	References	31
10.1.	Normative References	31
10.2.	Informative References	31
Appendix A.	Change Log	33
A.1.	00 to 01	33
Appendix B.	Module Review Checklist	34
Appendix C.	YANG Module Template	36
	Author's Address	38

1. Introduction

The standardization of network configuration interfaces for use with the Network Configuration Protocol [[RFC6241](#)] requires a modular set of data models, which can be reused and extended over time.

This document defines a set of usage guidelines for Standards Track documents containing [[RFC6020](#)] data models. YANG is used to define the data structures, protocol operations, and notification content used within a NETCONF server. A server that supports a particular YANG module will support client NETCONF operation requests, as indicated by the specific content defined in the YANG module.

This document is similar to the Structure of Management Information version 2 (SMIV2) usage guidelines specification [[RFC4181](#)] in intent and structure. However, since that document was written a decade after SMIV2 modules had been in use, it was published as a 'Best Current Practice' (BCP). This document is not a BCP, but rather an informational reference, intended to promote consistency in documents containing YANG modules.

Many YANG constructs are defined as optional to use, such as the description statement. However, in order to maximize interoperability of NETCONF implementations utilizing YANG data models, it is desirable to define a set of usage guidelines that may require a higher level of compliance than the minimum level defined in the YANG specification.

In addition, YANG allows constructs such as infinite length identifiers and string values, or top-level mandatory nodes, that a compliant server is not required to support. Only constructs that all servers are required to support can be used in IETF YANG modules.

This document defines usage guidelines related to the NETCONF operations layer and NETCONF content layer, as defined in [[RFC6241](#)]. These guidelines are intended to be used by authors and reviewers to improve the readability and interoperability of published YANG data models.

Note that this document is not a YANG tutorial and the reader is expected to know the YANG data modeling language before using this document.

2. Terminology

2.1. Requirements Notation

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

[RFC 2119](#) language is used here to express the views of the NETMOD working group regarding content for YANG modules. YANG modules complying with this document will treat the [RFC 2119](#) terminology as if it were describing best current practices.

2.2. NETCONF Terms

The following terms are defined in [[RFC6241](#)] and are not redefined here:

- o capabilities
- o client
- o operation
- o server

2.3. YANG Terms

The following terms are defined in [[RFC6020](#)] and are not redefined here:

- o data node
- o module
- o namespace
- o submodule
- o version
- o YANG
- o YIN

Note that the term 'module' may be used as a generic term for a YANG module or submodule. When describing properties that are specific to submodules, the term 'submodule' is used instead.

[2.4.](#) Terms

The following terms are used throughout this document:

- o published: A stable release of a module or submodule, usually contained in an RFC.
- o unpublished: An unstable release of a module or submodule, usually contained in an Internet-Draft.

3. YANG Tree Diagrams

YANG tree diagrams provide a concise representation of a YANG module to help readers understand the module structure.

The meaning of the symbols in YANG tree diagrams is as follows:

- o Brackets "[" and "]" enclose list keys.
- o Abbreviations before data node names: "rw" means configuration (read-write) and "ro" state data (read-only).
- o Symbols after data node names: "?" means an optional node, "!" means a presence container, and "*" denotes a list and leaf-list.
- o Parentheses enclose choice and case nodes, and case nodes are also marked with a colon (":").
- o Ellipsis ("...") stands for contents of subtrees that are not shown.

4. General Documentation Guidelines

YANG data model modules under review are likely to be contained in Internet-Drafts. All guidelines for Internet-Draft authors MUST be followed. The RFC Editor provides guidelines for authors of RFCs, which are first published as Internet-Drafts. These guidelines should be followed and are defined in [[RFC2223](#)] and updated in [[RFC5741](#)] and "RFC Document Style" [[RFC-STYLE](#)].

The following sections MUST be present in an Internet-Draft containing a module:

- o Narrative sections
- o Definitions section
- o Security Considerations section
- o IANA Considerations section
- o References section

4.1. Module Copyright

The module description statement MUST contain a reference to the latest approved IETF Trust Copyright statement, which is available online at:

<http://trustee.ietf.org/license-info/>

Each YANG module or submodule contained within an Internet-Draft or RFC is considered to be a code component. The strings '<CODE BEGINS>' and '<CODE ENDS>' MUST be used to identify each code component.

The '<CODE BEGINS>' tag SHOULD be followed by a string identifying the file name specified in [Section 5.2 of \[RFC6020\]](#). The following example is for the '2010-01-18' revision of the 'ietf-foo' module:

```
<CODE BEGINS> file "ietf-foo@2010-01-18.yang"
  module ietf-foo {
    // ...
    revision 2010-01-18 {
      description "Latest revision";
      reference "RFC XXXX";
    }
    // ...
  }
```


<CODE ENDS>

Note that this convention MUST NOT be used for example modules or module fragments.

[FIXME: should a new convention called <EXAMPLE BEGINS> be added for YANG example modules?]

4.2. Terminology Section

A terminology section MUST be present if any terms are defined in the document or if any terms are imported from other documents.

If YANG tree diagrams are used, then a sub-section explaining the YANG tree diagram syntax MUST be present, containing the following text:

A simplified graphical representation of the data model is used in this document. The meaning of the symbols in these diagrams is defined in [RFCXXXX].

-- RFC Editor: Replace XXXX with RFC number and remove note

4.3. Tree Diagrams

YANG tree diagrams provide a concise representation of a YANG module, and SHOULD be included to help readers understand YANG module structure. Tree diagrams MAY be split into sections to correspond to document structure.

The following example shows a simple YANG tree diagram:

```
+--rw top-level-config-container
|  +--rw config-list* [key-name]
|      +--rw key-name                string
|      +--rw optional-parm?          string
|      +--rw mandatory-parm          identityref
|      +--ro read-only-leaf          string
+--ro top-level-nonconfig-container
    +--ro nonconfig-list* [name]
        +--ro name                    string
        +--ro type                    string
```

4.4. Narrative Sections

The narrative part MUST include an overview section that describes the scope and field of application of the module(s) defined by the specification and that specifies the relationship (if any) of these

modules to other standards, particularly to standards containing other YANG modules. The narrative part SHOULD include one or more sections to briefly describe the structure of the modules defined in the specification.

If the module(s) defined by the specification imports definitions from other modules (except for those defined in the [RFC6020] or [RFC6991] documents), or are always implemented in conjunction with other modules, then those facts MUST be noted in the overview section, as MUST be noted any special interpretations of definitions in other modules.

4.5. Definitions Section

This section contains the module(s) defined by the specification. These modules MUST be written using the YANG syntax defined in [RFC6020]. A YIN syntax version of the module MAY also be present in the document. There MAY also be other types of modules present in the document, such as SMIV2, which are not affected by these guidelines.

See [Section 5](#) for guidelines on YANG usage.

4.6. Security Considerations Section

Each specification that defines one or more modules MUST contain a section that discusses security considerations relevant to those modules.

This section MUST be patterned after the latest approved template (available at <http://trac.tools.ietf.org/area/ops/trac/wiki/yang-security-guidelines>). [Section 7.1](#) contains the security considerations template dated 2013-05-08. Authors MUST check the webpage at the URL listed above in case there is a more recent version available.

In particular:

- o Writable data nodes that could be especially disruptive if abused MUST be explicitly listed by name and the associated security risks MUST be explained.
- o Readable data nodes that contain especially sensitive information or that raise significant privacy concerns MUST be explicitly listed by name and the reasons for the sensitivity/privacy concerns MUST be explained.

- o Operations (i.e., YANG 'rpc' statements) that are potentially harmful to system behavior or that raise significant privacy concerns MUST be explicitly listed by name and the reasons for the sensitivity/privacy concerns MUST be explained.

4.7. IANA Considerations Section

In order to comply with IESG policy as set forth in <http://www.ietf.org/id-info/checklist.html>, every Internet-Draft that is submitted to the IESG for publication MUST contain an IANA Considerations section. The requirements for this section vary depending on what actions are required of the IANA. If there are no IANA considerations applicable to the document, then the IANA Considerations section stating that there are no actions is removed by the RFC Editor before publication. Refer to the guidelines in [\[RFC5226\]](#) for more details.

4.7.1. Documents that Create a New Namespace

If an Internet-Draft defines a new namespace that is to be administered by the IANA, then the document MUST include an IANA Considerations section that specifies how the namespace is to be administered.

Specifically, if any YANG module namespace statement value contained in the document is not already registered with IANA, then a new YANG Namespace registry entry MUST be requested from the IANA. The [\[RFC6020\]](#) specification includes the procedure for this purpose in its IANA Considerations section.

4.7.2. Documents that Extend an Existing Namespace

It is possible to extend an existing namespace using a YANG submodule that belongs to an existing module already administered by IANA. In this case, the document containing the main module MUST be updated to use the latest revision of the submodule.

4.8. Reference Sections

For every import or include statement that appears in a module contained in the specification, which identifies a module in a separate document, a corresponding normative reference to that document MUST appear in the Normative References section. The reference MUST correspond to the specific module version actually used within the specification.

For every normative reference statement that appears in a module contained in the specification, which identifies a separate document,

a corresponding normative reference to that document SHOULD appear in the Normative References section. The reference SHOULD correspond to the specific document version actually used within the specification. If the reference statement identifies an informative reference, which identifies a separate document, a corresponding informative reference to that document MAY appear in the Informative References section.

4.9. Validation Tools

All modules need to be validated before submission in an Internet Draft. The 'pyang' YANG compiler is freely available from github:

<https://github.com/mbj4668/pyang>

If the 'pyang' compiler is used, then the "--ietf" command line option SHOULD be used to identify any IETF guideline issues.

5. YANG Usage Guidelines

In general, modules in IETF Standards Track specifications **MUST** comply with all syntactic and semantic requirements of YANG [RFC6020]. The guidelines in this section are intended to supplement the YANG specification, which is intended to define a minimum set of conformance requirements.

In order to promote interoperability and establish a set of practices based on previous experience, the following sections establish usage guidelines for specific YANG constructs.

Only guidelines that clarify or restrict the minimum conformance requirements are included here.

5.1. Module Naming Conventions

Modules contained in Standards Track documents **SHOULD** be named according to the guidelines in the IANA Considerations section of [RFC6020].

A distinctive word or acronym (e.g., protocol name or working group acronym) **SHOULD** be used in the module name. If new definitions are being defined to extend one or more existing modules, then the same word or acronym should be reused, instead of creating a new one.

All published module names **MUST** be unique. For a YANG module published in an RFC, this uniqueness is guaranteed by IANA. For unpublished modules, the authors need to check that no other work in progress is using the same module name.

Once a module name is published, it **MUST NOT** be reused, even if the RFC containing the module is reclassified to 'Historic' status.

5.2. Identifiers

Identifiers for all YANG identifiers in published modules **MUST** be between 1 and 64 characters in length. These include any construct specified as an 'identifier-arg-str' token in the ABNF in [Section 12 of \[RFC6020\]](#).

5.3. Defaults

In general, it is suggested that substatements containing very common default values **SHOULD NOT** be present. The following substatements are commonly used with the default value, which would make the module difficult to read if used everywhere they are allowed.

Statement	Default Value
config	true
mandatory	false
max-elements	unbounded
min-elements	0
ordered-by	system
status	current
yin-element	false

Statement Defaults

5.4. Conditional Statements

A module may be conceptually partitioned in several ways, using the 'if-feature' and/or 'when' statements.

Data model designers need to carefully consider all modularity aspects, including the use of YANG conditional statements.

If a data definition is optional, depending on server support for a NETCONF protocol capability, then a YANG 'feature' statement SHOULD be defined to indicate that the NETCONF capability is supported within the data model.

If any notification data, or any data definition, for a non-configuration data node is not mandatory, then the server may or may not be required to return an instance of this data node. If any conditional requirements exist for returning the data node in a notification payload or retrieval request, they MUST be documented somewhere. For example, a 'when' or 'if-feature' statement could apply to the data node, or the conditional requirements could be explained in a 'description' statement within the data node or one of its ancestors (if any).

If any 'if-feature' statements apply to a list node, then the same 'if-feature' statements MUST apply to any key leaf nodes for the list. There MUST NOT be any 'if-feature' statements applied to any key leaf that do not also apply to the parent list node.

There SHOULD NOT be any 'when' statements applied to a key leaf node. It is possible that a 'when' statement for an ancestor node of a key leaf will have the exact node-set result as the key leaf. In such a case, the 'when' statement for the key leaf is redundant and SHOULD be avoided.

5.5. XPath Usage

This section describes guidelines for using the XML Path Language [[W3C.REC-xpath-19991116](#)] (XPath) within YANG modules.

5.5.1. Function Library

The 'position' and 'last' functions SHOULD NOT be used. This applies to implicit use of the 'position' function as well (e.g., '//chapter[42]'). A server is only required to maintain the relative XML document order of all instances of a particular user-ordered list or leaf-list. The 'position' and 'last' functions MAY be used if they are evaluated in a context where the context node is a user-ordered 'list' or 'leaf-list'.

The 'id' function SHOULD NOT be used. The 'ID' attribute is not present in YANG documents so this function has no meaning. The YANG compiler SHOULD return an empty string for this function.

The 'namespace-uri' and 'name' functions SHOULD NOT be used. Expanded names in XPath are different than YANG. A specific canonical representation of a YANG expanded name does not exist.

The 'lang' function SHOULD NOT be used. This function does not apply to YANG because there is no 'lang' attribute set with the document. The YANG compiler SHOULD return 'false' for this function.

The 'local-name', 'namespace-uri', 'name', 'string', and 'number' functions SHOULD NOT be used if the argument is a node-set. If so, the function result will be determined by the document order of the node-set. Since this order can be different on each server, the function results can also be different. Any function call that implicitly converts a node-set to a string will also have this issue.

The 'local-name' function SHOULD NOT be used to reference local names outside of the YANG module defining the must or when expression containing the 'local-name' function. Example of a local-name function that should not be used:

```
/*[local-name()='foo']
```

5.5.2. Axes

The 'attribute' and 'namespace' axes are not supported in YANG, and MAY be empty in a NETCONF server implementation.

The 'preceding', and 'following' axes SHOULD NOT be used. These constructs rely on XML document order within a NETCONF server

configuration database, which may not be supported consistently or produce reliable results across implementations. Predicate expressions based on static node properties (e.g., element name or value, 'ancestor' or 'descendant' axes) SHOULD be used instead. The 'preceding' and 'following' axes MAY be used if document order is not relevant to the outcome of the expression (e.g., check for global uniqueness of a parameter value).

The 'preceding-sibling' and 'following-sibling' axes SHOULD NOT be used, however they MAY be used if document order is not relevant to the outcome of the expression.

A server is only required to maintain the relative XML document order of all instances of a particular user-ordered list or leaf-list. The 'preceding-sibling' and 'following-sibling' axes MAY be used if they are evaluated in a context where the context node is a user-ordered 'list' or 'leaf-list'.

5.5.3. Types

Data nodes that use the 'int64' and 'uint64' built-in type SHOULD NOT be used within numeric or boolean expressions. There are boundary conditions in which the translation from the YANG 64-bit type to an XPath number can cause incorrect results. Specifically, an XPath 'double' precision floating point number cannot represent very large positive or negative 64-bit numbers because it only provides a total precision of 53 bits. The 'int64' and 'uint64' data types MAY be used in numeric expressions if the value can be represented with no more than 53 bits of precision.

Data modelers need to be careful not to confuse the YANG value space and the XPath value space. The data types are not the same in both, and conversion between YANG and XPath data types SHOULD be considered carefully.

Explicit XPath data type conversions MAY be used (e.g., 'string', 'boolean', or 'number' functions), instead of implicit XPath data type conversions.

XPath expressions that contain a literal value representing a YANG identity SHOULD always include the declared prefix of the module where the identity is defined.

XPath expressions for 'when' statements SHOULD NOT reference the context node or any descendant nodes of the context node. They MAY reference descendant nodes if the 'when' statement is contained within an 'augment' statement, and the referenced nodes are not defined within the 'augment' statement.

Example:

```
augment "/rt:active-route/rt:input/rt:destination-address" {
  when "rt:address-family='v4ur:ipv4-unicast'" {
    description
      "This augment is valid only for IPv4 unicast.";
  }
  // nodes defined here within the augment-stmt
  // cannot be referenced in the when-stmt
}
```

[5.5.4.](#) Wildcards

It is possible to construct XPath expressions that will evaluate differently when combined with several modules within a server implementation, then when evaluated within the single module. This is due to augmenting nodes from other modules.

Wildcard expansion is done within a server against all the nodes from all namespaces, so it is possible for a 'must' or 'when' expression that uses the '*' operator will always evaluate to false if processed within a single YANG module. In such cases, the 'description' statement SHOULD clarify that augmenting objects are expected to match the wildcard expansion.

```
when /foo/services/*/active {
  description
    "No services directly defined in this module.
    Matches objects that have augmented the services container.";
}
```

[5.6.](#) Lifecycle Management

The status statement MUST be present if its value is 'deprecated' or 'obsolete'. The status SHOULD NOT be changed from 'current' directly to 'obsolete'. An object SHOULD be available for at least one year with 'deprecated' status before it is changed to 'obsolete'.

The module or submodule name MUST NOT be changed, once the document containing the module or submodule is published.

The module namespace URI value MUST NOT be changed, once the document containing the module is published.

The revision-date substatement within the imports statement SHOULD be present if any groupings are used from the external module.

The revision-date substatement within the include statement SHOULD be

present if any groupings are used from the external submodule.

If submodules are used, then the document containing the main module MUST be updated so that the main module revision date is equal or more recent than the revision date of any submodule that is (directly or indirectly) included by the main module.

5.7. Module Header, Meta, and Revision Statements

For published modules, the namespace MUST be a globally unique URI, as defined in [[RFC3986](#)]. This value is usually assigned by the IANA.

The organization statement MUST be present. If the module is contained in a document intended for Standards Track status, then the organization SHOULD be the IETF working group chartered to write the document.

The contact statement MUST be present. If the module is contained in a document intended for Standards Track status, then the working group web and mailing information MUST be present, and the main document author or editor contact information SHOULD be present. If additional authors or editors exist, their contact information MAY be present. In addition, the Area Director and other contact information MAY be present.

The description statement MUST be present. The appropriate IETF Trust Copyright text MUST be present, as described in [Section 4.1](#).

If the module relies on information contained in other documents, which are not the same documents implied by the import statements present in the module, then these documents MUST be identified in the reference statement.

A revision statement MUST be present for each published version of the module. The revision statement MUST have a reference substatement. It MUST identify the published document that contains the module. Modules are often extracted from their original documents, and it is useful for developers and operators to know how to find the original source document in a consistent manner. The revision statement MAY have a description substatement.

Each new revision MUST include a revision date that is higher than any other revision date in the module. The revision date does not need to be updated if the module contents do not change in the new document revision.

It is acceptable to reuse the same revision statement within unpublished versions (i.e., Internet-Drafts), but the revision date

MUST be updated to a higher value each time the Internet-Draft is re-posted.

5.8. Namespace Assignments

It is RECOMMENDED that only valid YANG modules be included in documents, whether or not they are published yet. This allows:

- o the module to compile correctly instead of generating disruptive fatal errors.
- o early implementors to use the modules without picking a random value for the XML namespace.
- o early interoperability testing since independent implementations will use the same XML namespace value.

Until a URI is assigned by the IANA, a proposed namespace URI MUST be provided for the namespace statement in a YANG module. A value SHOULD be selected that is not likely to collide with other YANG namespaces. Standard module names, prefixes, and URI strings already listed in the YANG Module Registry MUST NOT be used.

A standard namespace statement value SHOULD have the following form:

```
<URN prefix string>:<module-name>
```

The following URN prefix string SHOULD be used for published and unpublished YANG modules:

```
urn:ietf:params:xml:ns:yang:
```

The following example URNs would be valid namespace statement values for Standards Track modules:

```
urn:ietf:params:xml:ns:yang:ietf-netconf-partial-lock
```

```
urn:ietf:params:xml:ns:yang:ietf-netconf-state
```

```
urn:ietf:params:xml:ns:yang:ietf-netconf
```

Note that a different URN prefix string SHOULD be used for non-Standards-Track modules. The string SHOULD be selected according to the guidelines in [[RFC6020](#)].

The following examples of non-Standards-Track modules are only suggestions. There are no guidelines for this type of URN in this document:

`http://example.com/ns/example-interfaces`

`http://example.com/ns/example-system`

5.9. Top-Level Data Definitions

The top-level data organization SHOULD be considered carefully, in advance. Data model designers need to consider how the functionality for a given protocol or protocol family will grow over time.

The separation of configuration data and operational state SHOULD be considered carefully. It is often useful to define separate top-level containers for configuration and non-configuration data.

The number of top-level data nodes within a module SHOULD be minimized. It is often useful to retrieve related information within a single subtree. If data is too distributed, it becomes difficult to retrieve all at once.

The names and data organization SHOULD reflect persistent information, such as the name of a protocol. The name of the working group SHOULD NOT be used because this may change over time.

A mandatory database data definition is defined as a node that a client must provide for the database to be valid. The server is not required to provide a value.

Top-level database data definitions MUST NOT be mandatory. If a mandatory node appears at the top level, it will immediately cause the database to be invalid. This can occur when the server boots or when a module is loaded dynamically at runtime.

5.10. Data Types

Selection of an appropriate data type (i.e., built-in type, existing derived type, or new derived type) is very subjective, and therefore few requirements can be specified on that subject.

Data model designers SHOULD use the most appropriate built-in data type for the particular application.

If extensibility of enumerated values is required, then the 'identityref' data type SHOULD be used instead of an enumeration or other built-in type.

For string data types, if a machine-readable pattern can be defined for the desired semantics, then one or more pattern statements SHOULD be present. A single quoted string SHOULD be used to specify the

pattern, since a double-quoted string can modify the content.

For string data types, if the length of the string is required to be bounded in all implementations, then a length statement **MUST** be present.

For numeric data types, if the values allowed by the intended semantics are different than those allowed by the unbounded intrinsic data type (e.g., 'int32'), then a range statement **SHOULD** be present.

The signed numeric data types (i.e., 'int8', 'int16', 'int32', and 'int64') **SHOULD NOT** be used unless negative values are allowed for the desired semantics.

For 'enumeration' or 'bits' data types, the semantics for each 'enum' or 'bit' **SHOULD** be documented. A separate description statement (within each 'enum' or 'bit' statement) **SHOULD** be present.

5.11. Reusable Type Definitions

If an appropriate derived type exists in any standard module, such as [[RFC6991](#)], then it **SHOULD** be used instead of defining a new derived type.

If an appropriate units identifier can be associated with the desired semantics, then a units statement **SHOULD** be present.

If an appropriate default value can be associated with the desired semantics, then a default statement **SHOULD** be present.

If a significant number of derived types are defined, and it is anticipated that these data types will be reused by multiple modules, then these derived types **SHOULD** be contained in a separate module or submodule, to allow easier reuse without unnecessary coupling.

The description statement **MUST** be present.

If the type definition semantics are defined in an external document (other than another YANG module indicated by an import statement), then the reference statement **MUST** be present.

5.12. Data Definitions

The description statement **MUST** be present in the following YANG statements:

- o anyxml
- o augment
- o choice
- o container
- o extension
- o feature
- o grouping
- o identity
- o leaf
- o leaf-list
- o list
- o notification
- o rpc
- o typedef

If the data definition semantics are defined in an external document, (other than another YANG module indicated by an import statement), then a reference statement **MUST** be present.

The 'anyxml' construct may be useful to represent an HTML banner containing markup elements, such as '' and '', and **MAY** be used in such cases. However, this construct **SHOULD NOT** be used if other YANG data node types can be used instead to represent the desired syntax and semantics.

It has been found that the 'anyxml' statement is not implemented consistently across all servers. It is possible that mixed mode XML will not be supported, or configuration anyxml nodes will not be supported.

If there are referential integrity constraints associated with the desired semantics that can be represented with XPath, then one or more 'must' statements **SHOULD** be present.

For list and leaf-list data definitions, if the number of possible

instances is required to be bounded for all implementations, then the max-elements statements SHOULD be present.

If any 'must' or 'when' statements are used within the data definition, then the data definition description statement SHOULD describe the purpose of each one.

5.13. Operation Definitions

If the operation semantics are defined in an external document (other than another YANG module indicated by an import statement), then a reference statement MUST be present.

If the operation impacts system behavior in some way, it SHOULD be mentioned in the description statement.

If the operation is potentially harmful to system behavior in some way, it MUST be mentioned in the Security Considerations section of the document.

5.14. Notification Definitions

The description statement MUST be present.

If the notification semantics are defined in an external document (other than another YANG module indicated by an import statement), then a reference statement MUST be present.

If the notification refers to a specific resource instance, then this instance SHOULD be identified in the notification data. This is usually done by including 'leafref' leaf nodes with the key leaf values for the resource instance. For example:

```
notification interface-up {  
  description "Sent when an interface is activated.";  
  leaf name {  
    type leafref {  
      path "/if:interfaces/if:interface/if:name";  
    }  
  }  
}
```

Note that there are no formal YANG statements to identify any data node resources associated with a notification. The description statement for the notification SHOULD specify if and how the notification identifies any data node resources associated with the specific event.

5.15. Feature Definitions

The YANG "feature" statement is used to define a label for a set of optional functionality within a module. The "if-feature" statement is used in the YANG statements associated with a feature.

The set of YANG features available in a module should be considered carefully. The description-stmt within a feature-stmt MUST specify any interactions with other features.

If there is a large set of objects associated with a YANG feature, then consider moving those objects to a separate module, instead of using a YANG feature. Note that the set of features within a module is easily discovered by the reader, but the set of related modules within the entire YANG library is not as easy to identity. Module names with a common prefix can help readers identity the set of related modules, but this assumes the reader will have discovered and installed all the relevant modules.

If one feature requires implementation of another feature, then an "if-feature" statement SHOULD be used in the dependent "feature" statement.

For example, feature2 requires implementation of feature1:

```
feature feature1 {
  description "Some protocol feature";
}

feature feature2 {
  if-feature "feature1";
  description "Another protocol feature";
}
```

5.16. Data Correlation

Data can be correlated in various ways, using common data types, common data naming, and common data organization. There are several ways to extend the functionality of a module, based on the degree of coupling between the old and new functionality:

- o inline: update the module with new protocol-accessible objects. The naming and data organization of the original objects is used. The new objects are in the original module namespace.
- o augment: create a new module with new protocol-accessible objects that augment the original data structure. The naming and data organization of the original objects is used. The new objects are

in the new module namespace.

- o mirror: create new objects in a new module or the original module, except use new a naming scheme and data location. The naming can be coupled in different ways. Tight coupling is achieved with a "leafref" data type. This method SHOULD be used. If the new data instances are not limited to the values in use in the original data structure, then the "require-instance" sub-statement MUST be set to "false". Loose coupling is achieved by using key leafs with the same data type as the original data structure.

It is sometimes useful to separate configuration and operational state, so that they do not not even share the exact same naming characteristics. The correlation between configuration the operational state data that is affected by changes in configuration is a complex problem. There may not be a simple 1:1 relationship between a configuration data node and an operational data node. Further work is needed in YANG to clarify this relationship. Protocol work may also be needed to allow a client to retrieve this type of information from a server. At this time the best practice is to clearly document any relationship to other data structures in the "description" statement.

6. IANA Considerations

This document registers one URI in the IETF XML registry [[RFC3688](#)].

The following registration has been made:

URI: urn:ietf:params:xml:ns:yang:ietf-template

Registrant Contact: The NETMOD WG of the IETF.

XML: N/A, the requested URI is an XML namespace.

Per this document, the following assignment has been made in the YANG Module Names Registry for the YANG module template in [Appendix C](#).

Field	Value
Name	ietf-template
Namespace	urn:ietf:params:xml:ns:yang:ietf-template
Prefix	temp
Reference	RFC XXXX

YANG Registry Assignment

7. Security Considerations

This document defines documentation guidelines for NETCONF content defined with the YANG data modeling language. The guidelines for how to write a Security Considerations section for a YANG module are defined in the online document

<http://trac.tools.ietf.org/area/ops/trac/wiki/yang-security-guidelines>

This document does not introduce any new or increased security risks into the management system.

The following section contains the security considerations template dated 2010-06-16. Be sure to check the webpage at the URL listed above in case there is a more recent version available.

Each specification that defines one or more YANG modules MUST contain a section that discusses security considerations relevant to those modules. This section MUST be patterned after the latest approved template (available at

<http://www.ops.ietf.org/netconf/yang-security-considerations.txt>).

In particular, writable data nodes that could be especially disruptive if abused MUST be explicitly listed by name and the associated security risks MUST be spelled out.

Similarly, readable data nodes that contain especially sensitive information or that raise significant privacy concerns MUST be explicitly listed by name and the reasons for the sensitivity/privacy concerns MUST be explained.

Further, if new RPC operations have been defined, then the security considerations of each new RPC operation MUST be explained.

7.1. Security Considerations Section Template

X. Security Considerations

The YANG module defined in this memo is designed to be accessed via the NETCONF protocol [[RFC6241](#)]. The lowest NETCONF layer is the secure transport layer and the mandatory-to-implement secure transport is SSH [[RFC6242](#)].

- if you have any writable data nodes (those are all the
- "config true" nodes, and remember, that is the default)
- describe their specific sensitivity or vulnerability.

There are a number of data nodes defined in this YANG module which are writable/creatable/deletable (i.e., config true, which is the default). These data nodes may be considered sensitive or vulnerable in some network environments. Write operations (e.g., edit-config) to these data nodes without proper protection can have a negative effect on network operations. These are the subtrees and data nodes and their sensitivity/vulnerability:

<list subtrees and data nodes and state why they are sensitive>

```
-- for all YANG modules you must evaluate whether any readable data
-- nodes (those are all the "config false" nodes, but also all other
-- nodes, because they can also be read via operations like get or
-- get-config) are sensitive or vulnerable (for instance, if they
-- might reveal customer information or violate personal privacy
-- laws such as those of the European Union if exposed to
-- unauthorized parties)
```

Some of the readable data nodes in this YANG module may be considered sensitive or vulnerable in some network environments. It is thus important to control read access (e.g., via get, get-config, or notification) to these data nodes. These are the subtrees and data nodes and their sensitivity/vulnerability:

<list subtrees and data nodes and state why they are sensitive>

```
-- if your YANG module has defined any rpc operations
-- describe their specific sensitivity or vulnerability.
```

Some of the RPC operations in this YANG module may be considered sensitive or vulnerable in some network environments. It is thus important to control access to these operations. These are the operations and their sensitivity/vulnerability:

<list RPC operations and state why they are sensitive>

8. Acknowledgments

The structure and contents of this document are adapted from [\[RFC4181\]](#), guidelines for MIB Documents, by C. M. Heard.

The working group thanks Martin Bjorklund, Juergen Schoenwaelder, Ladislav Lhotka, and Jernej Tuljak for their extensive reviews and contributions to this document.

9. Changes Since [RFC 6087](#)

The following changes have been made to the guidelines published in [\[RFC6087\]](#):

- o Updated NETCONF reference from [RFC 4741](#) to [RFC 6241](#)
- o Updated NETCONF over SSH citation from [RFC 4742](#) to [RFC 6242](#)
- o Updated YANG Types reference from [RFC 6021](#) to [RFC 6991](#)
- o Updated obsolete URLs for IETF resources
- o Changed top-level data node guideline
- o Clarified XPath usage for a literal value representing a YANG identity
- o Clarified XPath usage for a when-stmt
- o Clarified XPath usage for 'proceeding-sibling' and 'following-sibling' axes
- o Added terminology guidelines
- o Added YANG tree diagram definition and guideline
- o Updated XPath guidelines for type conversions and function library usage.
- o Updated data types section
- o Updated notifications section
- o Clarified conditional key leaf nodes
- o Clarify usage of 'uint64' and 'int64' data types
- o Added text on YANG feature usage

10. References

10.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC2223] Postel, J. and J. Reynolds, "Instructions to RFC Authors", [RFC 2223](#), October 1997.
- [RFC3688] Mealling, M., "The IETF XML Registry", [BCP 81](#), [RFC 3688](#), January 2004.
- [RFC3986] Berners-Lee, T., Fielding, R., and L. Masinter, "Uniform Resource Identifier (URI): Generic Syntax", STD 66, [RFC 3986](#), January 2005.
- [RFC5378] Bradner, S. and J. Contreras, "Rights Contributors Provide to the IETF Trust", [BCP 78](#), [RFC 5378](#), November 2008.
- [RFC5741] Daigle, L., Kolkman, O., and IAB, "RFC Streams, Headers, and Boilerplates", [RFC 5741](#), December 2009.
- [RFC6020] Bjorklund, M., "YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF)", [RFC 6020](#), October 2010.
- [RFC6241] Enns, R., Ed., Bjorklund, M., Ed., Schoenwaelder, J., Ed., and A. Bierman, Ed., "Network Configuration Protocol (NETCONF)", [RFC 6241](#), June 2011.
- [RFC6991] Schoenwaelder, J., "Common YANG Data Types", [RFC 6991](#), July 2013.
- [W3C.REC-xpath-19991116]
Clark, J. and S. DeRose, "XML Path Language (XPath) Version 1.0", World Wide Web Consortium Recommendation REC-xpath-19991116, November 1999, <<http://www.w3.org/TR/1999/REC-xpath-19991116>>.

10.2. Informative References

- [RFC-STYLE]
Braden, R., Ginoza, S., and A. Hagens, "RFC Document Style", September 2009, <<http://www.rfc-editor.org/rfc-style-guide/rfc-style>>.
- [RFC4181] Heard, C., "Guidelines for Authors and Reviewers of MIB

Documents", [BCP 111](#), [RFC 4181](#), September 2005.

[RFC5226] Narten, T. and H. Alvestrand, "Guidelines for Writing an IANA Considerations Section in RFCs", [BCP 26](#), [RFC 5226](#), May 2008.

[RFC6087] Bierman, A., "Guidelines for Authors and Reviewers of YANG Data Model Documents", [RFC 6087](#), January 2011.

Appendix A. Change Log

-- RFC Ed.: remove this section before publication.

A.1. 00 to 01

All issues from the issue tracker have been addressed.

<https://github.com/netmod-wg/rfc6087bis/issues>

- o Issue 1: Tree Diagrams: Added [Section 3](#) so RFCs with YANG modules can use an Informative reference to this RFC for tree diagrams. Updated guidelines to reference this RFC when tree diagrams are used
- o Issue 2: XPath function restrictions: Added paragraphs in XPath usage section for 'id', 'namespace-uri', 'name', and 'lang' functions
- o Issue 3: XPath function document order issues: Added paragraph in XPath usage section about node-set ordering for 'local-name', 'namespace-uri', 'name', 'string' and 'number' functions. Also any function that implicitly converts a node-set to a string.
- o Issue 4: XPath preceding-sibling and following-sibling: Checked and text in XPath usage section already has proposed text from Lada.
- o Issue 5: XPath 'when-stmt' reference to descendant nodes: Added exception and example in XPath Usage section for augmented nodes.
- o Issue 6: XPath numeric conversions: Changed 'numeric expressions' to 'numeric and boolean expressions'
- o Issue 7: XPath module containment: Added sub-section on XPath wildcards
- o Issue 8: status-stmt usage: Added text to Lifecycle Management section about transitioning from active to deprecated and then to obsolete.
- o Issue 9: resource identification in notifications: Add text to Notifications section about identifying resources and using the leafref data type.
- o Issue 10: single quoted strings: Added text to Data Types section about using a single-quoted string for patterns.

Appendix B. Module Review Checklist

This section is adapted from [RFC 4181](#).

The purpose of a YANG module review is to review the YANG module both for technical correctness and for adherence to IETF documentation requirements. The following checklist may be helpful when reviewing an Internet-Draft:

- o I-D Boilerplate -- verify that the draft contains the required Internet-Draft boilerplate (see <http://www.ietf.org/id-info/guidelines.html>), including the appropriate statement to permit publication as an RFC, and that I-D boilerplate does not contain references or section numbers.
- o Abstract -- verify that the abstract does not contain references, that it does not have a section number, and that its content follows the guidelines in <http://www.ietf.org/id-info/guidelines.html>.
- o Copyright Notice -- verify that the draft has the appropriate text regarding the rights that document contributors provide to the IETF Trust [[RFC5378](#)]. Verify that it contains the full IETF Trust copyright notice at the beginning of the document. The IETF Trust Legal Provisions (TLP) can be found at:

<http://trustee.ietf.org/license-info/>

- o Security Considerations section -- verify that the draft uses the latest approved template from the OPS area website (<http://trac.tools.ietf.org/area/ops/trac/wiki/yang-security-guidelines>) and that the guidelines therein have been followed.
- o IANA Considerations section -- this section must always be present. For each module within the document, ensure that the IANA Considerations section contains entries for the following IANA registries:

XML Namespace Registry: Register the YANG module namespace.

YANG Module Registry: Register the YANG module name, prefix, namespace, and RFC number, according to the rules specified in [[RFC6020](#)].

- o References -- verify that the references are properly divided between normative and informative references, that [RFC 2119](#) is included as a normative reference if the terminology defined therein is used in the document, that all references required by the boilerplate are present, that all YANG modules containing imported items are cited as normative references, and that all citations point to the most current RFCs unless there is a valid reason to do otherwise (for example, it is OK to include an informative reference to a previous version of a specification to help explain a feature included for backward compatibility). Be sure citations for all imported modules are present somewhere in the document text (outside the YANG module).
- o License -- verify that the draft contains the Simplified BSD License in each YANG module or submodule. Some guidelines related to this requirement are described in [Section 4.1](#). Make sure that the correct year is used in all copyright dates. Use the approved text from the latest Trust Legal Provisions (TLP) document, which can be found at:

<http://trustee.ietf.org/license-info/>

- o Other Issues -- check for any issues mentioned in <http://www.ietf.org/id-info/checklist.html> that are not covered elsewhere.
- o Technical Content -- review the actual technical content for compliance with the guidelines in this document. The use of a YANG module compiler is recommended when checking for syntax errors. A list of freely available tools and other information can be found at:

<http://trac.tools.ietf.org/wg/netconf/trac/wiki>

Checking for correct syntax, however, is only part of the job. It is just as important to actually read the YANG module document from the point of view of a potential implementor. It is particularly important to check that description statements are sufficiently clear and unambiguous to allow interoperable implementations to be created.

[Appendix C](#). YANG Module Template

```
<CODE BEGINS> file "ietf-template@2010-05-18.yang"

module ietf-template {

    // replace this string with a unique namespace URN value
    namespace
        "urn:ietf:params:xml:ns:yang:ietf-template";

    // replace this string, and try to pick a unique prefix
    prefix "temp";

    // import statements here: e.g.,
    // import ietf-yang-types { prefix yang; }
    // import ietf-inet-types { prefix inet; }

    // identify the IETF working group if applicable
    organization
        "IETF NETMOD (NETCONF Data Modeling Language) Working Group";

    // update this contact statement with your info
    contact
        "WG Web:  <http://tools.ietf.org/wg/your-wg-name/>
        WG List:  <mailto:your-wg-name@ietf.org>

        WG Chair: your-WG-chair
                  <mailto:your-WG-chair@example.com>

        Editor:   your-name
                  <mailto:your-email@example.com>";

    // replace the first sentence in this description statement.
    // replace the copyright notice with the most recent
    // version, if it has been updated since the publication
    // of this document
    description
        "This module defines a template for other YANG modules.

        Copyright (c) <insert year> IETF Trust and the persons
        identified as authors of the code.  All rights reserved.

        Redistribution and use in source and binary forms, with or
        without modification, is permitted pursuant to, and subject
        to the license terms contained in, the Simplified BSD License
```


set forth in [Section 4.c](#) of the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>).

This version of this YANG module is part of RFC XXXX; see the RFC itself for full legal notices.";

```
// RFC Ed.: replace XXXX with actual RFC number and remove
// this note
```

```
reference "RFC XXXX";
```

```
// RFC Ed.: remove this note
// Note: extracted from RFC XXXX
```

```
// replace '2010-05-18' with the module publication date
// The format is (year-month-day)
revision "2010-05-18" {
  description
    "Initial version";
}
```

```
// extension statements
```

```
// feature statements
```

```
// identity statements
```

```
// typedef statements
```

```
// grouping statements
```

```
// data definition statements
```

```
// augment statements
```

```
// rpc statements
```

```
// notification statements
```

```
// DO NOT put deviation statements in a published module
```

```
}
```

<CODE ENDS>

Author's Address

Andy Bierman
YumaWorks

Email: andy@yumaworks.com