

Network Working Group
Internet-Draft
Intended status: Standards Track
Expires: July 22, 2012

J. Schoenwaelder
Jacobs University
January 19, 2012

Translation of SMIV2 MIB Modules to YANG Modules
draft-ietf-netmod-smi-yang-04

Abstract

YANG is a data modeling language used to model configuration and state data manipulated by the NETCONF protocol, NETCONF remote procedure calls, and NETCONF notifications. The Structure of Management Information (SMIV2) defines fundamental data types, an object model, and the rules for writing and revising MIB modules for use with the SNMP protocol. This document defines a translation of SMIV2 MIB modules into YANG modules, enabling read-only access to data objects defined in SMIV2 MIB modules via NETCONF.

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on July 22, 2012.

Copyright Notice

Copyright (c) 2012 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must

include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	3
2.	Mapping of Well Known Types	4
3.	Translation of SMIV2 Modules and SMIV2 IMPORT Clauses	5
3.1.	Example: IMPORTS of IF-MIB	6
4.	Translation of the MODULE-IDENTITY Macro	7
4.1.	MODULE-IDENTITY Translation Rules	7
4.2.	Example: MODULE-IDENTITY of IF-MIB	8
5.	Translation of the TEXTUAL-CONVENTION Macro	9
5.1.	TEXTUAL-CONVENTION Translation Rules	9
5.2.	Example: OwnerString and InterfaceIndex of IF-MIB	10
5.3.	Example: IfDirection of the DIFFSERV-MIB	10
6.	Translation of OBJECT IDENTIFIER Assignments	12
7.	Translation of the OBJECT-TYPE Macro	13
7.1.	Scalar and Columnar Object Translation Rules	13
7.2.	Example: ifNumber and ifIndex of the IF-MIB	14
7.3.	Non-Augmenting Conceptual Table Translation Rules	15
7.4.	Example: ifTable of the IF-MIB	17
7.5.	Example: ifRcvAddressTable of the IF-MIB	17
7.6.	Example: alHostTable of the RMON2-MIB	19
7.7.	Augmenting Conceptual Tables Translation Rules	20
7.8.	Example: ifXTable of the IF-MIB	21
8.	Translation of the OBJECT-IDENTITY Macro	23
8.1.	OBJECT-IDENTITY Translation Rules	23
8.2.	Example: diffServTbParamSimpleTokenBucket of the DIFFSERV-MIB	23
9.	Translation of the NOTIFICATION-TYPE Macro	24
9.1.	NOTIFICATION-TYPE Translation Rules	24
9.2.	Example: linkDown NOTIFICATION-TYPE of IF-MIB	24
10.	YANG Language Extension Definition	27
11.	Implementing Configuration Data Nodes	31
11.1.	Example: addressMapControlTable of RMON2-MIB	31
12.	IANA Considerations	34
13.	Security Considerations	35
14.	Acknowledgements	36
15.	References	37
15.1.	Normative References	37

15.2. Informative References	37
Appendix A. Mapping of Well Known Types (normative)	39
Appendix B. Module Prefix Generation (informative)	42
Author's Address	43

[1.](#) Introduction

This document describes a translation of SMIV2 [[RFC2578](#)], [[RFC2579](#)], [[RFC2580](#)] MIB modules into YANG [[RFC6020](#)] modules, enabling read-only access to data objects defined in SMIV2 MIB modules via NETCONF. The mapping is illustrated by examples showing the translation of parts of the IF-MIB [[RFC2863](#)], the DIFFSERV-MIB [[RFC3289](#)], and the RMON2-MIB [[RFC4502](#)] SMIV2 module.

SMIV1 modules may be converted to YANG by first following the rules in [[RFC3584](#)] to convert the SMIV1 module to SMIV2, then following the rules in this document to convert to YANG.

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [BCP 14](#), [[RFC2119](#)].

2. Mapping of Well Known Types

The SMIV2 base types and some well known derived textual conventions are mapped to YANG types according to [Appendix A](#). The mapping of the OCTET STRING depends on the context. If an OCTET STRING type has an associated DISPLAY-HINT, then the corresponding YANG base type is the string type. Otherwise, the binary type is used. Similarly, the mapping of the INTEGER type depends on its usage as an enumeration or a 32-bit integral type. Implementations are encouraged to provide options to handle situations where DISPLAY-HINTs are added during a revision of a module and backwards compatibility must be preserved.

The mappings shown in [Appendix A](#) may impact the imports of the generated YANG module since some SMIV2 types and textual conventions map to YANG types defined in the `ietf-yang-types` and `ietf-inet-types` YANG modules defined in [[RFC6021](#)] and the `ietf-yang-smiv2` YANG module defined in this document. Implementations MUST add any additional imports required by the type mapping.

[3.](#) Translation of SMIV2 Modules and SMIV2 IMPORT Clauses

SMIV2 modules are mapped to corresponding YANG modules. The YANG module name MUST be the same as the SMIV2 module name.

The YANG namespace MUST be constructed out of a constant prefix followed by the SMIV2 module name. Since SMIV2 module names can be assumed to be unique (see [Section 3 in \[RFC2578\]](#)), the resulting YANG namespace is unique. The registered prefix is urn:ietf:params:xml:ns:yang:smiv2:, see the IANA considerations in [Section 12](#).

The YANG prefix MAY be derived from the SMIV2 module name using the module prefix generation algorithm described in [Appendix B](#). The YANG prefix is supposed to be short and it must be unique within the set of all prefixes used by a YANG module. The algorithm described in [Appendix B](#) generates such prefixes.

SMIV2 IMPORT clauses are translated to YANG import statements. One major difference between the SMIV2 import mechanism and the YANG import mechanism is that SMIV2 IMPORT clauses import specific symbols from an SMIV2 module while the YANG import statement imports all

symbols of the referenced YANG module.

In order to produce correct and complete YANG import statements, the following rules MUST be used:

- o Process each item in each SMIV2 IMPORT clause as follows:
 1. If an import statement for this SMIV2 module has already been generated, then ignore this item.
 2. Otherwise, if the SMIV2 module name is SNMPv2-SMI or SNMPv2-CONF, then ignore this item. Note that these two modules can be completely ignored since all definitions in these modules are translated by translation rules.
 3. Otherwise, if this item is a textual convention matching one of the textual conventions in the SMIV2 types column of [Appendix A](#) (e.g., MacAddress, PhysAddress, or TimeStamp) then ignore this item.
 4. Otherwise, if the item is used in a SYNTAX clause of an OBJECT-TYPE whose MAX-ACCESS is not accessible-for-notify, then generate an import statement as described below.
 5. Otherwise, if the item is used in an OBJECTS clause of a NOTIFICATION-TYPE, then generate an import statement as

described below.

6. Otherwise, if the item is used in an INDEX or AUGMENTS clause, then generate an import statement as described below.
 7. Otherwise, ignore this item. Some examples of this case are OBJECT IDENTIFIER assignments and objects that are only referenced in MODULE-COMPLIANCE, OBJECT-GROUP, or NOTIFICATION-GROUP clauses.
- o Generate any additional import statements as required by the type translations according to the type mapping table [Appendix A](#). This requires the translator to consider all the types used in the SMIV2 module in order to produce the imports.

- o Generate an import statement for the YANG module `ietf-yang-smiv2` with the prefix `smiv2`.

The generated import statements use the untranslated SMIV2 module names or the names of well-known YANG modules as their argument. The import statement must contain a prefix statement. The prefixes MAY be generated by applying the module prefix generation algorithm described in [Appendix B](#).

[3.1](#). Example: IMPORTS of IF-MIB

The translation of the IF-MIB [[RFC2863](#)] leads to the YANG module and namespace/prefix statement and the import statements shown below. The prefix is the translation of the SMIV2 module name IF-MIB to lowercase (consisting of two tokens and thus no further abbreviation).

```
module IF-MIB {  
  
    namespace "urn:ietf:params:xml:ns:yang:smiv2:IF-MIB";  
    prefix "if-mib";  
  
    import IANAifType-MIB      { prefix "ianaiftype-mib"; }  
    import SNMPv2-TC          { prefix "snmpv2-tc"; }  
    import ietf-yang-types    { prefix "yang"; }  
    import ietf-yang-smiv2    { prefix "smiv2"; }  
}
```

[4](#). Translation of the MODULE-IDENTITY Macro

The SMIV2 requires an invocation of the MODULE-IDENTITY macro to provide contact and revision history for a MIB module. The clauses of the SMIV2 MODULE-IDENTITY macro MUST be translated into YANG statements as detailed below.

[4.1](#). MODULE-IDENTITY Translation Rules

- o The SMIV2 ORGANIZATION clause is mapped to the YANG organization statement.
- o The SMIV2 CONTACT-INFO clause is mapped to the YANG contact statement.
- o The SMIV2 DESCRIPTION clause is mapped to the YANG description statement.
- o Each SMIV2 REVISION clause is mapped to a YANG revision statement. The revision is identified by the date argument of the SMIV2 REVISION clause. DESCRIPTION sub-clauses of REVISION clauses are mapped to corresponding description statement nested in revision clauses.
- o The SMIV2 LAST-UPDATED clause is ignored if the associated date matches a REVISION clause. Otherwise, an additional revision statement is generated.
- o A top-level YANG container is generated. The container's name is the SMIV2 module name and the container MUST be config false. The generation of the top-level container MAY be skipped if the SMIV2 module does not define any objects that go into the top-level container (e.g., an SMIV2 module only defining textual conventions).
- o The object identifier value of the invocation of the SMIV2 MODULE-IDENTITY is translated into an smiv2:oid statement contained in an smiv2:alias statement representing the MODULE-IDENTITY macro invocation. Refer to the YANG extension defined in [Section 10](#).

While all proper SMIV2 modules must have exactly one MODULE-IDENTITY macro invocation, there are a few notable exceptions. The modules defining the SMIV2 language (i.e., the SNMPv2-SMI, SNMPv2-TC, and SNMPv2-CONF modules) do not invoke the MODULE-IDENTITY macro. Furthermore, SMIV2 modules generated from SMIV1 modules may miss an invocation of the MODULE-IDENTITY macro as well. In such cases, it is preferable to not generate organization, contact, description, and revision statements.

The translation of the MODULE-IDENTITY of the IF-MIB [[RFC2863](#)] leads to the following YANG statements:

```
organization
  "IETF Interfaces MIB Working Group";

contact
  "Keith McCloghrie
  Cisco Systems, Inc.
  170 West Tasman Drive
  San Jose, CA 95134-1706
  US

  408-526-5260
  kzm@cisco.com";

description
  "The MIB module to describe generic objects for network
  interface sub-layers. This MIB is an updated version of
  MIB-II's ifTable, and incorporates the extensions defined in
  RFC 1229.";

revision "2000-06-14" {
  description
    "Clarifications agreed upon by the Interfaces MIB WG, and
    published as RFC 2863.";
}
revision "1996-02-28" {
  description
    "Revisions made by the Interfaces MIB WG, and published in
    RFC 2233.";
}
revision "1993-11-08" {
  description
    "Initial revision, published as part of RFC 1573.";
}

container IF-MIB {
  config false;
}
```

[5.](#) Translation of the TEXTUAL-CONVENTION Macro

The SMIV2 uses invocations of the TEXTUAL-CONVENTION macro to define new types derived from the SMIV2 base types. Invocations of the TEXTUAL-CONVENTION macro MUST be translated into YANG typedef statements as detailed below.

[5.1.](#) TEXTUAL-CONVENTION Translation Rules

The name of the TEXTUAL-CONVENTION macro invocation is used as the name of the generated typedef statement. The clauses of the SMIV2 TEXTUAL-CONVENTION macro are mapped to YANG statements embedded in the typedef statement as follows:

- o The SMIV2 DISPLAY-HINT clause is used to determine the type mapping of types derived from the OCTET STRING type as explained in [Section 2](#). Furthermore, the DISPLAY-HINT value MAY be used to generate a regular expression for the YANG pattern statement within the type statement.
- o The SMIV2 DISPLAY-HINT is translated into an smiv2:display-hint statement. Refer to the YANG extension defined in [Section 10](#).
- o The SMIV2 STATUS clause is mapped to the YANG status statement. The generation of the YANG status statement is skipped if the value of the STATUS clause is current.
- o The SMIV2 DESCRIPTION clause is mapped to the YANG description statement.
- o The SMIV2 REFERENCE clause is mapped to the YANG reference statement.
- o The SMIV2 SYNTAX clause is mapped to the YANG type statement. SMIV2 range restrictions are mapped to YANG range statements while SMIV2 length restrictions are mapped to YANG length statements. SMIV2 INTEGER enumerations are mapped to YANG enum/value statements. SMIV2 BITS are mapped to YANG bit/position statements.

This translation assumes that labels of named numbers and named bits do not change when an SMIV2 module is revised. This is consistent with the clarification of the SMIV2 module revision rules in [Section 4.9 of \[RFC4181\]](#).

[5.2.](#) Example: OwnerString and InterfaceIndex of IF-MIB

The translation of the OwnerString and InterfaceIndex textual conventions of the IF-MIB [[RFC2863](#)] are shown below.

```
typedef OwnerString {
  type string {
    length "0..255";
    pattern '\p{IsBasicLatin}{0,255}';
  }
  status deprecated;
  description
    "This data type is used to model an administratively
    assigned name of the owner of a resource. This information
    is taken from the NVT ASCII character set. It is suggested
    that this name contain one or more of the following: ASCII
    form of the manager station's transport address, management
    station name (e.g., domain name), network management
    personnel's name, location, or phone number. In some cases
    the agent itself will be the owner of an entry. In these
    cases, this string shall be set to a string starting with
    'agent'.";
  smiv2:display-hint "255a";
}

typedef InterfaceIndex {
  type int32 {
    range "1..2147483647";
  }
  description
    "A unique value, greater than zero, for each interface or
    interface sub-layer in the managed system. It is
    recommended that values are assigned contiguously starting
    from 1. The value for each interface sub-layer must remain
    constant at least from one re-initialization of the entity's
    network management system to the next re-initialization.";
  smiv2:display-hint "d";
}
```

5.3. Example: IfDirection of the DIFFSERV-MIB

The translation of the IfDirection textual convention of the DIFFSERV-MIB [[RFC3289](#)] is shown below.

```
typedef IfDirection {
  type enumeration {
    enum inbound { value 1; }
    enum outbound { value 2; }
  }
  description
    "IfDirection specifies a direction of data travel on an
    interface. 'inbound' traffic is operated on during reception from
    the interface, while 'outbound' traffic is operated on prior to
    transmission on the interface.";
}
```

6. Translation of OBJECT IDENTIFIER Assignments

The SMIV2 uses OBJECT IDENTIFIER assignments to introduce names for intermediate nodes in the OBJECT IDENTIFIER tree. OBJECT IDENTIFIER assignments are translated into smiv2:alias statements. Refer to the YANG extension defined in [Section 10](#).

[7.](#) Translation of the OBJECT-TYPE Macro

The SMIV2 uses the OBJECT-TYPE macro to define objects and the structure of conceptual tables. Objects exist either as scalars (exactly one instance within an SNMP context) or columnar objects within conceptual tables (zero or multiple instances within an SNMP context). A number of auxiliary objects define the index (key) of a conceptual table. Furthermore, conceptual tables can be augmented by other conceptual tables. All these differences must be taken into account when translating SMIV2 OBJECT-TYPE macro invocations to YANG. Invocations of the OBJECT-TYPE macro MUST be translated into YANG statements as detailed below.

[7.1.](#) Scalar and Columnar Object Translation Rules

SMIV2 OBJECT-TYPE macro invocations defining scalars or columnar objects with a MAX-ACCESS of "not-accessible", "read-only", "read-write" and "read-create" are translated to YANG leaf

statements. Additionally, columnar objects with a MAX-ACCESS of accessible-for-notify are translated to YANG leaf statements if that columnar object is part of the INDEX clause of the table containing that columnar object. The name of the leaf is the name associated with the SMIV2 OBJECT-TYPE macro invocation. SMIV2 OBJECT-TYPE macro invocations with a MAX-ACCESS of "accessible-for-notify" are not translated to YANG data tree leafs but instead into YANG notification leafs.

Leaf statements for scalar objects are created in a container representing the scalar's parent node in the OID tree. This container is named after the scalar's parent node in the OID tree and placed in the top-level container representing the SMIV2 module, see [Section 4.1](#). In the rare case that the scalar's parent node has multiple names, the automatic translation MUST fail with an error and the name clash needs to be investigated and fixed manually. In case a previous revision of the SMIV2 module did not have an ambiguity, then the name used by the previous revision MUST be used. The leaf statements representing columnar objects are created in the list representing a conceptual row, see [Section 7.3](#).

- o The SMIV2 SYNTAX clause is mapped to the YANG type statement. SMIV2 range restrictions are mapped to YANG range statements while SMIV2 length restrictions are mapped to YANG length statements. SMIV2 INTEGER enumerations are mapped to YANG enum/value statements. SMIV2 BITS are mapped to YANG bit/position statements.
- o The SMIV2 UNITS clause is mapped to the YANG units statement.

- o The SMIV2 MAX-ACCESS is translated into an smiv2:max-access statement. Refer to the YANG extension defined in [Section 10](#).
- o The SMIV2 STATUS clause is mapped to the YANG status statement. The generation of the YANG status statement is skipped if the value of the STATUS clause is current.
- o The SMIV2 DESCRIPTION clause is mapped to the YANG description statement.
- o The SMIV2 REFERENCE clause is mapped to the YANG reference

statement.

- o The SMIV2 DEFVAL clause is mapped to an smiv2:defval statement. Refer to the YANG extension defined in [Section 10](#).
- o The value of the SMIV2 OBJECT-TYPE macro invocation is translated into an smiv2:oid statement. Refer to the YANG extension defined in [Section 10](#).

This translation assumes that labels of named numbers and named bits do not change when an SMIV2 module is revised. This is consistent with the clarification of the SMIV2 module revision rules in [Section 4.9 of \[RFC4181\]](#).

[7.2](#). Example: ifNumber and ifIndex of the IF-MIB

The translations of the ifNumber scalar object and the ifIndex columnar object of the IF-MIB [\[RFC2863\]](#) are shown below. Since ifNumber is a scalar object in the interfaces branch of the IF-MIB, the YANG leaf ifNumber will be placed in a YANG container called interfaces, which is registered in the top-level container IF-MIB.

```
leaf ifNumber {
  type int32;
  description
    "The number of network interfaces (regardless of their
```

```

    current state) present on this system.";
    smiv2:max-access "read-only";
    smiv2:oid "1.3.6.1.2.1.2.1";
}

leaf ifIndex {
    type if-mib:InterfaceIndex;
    description
        "A unique value, greater than zero, for each interface. It
        is recommended that values are assigned contiguously
        starting from 1. The value for each interface sub-layer
        must remain constant at least from one re-initialization of
        the entity's network management system to the next re-
        initialization.";
    smiv2:max-access "read-only";
    smiv2:oid "1.3.6.1.2.1.2.2.1.1";
}

```

[7.3.](#) Non-Augmenting Conceptual Table Translation Rules

An OBJECT-TYPE macro invocation defining a non-augmenting conceptual table is translated to a YANG container statement using the name of the OBJECT-TYPE macro invocation. This container is created in the top-level container representing the SMIV2 module. The clauses of the macro are translated as follows:

- o The SMIV2 SYNTAX clause is ignored
- o The SMIV2 UNITS clause is ignored.
- o The SMIV2 MAX-ACCESS clause is ignored.
- o The SMIV2 STATUS clause is mapped to the YANG status statement. The generation of the YANG status statement is skipped if the value of the STATUS clause is current.
- o The SMIV2 DESCRIPTION clause is mapped to the YANG description statement.
- o The SMIV2 REFERENCE clause is mapped to the YANG reference statement.
- o The value of the SMIV2 OBJECT-TYPE macro invocation is translated into an smiv2:oid statement. Refer to the YANG extension defined

in [Section 10](#).

An OBJECT-TYPE macro invocation defining a conceptual row is translated to a YANG list statement. It is contained in the YANG container representing the conceptual table. The generated list uses the name of the row OBJECT-TYPE macro invocation. The clauses of the OBJECT-TYPE macro are translated as follows:

- o The SMIV2 SYNTAX clause is ignored.
- o The SMIV2 UNITS clause is ignored.
- o The SMIV2 MAX-ACCESS clause is ignored.
- o The SMIV2 STATUS clause is mapped to the YANG status statement. The generation of the YANG status statement is skipped if the value of the STATUS clause is current.
- o The SMIV2 DESCRIPTION clause is mapped to the YANG description statement.
- o The SMIV2 REFERENCE clause is mapped to the YANG reference statement.
- o The SMIV2 INDEX clause is mapped to the YANG key clause listing the columnar objects forming the key of the YANG list. If the same object appears more than once in the INDEX clause, append '<n>' to the duplicate object name(s) where '<n>' counts the occurrences of the object in the INDEX clause, starting from 2. Additional leaf statements must be created to define the leafs introduced.
- o If the SMIV2 INDEX clause contains the IMPLIED keyword, then an smiv2:implied statement is generated to record the name of the object preceded by the IMPLIED keyword. Refer to the YANG extension defined in [Section 10](#).
- o The value of the SMIV2 OBJECT-TYPE macro invocation is translated into an smiv2:oid statement. Refer to the YANG extension defined in [Section 10](#).

Within the list statement, YANG leaf statements are created for columnar objects as described in [Section 7.1](#). For objects listed in the SMIV2 INDEX clause that are not part of the conceptual table itself, YANG leaf statements of type leafref pointing to the referenced definition are created.

[7.4.](#) Example: ifTable of the IF-MIB

The translation of the definition of the ifTable of the IF-MIB [[RFC2863](#)] is shown below.

```
container ifTable {
  description
    "A list of interface entries. The number of entries is
    given by the value of ifNumber.";
  smiv2:oid "1.3.6.1.2.1.2.2";

  list ifEntry {
    key "ifIndex";
    description
      "An entry containing management information applicable to a
      particular interface.";
    smiv2:oid "1.3.6.1.2.1.2.2.1";

    leaf ifIndex {
      type if-mib:InterfaceIndex;
      description
        "A unique value, greater than zero, for each interface. It
        is recommended that values are assigned contiguously
        starting from 1. The value for each interface sub-layer
        must remain constant at least from one re-initialization of
        the entity's network management system to the next re-
        initialization.";
      smiv2:max-access "read-only";
      smiv2:oid "1.3.6.1.2.1.2.2.1.1";
    }

    // ...
  }
}
```

[7.5.](#) Example: ifRcvAddressTable of the IF-MIB

The translation of the definition of the ifRcvAddressTable of the IF-MIB [[RFC2863](#)] is shown below.

```
container ifRcvAddressTable {
  description
    "This table contains an entry for each address (broadcast,
    multicast, or uni-cast) for which the system will receive
    packets/frames on a particular interface, except as follows:

    - for an interface operating in promiscuous mode, entries
    are only required for those addresses for which the system
    would receive frames were it not operating in promiscuous
    mode.

    - for 802.5 functional addresses, only one entry is
    required, for the address which has the functional address
    bit ANDed with the bit mask of all functional addresses for
    which the interface will accept frames.

    A system is normally able to use any unicast address which
    corresponds to an entry in this table as a source address.";
  smiv2:oid "1.3.6.1.2.1.31.1.4";

  list ifRcvAddressEntry {
    key "ifIndex ifRcvAddressAddress";
    description
      "A list of objects identifying an address for which the
      system will accept packets/frames on the particular
      interface identified by the index value ifIndex.";
    smiv2:oid "1.3.6.1.2.1.31.1.4.1";

    leaf ifIndex {
      type leafref {
        path "/if-mib:IF-MIB/if-mib:ifTable" +
          "/if-mib:ifEntry/if-mib:ifIndex";
      }
    }
  }
}
```

```

}

leaf ifRcvAddressAddress {
  type yang:phys-address;
  description
    "An address for which the system will accept packets/frames
    on this entry's interface.";
  smiv2:max-access "not-accessible";
  smiv2:oid "1.3.6.1.2.1.31.1.4.1.1";
}

// ...
}
}

```

[7.6.](#) Example: alHostTable of the RMON2-MIB

The translation of the definition of the alHostTable of the RMON2-MIB [[RFC4502](#)] is shown below.

```

container alHostTable {
  description
    "A collection of statistics for a particular protocol from a
    particular network address that has been discovered on an
    interface of this device.

    The probe will populate this table for all protocols in the
    protocol directory table whose value of
    protocolDirHostConfig is equal to supportedOn(3), and
    will delete any entries whose protocolDirEntry is deleted or
    has a protocolDirHostConfig value of supportedOff(2).

    The probe will add to this table all addresses
    seen as the source or destination address in all packets with
    no MAC errors and will increment octet and packet counts in
    the table for all packets with no MAC errors. Further,
    entries will only be added to this table if their address
    exists in the nlHostTable and will be deleted from this table
    if their address is deleted from the nlHostTable.";
  smiv2:oid "1.3.6.1.2.1.16.16.1";
}

```

```
list alHostEntry {
  key "hlHostControlIndex alHostTimeMark protocolDirLocalIndex "
    + "nlHostAddress protocolDirLocalIndex_2";
  description
    "A conceptual row in the alHostTable.
```

The hlHostControlIndex value in the index identifies the hlHostControlEntry on whose behalf this entry was created. The first protocolDirLocalIndex value in the index identifies the network-layer protocol of the address. The nlHostAddress value in the index identifies the network-layer address of this entry. The second protocolDirLocalIndex value in the index identifies the protocol that is counted by this entry.

An example of the indexing in this entry is alHostOutPkts.1.783495.18.4.128.2.6.6.34.

Note that some combinations of index values may result in an index that exceeds 128 sub-identifiers in length, which exceeds the maximum for the SNMP protocol. Implementations should take care to avoid such combinations.";

```
smiv2:oid "1.3.6.1.2.1.16.16.1.1";
```

```
// ...
```

```
leaf protocolDirLocalIndex {
  type leafref {
    path "/rmon2-mib:RMON2-MIB/"
      + "rmon2-mib:protocolDirTable/"
      + "rmon2-mib:protocolDirEntryf/"
      + "rmon2-mib:protocolDirLocalIndex";
  }
}
```

```
// ...
```

```
leaf protocolDirLocalIndex_2 {
  type leafref {
    path "/rmon2-mib:RMON2-MIB/"
      + "rmon2-mib:protocolDirTable/"
```

```

        + "rmon2-mib:protocolDirEntry/"
        + "rmon2-mib:protocolDirLocalIndex";
    }
}

// ...
}
}

```

[7.7.](#) Augmenting Conceptual Tables Translation Rules

An OBJECT-TYPE macro invocation defining an augmenting conceptual table is translated to a YANG `smiv2:alias` statement. Refer to the YANG extension defined in [Section 10](#). The clauses of the macro are translated as follows:

- o The SMIV2 SYNTAX clause is ignored.
- o The SMIV2 UNITS clause is ignored.
- o The SMIV2 MAX-ACCESS clause is ignored.
- o The SMIV2 STATUS clause is mapped to the YANG status statement. The generation of the YANG status statement is skipped if the value of the STATUS clause is current.
- o The SMIV2 DESCRIPTION clause is mapped to the YANG description statement.

- o The SMIV2 REFERENCE clause is mapped to the YANG reference statement.
- o The value of the SMIV2 OBJECT-TYPE macro invocation is translated into an `smiv2:oid` statement. Refer to the YANG extension defined in [Section 10](#).

An OBJECT-TYPE macro invocation defining a conceptual row augmentation is translated to a YANG `smiv2:alias` statement and a YANG `augment` statement using the path to the augmented table as its argument. The clauses of the OBJECT-TYPE macro are translated as follows:

- o The SMIV2 SYNTAX clause is ignored.
- o The SMIV2 UNITS clause is ignored.
- o The SMIV2 MAX-ACCESS clause is ignored.
- o The SMIV2 STATUS clause is mapped to the YANG status statement. The generation of the YANG status statement is skipped if the value of the STATUS clause is current.
- o The SMIV2 DESCRIPTION clause is mapped to the YANG description statement.
- o The SMIV2 REFERENCE clause is mapped to the YANG reference statement.
- o The value of the SMIV2 OBJECT-TYPE macro invocation is translated into an smiv2:oid statement. Refer to the YANG extension defined in [Section 10](#).

Within the augment statement, YANG leaf statements are created as described in [Section 7.1](#).

[7.8](#). Example: ifXTable of the IF-MIB

The translation of the definition of the ifXTable of the IF-MIB [[RFC2863](#)] is shown below.

```
smiv2:alias "ifXTable" {
  description
    "A list of interface entries. The number of entries is
    given by the value of ifNumber. This table contains
    additional objects for the interface table.";
```

```

    smiv2:oid "1.3.6.1.2.1.31.1.1";
}

smiv2:alias "ifXEntry" {
  description
    "An entry containing additional management information
    applicable to a particular interface.";
  smiv2:oid "1.3.6.1.2.1.31.1.1.1";
}

augment "/if-mib:IF-MIB/if-mib:ifTable/if-mib:ifEntry" {
  description
    "An entry containing additional management information
    applicable to a particular interface.";
  smiv2:oid "1.3.6.1.2.1.31.1.1.1";

  leaf ifName {
    type snmpv2-tc:DisplayString;
    description
      "The textual name of the interface. The value of this
      object should be the name of the interface as assigned by
      the local device and should be suitable for use in commands
      entered at the device's `console`. This might be a text
      name, such as `le0` or a simple port number, such as `1`,
      depending on the interface naming syntax of the device. If
      several entries in the ifTable together represent a single
      interface as named by the device, then each will have the
      same value of ifName. Note that for an agent which responds
      to SNMP queries concerning an interface on some other
      (proxied) device, then the value of ifName for such an
      interface is the proxied device's local name for it.

      If there is no local name, or this object is otherwise not
      applicable, then this object contains a zero-length string.";
    smiv2:max-access "read-only";
    smiv2:oid "1.3.6.1.2.1.31.1.1.1.1";
  }

  // ...
}

```

[8.](#) Translation of the OBJECT-IDENTITY Macro

The SMIV2 uses invocations of the OBJECT-IDENTITY macro to define information about an OBJECT IDENTIFIER assignment. Invocations of the OBJECT-IDENTITY macro MUST be translated into YANG identity statements as detailed below.

[8.1.](#) OBJECT-IDENTITY Translation Rules

The name of the OBJECT-IDENTITY macro invocation is used as the name of the generated identity statement. The generated identity statement uses the `smiv2:object-identity` defined in [Section 10](#) as its base. The clauses of the SMIV2 OBJECT-IDENTITY macro are mapped to YANG statements as follows:

- o The SMIV2 STATUS clause is mapped to the YANG status statement. The generation of the YANG status statement is skipped if the value of the STATUS clause is current.
- o The SMIV2 DESCRIPTION clause is mapped to the YANG description statement.
- o The SMIV2 REFERENCE clause is mapped to the YANG reference statement.
- o The value of the SMIV2 OBJECT-IDENTITY macro invocation is translated into an `smiv2:oid` statement. Refer to the YANG extension defined in [Section 10](#).

[8.2.](#) Example: `diffServTBParamSimpleTokenBucket` of the DIFFSERV-MIB

The translation of the `diffServTBParamSimpleTokenBucket` of the DIFFSERV-MIB [[RFC3289](#)] is shown below.

```
identity diffServTBParamSimpleTokenBucket {
  base "smiv2:object-identity";
  description
    "Two Parameter Token Bucket Meter as described in the Informal
    Differentiated Services Model section 5.2.3.";
  smiv2:oid "1.3.6.1.2.1.97.3.1.1";
}
```

[9.](#) Translation of the NOTIFICATION-TYPE Macro

The SMIV2 provides the NOTIFICATION-TYPE macro to define event notifications. YANG provides the notification statement for the same purpose. Invocations of the NOTIFICATION-TYPE macro MUST be translated into YANG notification statements as detailed below.

[9.1.](#) NOTIFICATION-TYPE Translation Rules

The name of the NOTIFICATION-TYPE macro invocation is used as the name of the generated notification statement. The clauses of the NOTIFICATION-TYPE macro are mapped to YANG statements embedded in the notification statement as follows.

- o The SMIV2 OBJECTS clause is mapped to a sequence of YANG containers. For each object listed in the OBJECTS clause value, a YANG container statement is generated. The name of this container is the string "object- $\langle n \rangle$ ", where $\langle n \rangle$ is the position of the object in the value of the OBJECTS clause (first element has position 1). If the current object belongs to a conceptual table, then a sequence of leaf statements is generated for each INDEX object of the conceptual table. These leafs are named after the INDEX objects and of type leafref. Finally, a leaf statement is generated named after the current object. If the current object has a MAX-ACCESS of "read-only", "read-write" or "read-create", then the generated leaf is of type leafref. Otherwise, if the current object has a MAX-ACCESS of "accessible-for-notify", then a leaf is generated, following the itemized steps in [Section 7.1](#).
- o The SMIV2 STATUS clause is mapped to the YANG status statement. The generation of the YANG status statement is skipped if the value of the STATUS clause is current.
- o The SMIV2 DESCRIPTION clause is mapped to the YANG description statement.
- o The SMIV2 REFERENCE clause is mapped to the YANG reference statement.
- o The value of the SMIV2 NOTIFICATION-TYPE macro invocation is translated into an smiv2:oid statement. Refer to the YANG extension defined in [Section 10](#).

9.2. Example: linkDown NOTIFICATION-TYPE of IF-MIB

The translation of the linkDown notification of the IF-MIB [[RFC2863](#)] is shown below.

```
notification linkDown {
  description
    "A linkDown trap signifies that the SNMP entity, acting in
    an agent role, has detected that the ifOperStatus object for
    one of its communication links is about to enter the down
    state from some other state (but not from the notPresent
    state). This other state is indicated by the included value
    of ifOperStatus.";
  smiv2:oid "1.3.6.1.6.3.1.1.5.3";

  container object-1 {
    leaf ifIndex {
      type leafref {
        path "/if-mib:IF-MIB/if-mib:ifTable" +
              "/if-mib:ifEntry/if-mib:ifIndex";
      }
    }
  }

  container object-2 {
    leaf ifIndex {
      type leafref {
        path "/if-mib:IF-MIB/if-mib:ifTable" +
              "/if-mib:ifEntry/if-mib:ifIndex";
      }
    }
    leaf ifAdminStatus {
      type leafref {
        path "/if-mib:IF-MIB/if-mib:ifTable" +
              "/if-mib:ifEntry/if-mib:ifAdminStatus";
      }
    }
  }

  container object-3 {
```

```
leaf ifIndex {
  type leafref {
    path "/if-mib:IF-MIB/if-mib:ifTable" +
        "/if-mib:ifEntry/if-mib:ifIndex";
  }
}
leaf ifOperStatus {
  type leafref {
    path "/if-mib:IF-MIB/if-mib:ifTable" +
        "/if-mib:ifEntry/if-mib:ifOperStatus";
  }
}
}
```

```
}
```

10. YANG Language Extension Definition

This section defines some YANG extension statements that can be used to capture some information present in SMIV2 modules that is not translated into core YANG statements. The YANG module references [\[RFC2578\]](#) and [\[RFC2579\]](#).

```
<CODE BEGINS> file "ietf-yang-smiv2@2011-11-25.yang"
```

```
module ietf-yang-smiv2 {
```

```
  namespace "urn:ietf:params:xml:ns:yang:ietf-yang-smiv2";  
  prefix "smiv2";
```

```
  organization  
    "IETF NETMOD (NETCONF Data Modeling Language) Working Group";
```

```
  contact  
    "WG Web: <http://tools.ietf.org/wg/netmod/>  
    WG List: <mailto:netmod@ietf.org>
```

WG Chair: David Kessens
<mailto:david.kessens@nsn.com>

WG Chair: Juergen Schoenwaelder
<mailto:j.schoenwaelder@jacobs-university.de>

Editor: Juergen Schoenwaelder
<mailto:j.schoenwaelder@jacobs-university.de>";

description

"This module defines YANG extensions that are used to translate SMIV2 concepts into YANG.

Copyright (c) 2011 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Simplified BSD License set forth in [Section 4.c](#) of the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>).

This version of this YANG module is part of RFC XXXX; see the RFC itself for full legal notices."
// RFC Ed.: replace XXXX with actual RFC number and remove this note

Schoenwaelder

Expires July 22, 2012

[Page 27]

Internet-Draft

Translation of SMIV2 to YANG

January 2012

```
// RFC Ed.: please update the date to the date of publication
revision 2011-11-25 {
  description
    "Initial revision.";
  reference
    "RFC XXXX: Translation of SMIV2 MIB Modules to YANG Modules";
  // RFC Ed.: replace XXXX with actual RFC number and remove this note
}
```

```
identity object-identity {
  description
    "Base identity for all SMIV2 OBJECT-IDENTITYs.";
}
```

```
typedef opaque {
  type binary;
  description
    "The Opaque type supports the capability to pass arbitrary ASN.1
    syntax. A value is encoded using the ASN.1 Basic Encoding Rules
    into a string of octets. This, in turn, is encoded as an OCTET
    STRING, in effect 'double-wrapping' the original ASN.1 value.

    In the value set and its semantics, this type is equivalent to
    the Opaque type of the SMIV2. This type exists in the SMIV2
    solely for backward-compatibility reasons and this is also
    true for this YANG data type.";
  reference
    "RFC 2578: Structure of Management Information Version 2 (SMIV2)";
}
```

```
extension display-hint {
  argument "format";
  description
    "The display-hint statement takes as an argument the DISPLAY-HINT
    assigned to an SMIV2 textual convention.";
  reference
    "RFC2579: Textual Conventions for SMIV2";
}
```

```
extension max-access {
  argument "access";
  description
    "The max-access statement takes as an argument the MAX-ACCESS
    assigned to an SMIV2 object definition";
  reference
    "RFC2578: Structure of Management Information Version 2 (SMIV2)";
}
```

```
extension defval {
  argument "value";
  description
    "The defval statement takes as an argument a default value
    defined by an SMIV2 DEFVAL clause. Note that the value is in
    the SMIV2 value space defined by the SMIV2 syntax of the
    corresponding object and not in the YANG value space
```

```

    defined by the corresponding YANG data type.";
reference
  "RFC2578: Structure of Management Information Version 2 (SMIv2)";
}

extension implied {
  argument "index";
  description
    "If an SMIv2 INDEX object is preceded by the IMPLIED keyword, then
    the implied statement is present in the yang module and takes as
    an argument the name of the IMPLIED index object.";
  reference
    "RFC2578: Structure of Management Information Version 2 (SMIv2)";
}

extension alias {
  argument "descriptor";
  description
    "The alias statement introduces an SMIv2 descriptor. The body of
    the alias statement is expected to contain an oid statement that
    provides the numeric OID associated with the descriptor.";
  reference
    "RFC2578: Structure of Management Information Version 2 (SMIv2)";
}

extension oid {
  argument "value";
  description
    "The oid statement takes as an argument the object identifier
    assigned to an SMIv2 definition. The object identifier value
    is written in decimal dotted notation.";
  reference
    "RFC2578: Structure of Management Information Version 2 (SMIv2)";
}

extension subid {
  argument "value";
  description
    "The subid statement takes as an argument the last sub-identifier
    of the object identifier assigned to an SMIv2 definition. The
    sub-identifier value is a single positive decimal natural number.

```

The subid statement may not be used as a substatement to any top-level node in a YANG document. The subid substatement may be used only as a substatement to a node having a parent node defined with either a smiv2:oid or smiv2:subid substatement.";

reference

[RFC2578](#): Structure of Management Information Version 2 (SMIV2);

}

}

<CODE ENDS>

11. Implementing Configuration Data Nodes

The translation of SMIV2 MIB modules into YANG modules defined above is read-only. One reason is that the persistency models of the underlying protocols, SNMP and NETCONF, are quite different. With SNMP, the persistency of a writable object depends either on the object definition itself (i.e., the text in the DESCRIPTION clause) or the persistency properties of the conceptual row it is part of, sometimes controlled via a columnar object using the StorageType textual convention. With NETCONF, the persistency of configuration objects is determined by the properties of the underlying datastore. Furthermore, NETCONF as defined in [\[RFC6241\]](#) does not provide a standard operation to modify operational state. The <edit-config> and <copy-config> operations only manipulate configuration data. As a consequence of these considerations, it is not possible to generate YANG configuration data nodes from SMIV2 definitions in an automated way.

However, for selected SMIV2 objects where the SNMP and NETCONF persistency semantics are consistent, implementations may choose to implement some YANG data nodes generated from SMIV2 definitions as configuration data nodes. Such a deviation from the generated read-only YANG module should be formally documented in the form of a separate YANG module that uses YANG deviation statements to change the config property of the data nodes implemented as configuration data nodes from false to true. Deviations that change the config false property to true without any other changes to the semantics of the data node do not affect the compliance with the YANG module generated from an SMIV2 module.

11.1. Example: addressMapControlTable of RMON2-MIB

The following example demonstrates how certain columnar objects of the addressMapControlTable of the RMON2-MIB [\[RFC4502\]](#) can be turned into YANG configuration data nodes. Note that YANG deviations affect the property of the target node only and are not inherited downwards.

```
module acme-RMON2-MIB-deviations {  
  
    namespace "http://acme.example.com/RMON2-MIB-deviations";  
    prefix "acme-rmon2-devs";  
  
    import RMON2-MIB {
```

```
    prefix "rmon2-mib";
    revision-date 2006-05-02;
}

revision 2012-01-11 {
```

```
    description
        "First version.";
}

deviation "/rmon2-mib:RMON2-MIB" {
    deviate replace {
        config true;
    }
}

deviation "/rmon2-mib:RMON2-MIB/"
    + "rmon2-mib:addressMapControlTable" {
    deviate replace {
        config true;
    }
}

deviation "/rmon2-mib:RMON2-MIB/"
    + "rmon2-mib:addressMapControlTable/"
    + "rmon2-mib:addressMapControlEntry" {
    deviate replace {
        config true;
    }
}

deviation "/rmon2-mib:RMON2-MIB/"
    + "rmon2-mib:addressMapControlTable/"
    + "rmon2-mib:addressMapControlEntry/"
    + "rmon2-mib:addressMapControlIndex" {
    deviate replace {
        config true;
    }
}

deviation "/rmon2-mib:RMON2-MIB/"
    + "rmon2-mib:addressMapControlTable/"
```

```

        + "rmon2-mib:addressMapControlEntry/"
        + "rmon2-mib:addressMapControlDataSource" {
    deviate replace {
        config true;
    }
}

deviation "/rmon2-mib:RMON2-MIB/"
    + "rmon2-mib:addressMapControlTable/"
    + "rmon2-mib:addressMapControlEntry/"
    + "rmon2-mib:addressMapControlOwner" {
    deviate replace {

```

```

        config true;
    }
}
}

```

A NETCONF server that implements the RMON2-MIB module with these deviations would advertise the following capabilities in its <hello> message (where whitespace has been added for readability):

```

<capability>
  urn:ietf:params:xml:ns:yang:smiv2:RMON2-MIB?
  module=RMON2-MIB&
  revision=2006-05-02&
  deviations=acme-RMON2-MIB-deviations
</capability>
<capability>
  http://acme.example.com/RMON2-MIB-deviations?
  module=acme-RMON2-MIB-deviations&
  revision=2012-01-11
</capability>

```

12. IANA Considerations

This document registers two URIs in the IETF XML registry [[RFC3688](#)]. Following the format in [RFC 3688](#), the following registrations have been made.

URI: urn:ietf:params:xml:ns:yang:ietf-yang-smiv2

Registrant Contact: The NETMOD WG of the IETF.

XML: N/A, the requested URI is an XML namespace.

URI: urn:ietf:params:xml:ns:yang:smiv2

Registrant Contact: The NETMOD WG of the IETF.

XML: N/A, the requested URI is an XML namespace.

This document registers a YANG module in the YANG Module Names registry [[RFC6020](#)].

name: ietf-yang-smiv2
namespace: urn:ietf:params:xml:ns:yang:ietf-yang-smiv2
prefix: smiv2
reference: RFC XXXX

13. Security Considerations

This document defines a translation of SMIV2 MIB modules into YANG modules, enabling read-only access to data objects defined in SMIV2 MIB modules via NETCONF. The translation itself has no security impact on the Internet.

Users of translated SMIV2 models that have been published as RFCs should consult the security considerations of the respective RFCs. In addition, the security considerations for the NETCONF protocol [[RFC6241](#)] should be consulted to understand how NETCONF protects potentially sensitive information.

[14.](#) Acknowledgements

The editor wishes to thank the following individuals for providing helpful comments on various versions of this document: Andy Bierman, Martin Bjorklund, David Reid, and David Spakes.

[15.](#) References

15.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC2578] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Structure of Management Information Version 2 (SMIV2)", STD 58, [RFC 2578](#), April 1999.
- [RFC2579] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Textual Conventions for SMIV2", STD 58, [RFC 2579](#), April 1999.
- [RFC2580] McCloghrie, K., Perkins, D., and J. Schoenwaelder, "Conformance Statements for SMIV2", STD 58, [RFC 2580](#), April 1999.
- [RFC6020] Bjorklund, M., Ed., "YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF)", [RFC 6020](#), October 2010.
- [RFC6021] Schoenwaelder, J., "Common YANG Data Types", [RFC 6021](#), October 2010.

15.2. Informative References

- [RFC2863] McCloghrie, K. and F. Kastenholz, "The Interfaces Group MIB", [RFC 2863](#), June 2000.
- [RFC3289] Baker, F., Chan, K., and A. Smith, "Management Information Base for the Differentiated Services Architecture", [RFC 3289](#), May 2002.
- [RFC3584] Frye, R., Levi, D., Routhier, S., and B. Wijnen, "Coexistence between Version 1, Version 2, and Version 3 of the Internet-standard Network Management Framework", [RFC 3584](#), August 2003.
- [RFC3688] Mealling, M., "The IETF XML Registry", [BCP 81](#), [RFC 3688](#), January 2004.
- [RFC4181] Heard, C., "Guidelines for Authors and Reviewers of MIB Documents", [BCP 111](#), [RFC 4181](#), September 2005.
- [RFC4502] Waldbusser, S., "Remote Network Monitoring Management Information Base Version 2", [RFC 4502](#), May 2006.

- [RFC6241] Enns, R., Ed., Bjorklund, M., Ed., Schoenwaelder, J., Ed., and A. Bierman, Ed., "Network Configuration Protocol (NETCONF)", [RFC 6241](#), June 2011.

[Appendix A](#). Mapping of Well Known Types (normative)

SMIV2 Module: SNMPv2-SMI
SMIV2 Type: INTEGER (used as an enumeration)
YANG Type: enumeration

SMIV2 Module: SNMPv2-SMI
SMIV2 Type: INTEGER (used as a numeric type)
YANG Type: int32

SMIV2 Module: SNMPv2-SMI
SMIV2 Type: Integer32
YANG Type: int32

SMIV2 Module: SNMPv2-SMI
SMIV2 Type: OCTET STRING (used as a binary string)
YANG Type: binary

SMIV2 Module: SNMPv2-SMI
SMIV2 Type: OCTET STRING (used to hold UTF8/ASCII characters)
YANG Type: string

SMIV2 Module: SNMPv2-SMI
SMIV2 Type: OBJECT IDENTIFIER
YANG Module: ietf-yang-types
YANG Type: object-identifier-128

SMIV2 Module: SNMPv2-SMI
SMIV2 Type: BITS
YANG Type: bits

SMIV2 Module: SNMPv2-SMI
SMIV2 Type: IpAddress
YANG Module: ietf-inet-types
YANG Type: ipv4-address

SMIV2 Module: SNMPv2-SMI
SMIV2 Type: Counter32
YANG Module: ietf-yang-types

YANG Type: counter32

SMIv2 Module: SNMPv2-SMI

SMIv2 Type: Gauge32

YANG Module: ietf-yang-types

YANG Type: gauge32

SMIv2 Module: SNMPv2-SMI

SMIv2 Type: TimeTicks

YANG Module: ietf-yang-types

YANG Type: timeticks

SMIv2 Module: SNMPv2-SMI

SMIv2 Type: Counter64

YANG Module: ietf-yang-types

YANG Type: counter64

SMIv2 Module: SNMPv2-SMI

SMIv2 Type: Unsigned32

YANG Type: uint32

SMIv2 Module: SNMPv2-SMI

SMIv2 Type: Opaque

YANG Module: ietf-yang-smiv2

YANG Type: opaque

SMIv2 Module: SNMPv2-TC

SMIv2 Type: PhysAddress

YANG Module: ietf-yang-types

YANG Type: phys-address

SMIv2 Module: SNMPv2-TC

SMIv2 Type: MacAddress

YANG Module: ietf-yang-types

YANG Type: mac-address

SMIv2 Module: SNMPv2-TC

SMIv2 Type: TruthValue

YANG Type: boolean

SMIv2 Module: SNMPv2-TC

SMIv2 Type: TimeStamp
YANG Module: ietf-yang-types
YANG Type: timestamp

SMIv2 Module: RMON2-MIB
SMIv2 Type: ZeroBasedCounter32
YANG Module: ietf-yang-types
YANG Type: zero-based-counter32

SMIv2 Module: HCNUM-TC
SMIv2 Type: ZeroBasedCounter64
YANG Module: ietf-yang-types
YANG Type: zero-based-counter64

SMIv2 Module: HCNUM-TC
SMIv2 Type: CounterBasedGauge64

YANG Module: ietf-yang-types
YANG Type: gauge64

SMIv2 Module: INET-ADDRESS-MIB
SMIv2 Type: InetAutonomousSystemNumber
YANG Module: ietf-inet-types
YANG Type: as-number

SMIv2 Module: INET-ADDRESS-MIB
SMIv2 Type: InetVersion
YANG Module: ietf-inet-types
YANG Type: ip-version

SMIv2 Module: INET-ADDRESS-MIB
SMIv2 Type: InetPortNumber
YANG Module: ietf-inet-types
YANG Type: port-number

SMIv2 Module: DIFFSERV-DSCP-TC
SMIv2 Type: Dscp
YANG Module: ietf-inet-types
YANG Type: dscp

SMIv2 Module: IPV6-FLOW-LABEL-MIB
SMIv2 Type: IPv6FlowLabel

YANG Module: ietf-inet-types
YANG Type: ipv6-flow-label

SMIV2 Module: URI-TC-MIB
SMIV2 Type: Uri
YANG Module: ietf-inet-types
YANG Type: uri

[Appendix B](#). Module Prefix Generation (informative)

This section describes an algorithm to generate module prefixes, to be used in the import statements. The input of the prefix generation algorithm is a set of prefixes (usually derived from imported module names) and a specific module name to be converted into a prefix. The algorithm described below produces a prefix for the given module name that is unique within the set of prefixes.

YANG Module	Prefix
ietf-yang-types	yang
ietf-inet-types	inet
ietf-yang-smiv2	smiv2

Table 1: Special prefixes for well known YANG modules

- o First, some predefined translations mapping well known YANG modules to short prefixes are tried (see Table 1). If a fixed translation rule exists and leads to a conflict free prefix, then the fixed translation is used.
- o Otherwise, prefixes are generated by tokenizing a YANG module name, using hyphens as token separators. The tokens derived from the module name are converted to lowercase characters. The prefix then becomes the shortest sequence of tokens concatenated using hyphens as separators, which includes at least two tokens and which is unique among all prefixes used in the YANG module.

In the worst case, the prefix derived from an SMIV2 module name becomes the SMIV2 module name translated to lower-case. But on average, much shorter prefixes are generated.

Author's Address

Juergen Schoenwaelder
Jacobs University

Email: j.schoenwaelder@jacobs-university.de

