

Network Working Group
Internet-Draft
Intended status: Standards Track
Expires: August 3, 2012

A. Bierman
Netconf Central
M. Bjorklund
Tail-f Systems
January 31, 2012

YANG Data Model for System Management
draft-ietf-netmod-system-mgmt-00

Abstract

This document defines a YANG data model for the configuration and identification of the management system of a device.

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on August 3, 2012.

Copyright Notice

Copyright (c) 2012 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Internet-Draft

YANG System Management

January 2012

Table of Contents

| | | |
|------------------------|--|--------------------|
| 1. | Introduction | 3 |
| 1.1. | Terminology | 3 |
| 1.1.1. | Terms | 3 |
| 2. | Objectives | 4 |
| 2.1. | System Identification | 4 |
| 2.2. | System Time Management | 4 |
| 2.3. | User Authentication | 4 |
| 3. | System Data Model | 5 |
| 3.1. | System Identification | 5 |
| 3.2. | System Time Management | 5 |
| 3.3. | DNS Resolver Model | 5 |
| 3.4. | RADIUS Client Model | 6 |
| 3.5. | User Authentication Model | 6 |
| 3.5.1. | SSH Public Key Authentication | 7 |
| 3.5.2. | Local User Password Authentication | 7 |
| 3.5.3. | RADIUS Password Authentication | 7 |
| 3.6. | System Control | 8 |
| 4. | System YANG module | 9 |
| 5. | IANA Considerations | 35 |
| 6. | Security Considerations | 36 |
| 7. | Normative References | 38 |
| | Authors' Addresses | 40 |

1. Introduction

This document defines a YANG [[RFC6020](#)] data model for the configuration and identification of the management system of a device.

Devices that are managed by NETCONF and perhaps other mechanisms have common properties that need to be configured and monitored in a standard way.

The YANG module defined in this document provides the following features:

- o system administrative data configuration
- o system identification monitoring
- o system time-of-day configuration and monitoring
- o user authentication configuration
- o local users configuration

1.1. Terminology

The keywords "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [BCP 14](#), [[RFC2119](#)].

1.1.1. Terms

The following terms are used within this document:

- o system: This term refers to the embodiment of the entire set of management interfaces that a single NETCONF server is supporting

at a given moment. The set of physical entities managed by a single NETCONF server can be static or it can change dynamically.

[2.](#) Objectives

[2.1.](#) System Identification

There are many common properties used to identify devices, operating systems, software versions, etc. that need to be supported in the system data module. These objects are defined as operational data and intended to be specific to the device vendor.

Some user-configurable administrative strings are also provided such as the system location and description.

[2.2.](#) System Time Management

The management of the date and time used by the system need to be supported. Use of one or more NTP servers to automatically set the system date and time need to be possible. Utilization of the Timezone database [[I-D.lear-iana-timezone-database](#)] also need to be supported.

[2.3.](#) User Authentication

The authentication mechanism need to support password authentication over RADIUS, to support deployment scenarios with centralized authentication servers. Additionally, local users need to be supported, for scenarios when no centralized authentication server exists, or for situations where the centralized authentication server cannot be reached from the device.

Since the mandatory transport protocol for NETCONF is SSH [[RFC6242](#)] the authentication model need to support SSH's "publickey" and "password" authentication methods [[RFC4252](#)].

The model for authentication configuration should be flexible enough to support authentication methods defined by other standard documents or by vendors.

[3.](#) System Data Model

[3.1.](#) System Identification

The data model for system identification has the following structure:

```
+--rw system
  +--rw contact?      string
  +--rw name?         string
  +--rw location?     string
  +--ro platform
    +--ro os-name?    string
    +--ro os-release? string
    +--ro os-version? string
    +--ro machine?    string
    +--ro nodename?   string
```

[3.2.](#) System Time Management

The data model for system time management has the following structure:

```

+---rw system
  +---rw clock
    |   +---ro current-datetime?      yang:date-and-time
    |   +---ro boot-datetime?        yang:date-and-time
    |   +---rw (timezone)?
    |     +---:(timezone-location)
    |       |   +---rw timezone-location?    string
    |       +---:(timezone-name)
    |         |   +---rw timezone-name?      string
    |         +---:(timezone-utc-offset)
    |           +---rw timezone-utc-offset?  int16
  +---rw ntp
    +---rw use-ntp?      boolean
    +---rw ntp-server [address]
      +---rw address    inet:host
      +---rw enabled    boolean

```

[3.3.](#) DNS Resolver Model

The data model for configuration of the DNS resolver has the following structure:

```

+---rw system
  +---rw dns
    +---rw search*    inet:host
    +---rw server*    inet:ip-address
    +---rw options
      +---rw ndots?    uint8
      +---rw timeout?  uint8
      +---rw attempts? uint8

```

[3.4.](#) RADIUS Client Model

The data model for configuration of the RADIUS client has the following structure:

```

+---rw system

```

```

+--rw radius
  +--rw server [address]
    |   +--rw address          inet:host
    |   +--rw authentication-port?  inet:port-number
    |   +--rw shared-secret?      string
  +--rw options
    +--rw timeout?      uint8
    +--rw attempts?    uint8

```

3.5. User Authentication Model

This document defines three authentication methods for use with NETCONF:

- o publickey for local users over SSH
- o password for local users over any transport
- o password for RADIUS users over any transport

Additional methods can be defined by other standard documents or by vendors.

This document defines two optional YANG features, "local-users" and "radius-authentication", which the server advertises to indicate support for configuring local users on the device, and support for using RADIUS for authentication, respectively.

The authentication parameters defined in this document are primarily used to configure authentication of NETCONF users, but MAY also be used by other interfaces, e.g., a Command Line Interface or a Web-based User Interface.

The data model for user authentication has the following structure:

```

+--rw system
  +--rw authentication
    +--rw user-authentication-order*  identityref
    +--rw user [name]
      +--rw name          string
      +--rw password?    crypt-hash

```

```
+++rw ssh-dsa?    binary
+++rw ssh-rsa?    binary
```

[3.5.1.](#) SSH Public Key Authentication

If the NETCONF server advertises the "local-users" feature, configuration of local users and their SSH public keys is supported in the /system/authentication/user list.

Public key authentication is requested by the SSH client. If the "local-users" feature is supported, then when a NETCONF client starts an SSH session towards the server using the "publickey" authentication "method name" [[RFC4252](#)], the SSH server looks up the user name given in the SSH authentication request in the /system/authentication/user list, and verifies the key as described in [[RFC4253](#)].

[3.5.2.](#) Local User Password Authentication

If the NETCONF server advertises the "local-users" feature, configuration of local users and their passwords is supported in the /system/authentication/user list.

For NETCONF transport protocols that support password authentication, the leaf-list "user-authentication-order" is used to control if local user password authentication should be used.

In SSH, password authentication is requested by the client. Other NETCONF transport protocols MAY also support password authentication.

When local user password authentication is requested, the NETCONF transport looks up the user name provided by the client in the /system/ authentication/user list, and verifies the password.

[3.5.3.](#) RADIUS Password Authentication

If the NETCONF server advertises the "radius-authentication" feature, the device supports user authentication using RADIUS.

For NETCONF transport protocols that support password authentication,

the leaf-list "user-authentication-order" is used to control if

RADIUS password authentication should be used.

In SSH, password authentication is requested by the client. Other NETCONF transport protocols MAY also support password authentication.

[3.6.](#) System Control

Two protocol operations are included to restart or shutdown the system. The 'system-restart' operation can be used to restart the entire system (not just the NETCONF server). The 'system-shutdown' operation can be used to power off the entire system.

4. System YANG module

RFC Ed.: update the date below with the date of RFC publication and remove this note.

This YANG module imports YANG extensions from [[I-D.ietf-netconf-access-control](#)], imports YANG types from [[RFC6021](#)], and references [[RFC1321](#)], [[RFC2865](#)], [[RFC3418](#)], [[RFC5607](#)], [[IEEE-1003.1-2008](#)], and [[FIPS.180-3.2008](#)].

```
<CODE BEGINS> file "ietf-system@2012-01-31.yang"
```

```
module ietf-system {
  namespace "urn:ietf:params:xml:ns:yang:ietf-system";
  prefix "sys";

  import ietf-yang-types {
    prefix yang;
  }

  import ietf-inet-types {
    prefix inet;
  }

  import ietf-netconf-acm {
    prefix nacm;
  }

  organization
    "IETF NETMOD (NETCONF Data Modeling Language) Working Group";

  contact
    "WG Web:  <http://tools.ietf.org/wg/netmod/>
    WG List:  <mailto:netmod@ietf.org>

    WG Chair: David Kessens
               <mailto:david.kessens@nsn.com>

    WG Chair: Juergen Schoenwaelder
               <mailto:j.schoenwaelder@jacobs-university.de>

    Editor:   Andy Bierman
               <mailto:andy@netconfcentral.org>

    Editor:   Martin Bjorklund
               <mailto:mbj@tail-f.com>";
```

description

Internet-Draft

YANG System Management

January 2012

"This module contains a collection of YANG definitions for the configuration and identification of the management system of a device.

Copyright (c) 2011 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Simplified BSD License set forth in [Section 4.c](#) of the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>).

This version of this YANG module is part of RFC XXXX; see the RFC itself for full legal notices.";

// RFC Ed.: replace XXXX with actual RFC number and remove this
// note.

// RFC Ed.: remove this note
// Note: extracted from [draft-ietf-netmod-system-mgmt-00.txt](#)

// RFC Ed.: update the date below with the date of RFC publication
// and remove this note.

```
revision 2012-01-31 {  
  description  
    "Initial revision.";  
  reference  
    "RFC XXXX: A YANG Data Model for System Management";  
}
```

```
/*  
 * Typedefs  
 */
```

```
typedef timezone-name {  
  description  
    "List of available timezone enumerations.
```

```
Based on the referenced list, but non-unique names
have been changed so they are unique enumeration
identifiers.";
reference
"Wikipedia: http://en.wikipedia.org/wiki/"
+ "List_of_time_zone_abbreviations";
type enumeration {
enum ACDT {
description
```

```
    "Australian Central Daylight Time UTC+10:30";
}
enum ACST {
description
    "Australian Central Standard Time UTC+09:30";
}
enum ACT {
description
    "ASEAN Common Time UTC+08";
}
enum ADT {
description
    "Atlantic Daylight Time UTC-03";
}
enum AEDT {
description
    "Australian Eastern Daylight Time UTC+11";
}
enum AEST {
description
    "Australian Eastern Standard Time UTC+10";
}
enum AFT {
description
    "Afghanistan Time UTC+04:30";
}
enum AKDT {
description
    "Alaska Daylight Time UTC-08";
}
enum AKST {
description
```

```

        "Alaska Standard Time UTC-09";
    }
    enum AMST {
        description
        "Armenia Summer Time UTC+05";
    }
    enum AMT {
        description
        "Armenia Time UTC+04";
    }
    enum ART {
        description
        "Argentina Time UTC-03";
    }
    enum AST {
        description

```

```

        "Arab Standard Time (Kuwait, Riyadh) UTC+03";
    }
    enum AST-2 {
        description
        "Arabian Standard Time (Abu Dhabi, Muscat) UTC+04";
    }
    enum AST-3 {
        description
        "Arabic Standard Time (Baghdad) UTC+03";
    }
    enum AST-4 {
        description
        "Atlantic Standard Time UTC-04";
    }
    enum AWDT {
        description
        "Australian Western Daylight Time UTC+09";
    }
    enum AWST {
        description
        "Australian Western Standard Time UTC+08";
    }
    enum AZOST {
        description
        "Azores Standard Time UTC-01";
    }

```

```

}
enum AZT {
    description
        "Azerbaijan Time UTC+04";
}
enum BDT {
    description
        "Brunei Time UTC+08";
}
enum BIOT {
    description
        "British Indian Ocean Time UTC+06";
}
enum BIT {
    description
        "Baker Island Time UTC-12";
}
enum BOT {
    description
        "Bolivia Time UTC-04";
}
enum BRT {
    description

```

```

        "Brasilia Time UTC-03";
}
enum BST {
    description
        "Bangladesh Standard Time UTC+06";
}
enum BST-2 {
    description
        "British Summer Time (British Standard Time
        from Feb 1968 to Oct 1971) UTC+01";
}
enum BTT {
    description
        "Bhutan Time UTC+06";
}
enum CAT {
    description
        "Central Africa Time UTC+02";
}

```

```

}
enum CCT {
    description
        "Cocos Islands Time UTC+06:30";
}
enum CDT {
    description
        "Central Daylight Time (North America) UTC-05";
}
enum CEDT {
    description
        "Central European Daylight Time UTC+02";
}
enum CEST {
    description
        "Central European Summer Time (Cf. HAEC) UTC+02";
}
enum CET {
    description
        "Central European Time UTC+01";
}
enum CHADT {
    description
        "Chatham Daylight Time UTC+13:45";
}
enum CHAST {
    description
        "Chatham Standard Time UTC+12:45";
}
enum CIST {

```

```

    description
        "Clipperton Island Standard Time UTC-08";
}
enum CKT {
    description
        "Cook Island Time UTC-10";
}
enum CLST {
    description
        "Chile Summer Time UTC-03";
}

```

```

enum CLT {
    description
        "Chile Standard Time UTC-04";
}
enum COST {
    description
        "Colombia Summer Time UTC-04";
}
enum COT {
    description
        "Colombia Time UTC-05";
}
enum CST {
    description
        "Central Standard Time (North America) UTC-06";
}
enum CST-2 {
    description
        "China Standard Time UTC+08";
}
enum CST-3 {
    description
        "Central Standard Time (Australia) UTC+09:30";
}
enum CT {
    description
        "China Time UTC+08";
}
enum CVT {
    description
        "Cape Verde Time UTC-01";
}
enum CXT {
    description
        "Christmas Island Time UTC+07";
}
enum CHST {

```

```

    description
        "Chamorro Standard Time UTC+10";
}
enum DFT {

```



```

        description
            "AIX specific equivalent of Central European Time UTC+01";
    }
    enum EAST {
        description
            "Easter Island Standard Time UTC-06";
    }
    enum EAT {
        description
            "East Africa Time UTC+03";
    }
    enum ECT {
        description
            "Eastern Caribbean Time (does not recognise DST) UTC-04";
    }
    enum ECT-2 {
        description
            "Ecuador Time UTC-05";
    }
    enum EDT {
        description
            "Eastern Daylight Time (North America) UTC-04";
    }
    enum EEDT {
        description
            "Eastern European Daylight Time UTC+03";
    }
    enum EEST {
        description
            "Eastern European Summer Time UTC+03";
    }
    enum EET {
        description
            "Eastern European Time UTC+02";
    }
    enum EST {
        description
            "Eastern Standard Time (North America) UTC-05";
    }
    enum FJT {
        description
            "Fiji Time UTC+12";
    }
    enum FKST {

```

```
        description
            "Falkland Islands Summer Time UTC-03";
    }
    enum FKT {
        description
            "Falkland Islands Time UTC-04";
    }
    enum GALT {
        description
            "Galapagos Time UTC-06";
    }
    enum GET {
        description
            "Georgia Standard Time UTC+04";
    }
    enum GFT {
        description
            "French Guiana Time UTC-03";
    }
    enum GILT {
        description
            "Gilbert Island Time UTC+12";
    }
    enum GIT {
        description
            "Gambier Island Time UTC-09";
    }
    enum GMT {
        description
            "Greenwich Mean Time UTC";
    }
    enum GST {
        description
            "South Georgia and the South Sandwich Islands UTC-02";
    }
    enum GST-2 {
        description
            "Gulf Standard Time UTC+04";
    }
    enum GYT {
        description
            "Guyana Time UTC-04";
    }
    enum HADT {
        description
            "Hawaii-Aleutian Daylight Time UTC-09";
    }
```

enum HAEC {

```
    description
        "Heure Avancee d'Europe Centrale francised name for
        CEST UTC+02";
}
enum HAST {
    description
        "Hawaii-Aleutian Standard Time UTC-10";
}
enum HKT {
    description
        "Hong Kong Time UTC+08";
}
enum HMT {
    description
        "Heard and McDonald Islands Time UTC+05";
}
enum HST {
    description
        "Hawaii Standard Time UTC-10";
}
enum ICT {
    description
        "Indochina Time UTC+07";
}
enum IDT {
    description
        "Israeli Daylight Time UTC+03";
}
enum IRKT {
    description
        "Irkutsk Time UTC+08";
}
enum IRST {
    description
        "Iran Standard Time UTC+03:30";
}
enum IST {
    description
        "Indian Standard Time UTC+05:30";
}
```

```
enum IST-2 {  
    description  
        "Irish Summer Time UTC+01";  
}  
enum IST-3 {  
    description  
        "Israel Standard Time UTC+02";  
}
```

```
enum JST {  
    description  
        "Japan Standard Time UTC+09";  
}  
enum KRAT {  
    description  
        "Krasnoyarsk Time UTC+07";  
}  
enum KST {  
    description  
        "Korea Standard Time UTC+09";  
}  
enum LHST {  
    description  
        "Lord Howe Standard Time UTC+10:30";  
}  
enum LINT {  
    description  
        "Line Islands Time UTC+14";  
}  
enum MAGT {  
    description  
        "Magadan Time UTC+11";  
}  
enum MDT {  
    description  
        "Mountain Daylight Time (North America) UTC-06";  
}  
enum MET {  
    description  
        "Middle European Time Same zone as CET UTC+02";  
}  
enum MEST {
```

```

        description
            "Middle European Saving Time Same zone as CEST UTC+02";
    }
    enum MIT {
        description
            "Marquesas Islands Time UTC-09:30";
    }
    enum MSD {
        description
            "Moscow Summer Time UTC+04";
    }
    enum MSK {
        description
            "Moscow Standard Time UTC+03";
    }

```

```

    enum MST {
        description
            "Malaysian Standard Time UTC+08";
    }
    enum MST-2 {
        description
            "Mountain Standard Time (North America) UTC-07";
    }
    enum MST-3 {
        description
            "Myanmar Standard Time UTC+06:30";
    }
    enum MUT {
        description
            "Mauritius Time UTC+04";
    }
    enum MYT {
        description
            "Malaysia Time UTC+08";
    }
    enum NDT {
        description
            "Newfoundland Daylight Time UTC-02:30";
    }
    enum NFT {
        description

```

```

        "Norfolk Time[1] UTC+11:30";
    }
    enum NPT {
        description
            "Nepal Time UTC+05:45";
    }
    enum NST {
        description
            "Newfoundland Standard Time UTC-03:30";
    }
    enum NT {
        description
            "Newfoundland Time UTC-03:30";
    }
    enum NZDT {
        description
            "New Zealand Daylight Time UTC+13";
    }
    enum NZST {
        description
            "New Zealand Standard Time UTC+12";
    }

```

```

    enum OMST {
        description
            "Omsk Time UTC+06";
    }
    enum PDT {
        description
            "Pacific Daylight Time (North America) UTC-07";
    }
    enum PETT {
        description
            "Kamchatka Time UTC+12";
    }
    enum PHOT {
        description
            "Phoenix Island Time UTC+13";
    }
    enum PKT {
        description
            "Pakistan Standard Time UTC+05";
    }

```

```

}
enum PST {
    description
        "Pacific Standard Time (North America) UTC-08";
}
enum PST-2 {
    description
        "Philippine Standard Time UTC+08";
}
enum RET {
    description
        "Reunion Time UTC+04";
}
enum SAMT {
    description
        "Samara Time UTC+04";
}
enum SAST {
    description
        "South African Standard Time UTC+02";
}
enum SBT {
    description
        "Solomon Islands Time UTC+11";
}
enum SCT {
    description
        "Seychelles Time UTC+04";
}
}

```

```

enum SGT {
    description
        "Singapore Time UTC+08";
}
enum SLT {
    description
        "Sri Lanka Time UTC+05:30";
}
enum SST {
    description
        "Samoa Standard Time UTC-11";
}
}

```

```

enum SST-2 {
    description
        "Singapore Standard Time UTC+08";
}
enum TAHT {
    description
        "Tahiti Time UTC-10";
}
enum THA {
    description
        "Thailand Standard Time UTC+07";
}
enum UTC {
    description
        "Coordinated Universal Time UTC";
}
enum UYST {
    description
        "Uruguay Summer Time UTC-02";
}
enum UYT {
    description
        "Uruguay Standard Time UTC-03";
}
enum VET {
    description
        "Venezuelan Standard Time UTC-04:30";
}
enum VLAT {
    description
        "Vladivostok Time UTC+10";
}
enum WAT {
    description
        "West Africa Time UTC+01";
}

```

```

enum WEDT {
    description
        "Western European Daylight Time UTC+01";
}
enum WEST {

```



```

        description
            "Western European Summer Time UTC+01";
    }
    enum WET {
        description
            "Western European Time UTC";
    }
    enum WST {
        description
            "Western Standard Time UTC+08";
    }
    enum YAKT {
        description
            "Yakutsk Time UTC+09";
    }
    enum YEKT {
        description
            "Yekaterinburg Time UTC+05";
    }
}

typedef crypt-hash {
    type string {
        pattern "$0$.* | $1|5|6$[a-zA-Z0-9./]{2,16}$.*";
    }
    description
        "The crypt-hash type is used to store passwords using
        a hash function. This type is implemented in various UNIX
        systems as the function crypt(3).

```

When a clear text value is set to a leaf of this type, the server calculates a password hash, and stores the result in the datastore. Thus, the password is never stored in clear text.

When a leaf of this type is read, the stored password hash is returned.

A value of this type matches one of the forms:

```

    $0$<clear text password>
    $<id>$<salt>$<password hash>

```

The '\$0\$' prefix signals that the value is clear text. When such a value is received by the server, a hash value is calculated, and the string '\$<id>\$<salt>\$' is prepended to the result, where <salt> is a random 2-16 characters long salt used to generate the digest. This value is stored in the configuration data store.

If a value starting with '\$<id>\$<salt>\$' is received, the server knows that the value already represents a hashed value, and stores it as is in the data store.

When a server needs to verify a password given by a user, it finds the stored password hash string for that user, extracts the salt, and calculates the hash with the salt and given password as input. If the calculated hash value is the same as the stored value, the password given by the client is correct.

This type defines the following hash functions:

| id | hash function | feature |
|----|---------------|--------------------|
| 1 | MD5 | crypt-hash-md5 |
| 5 | SHA-256 | crypt-hash-sha-256 |
| 6 | SHA-512 | crypt-hash-sha-512 |

The server indicates support for the different hash functions by advertising the corresponding feature.";

reference

"IEEE Std 1003.1-2008 - crypt() function

Wikipedia: [http://en.wikipedia.org/wiki/Crypt_\(Unix\)](http://en.wikipedia.org/wiki/Crypt_(Unix))

[RFC 1321](#): The MD5 Message-Digest Algorithm

FIPS.180-3.2008: Secure Hash Standard";

}

/*

* Features

*/

feature radius {

description

"Indicates that the device can be configured as a RADIUS client.";

reference

"[RFC 2865](#): Remote Authentication Dial In User Service "

+ "(RADIUS)";

}

Internet-Draft

YANG System Management

January 2012

```
feature authentication {
  description
    "Indicates that the device can be configured
    to do authentication of users.";
}

feature local-users {
  if-feature authentication;
  description
    "Indicates that the device supports
    local user authentication.";
}

feature radius-authentication {
  if-feature radius;
  if-feature authentication;
  description
    "Indicates that the device supports user authentication over
    RADIUS.";
  reference
    "RFC 2865: Remote Authentication Dial In User Service (RADIUS)
    RFC 5607: Remote Authentication Dial-In User Service (RADIUS)
    Authorization for Network Access Server (NAS)
    Management";
}

feature crypt-hash-md5 {
  description
    "Indicates that the device supports the MD5
    hash function in 'crypt-hash' values";
  reference "RFC 1321: The MD5 Message-Digest Algorithm";
}

feature crypt-hash-sha-256 {
  description
    "Indicates that the device supports the SHA-256
    hash function in 'crypt-hash' values";
  reference "FIPS.180-3.2008: Secure Hash Standard";
}

feature crypt-hash-sha-512 {
  description
```

```

        "Indicates that the device supports the SHA-512
        hash function in 'crypt-hash' values";
        reference "FIPS.180-3.2008: Secure Hash Standard";
    }

    feature ntp {

```

```

        description
        "Indicates that the device can be configured
        to use one or more NTP servers to set the
        system date and time.";
    }

    feature timezone-location {
        description
        "Indicates that the local timezone on the device
        can be configured to use the TZ database
        to set the timezone and manage daylight savings time.";
        reference
        "TZ Database http://www.twinsun.com/tz/tz-link.htm
        Maintaining the Timezone Database
        draft-lear-iana-timezone-database-04.txt";
    }

    feature timezone-name {
        description
        "Indicates that the local timezone on the device
        can be configured using the timezone enumeration
        strings as an alias for an UTC offset.";
        reference
        "Wikipedia: http://en.wikipedia.org/wiki/
        + "List_of_time_zone_abbreviations";
    }

    /*
    * Identities
    */

    identity authentication-method {
        description
        "Base identity for user authentication methods.";
    }

```

```

identity radius {
  base authentication-method;
  description
    "Indicates user authentication using RADIUS.";
  reference
    "RFC 2865: Remote Authentication Dial In User Service (RADIUS)
    RFC 5607: Remote Authentication Dial-In User Service (RADIUS)
    Authorization for Network Access Server (NAS)
    Management";
}

identity local-users {

```

```

  base authentication-method;
  description
    "Indicates password-based authentication of locally
    configured users.";
}

/*
 * Top-level container
 */

container system {
  description
    "System group configuration.";

  leaf contact {
    type string {
      length "0..255";
    }
    default "";
    description
      "The administrator contact information for the system.";
    reference
      "RFC 3418 - Management Information Base (MIB) for the
      Simple Network Management Protocol (SNMP)
      SNMPv2-MIB.sysContact";
  }

  leaf name {

```

```

    type string {
        length "0..255";
    }
    default "";
    description
        "The administratively assigned system name.";
    reference
        "RFC 3418 - Management Information Base (MIB) for the
        Simple Network Management Protocol (SNMP)
        SNMPv2-MIB.sysName";
}

leaf location {
    type string {
        length "0..255";
    }
    default "";
    description
        "The system location";
    reference

```

```

        "RFC 3418 - Management Information Base (MIB) for the
        Simple Network Management Protocol (SNMP)
        SNMPv2-MIB.sysLocation";
}

container platform {
    config false;
    description
        "Contains vendor-specific information for
        identifying the system platform and operating system.";
    reference
        "IEEE Std 1003.1-2008 - sys/utsname.h";

    leaf os-name {
        type string;
        description
            "The name of the operating system in use,
            for example 'Linux'";
        reference
            "IEEE Std 1003.1-2008 - utsname.sysname";
    }
}

```

```

leaf os-release {
    type string;
    description
        "The current release level of the operating
        system in use. This string MAY indicate
        the OS source code revision.";
    reference
        "IEEE Std 1003.1-2008 - utsname.release";
}

leaf os-version {
    type string;
    description
        "The current version level of the operating
        system in use. This string MAY indicate
        the specific OS build date and target variant
        information.";
    reference
        "IEEE Std 1003.1-2008 - utsname.version";
}

leaf machine {
    type string;
    description
        "A vendor-specific identifier string representing
        the hardware in use.";

```

```

    reference
        "IEEE Std 1003.1-2008 - utsname.machine";
}

leaf nodename {
    type string;
    description
        "The host name of this system.";
    reference
        "IEEE Std 1003.1-2008 - utsname.nodename";
}
}

container clock {

```

```

description
  "Configuration and monitoring of the system
  date and time properties.";

leaf current-datetime {
  type yang:date-and-time;
  config false;
  description
    "The current system date and time.";
}

leaf boot-datetime {
  type yang:date-and-time;
  config false;
  description
    "The system date and time when the NETCONF
    server last restarted.";
}

choice timezone {
  description
    "Configure the system timezone information.";

  leaf timezone-location {
    if-feature timezone-location;
    type string;
    description
      "The TZ database location identifier string
      to use for the system, such as 'Europe/Stockholm'.";
  }

  leaf timezone-name {
    if-feature timezone-name;
    type timezone-name;
  }
}

```

```

description
  "The timezone enumeration string to use
  for the system, such as 'CET'.";
}

leaf timezone-utc-offset {
  type int16 {

```



```

        range "-1439 .. 1439";
    }
    description
        "The number of minutes to add to UTC time to
        identify the timezone for this system.
        For example, 'UTC - 8:00 hours' would be
        represented as '-480'.";
    }
}

container ntp {
    if-feature ntp;

    description
        "Configuration of the NTP client.";

    leaf use-ntp {
        type boolean;
        default true;
        description
            "Indicates that the system should attempt
            to synchronize the system clock with an
            NTP server from the 'ntp-server' list.";
    }

    list ntp-server {
        key address;
        ordered-by user;
        description
            "List of NTP servers to use for
            system clock synchronization. If 'use-ntp'
            is 'true', then the system will attempt to
            contact and utilize the specified NTP servers.
            The user specified order indicates the server priority.";

        leaf address {
            type inet:host;
            description
                "The IP address or domain name of the NTP server.";
        }
    }
}

```

```

    leaf enabled {
        type boolean;
        default true;
        description
            "Indicates whether this server is enabled for use or
            not.";
    }
}

container dns {
    description
        "Configuration of the DNS resolver.";

    leaf-list search {
        type inet:host;
        ordered-by user;
        description
            "An ordered list of domains to search when resolving
            a host name.";
    }
    leaf-list server {
        type inet:ip-address;
        ordered-by user;
        description
            "Addresses of the name servers that the resolver should
            query.

            Implementations MAY limit the number of entries in this
            leaf list.";
    }
    container options {
        description
            "Resolver options. The set of available options has been
            limited to those that are generally available across
            different resolver implementations, and generally
            useful.";
        leaf ndots {
            type uint8;
            default "1";
            description
                "This parameter sets a threshold for the number of dots
                which must appear in a query request before an initial
                absolute query will be made.";
        }
        leaf timeout {
            type uint8;
            units "seconds";
        }
    }
}

```

```
        default "5";
        description
            "The amount of time the resolver will wait for a
             response from a remote name server before
             retrying the query via a different name server.";
    }
    leaf attempts {
        type uint8;
        default "2";
        description
            "The number of times the resolver will send a query to
             its name servers before giving up and returning an
             error to the calling application.";
    }
}

container radius {
    if-feature radius;

    description
        "Configuration of the RADIUS client.";

    list server {
        key address;
        ordered-by user;
        description
            "List of RADIUS servers used by the device.";

        leaf address {
            type inet:host;
            description
                "The address of the RADIUS server.";
        }
        leaf authentication-port {
            type inet:port-number;
            default "1812";
            description
                "The port number of the RADIUS server.";
        }
        leaf shared-secret {
            type string;
            nacm:default-deny-all;
        }
    }
}
```

```
description
  "The shared secret which is known to both the RADIUS
  client and server.";
reference
  "RFC 2865: Remote Authentication Dial In User Service";
```

```
    }
  }
  container options {
    description
      "RADIUS client options.";

    leaf timeout {
      type uint8;
      units "seconds";
      default "5";
      description
        "The number of seconds the device will wait for a
        response from a RADIUS server before trying with a
        different server.";
    }
    leaf attempts {
      type uint8;
      default "2";
      description
        "The number of times the device will send a query to
        the RADIUS servers before giving up.";
    }
  }
}

container authentication {
  nacm:default-deny-write;
  if-feature authentication;

  description
    "The authentication configuration subtree.";

  leaf-list user-authentication-order {
    type identityref {
      base authentication-method;
    }
  }
}
```

```

must '(. = "sys:radius" and ../../radius/server) or'
  + '(. != "sys:radius")' {
  error-message
    "When 'radius' is used, a radius server"
  + " must be configured.";
}
ordered-by user;

description
  "When the device authenticates a user with
  a password, it tries the authentication methods in this
  leaf-list in order.  If authentication with one method

```

```

  fails, the next method is used.  If no method succeeds,
  the user is denied access.

  If the 'radius-authentication' feature is advertised by
  the NETCONF server, the 'radius' identity can be added to
  this list.

  If the 'local-users' feature is advertised by the
  NETCONF server, the 'local-users' identity can be
  added to this list.";
}

list user {
  if-feature local-users;
  key name;
  description
    "The list of local users configured on this device.";

  leaf name {
    type string;
    description
      "The user name string identifying this entry.";
  }
  leaf password {
    type crypt-hash;
    description
      "The password for this entry.";
  }
  leaf ssh-dsa {

```

```

        type binary;
        description
            "The public DSA key for this entry.";
    }
    leaf ssh-rsa {
        type binary;
        description
            "The public RSA key for this entry.";
    }
}

rpc set-current-datetime {
    nacm:default-deny-all;
    description
        "Manually set the /system/clock/current-datetime leaf
        to the specified value."
}

```

```

        If the /system/ntp/ntp-in-use leaf exists and
        is set to 'true', then this operation will
        fail with error-tag 'operation-failed',
        and error-app-tag value of 'ntp-active';
    input {
        leaf current-datetime {
            type yang:date-and-time;
            mandatory true;
            description
                "The current system date and time.";
        }
    }
}

rpc system-restart {
    nacm:default-deny-all;
    description
        "Request that the entire system be restarted immediately.
        A server SHOULD send an rpc reply to the client before
        restarting the system.";
}

```

```
rpc system-shutdown {
  nacm:default-deny-all;
  description
    "Request that the entire system be shut down immediately.
    A server SHOULD send an rpc reply to the client before
    shutting down the system.";
}

}

<CODE ENDS>
```

[5.](#) IANA Considerations

This document registers a URI in the IETF XML registry [[RFC3688](#)]. Following the format in [RFC 3688](#), the following registration is requested to be made.

URI: urn:ietf:params:xml:ns:yang:ietf-system

Registrant Contact: The NETMOD WG of the IETF.

XML: N/A, the requested URI is an XML namespace.

This document registers a YANG module in the YANG Module Names registry [[RFC6020](#)].

name: ietf-system
namespace: urn:ietf:params:xml:ns:yang:ietf-system
prefix: sys
reference: RFC XXXX

6. Security Considerations

The YANG module defined in this memo is designed to be accessed via the NETCONF protocol [[RFC6241](#)]. The lowest NETCONF layer is the secure transport layer and the mandatory-to-implement secure transport is SSH [[RFC6242](#)].

There are a number of data nodes defined in this YANG module which

are writable/creatable/deletable (i.e., config true, which is the default). These data nodes may be considered sensitive or vulnerable in some network environments. Write operations (e.g., edit-config) to these data nodes without proper protection can have a negative effect on network operations. These are the subtrees and data nodes and their sensitivity/vulnerability:

- o /system/clock/timezone: This choice contains the objects used to control the timezone used by the device.
- o /system/ntp: This container contains the objects used to control the Network Time Protocol servers used by the device.
- o /system/dns: This container contains the objects used to control the Domain Name System servers used by the device.
- o /system/radius: This container contains the objects used to control the Remote Authentication Dial-In User Service servers used by the device.
- o /system/authentication/user-authentication-order: This leaf controls how user login attempts are authenticated by the device.
- o /system/authentication/user: This list contains the local users enabled on the system.

Some of the readable data nodes in this YANG module may be considered sensitive or vulnerable in some network environments. It is thus important to control read access (e.g., via get, get-config, or notification) to these data nodes. These are the subtrees and data nodes and their sensitivity/vulnerability:

- o /system/platform: This container has objects which help identify the specific NETCONF server and/or operating system implementation used on the device.

Some of the RPC operations in this YANG module may be considered sensitive or vulnerable in some network environments. It is thus important to control access to these operations. These are the operations and their sensitivity/vulnerability:

- o set-current-datetime: Changes the current date and time on the

device.

- o system-restart: Reboots the device.
- o system-shutdown: Shuts down the device.

7. Normative References

[FIPS.180-3.2008]

National Institute of Standards and Technology, "Secure Hash Standard", FIPS PUB 180-3, October 2008, <http://csrc.nist.gov/publications/fips/fips180-3/fips180-3_final.pdf>.

[I-D.ietf-netconf-access-control]

Bierman, A. and M. Bjorklund, "Network Configuration Protocol (NETCONF) Access Control Model", [draft-ietf-netconf-access-control-05](#) (work in progress), October 2011.

[I-D.lear-iana-timezone-database]

Lear, E. and P. Eggert, "IANA Procedures for Maintaining the Timezone Database", [draft-lear-iana-timezone-database-04](#) (work in progress), May 2011.

[IEEE-1003.1-2008]

Institute of Electrical and Electronics Engineers, "POSIX.1-2008", IEEE Standard 1003.1, March 2008.

[RFC1321] Rivest, R., "The MD5 Message-Digest Algorithm", [RFC 1321](#), April 1992.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.

[RFC2865] Rigney, C., Willens, S., Rubens, A., and W. Simpson, "Remote Authentication Dial In User Service (RADIUS)", [RFC 2865](#), June 2000.

[RFC3418] Presuhn, R., "Management Information Base (MIB) for the Simple Network Management Protocol (SNMP)", STD 62, [RFC 3418](#), December 2002.

[RFC3688] Mealling, M., "The IETF XML Registry", [BCP 81](#), [RFC 3688](#), January 2004.

[RFC4252] Ylonen, T. and C. Lonvick, "The Secure Shell (SSH) Authentication Protocol", [RFC 4252](#), January 2006.

[RFC4253] Ylonen, T. and C. Lonvick, "The Secure Shell (SSH) Transport Layer Protocol", [RFC 4253](#), January 2006.

[RFC5607] Nelson, D. and G. Weber, "Remote Authentication Dial-In

Bierman & Bjorklund

Expires August 3, 2012

[Page 38]

Internet-Draft

YANG System Management

January 2012

User Service (RADIUS) Authorization for Network Access Server (NAS) Management", [RFC 5607](#), July 2009.

[RFC6020] Bjorklund, M., "YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF)", [RFC 6020](#), October 2010.

[RFC6021] Schoenwaelder, J., "Common YANG Data Types", [RFC 6021](#), October 2010.

[RFC6241] Enns, R., Ed., Bjorklund, M., Ed., Schoenwaelder, J., Ed., and A. Bierman, Ed., "Network Configuration Protocol (NETCONF)", [RFC 6241](#), June 2011.

[RFC6242] Wasserman, M., "Using the NETCONF Protocol over Secure Shell (SSH)", [RFC 6242](#), June 2011.

Authors' Addresses

Andy Bierman
Netconf Central

Email: andy@netconfcentral.org

Martin Bjorklund
Tail-f Systems

Email: mbj@tail-f.com

