

Netmod  
Internet-Draft  
Intended status: Standards Track  
Expires: September 30, 2021

B. Lengyel  
Ericsson  
B. Claise  
Cisco Systems, Inc.  
March 29, 2021

YANG Instance Data File Format  
draft-ietf-netmod-yang-instance-file-format-13

## Abstract

There is a need to document data defined in YANG models when a live server is unavailable. Data is often needed at design or implementation time or needed when a live running server is unavailable. This document specifies a standard file format for YANG instance data, which follows the syntax and semantics of existing YANG models, and annotates it with metadata.

## Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on September 30, 2021.

## Copyright Notice

Copyright (c) 2021 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in [Section 4.e](#) of

Internet-Draft

YANG Instance Data

March 2021

the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

<a href="#">1. Introduction</a>	2
<a href="#">1.1. Terminology</a>	3
<a href="#">1.2. Principles</a>	4
<a href="#">1.3. Delivery of Instance Data</a>	4
<a href="#">1.4. Data Life cycle</a>	5
<a href="#">2. Instance Data File Format</a>	5
<a href="#">2.1. Specifying the Content Schema</a>	7
<a href="#">2.1.1. Inline Method</a>	7
<a href="#">2.1.2. Simplified-Inline Method</a>	8
<a href="#">2.1.3. URI Method</a>	8
<a href="#">2.2. Examples</a>	8
<a href="#">2.2.1. Documentation of server capabilities</a>	8
<a href="#">2.2.2. Preloading default configuration data</a>	10
<a href="#">2.2.3. Storing diagnostics data</a>	11
<a href="#">3. YANG Instance Data Model</a>	12
<a href="#">3.1. Tree Diagram</a>	12
<a href="#">3.2. YANG Model</a>	13
<a href="#">4. Security Considerations</a>	19
<a href="#">5. IANA Considerations</a>	20
<a href="#">5.1. URI Registration</a>	20
<a href="#">5.2. YANG Module Name Registration</a>	20
<a href="#">6. Acknowledgments</a>	20
<a href="#">7. References</a>	20
<a href="#">7.1. Normative References</a>	20
<a href="#">7.2. Informative References</a>	22
<a href="#">Appendix A. Changes between revisions</a>	23
<a href="#">Appendix B. Backwards Compatibility</a>	25
<a href="#">Appendix C. Detailed Use Cases</a>	25
<a href="#">C.1. Use Case 1: Early Documentation of Server Capabilities</a>	26
<a href="#">C.2. Use Case 2: Preloading Data</a>	27
<a href="#">C.3. Use Case 3: Documenting Factory Default Settings</a>	27
<a href="#">Authors' Addresses</a>	27

## [1. Introduction](#)

There is a need to document data defined in YANG models when a live server is unavailable. Data is often needed at design or implementation time or needed when a live running server is

unavailable. To facilitate this offline delivery of data, this document specifies a standard format for YANG instance data sets and YANG instance data files. The format of the instance data set is defined by the "ietf-yang-instance-data" YANG module, see [Section 3](#).

The YANG data model in this document conforms to the Network Management Datastore Architecture (NMDA) defined in [[RFC8342](#)]

The following is a list of already implemented and potential use cases.

UC1 Documentation of server capabilities

UC2 Preloading default configuration data

UC3 Documenting Factory Default Settings

UC4 Storing the configuration of a device, e.g., for backup, archive or audit purposes

UC5 Storing diagnostics data

UC6 Allowing YANG instance data to potentially be carried within other IPC message formats

UC7 Default instance data used as part of a templating solution

UC8 Providing data examples in RFCs or internet drafts

In [Appendix C](#) describes the first three use cases in detail.

There are many and varied use cases where YANG instance data could be used. This document does not limit future uses of instance data sets, so specifying how and when to use YANG instance data is out of scope for this document. It is anticipated that other documents will define specific use cases. Use cases are listed only as examples.

### [1.1.](#) Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and

"OPTIONAL" in this document are to be interpreted as described in [BCP 14](#) [[RFC2119](#)] [[RFC8174](#)] when, and only when, they appear in all capitals, as shown here.

Instance Data: A collection of instantiated data nodes.

Instance Data Set: A named set of data items annotated with metadata that can be used as instance data in a YANG data tree.

Instance Data File: A file containing an instance data set formatted according to the rules described in this document.

Lengyel & Claise

Expires September 30, 2021

[Page 3]

---

Internet-Draft

YANG Instance Data

March 2021

Content-schema: A set of YANG modules with their revision, supported features, and deviations for which the instance data set contains instance data.

Content defining YANG module: an individual YANG module that is part of the content-schema.

The term "server" is used as defined in [[RFC8342](#)].

## 1.2. Principles

The following is a list of the basic principles of the instance data format:

- P1 Two standard formats shall be defined based on the XML and JSON encodings.
- P2 Instance data shall reuse existing encoding rules for YANG defined data.
- P3 Metadata about the instance data set ([Section 2](#), Paragraph 9) shall be defined.
- P4 A YANG instance data set shall be allowed to contain data for multiple YANG modules.
- P5 Instance data shall be allowed to contain configuration data, state data, or a mix of the two.

- P6 Partial data sets shall be allowed.
- P7 The YANG instance data format shall be usable for any data for which YANG module(s) are defined and available to the reader, independent of whether the module is implemented by a server.
- P8 It shall be possible to report the identity of the datastore with which the instance data set is associated.

### 1.3. Delivery of Instance Data

Instance data sets that are produced as a result of some sort of specification or design effort may be available without the need for a live server e.g., via download from the vendor's website, or in any other way that product documentation is distributed.

Other instance data sets may be read from or produced by the YANG server itself e.g., UC5 documenting diagnostic data.

---

Lengyel & Claise

Expires September 30, 2021

[Page 4]

---

Internet-Draft

YANG Instance Data

March 2021

### 1.4. Data Life cycle

A YANG instance data set is created at a specific point of time. If the data changes afterwards, this is not represented in the instance data set anymore. The current values may be retrieved at run-time via NETCONF/RESTCONF or received e.g., in YANG-Push notifications.

Whether the instance data changes and if so, when and how, should be described either in the instance data set's description statement or in some other implementation specific manner.

## 2. Instance Data File Format

A YANG instance data file MUST contain a single instance data set and no additional data.

The format of the instance data set is defined by the "ietf-yang-instance-data" YANG module. It is made up of a header part and content-data. The header part carries metadata for the instance data set. The content-data, defined as an anydata data node, carries the instance data that the user wants to document/provide. The syntax and semantics of content-data is defined by the content-schema.

Two formats are specified based on the XML and JSON YANG encodings. Later as other YANG encodings (e.g., CBOR) are defined, further instance data formats may be specified.

The content-data part MUST conform to the content-schema, while allowing for the exceptions listed below. The content-data part SHALL follow the encoding rules defined in [[RFC7950](#)] for XML and [[RFC7951](#)] for JSON and MUST use UTF-8 character encoding. Content-data MAY include:

- o metadata as defined by [[RFC7952](#)].
- o a default attribute as defined in [[RFC6243](#) section 6. and in [[RFC8040](#) section 4.8.9].
- o origin metadata as specified in [[RFC8526](#)] and [[RFC8527](#)]
- o implementation specific metadata relevant to individual data nodes. Unknown metadata MUST be ignored by users of instance data, allowing it to be used later for other purposes.

An instance data set MAY contain data for any number of YANG modules; if needed it MAY carry the complete configuration and state data for a server. Default values SHOULD NOT be included.

Configuration ("config true") and operational state data ("config false") MAY be mixed in the instance data file.

Instance data files MAY contain partial data sets. This means "mandatory", "min-elements", "require-instance true", "must" and "when" constrains MAY be violated.

The name of the instance data file SHOULD be of the form:

```
instance-data-set-name ['@' ( revision-date / timestamp ) ]  
                      ( '.xml' / '.json' )
```

E.g., acme-router-modules@2018-01-25.xml

E.g., acme-router-modules@2018-01-25T15\_06\_34\_3+01\_00.json

If the leaf "name" is present in the instance data header, its value SHOULD be used for the "instance-data-set-name". If the "revision-date" is present in both the filename and in the instance data header, the revision date in the file name MUST be set to the latest revision date inside the instance data set. If the "timestamp" is present both in the filename and in the instance data header, the timestamp in the file name SHOULD be set to the timestamp inside the instance data set; any colons, if present, shall be replaced by underscores.

Metadata, information about the data set itself SHOULD be included in the instance data set. Some metadata items are defined in the YANG module "ietf-yang-instance-data", but other items MAY be used.

Metadata MUST include:

- \* Version of the YANG Instance Data format

Metadata SHOULD include:

- \* Name of the data set
- \* Content schema specification (i.e., the "content-schema" node)
- \* Description of the instance data set. The description SHOULD contain information whether and how the data can change during the lifetime of the server.

## 2.1. Specifying the Content Schema

To properly understand and use an instance data set, the user needs to know the content-schema. One of the following methods SHOULD be used:

Inline method: Include the needed information as part of the instance data set.

Simplified-Inline method: Include the needed information as part of the instance data set; short specification.

URI method: Include a URI that references another YANG instance data file. This instance data file will use the same content-schema as the referenced YANG instance data file. (if you don't want to repeat the info again and again)

External Method: Do not include the "content-schema" node; the user needs to obtain the information through external documents.

Additional methods e.g., a YANG-package based solution may be added later.

Note, the specified content-schema only indicates the set of modules that were used to define this YANG instance data set. Sometimes instance data may be used for a server supporting a different YANG module set (e.g., for the "Preloading default configuration data" use-case, UC2 in [Section 1](#), the instance data set may not be updated every time the YANG modules on the server are updated). Whether an instance data set originally defined using a specific content-schema is usable with a different other schema depends on many factors including the amount of differences and the compatibility between the original and the other schema, considering modules, revisions, features, deviations, the scope of the instance data, etc.

### [2.1.1.](#) Inline Method

One or more inline-module elements define YANG module(s) used to specify the content defining YANG modules.

E.g., ietf-yang-library@2016-06-21

The `anydata` inline-schema carries instance data (conforming to the inline-modules) that actually specifies the content defining YANG modules including revision, supported features, deviations and any relevant additional data (e.g., revision labels, described by [[I-D.ietf-netmod-yang-module-versioning](#)]) as alternative to the

Figure 2.

### 2.1.2. Simplified-Inline Method

The instance data set contains a list of content defining YANG modules including the revision date for each. Usage of this method implies that the modules are used without any deviations and with all features supported. An example of the "simplified-inline" method is provided in Figure 3.

### 2.1.3. URI Method

The "same-schema-as-file" leaf SHALL contain a URI that references another YANG instance data file. The current instance data file will use the same content schema as the referenced file.

The referenced instance data file MAY have no content-data if it is used solely for specifying the content-schema.

If a referenced instance data file is unavailable, content-schema is unknown.

The URI method is advantageous when the user wants to avoid the overhead of specifying the content-schema in each instance data file: E.g., In UC6, when the system creates a diagnostic file every minute to document the state of the server.

An example of the "URI" method is provided in Figure 4.

## 2.2. Examples

### 2.2.1. Documentation of server capabilities

The example reflects UC1 in [Section 1](#). It provides a list of supported YANG modules and NETCONF capabilities for a server. It uses the "inline" method to specify the content-schema.

The example uses artwork folding [[RFC8792](#)].

```
===== NOTE: '\' line wrapping per BCP XXX (RFC XXXX) =====  
<?xml version="1.0" encoding="UTF-8"?>  
<instance-data-set xmlns=\n    "urn:ietf:params:xml:ns:yang:ietf-yang-instance-data">\n    <name>acme-router-modules</name>\n    <content-schema>\n        <inline-content-schema>
```

```
<inline-module>ietf-yang-library@2016-06-21</inline-module>
<inline-schema>
  <modules-state \>
    xmlns="urn:ietf:params:xml:ns:yang:ietf-yang-library">
    <module>
      <name>ietf-yang-library</name>
      <revision>2016-06-21</revision>
    </module>
    <module>
      <name>ietf-netconf-monitoring</name>
      <revision>2010-10-04</revision>
    </module>
  </modules-state>
</inline-schema>
</inline-content-schema>
</content-schema>
<revision>
  <date>1956-10-23</date>
  <description>Initial version</description>
</revision>
<description>Defines the minimal set of modules that any \
  acme-router will contain.</description>
<contact>info@acme.com</contact>
<content-data>
  <modules-state \>
    xmlns="urn:ietf:params:xml:ns:yang:ietf-yang-library">
    <module>
      <name>ietf-yang-library</name>
      <revision>2016-06-21</revision>
      <namespace>\>
        urn:ietf:params:xml:ns:yang:ietf-yang-library\>
      </namespace>
      <conformance-type>implement</conformance-type>
    </module>
    <module>
      <name>ietf-system</name>
      <revision>2014-08-06</revision>
      <namespace>urn:ietf:params:xml:ns:yang:ietf-system</namespace>
      <feature>sys:authentication</feature>
      <feature>sys:local-users</feature>
      <deviation>
        <name>acme-system-ext</name>
        <revision>2018-08-06</revision>
      </deviation>
      <conformance-type>implement</conformance-type>
    </module>
```

```
<module>
  <name>ietf-netconf-monitoring</name>
```

```
<revision>2010-10-04</revision>
<namespace> \
  urn:ietf:params:xml:ns:yang:ietf-netconf-monitoring \
</namespace>
<conformance-type>implement</conformance-type>
</module>
<module>
  <name>ietf-yang-types</name>
  <revision>2013-07-15</revision>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-yang-types \
    </namespace>
  <conformance-type>import</conformance-type>
</module>
<module>
  <name>acme-system-ext</name>
  <revision>2018-08-06</revision>
  <namespace>urn:rdns:acme.com:oammodel:acme-system-ext \
    </namespace>
  <conformance-type>implement</conformance-type>
</module>
</modules-state>
<netconf-state \
  xmlns="urn:ietf:params:xml:ns:yang:ietf-netconf-monitoring">
  <capabilities>
    <capability> \
      urn:ietf:params:netconf:capability:validate:1.1 \
    </capability>
  </capabilities>
</netconf-state>
</content-data>
</instance-data-set>
```

Figure 2

### 2.2.2. Preloading default configuration data

The example reflects UC2 in [Section 1](#). It provides a default rule set for a read-only operator role. It uses the "simplified-inline" method for specifying the content-schema.

---

Internet-Draft

YANG Instance Data

March 2021

```
<?xml version="1.0" encoding="UTF-8"?>
<instance-data-set
  xmlns="urn:ietf:params:xml:ns:yang:ietf-yang-instance-data">
  <name>read-only-acm-rules</name>
  <content-schema>
    <module>ietf-netconf-acm@2018-02-14</module>
  </content-schema>
  <revision>
    <date>1776-07-04</date>
    <description>Initial version</description>
  </revision>
  <description>Access control rules for a read-only role.</description>
  <content-data>
    <nacm xmlns="urn:ietf:params:xml:ns:yang:ietf-netconf-acm">
      <enable-nacm>true</enable-nacm>
      <read-default>deny</read-default>
      <exec-default>deny</exec-default>
      <rule-list>
        <name>read-only-role</name>
        <group>read-only-group</group>
        <rule>
          <name>read-all</name>
          <module-name>*</module-name>
          <access-operation>read</access-operation>
          <action>permit</action>
        </rule>
      </rule-list>
    </nacm>
  </content-data>
</instance-data-set>
```

Figure 3

### 2.2.3. Storing diagnostics data

The example reflects UC5 in [Section 1](#). An instance data set is produced by the server every 15 minutes that contains statistics about the NETCONF server. As a new set is produced periodically many times a day a revision-date would be useless; instead a timestamp is included.

```
{  
  "ietf-yang-instance-data:instance-data-set": {  
    "name": "acme-router-netconf-diagnostics",  
    "content-schema": {  
      "same-schema-as-file": "file:///acme-diagnostics-schema.json"  
    },  
    "timestamp": "2018-01-25T17:00:38Z",  
    "description": ["NETCONF statistics"],  
    "content-data": {  
      "ietf-netconf-monitoring:netconf-state": {  
        "statistics": {  
          "netconf-start-time": "2018-12-05T17:45:00Z",  
          "in-bad-hellos": "32",  
          "in-sessions": "397",  
          "dropped-sessions": "87",  
          "in-rpcs": "8711",  
          "in-bad-rpcs": "408",  
          "out-rpc-errors": "408",  
          "out-notifications": "39007"  
        }  
      }  
    }  
  }  
}
```

## Figure 4

### 3. YANG Instance Data Model

#### 3.1. Tree Diagram

The following tree diagram [[RFC8340](#)] provides an overview of the data model.

```
module: ietf-yang-instance-data
  structure instance-data-set:
    +-- name?          string
    +-- format-version? string
    +-- content-schema
      +-- (content-schema-spec)?
        +---:(simplified-inline)
        |  +-- module*
        |    module-with-revision-date
        +---:(inline) {inline-content-schema}?
        |  +-- inline-content-schema
        |    +-- inline-module*   module-with-revision-date
        |    +-- inline-schema   <anydata>
      +---:(uri)
        +-- same-schema-as-file?    inet:uri
    +-- description*     string
    +-- contact?         string
    +-- organization?   string
```

```

+-- datastore?          ds: datastore-ref
+-- revision* [date]
|  +-- date            string
|  +-- description?    string
+-- timestamp?         yang: date-and-time
+-- content-data?      <anydata>

```

### 3.2. YANG Model

This YANG module imports typedefs from [[RFC6991](#)], identities from [[RFC8342](#)] and the "structure" extension from [[RFC8791](#)]. It also references [[RFC8525](#)].

```

<CODE BEGINS> file "ietf-yang-instance-data@2021-03-23.yang"
module ietf-yang-instance-data {
    yang-version 1.1;
    namespace "urn:ietf:params:xml:ns:yang:ietf-yang-instance-data";
    prefix yid;

    import ietf-yang-structure-ext {
        prefix sx;
        reference
            "YANG Data Structure Extensions:
            draft-ietf-netmod-yang-data-ext-05";
    }
    import ietf-datastores {
        prefix ds;
        reference
            "RFC 8342: Network Management Datastore Architecture (NMDA)";
    }
}

```

```

import ietf-inet-types {
    prefix inet;
    reference
        "RFC 6991: Common YANG Data Types";
}
import ietf-yang-types {
    prefix yang;
    reference
        "RFC 6991: Common YANG Data Types";
}

```

```
organization
  "IETF NETMOD Working Group";
contact
  "WG Web: <https://datatracker.ietf.org/wg/netmodf/>
   WG List: <mailto:netmod@ietf.org>

  Author: Balazs Lengyel
          <mailto:balazs.lengyel@ericsson.com>";
description
  "The module defines the structure and content of YANG
   instance data sets.

  The key words 'MUST', 'MUST NOT', 'REQUIRED', 'SHALL',
  'SHALL NOT', 'SHOULD', 'SHOULD NOT', 'RECOMMENDED',
  'NOT RECOMMENDED', 'MAY', and 'OPTIONAL' in this document
  are to be interpreted as described in BCP 14 \(RFC 2119\)
  (RFC 8174) when, and only when, they appear in all
  capitals, as shown here.
```

Copyright (c) 2020 IETF Trust and the persons identified as  
authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or  
without modification, is permitted pursuant to, and subject  
to the license terms contained in, the Simplified BSD License  
set forth in [Section 4.c](#) of the IETF Trust's Legal Provisions  
Relating to IETF Documents  
(<http://trustee.ietf.org/license-info>).

This version of this YANG module is part of RFC XXXX; see  
the RFC itself for full legal notices.";

```
revision 2021-03-23 {
  description
    "Initial revision.";
  reference
    "RFC XXXX: YANG Instance Data Format";
```

```
}
```

```
feature inline-content-schema {
  description
```

```

    "This feature indicates that inline content-schema
    option is supported. Support for this feature might
    be documented only via out-of-band documentation.";
}

typedef module-with-revision-date {
    type string {
        pattern '[a-zA-Z_][a-zA-Z0-9\-\_]*' +
            '(@\d{4}-(1[0-2]|0[1-9])-(0[1-9]|1|2)[0-9]|3[0-1]))?';
        pattern '.|..|[^\xX].*|.[^mM].*|..[^lL].*';
    }
    description
        "A type defining a module name and an optional revision
        date, e.g. ietf-yang-library@2016-06-21";
}

sx:structure "instance-data-set" {
    description
        "A data structure to define a format for YANG instance
        data. The majority of the YANG nodes provide meta-data
        about the instance data; the instance data itself is
        is contained only in the 'content-data' node.";
    leaf name {
        type string;
        description
            "An arbitrary name for the YANG instance data set. This
            value is primarily used for descriptive purposes. However,
            when the instance data set is saved to a file, then the
            filename MUST encode the name's value, per Section 3
            of RFC XXXX.";
    }
    leaf format-version {
        type string {
            pattern '\d{4}-(1[0-2]|0[1-9])-(0[1-9]|1|2)[0-9]|3[0-1])';
        }
        default "2021-03-23";
        description
            "The 'revision' of the 'ietf-yang-instance-data' module
            used to encode this 'instance-data-set'.";
    }
    container content-schema {
        description
            "The content schema (i.e., YANG modules) used to create
            the instance data set.

```

```
If not present the user needs to obtain the information
through external documents.";
choice content-schema-spec {
    description
        "Specification of the content-schema.";
    case simplified-inline {
        leaf-list module {
            type module-with-revision-date;
            min-elements 1;
            description
                "The list of content defining YANG modules.
```

The value SHALL start with the module name.  
If the module contains a revision statement the  
revision date SHALL be included in the leaf-list  
entry. If other methods (e.g., revision-label) are  
defined to identify individual module revisions  
those MAY be used instead of using a revision date.

E.g., ietf-yang-library@2016-06-21

Usage of this leaf-list implies the modules are  
used without any deviations and with all features  
supported. Multiple revisions of the same module  
MUST NOT be specified.";

```
}
```

```
}
```

```
case inline {
    if-feature "inline-content-schema";
    container inline-content-schema {
        description
            "Module(s) describing the schema for the
            content-data.";
        leaf-list inline-module {
            type module-with-revision-date;
            min-elements 1;
            description
                "Indicates that content defining YANG modules
                are specified inline.
```

The value SHALL start with the module name.  
If the module contains a revision statement the  
revision date SHALL be included in the  
leaf-list entry. If other methods  
(e.g., revision-label) are defined to identify  
individual module revisions those MAY be used  
instead of using a revision date.

Internet-Draft

YANG Instance Data

March 2021

E.g., ietf-yang-library@2016-06-21

The first item is either ietf-yang-library or some other YANG module that contains a list of YANG modules with their name, revision-date, supported-features, and deviations.

The usage of revision '2019-01-04' of the 'ietf-yang-library' module MUST be supported. Using other modules, module versions MAY also be supported.

Some versions of ietf-yang-library MAY contain different module-sets for different datastores. In this case the instance data set MUST contain the 'datastore' leaf and instance data for the ietf-yang-library MUST also contain information specifying the module-set for the relevant datastore.

```
Subsequent items MAY specify YANG modules
augmenting the first module with useful data
(e.g., revision label).";
reference
    "RFC 8525: YANG Library";
}
anydata inline-schema {
    mandatory true;
    description
        "Instance data corresponding to the YANG modules
        specified in the inline-module nodes defining
        the set of content defining YANG modules for
        this instance-data-set.";
}
}
case uri {
    leaf same-schema-as-file {
        type inet:uri;
        description
            "A reference to another YANG instance data file.
```

```

        This instance data file uses the same
        content schema as the referenced file.";
    }
}
}
}
leaf-list description {
    type string;

```

---

```

description
    "Description of the instance data set.";
}
leaf contact {
    type string;
    description
        "Contact information for the person or
        organization to whom queries concerning this
        instance data set should be sent.";
}
leaf organization {
    type string;
    description
        "Organization responsible for the instance
        data set.";
}
leaf datastore {
    type ds:datastore-ref;
    description
        "The identity of the datastore with which the
        instance data set is associated, e.g., the datastore from
        where the data was read or the datastore into which the data
        may be loaded or the datastore which is being documented.
        If a single specific datastore cannot be specified, the
        leaf MUST be absent.

        If this leaf is absent, then the datastore to which the
        instance data belongs is unspecified.";
}
list revision {
    key "date";
    description
        "Instance data sets that are produced as
```

a result of some sort of specification or design effort SHOULD have at least one revision entry. For every published editorial change, a new one SHOULD be added in front of the revisions sequence so that all revisions are in reverse chronological order.

In case of instance data sets that are read from or produced by a server or otherwise subject to frequent updates or changes, revision SHOULD NOT be present";

```
leaf date {  
    type string {  
        pattern '\d{4}-(1[0-2]|0[1-9])-(0[1-9]|1[0-9]|3[0-1])';  
    }  
    description
```

```
"Specifies the date the instance data set  
was last modified. Formatted as YYYY-MM-DD";  
}  
leaf description {  
    type string;  
    description  
    "Description of this revision of the instance data set.";  
}  
leaf timestamp {  
    type yang:date-and-time;  
    description  
    "The date and time when the instance data set  
was last modified.  
  
In case of instance data sets that are read from or  
produced by a server or otherwise subject to frequent  
updates or changes, timestamp SHOULD be present";  
}  
anydata content-data {  
    description  
    "Contains the real instance data.  
    The data MUST conform to the relevant YANG modules specified  
    either in the content-schema or in some other  
    implementation specific manner.";
```

```
    }
}
<CODE ENDS>
```

#### 4. Security Considerations

The YANG module defined in this document only defines a wrapper structure specifying a format and a metadata header for YANG instance data defined by the content-schema. Because of this the security considerations template for YANG models in [section 3.7.1 in \[RFC8407\]](#) is not followed. The instance data is designed to be accessed as a stored file or over any file access method or protocol.

The document does not specify any method to influence the behavior of a server.

Instance data files may contain sensitive data.

The header part is not security sensitive.

The security sensitivity of the instance data in the content part is completely dependent on the content schema. Depending on the nature

---

Lengyel & Claise

Expires September 30, 2021

[Page 19]

---

Internet-Draft

YANG Instance Data

March 2021

of the instance data, instance data files MAY need to be handled in a secure way. The same kind of handling should be applied, that would be needed for the result of a read operation returning the same data.

Instance data files should be protected against modification or unauthorized access using normal file handling mechanisms. Care should be taken, when copying the original files or providing file access for additional users, not to reveal information unintentionally.

#### 5. IANA Considerations

This document registers one URI and one YANG module.

##### 5.1. URI Registration

This document registers one URI in the IETF XML registry [[RFC3688](#)]. Following the format in [RFC 3688](#), the following registration is requested to be made:

URI: urn:ietf:params:xml:ns.yang:ietf-yang-instance-data  
Registrant Contact: The IESG.  
XML: N/A, the requested URI is an XML namespace.

## 5.2. YANG Module Name Registration

This document registers one YANG module in the YANG Module Names registry [[RFC6020](#)].

```
name: ietf-yang-instance-data
namespace: urn:ietf:params:xml:ns.yang:ietf-yang-instance-data
prefix: yid
reference: RFC XXXX
```

## 6. Acknowledgments

For their valuable comments, discussions, and feedback, we wish to acknowledge Andy Bierman, Juergen Schoenwaelder, Rob Wilton, Joe Clarke, Kent Watsen Martin Bjorklund, Ladislav Lhotka, Qin Wu and other members of the Netmod WG.

## 7. References

### 7.1. Normative References

Lengyel & Claise

Expires September 30, 2021

[Page 20]

---

Internet-Draft

YANG Instance Data

March 2021

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.

[RFC6243] Bierman, A. and B. Lengyel, "With-defaults Capability for NETCONF", [RFC 6243](#), DOI 10.17487/RFC6243, June 2011, <<https://www.rfc-editor.org/info/rfc6243>>.

[RFC6991] Schoenwaelder, J., Ed., "Common YANG Data Types", [RFC 6991](#), DOI 10.17487/RFC6991, July 2013, <<https://www.rfc-editor.org/info/rfc6991>>.

- [RFC7950] Bjorklund, M., Ed., "The YANG 1.1 Data Modeling Language", [RFC 7950](#), DOI 10.17487/RFC7950, August 2016, <<https://www.rfc-editor.org/info/rfc7950>>.
- [RFC7951] Lhotka, L., "JSON Encoding of Data Modeled with YANG", [RFC 7951](#), DOI 10.17487/RFC7951, August 2016, <<https://www.rfc-editor.org/info/rfc7951>>.
- [RFC7952] Lhotka, L., "Defining and Using Metadata with YANG", [RFC 7952](#), DOI 10.17487/RFC7952, August 2016, <<https://www.rfc-editor.org/info/rfc7952>>.
- [RFC8040] Bierman, A., Bjorklund, M., and K. Watsen, "RESTCONF Protocol", [RFC 8040](#), DOI 10.17487/RFC8040, January 2017, <<https://www.rfc-editor.org/info/rfc8040>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in [RFC 2119](#) Key Words", [BCP 14](#), [RFC 8174](#), DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.
- [RFC8342] Bjorklund, M., Schoenwaelder, J., Shafer, P., Watsen, K., and R. Wilton, "Network Management Datastore Architecture (NMDA)", [RFC 8342](#), DOI 10.17487/RFC8342, March 2018, <<https://www.rfc-editor.org/info/rfc8342>>.
- [RFC8525] Bierman, A., Bjorklund, M., Schoenwaelder, J., Watsen, K., and R. Wilton, "YANG Library", [RFC 8525](#), DOI 10.17487/RFC8525, March 2019, <<https://www.rfc-editor.org/info/rfc8525>>.
- [RFC8526] Bjorklund, M., Schoenwaelder, J., Shafer, P., Watsen, K., and R. Wilton, "NETCONF Extensions to Support the Network Management Datastore Architecture", [RFC 8526](#), DOI 10.17487/RFC8526, March 2019, <<https://www.rfc-editor.org/info/rfc8526>>.

- [RFC8527] Bjorklund, M., Schoenwaelder, J., Shafer, P., Watsen, K., and R. Wilton, "RESTCONF Extensions to Support the Network Management Datastore Architecture", [RFC 8527](#), DOI 10.17487/RFC8527, March 2019, <<https://www.rfc-editor.org/info/rfc8527>>.

- [RFC8791] Bierman, A., Bjoerklund, M., and K. Watsen, "YANG Data Structure Extensions", [RFC 8791](#), DOI 10.17487/RFC8791, June 2020, <<https://www.rfc-editor.org/info/rfc8791>>.

## 7.2. Informative References

- [I-D.ietf-netmod-yang-module-versioning]  
Wilton, R., Rahman, R., Lengyel, B., Clarke, J., Sterne, J., Claise, B., and K. D'Souza, "Updated YANG Module Revision Handling", [draft-ietf-netmod-yang-module-versioning-01](#) (work in progress), July 2020.
- [RFC3688] Mealling, M., "The IETF XML Registry", [BCP 81](#), [RFC 3688](#), DOI 10.17487/RFC3688, January 2004, <<https://www.rfc-editor.org/info/rfc3688>>.
- [RFC6020] Bjorklund, M., Ed., "YANG – A Data Modeling Language for the Network Configuration Protocol (NETCONF)", [RFC 6020](#), DOI 10.17487/RFC6020, October 2010, <<https://www.rfc-editor.org/info/rfc6020>>.
- [RFC8340] Bjorklund, M. and L. Berger, Ed., "YANG Tree Diagrams", [BCP 215](#), [RFC 8340](#), DOI 10.17487/RFC8340, March 2018, <<https://www.rfc-editor.org/info/rfc8340>>.
- [RFC8407] Bierman, A., "Guidelines for Authors and Reviewers of Documents Containing YANG Data Models", [BCP 216](#), [RFC 8407](#), DOI 10.17487/RFC8407, October 2018, <<https://www.rfc-editor.org/info/rfc8407>>.
- [RFC8632] Vallin, S. and M. Bjorklund, "A YANG Data Model for Alarm Management", [RFC 8632](#), DOI 10.17487/RFC8632, September 2019, <<https://www.rfc-editor.org/info/rfc8632>>.
- [RFC8641] Clemm, A. and E. Voit, "Subscription to YANG Notifications for Datastore Updates", [RFC 8641](#), DOI 10.17487/RFC8641, September 2019, <<https://www.rfc-editor.org/info/rfc8641>>.
- [RFC8792] Watsen, K., Auerswald, E., Farrel, A., and Q. Wu, "Handling Long Lines in Content of Internet-Drafts and RFCs", [RFC 8792](#), DOI 10.17487/RFC8792, June 2020, <<https://www.rfc-editor.org/info/rfc8792>>.

[RFC8808] Wu, Q., Lengyel, B., and Y. Niu, "A YANG Data Model for Factory Default Settings", [RFC 8808](#), DOI 10.17487/RFC8808, August 2020, <<https://www.rfc-editor.org/info/rfc8808>>.

## [Appendix A.](#) Changes between revisions

Note to RFC Editor (To be removed by RFC Editor)

v09 – v13

- o Editorial updates

v08 – v09

- o Removed reference to similar to get reply
- o Introduced artwork folding in the examples

v07 – v08

- o Moved compatibility into appendix
- o Renamed yid-version to format-version. Changed format to date of the YANG module
- o Made support of ietf-yang-library mandatory if inline-content-schema is supported
- o Many small changes based on WGLC

v06 – v07

- o Updated terminology, use-cases
- o Many small changes based on WGLC

v05 – v06

- o Modified module name format, removed .yin or .yang extension
- o Removed pattern for module and inline-module. The usage of revision-label should also be allowed.

v04 – v05

- o Updated according to YANG-Doctor review
- o Updated security considerations

Internet-Draft

YANG Instance Data

March 2021

- o Added a wrapping container for the schema, and renamed the data nodes in the inline and uri cases.
- o Allowed .yin for simplified-inline schema naming. Made date optional if it is unavailable in the YANG module.
- o Added a mandatory yid-version to the header metadata to allow later updates of the module.

v03 – v04

- o removed entity-tag and last-modified timestamp
- o Added simplified-inline method of content-schema specification

v02 – v03

- o target renamed to "content-schema" and "content defining YANG module(s)"
- o Made name of instance data set optional
- o Updated according to [draft-ietf-netmod-yang-data-ext-03](#)
- o Clarified that entity-tag and last-modified timestamp are encoded as metadata. While they contain useful data, the HTTP-header based encoding from Restconf is not suitable.

v01 – v02

- o Removed design time from terminology
- o Defined the format of the content-data part by referencing various RFCs and drafts instead of the result of the get-data and get operations.
- o Changed target-ptr to a choice
- o Inline target-ptr may include augmenting modules and alternatives to ietf-yang-library
- o Moved list of target modules into a separate <target-modules>

element.

- o Added backwards compatibility considerations

v00 – v01

Lengyel & Claise

Expires September 30, 2021

[Page 24]

---

Internet-Draft

YANG Instance Data

March 2021

- o Added the target-ptr metadata with 3 methods
- o Added timestamp metadata
- o Removed usage of dedicated .yid file extension
- o Added list of use cases
- o Added list of principles
- o Updated examples
- o Moved detailed use case descriptions to appendix

## [Appendix B.](#) Backwards Compatibility

The concept of backwards compatibility and what changes are backwards compatible are not defined for "instance data sets" as it is highly dependent on the specific use case and the content-schema.

In case of "instance data sets" that are the result of design or specification activity, some changes that may be good to avoid are listed below.

YANG uses the concept of managed entities identified by key values; if the connection between the represented entity and the key value is not preserved during an update, this may lead to the following problems.

- o If the key value of a list entry that represents the same managed entity as before is changed, the user may mistakenly identify the list entry as new.
- o If the meaning of a list entry is changed, but the key values are not (e.g., redefining an alarm-type but not changing its alarm-

`type-id`) the change may not be noticed.

- o If the key value of a previously removed list entry is reused for a different entity, the change may be misinterpreted as reintroducing the previous entity.

## [Appendix C.](#) Detailed Use Cases

This section is non-normative.

Lengyel & Claise

Expires September 30, 2021

[Page 25]

---

Internet-Draft

YANG Instance Data

March 2021

### [C.1.](#) Use Case 1: Early Documentation of Server Capabilities

A server has a number of server-capabilities that are defined in YANG modules and can be retrieved from the server using protocols like NETCONF or RESTCONF. Server capabilities include:

- o data defined in "ietf-yang-library": YANG modules, submodules, features, deviations, schema-mounts, and datastores supported ([\[RFC8525\]](#))
- o alarms supported ([\[RFC8632\]](#))
- o data nodes and subtrees that support or do not support on-change notifications ([\[RFC8641\]](#))
- o netconf-capabilities in ietf-netconf-monitoring

While it is good practice to allow a client to query these capabilities from the live server, that is often not possible.

Often when a network node is released, an associated NMS (network management system) is also released with it. The NMS depends on the capabilities of the server. During NMS implementation, information about server capabilities is needed. If the information is unavailable early in some offline document, but only as instance data from the live network node, the NMS implementation will be delayed, because it has to wait until the network node is ready. Also assuming that all NMS implementors will have a correctly configured

network nodes from which data can be retrieved, is a very expensive proposition. (An NMS may handle dozens of node types.)

Network operators often build their own home-grown NMS systems that need to be integrated with a vendor's network node. The operator needs to know the network node's server capabilities in order to do this. Moreover, the network operator's decision to buy a vendor's product may even be influenced by the network node's OAM feature set documented as the server's capabilities.

Beside NMS implementors, system integrators and many others also need the same information early. Examples could be model driven testing, generating documentation, etc.

Most server-capabilities are relatively stable and change only during upgrade or due to licensing or the addition or removal of hardware. They are usually defined by a vendor at design time, before the product is released. It is feasible and advantageous to define/document them early e.g., in a YANG instance data File.

It is anticipated that a separate IETF document will define in detail how and which set of server capabilities should be documented.

## C.2. Use Case 2: Preloading Data

There are parts of the configuration that must be fully configurable by the operator. However, often a simple default configuration will be sufficient.

One example is access control groups/roles and related rules. While a sophisticated operator may define dozens of different groups, often a basic (read-only operator, read-write system administrator, security-administrator) triplet will be enough. Vendors will often provide such default configuration data to make device configuration easier for an operator.

Defining access control data is a complex task. To help, the device vendor predefines a set of default groups (/nacm:nacm/groups) and rules for these groups to access specific parts of common models (/nacm:nacm/rule-list/rule).

YANG instance data files are used to document and/or preload the default configuration.

### [C.3. Use Case 3: Documenting Factory Default Settings](#)

Nearly every server has a factory default configuration. If the system is really badly misconfigured or if the current configuration is to be abandoned, the system can be reset the default factory configuration.

The operator currently needs to know what the default configuration actually contains. YANG instance data can be used to document the factory default configuration. See [[RFC8808](#)].

#### Authors' Addresses

Balazs Lengyel  
Ericsson  
Magyar Tudosok korutja 11  
1117 Budapest  
Hungary

Phone: +36-70-330-7909  
Email: [balazs.lengyel@ericsson.com](mailto:balazs.lengyel@ericsson.com)

---

Lengyel & Claise

Expires September 30, 2021

[Page 27]

---

Internet-Draft

YANG Instance Data

March 2021

Benoit Claise  
Cisco Systems, Inc.  
De Kleetlaan 6a b1  
1831 Diegem  
Belgium

Phone: +32 2 704 5622  
Email: [bclaise@cisco.com](mailto:bclaise@cisco.com)

Lengyel & Claise

Expires September 30, 2021

[Page 28]