

OAuth Working Group
Internet-Draft
Intended status: Standards Track
Expires: September 22, 2016

M. Jones
Microsoft
N. Sakimura
NRI
J. Bradley
Ping Identity
March 21, 2016

OAuth 2.0 Authorization Server Discovery Metadata
draft-ietf-oauth-discovery-02

Abstract

This specification defines a discovery metadata format that an OAuth 2.0 client can use to obtain the information needed to interact with an OAuth 2.0 authorization server, including its endpoint locations and authorization server capabilities.

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on September 22, 2016.

Copyright Notice

Copyright (c) 2016 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in [Section 4.e](#) of

the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	3
1.1.	Requirements Notation and Conventions	3
1.2.	Terminology	3
2.	Authorization Server Metadata	4
3.	Obtaining Authorization Server Discovery Metadata	7
3.1.	Authorization Server Discovery Metadata Request	8
3.2.	Authorization Server Discovery Metadata Response	9
3.3.	Authorization Server Discovery Metadata Validation	10
4.	String Operations	10
5.	Compatibility Notes	11
6.	Security Considerations	11
6.1.	TLS Requirements	11
6.2.	Impersonation Attacks	12
6.3.	Publishing Metadata in a Standard Format	12
6.4.	Protected Resources	12
7.	IANA Considerations	13
7.1.	OAuth Authorization Server Discovery Metadata Registry	14
7.1.1.	Registration Template	14
7.1.2.	Initial Registry Contents	14
7.2.	Updated Registration Instructions	18
7.3.	Well-Known URI Registry	18
7.3.1.	Registry Contents	18
8.	References	18
8.1.	Normative References	18
8.2.	Informative References	21
Appendix A.	Acknowledgements	22
Appendix B.	Document History	22
	Authors' Addresses	23

1. Introduction

This specification generalizes the discovery metadata format defined by "OpenID Connect Discovery 1.0" [[OpenID.Discovery](#)] in a way that is compatible with OpenID Connect Discovery, while being applicable to a wider set of OAuth 2.0 use cases. This is intentionally parallel to the way that the "OAuth 2.0 Dynamic Client Registration Protocol" [[RFC7591](#)] specification generalized the dynamic client registration mechanisms defined by "OpenID Connect Dynamic Client Registration 1.0" [[OpenID.Registration](#)] in a way that was compatible with it.

The discovery metadata for an authorization server is retrieved from a well-known location as a JSON [[RFC7159](#)] document, which declares its endpoint locations and authorization server capabilities. This process is described in [Section 3](#).

The means by which the client obtains the location of the authorization server discovery metadata document is out of scope. In some cases, the location may be manually configured into the client. In other cases, it may be dynamically discovered, for instance, through the use of WebFinger [[RFC7033](#)], as described in [Section 2](#) of "OpenID Connect Discovery 1.0" [[OpenID.Discovery](#)].

1.1. Requirements Notation and Conventions

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

All uses of JSON Web Signature (JWS) [[JWS](#)] and JSON Web Encryption (JWE) [[JWE](#)] data structures in this specification utilize the JWS Compact Serialization or the JWE Compact Serialization; the JWS JSON Serialization and the JWE JSON Serialization are not used.

1.2. Terminology

This specification uses the terms "Access Token", "Authorization Code", "Authorization Endpoint", "Authorization Grant", "Authorization Server", "Client", "Client Authentication", "Client Identifier", "Client Secret", "Grant Type", "Protected Resource", "Redirection URI", "Refresh Token", "Resource Owner", "Resource Server", "Response Type", and "Token Endpoint" defined by OAuth 2.0 [RFC6749], the terms "Claim Name", "Claim Value", and "JSON Web Token (JWT)" defined by JSON Web Token (JWT) [JWT], and the term "Response Mode" defined by OAuth 2.0 Multiple Response Type Encoding Practices [OAuth.Responses].

[2.](#) Authorization Server Metadata

Authorization servers can have metadata describing their configuration. The following authorization server metadata values are used by this specification and are registered in the IANA "OAuth Authorization Server Discovery Metadata" registry established in [Section 7.1](#):

issuer

REQUIRED. The authorization server's issuer identifier, which is a URL that uses the "https" scheme and has no query or fragment components. This is the location where ".well-known" [RFC 5785](#) [RFC5785] resources containing information about the authorization server are published. Using these well-known resources is described in [Section 3](#). The issuer identifier is used to prevent authorization server mix-up attacks, as described in "OAuth 2.0 Mix-Up Mitigation" [[I-D.ietf-oauth-mix-up-mitigation](#)].

authorization_endpoint

REQUIRED. URL of the authorization server's authorization endpoint [[RFC6749](#)].

token_endpoint

URL of the authorization server's token endpoint [[RFC6749](#)]. This is REQUIRED unless only the implicit grant type is used.

jwks_uri

OPTIONAL. URL of the authorization server's JWK Set [[JWK](#)] document. This contains the signing key(s) the client uses to

validate signatures from the authorization server. The JWK Set MAY also contain the server's encryption key(s), which are used by clients to encrypt requests to the server. When both signing and encryption keys are made available, a "use" (public key use) parameter value is REQUIRED for all keys in the referenced JWK Set to indicate each key's intended usage. Although some algorithms allow the same key to be used for both signatures and encryption, doing so is NOT RECOMMENDED, as it is less secure. The JWK "x5c" parameter MAY be used to provide X.509 representations of keys provided. When used, the bare key values MUST still be present and MUST match those in the certificate.

registration_endpoint

OPTIONAL. URL of the authorization server's OAuth 2.0 Dynamic Client Registration endpoint [[RFC7591](#)].

scopes_supported

RECOMMENDED. JSON array containing a list of the OAuth 2.0 [[RFC6749](#)] "scope" values that this authorization server supports. Servers MAY choose not to advertise some supported scope values even when this parameter is used.

response_types_supported

REQUIRED. JSON array containing a list of the OAuth 2.0 "response_type" values that this authorization server supports. The array values used are the same as those used with the "response_types" parameter defined by "OAuth 2.0 Dynamic Client Registration Protocol" [[RFC7591](#)].

response_modes_supported

OPTIONAL. JSON array containing a list of the OAuth 2.0 "response_mode" values that this authorization server supports, as specified in OAuth 2.0 Multiple Response Type Encoding Practices [[OAuth.Responses](#)]. If omitted, the default is "["query", "fragment"]". The response mode value "form_post" is also defined in OAuth 2.0 Form Post Response Mode [[OAuth.Post](#)].

grant_types_supported

OPTIONAL. JSON array containing a list of the OAuth 2.0 grant type values that this authorization server supports. The array values used are the same as those used with the "grant_types" parameter defined by "OAuth 2.0 Dynamic Client Registration Protocol" [[RFC7591](#)]. If omitted, the default value is ["authorization_code", "implicit"].

token_endpoint_auth_methods_supported

OPTIONAL. JSON array containing a list of client authentication methods supported by this token endpoint. Client authentication method values are used in the "token_endpoint_auth_method" parameter defined in [Section 2 of \[RFC7591\]](#). If omitted, the default is "client_secret_basic" -- the HTTP Basic Authentication Scheme specified in [Section 2.3.1](#) of OAuth 2.0 [[RFC6749](#)].

token_endpoint_auth_signing_alg_values_supported

OPTIONAL. JSON array containing a list of the JWS signing algorithms ("alg" values) supported by the token endpoint for the signature on the JWT [[JWT](#)] used to authenticate the client at the token endpoint for the "private_key_jwt" and "client_secret_jwt" authentication methods. Servers SHOULD support "RS256". The value "none" MUST NOT be used.

service_documentation

OPTIONAL. URL of a page containing human-readable information that developers might want or need to know when using the authorization server. In particular, if the authorization server does not support Dynamic Client Registration, then information on how to register clients needs to be provided in this documentation.

ui_locales_supported

OPTIONAL. Languages and scripts supported for the user interface, represented as a JSON array of [BCP47](#) [[RFC5646](#)] language tag values.

op_policy_uri

OPTIONAL. URL that the authorization server provides to the

person registering the client to read about the authorization server's requirements on how the client can use the data provided by the authorization server. The registration process SHOULD display this URL to the person registering the client if it is given. As described in [Section 5](#), despite the identifier "op_policy_uri", appearing to be OpenID-specific, its usage in this specification is actually referring to a general OAuth 2.0 feature that is not specific to OpenID Connect.

op_tos_uri

OPTIONAL. URL that the authorization server provides to the person registering the client to read about authorization server's terms of service. The registration process SHOULD display this URL to the person registering the client if it is given. As described in [Section 5](#), despite the identifier "op_tos_uri", appearing to be OpenID-specific, its usage in this specification is actually referring to a general OAuth 2.0 feature that is not specific to OpenID Connect.

revocation_endpoint

OPTIONAL. URL of the authorization server's OAuth 2.0 revocation endpoint [[RFC7009](#)].

revocation_endpoint_auth_methods_supported

OPTIONAL. JSON array containing a list of client authentication methods supported by this revocation endpoint. The valid client authentication method values are those registered in the IANA "OAuth Token Endpoint Authentication Methods" registry [[IANA.OAuth.Parameters](#)].

revocation_endpoint_auth_signing_alg_values_supported

OPTIONAL. JSON array containing a list of the JWS signing algorithms ("alg" values) supported by the revocation endpoint for the signature on the JWT [[JWT](#)] used to authenticate the client at the revocation endpoint for the "private_key_jwt" and "client_secret_jwt" authentication methods. The value "none" MUST NOT be used.

introspection_endpoint

OPTIONAL. URL of the authorization server's OAuth 2.0 introspection endpoint [[RFC7662](#)].

introspection_endpoint_auth_methods_supported

OPTIONAL. JSON array containing a list of client authentication methods supported by this introspection endpoint. The valid client authentication method values are those registered in the IANA "OAuth Token Endpoint Authentication Methods" registry [[IANA.OAuth.Parameters](#)] or those registered in the IANA "OAuth Access Token Types" registry [[IANA.OAuth.Parameters](#)]. (These values are and will remain distinct, due to [Section 7.2](#).)

introspection_endpoint_auth_signing_alg_values_supported

OPTIONAL. JSON array containing a list of the JWS signing algorithms ("alg" values) supported by the introspection endpoint for the signature on the JWT [[JWT](#)] used to authenticate the client at the introspection endpoint for the "private_key_jwt" and "client_secret_jwt" authentication methods. The value "none" MUST NOT be used.

code_challenge_methods_supported

OPTIONAL. JSON array containing a list of PKCE [[RFC7636](#)] code challenge methods supported by this authorization server. Code challenge method values are used in the "code_challenge_method" parameter defined in [Section 4.3 of \[RFC7636\]](#). The valid code challenge method values are those registered in the IANA "PKCE Code Challenge Methods" registry [[IANA.OAuth.Parameters](#)].

Additional authorization server metadata parameters MAY also be used. Some are defined by other specifications, such as OpenID Connect Discovery 1.0 [[OpenID.Discovery](#)].

[3](#). Obtaining Authorization Server Discovery Metadata

Authorization servers supporting discovery MUST make a JSON document containing discovery metadata as specified in [Section 2](#) available at a path formed by concatenating a well-known URI string such as `"/.well-known/oauth-authorization-server"` to the authorization

server's issuer identifier. The syntax and semantics of

".well-known" are defined in [RFC 5785](#) [[RFC5785](#)]. The well-known URI path suffix used MUST be registered in the IANA "Well-Known URIs" registry [[IANA.well-known](#)].

Different applications utilizing OAuth authorization servers in application-specific ways may define and register different well-known URI path suffixes used to publish authorization server metadata as used by those applications. For instance, if the Example application uses an OAuth authorization server in an Example-specific way, and there are Example-specific metadata values that it needs to publish, then it might register and use the "example-configuration" URI path suffix and publish the metadata document at the path formed by concatenating `"/.well-known/example-configuration"` to the authorization server's issuer identifier.

An OAuth 2.0 application using this specification MUST specify what well-known URI string it will use for this purpose. The same authorization server MAY choose to publish its metadata at multiple well-known locations relative to its issuer identifier, for example, publishing metadata at both `"/.well-known/example-configuration"` and `"/.well-known/oauth-authorization-server"`.

Some OAuth applications will choose to use the well-known URI path suffix "openid-configuration" and publish the metadata document at the path formed by concatenating `"/.well-known/openid-configuration"` to the authorization server's issuer identifier. As described in [Section 5](#), despite the identifier `"/.well-known/openid-configuration"`, appearing to be OpenID-specific, its usage in this specification is actually referring to a general OAuth 2.0 feature that is not specific to OpenID Connect.

[3.1](#). Authorization Server Discovery Metadata Request

An authorization server discovery metadata document MUST be queried using an HTTP "GET" request at the previously specified path.

The client would make the following request when the issuer identifier is `"https://example.com"` and the well-known URI path suffix is `"oauth-authorization-server"` to obtain the discovery metadata, since the issuer identifier contains no path component:

```
GET /.well-known/oauth-authorization-server HTTP/1.1
Host: example.com
```

If the issuer identifier value contains a path component, any terminating `"/` MUST be removed before appending `"/.well-known/"` and

the well-known URI path suffix. The client would make the following request when the issuer identifier is "https://example.com/issuer1" and the well-known URI path suffix is "oauth-authorization-server" to obtain the discovery metadata, since the issuer identifier contains a path component:

```
GET /issuer1/.well-known/oauth-authorization-server HTTP/1.1
Host: example.com
```

Using path components enables supporting multiple issuers per host. This is required in some multi-tenant hosting configurations. This use of ".well-known" is for supporting multiple issuers per host; unlike its use in [RFC 5785](#) [[RFC5785](#)], it does not provide general information about the host.

[3.2](#). Authorization Server Discovery Metadata Response

The response is a set of claims about the authorization server's configuration, including all necessary endpoints and public key location information. A successful response MUST use the 200 OK HTTP status code and return a JSON object using the "application/json" content type that contains a set of claims as its members that are a subset of the metadata values defined in [Section 2](#). Other claims MAY also be returned.

Claims that return multiple values are represented as JSON arrays. Claims with zero elements MUST be omitted from the response.

An error response uses the applicable HTTP status code value.

The following is a non-normative example response:

```
HTTP/1.1 200 OK
Content-Type: application/json

{
  "issuer":
    "https://server.example.com",
  "authorization_endpoint":
    "https://server.example.com/authorize",
  "token_endpoint":
    "https://server.example.com/token",
  "token_endpoint_auth_methods_supported":
    ["client_secret_basic", "private_key_jwt"],
  "token_endpoint_auth_signing_alg_values_supported":
    ["RS256", "ES256"],
  "userinfo_endpoint":
    "https://server.example.com/userinfo",
  "jwks_uri":
    "https://server.example.com/jwks.json",
  "registration_endpoint":
    "https://server.example.com/register",
  "scopes_supported":
    ["openid", "profile", "email", "address",
     "phone", "offline_access"],
  "response_types_supported":
    ["code", "code token"],
  "service_documentation":
    "http://server.example.com/service_documentation.html",
  "ui_locales_supported":
    ["en-US", "en-GB", "en-CA", "fr-FR", "fr-CA"]
}
```

[3.3.](#) Authorization Server Discovery Metadata Validation

The "issuer" value returned MUST be identical to the authorization server's issuer identifier value that was concatenated with the well-known URI path suffix to create the URL used to retrieve the discovery metadata. If these values are not identical, the data

contained in the response MUST NOT be used.

[4.](#) String Operations

Processing some OAuth 2.0 messages requires comparing values in the messages to known values. For example, the member names in the discovery metadata response might be compared to specific member names such as "issuer". Comparing Unicode [[UNICODE](#)] strings,

Jones, et al.

Expires September 22, 2016

[Page 10]

Internet-Draft

OAuth 2.0 Discovery Metadata

March 2016

however, has significant security implications.

Therefore, comparisons between JSON strings and other Unicode strings MUST be performed as specified below:

1. Remove any JSON applied escaping to produce an array of Unicode code points.
2. Unicode Normalization [[USA15](#)] MUST NOT be applied at any point to either the JSON string or to the string it is to be compared against.
3. Comparisons between the two strings MUST be performed as a Unicode code point to code point equality comparison.

[5.](#) Compatibility Notes

The identifiers `"/.well-known/openid-configuration"`, `"op_policy_uri"`, and `"op_tos_uri"` contain strings referring to the OpenID Connect [[OpenID.Core](#)] family of specifications that were originally defined by "OpenID Connect Discovery 1.0" [[OpenID.Discovery](#)]. Despite the reuse of these identifiers that appear to be OpenID-specific, their usage in this specification is actually referring to general OAuth 2.0 features that are not specific to OpenID Connect.

[6.](#) Security Considerations

[6.1.](#) TLS Requirements

Implementations MUST support TLS. Which version(s) ought to be

implemented will vary over time, and depend on the widespread deployment and known security vulnerabilities at the time of implementation. The authorization server MUST support TLS version 1.2 [[RFC5246](#)] and MAY support additional transport-layer security mechanisms meeting its security requirements. When using TLS, the client MUST perform a TLS/SSL server certificate check, per [RFC 6125](#) [[RFC6125](#)]. Implementation security considerations can be found in Recommendations for Secure Use of TLS and DTLS [[BCP195](#)].

To protect against information disclosure and tampering, confidentiality protection MUST be applied using TLS with a ciphersuite that provides confidentiality and integrity protection.

[6.2.](#) Impersonation Attacks

TLS certificate checking MUST be performed by the client, as described in [Section 6.1](#), when making an authorization server discovery metadata request. Checking that the server certificate is valid for the issuer identifier URL prevents man-in-middle and DNS-based attacks. These attacks could cause a client to be tricked into using an attacker's keys and endpoints, which would enable impersonation of the legitimate authorization server. If an attacker can accomplish this, they can access the resources that the affected client has access to using the authorization server that they are impersonating.

An attacker may also attempt to impersonate an authorization server by publishing a discovery document that contains an "issuer" claim using the issuer identifier URL of the authorization server being impersonated, but with its own endpoints and signing keys. This would enable it to impersonate that authorization server, if accepted by the client. To prevent this, the client MUST ensure that the issuer identifier URL it is using as the prefix for the discovery metadata request exactly matches the value of the "issuer" metadata value in the authorization server discovery metadata document received by the client.

[6.3.](#) Publishing Metadata in a Standard Format

Publishing information about the authorization server in a standard format makes it easier for both legitimate clients and attackers to use the authorization server. Whether an authorization server publishes its metadata in an ad-hoc manner or in the standard format defined by this specification, the same defenses against attacks that might be mounted that use this information should be applied.

[6.4.](#) Protected Resources

Secure determination of appropriate protected resource endpoints to use with an authorization server is out of scope of this specification. This specification assumes that the client has a means of determining appropriate resource endpoint(s) to use with an authorization server and that the client is using the correct discovery metadata for each authorization server. Implementers need to be aware that if an inappropriate resource endpoint is used by the client, that an attacker may be able to act as a man-in-the-middle proxy to a valid protected resource without it being detected by the authorization server or the client.

The ways to determine the appropriate protected resources to use with an authorization server are in general, application-dependent. For

instance, some authorization servers are used with a fixed protected resource or set of protected resources, the locations of which may be well known, or which could be published as metadata values by the authorization server. In other cases, the set of resources that can be used with an authorization server can be dynamically changed by administrative actions. Many other means of determining appropriate associations between authorization servers and protected resources are also possible.

[7.](#) IANA Considerations

The following registration procedure is used for the registry established by this specification.

Values are registered on a Specification Required [[RFC5226](#)] basis after a two-week review period on the oauth-ext-review@ietf.org mailing list, on the advice of one or more Designated Experts.

However, to allow for the allocation of values prior to publication, the Designated Experts may approve registration once they are satisfied that such a specification will be published.

Registration requests sent to the mailing list for review should use an appropriate subject (e.g., "Request to register OAuth Authorization Server Discovery Metadata: example").

Within the review period, the Designated Experts will either approve or deny the registration request, communicating this decision to the review list and IANA. Denials should include an explanation and, if applicable, suggestions as to how to make the request successful. Registration requests that are undetermined for a period longer than 21 days can be brought to the IESG's attention (using the iesg@ietf.org mailing list) for resolution.

Criteria that should be applied by the Designated Experts includes determining whether the proposed registration duplicates existing functionality, determining whether it is likely to be of general applicability or whether it is useful only for a single application, and whether the registration makes sense.

IANA must only accept registry updates from the Designated Experts and should direct all requests for registration to the review mailing list.

It is suggested that multiple Designated Experts be appointed who are able to represent the perspectives of different applications using this specification, in order to enable broadly-informed review of registration decisions. In cases where a registration decision could

be perceived as creating a conflict of interest for a particular Expert, that Expert should defer to the judgment of the other Experts.

[7.1.](#) OAuth Authorization Server Discovery Metadata Registry

This specification establishes the IANA "OAuth Authorization Server Discovery Metadata" registry for OAuth 2.0 authorization server metadata names. The registry records the authorization server metadata member and a reference to the specification that defines it.

[7.1.1.](#) Registration Template

Discovery Metadata Name:

The name requested (e.g., "issuer"). This name is case-sensitive. Names may not match other registered names in a case-insensitive manner unless the Designated Experts state that there is a compelling reason to allow an exception.

Discovery Metadata Description:

Brief description of the discovery metadata (e.g., "Issuer URL").

Change Controller:

For Standards Track RFCs, list the "IESG". For others, give the name of the responsible party. Other details (e.g., postal address, email address, home page URI) may also be included.

Specification Document(s):

Reference to the document or documents that specify the parameter, preferably including URIs that can be used to retrieve copies of the documents. An indication of the relevant sections may also be included but is not required.

[7.1.2.](#) Initial Registry Contents

- o Discovery Metadata Name: "issuer"
- o Discovery Metadata Description: Authorization server's issuer identifier URL
- o Change Controller: IESG
- o Specification Document(s): [Section 2](#) of [[this specification]]

- o Discovery Metadata Name: "authorization_endpoint"
- o Discovery Metadata Description: URL of the authorization server's authorization endpoint
- o Change Controller: IESG
- o Specification Document(s): [Section 2](#) of [[this specification]]

- o Discovery Metadata Name: "token_endpoint"
- o Discovery Metadata Description: URL of the authorization server's token endpoint
- o Change Controller: IESG

- o Specification Document(s): [Section 2](#) of [[this specification]]
- o Discovery Metadata Name: "jwks_uri"
- o Discovery Metadata Description: URL of the authorization server's JWK Set document
- o Change Controller: IESG
- o Specification Document(s): [Section 2](#) of [[this specification]]
- o Discovery Metadata Name: "registration_endpoint"
- o Discovery Metadata Description: URL of the authorization server's OAuth 2.0 Dynamic Client Registration Endpoint
- o Change Controller: IESG
- o Specification Document(s): [Section 2](#) of [[this specification]]
- o Discovery Metadata Name: "scopes_supported"
- o Discovery Metadata Description: JSON array containing a list of the OAuth 2.0 "scope" values that this authorization server supports
- o Change Controller: IESG
- o Specification Document(s): [Section 2](#) of [[this specification]]
- o Discovery Metadata Name: "response_types_supported"
- o Discovery Metadata Description: JSON array containing a list of the OAuth 2.0 "response_type" values that this authorization server supports
- o Change Controller: IESG
- o Specification Document(s): [Section 2](#) of [[this specification]]
- o Discovery Metadata Name: "response_modes_supported"
- o Discovery Metadata Description: JSON array containing a list of the OAuth 2.0 "response_mode" values that this authorization server supports
- o Change Controller: IESG
- o Specification Document(s): [Section 2](#) of [[this specification]]
- o Discovery Metadata Name: "grant_types_supported"
- o Discovery Metadata Description: JSON array containing a list of the OAuth 2.0 grant type values that this authorization server supports
- o Change Controller: IESG
- o Specification Document(s): [Section 2](#) of [[this specification]]

- o Discovery Metadata Name: "token_endpoint_auth_methods_supported"
- o Discovery Metadata Description: JSON array containing a list of client authentication methods supported by this token endpoint
- o Change Controller: IESG
- o Specification Document(s): [Section 2](#) of [[this specification]]

- o Discovery Metadata Name: "token_endpoint_auth_signing_alg_values_supported"
- o Discovery Metadata Description: JSON array containing a list of the JWS signing algorithms supported by the token endpoint for the signature on the JWT used to authenticate the client at the token endpoint
- o Change Controller: IESG
- o Specification Document(s): [Section 2](#) of [[this specification]]

- o Discovery Metadata Name: "service_documentation"
- o Discovery Metadata Description: URL of a page containing human-readable information that developers might want or need to know when using the authorization server
- o Change Controller: IESG
- o Specification Document(s): [Section 2](#) of [[this specification]]

- o Discovery Metadata Name: "ui_locales_supported"
- o Discovery Metadata Description: Languages and scripts supported for the user interface, represented as a JSON array of [BCP47](#) language tag values
- o Change Controller: IESG
- o Specification Document(s): [Section 2](#) of [[this specification]]

- o Discovery Metadata Name: "op_policy_uri"
- o Discovery Metadata Description: URL that the authorization server provides to the person registering the client to read about the authorization server's requirements on how the client can use the data provided by the authorization server
- o Change Controller: IESG
- o Specification Document(s): [Section 2](#) of [[this specification]]

- o Discovery Metadata Name: "op_tos_uri"
- o Discovery Metadata Description: URL that the authorization server provides to the person registering the client to read about authorization server's terms of service
- o Change Controller: IESG
- o Specification Document(s): [Section 2](#) of [[this specification]]

- o Discovery Metadata Name: "revocation_endpoint"
- o Discovery Metadata Description: URL of the authorization server's OAuth 2.0 revocation endpoint

- o Change Controller: IESG
- o Specification Document(s): [Section 2](#) of [[this specification]]
- o Discovery Metadata Name:
"revocation_endpoint_auth_methods_supported"
- o Discovery Metadata Description: JSON array containing a list of client authentication methods supported by this revocation endpoint
- o Change Controller: IESG
- o Specification Document(s): [Section 2](#) of [[this specification]]
- o Discovery Metadata Name:
"revocation_endpoint_auth_signing_alg_values_supported"
- o Discovery Metadata Description: JSON array containing a list of the JWS signing algorithms supported by the revocation endpoint for the signature on the JWT used to authenticate the client at the revocation endpoint
- o Change Controller: IESG
- o Specification Document(s): [Section 2](#) of [[this specification]]
- o Discovery Metadata Name: "introspection_endpoint"
- o Discovery Metadata Description: URL of the authorization server's OAuth 2.0 introspection endpoint
- o Change Controller: IESG
- o Specification Document(s): [Section 2](#) of [[this specification]]
- o Discovery Metadata Name:
"introspection_endpoint_auth_methods_supported"
- o Discovery Metadata Description: JSON array containing a list of client authentication methods supported by this introspection endpoint
- o Change Controller: IESG
- o Specification Document(s): [Section 2](#) of [[this specification]]
- o Discovery Metadata Name:
"introspection_endpoint_auth_signing_alg_values_supported"
- o Discovery Metadata Description: JSON array containing a list of the JWS signing algorithms supported by the introspection endpoint for the signature on the JWT used to authenticate the client at the introspection endpoint

- o Change Controller: IESG
- o Specification Document(s): [Section 2](#) of `[[this specification]]`
- o Discovery Metadata Name: "code_challenge_methods_supported"
- o Discovery Metadata Description: PKCE code challenge methods supported by this authorization server

Jones, et al.

Expires September 22, 2016

[Page 17]

Internet-Draft

OAuth 2.0 Discovery Metadata

March 2016

- o Change Controller: IESG
- o Specification Document(s): [Section 2](#) of `[[this specification]]`

[7.2.](#) Updated Registration Instructions

This specification adds to the instructions for the Designated Experts of the following IANA registries, both of which are in the "OAuth Parameters" registry [[IANA.OAuth.Parameters](#)]:

- o OAuth Access Token Types
- o OAuth Token Endpoint Authentication Methods

IANA has added a link to this specification in the Reference sections of these registries. `[[RFC Editor: The above sentence is written in the past tense as it would appear in the final specification, even though these links won't actually be created until after the IESG has requested publication of the specification. Please delete this note after the links are in place.]]`

For these registries, the designated experts must reject registration requests in one registry for values already occurring in the other registry. This is necessary because the "introspection_endpoint_auth_methods_supported" parameter allows for the use of values from either registry. That way, because the values in the two registries will continue to be mutually exclusive, no ambiguities will arise.

[7.3.](#) Well-Known URI Registry

This specification registers the well-known URI defined in [Section 3](#) in the IANA "Well-Known URIs" registry [[IANA.well-known](#)] established by [RFC 5785](#) [[RFC5785](#)].

[7.3.1.](#) Registry Contents

- o URI suffix: "oauth-authorization-server"
- o Change controller: IESG
- o Specification document: [Section 3](#) of [[this specification]]
- o Related information: (none)

[8.](#) References

[8.1.](#) Normative References

- [BCP195] Sheffer, Y., Holz, R., and P. Saint-Andre, "Recommendations for Secure Use of Transport Layer Security (TLS) and Datagram Transport Layer Security (DTLS)", [BCP 195](#), [RFC 7525](#), DOI 10.17487/RFC7525,

Jones, et al. Expires September 22, 2016 [Page 18]

Internet-Draft OAuth 2.0 Discovery Metadata March 2016

May 2015, <<http://www.rfc-editor.org/info/bcp195>>.

- [IANA.OAuth.Parameters]
IANA, "OAuth Parameters",
<<http://www.iana.org/assignments/oauth-parameters>>.

- [JWA] Jones, M., "JSON Web Algorithms (JWA)", [RFC 7518](#), DOI 10.17487/RFC7518, May 2015, <<http://tools.ietf.org/html/rfc7518>>.

- [JWE] Jones, M. and J. Hildebrand, "JSON Web Encryption (JWE)", [RFC 7516](#), DOI 10.17487/RFC7516, May 2015, <<http://tools.ietf.org/html/rfc7516>>.

- [JWK] Jones, M., "JSON Web Key (JWK)", [RFC 7517](#), DOI 10.17487/RFC7517, May 2015, <<http://tools.ietf.org/html/rfc7517>>.

- [JWS] Jones, M., Bradley, J., and N. Sakimura, "JSON Web Signature (JWS)", [RFC 7515](#), DOI 10.17487/RFC7515, May 2015, <<http://tools.ietf.org/html/rfc7515>>.

- [JWT] Jones, M., Bradley, J., and N. Sakimura, "JSON Web Token (JWT)", [RFC 7519](#), DOI 10.17487/RFC7519, May 2015, <<http://tools.ietf.org/html/rfc7519>>.

[OAuth.Post]

Jones, M. and B. Campbell, "OAuth 2.0 Form Post Response Mode", April 2015, <http://openid.net/specs/oauth-v2-form-post-response-mode-1_0.html>.

[OAuth.Responses]

de Medeiros, B., Ed., Scurtescu, M., Tarjan, P., and M. Jones, "OAuth 2.0 Multiple Response Type Encoding Practices", February 2014, <http://openid.net/specs/oauth-v2-multiple-response-types-1_0.html>.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<http://www.rfc-editor.org/info/rfc2119>>.

[RFC2246] Dierks, T. and C. Allen, "The TLS Protocol Version 1.0", [RFC 2246](#), DOI 10.17487/RFC2246, January 1999, <<http://www.rfc-editor.org/info/rfc2246>>.

[RFC3986] Berners-Lee, T., Fielding, R., and L. Masinter, "Uniform Resource Identifier (URI): Generic Syntax", STD 66, [RFC 3986](#), DOI 10.17487/RFC3986, January 2005,

Jones, et al.

Expires September 22, 2016

[Page 19]

Internet-Draft

OAuth 2.0 Discovery Metadata

March 2016

<<http://www.rfc-editor.org/info/rfc3986>>.

[RFC5226] Narten, T. and H. Alvestrand, "Guidelines for Writing an IANA Considerations Section in RFCs", [BCP 26](#), [RFC 5226](#), DOI 10.17487/RFC5226, May 2008, <<http://www.rfc-editor.org/info/rfc5226>>.

[RFC5246] Dierks, T. and E. Rescorla, "The Transport Layer Security (TLS) Protocol Version 1.2", [RFC 5246](#), DOI 10.17487/RFC5246, August 2008, <<http://www.rfc-editor.org/info/rfc5246>>.

[RFC5646] Phillips, A., Ed. and M. Davis, Ed., "Tags for Identifying Languages", [BCP 47](#), [RFC 5646](#), DOI 10.17487/RFC5646, September 2009, <<http://www.rfc-editor.org/info/rfc5646>>.

[RFC5785] Nottingham, M. and E. Hammer-Lahav, "Defining Well-Known Uniform Resource Identifiers (URIs)", [RFC 5785](#), DOI 10.17487/RFC5785, April 2010,

<<http://www.rfc-editor.org/info/rfc5785>>.

- [RFC6125] Saint-Andre, P. and J. Hodges, "Representation and Verification of Domain-Based Application Service Identity within Internet Public Key Infrastructure Using X.509 (PKIX) Certificates in the Context of Transport Layer Security (TLS)", [RFC 6125](#), DOI 10.17487/RFC6125, March 2011, <<http://www.rfc-editor.org/info/rfc6125>>.
- [RFC6749] Hardt, D., Ed., "The OAuth 2.0 Authorization Framework", [RFC 6749](#), DOI 10.17487/RFC6749, October 2012, <<http://www.rfc-editor.org/info/rfc6749>>.
- [RFC7009] Lodderstedt, T., Ed., Dronia, S., and M. Scurtescu, "OAuth 2.0 Token Revocation", [RFC 7009](#), DOI 10.17487/RFC7009, August 2013, <<http://www.rfc-editor.org/info/rfc7009>>.
- [RFC7033] Jones, P., Salgueiro, G., Jones, M., and J. Smarr, "WebFinger", [RFC 7033](#), DOI 10.17487/RFC7033, September 2013, <<http://www.rfc-editor.org/info/rfc7033>>.
- [RFC7159] Bray, T., Ed., "The JavaScript Object Notation (JSON) Data Interchange Format", [RFC 7159](#), DOI 10.17487/RFC7159, March 2014, <<http://www.rfc-editor.org/info/rfc7159>>.
- [RFC7565] Saint-Andre, P., "The 'acct' URI Scheme", [RFC 7565](#), DOI 10.17487/RFC7565, May 2015, <<http://www.rfc-editor.org/info/rfc7565>>.

Jones, et al.

Expires September 22, 2016

[Page 20]

Internet-Draft

OAuth 2.0 Discovery Metadata

March 2016

- [RFC7591] Richer, J., Ed., Jones, M., Bradley, J., Machulak, M., and P. Hunt, "OAuth 2.0 Dynamic Client Registration Protocol", [RFC 7591](#), DOI 10.17487/RFC7591, July 2015, <<http://www.rfc-editor.org/info/rfc7591>>.
- [RFC7636] Sakimura, N., Ed., Bradley, J., and N. Agarwal, "Proof Key for Code Exchange by OAuth Public Clients", [RFC 7636](#), DOI 10.17487/RFC7636, September 2015, <<http://www.rfc-editor.org/info/rfc7636>>.
- [RFC7662] Richer, J., Ed., "OAuth 2.0 Token Introspection", [RFC 7662](#), DOI 10.17487/RFC7662, October 2015,

<<http://www.rfc-editor.org/info/rfc7662>>.

[UNICODE] The Unicode Consortium, "The Unicode Standard",
<<http://www.unicode.org/versions/latest/>>.

[USA15] Davis, M. and K. Whistler, "Unicode Normalization Forms",
Unicode Standard Annex 15, June 2015,
<<http://www.unicode.org/reports/tr15/>>.

8.2. Informative References

[I-D.ietf-oauth-mix-up-mitigation]
Jones, M., Bradley, J., and N. Sakimura, "OAuth 2.0 Mix-Up Mitigation", [draft-ietf-oauth-mix-up-mitigation-00](#) (work in progress), March 2016.

[IANA.well-known]
IANA, "Well-Known URIs",
<<http://www.iana.org/assignments/well-known-uris>>.

[OpenID.Core]
Sakimura, N., Bradley, J., Jones, M., de Medeiros, B., and C. Mortimore, "OpenID Connect Core 1.0", November 2014,
<http://openid.net/specs/openid-connect-core-1_0.html>.

[OpenID.Discovery]
Sakimura, N., Bradley, J., Jones, M., and E. Jay, "OpenID Connect Discovery 1.0", November 2014, <http://openid.net/specs/openid-connect-discovery-1_0.html>.

[OpenID.Registration]
Sakimura, N., Bradley, J., and M. Jones, "OpenID Connect Dynamic Client Registration 1.0", November 2014, <http://openid.net/specs/openid-connect-registration-1_0.html>.

Jones, et al. Expires September 22, 2016 [Page 21]

Internet-Draft OAuth 2.0 Discovery Metadata March 2016

[Appendix A](#). Acknowledgements

This specification is based on the OpenID Connect Discovery 1.0 specification, which was produced by the OpenID Connect working group of the OpenID Foundation.

Review comments resulting in substantive edits to the specification were made by Brian Campbell, William Denniss, Vladimir Dzhuvinov, Samuel Erdtman, George Fletcher, Phil Hunt, Tony Nadalin, and Justin Richer.

[Appendix B](#). Document History

[[to be removed by the RFC Editor before publication as an RFC]]

-02

- o Changed the title to OAuth 2.0 Authorization Server Discovery Metadata.
- o Made "jwks_uri" and "registration_endpoint" OPTIONAL.
- o Defined the well-known URI string
"/.well-known/oauth-authorization-server".
- o Added security considerations about publishing authorization server discovery metadata in a standard format.
- o Added security considerations about protected resources.
- o Added more information to the "grant_types_supported" and "response_types_supported" definitions.
- o Referenced the working group Mix-Up Mitigation draft.
- o Changed some example metadata values.
- o Acknowledged individuals for their contributions to the specification.

-01

- o Removed WebFinger discovery.
- o Clarified the relationship between the issuer identifier URL and the well-known URI path relative to it at which the discovery metadata document is located.

-00

- o Created the initial working group version based on [draft-jones-oauth-discovery-01](#), with no normative changes.

Authors' Addresses

Michael B. Jones
Microsoft

Email: mbj@microsoft.com

URI: <http://self-issued.info/>

Nat Sakimura
Nomura Research Institute, Ltd.

Email: n-sakimura@nri.co.jp

URI: <http://nat.sakimura.org/>

John Bradley
Ping Identity

Email: ve7jtb@ve7jtb.com

URI: <http://www.thread-safe.com/>

