

OAuth Working Group
Internet-Draft
Intended status: Standards Track
Expires: September 28, 2015

J. Richer, Ed.
March 27, 2015

OAuth 2.0 Token Introspection
draft-ietf-oauth-introspection-07

Abstract

This specification defines a method for a protected resource to query an OAuth 2.0 authorization server to determine the active state of an OAuth 2.0 token and to determine meta-information about this token. OAuth 2.0 deployments can use this method to convey information about the authorization context of the token from the authorization server to the protected resource.

Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on September 28, 2015.

Copyright Notice

Copyright (c) 2015 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents

Internet-Draft

oauth-introspection

March 2015

(<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	2
1.1.	Terminology	3
2.	Introspection Endpoint	3
2.1.	Introspection Request	4
2.2.	Introspection Response	5
2.3.	Error Response	8
3.	IANA Considerations	8
3.1.	OAuth Token Introspection Response Registry	8
3.1.1.	Registration Template	9
3.1.2.	Initial Registry Contents	9
4.	Security Considerations	11
5.	Privacy Considerations	13
6.	Acknowledgements	13
7.	References	13
7.1.	Normative References	13
7.2.	Informative References	14
Appendix A.	Use with Proof of Possession Tokens	14
Appendix B.	Document History	15
	Author's Address	16

[1.](#) Introduction

In OAuth 2.0, the contents of tokens are opaque to clients. This means that the client does not need to know anything about the content or structure of the token itself, if there is any. However, there is still a large amount of metadata that may be attached to a token, such as its current validity, approved scopes, and information about the context in which the token was issued. These pieces of information are often vital to protected resources making authorization decisions based on the tokens being presented. Since OAuth 2.0 [[RFC6749](#)] does not define a protocol for the resource server to learn meta-information about a token that it has received from an authorization server, several different approaches have been

developed to bridge this gap. These include using structured token formats such as JWT [JWT] or proprietary inter-service communication mechanisms (such as shared databases and protected enterprise service buses) that convey token information.

This specification defines an interoperable web API that allows authorized protected resources to query the authorization server to determine the set of metadata for a given token that was presented to them by an OAuth 2.0 client. This metadata includes whether or not the token is currently active (or if it has expired or otherwise been revoked), what rights of access the token carries (usually conveyed through OAuth 2.0 scopes), and the authorization context in which the token was granted (including who authorized the token and which client it was issued to). Token introspection allows a protected resource to query this information regardless of whether or not it is carried in the token itself, allowing this method to be used along with or independently of structured token values. Additionally, a protected resource can use the mechanism described in this specification to introspect the token in a particular authorization decision context and ascertain the relevant metadata about the token in order to make this authorization decision appropriately.

1.1. Terminology

This section defines the terminology used by this specification. This section is a normative portion of this specification, imposing requirements upon implementations.

This specification uses the terms "access token", "authorization endpoint", "authorization grant", "authorization server", "client", "client identifier", "protected resource", "refresh token", "resource owner", "resource server", and "token endpoint" defined by OAuth 2.0 [RFC6749], and the terms "claim names" and "claim values" defined by JSON Web Token (JWT) [JWT].

2. Introspection Endpoint

The introspection endpoint is an OAuth 2.0 endpoint that takes a parameter representing an OAuth 2.0 token and returns a JSON [RFC7159] document representing the meta information surrounding the token, including whether this token is currently active. The

definition of an active token is up to the authorization server, but this is commonly a token that has been issued by this authorization server, is not expired, has not been revoked, and is within the purview of the protected resource making the introspection call.

The introspection endpoint MUST be protected by a transport-layer security mechanism as described in [Section 4](#).

[2.1](#). Introspection Request

The protected resource calls the introspection endpoint using an HTTP POST [[RFC7231](#)] request with parameters sent as "application/x-www-form-urlencoded" data as defined in [[W3C.REC-html5-20141028](#)]. The authorization server MAY allow an HTTP GET [[RFC7231](#)] request with parameters passed in the query string as defined in [[W3C.REC-html5-20141028](#)]. The protected resource sends a parameter representing the token along with optional parameters representing additional context that is known by the protected resource to aid the authorization server in its response.

token REQUIRED. The string value of the token. For access tokens, this is the "access_token" value returned from the token endpoint defined in OAuth 2.0 [[RFC6749](#)] [section 5.1](#). For refresh tokens, this is the "refresh_token" value returned from the token endpoint as defined in OAuth 2.0 [[RFC6749](#)] [section 5.1](#). Other token types are outside the scope of this specification.

token_type_hint OPTIONAL. A hint about the type of the token submitted for introspection. The protected resource MAY pass this parameter in order to help the authorization server to optimize the token lookup. If the server is unable to locate the token using the given hint, it MUST extend its search across all of its supported token types. An authorization server MAY ignore this parameter, particularly if it is able to detect the token type automatically. Values for this field are defined in OAuth Token Revocation [[RFC7009](#)].

The endpoint MAY allow other parameters to provide further context to

the query. For instance, an authorization service may need to know the IP address of the client accessing the protected resource in order to determine the appropriateness of the token being presented.

To prevent unauthorized token scanning attacks, the endpoint MUST also require some form of authorization to access this endpoint, such as client authentication as described in OAuth 2.0 [RFC6749] or a separate OAuth 2.0 access token such as the bearer token described in OAuth 2.0 Bearer Token Usage [RFC6750]. The methods of managing and validating these authentication credentials are out of scope of this specification.

For example, the following example shows a protected resource calling the token introspection endpoint to query about an OAuth 2.0 bearer. The protected resource is using a separate OAuth 2.0 bearer token to authorize this call.

Following is a non-normative example request:

```
POST /introspect HTTP/1.1
Host: server.example.com
Accept: application/json
Content-Type: application/x-www-form-urlencoded
Authorization: Bearer 23410913-abewfq.123483
```

```
token=2YotnFZFEjr1zCsicMWpAA
```

In this example, the protected resource uses a client identifier and client secret to authenticate itself to the introspection endpoint as well as send a token type hint.

Following is a non-normative example request:

```
POST /introspect HTTP/1.1
Host: server.example.com
Accept: application/json
Content-Type: application/x-www-form-urlencoded
Authorization: Basic czZCaGRSa3F0MzpnWDFmQmF0M2JW
```

token=mF_9.B5f-4.1JqM&token_type_hint=access_token

[2.2.](#) Introspection Response

The server responds with a JSON object [[RFC7159](#)] in "application/json" format with the following top-level members.

active

REQUIRED. Boolean indicator of whether or not the presented token is currently active. The specifics of a token's "active" state will vary depending on the implementation of the authorization server, and the information it keeps about its tokens, but a "true" value return for the "active" property will generally indicate that a given token has been issued by this authorization server, has not been revoked by the resource owner, and is within its given time window of validity (e.g. After its issuance time but not yet expired). See [Section 4](#) for information on implementation of such checks.

scope

OPTIONAL. A space-separated list of strings representing the scopes associated with this token, in the format described in [section 3.3](#) of OAuth 2.0 [[RFC6749](#)].

client_id

OPTIONAL. Client identifier for the OAuth 2.0 client that requested this token.

username

OPTIONAL. Human-readable identifier for the resource owner who authorized this token.

token_type

OPTIONAL. Type of the token as defined in [section 5.1](#) of OAuth 2.0 [[RFC6749](#)].

exp

OPTIONAL. Integer timestamp, measured in the number of seconds since January 1 1970 UTC, indicating when this token will expire, as defined in JWT [[JWT](#)].

iat

OPTIONAL. Integer timestamp, measured in the number of seconds since January 1 1970 UTC, indicating when this token was

originally issued, as defined in JWT [[JWT](#)].

nbf
OPTIONAL. Integer timestamp, measured in the number of seconds since January 1 1970 UTC, indicating when this token is not to be used before, as defined in JWT [[JWT](#)].

sub
OPTIONAL. Subject of the token, as defined in JWT [[JWT](#)]. Usually a machine-readable identifier of the resource owner who authorized this token.

aud
OPTIONAL. Service-specific string identifier or list of string identifiers representing the intended audience for this token, as defined in JWT [[JWT](#)].

iss
OPTIONAL. String representing the issuer of this token, as defined in JWT [[JWT](#)].

jti
OPTIONAL. String identifier for the token, as defined in JWT [[JWT](#)].

Specific implementations MAY extend this structure with their own service-specific response names as top-level members of this JSON object. Response names intended to be used across domains MUST be registered in the OAuth Token Introspection Response registry defined in [Section 3.1](#).

The authorization server MAY respond differently to different protected resources making the same request. For instance, an authorization server MAY limit which scopes from a given token are returned for each protected resource in order to prevent protected resources from learning more about the larger network than is necessary for their function.

The response MAY be cached by the protected resource to improve performance and reduce load on the introspection endpoint, but at the cost of liveness of the information used by the protected resource. See [Section 4](#) for more information regarding the trade off when the response is cached.

For example, the following response contains a set of information about an active token:

Following is a non-normative example response:

```
HTTP/1.1 200 OK
Content-Type: application/json

{
  "active": true,
  "client_id": "l238j323ds-23ij4",
  "username": "jdoe",
  "scope": "read write dolphin",
  "sub": "Z503upPC88QrAjx00dis",
  "aud": "https://protected.example.net/resource",
  "iss": "https://server.example.com/",
  "exp": 1419356238,
  "iat": 1419350238,
  "extension_field": "twenty-seven"
}
```

If the introspection call is properly authorized but the token is not active, does not exist on this server, or the protected resource is not allowed to introspect this particular token, the authorization server MUST return an introspection response with the active field set to false. Note that in order to avoid disclosing too much of the authorization server's state to a third party, the authorization server SHOULD NOT include any additional information about an inactive token, including why the token is inactive. For example, the response for a token that has been revoked or is otherwise invalid would look like the following:

Following is a non-normative example response:

```
HTTP/1.1 200 OK
Content-Type: application/json

{
  "active": false
}
```


If the protected resource uses OAuth 2.0 client credentials to authenticate to the introspection endpoint and its credentials are invalid, the authorization server responds with an HTTP 401 (Unauthorized) as described in [section 5.2](#) of OAuth 2.0 [[RFC6749](#)].

If the protected resource uses an OAuth 2.0 bearer token to authorize its call to the introspection endpoint and the token used for authorization does not contain sufficient privileges or is otherwise invalid for this request, the authorization server responds with an HTTP 401 code as described in [section 3](#) of OAuth 2.0 Bearer Token Usage [[RFC6750](#)].

Note that a properly formed and authorized query for an inactive or otherwise invalid token (or a token the protected resource is not allowed to know about) is not considered an error response by this specification. In these cases, the authorization server MUST instead respond with an introspection response with the "active" field set to "false" as described in [Section 2.2](#).

[3](#). IANA Considerations

[3.1](#). OAuth Token Introspection Response Registry

This specification establishes the OAuth Token Introspection Response registry.

OAuth registration client metadata names and descriptions are registered with a Specification Required ([RFC5226](#)) after a two-week review period on the `oauth-ext-review@ietf.org` mailing list, on the advice of one or more Designated Experts. However, to allow for the allocation of names prior to publication, the Designated Expert(s) may approve registration once they are satisfied that such a specification will be published.

Registration requests sent to the mailing list for review should use an appropriate subject (e.g., "Request to register OAuth Token Introspection Response name: example").

Within the review period, the Designated Expert(s) will either approve or deny the registration request, communicating this decision to the review list and IANA. Denials should include an explanation and, if applicable, suggestions as to how to make the request successful.

IANA must only accept registry updates from the Designated Expert(s) and should direct all requests for registration to the review mailing list.

[3.1.1.](#) Registration Template

Name:

The name requested (e.g., "example"). This name is case sensitive. Names that match other registered names in a case insensitive manner SHOULD NOT be accepted. Names that match claims registered in the JSON Web Token Claims registry established by [\[JWT\]](#) SHOULD have comparable definitions and semantics.

Description:

Brief description of the metadata value (e.g., "Example description").

Change controller:

For Standards Track RFCs, state "IESG". For others, give the name of the responsible party. Other details (e.g., postal address, email address, home page URI) may also be included.

Specification document(s):

Reference to the document(s) that specify the token endpoint authorization method, preferably including a URI that can be used to retrieve a copy of the document(s). An indication of the relevant sections may also be included but is not required.

[3.1.2.](#) Initial Registry Contents

The initial contents of the OAuth Token Introspection Response registry are:

- o Name: "active"
- o Description: Token active status
- o Change Controller: IESG
- o Specification Document(s): [Section 2.2](#) of [\[\[this document \]\]](#).

- o Name: "username"
- o Description: User identifier of the resource owner
- o Change Controller: IESG
- o Specification Document(s): [Section 2.2](#) of [\[\[this document \]\]](#).

- o Name: "client_id"
- o Description: Client identifier of the client

- o Change Controller: IESG
- o Specification Document(s): [Section 2.2](#) of [[this document]].

- o Name: "scope"
- o Description: Authorized scopes of the token
- o Change Controller: IESG
- o Specification Document(s): [Section 2.2](#) of [[this document]].
- o Name: "token_type"
- o Description: Type of the token
- o Change Controller: IESG
- o Specification Document(s): [Section 2.2](#) of [[this document]].
- o Name: "exp"
- o Description: Expiration timestamp of the token
- o Change Controller: IESG
- o Specification Document(s): [Section 2.2](#) of [[this document]].
- o Name: "iat"
- o Description: Issuance timestamp of the token
- o Change Controller: IESG
- o Specification Document(s): [Section 2.2](#) of [[this document]].
- o Name: "nbf"
- o Description: Timestamp which the token is not valid before
- o Change Controller: IESG
- o Specification Document(s): [Section 2.2](#) of [[this document]].
- o Name: "sub"
- o Description: Subject of the token
- o Change Controller: IESG
- o Specification Document(s): [Section 2.2](#) of [[this document]].
- o Name: "aud"
- o Description: Audience of the token
- o Change Controller: IESG
- o Specification Document(s): [Section 2.2](#) of [[this document]].
- o Name: "iss"
- o Description: Issuer of the token
- o Change Controller: IESG
- o Specification Document(s): [Section 2.2](#) of [[this document]].

- o Name: "jti"
- o Description: Unique identifier of the token
- o Change Controller: IESG
- o Specification Document(s): [Section 2.2](#) of [[this document]].

[4.](#) Security Considerations

Since there are many different and valid ways to implement an OAuth 2.0 system, there are consequently many ways for an authorization server to determine whether or not a token is currently "active" or not. However, since resource servers using token introspection rely on the authorization server to determine the state of a token, the authorization server MUST perform all applicable checks against a token's state. For instance:

- o If the token can expire, the authorization server MUST determine whether or not the token has expired.
- o If the token can be issued before it is able to be used, the authorization server MUST determine whether or not a token's valid period has started yet.
- o If the token can be revoked after it was issued, the authorization server MUST determine whether or not such a revocation has taken place.
- o If the token has been signed, the authorization server MUST validate the signature.

If an authorization server fails to perform any applicable check, the resource server could make an errant security decision based on that response. Note that not all of these checks will be applicable to all OAuth 2.0 deployments and it is up to the authorization server to determine which of these checks (and any other checks) apply.

If left unprotected and un-throttled, the introspection endpoint could present a means for an attacker to poll a series of possible token values, fishing for a valid token. To prevent this, the authorization server MUST require authentication of protected resources that need to access the introspection endpoint and SHOULD

require protected resources to be specifically authorized to call the introspection endpoint. The specifics of this authentication credentials are out of scope of this specification, but commonly these credentials could take the form of any valid client authentication mechanism used with the token endpoint, an OAuth 2.0 access token, or other HTTP authorization or authentication mechanism. A single piece of software acting as both a client and a protected resource MAY re-use the same credentials between the token endpoint and the introspection endpoint, though doing so potentially conflates the activities of the client and protected resource portions of the software and the authorization server MAY require separate credentials for each mode.

Since the introspection endpoint takes in OAuth 2.0 tokens as parameters and responds with information used to make authorization decisions, the server MUST support TLS 1.2 [RFC 5246](#) [[RFC5246](#)] and MAY

support additional transport-layer mechanisms meeting its security requirements. When using TLS, the client or protected resource MUST perform a TLS/SSL server certificate check, per [RFC 6125](#) [[RFC6125](#)]. Implementation security considerations can be found in Recommendations for Secure Use of TLS and DTLS [[TLS.BCP](#)].

In order to prevent the values of access tokens being from leaking into server-side logs via query parameters, an authorization server offering token introspection MAY disallow HTTP GET and instead require an HTTP POST method to be used at the introspection endpoint.

In order to avoid disclosing internal server state, an introspection response for an inactive token SHOULD NOT contain any additional claims beyond the required "active" claim (with its value set to "false").

Since a protected resource MAY cache the response of the introspection endpoint, designers of an OAuth 2.0 system using this protocol MUST consider the performance and security trade-offs inherent in caching security information such as this. A less aggressive cache with a short timeout will provide the protected resource with more up to date information (due to it needing to query the introspection endpoint more often) at the cost of increased network traffic and load on the introspection endpoint. A more aggressive cache with a longer duration will minimize network traffic

and load on the introspection endpoint, but at the cost of liveness of information about the token. For example, the token may be revoked while the protected resource is relying on the value of the cached response to make authorization decisions. This creates a window during which a revoked token could be used at the protected resource. Consequently, an acceptable cache validity duration needs to be carefully considered given the concerns and sensitivities of the protected resource being accessed and the likelihood of a token being revoked or invalidated in the interim period. Highly sensitive environments can opt to disable caching entirely on the protected resource in order to maximize liveness of information.

An authorization server offering token introspection **MUST** be able to understand the token values being presented to it during this call. The exact means by which this happens is an implementation detail and outside the scope of this specification. For unstructured tokens, this could take the form of a simple server-side database query against a data store containing the context information for the token. For structured tokens, this could take the form of the server parsing the token, validating its signature or other protection mechanisms, and returning the information contained in the token back to the protected resource (allowing the protected resource to be unaware of the token's contents, much like the client).

Note that for tokens carrying encrypted information that is needed during the introspection process, the authorization server **MUST** be able to decrypt and validate the token in order to access this information. Also note that in cases where the authorization server stores no information about the token and has no means of accessing information about the token by parsing the token itself, it can not likely offer an introspection service.

[5.](#) Privacy Considerations

The introspection response may contain privacy-sensitive information such as user identifiers for resource owners. When this is the case, measures **MUST** be taken to prevent disclosure of this information to unintended parties. One way to limit disclosure is to require authorization to call the introspection endpoint and to limit calls to only registered and trusted protected resource servers. Another method is to transmit user identifiers as opaque service-specific strings, potentially returning different identifiers to each

protected resource. Omitting privacy-sensitive information from an introspection response is the simplest way of minimizing privacy issues.

6. Acknowledgements

Thanks to the OAuth Working Group and the UMA Working Group for feedback.

7. References

7.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC5226] Narten, T. and H. Alvestrand, "Guidelines for Writing an IANA Considerations Section in RFCs", [BCP 26](#), [RFC 5226](#), May 2008.
- [RFC5246] Dierks, T. and E. Rescorla, "The Transport Layer Security (TLS) Protocol Version 1.2", [RFC 5246](#), August 2008.
- [RFC6125] Saint-Andre, P. and J. Hodges, "Representation and Verification of Domain-Based Application Service Identity within Internet Public Key Infrastructure Using X.509 (PKIX) Certificates in the Context of Transport Layer Security (TLS)", [RFC 6125](#), March 2011.

Richer

Expires September 28, 2015

[Page 13]

Internet-Draft

oauth-introspection

March 2015

- [RFC6749] Hardt, D., "The OAuth 2.0 Authorization Framework", [RFC 6749](#), October 2012.
- [RFC6750] Jones, M. and D. Hardt, "The OAuth 2.0 Authorization Framework: Bearer Token Usage", [RFC 6750](#), October 2012.
- [RFC7009] Lodderstedt, T., Dronia, S., and M. Scurtescu, "OAuth 2.0 Token Revocation", [RFC 7009](#), August 2013.
- [RFC7159] Bray, T., "The JavaScript Object Notation (JSON) Data Interchange Format", [RFC 7159](#), March 2014.

[RFC7231] Fielding, R. and J. Reschke, "Hypertext Transfer Protocol (HTTP/1.1): Semantics and Content", [RFC 7231](#), June 2014.

[W3C.REC-html5-20141028]

Hickson, I., Berjon, R., Faulkner, S., Leithead, T., Navara, E., O'Connor, E., and S. Pfeiffer, "HTML5", World Wide Web Consortium Recommendation REC-html5-20141028, October 2014, <<http://www.w3.org/TR/2014/REC-html5-20141028>>.

[7.2.](#) Informative References

[JWT] Jones, M., Bradley, J., and N. Sakimura, "JSON Web Token (JWT)", [draft-ietf-oauth-json-web-token](#) (work in progress), July 2014.

[TLS.BCP] Sheffer, Y., Holz, R., and P. Saint-Andre, "Recommendations for Secure Use of TLS and DTLS", November 2014.

[Appendix A.](#) Use with Proof of Possession Tokens

With bearer tokens such as those defined by OAuth 2.0 Bearer Token Usage [[RFC6750](#)], the protected resource will have in its possession the entire secret portion of the token for submission to the introspection service. However, for proof-of-possession style tokens, the protected resource will have only a token identifier used during the request, along with the cryptographic signature on the request. The protected resource would be able to submit the token identifier to the authorization server's token endpoint in order to obtain the necessary key information needed to validate the signature on the request. The details of this usage are outside the scope of this specification and will be defined in an extension to this specification.

[Appendix B.](#) Document History

[[To be removed by the RFC Editor.]]

-07

- o Created a separate IANA registry for introspection responses, importing the values from JWT.

-06

- o Clarified relationship between AS and RS in introduction.
- o Used updated TLS text imported from Dyn-Reg drafts.
- o Clarified definition of active state.
- o Added some advice on caching responses.
- o Added security considerations on active state implementation.
- o Changed user_id to username based on WG feedback.

-05

- o Typo fix.
- o Updated author information.
- o Removed extraneous "linewrap" note from examples.

- 04

- o Removed "resource_id" from request.
- o Added examples.

- 03

- o Updated HTML and HTTP references.
- o Call for registration of parameters in the JWT registry.

- 02

- o Removed SAML pointer.
- o Clarified what an "active" token could be.
- o Explicitly declare introspection request as x-www-form-urlencoded format.
- o Added extended example.
- o Made protected resource authentication a MUST.

- 01

- o Fixed casing and consistent term usage.
- o Incorporated working group comments.

- o Clarified that authorization servers need to be able to understand the token if they're to introspect it.
- o Various editorial cleanups.

- 00

- o Created initial IETF draft based on [draft-richer-oauth-introspection-06](#) with no normative changes.

Author's Address

Justin Richer (editor)

Email: ietf@justin.richer.org

