

OAuth Working Group  
Internet-Draft  
Intended status: Standards Track  
Expires: December 12, 2019

N. Sakimura  
Nomura Research Institute  
J. Bradley  
Yubico  
June 10, 2019

The OAuth 2.0 Authorization Framework: JWT Secured Authorization Request  
(JAR)  
[draft-ietf-oauth-jwsreq-19](#)

Abstract

The authorization request in OAuth 2.0 described in [RFC 6749](#) utilizes query parameter serialization, which means that Authorization Request parameters are encoded in the URI of the request and sent through user agents such as web browsers. While it is easy to implement, it means that (a) the communication through the user agents are not integrity protected and thus the parameters can be tainted, and (b) the source of the communication is not authenticated. Because of these weaknesses, several attacks to the protocol have now been put forward.

This document introduces the ability to send request parameters in a JSON Web Token (JWT) instead, which allows the request to be signed with JSON Web Signature (JWS) and encrypted with JSON Web Encryption (JWE) so that the integrity, source authentication and confidentiality property of the Authorization Request is attained. The request can be sent by value or by reference.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on December 12, 2019.

## Copyright Notice

Copyright (c) 2019 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](https://trustee.ietf.org/license-info) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

<a href="#">1.</a>	<a href="#">Introduction</a>	<a href="#">3</a>
<a href="#">1.1.</a>	<a href="#">Requirements Language</a>	<a href="#">5</a>
<a href="#">2.</a>	<a href="#">Terminology</a>	<a href="#">5</a>
<a href="#">2.1.</a>	<a href="#">Request Object</a>	<a href="#">5</a>
<a href="#">2.2.</a>	<a href="#">Request Object URI</a>	<a href="#">6</a>
<a href="#">3.</a>	<a href="#">Symbols and abbreviated terms</a>	<a href="#">6</a>
<a href="#">4.</a>	<a href="#">Request Object</a>	<a href="#">6</a>
<a href="#">5.</a>	<a href="#">Authorization Request</a>	<a href="#">8</a>
<a href="#">5.1.</a>	<a href="#">Passing a Request Object by Value</a>	<a href="#">9</a>
<a href="#">5.2.</a>	<a href="#">Passing a Request Object by Reference</a>	<a href="#">9</a>
<a href="#">5.2.1.</a>	<a href="#">URI Referencing the Request Object</a>	<a href="#">11</a>
<a href="#">5.2.2.</a>	<a href="#">Request using the "request_uri" Request Parameter</a>	<a href="#">11</a>
<a href="#">5.2.3.</a>	<a href="#">Authorization Server Fetches Request Object</a>	<a href="#">11</a>
<a href="#">6.</a>	<a href="#">Validating JWT-Based Requests</a>	<a href="#">12</a>
<a href="#">6.1.</a>	<a href="#">Encrypted Request Object</a>	<a href="#">12</a>
<a href="#">6.2.</a>	<a href="#">JWS Signed Request Object</a>	<a href="#">13</a>
<a href="#">6.3.</a>	<a href="#">Request Parameter Assembly and Validation</a>	<a href="#">13</a>
<a href="#">7.</a>	<a href="#">Authorization Server Response</a>	<a href="#">13</a>
<a href="#">8.</a>	<a href="#">TLS Requirements</a>	<a href="#">13</a>
<a href="#">9.</a>	<a href="#">IANA Considerations</a>	<a href="#">14</a>
<a href="#">10.</a>	<a href="#">Security Considerations</a>	<a href="#">14</a>
<a href="#">10.1.</a>	<a href="#">Choice of Algorithms</a>	<a href="#">14</a>
<a href="#">10.2.</a>	<a href="#">Request Source Authentication</a>	<a href="#">15</a>
<a href="#">10.3.</a>	<a href="#">Explicit Endpoints</a>	<a href="#">15</a>
<a href="#">10.4.</a>	<a href="#">Risks Associated with request_uri</a>	<a href="#">16</a>
<a href="#">10.4.1.</a>	<a href="#">DDoS Attack on the Authorization Server</a>	<a href="#">16</a>
<a href="#">10.4.2.</a>	<a href="#">Request URI Rewrite</a>	<a href="#">16</a>
<a href="#">11.</a>	<a href="#">TLS security considerations</a>	<a href="#">17</a>
<a href="#">12.</a>	<a href="#">Privacy Considerations</a>	<a href="#">17</a>
<a href="#">12.1.</a>	<a href="#">Collection limitation</a>	<a href="#">17</a>
<a href="#">12.2.</a>	<a href="#">Disclosure Limitation</a>	<a href="#">18</a>



<a href="#">12.2.1.</a>	Request Disclosure . . . . .	<a href="#">18</a>
<a href="#">12.2.2.</a>	Tracking using Request Object URI . . . . .	<a href="#">18</a>
<a href="#">13.</a>	Acknowledgements . . . . .	<a href="#">18</a>
<a href="#">14.</a>	Revision History . . . . .	<a href="#">19</a>
<a href="#">15.</a>	References . . . . .	<a href="#">24</a>
<a href="#">15.1.</a>	Normative References . . . . .	<a href="#">25</a>
<a href="#">15.2.</a>	Informative References . . . . .	<a href="#">26</a>
	Authors' Addresses . . . . .	<a href="#">27</a>

## [1.](#) Introduction

The Authorization Request in OAuth 2.0 [[RFC6749](#)] utilizes query parameter serialization and is typically sent through user agents such as web browsers.

For example, the parameters "response\_type", "client\_id", "state", and "redirect\_uri" are encoded in the URI of the request:

```
GET /authorize?response_type=code&client_id=s6BhdRkqt3&state=xyz
&redirect_uri=https%3A%2F%2Fclient%2Eexample%2Ecom%2Fcb HTTP/1.1
Host: server.example.com
```

While it is easy to implement, the encoding in the URI does not allow application layer security with confidentiality and integrity protection to be used. While TLS is used to offer communication security between the Client and the user-agent as well as the user-agent and the Authorization Server, TLS sessions are terminated in the user-agent. In addition, TLS sessions may be terminated prematurely at some middlebox (such as a load balancer).

As the result, the Authorization Request of [[RFC6749](#)] has shortcomings in that:

- (a) the communication through the user agents are not integrity protected and thus the parameters can be tainted (integrity protection failure)
- (b) the source of the communication is not authenticated (source authentication failure)
- (c) the communication through the user agents can be monitored (containment / confidentiality failure).

Due to these inherent weaknesses, several attacks against the protocol, such as Redirection URI rewriting and Mix-up attack [[FETT](#)], have been identified.

The use of application layer security mitigates these issues.



The use of application layer security allows requests to be prepared by a third party so that a client application cannot request more permissions than previously agreed. This offers an additional degree of privacy protection.

Furthermore, the request by reference allows the reduction of over-the-wire overhead.

The JWT [[RFC7519](#)] encoding has been chosen because of

- (1) its close relationship with JSON, which is used as OAuth's response format
- (2) its developer friendliness due to its textual nature
- (3) its relative compactness compared to XML
- (4) its development status that it is an RFC and so is its associated signing and encryption methods as [[RFC7515](#)] and [[RFC7516](#)]
- (5) the relative ease of JWS and JWE compared to XML Signature and Encryption.

The parameters "request" and "request\_uri" are introduced as additional authorization request parameters for the OAuth 2.0 [[RFC6749](#)] flows. The "request" parameter is a JSON Web Token (JWT) [[RFC7519](#)] whose JWT Claims Set holds the JSON encoded OAuth 2.0 authorization request parameters. This JWT is integrity protected and source authenticated using JWS.

The JWT [[RFC7519](#)] can be passed to the authorization endpoint by reference, in which case the parameter "request\_uri" is used instead of the "request".

Using JWT [[RFC7519](#)] as the request encoding instead of query parameters has several advantages:

- (a) (integrity protection) The request can be signed so that the integrity of the request can be checked.
- (b) (source authentication) The request can be signed so that the signer can be authenticated.
- (c) (confidentiality protection) The request can be encrypted so that end-to-end confidentiality can be provided even if the TLS connection is terminated at one point or another.



- (d) (collection minimization) The request can be signed by a third party attesting that the authorization request is compliant with a certain policy. For example, a request can be pre-examined by a third party that all the personal data requested is strictly necessary to perform the process that the end-user asked for, and statically signed by that third party. The authorization server then examines the signature and shows the conformance status to the end-user, who would have some assurance as to the legitimacy of the request when authorizing it. In some cases, it may even be desirable to skip the authorization dialogue under such circumstances.

There are a few cases that request by reference is useful such as:

1. When it is desirable to reduce the size of transmitted request. The use of application layer security increases the size of the request, particularly when public key cryptography is used.
2. When the client does not want to do the crypto. The Authorization Server may provide an endpoint to accept the Authorization Request through direct communication with the Client so that the Client is authenticated and the channel is TLS protected.

This capability is in use by OpenID Connect [[OpenID.Core](#)].

### **1.1. Requirements Language**

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

## **2. Terminology**

For the purposes of this specification, the following terms and definitions in addition to what is defined in OAuth 2.0 Framework [[RFC6749](#)], JSON Web Signature [[RFC7515](#)], and JSON Web Encryption [[RFC7519](#)] apply.

### **2.1. Request Object**

JWT [[RFC7519](#)] that holds an OAuth 2.0 authorization request as JWT Claims Set





## **2.2. Request Object URI**

Absolute URI from which the Request Object ([Section 2.1](#)) can be obtained

## **3. Symbols and abbreviated terms**

The following abbreviations are common to this specification.

JSON Javascript Object Notation

JWT JSON Web Token

JWS JSON Web Signature

JWE JSON Web Encryption

URI Uniform Resource Identifier

URL Uniform Resource Locator

## **4. Request Object**

A Request Object ([Section 2.1](#)) is used to provide authorization request parameters for an OAuth 2.0 authorization request. It MUST contain all the OAuth 2.0 [[RFC6749](#)] authorization request parameters including extension parameters. The parameters are represented as the JWT claims. Parameter names and string values MUST be included as JSON strings. Since Request Objects are handled across domains and potentially outside of a closed ecosystem, per [section 8.1 of \[RFC8259\]](#), these JSON strings MUST be encoded using UTF-8 [[RFC3629](#)]. Numerical values MUST be included as JSON numbers. It MAY include any extension parameters. This JSON [[RFC7159](#)] constitutes the JWT Claims Set defined in JWT [[RFC7519](#)]. The JWT Claims Set is then signed or signed and encrypted.

To sign, JSON Web Signature (JWS) [[RFC7515](#)] is used. The result is a JWS signed JWT [[RFC7519](#)]. If signed, the Authorization Request Object SHOULD contain the Claims "iss" (issuer) and "aud" (audience) as members, with their semantics being the same as defined in the JWT [[RFC7519](#)] specification. The value of "aud" should be the value of the Authorization Server (AS) "issuer" as defined in [RFC8414](#) [[RFC8414](#)].

To encrypt, JWE [[RFC7516](#)] is used. When both signature and encryption are being applied, the JWT MUST be signed then encrypted as advised in the [section 11.2 of \[RFC7519\]](#). The result is a Nested JWT, as defined in [[RFC7519](#)].



The Authorization Request Object MAY be sent by value as described in [Section 5.1](#) or by reference as described in [Section 5.2](#).

"request" and "request\_uri" parameters MUST NOT be included in Request Objects.

The following is an example of the Claims in a Request Object before base64url encoding and signing. Note that it includes extension variables such as "nonce" and "max\_age".

```
{
  "iss": "s6BhdRkqt3",
  "aud": "https://server.example.com",
  "response_type": "code id_token",
  "client_id": "s6BhdRkqt3",
  "redirect_uri": "https://client.example.org/cb",
  "scope": "openid",
  "state": "af0ifjsldkj",
  "nonce": "n-0S6_WzA2Mj",
  "max_age": 86400
}
```

Signing it with the "RS256" algorithm results in this Request Object value (with line wraps within values for display purposes only):

eyJhbGciOiJSUzI1NiIsImtpZCI6Im9yYmRjIn0.ew0KICJpc3MiOiAic2ZCaGRSa3E0MjYsDQogImF1ZCI6ICJodHRwczovL3NlcnZlci5leGFtcGx1LmNvbSIsDQogInJlc3BvbmlX3R5cGUiOiAiY29kZSBpZF90b2t1biIsDQogImNsawVudF9pZCI6ICJzNkJoZFJrcXQzIiwNCiAicmVkaXJlY3RfdXJpIjogImh0dHBzOi8vY2xpZW50LmV4YW1wbgUub3JnL2NiIiwNCiAic2NvcGUiOiAib3Blbm1kIiwNCiAic3RhduiOiAiYWYwawZqc2xka2oiLA0KICJub25jZSI6ICJuLTBTNl9XekEyTWOiLA0KICJtYXhfYWdlIjogODY0MDAsDQogImNsYWltcyI6IA0KICB7DQogICAidXNlcm1uZm8iOiANCiAgICB7DQogICAgICJnaXZlbn19uYW11IjogeyJlc3NlbnRpYWwiOiB0cnVlfSwNCiAgICAgIm5pY2tuYW11IjogbnVsbCwNCiAgICAgImVtYWlsIjogeyJlc3NlbnRpYWwiOiB0cnVlfsWNCiAgICAgImVtYWlsX3Zlcm1maWVkJjogeyJlc3NlbnRpYWwiOiB0cnVlfsWNCiAgICAgInBpY3R1cmUiOiBudWxsDQogICAgfSwNCiAgICJpZF90b2t1biI6IA0KICAgIHsNCiAgICAgImdlbmRlciI6IG51bGwsDQogICAgICJiaXJ0aGRhdGuiOiB7ImVzc2VuZGlhbCI6IHRYdWV9LA0KICAgICAiYWNyIjogeyJ2YWx1ZXMiOiBbInVybjptYWNo10m1uY29tbW9uOmlhcDpzaWx2ZXIiX3R5cGUiOiB0cnVlfsWNCiAgICAgImVtYWlsX3Zlcm1maWVkJjogeyJlc3NlbnRpYWwiOiB0cnVlfsWNCiAgICAgInBpY3R1cmUiOiBudWxsDQogICAgfSwNCiAgICJpZF90b2t1biI6IA0KICAgIHsNCiAgICAgImdlbmRlciI6IG51bGwsDQogICAgICJiaXJ0aGRhdGuiOiB7ImVzc2VuZGlhbCI6IHRYdWV9LA0KICAgICAiYWNyIjogeyJ2YWx1ZXMiOiBbInVybjptYWNo10m1uY29tbW9uOmlhcDpzaWx2ZXIiX3R5cGUiOiB0cnVlfsWNCiAgICAgImVtYWlsX3Zlcm1maWVkJjogeyJlc3NlbnRpYWwiOiB0cnVlfsWNCiAgICAgInBpY3R1cmUiOiBudWxsDQogICAgfSwNCiAgICJpZF90b2t1biI6IA0KICAgIHsNCiAgICAgImdlbmRlciI6IG51bGwsDQogICAgICJiaXJ0aGRhdGuiOiB7ImVzc2VuZGlhbCI6IHRYdWV9LA0KICAgICAiYWNyIjogeyJ2YWx1ZXMiOiBbInVybjptYWNo10m1uY29tbW9uOmlhcDpzaWx2ZXIiX3R5cGUiOiB0cnVlfsWNCiAgICAgImVtYWlsX3Zlcm1maWVkJjogeyJlc3NlbnRpYWwiOiB0cnVlfsWNCiAgICAgInBpY3R1cmUiOiBudWxsDQogICAgfSwNCiAgICJpZF90b2t1biI6IA0KICAgIHsNCiAgICAgImdlbmRlciI6IG51bGwsDQogICAgICJiaXJ0aGRhdGuiOiB7ImVzc2VuZGlhbCI6IHRYdWV9LA0KICAgICAiYWNyIjogeyJ2YWx1ZXMiOiBbInVybjptYWNo10m1uY29tbW9uOmlhcDpzaWx2ZXIiX3R5cGUiOiB0cnVlfsWNCiAgICAgImVtYWlsX3Zlcm1maWVkJjogeyJlc3NlbnRpYWwiOiB0cnVlfsWNCiAgICAgInBpY3R1cmUiOiBudWxsDQogICAgfSwNCiAgICJpZF90b2t1biI6IA0KICAgIHsNCiAgICAgImdlbmRlciI6IG51bGwsDQogICAgICJiaXJ0aGRhdGuiOiB7ImVzc2VuZGlhbCI6IHRYdWV9LA0KICAgICAiYWNyIjogeyJ2YWx1ZXMiOiBbInVybjptYWNo10m1uY29tbW9uOmlhcDpzaWx2ZXIiX3R5cGUiOiB0cnVlfsWNCiAgICAgImVtYWlsX3Zlcm1maWVkJjogeyJlc3NlbnRpYWwiOiB0cnVlfsWNCiAgICAgInBpY3R1cmUiOiBudWxsDQogICAgfSwNCiAgICJpZF90b2t1biI6IA0KICAgIHsNCiAgICAgImdlbmRlciI6IG51bGwsDQogICAgICJiaXJ0aGRhdGuiOiB7ImVzc2VuZGlhbCI6IHRYdWV9LA0KICAgICAiYWNyIjogeyJ2YWx1ZXMiOiBbInVybjptYWNo10m1uY29tbW9uOmlhcDpzaWx2ZXIiX3R5cGUiOiB0cnVlfsWNCiAgICAgImVtYWlsX3Zlcm1maWVkJjogeyJlc3NlbnRpYWwiOiB0cnVlfsWNCiAgICAgInBpY3R1cmUiOiBudWxsDQogICAgfSwNCiAgICJpZF90b2t1biI6IA0KICAgIHsNCiAgICAgImdlbmRlciI6IG51bGwsDQogICAgICJiaXJ0aGRhdGuiOiB7ImVzc2VuZGlhbCI6IHRYdWV9LA0KICAgICAiYWNyIjogeyJ2YWx1ZXMiOiBbInVybjptYWNo10m1uY29tbW9uOmlhcDpzaWx2ZXIiX3R5cGUiOiB0cnVlfsWNCiAgICAgImVtYWlsX3Zlcm1maWVkJjogeyJlc3NlbnRpYWwiOiB0cnVlfsWNCiAgICAgInBpY3R1cmUiOiBudWxsDQogICAgfSwNCiAgICJpZF90b2t1biI6IA0KICAgIHsNCiAgICAgImdlbmRlciI6IG51bGwsDQogICAgICJiaXJ0aGRhdGuiOiB7ImVzc2VuZGlhbCI6IHRYdWV9LA0KICAgICAiYWNyIjogeyJ2YWx1ZXMiOiBbInVybjptYWNo10m1uY29tbW9uOmlhcDpzaWx2ZXIiX3R5cGUiOiB0cnVlfsWNCiAgICAgImVtYWlsX3Zlcm1maWVkJjogeyJlc3NlbnRpYWwiOiB0cnVlfsWNCiAgICAgInBpY3R1cmUiOiBudWxsDQogICAgfSwNCiAgICJpZF90b2t1biI6IA0KICAgIHsNCiAgICAgImdlbmRlciI6IG51bGwsDQogICAgICJiaXJ0aGRhdGuiOiB7ImVzc2VuZGlhbCI6IHRYdWV9LA0KICAgICAiYWNyIjogeyJ2YWx1ZXMiOiBbInVybjptYWNo10m1uY29tbW9uOmlhcDpzaWx2ZXIiX3R5cGUiOiB0cnVlfsWNCiAgICAgImVtYWlsX3Zlcm1maWVkJjogeyJlc3NlbnRpYWwiOiB0cnVlfsWNCiAgICAgInBpY3R1cmUiOiBudWxsDQogICAgfSwNCiAgICJpZF90b2t1biI6IA0KICAgIHsNCiAgICAgImdlbmRlciI6IG51bGwsDQogICAgICJiaXJ0aGRhdGuiOiB7ImVzc2VuZGlhbCI6IHRYdWV9LA0KICAgICAiYWNyIjogeyJ2YWx1ZXMiOiBbInVybjptYWNo10m1uY29tbW9uOmlhcDpzaWx2ZXIiX3R5cGUiOiB0cnVlfsWNCiAgICAgImVtYWlsX3Zlcm1maWVkJjogeyJlc3NlbnRpYWwiOiB0cnVlfsWNCiAgICAgInBpY3R1cmUiOiBudWxsDQogICAgfSwNCiAgICJpZF90b2t1biI6IA0KICAgIHsNCiAgICAgImdlbmRlciI6IG51bGwsDQogICAgICJiaXJ0aGRhdGuiOiB7ImVzc2VuZGlhbCI6IHRYdWV9LA0KICAgICAiYWNyIjogeyJ2YWx1ZXMiOiBbInVybjptYWNo10m1uY29tbW9uOmlhcDpzaWx2ZXIiX3R5cGUiOiB0cnVlfsWNCiAgICAgImVtYWlsX3Zlcm1maWVkJjogeyJlc3NlbnRpYWwiOiB0cnVlfsWNCiAgICAgInBpY3R1cmUiOiBudWxsDQogICAgfSwNCiAgICJpZF90b2t1biI6IA0KICAgIHsNCiAgICAgImdlbmRlciI6IG51bGwsDQogICAgICJiaXJ0aGRhdGuiOiB7ImVzc2VuZGlhbCI6IHRYdWV9LA0KICAgICAiYWNyIjogeyJ2YWx1ZXMiOiBbInVybjptYWNo10m1uY29tbW9uOmlhcDpzaWx2ZXIiX3R5cGUiOiB0cnVlfsWNCiAgICAgImVtYWlsX3Zlcm1maWVkJjogeyJlc3NlbnRpYWwiOiB0cnVlfsWNCiAgICAgInBpY3R1cmUiOiBudWxsDQogICAgfSwNCiAgICJpZF90b2t1biI6IA0KICAgIHsNCiAgICAgImdlbmRlciI6IG51bGwsDQogICAgICJiaXJ0aGRhdGuiOiB7ImVzc2VuZGlhbCI6IHRYdWV9LA0KICAgICAiYWNyIjogeyJ2YWx1ZXMiOiBbInVybjptYWNo10m1uY29tbW9uOmlhcDpzaWx2ZXIiX3R5cGUiOiB0cnVlfsWNCiAgICAgImVtYWlsX3Zlcm1maWVkJjogeyJlc3NlbnRpYWwiOiB0cnVlfsWNCiAgICAgInBpY3R1cmUiOiBudWxsDQogICAgfSwNCiAgICJpZF90b2t1biI6IA0KICAgIHsNCiAgICAgImdlbmRlciI6IG51bGwsDQogICAgICJiaXJ0aGRhdGuiOiB7ImVzc2VuZGlhbCI6IHRYdWV9LA0KICAgICAiYWNyIjogeyJ2YWx1ZXMiOiBbInVybjptYWNo10m1uY29tbW9uOmlhcDpzaWx2ZXIiX3R5cGUiOiB0cnVlfsWNCiAgICAgImVtYWlsX3Zlcm1maWVkJjogeyJlc3NlbnRpYWwiOiB0cnVlfsWNCiAgICAgInBpY3R1cmUiOiBudWxsDQogICAgfSwNCiAgICJpZF90b2t1biI6IA0KICAgIHsNCiAgICAgImdlbmRlciI6IG51bGwsDQogICAgICJiaXJ0aGRhdGuiOiB7ImVzc2VuZGlhbCI6IHRYdWV9LA0KICAgICAiYWNyIjogeyJ2YWx1ZXMiOiBbInVybjptYWNo10m1uY29tbW9uOmlhcDpzaWx2ZXIiX3R5cGUiOiB0cnVlfsWNCiAgICAgImVtYWlsX3Zlcm1maWVkJjogeyJlc3NlbnRpYWwiOiB0cnVlfsWNCiAgICAgInBpY3R1cmUiOiBudWxsDQogICAgfSwNCiAgICJpZF90b2t1biI6IA0KICAgIHsNCiAgICAgImdlbmRlciI6IG51bGwsDQogICAgICJiaXJ0aGRhdGuiOiB7ImVzc2VuZGlhbCI6IHRYdWV9LA0KICAgICAiYWNyIjogeyJ2YWx1ZXMiOiBbInVybjptYWNo10m1uY29tbW9uOmlhcDpzaWx2ZXIiX3R5cGUiOiB0cnVlfsWNCiAgICAgImVtYWlsX3Zlcm1maWVkJjogeyJlc3NlbnRpYWwiOiB0cnVlfsWNCiAgICAgInBpY3R1cmUiOiBudWxsDQogICAgfSwNCiAgICJpZF90b2t1biI6IA0KICAgIHsNCiAgICAgImdlbmRlciI6IG51bGwsDQogICAgICJiaXJ0aGRhdGuiOiB7ImVzc2VuZGlhbCI6IHRYdWV9LA0KICAgICAiYWNyIjogeyJ2YWx1ZXMiOiBbInVybjptYWNo10m1uY29tbW9uOmlhcDpzaWx2ZXIiX3R5cGUiOiB0cnVlfsWNCiAgICAgImVtYWlsX3Zlcm1maWVkJjogeyJlc3NlbnRpYWwiOiB0cnVlfsWNCiAgICAgInBpY3R1cmUiOiBudWxsDQogICAgfSwNCiAgICJpZF90b2t1biI6IA0KIC



The following RSA public key, represented in JWK format, can be used to validate the Request Object signature in this and subsequent Request Object examples (with line wraps within values for display purposes only):

```
{
  "kty": "RSA",
  "kid": "k2bdc",
  "n": "y9Lqv4fCp6Ei-u2-ZCKq83YvbFEk6JMs_pSj76eMkddWRuWX2aBKGHAtKlE5P
7_vn__PCKZWePt3vGkB6ePgZAFu08NmKemwE5bQI0e6kIChtt_6KzT50aaXDF
I6qCLJmk51Cc4VYFaxggevMncYrzaW_50mZ1yGSFIQzLYP8bijAHGVjdEFgZa
ZEN9lsn_GdWLJaJpHrB3R0lS50E45wxr1lg9xMncVb8qDPuXZarvghLL0Hz0uYR
adBJVowZowDNTpKpk2RklZ7QaB07XDv3uR7s_sf2g-bAjSYxYUGsqkNA9b3xV
w53am_UZZ3tZbFTIh557JICWKHlWj5uzeJXaw",
  "e": "AQAB"
}
```

## 5. Authorization Request

The client constructs the authorization request URI by adding one of the following parameters but not both to the query component of the authorization endpoint URI using the "application/x-www-form-urlencoded" format:

request The Request Object ([Section 2.1](#)) that holds authorization request parameters stated in [section 4](#) of OAuth 2.0 [[RFC6749](#)].

`request_uri` The absolute URI as defined by [RFC3986](#) [[RFC3986](#)] that points to the Request Object ([Section 2.1](#)) that holds authorization request parameters stated in [section 4](#) of OAuth 2.0 [[RFC6749](#)].

The client directs the resource owner to the constructed URI using an HTTP redirection response, or by other means available to it via the user-agent.

For example, the client directs the end user's user-agent to make the following HTTPS request:

```
GET /authz?request=eyJhbGciOiJIbGZwIiwiaWF0IjoxNjE2MjM5OTI5fQ.eyJ1b250b29udGVudCI6ImF1dG8iLCJ0eXBlIjoiYXV0aGVudGVudCJ9 HTTP/1.1
Host: server.example.com
```

The value for the request parameter is abbreviated for brevity.

The authorization request object **MUST** be one of the following:

- (a) JWS signed













### **5.2.1. URI Referencing the Request Object**

The Client stores the Request Object resource either locally or remotely at a URI the Authorization Server can access. Such facility may be provided by the authorization server or a third party. For example, the authorization server may provide a URL to which the client POSTs the request object and obtains the Request URI. This URI is the Request Object URI, "request\_uri".

It is possible for the Request Object to include values that are to be revealed only to the Authorization Server. As such, the "request\_uri" MUST have appropriate entropy for its lifetime. For the guidance, refer to 5.1.4.2.2 of [RFC6819]. It is RECOMMENDED that it be removed after a reasonable timeout unless access control measures are taken.

The following is an example of a Request Object URI value (with line wraps within values for display purposes only):

```
https://tfp.example.org/request.jwt#
GkurKxf5T0Y-mnPFCHqWOMiZi4VS138cQ0_V7PZHAdM
```

### **5.2.2. Request using the "request\_uri" Request Parameter**

The Client sends the Authorization Request to the Authorization Endpoint.

The following is an example of an Authorization Request using the "request\_uri" parameter (with line wraps within values for display purposes only):

```
https://server.example.com/authorize?
  response_type=code%20id_token
  &client_id=s6BhdRkqt3
  &request_uri=https%3A%2F%2Ftfp.example.org%2Frequest.jwt
  %23GkurKxf5T0Y-mnPFCHqWOMiZi4VS138cQ0_V7PZHAdM
  &state=af0ifjsldkj
```

### **5.2.3. Authorization Server Fetches Request Object**

Upon receipt of the Request, the Authorization Server MUST send an HTTP "GET" request to the "request\_uri" to retrieve the referenced Request Object, unless it is stored in a way so that it can retrieve it through other mechanism securely, and parse it to recreate the Authorization Request parameters.



The following is an example of this fetch process:

```
GET /request.jwt HTTP/1.1
Host: tfp.example.org
```

The following is an example of the fetch response:

```
HTTP/1.1 200 OK
Date: Thu, 16 Feb 2017 23:52:39 GMT
Server: Apache/2.2.22 (tfp.example.org)
Content-type: application/jwt
Content-Length: 1250
Last-Modified: Wed, 15 Feb 2017 23:52:32 GMT
```

```
eyJhbGciOiJSUzI1NiIsImtpZCI6ImNlcnZlci5leGFtcGxlImNvbSIsDQogInJl
c3BvbnNlX3R5cGU0IiAiY29kZSBpZDQogImNsaWVudF9pZCI6ICJzNk
JoZFJrcXQzIiwNCiAicmVkaXJlY3RfdXJpIjogImh0dHBzOi8vY2xpZW50LmV4YW1w
bGUub3JnL2NiIiwNCiAic2NvcGU0IiAib3BlbmlkIiwNCiAic3RhZGU0IiAiYWYwaW
Zqc2xka2oiLA0KICJub25jZSI6ICJuLTBTNl9XekEyT2oiLA0KICJtYXhfYWdlIjog
ODY0MDAsDQogImNsYWltcyI6IA0KICB7DQogICAidXNlcmZm8iOiANCiAgICB7DQ
ogICAgICJnaXZlbnl9uYw1lIjogeyJlc3NlbnRpYwWiOiB0cnVlfSwNCiAgICAgIm5p
Y2tuYW1lIjogbnVsbCwNCiAgICAgImVtYWlsIjogeyJlc3NlbnRpYwWiOiB0cnVlfS
wNCiAgICAgImVtYWlsX3ZlcmZmVkaXJogeyJlc3NlbnRpYwWiOiB0cnVlfSwNCiAg
ICAgInBpY3R1cmUiOiBudWxsDQogICAgfSwNCiAgICJpZDQogImNsaWVudF9pZCI6IA0K
ICAgIHsNCiAgICAgImdlbmRlciI6IG51bGwSDQogICAgICJiaXJ0aGRhdGU0IiB7ImVzc2Vu
dGhlbCI6IHRydWV9LA0KICAgICAiYWNyIjogeyJ2YXNlZXMiOiBbInVybjptYWNlOm
luY29tbW9uOm1hcDpzaWx2ZXIiXX0NCiAgICB9DQogIH0NCn0.nwwnNsk1-Zkbnvs
F6zTHm8CHERFMGQPhos-EJcaH4Hh-sMgk8ePrGhw_trPYs8KQxsn6R9Emo_wHwajyF
KzuMXZFSZ3p6Mb8dkxtVyjoy2GIzvuJT_u7PkY2t8QU9hjBcHs68PkgjDVTrG1uRTx
0GxFbuPbj96tVuJl1pTnmFCUR6IE0XKYr7iG0CRB3btfJhM0_AKQUfqKnRlrRsc8K
ol-cSLWoYE9l5QqholImzjT_cMnNIZnW9E7CDyWXTs070xnB4SkG6pXfLSjLLlXmPG
iyon_-Te111V8uE83IlzCYIb_NMXvtTIVc1jpspnTSD7xMbpL-2QgwUsAlMGzw
```

## 6. Validating JWT-Based Requests

### 6.1. Encrypted Request Object

If the request object is encrypted, the Authorization Server **MUST** decrypt the JWT in accordance with the JSON Web Encryption [[RFC7516](#)] specification.

The result is a signed request object.

If decryption fails, the Authorization Server **MUST** return an "invalid\_request\_object" error.



### **6.2. JWS Signed Request Object**

The Authorization Server MUST perform the signature validation of the JSON Web Signature [[RFC7515](#)] signed request object. For this, the "alg" Header Parameter in its JOSE Header MUST match the value of the pre-registered algorithm. The signature MUST be validated against the appropriate key for that "client\_id" and algorithm.

If signature validation fails, the Authorization Server MUST return an "invalid\_request\_object" error.

### **6.3. Request Parameter Assembly and Validation**

The Authorization Server MUST extract the set of Authorization Request parameters from the Request Object value. The Authorization Server MUST only use the parameters in the Request Object even if the same parameter is provided in the query parameter. The Authorization Server then validates the request as specified in OAuth 2.0 [[RFC6749](#)].

If the validation fails, then the Authorization Server MUST return an error as specified in OAuth 2.0 [[RFC6749](#)].

## **7. Authorization Server Response**

Authorization Server Response is created and sent to the client as in [Section 4](#) of OAuth 2.0 [[RFC6749](#)] .

In addition, this document uses these additional error values:

`invalid_request_uri` The "request\_uri" in the Authorization Request returns an error or contains invalid data.

`invalid_request_object` The request parameter contains an invalid Request Object.

`request_not_supported` The Authorization Server does not support the use of the "request" parameter.

`request_uri_not_supported` The Authorization Server does not support the use of the "request\_uri" parameter.

## **8. TLS Requirements**

Client implementations supporting the Request Object URI method MUST support TLS following Recommendations for Secure Use of Transport Layer Security (TLS) and Datagram Transport Layer Security (DTLS) [[BCP195](#)].





To protect against information disclosure and tampering, confidentiality protection MUST be applied using TLS with a cipher suite that provides confidentiality and integrity protection.

HTTP clients MUST also verify the TLS server certificate, using subjectAltName dNSName identities as described in [\[RFC6125\]](#), to avoid man-in-the-middle attacks. The rules and guidelines defined in [\[RFC6125\]](#) apply here, with the following considerations:

- o Support for DNS-ID identifier type (that is, the dNSName identity in the subjectAltName extension) is REQUIRED. Certification authorities which issue server certificates MUST support the DNS-ID identifier type, and the DNS-ID identifier type MUST be present in server certificates.
- o DNS names in server certificates MAY contain the wildcard character "\*".
- o Clients MUST NOT use CN-ID identifiers; a CN field may be present in the server certificate's subject name, but MUST NOT be used for authentication within the rules described in [\[BCP195\]](#).
- o SRV-ID and URI-ID as described in [Section 6.5 of \[RFC6125\]](#) MUST NOT be used for comparison.

## **9. IANA Considerations**

This specification requests no actions by IANA.

## **10. Security Considerations**

In addition to the all the security considerations discussed in OAuth 2.0 [\[RFC6819\]](#), the security considerations in [\[RFC7515\]](#), [\[RFC7516\]](#), and [\[RFC7518\]](#) needs to be considered. Also, there are several academic papers such as [\[BASIN\]](#) that provide useful insight into the security properties of protocols like OAuth.

In consideration of the above, this document advises taking the following security considerations into account.

### **10.1. Choice of Algorithms**

When sending the authorization request object through "request" parameter, it MUST either be signed using JWS [\[RFC7515\]](#) or encrypted using JWE [\[RFC7516\]](#) with then considered appropriate algorithm.



### **10.2. Request Source Authentication**

The source of the Authorization Request MUST always be verified. There are several ways to do it in this specification.

- (a) Verifying the JWS Signature of the Request Object.
- (b) Verifying that the symmetric key for the JWE encryption is the correct one if the JWE is using symmetric encryption.
- (c) Verifying the TLS Server Identity of the Request Object URI. In this case, the Authorization Server MUST know out-of-band that the Client uses Request Object URI and only the Client is covered by the TLS certificate. In general, it is not a reliable method.
- (d) Authorization Server is providing an endpoint that provides a Request Object URI in exchange for a Request Object. In this case, the Authorization Server MUST perform Client Authentication to accept the Request Object and bind the Client Identifier to the Request Object URI it is providing. Since Request Object URI can be replayed, the lifetime of the Request Object URI MUST be short and preferably one-time use. The entropy of the Request Object URI MUST be sufficiently large. The adequate shortness of the validity and the entropy of the Request Object URI depends on the risk calculation based on the value of the resource being protected. A general guidance for the validity time would be less than a minute and the Request Object URI is to include a cryptographic random value of 128bit or more at the time of the writing of this specification.
- (e) A third party, such as a Trust Framework Provider, provides an endpoint that provides a Request Object URI in exchange for a Request Object. The same requirements as (b) above apply. In addition, the Authorization Server MUST know out-of-band that the Client utilizes the Trust Framework Operator.

### **10.3. Explicit Endpoints**

Although this specification does not require them, research such as [\[BASIN\]](#) points out that it is a good practice to explicitly state the intended interaction endpoints and the message position in the sequence in a tamper evident manner so that the intent of the initiator is unambiguous. The endpoints that come into question in this specification are :

- (a) Protected Resources ("protected\_resources")



- (b) Authorization Endpoint ("authorization\_endpoint")
- (c) Redirection URI ("redirect\_uri")
- (d) Token Endpoint ("token\_endpoint")

Further, if dynamic discovery is used, then the discovery related endpoints also come into question.

In [RFC6749], while Redirection URI is included, others are not included in the Authorization Request. As the result, the same applies to Authorization Request Object.

The lack of the link among those endpoints are cited as the cause of Cross-Phase Attacks introduced in [FETT]. An extension specification should be created as a measure to address the risk.

#### **10.4. Risks Associated with request\_uri**

The introduction of "request\_uri" introduces several attack possibilities.

##### **10.4.1. DDoS Attack on the Authorization Server**

A set of malicious client can launch a DoS attack to the authorization server by pointing the "request\_uri" to a uri that returns extremely large content or extremely slow to respond. Under such an attack, the server may use up its resource and start failing.

Similarly, a malicious client can specify the "request\_uri" value that itself points to an authorization request URI that uses "request\_uri" to cause the recursive lookup.

To prevent such attack to succeed, the server should (a) check that the value of "request\_uri" parameter does not point to an unexpected location, (b) check the content type of the response is "application/jwt" (c) implement a time-out for obtaining the content of "request\_uri", and (d) do not perform recursive GET on the "request\_uri".

##### **10.4.2. Request URI Rewrite**

The value of "request\_uri" is not signed thus it can be tampered by Man-in-the-browser attacker. Several attack possibilities rise because of this, e.g., (a) attacker may create another file that the rewritten URI points to making it possible to request extra scope (b) attacker launches a DoS attack to a victim site by setting the value of "request\_uri" to be that of the victim.



To prevent such attack to succeed, the server should (a) check that the value of "request\_uri" parameter does not point to an unexpected location, (b) check the content type of the response is "application/jwt" (c) implement a time-out for obtaining the content of "request\_uri".

## **11. TLS security considerations**

Current security considerations can be found in Recommendations for Secure Use of TLS and DTLS [[BCP195](#)]. This supersedes the TLS version recommendations in OAuth 2.0 [[RFC6749](#)].

## **12. Privacy Considerations**

When the Client is being granted access to a protected resource containing personal data, both the Client and the Authorization Server need to adhere to Privacy Principles. [RFC 6973](#) Privacy Considerations for Internet Protocols [[RFC6973](#)] gives excellent guidance on the enhancement of protocol design and implementation. The provision listed in it should be followed.

Most of the provision would apply to The OAuth 2.0 Authorization Framework [[RFC6749](#)] and The OAuth 2.0 Authorization Framework: Bearer Token Usage [[RFC6750](#)] and are not specific to this specification. In what follows, only the specific provisions to this specification are noted.

### **12.1. Collection limitation**

When the Client is being granted access to a protected resource containing personal data, the Client SHOULD limit the collection of personal data to that which is within the bounds of applicable law and strictly necessary for the specified purpose(s).

It is often hard for the user to find out if the personal data asked for is strictly necessary. A Trust Framework Provider can help the user by examining the Client request and comparing to the proposed processing by the Client and certifying the request. After the certification, the Client, when making an Authorization Request, can submit Authorization Request to the Trust Framework Provider to obtain the Request Object URI.

Upon receiving such Request Object URI in the Authorization Request, the Authorization Server first verifies that the authority portion of the Request Object URI is a legitimate one for the Trust Framework Provider. Then, the Authorization Server issues HTTP GET request to the Request Object URI. Upon connecting, the Authorization Server MUST verify the server identity represented in the TLS certificate is





legitimate for the Request Object URI. Then, the Authorization Server can obtain the Request Object, which includes the "client\_id" representing the Client.

The Consent screen MUST indicate the Client and SHOULD indicate that the request has been vetted by the Trust Framework Operator for the adherence to the Collection Limitation principle.

## **12.2. Disclosure Limitation**

### **12.2.1. Request Disclosure**

This specification allows extension parameters. These may include potentially sensitive information. Since URI query parameter may leak through various means but most notably through referrer and browser history, if the authorization request contains a potentially sensitive parameter, the Client SHOULD JWE [RFC7516] encrypt the request object.

Where Request Object URI method is being used, if the request object contains personally identifiable or sensitive information, the "request\_uri" SHOULD be used only once, have a short validity period, and MUST have large enough entropy deemed necessary with applicable security policy unless the Request Object itself is JWE [RFC7516] Encrypted. The adequate shortness of the validity and the entropy of the Request Object URI depends on the risk calculation based on the value of the resource being protected. A general guidance for the validity time would be less than a minute and the Request Object URI is to include a cryptographic random value of 128bit or more at the time of the writing of this specification.

### **12.2.2. Tracking using Request Object URI**

Even if the protected resource does not include a personally identifiable information, it is sometimes possible to identify the user through the Request Object URI if persistent per-user Request Object URI is used. A third party may observe it through browser history etc. and start correlating the user's activity using it. In a way, it is a data disclosure as well and should be avoided.

Therefore, per-user Request Object URI should be avoided.

## **13. Acknowledgements**

The following people contributed to the creation of this document in the OAuth WG. (Affiliations at the time of the contribution are used.)



Sergey Beryozkin, Brian Campbell (Ping Identity), Vladimir Dzhuvinov (Connect2id), Michael B. Jones (Microsoft), Torsten Lodderstedt (YES) Jim Manico, Axel Nenker (Deutsche Telecom), Hannes Tschofenig (ARM), Ben Campbell, Kathleen Moriarty (as AD), and Steve Kent (as SECDIR).

The following people contributed to creating this document through the OpenID Connect Core 1.0 [[OpenID.Core](#)].

Brian Campbell (Ping Identity), George Fletcher (AOL), Ryo Itou (Mixi), Edmund Jay (Illumila), Michael B. Jones (Microsoft), Breno de Medeiros (Google), Hideki Nara (TACT), Justin Richer (MITRE).

In addition, the following people contributed to this and previous versions through the OAuth Working Group.

Dirk Balfanz (Google), James H. Manger (Telstra), John Panzer (Google), David Recordon (Facebook), Marius Scurtescu (Google), Luke Shepard (Facebook).

## **14. Revision History**

Note to the RFC Editor: Please remove this section from the final RFC.

-19

- o AD cooments
- o [Section 5.2.1](#). s/Requiest URI/Request URI/
- o [Section 8](#) s/[[BCP195](#)] ./[[BCP195](#)]./
- o [Section 10.3](#). s/sited/cited/
- o [Section 11](#). Typo. s/Curent/Current/

-17

- o #78 Typos in content-type

-16

- o Treated remaining Ben Campbell comments.

-15

- o Removed further duplication



-14

- o #71 Reiterate dynamic params are included.
- o #70 Made clear that AS must return error.
- o #69 Inconsistency of the need to sign.
- o Fixed Mime-type.
- o #67 Inconsistence in requiring HTTPS in request uri.
- o #66 Dropped ISO 29100 reference.
- o #25 Removed Encrypt only option.
- o #59 Same with #25.

-13

- o add TLS Security Consideration section
- o replace [RFC7525](#) reference with [BCP195](#)
- o moved front tag in FETT reference to fix XML structure
- o changes reference from SoK to FETT

-12

- o fixes #62 - Alexey Melnikov Discuss
- o fixes #48 - OPSDIR Review : General - delete semicolons after list items
- o fixes #58 - DP Comments for the Last Call
- o fixes #57 - GENART - Remove "non-normative ... " from examples.
- o fixes #45 - OPSDIR Review : Introduction - are attacks discovered or already opened
- o fixes #49 - OPSDIR Review : Introduction - Inconsistent colons after initial sentence of list items.
- o fixes #53 - OPSDIR Review : 6.2 JWS Signed Request Object - Clarify JOSE Header



- o fixes #42 - OPSDIR Review : Introduction - readability of 'and' is confusing
- o fixes #50 - OPSDIR Review : [Section 4](#) Request Object - Clarify 'signed, encrypted, or signed and encrypted'
- o fixes #39 - OPSDIR Review : Abstract - Explain/Clarify JWS and JWE
- o fixed #50 - OPSDIR Review : [Section 4](#) Request Object - Clarify 'signed, encrypted, or signed and encrypted'
- o fixes #43 - OPSDIR Review : Introduction - 'properties' sounds awkward and are not exactly 'properties'
- o fixes #56 - OPSDIR Review : 12 Acknowledgements - 'contribution is' => 'contribution are'
- o fixes #55 - OPSDIR Review : 11.2.2 Privacy Considerations - ' It is in a way' => 'In a way, it is'
- o fixes #54 - OPSDIR Review : 11 Privacy Considerations - 'and not specific' => 'and are not specific'
- o fixes #51 - OPSDIR Review : [Section 4](#) Request Object - 'It is fine' => 'It is recommended'
- o fixes #47 - OPSDIR Review : Introduction - 'over- the- wire' => 'over-the-wire'
- o fixes #46 - OPSDIR Review : Introduction - 'It allows' => 'The use of application security' for
- o fixes #44 - OPSDIR Review : Introduction - 'has' => 'have'
- o fixes #41 - OPSDIR Review : Introduction - missing 'is' before 'typically sent'
- o fixes #38 - OPSDIR Review : [Section 11](#) - Delete 'freely accessible' regarding ISO 29100

-11

- o s/bing/being/

- o Added history for -10

-10





- o #20: KM1 -- some wording that is awkward in the TLS section.
  - o #21: KM2 - the additional attacks against OAuth 2.0 should also have a pointer
  - o #22: KM3 -- Nit: in the first line of 10.4:
  - o #23: KM4 -- Mention [RFC6973](#) in [Section 11](#) in addition to ISO 29100
  - o #24: SECDIR review: [Section 4](#) -- Confusing requirements for sign+encrypt
  - o #25: SECDIR review: [Section 6](#) -- authentication and integrity need not be provided if the requestor encrypts the token?
  - o #26: SECDIR Review: [Section 10](#) -- why no reference for JWS algorithms?
  - o #27: SECDIR Review: [Section 10.2](#) - how to do the agreement between client and server "a priori"?
  - o #28: SECDIR Review: [Section 10.3](#) - Indication on "large entropy" and "short lifetime" should be indicated
  - o #29: SECDIR Review: [Section 10.3](#) - Typo
  - o #30: SECDIR Review: [Section 10.4](#) - typos and missing articles
  - o #31: SECDIR Review: [Section 10.4](#) - Clearer statement on the lack of endpoint identifiers needed
  - o #32: SECDIR Review: [Section 11](#) - ISO29100 needs to be moved to normative reference
  - o #33: SECDIR Review: [Section 11](#) - Better English and Entropy language needed
  - o #34: [Section 4](#): Typo
  - o #35: More Acknowledgment
  - o #36: DP - More precise qualification on Encryption needed.
- 09
- o Minor Editorial Nits.
  - o [Section 10.4](#) added.



- o Explicit reference to Security consideration (10.2) added in [section 5](#) and [section 5.2](#).
- o , (add yourself) removed from the acknowledgment.

-08

- o Applied changes proposed by Hannes on 2016-06-29 on IETF OAuth list recorded as <https://bitbucket.org/Nat/oauth-jwsreq/issues/12/>.
- o TLS requirements added.
- o Security Consideration reinforced.
- o Privacy Consideration added.
- o Introduction improved.

-07

- o Changed the abbrev to OAuth JAR from oauth-jar.
- o Clarified sig and enc methods.
- o Better English.
- o Removed claims from one of the example.
- o Re-worded the URI construction.
- o Changed the example to use request instead of request\_uri.
- o Clarified that Request Object parameters take precedence regardless of request or request\_uri parameters were used.
- o Generalized the language in 4.2.1 to convey the intent more clearly.
- o Changed "Server" to "Authorization Server" as a clarification.
- o Stopped talking about request\_object\_signing\_alg.
- o IANA considerations now reflect the current status.
- o Added Brian Campbell to the contributors list. Made the lists alphabetic order based on the last names. Clarified that the affiliation is at the time of the contribution.



- o Added "older versions of " to the reference to IE uri length limitations.
- o Stopped talking about signed or unsigned JWS etc.
- o 1.Introduction improved.

-06

- o Added explanation on the 512 chars URL restriction.
- o Updated Acknowledgements.

-05

- o More alignment with OpenID Connect.

-04

- o Fixed typos in examples. (request\_url -> request\_uri, cliend\_id -> client\_id)
- o Aligned the error messages with the OAuth IANA registry.
- o Added another rationale for having request object.

-03

- o Fixed the non-normative description about the advantage of static signature.
- o Changed the requirement for the parameter values in the request itself and the request object from 'MUST MATCH' to 'Req Obj takes precedence.

-02

- o Now that they are RFCs, replaced JWS, JWE, etc. with RFC numbers.

-01

- o Copy Edits.

## [15.](#) References



### **15.1. Normative References**

- [BCP195] Sheffer, Y., Holz, R., and P. Saint-Andre, "Recommendations for Secure Use of Transport Layer Security (TLS) and Datagram Transport Layer Security (DTLS)", [BCP 195](#), [RFC 7525](#), May 2015.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC3629] Yergeau, F., "UTF-8, a transformation format of ISO 10646", STD 63, [RFC 3629](#), DOI 10.17487/RFC3629, November 2003, <<https://www.rfc-editor.org/info/rfc3629>>.
- [RFC3986] Berners-Lee, T., Fielding, R., and L. Masinter, "Uniform Resource Identifier (URI): Generic Syntax", STD 66, [RFC 3986](#), DOI 10.17487/RFC3986, January 2005, <<https://www.rfc-editor.org/info/rfc3986>>.
- [RFC6125] Saint-Andre, P. and J. Hodges, "Representation and Verification of Domain-Based Application Service Identity within Internet Public Key Infrastructure Using X.509 (PKIX) Certificates in the Context of Transport Layer Security (TLS)", [RFC 6125](#), DOI 10.17487/RFC6125, March 2011, <<https://www.rfc-editor.org/info/rfc6125>>.
- [RFC6749] Hardt, D., Ed., "The OAuth 2.0 Authorization Framework", [RFC 6749](#), DOI 10.17487/RFC6749, October 2012, <<https://www.rfc-editor.org/info/rfc6749>>.
- [RFC6750] Jones, M. and D. Hardt, "The OAuth 2.0 Authorization Framework: Bearer Token Usage", [RFC 6750](#), DOI 10.17487/RFC6750, October 2012, <<https://www.rfc-editor.org/info/rfc6750>>.
- [RFC7159] Bray, T., Ed., "The JavaScript Object Notation (JSON) Data Interchange Format", [RFC 7159](#), DOI 10.17487/RFC7159, March 2014, <<https://www.rfc-editor.org/info/rfc7159>>.
- [RFC7230] Fielding, R., Ed. and J. Reschke, Ed., "Hypertext Transfer Protocol (HTTP/1.1): Message Syntax and Routing", [RFC 7230](#), DOI 10.17487/RFC7230, June 2014, <<https://www.rfc-editor.org/info/rfc7230>>.





- [RFC7515] Jones, M., Bradley, J., and N. Sakimura, "JSON Web Signature (JWS)", [RFC 7515](#), DOI 10.17487/RFC7515, May 2015, <<https://www.rfc-editor.org/info/rfc7515>>.
- [RFC7516] Jones, M. and J. Hildebrand, "JSON Web Encryption (JWE)", [RFC 7516](#), DOI 10.17487/RFC7516, May 2015, <<https://www.rfc-editor.org/info/rfc7516>>.
- [RFC7518] Jones, M., "JSON Web Algorithms (JWA)", [RFC 7518](#), DOI 10.17487/RFC7518, May 2015, <<https://www.rfc-editor.org/info/rfc7518>>.
- [RFC7519] Jones, M., Bradley, J., and N. Sakimura, "JSON Web Token (JWT)", [RFC 7519](#), DOI 10.17487/RFC7519, May 2015, <<https://www.rfc-editor.org/info/rfc7519>>.
- [RFC8141] Saint-Andre, P. and J. Klensin, "Uniform Resource Names (URNs)", [RFC 8141](#), DOI 10.17487/RFC8141, April 2017, <<https://www.rfc-editor.org/info/rfc8141>>.
- [RFC8259] Bray, T., Ed., "The JavaScript Object Notation (JSON) Data Interchange Format", STD 90, [RFC 8259](#), DOI 10.17487/RFC8259, December 2017, <<https://www.rfc-editor.org/info/rfc8259>>.
- [RFC8414] Jones, M., Sakimura, N., and J. Bradley, "OAuth 2.0 Authorization Server Metadata", [RFC 8414](#), DOI 10.17487/RFC8414, June 2018, <<https://www.rfc-editor.org/info/rfc8414>>.

## **15.2. Informative References**

- [BASIN] Basin, D., Cremers, C., and S. Meier, "Provably Repairing the ISO/IEC 9798 Standard for Entity Authentication", Journal of Computer Security - Security and Trust Principles Volume 21 Issue 6, Pages 817-846, November 2013, <<https://www.cs.ox.ac.uk/people/cas.cremers/downloads/papers/BCM2012-iso9798.pdf>>.
- [FETT] Fett, D., Kusters, R., and G. Schmitz, "A Comprehensive Formal Security Analysis of OAuth 2.0", CCS '16 Proceedings of the 2016 ACM SIGSAC Conference on Computer and Communications Security Pages 1204-1215 , October 2016, <<https://infsec.univ-trier.de/people/publications/paper/FettKuestersSchmitz-CCS-2016.pdf>>.



## [OpenID.Core]

Sakimura, N., Bradley, J., Jones, M., de Medeiros, B., and C. Mortimore, "OpenID Connect Core 1.0", OpenID Foundation Standards, February 2014, <[http://openid.net/specs/openid-connect-core-1\\_0.html](http://openid.net/specs/openid-connect-core-1_0.html)>.

[RFC6819] Lodderstedt, T., Ed., McGloin, M., and P. Hunt, "OAuth 2.0 Threat Model and Security Considerations", [RFC 6819](#), DOI 10.17487/RFC6819, January 2013, <<https://www.rfc-editor.org/info/rfc6819>>.

[RFC6973] Cooper, A., Tschofenig, H., Aboba, B., Peterson, J., Morris, J., Hansen, M., and R. Smith, "Privacy Considerations for Internet Protocols", [RFC 6973](#), DOI 10.17487/RFC6973, July 2013, <<https://www.rfc-editor.org/info/rfc6973>>.

## Authors' Addresses

Nat Sakimura  
Nomura Research Institute  
Otemachi Financial City Grand Cube, 1-9-2 Otemachi  
Chiyoda-ku, Tokyo 100-0004  
Japan

Phone: +81-3-5533-2111  
Email: [n-sakimura@nri.co.jp](mailto:n-sakimura@nri.co.jp)  
URI: <http://nat.sakimura.org/>

John Bradley  
Yubico  
Casilla 177, Sucursal Talagante  
Talagante, RM  
Chile

Phone: +1.202.630.5272  
Email: [ve7jtb@ve7jtb.com](mailto:ve7jtb@ve7jtb.com)  
URI: <http://www.thread-safe.com/>

