

OAuth Working Group
Internet-Draft
Intended status: Standards Track
Expires: January 15, 2014

B. Campbell
Ping Identity
C. Mortimore
Salesforce
M. Jones
Microsoft
July 14, 2013

**SAML 2.0 Profile for OAuth 2.0 Client Authentication and Authorization
Grants
draft-ietf-oauth-saml2-bearer-17**

Abstract

This specification defines the use of a SAML 2.0 Bearer Assertion as a means for requesting an OAuth 2.0 access token as well as for use as a means of client authentication.

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on January 15, 2014.

Copyright Notice

Copyright (c) 2013 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in [Section 4](#).e of

the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	3
1.1.	Notational Conventions	4
1.2.	Terminology	4
2.	HTTP Parameter Bindings for Transporting Assertions	4
2.1.	Using SAML Assertions as Authorization Grants	5
2.2.	Using SAML Assertions for Client Authentication	5
3.	Assertion Format and Processing Requirements	6
3.1.	Authorization Grant Processing	8
3.2.	Client Authentication Processing	9
4.	Authorization Grant Example	9
5.	Interoperability Considerations	11
6.	Security Considerations	11
7.	IANA Considerations	11
7.1.	Sub-Namespace Registration of urn:ietf:params:oauth:grant-type:saml2-bearer	11
7.2.	Sub-Namespace Registration of urn:ietf:params:oauth:client-assertion-type:saml2-bearer	12
8.	References	12
8.1.	Normative References	12
8.2.	Informative References	13
Appendix A.	Acknowledgements	13
Appendix B.	Document History	14
Authors' Addresses	19

1. Introduction

The Security Assertion Markup Language (SAML) 2.0 [[OASIS.saml-core-2.0-os](#)] is an XML-based framework that allows identity and security information to be shared across security domains. The SAML specification, while primarily targeted at providing cross domain Web browser single sign-on, was also designed to be modular and extensible to facilitate use in other contexts.

The Assertion, an XML security token, is a fundamental construct of SAML that is often adopted for use in other protocols and specifications. An Assertion is generally issued by an identity provider and consumed by a service provider who relies on its content to identify the Assertion's subject for security related purposes.

The OAuth 2.0 Authorization Framework [[RFC6749](#)] provides a method for making authenticated HTTP requests to a resource using an access token. Access tokens are issued to third-party clients by an authorization server (AS) with the (sometimes implicit) approval of the resource owner. In OAuth, an authorization grant is an abstract term used to describe intermediate credentials that represent the resource owner authorization. An authorization grant is used by the client to obtain an access token. Several authorization grant types are defined to support a wide range of client types and user experiences. OAuth also allows for the definition of new extension grant types to support additional clients or to provide a bridge between OAuth and other trust frameworks. Finally, OAuth allows the definition of additional authentication mechanisms to be used by clients when interacting with the authorization server.

The Assertion Framework for OAuth 2.0 Client Authentication and Authorization Grants [[I-D.ietf-oauth-assertions](#)] specification is an abstract extension to OAuth 2.0 that provides a general framework for the use of Assertions as client credentials and/or authorization grants with OAuth 2.0. This specification profiles the Assertion Framework for OAuth 2.0 Client Authentication and Authorization Grants [[I-D.ietf-oauth-assertions](#)] specification to define an extension grant type that uses a SAML 2.0 Bearer Assertion to request an OAuth 2.0 access token as well as for use as client credentials. The format and processing rules for the SAML Assertion defined in this specification are intentionally similar, though not identical, to those in the Web Browser SSO Profile defined in the SAML Profiles [[OASIS.saml-profiles-2.0-os](#)] specification. This specification is reusing, to the extent reasonable, concepts and patterns from that well-established Profile.

This document defines how a SAML Assertion can be used to request an access token when a client wishes to utilize an existing trust

relationship, expressed through the semantics of (and digital signature or keyed message digest calculated over) the SAML Assertion, without a direct user approval step at the authorization server. It also defines how a SAML Assertion can be used as a client authentication mechanism. The use of an Assertion for client authentication is orthogonal to and separable from using an Assertion as an authorization grant. They can be used either in combination or separately. Client assertion authentication is nothing more than an alternative way for a client to authenticate to the token endpoint and must be used in conjunction with some grant type to form a complete and meaningful protocol request. Assertion authorization grants may be used with or without client authentication or identification. Whether or not client authentication is needed in conjunction with an assertion authorization grant, as well as the supported types of client authentication, are policy decisions at the discretion of the authorization server.

The process by which the client obtains the SAML Assertion, prior to exchanging it with the authorization server or using it for client authentication, is out of scope.

1.1. Notational Conventions

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

Unless otherwise noted, all the protocol parameter names and values are case sensitive.

1.2. Terminology

All terms are as defined in The OAuth 2.0 Authorization Framework [[RFC6749](#)], the Assertion Framework for OAuth 2.0 Client Authentication and Authorization Grants [[I-D.ietf-oauth-assertions](#)], and the Security Assertion Markup Language (SAML) 2.0 [[OASIS.saml-core-2.0-os](#)] specifications.

2. HTTP Parameter Bindings for Transporting Assertions

The Assertion Framework for OAuth 2.0 Client Authentication and Authorization Grants [[I-D.ietf-oauth-assertions](#)] specification defines generic HTTP parameters for transporting Assertions during interactions with a token endpoint. This section defines specific parameters and treatments of those parameters for use with SAML 2.0 Bearer Assertions.

2.1. Using SAML Assertions as Authorization Grants

To use a SAML Bearer Assertion as an authorization grant, use an access token request as defined in [Section 4](#) of the Assertion Framework for OAuth 2.0 Client Authentication and Authorization Grants [[I-D.ietf-oauth-assertions](#)] specification with the following specific parameter values and encodings.

The value of the "grant_type" parameter MUST be "urn:ietf:params:oauth:grant-type:saml2-bearer".

The value of the "assertion" parameter MUST contain a single SAML 2.0 Assertion. The SAML Assertion XML data MUST be encoded using base64url, where the encoding adheres to the definition in [Section 5 of RFC 4648](#) [[RFC4648](#)] and where the padding bits are set to zero. To avoid the need for subsequent encoding steps (by "application/x-www-form-urlencoded" [[W3C.REC-html401-19991224](#)], for example), the base64url encoded data SHOULD NOT be line wrapped and pad characters ("=") SHOULD NOT be included.

The "scope" parameter may be used, as defined in the Assertion Framework for OAuth 2.0 Client Authentication and Authorization Grants [[I-D.ietf-oauth-assertions](#)] specification, to indicate the requested scope.

Authentication of the client is optional, as described in [Section 3.2.1](#) of OAuth 2.0 [[RFC6749](#)] and consequently, the "client_id" is only needed when a form of client authentication that relies on the parameter is used.

The following non-normative example demonstrates an Access Token Request with an assertion as an authorization grant (with extra line breaks for display purposes only):

```
POST /token.oauth2 HTTP/1.1
Host: as.example.com
Content-Type: application/x-www-form-urlencoded

grant_type=urn%3Aietf%3Aparams%3Aoauth%3Agrant-type%3Asaml2-bearer&
assertion=PHNhbWxwO1...[omitted for brevity]...ZT4
```

2.2. Using SAML Assertions for Client Authentication

To use a SAML Bearer Assertion for client authentication, use the following parameter values and encodings.

The value of the "client_assertion_type" parameter MUST be "urn:ietf:params:oauth:client-assertion-type:saml2-bearer".

The value of the "client_assertion" parameter MUST contain a single SAML 2.0 Assertion. The SAML Assertion XML data MUST be encoded using base64url, where the encoding adheres to the definition in [Section 5 of RFC 4648](#) [[RFC4648](#)] and where the padding bits are set to zero. To avoid the need for subsequent encoding steps (by "application/x-www-form-urlencoded" [[W3C.REC-html401-19991224](#)], for example), the base64url encoded data SHOULD NOT be line wrapped and pad characters ("=") SHOULD NOT be included.

The following non-normative example demonstrates a client authenticating using an assertion during the presentation of an authorization code grant in an Access Token Request (with extra line breaks for display purposes only):

```
POST /token.oauth2 HTTP/1.1
Host: as.example.com
Content-Type: application/x-www-form-urlencoded

grant_type=authorization_code&
code=vAZEIHjQTHuGgaSvyW9h00RpusLzkvT0ww3trZBxZpo&
client_assertion_type=urn%3Aietf%3Aparams%3Aoauth
%3Aclient-assertion-type%3Asaml2-bearer&
client_assertion=PHNhbW...[omitted for brevity]...ZT
```

3. Assertion Format and Processing Requirements

In order to issue an access token response as described in OAuth 2.0 [[RFC6749](#)] or to rely on an Assertion for client authentication, the authorization server MUST validate the Assertion according to the criteria below. Application of additional restrictions and policy are at the discretion of the authorization server.

1. The Assertion's <Issuer> element MUST contain a unique identifier for the entity that issued the Assertion. Issuer values SHOULD be compared using the Simple String Comparison method defined in [Section 6.2.1 of RFC 3986](#) [[RFC3986](#)], unless otherwise specified by the application.
2. The Assertion MUST contain a <Conditions> element with an <AudienceRestriction> element with an <Audience> element that identifies the authorization server as an intended audience. [Section 2.5.1.4](#) of Assertions and Protocols for the OASIS Security Assertion Markup Language [[OASIS.saml-core-2.0-os](#)] defines the <AudienceRestriction> and <Audience> elements and, in addition to the URI references discussed there, the token endpoint URL of the authorization server MAY be used as a URI that identifies the authorization server as an intended

- audience. Assertions that do not identify the Authorization Server as an intended audience **MUST** be rejected. Audience values **SHOULD** be compared using the Simple String Comparison method defined in [Section 6.2.1 of RFC 3986](#) [RFC3986], unless otherwise specified by the application.
3. The Assertion **MUST** contain a <Subject> element. The subject **MAY** identify the resource owner for Additional information identifying the subject/principal of the transaction **MAY** be included in an <AttributeStatement>.
 - A. When using an Assertion as an authorization grant, the Subject **SHOULD** identify an authorized accessor for whom the access token is being requested (typically the resource owner, or an authorized delegate).
 - B. For client authentication, the Subject **MUST** be the "client_id" of the OAuth client.
 4. The Assertion **MUST** have an expiry that limits the time window during which it can be used. The expiry can be expressed either as the NotOnOrAfter attribute of the <Conditions> element or as the NotOnOrAfter attribute of a suitable <SubjectConfirmationData> element.
 5. The <Subject> element **MUST** contain at least one <SubjectConfirmation> element that allows the authorization server to confirm it as a Bearer Assertion. Such a <SubjectConfirmation> element **MUST** have a Method attribute with a value of "urn:oasis:names:tc:SAML:2.0:cm:bearer". The <SubjectConfirmation> element **MUST** contain a <SubjectConfirmationData> element, unless the Assertion has a suitable NotOnOrAfter attribute on the <Conditions> element, in which case the <SubjectConfirmationData> element **MAY** be omitted. When present, the <SubjectConfirmationData> element **MUST** have a Recipient attribute with a value indicating the token endpoint URL of the authorization server (or an acceptable alias). The authorization server **MUST** verify that the value of the Recipient attribute matches the token endpoint URL (or an acceptable alias) to which the Assertion was delivered. The <SubjectConfirmationData> element **MUST** have a NotOnOrAfter attribute that limits the window during which the Assertion can be confirmed. The <SubjectConfirmationData> element **MAY** also contain an Address attribute limiting the client address from which the Assertion can be delivered. Verification of the Address is at the discretion of the authorization server.

6. The authorization server MUST verify that the NotOnOrAfter instant has not passed, subject to allowable clock skew between systems. An invalid NotOnOrAfter instant on the <Conditions> element invalidates the entire Assertion. An invalid NotOnOrAfter instant on a <SubjectConfirmationData> element only invalidates the individual <SubjectConfirmation>. The authorization server MAY reject Assertions with a NotOnOrAfter instant that is unreasonably far in the future. The authorization server MAY ensure that Bearer Assertions are not replayed, by maintaining the set of used ID values for the length of time for which the Assertion would be considered valid based on the applicable NotOnOrAfter instant.
7. If the Assertion issuer authenticated the subject, the Assertion SHOULD contain a single <AuthnStatement> representing that authentication event.
8. If the Assertion was issued with the intention that the presenter act autonomously on behalf of the subject, an <AuthnStatement> SHOULD NOT be included. The presenter SHOULD be identified in the <NameID> or similar element in the <SubjectConfirmation> element, or by other available means like SAML V2.0 Condition for Delegation Restriction [[OASIS.saml-deleg-cs](#)].
9. Other statements, in particular <AttributeStatement> elements, MAY be included in the Assertion.
10. The Assertion MUST be digitally signed or have a keyed message digest applied by the issuer. The authorization server MUST reject assertions with an invalid signature or keyed message digest.
11. Encrypted elements MAY appear in place of their plain text counterparts as defined in [[OASIS.saml-core-2.0-os](#)].
12. The authorization server MUST verify that the Assertion is valid in all other respects per [[OASIS.saml-core-2.0-os](#)], such as (but not limited to) evaluating all content within the Conditions element including the NotOnOrAfter and NotBefore attributes, rejecting unknown condition types, etc.

[3.1. Authorization Grant Processing](#)

Assertion authorization grants may be used with or without client authentication or identification. Whether or not client authentication is needed in conjunction with an assertion authorization grant, as well as the supported types of client

authentication, are policy decisions at the discretion of the authorization server. However, if client credentials are present in the request, the authorization server MUST validate them.

If the Assertion is not valid, or its subject confirmation requirements cannot be met, the authorization server MUST construct an error response as defined in OAuth 2.0 [RFC6749]. The value of the "error" parameter MUST be the "invalid_grant" error code. The authorization server MAY include additional information regarding the reasons the Assertion was considered invalid using the "error_description" or "error_uri" parameters.

For example:

```
HTTP/1.1 400 Bad Request
Content-Type: application/json
Cache-Control: no-store

{
  "error": "invalid_grant",
  "error_description": "Audience validation failed"
}
```

3.2. Client Authentication Processing

If the client Assertion is not valid, or its subject confirmation requirements cannot be met, the authorization server MUST construct an error response as defined in OAuth 2.0 [RFC6749]. The value of the "error" parameter MUST be the "invalid_client" error code. The authorization server MAY include additional information regarding the reasons the Assertion was considered invalid using the "error_description" or "error_uri" parameters.

4. Authorization Grant Example

Though non-normative, the following examples illustrate what a conforming Assertion and access token request would look like.

The example shows an assertion issued and signed by the SAML Identity Provider identified as "https://saml-idp.example.com". The subject of the assertion is identified by email address as "brian@example.com", who authenticated to the Identity Provider by means of a digital signature where the key was validated as part of an X.509 Public Key Infrastructure. The intended audience of the assertion is "https://saml-sp.example.net", which is an identifier for a SAML Service Provider with which the authorization server identifies itself. The assertion is sent as part of an access token

request to the authorization server's token endpoint at "https://authz.example.net/token.oauth2".

Below is an example SAML 2.0 Assertion (whitespace formatting is for display purposes only):

```
<Assertion IssueInstant="2010-10-01T20:07:34.619Z"
  ID="ef1xsbZxPV2oqjd7HTLRLIBlBb7"
  Version="2.0"
  xmlns="urn:oasis:names:tc:SAML:2.0:assertion">
  <Issuer>https://saml-idp.example.com</Issuer>
  <ds:Signature xmlns:ds="http://www.w3.org/2000/09/xmldsig#">
    [...omitted for brevity...]
  </ds:Signature>
  <Subject>
    <NameID
      Format="urn:oasis:names:tc:SAML:1.1:nameid-format:emailAddress">
      brian@example.com
    </NameID>
    <SubjectConfirmation
      Method="urn:oasis:names:tc:SAML:2.0:cm:bearer">
      <SubjectConfirmationData
        NotOnOrAfter="2010-10-01T20:12:34.619Z"
        Recipient="https://authz.example.net/token.oauth2"/>
      </SubjectConfirmation>
    </Subject>
    <Conditions>
      <AudienceRestriction>
        <Audience>https://saml-sp.example.net</Audience>
      </AudienceRestriction>
    </Conditions>
    <AuthnStatement AuthnInstant="2010-10-01T20:07:34.371Z">
      <AuthnContext>
        <AuthnContextClassRef>
          urn:oasis:names:tc:SAML:2.0:ac:classes:X509
        </AuthnContextClassRef>
      </AuthnContext>
    </AuthnStatement>
  </Assertion>
```

Figure 1: Example SAML 2.0 Assertion

To present the Assertion shown in the previous example as part of an access token request, for example, the client might make the following HTTPS request (with extra line breaks for display purposes only):

```
POST /token.oauth2 HTTP/1.1
Host: authz.example.net
Content-Type: application/x-www-form-urlencoded

grant_type=urn%3Aietf%3Aparams%3Aoauth%3Agrant-type%3Asaml2-
bearer&assertion=PEFzc2VydGlvbiBJc3N1ZUluc3RhbnQ9IjIwMTEtMDU
[...omitted for brevity...]aG5TdGF0ZW1lbnQ-PC9Bc3NlcnRpb24-
```

Figure 2: Example Request

5. Interoperability Considerations

Agreement between system entities regarding identifiers, keys, and endpoints is required in order to achieve interoperable deployments of this profile. Specific items that require agreement are as follows: values for the issuer and audience identifiers, the location of the token endpoint, and the key used to apply and verify the digital signature over the assertion. The exchange of such information is explicitly out of scope for this specification and typical deployment of it will be done alongside existing SAML Web SSO deployments that have already established a means of exchanging such information. Metadata for the OASIS Security Assertion Markup Language (SAML) V2.0 [[OASIS.saml-metadata-2.0-os](#)] is one common method of exchanging SAML related information about system entities.

6. Security Considerations

No additional security considerations apply beyond those described within The OAuth 2.0 Authorization Framework [[RFC6749](#)], the Assertion Framework for OAuth 2.0 Client Authentication and Authorization Grants [[I-D.ietf-oauth-assertions](#)], and the Security and Privacy Considerations for the OASIS Security Assertion Markup Language (SAML) V2.0 [[OASIS.saml-sec-consider-2.0-os](#)] specifications.

7. IANA Considerations

7.1. Sub-Namespace Registration of urn:ietf:params:oauth:grant-type:saml2-bearer

This is a request to IANA to please register the value

"grant-type:saml2-bearer" in the registry urn:ietf:params:oauth established in An IETF URN Sub-Namespace for OAuth [[RFC6755](#)].

- o URN: urn:ietf:params:oauth:grant-type:saml2-bearer
- o Common Name: SAML 2.0 Bearer Assertion Grant Type Profile for OAuth 2.0
- o Change controller: IETF
- o Specification Document: [[this document]]

[7.2.](#) Sub-Namespace Registration of urn:ietf:params:oauth:client-assertion-type:saml2-bearer

This is a request to IANA to please register the value "client-assertion-type:saml2-bearer" in the registry urn:ietf:params:oauth established in An IETF URN Sub-Namespace for OAuth [[RFC6755](#)].

- o URN: urn:ietf:params:oauth:client-assertion-type:saml2-bearer
- o Common Name: SAML 2.0 Bearer Assertion Profile for OAuth 2.0 Client Authentication
- o Change controller: IETF
- o Specification Document: [[this document]]

[8.](#) References

[8.1.](#) Normative References

- [I-D.ietf-oauth-assertions]
Campbell, B., Mortimore, C., Jones, M., and Y. Golang,
"Assertion Framework for OAuth 2.0 Client Authentication
and Authorization Grants", [draft-ietf-oauth-assertions](#)
(work in progress), July 2013.
- [OASIS.saml-core-2.0-os]
Cantor, S., Kemp, J., Philpott, R., and E. Maler,
"Assertions and Protocol for the OASIS Security Assertion
Markup Language (SAML) V2.0", OASIS Standard saml-core-
2.0-os, March 2005.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate
Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.

- [RFC3986] Berners-Lee, T., Fielding, R., and L. Masinter, "Uniform Resource Identifier (URI): Generic Syntax", STD 66, [RFC 3986](#), January 2005.
- [RFC4648] Josefsson, S., "The Base16, Base32, and Base64 Data Encodings", [RFC 4648](#), October 2006.
- [RFC6749] Hardt, D., "The OAuth 2.0 Authorization Framework", [RFC 6749](#), October 2012.
- [RFC6755] Campbell, B. and H. Tschofenig, "An IETF URN Sub-Namespace for OAuth", [RFC 6755](#), October 2012.

8.2. Informative References

- [OASIS.saml-deleg-cs]
Cantor, S., Ed., "SAML V2.0 Condition for Delegation Restriction", Nov 2009.
- [OASIS.saml-metadata-2.0-os]
Cantor, S., Moreh, J., Philpott, R., and E. Maler, "Metadata for the Security Assertion Markup Language (SAML) V2.0", OASIS Standard `saml-metadata-2.0-os`, March 2005.
- [OASIS.saml-profiles-2.0-os]
Hughes, J., Cantor, S., Hodges, J., Hirsch, F., Mishra, P., Philpott, R., and E. Maler, "Profiles for the OASIS Security Assertion Markup Language (SAML) V2.0", OASIS Standard `OASIS.saml-profiles-2.0-os`, March 2005.
- [OASIS.saml-sec-consider-2.0-os]
Hirsch, F., Philpott, R., and E. Maler, "Security and Privacy Considerations for the OASIS Security Markup Language (SAML) V2.0", OASIS Standard `saml-sec-consider-2.0-os`, March 2005.
- [W3C.REC-html401-19991224]
Hors, A., Raggett, D., and I. Jacobs, "HTML 4.01 Specification", World Wide Web Consortium Recommendation REC-html401-19991224, December 1999, <<http://www.w3.org/TR/1999/REC-html401-19991224>>.

Appendix A. Acknowledgements

The following people contributed wording and concepts to this document: Paul Madsen, Patrick Harding, Peter Motykowski, Eran

Hammer, Peter Saint-Andre, Ian Barnett, Eric Fazendin, Torsten Lodderstedt, Susan Harper, Scott Tomilson, Scott Cantor, Hannes Tschofenig, David Waite, Phil Hunt, and Mukesh Bhatnagar.

Appendix B. Document History

[[to be removed by RFC editor before publication as an RFC]]

[draft-ietf-oauth-saml2-bearer-17](#)

- o Stated that issuer and audience values SHOULD be compared using the Simple String Comparison method defined in [Section 6.2.1 of RFC 3986](#) unless otherwise specified by the application.

[draft-ietf-oauth-saml2-bearer-16](#)

- o Changed title from "SAML 2.0 Bearer Assertion Profiles for OAuth 2.0" to "SAML 2.0 Profile for OAuth 2.0 Client Authentication and Authorization Grants" to be more explicit about the scope of the document per <http://www.ietf.org/mail-archive/web/oauth/current/msg11063.html>.
- o Fixed typo in text identifying the presenter from "or similar element, the" to "or similar element in the".
- o Numbered the list of processing rules.
- o Smallish editorial cleanups to try and improve readability and comprehensibility.
- o Cleaner split out of the processing rules in cases where they differ for client authentication and authorization grants.
- o Clarified the parameters that are used/available for authorization grants.
- o Added Interoperability Considerations section and info reference to SAML Metadata.
- o Added more explanatory context to the example in [Section 4](#).

[draft-ietf-oauth-saml2-bearer-15](#)

- o Reference [RFC 6749](#) and [RFC 6755](#).
- o Update [draft-ietf-oauth-assertions](#) reference to -06.

- o Remove extraneous word per <http://www.ietf.org/mail-archive/web/oauth/current/msg10055.html>
- [draft-ietf-oauth-saml2-bearer-14](#)
- o Add more text to intro explaining that an assertion grant type can be used with or without client authentication/identification and that client assertion authentication is nothing more than an alternative way for a client to authenticate to the token endpoint
- o Add examples to Sections [2.1](#) and [2.2](#)
- o Update references

[draft-ietf-oauth-saml2-bearer-13](#)

- o Update references: oauth-assertions-04, oauth-urn-sub-ns-05, oauth-28
- o Changed "Description" to "Specification Document" in both registration requests in IANA Considerations per changes to the template in ietf-oauth-urn-sub-ns(-03)
- o Added "(or an acceptable alias)" so that it's in both sentences about Recipient and the token endpoint URL so there's no ambiguity
- o Update area and workgroup (now Security and OAuth was Internet and nothing)

[draft-ietf-oauth-saml2-bearer-12](#)

- o updated reference to [draft-ietf-oauth-v2](#) from -25 to -26 and [draft-ietf-oauth-assertions](#) from -02 to -03

[draft-ietf-oauth-saml2-bearer-11](#)

- o Removed text about limited lifetime access tokens and the SHOULD NOT on issuing refresh tokens. The text was moved to [draft-ietf-oauth-assertions-02](#) and somewhat modified per <http://www.ietf.org/mail-archive/web/oauth/current/msg08298.html>.
- o Fixed typo/missing word per <http://www.ietf.org/mail-archive/web/oauth/current/msg08733.html>.
- o Added Terminology section.

[draft-ietf-oauth-saml2-bearer-10](#)

- o fix a spelling mistake

[draft-ietf-oauth-saml2-bearer-09](#)

- o Attempt to address an ambiguity around validation requirements when the Conditions element contain a NotOnOrAfter and SubjectConfirmation/SubjectConfirmationData does too. Basically it needs to have at least one bearer SubjectConfirmation element but that element can omit SubjectConfirmationData, if Conditions has an expiry on it. Otherwise, a valid SubjectConfirmation must have a SubjectConfirmationData with Recipient and NotOnOrAfter. And any SubjectConfirmationData that has those elements needs to have them checked.
- o clarified that AudienceRestriction is under Conditions (even though it's implied by schema)
- o fix a typo

[draft-ietf-oauth-saml2-bearer-08](#)

- o fix some typos

[draft-ietf-oauth-saml2-bearer-07](#)

- o update reference from [draft-campbell-oauth-urn-sub-ns](#) to [draft-ietf-oauth-urn-sub-ns](#)
- o Updated to reference [draft-ietf-oauth-v2-20](#)

[draft-ietf-oauth-saml2-bearer-06](#)

- o Fix three typos NamseID->NameID and (2x) Namespace->Namespace

[draft-ietf-oauth-saml2-bearer-05](#)

- o Allow for subject confirmation data to be optional when Conditions contain audience and NotOnOrAfter
- o Rework most of the spec to profile [draft-ietf-oauth-assertions](#) for both authn and authz including (but not limited to):
 - * remove requirement for issuer to be urn:oasis:names:tc:SAML:2.0:nameid-format:entity
 - * change wording on Subject requirements

- o using a MAY, explicitly say that the Audience can be token endpoint URL of the authorization server
- o Change title to be more generic (allowing for client authn too)
- o added client authentication to the abstract
- o register and use urn:ietf:params:oauth:grant-type:saml2-bearer for grant type rather than http://oauth.net/grant_type/saml/2.0/bearer
- o register urn:ietf:params:oauth:client-assertion-type:saml2-bearer
- o remove scope parameter as it is defined in <http://tools.ietf.org/html/draft-ietf-oauth-assertions>
- o remove assertion param registration because it [should] be in <http://tools.ietf.org/html/draft-ietf-oauth-assertions>
- o fix typo(s) and update/add references

[draft-ietf-oauth-saml2-bearer-04](#)

- o Changed the grant_type URI from "http://oauth.net/grant_type/assertion/saml/2.0/bearer" to "http://oauth.net/grant_type/saml/2.0/bearer" - dropping the word assertion from the path. Recent versions of [draft-ietf-oauth-v2](#) no longer refer to extension grants using the word assertion so this URI is more reflective of that. It also more closely aligns with the grant type URI in [draft-jones-oauth-jwt-bearer-00](#) which is "http://oauth.net/grant_type/jwt/1.0/bearer".
- o Added "case sensitive" to scope definition to align with [draft-ietf-oauth-v2-15](#)/16.
- o Updated to reference [draft-ietf-oauth-v2-16](#)

[draft-ietf-oauth-saml2-bearer-03](#)

- o Cleanup of some editorial issues.

[draft-ietf-oauth-saml2-bearer-02](#)

- o Added scope parameter with text copied from [draft-ietf-oauth-v2-12](#) (the reorg of [draft-ietf-oauth-v2-12](#) made it so scope wasn't really inherited by this spec anymore)
- o Change definition of the assertion parameter to be more generally applicable per the suggestion near the end of

<http://www.ietf.org/mail-archive/web/oauth/current/msg05253.html>

- o Editorial changes based on feedback

[draft-ietf-oauth-saml2-bearer-01](#)

- o Update spec name when referencing [draft-ietf-oauth-v2](#) (The OAuth 2.0 Protocol Framework -> The OAuth 2.0 Authorization Protocol)
- o Update wording in Introduction to talk about extension grant types rather than the assertion grant type which is a term no longer used in OAuth 2.0
- o Updated to reference [draft-ietf-oauth-v2-12](#) and denote as work in progress
- o Update Parameter Registration Request to use similar terms as [draft-ietf-oauth-v2-12](#) and remove Related information part
- o Add some text giving discretion to AS on rejecting assertions with unreasonably long validity window.

[draft-ietf-oauth-saml2-bearer-00](#)

- o Added Parameter Registration Request for "assertion" to IANA Considerations.
- o Changed document name to [draft-ietf-oauth-saml2-bearer](#) in anticipation of becoming an OAUTH WG item.
- o Attempt to move the entire definition of the 'assertion' parameter into this draft (it will no longer be defined in OAuth 2 Protocol Framework).

[draft-campbell-oauth-saml-01](#)

- o Updated to reference [draft-ietf-oauth-v2-11](#) and reflect changes from -10 to -11.
- o Updated examples.
- o Relaxed processing rules to allow for more than one SubjectConfirmation element.
- o Removed the 'MUST NOT contain a NotBefore attribute' on SubjectConfirmationData.

- o Relaxed wording that ties the subject of the Assertion to the resource owner.
- o Added some wording about identifying the client when the subject hasn't directly authenticated including an informative reference to SAML V2.0 Condition for Delegation Restriction.
- o Added a few examples to the language about verifying that the Assertion is valid in all other respects.
- o Added some wording to the introduction about the similarities to Web SSO in the format and processing rules
- o Changed the grant_type (was assertion_type) URI from http://oauth.net/assertion_type/saml/2.0/bearer to http://oauth.net/grant_type/assertion/saml/2.0/bearer
- o Changed title to include "Grant Type" in it.
- o Editorial updates based on feedback from the WG and others (including capitalization of Assertion when referring to SAML).

[draft-campbell-oauth-saml-00](#)

- o Initial I-D

Authors' Addresses

Brian Campbell
Ping Identity

Email: brian.d.campbell@gmail.com

Chuck Mortimore
Salesforce.com

Email: cmortimore@salesforce.com

Michael B. Jones
Microsoft

Email: mbj@microsoft.com

URI: <http://self-issued.info/>

